



Using HTTP Methods for RESTful Services

[Quick-Tips](#)
[Resource Naming](#)

The HTTP verbs comprise a major portion of our “uniform interface” constraint and provide us the action counterpart to the noun-based resource. The primary or most-commonly-used HTTP verbs (or methods, as they are properly called) are POST, GET, PUT, PATCH, and DELETE. These correspond to create, read, update, and delete (or CRUD) operations, respectively. There are a number of other verbs, too, but are utilized less frequently. Of those less-frequent methods, OPTIONS and HEAD are used more often than others.

Below is a table summarizing recommended return values of the primary HTTP methods in combination with the resource URIs:

HTTP Verb	CRUD	Entire Collection (e.g. /customers)	Specific Item (e.g. /customers/{id})
POST	Create	201 (Created), 'Location' header with link to /customers/{id} containing new ID.	404 (Not Found), 409 (Conflict) if resource already exists..
GET	Read	200 (OK), list of customers. Use pagination, sorting and filtering to navigate big lists.	200 (OK), single customer. 404 (Not Found), if ID not found or invalid.
PUT	Update/Replace	405 (Method Not Allowed), unless you want to update/replace every resource in the entire collection.	200 (OK) or 204 (No Content). 404 (Not Found), if ID not found or invalid.
PATCH	Update/Modify	405 (Method Not Allowed), unless you want to modify the collection itself.	200 (OK) or 204 (No Content). 404 (Not Found), if ID not found or invalid.
DELETE	Delete	405 (Method Not Allowed), unless you want to delete the whole collection—not often desirable.	200 (OK). 404 (Not Found), if ID not found or invalid.

Below is a more-detailed discussion of the main HTTP methods. Click on a tab for more information about the desired HTTP method.

[POST](#)
[GET](#)
[PUT](#)
[PATCH](#)
[DELETE](#)

DELETE is pretty easy to understand. It is used to **delete** a resource identified by a URI.

On successful deletion, return HTTP status 200 (OK) along with a response body, perhaps the representation of the deleted item (often demands too much bandwidth), or a wrapped response (see Return Values below). Either that or return HTTP status 204 (NO CONTENT) with no response body. In other words, a 204 status with no body, or the JSEND-style response and HTTP status 200 are the recommended responses.

HTTP-spec-wise, DELETE operations are idempotent. If you DELETE a resource, it's removed. Repeatedly calling DELETE on that resource ends up the same: the resource is gone. If calling DELETE say, decrements a counter (within the resource), the DELETE call is no longer idempotent. As mentioned previously, usage statistics and measurements may be updated while still considering the service idempotent as long as no resource data is changed. Using POST for non-idempotent resource requests is recommended.

There is a caveat about DELETE idempotence, however. Calling DELETE on a resource a second time will often return a 404 (NOT FOUND) since it was already removed and therefore is no longer findable. This, by some opinions, makes

DELETE operations no longer idempotent, however, the end-state of the resource is the same. Returning a 404 is acceptable and communicates accurately the status of the call.

Examples:

- *DELETE* <http://www.example.com/customers/12345>
- *DELETE* <http://www.example.com/customers/12345/orders>
- *DELETE* <http://www.example.com/bucket/sample>



This work by RestApiTutorial.com is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).