SIMATS ENGINEERING
ASSESSMENT TOOL 2

COURSE CODE: ITA 06 **COURSE NAME: MACHINE LEARNING**


COURSE OUTCOME COVERED
CO3: Bayes Theorem – Concept Learning – Maximum Likelihood – Minimum Description Length Principle – Bayes Optimal Classifier – Gibbs Algorithm – Naïve Bayes Classifier – Bayesian Belief Network – EM Algorithm – Probability Learning – Sample Complexity – Finite and Infinite Hypothesis Spaces – Mistake Bound Model, (BL 6) *Assessment Tool Weightage: 20%*

QUESTIONS: 15 **Total Marks:25**

Annexure A

Case Study

Code of Conduct:
I T . KODANDA RAM (192524162) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.
I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student: 

Annexure A

Short Answer Test

1, A hospital aims to develop an intelligent system to diagnose diseases based on patient symptoms and medical history. Using concepts such as Bayes' Theorem, Naïve Bayes classifiers, and Bayesian Belief Networks, design a probabilistic model for diagnosis. Analyze how uncertainty is handled and how conditional dependencies between symptoms influence predictions. Discuss the role of probability learning and evaluate the effectiveness of your approach with respect to real-world constraints.

2. An organization wants to build a spam detection system for emails using machine learning techniques. Using Naïve Bayes and Bayes Optimal Classifier concepts, design a classification system. Compare Maximum Likelihood estimation with Minimum Description Length (MDL) principle in feature selection. Analyze system performance, discuss trade-offs in model complexity, and evaluate how sample size and hypothesis space affect classification accuracy.

3. A retail company wants to segment its customers based on purchasing behavior, but the data contains hidden patterns and incomplete information. Apply the EM algorithm to identify clusters and estimate underlying distributions. Analyze convergence behavior, initialization challenges, and the role of probability learning. Discuss how the results can be used for targeted marketing and evaluate limitations of the approach.

4. A research team is developing a concept learning system to classify medical images into normal and abnormal categories. Using hypothesis space search and the Candidate Elimination approach, design a model that learns from labeled examples. Analyze the impact of finite vs infinite hypothesis spaces, sample complexity, and mistake bound model on learning performance. Evaluate how well the system generalizes to unseen data.

5. A financial institution needs to make investment decisions under uncertain market conditions. Using Bayesian inference, Gibbs algorithm, and probability learning, design a system to predict outcomes and update beliefs dynamically. Analyze how prior knowledge influences predictions, evaluate risk using posterior probabilities, and discuss how the model adapts as new data becomes available. Consider computational challenges and optimization strategies.

6. An autonomous vehicle system must make real-time driving decisions under uncertain environmental conditions such as weather, traffic, and pedestrian movement. Using Bayesian inference, Naïve Bayes classifiers, and probabilistic reasoning, design a model to predict safe driving actions. Analyze how uncertainty and sensor noise are handled, and evaluate system reliability under dynamic conditions.

7. A healthcare organization aims to predict patient risk levels for chronic diseases using historical and lifestyle data. Apply probability learning, Bayes' Theorem, and hypothesis space search to design the model. Analyze the impact of prior probabilities, feature dependencies, and sample size. Evaluate the model's interpretability and its usefulness in preventive healthcare strategies.

8. A bank wants to detect fraudulent transactions using machine learning under uncertain and evolving patterns. Using Bayesian Belief Networks and EM algorithm concepts, design a detection system. Analyze hidden variables, incomplete data handling, and convergence issues. Evaluate how probability-based reasoning improves detection accuracy and reduces false positives in real-world scenarios.

9. An e-commerce platform aims to recommend products to users based on browsing and purchase history. Using Naïve Bayes and Bayesian learning concepts, design a influence recommendation model. Analyze how conditional probabilities recommendations and how uncertainty in user preferences is managed. Evaluate scalability and performance in handling large, dynamic datasets.

10. A research institute is building a system to predict climate changes using historical environmental data. Apply probabilistic models such as Bayesian inference and EM algorithm to handle incomplete and noisy datasets. Analyze convergence behavior, uncertainty modeling, and the influence of prior knowledge. Evaluate the system's effectiveness in long-term environmental forecasting.

11. A telecommunications company aims to predict customer churn using historical usage data and service feedback. Using probabilistic models such as **Naïve Bayes**, **Bayesian inference**, and hypothesis space search, design a predictive system. Analyze how prior probabilities and feature dependencies influence churn prediction. Evaluate how uncertainty in customer behavior is handled and discuss the effectiveness of the model in improving customer retention strategies.

12. A smart healthcare system is designed to monitor patients in real-time using wearable sensors. Using **Bayesian Belief Networks** and probability learning, develop a model to detect anomalies in vital signs. Analyze how conditional dependencies between physiological parameters are modeled and how uncertainty due to sensor noise is handled. Evaluate system performance and discuss challenges in real-time deployment.

13. A logistics company wants to optimize delivery routes under uncertain traffic and weather conditions. Using **Bayesian inference** and probabilistic reasoning, design a system that predicts optimal routes dynamically. Analyze how prior knowledge and

real-time data updates influence decision-making. Evaluate computational complexity and discuss how uncertainty impacts route optimization efficiency.

14. A cybersecurity system is developed to detect network intrusions using probabilistic learning methods. Apply **Naïve Bayes classifiers**, **EM algorithm**, and Bayesian learning to model normal and abnormal network behavior. Analyze how hidden patterns and incomplete data are handled. Evaluate the system's effectiveness in reducing false alarms and improving detection accuracy in dynamic environments.

15. An agriculture-based system aims to predict crop yield under uncertain environmental conditions such as rainfall, soil quality, and temperature. Using **Bayesian inference** and probability learning, design a predictive model. Analyze how prior agricultural knowledge and seasonal variations influence predictions. Evaluate the model's reliability and discuss its impact on decision-making for farmers and policy planning.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary (5 Marks)	Level 3 – Proficient (4 Marks)	Level 2 – Developing (2–3 Marks)	Level 1 – Beginning (0–1 Mark)
Conceptual Understanding	**30**	Demonstrates clear and complete understanding of the concept	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor or incorrect understanding
Accuracy of Answer	**20**	Completely correct answer with no errors	Mostly correct with minor errors	Partially correct with noticeable errors	Incorrect or irrelevant answer
Application of Knowledge	**20**	Correctly applies concepts to solve the question/problem	Applies concepts with minor mistakes	Limited or partially correct application	No or incorrect application
Completeness of Response	**15**	Covers all required parts of the question	Covers most parts with minor omissions	Covers only some parts	Incomplete or missing response
Clarity & Presentation	**15**	Clear, concise, and well-organized answer	Understandable with minor issues	Somewhat unclear or poorly structured	Difficult to understand

1. Probabilistic Hospital Diagnosis Using Bayes' Theorem, Naïve Bayes and Bayesian Belief Networks

Case-study solution and model design

Design. Define the target variable D as a disease and evidence variables as symptoms, medical history, age and test results. First estimate prior disease probabilities P(D) from representative clinical data. For observed evidence E, apply Bayes' theorem: P(D|E)=P(E|D)P(D)/P(E). A Naïve Bayes model approximates P(E|D) as the product of feature likelihoods P(Ei|D). A Bayesian Belief Network (BBN) can represent clinically meaningful dependencies, for example Disease → Fever, Disease → Cough, and Smoking → LungDisease → Cough. The BBN factorizes the joint distribution according to its directed acyclic graph and supports inference when some evidence is missing.

Analysis of uncertainty and core concepts

Uncertainty and dependencies. The output should be posterior probabilities for candidate diseases, not an unsupported certain diagnosis. Missing symptoms can be marginalized over; uncertain or noisy test results should use sensitivity/specificity likelihoods. Naïve Bayes is simple and fast, but correlated symptoms can be double-counted because conditional independence is assumed. A BBN represents selected dependencies explicitly, improving realism when its structure and conditional probability tables are valid. Probability learning estimates priors and conditional probabilities from labelled records, using smoothing or Bayesian priors when counts are sparse.

Evaluation, practical constraints and application

Evaluation and real-world constraints. Split patient records by patient, not by visit, into training/validation/test sets to avoid leakage. Evaluate sensitivity/recall for dangerous missed cases, specificity, precision, calibration (e.g., Brier score), confusion matrix and subgroup performance. Validate externally across hospitals and time periods. Constraints include missing records, class imbalance, changing disease prevalence, privacy, bias, interpretability and the need for clinician oversight. A probability score supports triage but must not replace medical judgement.

Illustrative implementation / workflow

import pandas as pd from sklearn.model_selection import train_test_split from sklearn.naive_bayes import GaussianNB from sklearn.metrics import classification_report, confusion_matrix, brier_score_loss from sklearn.calibration import CalibratedClassifierCV # CSV must contain numeric symptom/history columns and a binary target 'disease' df = pd.read_csv("patient_data.csv") X = df.drop(columns="disease") y = df["disease"] Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.2, stratify=y, random_state=42) model = GaussianNB().fit(Xtr, ytr) pred = model.predict(Xte) prob = model.predict_proba(Xte)[:, 1] print(classification_report(yte, pred)) print("Confusion matrix:\n", confusion_matrix(yte, pred)) print("Brier score:", brier_score_loss(yte, prob))

Implementation steps: (1) Validate units, ranges and missingness in the clinical table. (2) Separate predictors from the disease label and split records by patient. (3) Fit the baseline classifier on training data only. (4) Calibrate posterior probabilities using a validation set. (5) Compare sensitivity, specificity, precision, Brier score and subgroup performance on held-out patients. (6) Document the threshold that triggers referral and retain clinician oversight. The example code assumes a binary target and numeric features; categorical variables need encoding and any imputation must be fitted on training data only.

Conclusion

Conclusion. A hybrid approach is practical: use Naïve Bayes as a fast baseline and a BBN when known dependencies matter. Calibrated posterior probabilities, rigorous validation and human review are essential before clinical deployment.

2. Spam Detection Using Naïve Bayes, Bayes Optimal Classification, MLE and MDL

Case-study solution and model design

System design. Label email messages as spam or legitimate. Convert text into token counts or TF-IDF features and train a Multinomial Naïve Bayes classifier. For a message x, estimate P(spam|x) and P(ham|x); classify as spam when the spam posterior exceeds a threshold selected for the cost of false positives and false negatives. Use additive smoothing so words unseen in training do not produce zero likelihood.

Analysis of uncertainty and core concepts

Naïve Bayes versus Bayes Optimal Classifier. Naïve Bayes uses one simplifying model and conditional-independence assumptions. The Bayes Optimal Classifier predicts by averaging predictions over all hypotheses weighted by their posterior probabilities: choose the class with greatest posterior-weighted vote. It can achieve minimum expected classification error under the assumed hypothesis/prior distribution, but exact averaging is often computationally infeasible. Naïve Bayes is a practical approximation.

Evaluation, practical constraints and application

MLE versus MDL for feature selection. Maximum Likelihood Estimation chooses parameters that maximize P(data|parameters); in a text model this estimates class and word probabilities from observed counts. MLE alone may favour overly complex models that fit training data. Minimum Description Length chooses the model that minimizes total encoding length, L(model)+L(data|model). MDL therefore balances model complexity against unexplained data and can prefer a smaller, more general feature set. MLE estimates parameters; MDL is a model/feature selection principle, so they are related but not identical alternatives.

Illustrative implementation / workflow

Conclusion. Use Naïve Bayes as a fast baseline, tune the decision threshold to business costs, and use MDL-style complexity control to avoid an unnecessarily large feature representation.

Implementation steps: (1) Normalize email text consistently and preserve a time-based test set. (2) Convert training messages to a sparse word-count matrix. (3) Fit Multinomial Naïve Bayes with smoothing. (4) Compare feature vocabularies by varying minimum document frequency or using validation-based feature selection. (5) Report precision, recall, F1, false-positive rate and PR-AUC. (6) Tune the spam threshold to the cost of incorrectly blocking legitimate mail. For a formal MDL comparison, calculate or approximate model-description length plus residual-data encoding length for each candidate feature set; do not treat MLE and MDL as identical algorithms.

Conclusion

Performance, sample size and hypothesis space. Measure precision, recall, F1, confusion matrix, false-positive rate and PR-AUC, especially because spam prevalence may be low. More labelled emails generally improve estimates and expose more vocabulary, but mislabeled or outdated examples can harm performance. A small hypothesis space is easier to estimate and less prone to overfitting but may miss new spam patterns; a very large space needs more data and regularization. Retrain or update cautiously as spam tactics change.

3. Retail Customer Segmentation Using the Expectation-Maximization (EM) Algorithm

Case-study solution and model design

Model. Represent each customer by purchase frequency, average basket value, category proportions, recency and discount use. Standardize numeric features and handle missing values explicitly, for example by imputation plus missingness indicators. Fit a Gaussian Mixture Model (GMM), which assumes data are generated from a mixture of K distributions. Each customer has a probability of belonging to each segment rather than only a hard assignment.

Analysis of uncertainty and core concepts

EM and probability learning. In the E-step, calculate each customer's responsibility for every mixture component using current weights, means and covariances. In the M-step, update those parameters using the responsibilities as weights. Repeat until the log-likelihood improvement is below a tolerance or the iteration limit is reached. The learned mixture weights estimate segment prevalence; component parameters estimate the distributions of purchasing behaviour.

Evaluation, practical constraints and application

Convergence and initialization. EM usually increases or maintains likelihood each iteration under standard conditions, but it can converge to a local optimum. Random starting centres, poor scaling, overlapping clusters and excessive K can lead to unstable segments or singular covariance estimates. Use multiple restarts, covariance regularization, sensible scaling and compare K with BIC/AIC plus business interpretability. Do not choose K using likelihood alone, since likelihood often rises with more components.

Illustrative implementation / workflow

Conclusion. EM provides soft membership and interpretable segment distributions, but the clusters must be stable, useful and validated against business outcomes.

Implementation steps: (1) Select behaviour variables available at the same customer snapshot date. (2) Impute missing numeric values and standardize using training data statistics. (3) Fit GMMs for a range of K values and repeat each fit with several initializations. (4) Record convergence, log-likelihood, AIC and BIC. (5) Inspect the posterior membership probabilities and profile each segment using original-scale averages. (6) Check segment stability across time and use controlled marketing tests to measure business value. The code prints diagnostics but does not claim that a particular K is best before the data are examined.

Conclusion

Marketing use and limitations. Segments can support personalized offers, loyalty campaigns, replenishment reminders and cross-selling. For example, a high-frequency, low-basket segment may respond to bundles, while high-value customers may benefit from loyalty rewards. Validate segments over time and test campaigns experimentally. Limitations include sensitivity to outliers and feature choice, non-Gaussian customer groups, changing behaviour, privacy concerns and the risk of treating probabilistic segments as fixed identities.

4. Medical Image Concept Learning with Candidate Elimination

Case-study solution and model design

Representation and design. Candidate Elimination is a concept-learning method that maintains the version space: all hypotheses consistent with labelled examples. For an introductory symbolic image classifier, convert images into interpretable features such as lesion shape, border regularity, colour variation or texture categories, then label each example normal/abnormal. The most-specific boundary S and most-general boundary G describe the remaining consistent hypotheses. Positive examples generalize S; negative examples specialize G.

Analysis of uncertainty and core concepts

Finite and infinite hypothesis spaces. If each feature has a finite set of values and the hypothesis language is restricted, the hypothesis space can be finite and explicitly searched. A rich space of continuous image features or arbitrary decision functions may be effectively infinite; it cannot be exhaustively enumerated, so a restricted representation or parametric learner is needed. Candidate Elimination is most appropriate when examples are noise-free and the target concept is represented in the hypothesis space. Real medical labels and images violate these assumptions frequently.

Evaluation, practical constraints and application

Sample complexity and mistake bound. Sample complexity is the number of labelled examples needed to learn a concept to a target accuracy/confidence. More attributes and a larger hypothesis space generally require more evidence. Under a finite, realizable hypothesis space, classic PAC-style bounds scale with log of the number of hypotheses and inversely with desired error/confidence terms. The mistake-bound model instead asks how many prediction errors a learner can make before convergence under stated assumptions. These are theoretical guarantees, not promises for noisy medical images.

Illustrative implementation / workflow

Conclusion. Candidate Elimination illustrates hypothesis-space narrowing, but medical-image classification usually requires richer feature learning and careful evaluation for noise, bias and external generalization.

Implementation steps: (1) Define a finite feature vocabulary and allowed values before learning. (2) Initialize S to the most-specific hypothesis and G to the most-general hypothesis. (3) For each labelled example, update the boundaries according to whether it is positive or negative. (4) Remove boundary members inconsistent with prior examples and check whether the version space becomes empty. (5) Test the learned rule on patient-separated examples. (6) Report sensitivity and specificity and compare against a stronger image model. Candidate Elimination requires carefully implemented minimal generalization/specialization; the pseudocode is a design outline and is not a medical-image classifier ready for deployment.

Conclusion

Generalization and evaluation. Split by patient and, where possible, by institution; avoid images from the same patient appearing in both training and test sets. Evaluate sensitivity, specificity, precision, recall, ROC/PR-AUC and calibration. Test on external hospitals and different scanners. Candidate Elimination's symbolic features may be interpretable but can discard subtle pixel-level patterns. For real deployment, compare with validated image models and require clinician review; do not use the toy algorithm as a clinical diagnostic tool.

5. Investment Prediction with Bayesian Inference, Gibbs Sampling and Probability Learning

Case-study solution and model design

System design. Define outcomes such as next-period return category (negative, neutral, positive) or probability of exceeding a loss threshold. Inputs may include historical returns, volatility, interest rates and market indicators. Specify a probabilistic model with prior distributions for unknown parameters and likelihood based on observed market data. Bayes' rule gives posterior parameters $P(\theta|D) \propto P(D|\theta)P(\theta)$, allowing uncertainty to be represented rather than issuing only a point forecast.

Analysis of uncertainty and core concepts

Role of prior knowledge and Gibbs algorithm. Priors can encode plausible parameter ranges or shrink extreme estimates when data are limited. They must be justified and sensitivity-tested because an unsuitable prior can bias predictions. Gibbs sampling is a Markov chain Monte Carlo method: sample each unknown parameter from its conditional posterior given current values of the other parameters and the data. After burn-in, samples approximate the joint posterior; predictions and risk measures are computed across these samples. Check trace plots, effective sample size and convergence diagnostics; samples are correlated and are not independent observations.

Evaluation, practical constraints and application

Risk and dynamic updating. Use posterior predictive distributions to estimate quantities such as P(return < –5%) or expected shortfall, not just the most likely direction. As new data arrive, update the posterior or refit the model using a rolling window/state-space model to allow changing regimes. Compare forecasts with simple baselines and evaluate calibration and risk coverage out of sample.

Illustrative implementation / workflow

Conclusion. Bayesian inference makes prior assumptions and predictive uncertainty explicit; Gibbs sampling is useful when posterior calculations are difficult analytically, provided convergence is checked and risk is evaluated out of sample.

Implementation steps: (1) Define the prediction horizon and risk metric before fitting. (2) Specify priors and a likelihood for returns or market states, documenting why the prior is reasonable. (3) Derive the full conditional posterior distributions required by Gibbs sampling. (4) Run multiple chains with different initial states and inspect trace plots, effective sample sizes and convergence diagnostics. (5) Generate posterior predictive returns and calculate downside probability and expected shortfall. (6) Back-test on later periods including transaction costs and market regimes. The conditional sampling equations depend on the selected statistical model, so the supplied pseudocode must be completed for that model rather than used as-is.

Conclusion

Computational challenges and optimization. High-dimensional posterior distributions can mix slowly, and correlated parameters may require many samples. Use a parsimonious model, sensible parameterization, multiple chains, convergence diagnostics and efficient vectorized computations. Account for transaction costs, market shocks, non-stationarity and data leakage. Predictions are uncertain and should support, not automatically determine, investment decisions.

6. Autonomous Driving Decisions Under Uncertain Conditions

Case-study solution and model design

Probabilistic model. Inputs include camera/radar/LiDAR detections, road geometry, weather, traffic density, pedestrian location and vehicle state. Define latent states such as pedestrian-intent and road-friction level, and actions such as brake, maintain speed or change lane. Bayesian inference updates P(state|sensor evidence). A Naïve Bayes classifier can provide a baseline for discrete context features, while a Bayesian network can represent dependencies among rain, road friction, braking distance and collision risk.

Analysis of uncertainty and core concepts

Sensor noise and uncertainty. Represent sensor outputs with likelihood models reflecting detection error and confidence. Fuse independent sensors only when the independence assumption is reasonable; correlated camera/radar errors should not be treated as independent evidence. Missing or conflicting readings should broaden uncertainty rather than force a confident state. Use temporal filtering and calibrated probabilities, and distinguish uncertainty due to randomness from uncertainty due to incomplete model knowledge.

Evaluation, practical constraints and application

Safe action selection and reliability. For each candidate action, estimate the posterior probability of a hazardous outcome and choose only among actions that satisfy a conservative safety constraint. A high-risk or low-confidence situation should trigger slowing, increasing distance or a minimal-risk stop. Evaluate collision/near-miss rates, false alarms, missed hazards, calibration and performance across weather, lighting, road types and vulnerable road users. Simulation and closed-course tests are required before road deployment.

Illustrative implementation / workflow

Conclusion. Probabilistic reasoning quantifies uncertainty, but reliability depends on calibrated sensor models, conservative decision thresholds and independent safety mechanisms.

Implementation steps: (1) Define sensor fields, coordinate systems and confidence scores. (2) Estimate sensor likelihoods from labelled validation data, including failure modes. (3) Specify the Bayesian network and conditional probability tables for weather, road friction, pedestrian intent and hazard state. (4) Update beliefs at each sensor cycle and estimate risk for each candidate action. (5) Apply hard safety constraints and a minimal-risk fallback when confidence is low or no action satisfies the risk limit. (6) Test in simulation and closed courses across rare weather and pedestrian scenarios before any real-world deployment.

Conclusion

Limitations. Real-time deadlines, sensor failures, rare events, distribution shift and imperfect maps make complete probabilistic modeling impossible. Bayesian predictions should be one component of a layered safety architecture with deterministic safety checks, redundancy and fallback behaviour.

7. Chronic Disease Risk Prediction Using Probability Learning and Hypothesis Search

Case-study solution and model design

Model design. Use historical and lifestyle variables such as age, family history, activity, diet, smoking, blood pressure and laboratory measurements to predict a defined outcome over a stated time horizon. Estimate prior risk P(D) from a representative cohort and calculate P(D|X) using Bayes' theorem. Naïve Bayes provides a transparent baseline; hypothesis-space search can compare candidate feature subsets or model structures using validation data. Preventive risk prediction should distinguish association from causation.

Analysis of uncertainty and core concepts

Prior probabilities, dependencies and sample size. Prior disease prevalence strongly affects posterior risk, especially when evidence is weak. A model trained on a high-risk clinic population may overpredict risk in a general population. Correlated variables (for example, body mass index and waist circumference) can violate Naïve Bayes independence and lead to overconfident posteriors. Larger representative datasets generally stabilize conditional probability estimates, while small samples need smoothing or hierarchical priors. Missingness and measurement errors must be assessed.

Evaluation, practical constraints and application

Interpretability and preventive use. Report calibrated risk categories with confidence/uncertainty, major contributing evidence and clinically meaningful thresholds. Evaluate sensitivity, specificity, precision, calibration, subgroup fairness and external validation. The model can prioritize screening, lifestyle counselling and follow-up, but clinicians should confirm risk and consider patient context. Monitor performance as prevalence, treatments and population behaviour change.

Illustrative implementation / workflow

import pandas as pd from sklearn.model_selection import train_test_split from sklearn.naive_bayes import GaussianNB from sklearn.metrics import roc_auc_score, brier_score_loss, classification_report df = pd.read_csv("chronic_risk.csv") # outcome column: disease_within_horizon X, y = df.drop(columns="disease_within_horizon"), df["disease_within_horizon"] Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.2, stratify=y, random_state=42) model = GaussianNB().fit(Xtr, ytr) pred, prob = model.predict(Xte), model.predict_proba(Xte)[:, 1] print(classification_report(yte, pred)) print("ROC-AUC:", roc_auc_score(yte, prob)) print("Brier score:", brier_score_loss(yte, prob)) # Compare performance across age/sex/region subgroups where ethically and legally appropriate.

Implementation steps: (1) Define a clinically meaningful outcome and prediction horizon. (2) Choose a representative cohort and estimate the base rate. (3) Fit a probabilistic baseline, checking missing values and correlated predictors. (4) Compare selected feature subsets using training-only feature selection and cross-validation. (5) Calibrate risk scores and assess discrimination, calibration and subgroup performance. (6) Test on a later cohort and convert risk estimates into prevention pathways with clinician review. The code expects a binary outcome and numeric features; encode categorical

variables and fit preprocessing only on training data.

Conclusion

Conclusion. A probabilistic risk model can support prevention when its base rates match the target population, dependencies are handled appropriately and its predictions are calibrated and clinically validated.

8. Fraud Detection Using Bayesian Belief Networks and EM

Case-study solution and model design

System design. Model observed transaction features such as amount, time, merchant category, location deviation, device change and transaction frequency. Include a latent variable F for fraud status and possible hidden behaviour patterns, with edges representing dependencies supported by domain knowledge. A Bayesian Belief Network calculates P(Fraud|observed transaction evidence). Use labelled historical fraud data to estimate conditional probability tables; where labels are incomplete, EM can estimate parameters involving latent variables.

Analysis of uncertainty and core concepts

Hidden variables, missing data and convergence. In the E-step, compute posterior responsibilities for latent states or missing values; in the M-step, update model parameters from expected sufficient statistics. EM can use incomplete data under a correctly specified likelihood, but it may converge to a local optimum and is sensitive to initialization. Use multiple starts, regularization, convergence monitoring and comparison of likelihoods. Missing values should not automatically be replaced with arbitrary zeros; their uncertainty should be represented or handled with principled imputation.

Evaluation, practical constraints and application

Detection accuracy and false positives. Fraud is usually rare, so accuracy alone is misleading. Measure precision, recall, PR-AUC, false-positive rate, detection delay and monetary loss prevented. Use posterior thresholds based on the cost of blocking legitimate transactions versus missing fraud. Route uncertain/high-impact cases to step-up authentication or human review. Monitor drift and retrain as fraud strategies evolve.

Illustrative implementation / workflow

Conclusion. Bayesian networks combine evidence transparently and EM can estimate models with latent or incomplete information, but operational success depends on calibrated thresholds, drift monitoring and cost-sensitive evaluation.

Implementation steps: (1) Build transaction features from historical data while avoiding future-information leakage. (2) Define labelled fraud status and any latent behaviour states. (3) Initialize BBN conditional probabilities from labelled counts with smoothing. (4) For incomplete records, use a likelihood that marginalizes missing variables where feasible. (5) Run EM with multiple initializations and track likelihood changes and convergence. (6) Set thresholds using precision-recall and the cost of false declines, then monitor drift and analyst-confirmed outcomes. Evaluate with time-based holdouts because random splits can overstate performance under evolving fraud patterns.

Conclusion

Limitations. Label delay, adversarial adaptation, privacy restrictions and extreme class imbalance complicate learning. EM cannot recover information absent from the data, and a BBN is only as reliable as its structure and probabilities. Use champion/challenger monitoring and audit subgroup impacts.

9. Product Recommendation Using Naïve Bayes and Bayesian Learning

Case-study solution and model design

Recommendation design. Represent each user by browsing events, product categories viewed, purchases, searches and contextual signals. For a candidate product p, estimate P(purchased|user evidence) or P(category|history) using a Naïve Bayes model. Bayes' theorem combines the prior popularity of a product/category with the likelihood of the observed behaviour. Rank candidates by posterior probability, optionally incorporating margin, availability and diversity constraints.

Analysis of uncertainty and core concepts

Conditional probabilities and uncertainty. Browsing a product category raises its likelihood but does not guarantee purchase. Sparse histories require smoothing so unseen interactions do not force probabilities to zero. User actions are correlated, so a naïve independence assumption may overcount repeated views or related clicks. Bayesian priors can shrink estimates for new users/products toward category-level or global rates. Display recommendations as ranked suggestions rather than certain statements about preference.

Evaluation, practical constraints and application

Scalability and dynamic data. Use sparse count matrices, incremental count updates, time decay for old events and batch/stream processing. Cache popular candidates and generate a smaller candidate set before ranking. Evaluate Precision@K, Recall@K, NDCG, coverage, diversity, latency and online conversion in A/B tests. Avoid data leakage by ensuring features precede the purchase being predicted.

Illustrative implementation / workflow

Conclusion. Bayesian recommendation provides interpretable probability-based ranking, while smoothing, time-aware updates and online evaluation help it remain useful at scale.

Implementation steps: (1) Build user-history features using only events before the recommendation time. (2) Split interactions by time so future purchases cannot leak into training. (3) Train a smoothed Naïve Bayes model for item/category outcomes. (4) Generate candidates, score them with posterior probabilities and filter unavailable or already-purchased items. (5) Measure Recall@K, Precision@K, NDCG, coverage and latency offline. (6) Run an A/B test for conversion and user satisfaction while monitoring popularity bias and privacy. The workflow is a design outline; a production recommender must define the user/item feature representation and evaluation split precisely.

Conclusion

Limitations. Cold-start users/items, popularity bias, feedback loops, privacy and rapidly changing tastes remain challenges. Naïve Bayes is efficient but may not capture sequence, collaborative effects or complex interactions; it can be combined with other recommenders.

10. Climate Forecasting with Bayesian Inference and EM

Case-study solution and model design

Model design. Combine historical temperature, rainfall, humidity, pressure and large-scale climate indicators. Use a probabilistic time-series or regression model to predict distributions for future climate variables rather than a single deterministic value. Bayesian inference represents uncertainty in parameters and forecasts; priors can encode physically plausible ranges or information from established climate studies. EM may estimate latent regimes (for example, weather states) or parameters when observations are incomplete.

Analysis of uncertainty and core concepts

Incomplete/noisy data and convergence. Record sensor quality, station changes and missingness patterns. A likelihood model can integrate over missing observations when assumptions justify it; otherwise use carefully documented imputation and sensitivity analysis. EM alternates posterior estimation of latent states with parameter updates, and can settle at local optima. Standardize/scale appropriately, use multiple starts where relevant, monitor likelihood and test whether inferred regimes are stable.

Evaluation, practical constraints and application

Uncertainty and prior influence. Separate measurement uncertainty, internal climate variability, parameter uncertainty and scenario uncertainty. Priors may stabilize estimates in data-sparse regions but should not overpower observations without justification. Report predictive intervals and calibration, not just point forecasts. Evaluate against persistence and climatology baselines using time-ordered holdouts, MAE/RMSE and interval coverage.

Illustrative implementation / workflow

Conclusion. Bayesian and EM methods can improve uncertainty handling and latent-regime estimation, but long-term climate conclusions require validated data, scenario awareness and physical context.

Implementation steps: (1) Quality-check stations, units, timestamps and sensor changes. (2) Preserve chronological ordering and reserve later years for testing. (3) Fit a Bayesian time-series/regression model with documented priors. (4) If a latent-regime or missing-data likelihood is used, initialize EM several times and compare convergence and information criteria. (5) Produce predictive intervals and compare interval coverage, MAE/RMSE and baseline forecasts. (6) Report scenario assumptions and avoid interpreting statistical extrapolation as a full physical climate projection.

Conclusion

Long-term effectiveness and limits. Long-range projections depend on emissions scenarios, physical feedbacks, non-stationarity and spatial resolution. A statistical model alone cannot replace physical climate models for policy-grade projections. Use multiple datasets, out-of-period validation and uncertainty ranges; communicate scenario assumptions clearly.

11. Customer Churn Prediction Using Naïve Bayes and Hypothesis Search

Case-study solution and model design

Model design. Define churn precisely, for example no paid activity within the next 30 or 60 days. Features may include tenure, monthly usage, dropped calls, plan type, complaints, payment issues and service feedback. Estimate P(churn) and conditional likelihoods from historical labelled records. Naïve Bayes offers a fast baseline; hypothesis-space search compares feature subsets and model structures using cross-validation rather than selecting features from the test set.

Analysis of uncertainty and core concepts

Prior probabilities and dependencies. The churn base rate affects posterior scores: if only a small proportion churn, a low posterior may still be meaningful. Usage, complaints and service quality can be correlated, violating Naïve Bayes independence and making probabilities overconfident. Use smoothing and calibrate probabilities on validation data. Compare feature subsets to determine whether redundant features help or hurt.

Evaluation, practical constraints and application

Uncertainty and retention strategy. Evaluate recall, precision, PR-AUC, calibration and lift in the highest-risk customer groups. Retention actions have costs, so rank customers by expected value of intervention rather than churn probability alone. Test offers with randomized experiments; a prediction of churn does not prove that a discount will prevent it. Monitor drift after pricing or service changes.

Illustrative implementation / workflow

import pandas as pd from sklearn.model_selection import train_test_split from sklearn.naive_bayes import GaussianNB from sklearn.metrics import classification_report, average_precision_score, brier_score_loss df = pd.read_csv("churn.csv") # numeric features and target 'churn' X, y = df.drop(columns="churn"), df["churn"] Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.2, stratify=y, random_state=42) model = GaussianNB().fit(Xtr, ytr) pred, prob = model.predict(Xte), model.predict_proba(Xte)[:, 1] print(classification_report(yte, pred)) print("PR-AUC / average precision:", average_precision_score(yte, prob)) print("Brier score:", brier_score_loss(yte, prob))

Implementation steps: (1) Define churn based on a future time window and freeze predictors at the scoring date. (2) Build a time-aware training and test split. (3) Fit Naïve Bayes and compare alternative feature subsets using cross-validation. (4) Calibrate probabilities and inspect how base-rate changes affect precision. (5) Rank customers by expected intervention value, not only churn score. (6) Randomize eligible retention offers to measure incremental retention and profit, and monitor model drift after service or pricing changes.

Conclusion

Conclusion. A probability-based churn model can focus retention resources, but success should be measured by incremental retention and profit, not classification accuracy alone.

12. Real-Time Wearable Anomaly Detection with a Bayesian Belief Network

Case-study solution and model design

Network design. Observe heart rate, oxygen saturation, temperature, respiratory rate and activity level. A Bayesian network can represent relationships such as activity → heart rate, illness state → temperature/respiration, and oxygenation state → SpO■. Conditional probability tables should be learned from validated data and adjusted for relevant context such as age and baseline. The output is P(anomaly|current readings, recent history), not a diagnosis by itself.

Analysis of uncertainty and core concepts

Dependencies and sensor noise. Physiological measures are related; modeling dependencies avoids treating each reading as independent evidence. Sensor readings should include quality flags, calibration status and missingness. Use likelihoods for noisy measurements and temporal smoothing to avoid alerts from single transient spikes. If readings conflict or sensor quality is poor, lower confidence and request repeat measurement rather than automatically escalating every event.

Evaluation, practical constraints and application

Performance and deployment. Measure sensitivity, specificity, false alerts per patient-day, detection delay, calibration and battery/network costs. Use patient-level validation and test across devices and activity conditions. Real-time deployment requires low-latency inference, secure transmission, privacy protection, fail-safe behaviour and clinical escalation protocols. Thresholds must be clinically approved and alerts must not be represented as a definitive diagnosis.

Illustrative implementation / workflow

Conclusion. A BBN can combine multiple noisy vital signs into a probabilistic alert score, but safe use requires personalization, validation and a clear clinical response workflow.

Implementation steps: (1) Establish each patient's baseline and check wearable sensor quality. (2) Define a BBN for activity, heart rate, oxygen saturation, temperature and respiratory state. (3) Learn conditional probabilities from validated labelled windows and represent measurement error. (4) Use temporal windows and quality flags to reduce single-sample false alarms. (5) Measure sensitivity, specificity, false alerts per patient-day, detection delay and inference latency. (6) Validate thresholds with clinical experts and define what the system does when connectivity or sensors fail.

Conclusion

Limitations. Physiological baselines differ across individuals; a population model can miss personalized anomalies. Sensor drift, motion artefacts, connectivity loss and class imbalance require monitoring and fallback rules.

13. Dynamic Delivery Routing Under Traffic and Weather Uncertainty

Case-study solution and model design

Probabilistic route model. Represent the road network as a graph. Each edge has a travel-time distribution conditioned on time of day, weather, incidents and recent traffic. Bayesian inference updates the distribution when new observations arrive. For a candidate route, estimate expected travel time and uncertainty or probability of exceeding a deadline. Choose a route minimizing expected cost subject to constraints such as delivery windows, vehicle limits and road closures.

Analysis of uncertainty and core concepts

Prior knowledge and real-time updates. Historical travel-time distributions provide priors for each road/time period. Live GPS, traffic feeds and weather observations update the posterior. When observations are sparse, the prior stabilizes estimates; when current evidence is strong, it should dominate. Detect stale feeds and conflicting reports rather than treating them as certain. Recalculate only affected edges when possible.

Evaluation, practical constraints and application

Complexity and efficiency. A shortest-path algorithm such as Dijkstra can use expected edge times, but minimizing expected time alone may ignore risk. Risk-sensitive routing can penalize variance or minimize deadline-miss probability. Recomputing a full route repeatedly can be expensive; use incremental graph updates, bounded rerouting frequency and precomputed alternatives. Travel times may be correlated across edges during regional weather events, so assuming independent edge times can underestimate total uncertainty.

Illustrative implementation / workflow

Conclusion. Bayesian updates improve route estimates as conditions change. A practical optimizer balances expected time, reliability, computational cost and the consequences of missed delivery windows.

Implementation steps: (1) Represent the road network as a graph and estimate historical edge-time distributions by time and weather. (2) Update edge distributions with live reports while checking freshness and confidence. (3) Score candidate routes using expected time plus a risk penalty or deadline-miss probability. (4) Recompute only affected routes and apply a minimum-benefit threshold before rerouting. (5) Evaluate travel-time error, deadline success, fuel use and reroute frequency on later journeys. (6) Test regional weather events and correlated edge delays, which can invalidate a simple independent-edge assumption.

Conclusion

Evaluation and limitations. Compare predicted versus actual travel time, MAE, deadline success rate, fuel use and reroute count. Test on time-ordered historical data and disruptions. Poor data, sudden incidents and driver constraints limit optimality; route recommendations must obey road rules and operational requirements.

14. Cybersecurity Intrusion Detection Using Naïve Bayes, EM and Bayesian Learning

Case-study solution and model design

Model design. Extract features from network flows such as connection duration, bytes, protocol, failed logins, packet rate and destination novelty. Train a Naïve Bayes classifier on labelled normal/attack traffic, and use Bayesian updating to estimate P(intrusion|features). EM can help model latent traffic modes or unlabeled mixtures, for example common normal behaviours and previously unseen patterns. Treat the EM cluster score as an anomaly signal, not automatically as a confirmed attack label.

Analysis of uncertainty and core concepts

Hidden patterns and incomplete data. EM estimates latent component assignments in the E-step and updates mixture parameters in the M-step. Multiple initializations and convergence checks are needed because local optima are possible. Missing features should be handled using appropriate likelihood marginalization or explicit missingness handling; arbitrary replacement may create false patterns. Combine supervised posterior scores with unsupervised anomaly scores and apply a threshold calibrated to operational capacity.

Evaluation, practical constraints and application

False alarms and dynamic environments. Measure precision, recall, PR-AUC, false positives per hour, detection delay and performance by attack type. Use time-based testing to simulate future traffic and monitor distribution shift. High-confidence alerts can be blocked automatically only under approved policy; uncertain cases can be investigated. Update models carefully because attackers may poison data or adapt to known rules.

Illustrative implementation / workflow

Hybrid detection workflow: # supervised_score = NaiveBayes.predict_proba(flow_features) # anomaly_score = EM_mixture_negative_log_likelihood(flow_features) # combine scores using a validation-trained/calibrated rule # if score exceeds high threshold: alert/block per security policy # elif score exceeds review threshold: send to analyst # monitor false-positive rate and drift; do not treat every cluster as an attack.

Implementation steps: (1) Extract flow-level features and label a time-ordered dataset. (2) Train Naïve Bayes on labelled traffic and fit an EM mixture to characterize latent normal patterns. (3) Calibrate and combine supervised posterior and anomaly scores on validation data. (4) Choose separate thresholds for alert, review and automated blocking according to policy. (5) Evaluate precision, recall, PR-AUC, false alarms per hour and detection delay by attack class. (6) Monitor distribution shift and protect model updates from poisoned or adversarial data.

Conclusion

Limitations and conclusion. Encrypted traffic, evolving attacks, rare labels, adversarial evasion and privacy constraints limit detection. Bayesian scores make evidence and uncertainty explicit, while EM can reveal hidden structure, but analyst feedback and layered security controls remain essential.

15. Crop Yield Prediction with Bayesian Inference and Probability Learning

Case-study solution and model design

Model design. Predict crop yield (for example tonnes per hectare) using rainfall, temperature, soil type, pH, nutrient levels, irrigation, seed variety, planting date and pest pressure. Use a probabilistic regression model to estimate a predictive distribution for yield, or discretize yield into low/medium/high classes and apply Bayes' theorem. Priors can encode agronomic knowledge, such as plausible yield ranges or expected response directions, but should be checked against local data. Include region and crop variety to avoid pooling incompatible farming conditions.

Analysis of uncertainty and core concepts

Prior knowledge and seasonal variation. Historical regional yield and expert knowledge provide priors when recent observations are scarce. Seasonal rainfall timing may matter more than total rainfall; temperature effects can vary by crop growth stage. Update predictions as weather and soil measurements arrive. Use hierarchical models to share information across regions while allowing local differences. Compare prior-sensitive and weak-prior fits to see whether conclusions depend strongly on assumptions.

Evaluation, practical constraints and application

Reliability and evaluation. Train on earlier seasons and test on later seasons, preferably with separate regions for external validation. Report MAE/RMSE, bias and predictive-interval coverage. Account for missing farm records, measurement error, extreme weather and changes in seed/fertilizer practices. Communicate ranges and scenario assumptions rather than one guaranteed yield number.

Illustrative implementation / workflow

Conclusion. Bayesian yield prediction combines data with prior agricultural knowledge and updates as the season develops. Reliability depends on local validation, seasonal modeling and honest uncertainty communication.

Implementation steps: (1) Build one row per farm-season with crop variety, soil, management and weather variables. (2) Check units, missingness and extreme measurements, and preserve season/region identifiers. (3) Train a Bayesian regression model on earlier seasons and test on later seasons or unseen regions. (4) Update in-season predictions when new rainfall and temperature observations arrive. (5) Report predictive intervals, MAE/RMSE, bias and interval coverage by crop and region. (6) Present scenario-based advice to farmers and planners with clear uncertainty ranges rather than guaranteed yield values.

Conclusion

Impact and limitations. Farmers can use forecasts to plan irrigation, fertilizer, storage, labour and crop insurance; policymakers can plan food supply and emergency support. Predictions should be accessible and accompanied by uncertainty because weather extremes and pests can shift outcomes beyond historical experience. The model supports decisions but does not replace local agronomic advice.