



Message Implementation Guideline

## Despatch Advice Outbound XML

Model: DespatchAdvice-outbound  
Version: GS1 BMB 3.1  
Variant: 6  
Issue date: 03.04.2019  
Author: Vidar Thoresen

1 Structure .....	3
2 Guideline .....	6

---

# Change log DespatchAdvice-outbound

Date	Variant	Comments
14.04.2019	6	Merged GS1 3.1 for Axia and Nyce systems

## Structure

Occurrence	Element/Attribute
------------	-------------------

Occurrence	Element/Attribute
1 .. 1	<b>despatchAdviceMessage</b>

1 .. 1	<b>sh:StandardBusinessDocumentHeader</b>
--------	--

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>HeaderVersion</b>
--------	----------------------

1 .. unbounded	<b>Sender</b>
----------------	---------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>Identifier</b>
--------	-------------------

1 .. 1	<i>Authority</i>
--------	------------------

1 .. unbounded	<b>Receiver</b>
----------------	-----------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>Identifier</b>
--------	-------------------

1 .. 1	<b>DocumentIdentification</b>
--------	-------------------------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>Standard</b>
--------	-----------------

1 .. 1	<b>TypeVersion</b>
--------	--------------------

1 .. 1	<b>InstanceIdentifier</b>
--------	---------------------------

1 .. 1	<b>Type</b>
--------	-------------

1 .. 1	<b>CreationDateAndTime</b>
--------	----------------------------

1 .. 10000	<b>despatchAdvice</b>
------------	-----------------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>creationDateTime</b>
--------	-------------------------

1 .. 1	<b>documentStatusCode</b>
--------	---------------------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>despatchAdviceIdentification</b>
--------	-------------------------------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

1 .. 1	<b>entityIdentification</b>
--------	-----------------------------

0 .. 1	<b>deliveryTypeCode</b>
--------	-------------------------

0 .. 1	<b>note</b>
--------	-------------

required	<i>languageCode</i>
----------	---------------------

1 .. 1	<b>receiver</b>
--------	-----------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

0 .. unbounded	<b>additionalPartyIdentification</b>
----------------	--------------------------------------

required	<i>additionalPartyIdentificationTypeCode</i>
----------	--

1 .. 1	<b>shipper</b>
--------	----------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

0 .. 1	<b>gln</b>
--------	------------

1 .. 1	<b>shipTo</b>
--------	---------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

0 .. unbounded	<b>additionalPartyIdentification</b>
----------------	--------------------------------------

required	<i>additionalPartyIdentificationTypeCode</i>
----------	--

0 .. 1	<b>address</b>
--------	----------------

1 .. 1	<i>xs:sequence</i>
--------	--------------------

0 .. 1	<b>city</b>
--------	-------------

0 .. 1	<b>countryCode</b>
--------	--------------------

0 .. 1	<b>name</b>
--------	-------------

0 .. 1	<b>postalCode</b>
--------	-------------------

0 .. 1	<b>streetAddressOne</b>
--------	-------------------------

1 .. 1	<b>inventoryLocation</b>
--------	--------------------------

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>gln</b>
0 .. 1	<b>additionalPartyIdentification</b>
1 .. 1	<i>additionalPartyIdentificationTypeCode</i>
required	
1 .. 1	<b>despatchInformation</b>
1 .. 1	<b>xsd:sequence</b>
0 .. 1	<b>despatchDateTime</b>
0 .. 1	<b>estimatedDeliveryDateTime</b>
0 .. 1	<b>despatchAdviceTransportInformation</b>
1 .. 1	<b>xsd:sequence</b>
0 .. 1	<b>consignmentIdentification</b>
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>ginc</b>
0 .. unbounded	<b>despatchAdviceLogisticUnit</b>
1 .. 1	<b>xsd:sequence</b>
0 .. 1	<b>logisticUnitIdentification</b>
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>sscc</b>
0 .. 1	<b>logisticUnitMeasurement</b>
1 .. 1	<b>xsd:sequence</b>
0 .. unbounded	<b>unitMeasurement</b>
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>measurementType</b>
1 .. 1	<b>measurementValue</b>
required	<i>measurementUnitCode</i>
1 .. 1	<b>xsd:sequence</b>
0 .. unbounded	<b>despatchAdviceLineItem</b>
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>lineItemNumber</b>
1 .. 1	<b>despatchedQuantity</b>
	<i>measurementUnitCode</i>
0 .. 1	<b>note</b>
required	<i>languageCode</i>
1 .. 1	<b>transactionalTradeItem</b>
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>gtin</b>
0 .. unbounded	<b>additionalTradeItemIdentification</b>
required	<i>additionalTradeItemIdentificationTypeCode</i>
1 .. 1	<b>xsd:sequence</b>
0 .. unbounded	<b>transactionalItemData</b>
1 .. 1	<b>xsd:sequence</b>
0 .. 1	<b>batchNumber</b>
0 .. 1	<b>bestBeforeDate</b>
0 .. unbounded	<b>serialNumber</b>
0 .. unbounded	<b>transactionalItemWeight</b>
1 .. 1	<b>xsd:sequence</b>
1 .. 1	<b>measurementType</b>
1 .. 1	<b>measurementValue</b>
required	<i>measurementUnitCode</i>
	<b>customerReference</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
<b>0 .. 1</b>	
1 .. 1	xsd:sequence
1 .. 1	<b>entityIdentification</b>

## Guideline

Element/Attribute	Annotation	
<b>despatchAdviceMessage</b>	Type	despatch_advice:DespatchAdviceMessageType
xsd:sequence	Occurrence	1 .. 1
<b>sh:StandardBusinessDocumentHeader</b>	Occurrence	1 .. 1
	Type	sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence	1 .. 1
<b>HeaderVersion</b>	Occurrence	1 .. 1
	Type	xsd:string
	Example	3.1
<b>Sender</b>	Occurrence	1 .. unbounded
	Type	sh:Partner
xsd:sequence	Occurrence	1 .. 1
<b>Identifier</b>	Occurrence	1 .. 1
	Type	sh:PartnerIdentification
	Remark	<b>GLN (GS1 location code) for sender of the message</b>
	Example	<b>7080000950171</b>
<i>Authority</i>	Type	xsd:string
	Example	14
	<b>Applicable Codes</b>	
	14	EAN International
<b>Receiver</b>	Occurrence	1 .. unbounded
	Type	sh:Partner
xsd:sequence	Occurrence	1 .. 1
<b>Identifier</b>	Occurrence	1 .. 1
	Type	sh:PartnerIdentification
	Remark	<b>Client id</b>
	Example	<b>123456</b>
<b>DocumentIdentification</b>	Occurrence	1 .. 1
	Type	sh:DocumentIdentification
xsd:sequence	Occurrence	1 .. 1
<b>Standard</b>	Occurrence	1 .. 1
	Type	xsd:string
	Example	<b>GS1 BMS</b>
<b>TypeVersion</b>	Occurrence	1 .. 1
	Type	xsd:string
	Example	3.1
<b>InstanceIdentifier</b>	Occurrence	1 .. 1
	Type	xsd:string
	Example	<b>GS1</b>
<b>Type</b>	Occurrence	1 .. 1
	Type	xsd:string
	Example	<b>DespatchAdviceOutbound</b>
<b>CreationDateAndTime</b>	Occurrence	1 .. 1
	Type	xsd:dateTime
	Remark	<b>Message date/time</b>
	Example	<b>2014-09-10T12:00:00</b>
<b>despatchAdvice</b>	Occurrence	1 .. 10000
	Type	despatch_advice:DespatchAdviceType
xsd:sequence	Occurrence	1 .. 1
<b>creationDateTime</b>	Occurrence	1 .. 1
	Type	xsd:dateTime
	Remark	<b>Document date/time</b>
	Example	<b>2014-09-10T11:00:00</b>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
<b>documentStatusCode</b>	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Example <b>ORIGINAL</b> <b>Applicable Codes</b> <b>ORIGINAL</b>
xsd:sequence	Occurrence 1 .. 1
<b>despatchAdviceIdentification</b>	Occurrence 1 .. 1 Type shared_common:EntityIdentificationType xsd:sequence Occurrence 1 .. 1 <b>entityIdentification</b> Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark <b>Order number received in the Customer Order 'orderIdentification'</b> Example <b>125987</b>
<b>deliveryTypeCode</b>	Occurrence 0 .. 1 Type ecom_common:DeliveryTypeCodeType Length 1 .. 80 Remark <b>Status code from Axia</b> Example <b>O4</b> <b>Applicable Codes</b> <b>99</b> Canceled <b>O1</b> EDI / API data received <b>O2</b> Order allocated <b>O3</b> Order picked <b>O4</b> Order sent
<b>note</b>	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark <b>Additional reference received in Customer Order 'note'</b> Example <b>69581A</b>
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Remark <b>Element required</b> Example <b>SE</b>
<b>receiver</b>	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType xsd:sequence Occurrence 1 .. 1 <b>additionalPartyIdentification</b> Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark <b>Client Id</b> Example <b>123456</b>
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example <b>88</b> <b>Applicable Codes</b> <b>88</b> Assigned by the owner of operation
<b>shipper</b>	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType xsd:sequence Occurrence 1 .. 1

**Bold** = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Description <b>Only used by Bring Frigo</b> Remark <b>GLN (GS1 location code) for shipper (consignor)</b> Example <b>73933217401018</b>
shipTo	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark <b>Customer id for delivery party</b> Example <b>50296</b>
additionalPartyIdentificationTypeCode	Type restriction (xsd:string) Length 1 .. 80 Use required Example <b>88</b> <b>Applicable Codes</b> <b>88</b> Assigned by the owner of operation
address	Occurrence 0 .. 1 Type shared_common:AddressType
xsd:sequence	Occurrence 1 .. 1
city	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark <b>ShipTo cityname</b> Example <b>OSLO</b>
countryCode	Occurrence 0 .. 1 Type shared_common:CountryCodeType Length 1 .. 80 Remark <b>Use ISO 3166 Alpha</b> Example <b>NO</b>
name	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark <b>ShipTo name</b> Example <b>ICA Kvantum</b>
postalCode	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark <b>ShipTo postal code</b> Example <b>1000</b>
streetAddressOne	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark <b>ShipTo Street address</b> Example <b>Lagervejen 14</b>
inventoryLocation	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark <b>GLN for warehouse location</b> Example <b>7393321401018</b>

**Bold** = Element, **Italic** = Attribute, **Grey** = Group



Element/Attribute	Annotation
<b>additionalPartyIdentification</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:AdditionalPartyIdentificationType <b>Length</b> 1 .. 80 <b>Remark</b> <b>Warehouse location</b> <b>Example</b> <b>BERGER</b>
	<b>Applicable Codes</b>
	<b>4033</b> Stavanger (Norway)
	<b>5500</b> Haugesund (Norway)
	<b>AES</b> Ålesund (Norway)
	<b>BERGER</b> Berger/Skedsbokorset (Norway)
	<b>BS02</b> Kongshavn (Norway)
	<b>BS07</b> Trollåsen (Norway)
	<b>BS17</b> Bergen (Norway)
	<b>BS26</b> Trondheim (Norway)
	<b>BS34</b> Tromsø (Norway)
	<b>FI01</b> (Finland)
	<b>JKPG01</b> Jönköping (Sweden)
	<b>NCD</b> Lierstrand (Norway)
<b>despatchInformation</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> ecom_common:DespatchInformationType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>despatchDateTime</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xsd:dateTime <b>Remark</b> <b>Despatch date/time from warehouse</b> <b>Example</b> <b>2014-10-09T10:12:00</b>
<b>estimatedDeliveryDateTime</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xsd:dateTime <b>Remark</b> <b>Estimated delivery Date</b> <b>Example</b> <b>2014-10-11T00:00:00</b>
<b>despatchAdviceTransportInformation</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> despatch_advice:DespatchAdviceTransportInformationType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>consignmentIdentification</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> shared_common:ConsignmentIdentificationType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>ginc</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:GINCType <b>Pattern</b> [-!%&'()*+,-./0-9;=<=>?A-Z_a-z]{4,30} <b>Remark</b> <b>GINC ( Global Shipment Identification Number)</b> <b>Remark</b> <b>As this is a required element fill in '73500538500000019' if GINC not is in use</b> <b>Example</b> <b>73500538500000019</b>
<b>despatchAdviceLogisticUnit</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> despatch_advice:DespatchAdviceLogisticUnitType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>logisticUnitIdentification</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> shared_common:LogisticUnitIdentificationType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>sscc</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:SSCCType <b>Pattern</b> \d{18} <b>Remark</b> <b>SSCC (Serial shipping container code)</b> <b>Example</b> <b>37323991248161986</b>
<b>logisticUnitMeasurement</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> ecom_common:LogisticUnitMeasurementType

**Bold** = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation
<i>xsd:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>unitMeasurement</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ecom_common:UnitMeasurementType
<i>xsd:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>measurementType</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> ecom_common:MeasurementTypeCodeType <b>Length</b> 1 .. 80 <b>Example</b> AAD
	<b>Applicable Codes</b>
	AAD Total Gross Weight
<b>measurementValue</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:MeasurementType <b>Remark</b> <b>Total Gross Weight</b> <b>Example</b> 825
<i>measurementUnitCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Use</b> required <b>Example</b> KGM
	<b>Applicable Codes</b>
	KGM kilogram
<i>xsd:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>despatchAdviceLineItem</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> despatch_advice:DespatchAdviceLineItemType
<i>xsd:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>lineItemNumber</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> xsd:positiveInteger <b>FractionDigits</b> 0 <b>Inclusive</b> 1 .. <b>Remark</b> <b>Line item number</b> <b>Example</b> 1
<b>despatchedQuantity</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:QuantityType <b>Remark</b> <b>Number of packages despatched</b> <b>Example</b> 50
<i>measurementUnitCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Example</b> PCE
	<b>Applicable Codes</b>
	PCE pieces
<b>note</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> shared_common:Description500Type <b>Length</b> 1 .. 500 <b>Remark</b> <b>Note sent i the CustomerOrder will be returned</b> <b>Example</b> 12-234-90A
<i>languageCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Use</b> required <b>Example</b> NO
	<b>Applicable Codes</b>
	NO
<b>transactionalTradeItem</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> ecom_common:TransactionalTradeItemType
<i>xsd:sequence</i>	<b>Occurrence</b> 1 .. 1
<b>gtin</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:GTINType <b>Pattern</b> \d{14}

**Bold** = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation
	<b>Remark</b> GTIN 13 (GS1 article number) if not used fillin zeros <b>Example</b> 00000000000000
<b>additionalTradeItemIdentification</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> shared_common:AdditionalTradeItemIdentificationType <b>Length</b> 1 .. 80
	<b>Remark</b> Supplier's article number <b>Example</b> 123456
<i>additionalTradeItemIdentificationTypeCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Use</b> required <b>Example</b> IN
	<b>Applicable Codes</b> <b>IN</b> Buyer's Item number <b>SA</b> Supplier's article number <b>ZGR</b> Grade
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>transactionalItemData</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ecom_common:TransactionalItemDataType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>batchNumber</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Remark</b> Batch number <b>Example</b> 2514780
<b>bestBeforeDate</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> xsd:date <b>Remark</b> Best before date (CCYYMMDD) <b>Example</b> 150101
<b>serialNumber</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 20 <b>Example</b> 34509810
<b>transactionalItemWeight</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> ecom_common:UnitMeasurementType
xsd:sequence	<b>Occurrence</b> 1 .. 1
<b>measurementType</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> ecom_common:MeasurementTypeCodeType <b>Length</b> 1 .. 80 <b>Example</b> AAC
	<b>Applicable Codes</b> <b>AAC</b> Total net weight
<b>measurementValue</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:MeasurementType <b>Remark</b> Total net weight <b>Example</b> 750
<i>measurementUnitCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Use</b> required <b>Example</b> KGM
	<b>Applicable Codes</b> <b>KGM</b> kilogram
<b>customerReference</b>	<b>Occurrence</b> 0 .. 1 <b>Type</b> shared_common:DocumentReferenceType
xsd:sequence	<b>Occurrence</b> 1 .. 1

**Bold** = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation	
└ <b>entityIdentification</b>	Occurrence	1 .. 1
	Type	restriction (xsd:string)
	Length	1 .. 80
	Remark	<b>Customer Reference</b>
	Example	<b>69581A</b>

```

<?xml version="1.0" encoding="utf-8"?>
<ns0:despatchAdviceMessage xmlns:ns0="urn:gs1:ecom:despatch_advice:xsd:3">
  <sh:StandardBusinessDocumentHeader
    xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader">
    <sh:HeaderVersion>3.1</sh:HeaderVersion>
    <sh:Sender>
      <sh:Identifier Authority="14">7080000950171</sh:Identifier>
    </sh:Sender>
    <sh:Receiver>
      <sh:Identifier Authority="30">999999</sh:Identifier>
    </sh:Receiver>
    <sh:DocumentIdentification>
      <sh:Standard>GS1 BMS</sh:Standard>
      <sh:TypeVersion>3.1</sh:TypeVersion>
      <sh:InstanceIdentifier>GS1</sh:InstanceIdentifier>
      <sh:Type>DespatchAdviceOutbound</sh:Type>
      <sh:CreationDateAndTime>2019-04-15T22:01:35</sh:CreationDateAndTime>
    </sh:DocumentIdentification>
  </sh:StandardBusinessDocumentHeader>
  <despatchAdvice>
    <creationDateTime>2019-04-13T17:00:18</creationDateTime>
    <creationDateTime>2019-04-13T17:00:18</creationDateTime>
    <documentStatusCode>ORIGINAL</documentStatusCode>
    <despatchAdviceIdentification>
      <entityIdentification>222333222</entityIdentification>
      <deliveryTypeCode>04</deliveryTypeCode>
      <note>1226543</note>
    </despatchAdviceIdentification>
    <shipTo>
      <address>
        <name>Customer name</name>
        <postalCode>1088</postalCode>
        <city>OSLO</city>
        <countrycode>NO</countrycode>
        <streetAddressOne>Customer street</streetAddressOne>
      </address>
      <contact />
    </shipTo>
    <inventoryLocation>
      <additionalPartyIdentification>NCD</additionalPartyIdentification>
    </inventoryLocation>
    <despatchInformation>
      <despatchDateTime>2019-04-13T00:00:00</despatchDateTime>
    </despatchInformation>
    <despatchAdviceTransportInformation>
      <consignmentIdentification>
        <ginc>7080000950171</ginc>
      </consignmentIdentification>
    </despatchAdviceTransportInformation>
    <despatchAdviceLogisticUnit>
      <despatchAdviceLineItem>
        <lineItemNumber>10</lineItemNumber>
        <transactionalTradeItem>
          <additionalTradeItemIdentification
            additionalTradeItemIdentificationTypeCode="IN">11111111</additionalTradeItemIdentification>

```

Bold = Element, Italic = Attribute, Grey = Group

```

description</tradeltemDescription>
    <tradeltemDescription>Article one
    <transactionalItemData>
        <batchNumber>M11111</batchNumber>
        <tradeltemQuantity>
measurementUnitCode="PCE">1.0</tradeltemQuantity>
        </transactionalItemData>
    </transactionalTradeltem>
    <despatchedQuantity>
measurementUnitCode="PCE">1.0</despatchedQuantity>
    </despatchAdviceLineItem>
</despatchAdviceLogisticUnit>
<despatchAdviceLogisticUnit>
    <despatchAdviceLineItem>
        <lineItemNumber>20</lineItemNumber>
        <transactionalTradeltem>
            <additionalTradeltemIdentification>
additionalTradeltemIdentificationTypeCode="IN">22222222</additionalTradeltemIdentification>
            <tradeltemDescription>Article two
description</tradeltemDescription>
            <transactionalItemData>
                <batchNumber>M22222</batchNumber>
                <tradeltemQuantity>
measurementUnitCode="PCE">1.0</tradeltemQuantity>
            </transactionalItemData>
            </transactionalTradeltem>
            <despatchedQuantity>
measurementUnitCode="PCE">1.0</despatchedQuantity>
            </despatchAdviceLineItem>
        </despatchAdviceLogisticUnit>
    </despatchAdvice>
</ns0:despatchAdviceMessage>

```