



Message Implementation Guideline

Despatch Order inbound XML

Model: DespatchAdvice-inbound
Version: GS1 BMB 3.1
Variant: 4
Issue date: 03.04.2019
Author: Vidar Thoresen

1 Structure	3
2 Guideline	5

Change log DespatchAdvice-inbound

Date	Variant	Comments
08.04.2019	4	Merged GS1 3.1 for Axia and Nyce systems

Structure

Occurrence	Element/Attribute
	despatchAdviceMessage
1 .. 1	xsd:sequence
1 .. 1	sh:StandardBusinessDocumentHeader
1 .. 1	xsd:sequence
1 .. 1	HeaderVersion
1 .. unbounded	Sender
1 .. 1	xsd:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. unbounded	Receiver
1 .. 1	xsd:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. 1	DocumentIdentification
1 .. 1	xsd:sequence
1 .. 1	Standard
1 .. 1	TypeVersion
1 .. 1	InstanceIdentifier
1 .. 1	Type
1 .. 1	CreationDateAndTime
1 .. 10000	despatchAdvice
1 .. 1	xsd:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
1 .. 1	xsd:sequence
1 .. 1	despatchAdviceIdentification
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
0 .. 1	deliveryTypeCode
	<i>codeListVersion</i>
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	receiver
1 .. 1	xsd:sequence
0 .. 1	gln
1 .. 1	shipper
1 .. 1	xsd:sequence
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	shipTo
1 .. 1	xsd:sequence
1 .. 1	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	despatchInformation
1 .. 1	xsd:sequence
0 .. 1	estimatedDeliveryDateTime
0 .. unbounded	despatchAdviceLogisticUnit
1 .. 1	xsd:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	logisticUnitIdentification
1 .. 1	xsd:sequence
1 .. 1	sscc
1 .. 1	xsd:sequence
0 .. unbounded	despatchAdviceLineItem
1 .. 1	xsd:sequence
1 .. 1	lineItemNumber
1 .. 1	despatchedQuantity
1 .. 1	<i>measurementUnitCode</i>
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	transactionalTradelItem
1 .. 1	xsd:sequence
1 .. 1	gtin
0 .. unbounded	additionalTradelItemIdentification
required	<i>additionalTradelItemIdentificationTypeCode</i>
1 .. 1	xsd:sequence
0 .. 1	tradelItemDescription
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. 1	productVariantIdentifier
0 .. unbounded	transactionalItemData
1 .. 1	xsd:sequence
0 .. 1	batchNumber
0 .. 1	bestBeforeDate
0 .. 1	productionDate
0 .. 1	productCertification
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
1 .. 1	xsd:sequence
0 .. 1	creationDateTime
0 .. 1	specification
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
0 .. 1	purchaseOrder
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
1 .. 1	xsd:sequence
0 .. 1	lineItemNumber

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation	
despatchAdviceMessage	Type	despatch_advice:DespatchAdviceMessageType
xsd:sequence	Occurrence	1 .. 1
sh:StandardBusinessDocumentHeader	Occurrence	1 .. 1
xsd:sequence	Type	sh:StandardBusinessDocumentHeader
HeaderVersion	Occurrence	1 .. 1
Occurrence	Type	xsd:string
Example		3.1
Sender	Occurrence	1 .. unbounded
Type		sh:Partner
xsd:sequence	Occurrence	1 .. 1
Identifier	Occurrence	1 .. 1
Type		sh:PartnerIdentification
Remark		Client Id
Example		12345
Authority	Type	xsd:string
	Applicable Codes	
	14	EAN International
	30	ISO 6523: Organization identification
	ZZ	Mutually defined
Receiver	Occurrence	1 .. unbounded
Type		sh:Partner
xsd:sequence	Occurrence	1 .. 1
Identifier	Occurrence	1 .. 1
Type		sh:PartnerIdentification
Remark		GLN for receiver of the message
Example		7080000950171
Authority	Type	xsd:string
	Applicable Codes	
	14	EAN International
	30	ISO 6523: Organization identification
	ZZ	Mutually defined
DocumentIdentification	Occurrence	1 .. 1
Type		sh:DocumentIdentification
xsd:sequence	Occurrence	1 .. 1
Standard	Occurrence	1 .. 1
Type		xsd:string
Example		GS1 BMS
TypeVersion	Occurrence	1 .. 1
Type		xsd:string
Example		3.1
InstanceIdentifier	Occurrence	1 .. 1
Type		xsd:string
Example		GS1
Type	Occurrence	1 .. 1
Type		xsd:string
Example		DespatchAdviceInbound
CreationDateAndTime	Occurrence	1 .. 1
Type		xsd:dateTime
Remark		Message date/time
Example		2014-09-24T10:15:25
despatchAdvice	Occurrence	1 .. 10000
xsd:sequence	Type	despatch_advice:DespatchAdviceType
	Occurrence	1 .. 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
creationDateTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Document date/time Example 2014-09-25T09:50:00
documentStatusCode	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Example ORIGINAL Applicable Codes ORIGINAL
xsd:sequence	Occurrence 1 .. 1
despatchAdviceIdentification	Occurrence 1 .. 1 Type shared_common:EntityIdentificationType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Purchase order number or reference to the message Example 456789
deliveryTypeCode	Occurrence 0 .. 1 Type ecom_common:DeliveryTypeCodeType Length 1 .. 80 Remark S to be used for Sampakk Remark R to be used for Return Example S Applicable Codes R Return-order S Sampak
codeListVersion	Type restriction (xsd:string) Length 1 .. 35 Applicable Codes S
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Element to be used for additional referens, as Purchase Order no.,which is searchable in Axia. Example 450347
languageCode	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO
receiver	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN for receiver (Warehouse) Example 7393321401018
shipper	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Id for shipper (Supplier) Example 7890
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 88 Assigned by the owner of operation
shipTo	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
additionalPartyIdentification	Occurrence 1 .. 1 Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Warehouse code for Bring Example BERGER Applicable Codes 4033 Stavanger (Norway) 5500 Haugesund (Norway) AES Ålesund (Norway) BERGER Berger/Skedsbokorset (Norway) BS02 Kongshavn (Norway) BS07 Trollåsen (Norway) BS17 Bergen (Norway) BS26 Trondheim (Norway) BS34 Tromsø (Norway) FI01 (Finland) JKPG01 Jönköping (Sweden) NCD Lierstrand (Norway)
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 88 Assigned by the owner of operation
despatchInformation	Occurrence 1 .. 1 Type ecom_common:DespatchInformationType
xsd:sequence	Occurrence 1 .. 1
estimatedDeliveryDateTime	Occurrence 0 .. 1 Type xsd:dateTime Remark Delivery Date/Time Example 2014-10-15T15:00
despatchAdviceLogisticUnit	Occurrence 0 .. unbounded Type despatch_advice:DespatchAdviceLogisticUnitType
xsd:sequence	Occurrence 1 .. 1
logisticUnitIdentification	Occurrence 0 .. 1 Type shared_common:LogisticUnitIdentificationType
xsd:sequence	Occurrence 1 .. 1
sscc	Occurrence 1 .. 1 Type shared_common:SSCCType Pattern \d{18} Remark SSCC Example 373655645638436204
xsd:sequence	Occurrence 1 .. 1

Bold = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation
despatchAdviceLineItem	Occurrence 0 .. unbounded Type despatch_advice:DespatchAdviceLineItemType
<i>xsd:sequence</i>	Occurrence 1 .. 1
lineItemNumber	Occurrence 1 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. Remark Order line number Example 1
despatchedQuantity	Occurrence 1 .. 1 Type shared_common:QuantityType Remark Despatch quantity Example 9
<i>measurementUnitCode</i>	Type restriction (xsd:string) Length 1 .. 80 Example PCE Applicable Codes PCE pieces
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Refers to order line - to be returned in the confirmation of the order Example 12346-9082-01
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO Applicable Codes DK EN FI NO SE
transactionalTradeItem	Occurrence 1 .. 1 Type ecom_common:TransactionalTradeItemType
<i>xsd:sequence</i>	Occurrence 1 .. 1
gtin	Occurrence 1 .. 1 Type shared_common:GTINType Pattern \d{14} Remark GTIN (GS1 article number) if not used fill in zeroes Example 00000000000000
additionalTradeItemIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalTradeItemIdentificationType Length 1 .. 80 Remark Supplier's article number Example 223344 Remark Buyer's item number Example 65432
<i>additionalTradeItemIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SA Example IN Applicable Codes IN Buyer's Item number

Bold = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation
	Applicable Codes SA Supplier's article number ZCI CustomsItem (false/true) ZCU Currency Coded ZGR Grade ZNP Net Price ZTP Total Price
xsd:sequence	Occurrence 1 .. 1
tradeItemDescription	Occurrence 0 .. 1 Type shared_common:Description200Type Length 1 .. 200 Remark Item Description Example Paperbox
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example EN
	Applicable Codes DK EN FI NO SE
<i>codeListVersion</i>	Type restriction (xsd:string) Length 1 .. 35
productVariantIdentifier	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Description Only used by Bring Frigo Remark Goods characteristics Example 1
	Applicable Codes 1 Frozen 2 Chilled 3 Dry
transactionalItemData	Occurrence 0 .. unbounded Type ecom_common:TransactionalItemDataType
xsd:sequence	Occurrence 1 .. 1
batchNumber	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Batch number Example 110621
bestBeforeDate	Occurrence 0 .. 1 Type xsd:date Remark Best before date Example 2015-01-01
productionDate	Occurrence 0 .. 1 Type xsd:date Remark Production date Example 2014-09-30
productCertification	Occurrence 0 .. 1 Type shared_common:DocumentReferenceType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80

Bold = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation
	Remark Export Certificate Number Example G17GDDGCA1451147
xsd:sequence	Occurrence 1 .. 1
creationDateTime	Occurrence 0 .. 1 Type xsd:dateTime Remark Certificate Date Example 2017-03-01T15:00:00
specification	Occurrence 0 .. 1 Type shared_common:DocumentReferenceType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Export Certificate Type Example GSP
	Applicable Codes
	EUR
	GSP
purchaseOrder	Occurrence 0 .. 1 Type shared_common:DocumentReferenceType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Purchase Order Number Example 6CE65B05BE09A
xsd:sequence	Occurrence 1 .. 1
lineItemNumber	Occurrence 0 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. Remark Purchase Order line item number Example 1

Bold = Element, *Italic* = Attribute, Grey = Group

```

<?xml version="1.0" encoding="UTF-8"?>
<ns0:despatchAdviceMessage xmlns:ns0="urn:gs1:ecom:despatch_advice:xsd:3">
  <ns1:StandardBusinessDocumentHeader
xmlns:ns1="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader">
    <ns1:HeaderVersion>3.1</ns1:HeaderVersion>
    <ns1:Sender>
        <ns1:Identifier Authority="14">999999</ns1:Identifier>
    </ns1:Sender>
    <ns1:Receiver>
        <ns1:Identifier Authority="14">7080003388100</ns1:Identifier>
    </ns1:Receiver>
    <ns1:DocumentIdentification>
        <ns1:Standard>GS1 BMS</ns1:Standard>
        <ns1:TypeVersion>3.1</ns1:TypeVersion>
        <ns1:InstanceIdentifier>GS1</ns1:InstanceIdentifier>
        <ns1:Type>DespatchAdviceInbound</ns1:Type>
        <ns1:CreationDateAndTime>2019-03-28T11:23:02</ns1:CreationDateAndTime>
    </ns1:DocumentIdentification>
  </ns1:StandardBusinessDocumentHeader>
  <despatchAdvice>
    <creationDateTime>2019-03-28T11:24:18</creationDateTime>
    <documentStatusCode>ORIGINAL</documentStatusCode>
    <despatchAdviceIdentification>
        <entityIdentification>0180026738</entityIdentification>
    </despatchAdviceIdentification>
    <deliveryTypeCode>220</deliveryTypeCode>
    <note languageCode="NO">0005011058</note>
    <receiver>
        <gln>99999999999999</gln>
    </receiver>
    <shipper>
        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">0000000000</additionalPartyIdentification>
        <address>
            <city>TestCity</city>
            <postalCode>9999</postalCode>
        </address>
    </shipper>
    <shipTo>
        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BS02</additionalPartyIdentification>
    </shipTo>
    <despatchInformation>
        <estimatedDeliveryDateTime>2019-03-28T11:24:18</estimatedDeliveryDateTime>
    </despatchInformation>
    <despatchAdviceLogisticUnit>
        <despatchAdviceLineItem>
            <lineItemNumber>000010</lineItemNumber>
            <despatchedQuantity measurementUnitCode="PCE">25.000</despatchedQuantity>
            <note languageCode="NO">000001</note>
            <transactionalTradeItem>
                <gtin>00000000000000</gtin>
                <additionalTradeItemIdentification
additionalTradeItemIdentificationTypeCode="SA">99999999</additionalTradeItemIdentification>
            </transactionalTradeItem>
        </despatchAdviceLineItem>
    </despatchAdviceLogisticUnit>
  </despatchAdvice>
</ns0:despatchAdviceMessage>

```

```
      <additionalTradeltemIdentification
additionalTradeltemIdentificationTypeCode="IN">99999</additionalTradeltemIdentification>
    </transactionalTradeltem>
  </despatchAdviceLineItem>
</despatchAdviceLogisticUnit>
</despatchAdvice>
</ns0:despatchAdviceMessage>
```