Software Requirements Specification (SRS)

Project: Web-Based ML Model Evaluator
Version: 1.0
Authors: All Members
Date: 10-10-2026
Status: Final

Revision history

Version	Date	Author	Change summary	Approval
0.2	12-10-2026	All Members	Reviewed Part A for consistency with SRS Part B and SAD;	

Approvals

Role	Name	Signature / Email	Date
Course Coordinator			

Table of Contents

1. Introduction
2. Overall description
3. External interfaces
4. System features (detailed)
5. Non-functional requirements (detailed)
6. Quality attributes & Acceptance tests
7. UML Use-Case Diagram
8. Requirements Traceability Matrix (RTM)

1. Introduction

1.1 Purpose

This Software Requirements Specification (SRS) defines the requirements for the Web-Based ML Model Evaluator (WBMME). It describes the system's purpose, scope, overall context, intended users, operating environment, constraints and assumptions. The document serves as a common reference for the project team, developers, testers and evaluators throughout the design, development, testing and evaluation of the system.

1.2 Scope

The system is a web application that allows users to upload tabular datasets, inspect and prepare data, select supported machine-learning algorithms, train models, evaluate model performance, and review or compare experiment results. The application also provides metric visualizations and downloadable reports. It is intended for educational and experimental model evaluation and does not guarantee the suitability of evaluated models for production use.

1.3 Audience

Primary audiences are students and data scientists using the evaluator, administrators responsible for platform operation, developers implementing the web and ML components, testers validating requirements, and project evaluators reviewing the deliverables.

1.4 Definitions

WBMME: Web-Based ML Model Evaluator. **UI**: User Interface. **API**: Application Programming Interface. **ML**: Machine Learning. **CSV**: Comma-Separated Values. **Dataset**: A collection of records and attributes supplied for analysis. **Preprocessing**: Preparing raw data for model training. **Training**: Fitting a selected algorithm to prepared data. **Evaluation**: Measuring a trained model against held-out data using defined metrics. **Experiment/run**: A recorded execution of a selected model and configuration. **RTM**: Requirements Traceability Matrix. **SRS**: Software Requirements Specification. **SAD**: Software Architecture Document.

2. Overall description

2.1 Product perspective

WBMME is a browser-accessible application consisting of a web presentation layer, server-side application logic, a machine-learning processing pipeline and persistent storage. The browser communicates with the server through application interfaces and does not access the database or file storage directly. The application layer validates requests and coordinates dataset handling, preprocessing, model training, evaluation and result storage. The machine-learning pipeline is designed to use Python and scikit-learn for model development and evaluation. The system follows a modular architecture that separates the user interface, application logic, machine-learning operations and data storage to support maintainability and testing.

2.2 Major product functions

The major functions of the Web-Based ML Model Evaluator are:

- Provide a web interface through which users can access the evaluator.
- Accept dataset uploads and validate supported file types, file sizes and required data structure.
- Display basic dataset information and support data preparation for model training.
- Allow users to select from supported machine-learning algorithms and configure permitted parameters.
- Train selected models using prepared datasets.
- Evaluate trained models using applicable performance metrics and visual summaries.
- Record experiment configurations, dataset metadata and evaluation results for later review.
- Support comparison of recorded experiment runs and export of evaluation results.
- Provide authentication and access control to restrict system functions and data access to authorized users.
- Validate inputs and maintain operational logs to support system reliability, security and maintenance.

2.3 User roles and characteristics

The system is intended for the following categories of users:

- **Data Scientist:** Uses the application to upload datasets, prepare data, select machine-learning algorithms, configure training, evaluate model performance and compare experiment results. The user is expected to have a basic understanding of machine-learning concepts and evaluation metrics.
- **Student:** Uses the application for coursework, learning and experimentation. The interface should provide clear feedback and guidance for dataset preparation, model selection and interpretation of evaluation results.
- **Administrator:** Manages authorized platform-level functions, such as user access and system settings, and monitors operational logs where these capabilities are provided. Administrative privileges are restricted to authorized users.

Each role is provided with permissions appropriate to its responsibilities. The role definitions and access permissions are specified in the functional and security requirements in Sections 4 and 5 and must remain consistent with the Software Architecture Document (SAD) and Test Plan.

2.4 Operating environment

The client side of WBMME operates through a modern desktop web browser with JavaScript enabled and network access to the application. The server environment must support Python and the selected web framework and machine-learning libraries. The planned application technologies include Python, Django, pandas, scikit-learn, joblib, Django templates, JavaScript and Chart.js. Persistent data may be managed using SQLite for development or PostgreSQL where required. Uploaded datasets and trained model artifacts are managed by the server and stored outside the publicly accessible web directory. The final software versions, database

configuration and deployment environment shall be specified according to the team's confirmed implementation choices.

2.5 Constraints

The development and operation of WBMME are subject to the following constraints:

- The system supports only the dataset formats, machine-learning algorithms and configuration options implemented by the project team.
- Uploaded datasets must undergo appropriate file type, size and structural validation before processing.
- Model training and evaluation performance depend on available processing power, memory, storage and dataset size.
- User datasets, trained model artifacts and experiment results must be accessible only to the appropriate users or authorized roles.
- All interactions between the browser and persistent storage must be mediated by the server-side application.
- The system must validate user inputs and handle invalid datasets, unsupported configurations and processing failures appropriately.
- The SRS, Software Architecture Document (SAD), test plan and related deliverables must use consistent requirement identifiers and terminology.
- The implemented technologies, supported features and user permissions must conform to the requirements approved by the project team.

4. System features (detailed)

This section specifies the functional requirements of WBMME, grouped by system feature in the style of the IEEE SRS template: description and priority, stimulus/response sequences, then the numbered requirements. Every requirement has a unique ID (MLE-F-nnn), uses “shall” for mandatory behaviour, states a measurable limit where one applies, and names how it will be verified.

Priority. High: needed for the minimal end-to-end flow. Medium: needed for a complete release. Low: may be deferred if the two-sprint schedule requires it (SAD 3.7, risk R8).

4.1 Authentication and access control

4.1.1 Description and priority

Lets a person create an account, log in, and use only the functions that their role allows. Three roles exist: Student, Data Scientist and Admin (SRS 2.3).

Priority: High. Every other feature depends on it, and it carries security objectives MLE-SO-001 and MLE-SO-002.

Table 4.1-1: Permissions by role

Capability	Student	Data Scientist	Admin
Register an account	Yes	Yes	No (created by an Admin or at installation)
Log in and log out	Yes	Yes	Yes
Upload, prepare and delete own datasets	Yes	Yes	No
Select a model, train and evaluate	Yes	Yes	No
View, compare and export own runs	Yes	Yes	No
Active training jobs at one time (MLE-SR-006)	1	2	Not applicable
List users, change roles, deactivate accounts	No	No	Yes
List and delete any dataset (metadata only)	No	No	Yes
View the audit log	No	No	Yes
Read another user's datasets, models or results	No	No	No

4.1.2 Stimulus/response sequences

- A visitor submits the registration form with valid data: the system creates the account with the chosen role (Student or Data Scientist) and shows the login page. With invalid data the form is shown again with a message per faulty field and no account is created.
- A user submits valid credentials: the system starts a session and shows the dashboard. With invalid credentials the system shows one generic message ("Invalid username or password") and starts no session.
- A logged-in user requests a page or API endpoint that the role does not permit: the system refuses the request (HTTP 403 or 404) and returns no data.
- A user selects Log out, or stays inactive for 30 minutes: the session ends and the login page is shown.

4.1.3 Functional requirements

ID	Requirement	Priority	Verification
MLE-F-001	The system shall let a visitor register with a unique username (3 to 30 characters: letters, digits and underscore), a valid e-mail address and a password of at least 8 characters that contains at least one letter and one digit, and shall let a registered user log in with username and password and log out. A failed login shall be refused with one generic message that does not reveal whether the username or the password was wrong. A deactivated account shall not be able to log in.	High	Test: TC-AUTH-01
MLE-F-002	The system shall assign every account exactly one role (Student, Data Scientist or Admin) and shall check the role on every page and API endpoint. Any access not explicitly permitted by Table 4.1-1 shall be denied with HTTP 403 or 404. Self-registration shall create only Student or Data Scientist accounts; the Admin role shall be assigned only by an existing Admin or at installation. Administration pages and endpoints shall be reachable only by the Admin role.	High	Test: TC-SEC-01

4.2 Data workspace (dataset upload and preparation)

4.2.1 Description and priority

Accepts a CSV dataset, validates it, shows what it contains, and prepares it for training (missing values, categorical encoding, target column and train/test split).

Priority: High. This is the first stage of the pipeline: Upload, Preprocess, Train, Evaluate, Record (SAD 3.5).

Table 4.2-1: Dataset and upload limits (used by MLE-F-003, MLE-F-006 and MLE-SR-003)

Parameter	Limit
File type	.csv only, UTF-8, comma-delimited, first row is the header
Maximum file size	10 MB (a file of exactly 10 MB is accepted; larger files are rejected)
Rows	At least 20 and at most 50,000 data rows
Columns	At least 2 and at most 100 columns; every data row has the same number of fields as the header
Datasets per user	At most 20 stored datasets
Target column	Between 2 and 20 distinct values; every class has at least 2 rows
Cell content	Always handled as data. A cell that starts with =, +, - or @ is never evaluated.

4.2.2 Stimulus/response sequences

- A user uploads a file that passes validation: the system stores it in the user's own directory and shows a preview and profile of the data.
- A user uploads a file that fails validation (wrong type, too large, empty, malformed): the system stores nothing and shows a message that names the reason.
- A user chooses a missing-value treatment and categorical encoding: the system confirms the settings and applies them when the split is created.
- A user selects the target column and test share: the system creates a stratified split, or refuses the choice and explains why (for example, fewer than two classes).

4.2.3 Functional requirements

ID	Requirement	Priority	Verification
MLE-F-003	The system shall accept a dataset upload only when the file meets every limit in Table 4.2-1, and shall store each accepted file in the uploading user's own directory. A rejected file shall not be stored, and the user shall receive a message that states the reason (wrong type, too large, empty or malformed). The owner shall be able to delete their own datasets.	High	Test: TC-DATA-01, TC-DATA-02
MLE-F-004	For every accepted dataset the system shall display the first 20 rows and a profile that gives the row count, the column names, the inferred type of each column (numeric or categorical) and the number of missing values in each column. The profile values shall equal values computed independently from the file.	High	Test: TC-DATA-01
MLE-F-005	The system shall let the user choose one treatment for missing values per dataset (drop the rows; fill numeric columns with the mean or the median; fill categorical columns with the most frequent value) and shall one-hot encode categorical feature columns. Both steps shall be fitted on the training split only and then applied to the test split.	High	Test: planned, Sprint 1
MLE-F-006	The system shall let the user select the target column, the share of rows used for testing (10% to 50% in steps of 5%, default 20%) and an integer random seed (default 42), and shall create a stratified split. The system shall refuse a target column that does not meet the target rule in Table 4.2-1 and shall state the reason.	High	Test: TC-MODEL-01

4.3 Model selection and training

4.3.1 Description and priority

Lets a user choose a classification algorithm from a fixed catalogue, set its parameters, and train it on the prepared data as a background job.

Priority: High. It is the core of the evaluator.

Table 4.3-1: Model catalogue and permitted hyperparameters

Model	Hyperparameter and permitted range	Default
Logistic Regression	C: 0.01 to 100. max_iter: 100 to 1000.	C = 1.0, max_iter = 200
k-Nearest Neighbours	n_neighbors: 1 to 50. weights: uniform or distance.	n_neighbors = 5, uniform
Decision Tree	max_depth: 1 to 50 or no limit. min_samples_split: 2 to 20.	No depth limit, min_samples_split = 2
Random Forest	n_estimators: 10 to 200. max_depth: 1 to 50 or no limit.	n_estimators = 100, no depth limit

4.3.2 Stimulus/response sequences

- A user selects a model: the system shows its default parameters (Table 4.3-1).
- A user enters a parameter value outside the permitted range: the system refuses it and names the parameter and its range. Training does not start.
- A user starts training: the system queues the job and shows the status Queued, then Running, then Completed or Failed.
- A user who already has the maximum number of active jobs starts another one: the system refuses it and states the limit (MLE-SR-006).

4.3.3 Functional requirements

ID	Requirement	Priority	Verification
MLE-F-007	The system shall offer a catalogue of at least four classification algorithms (Logistic Regression, k-Nearest Neighbours, Decision Tree and Random Forest; Table 4.3-1) and shall let the user select exactly one per run. The catalogue is fixed: the system shall not accept a user-supplied model or algorithm.	High	Test: TC-MODEL-01
MLE-F-008	For the selected model the system shall let the user edit at least two hyperparameters within the ranges in Table 4.3-1 and shall refuse any value outside its range, before training starts, with a message that names the parameter and its permitted range.	Medium	Test: TC-MODEL-01
MLE-F-009	The system shall train the selected model on the training split as a background job, shall show the job status as Queued, Running, Completed or Failed, and shall store the trained model so that only the owning user can use it. The user interface shall stay usable while a job runs.	High	Test: TC-MODEL-01

4.4 Evaluation and explainability

4.4.1 Description and priority

Measures a trained model against the held-out test split and presents the result as numbers and charts.

Priority: High for metrics and charts (MLE-F-010, F-011); Medium for feature importance (MLE-F-012).

4.4.2 Stimulus/response sequences

- A user opens the results page of a completed run: the system shows accuracy, precision, recall, F1 and (where available) ROC-AUC.
- The user opens the charts: the system shows the confusion matrix and a bar chart of the metrics.
- The user opens feature importance: the system lists features by importance, or states that the chosen model does not provide it.

4.4.3 Functional requirements

ID	Requirement	Priority	Verification
MLE-F-010	For every completed run the system shall compute accuracy, precision, recall and F1-score on the test split (macro-averaged when the target has more than two classes) and ROC-AUC when the model provides probability estimates. Each value shall equal the scikit-learn reference value for the same split and seed within 0.001.	High	Test: TC-EVAL-01
MLE-F-011	For every completed run the system shall display a confusion matrix whose cell counts add up to the number of rows in the test split, and a bar chart of the metrics defined in MLE-F-010.	High	Test: TC-EVAL-01
MLE-F-012	For models that provide feature importance (Logistic Regression coefficients, Decision Tree and Random Forest importances) the system shall list every feature with its importance in descending order. For other models it shall state that feature importance is not available. SHAP explanations are optional and are not committed by this SRS.	Medium	Test: planned, Sprint 2

4.5 Experiment management and reporting

4.5.1 Description and priority

Keeps a record of every run so that results can be reviewed, compared and exported.

Priority: High for saving runs (MLE-F-013); Medium for comparison and export (MLE-F-014, F-015).

4.5.2 Stimulus/response sequences

- A run finishes (Completed or Failed): the system saves it automatically and lists it in the history, newest first.
- A user selects two to four runs on the same dataset and target and chooses Compare: the system shows their settings and metrics side by side.
- A user selects runs on different datasets: the system refuses and explains that only runs on the same dataset and target can be compared.
- A user chooses Export: the system downloads a CSV file with the settings and metrics of the selected run or comparison.

4.5.3 Functional requirements

ID	Requirement	Priority	Verification
MLE-F-013	The system shall save every run automatically with its owner, dataset, target column, split settings, model, parameters, status, metrics, start time and end time, and shall list the owner's runs newest first. A saved run shall be kept until its owner deletes it.	High	Test: TC-EXP-01
MLE-F-014	The system shall let the user select two to four of their own runs on the same dataset and target column and shall show their parameters and metrics side by side. The displayed values shall equal those on each run's own page. The system shall refuse a selection that mixes datasets or target columns and shall explain why.	Medium	Test: TC-EXP-01
MLE-F-015	The system shall export a run, or a comparison of runs, as a CSV file that contains the run settings and metrics. Any exported cell that begins with =, +, - or @ shall be neutralised so that a spreadsheet program does not evaluate it as a formula. PDF export is desirable but is not committed by this SRS.	Medium	Test: TC-DATA-02 (step 3); full export test planned, Sprint 2

4.6 Administration

4.6.1 Description and priority

Lets an Admin manage user accounts and stored datasets and review the audit log, without being able to read users' data.

Priority: High. Needed to manage accounts and to review the audit log required by MLE-SR-005.

4.6.2 Stimulus/response sequences

- An Admin opens user management: the system lists all accounts with role and status, and offers Change role and Deactivate or Reactivate for each.
- An Admin deletes a dataset: the system asks for confirmation, removes the file and its metadata, and writes an audit-log entry.

- An Admin opens the audit log: the system lists entries newest first with user ID, action and timestamp.
- A non-Admin requests any of these pages: the system refuses the request (MLE-F-002).

4.6.3 Functional requirements

ID	Requirement	Priority	Verification
MLE-F-016	The system shall let an Admin list all user accounts, change a user's role, deactivate and reactivate an account, list the metadata (name, owner, size and upload date) of all datasets, delete any dataset, and view the audit log defined in MLE-SR-005. The application shall not let an Admin view the contents of another user's dataset.	High	Test: TC-SEC-01

5. Non-functional requirements (detailed)

Non-functional requirements are identified as MLE-NF-nnn (quality and performance) and MLE-SR-nnn (security). Each states a measurable target and a verification method. Security comes first (section 5.1) because it carries the three security objectives referenced by SAD 3.9.

5.1 Security

The objectives and requirements below are aligned with the STRIDE threat model and the security architecture in SAD 3.9. Section 5.1.3 shows the mapping row by row.

5.1.1 Security objectives

ID	Objective	STRIDE threats addressed	Requirements that deliver it
MLE-SO-001 Confidentiality	Confidentiality of each user's datasets, models and results. Only the owner (and, for account and dataset management, an Admin) can read or change a user's data. Credentials, sessions and traffic are protected from disclosure.	Spoofing, Information disclosure, Elevation of privilege	MLE-SR-001, SR-002, SR-005(a), SR-007; MLE-F-002
MLE-SO-002 Integrity	Integrity of uploaded data, trained models and reported metrics. Uploaded files are validated before use, only artifacts created by the system are loaded, and every change is attributable to a user.	Tampering, Repudiation	MLE-SR-003, SR-004, SR-005(b)

ID	Objective	STRIDE threats addressed	Requirements that deliver it
MLE-SO-003 Availability	Availability of the service against abusive or oversized requests. Request size, request rate, concurrent jobs and job run time are bounded so that one user cannot exhaust the server.	Denial of service	MLE-SR-006

5.1.2 Security requirements

ID	Requirement	Objective	Threat	Verified by
MLE-SR-001	The system shall store passwords only as salted hashes created with PBKDF2 or bcrypt, and shall never display or log a password.	Confidentiality	Spoofing	Test: TC-AUTH-01 (step 5); inspection
MLE-SR-002	On the deployed build, all traffic between browser and server shall use HTTPS with TLS 1.2 or higher. Plain HTTP requests shall be redirected to HTTPS or refused, and TLS 1.0 and 1.1 shall be refused. (Local development builds are exempt.)	Confidentiality	Information disclosure	Test: SV-02 (TLS scan of the deployed build)
MLE-SR-003	The system shall accept an upload only when its extension is .csv, its declared MIME type is text/csv or text/plain, its size is within Table 4.2-1, and its content parses as a CSV file with a consistent number of columns. Uploaded content shall never be executed or deserialised, and rejected uploads shall not be stored.	Integrity	Tampering	Test: TC-DATA-02
MLE-SR-004	The system shall load only model artifacts that it created itself, shall not accept an uploaded model file through any page or endpoint, and shall store artifacts in per-user directories outside the web root, so that no artifact can be requested by a URL.	Integrity	Tampering, Elevation of privilege	Test: SV-04; code inspection
MLE-SR-005	(a) Every read, change or delete of a dataset, run or artifact shall first check that the requester owns it (or is an Admin where MLE-F-016 allows), and shall otherwise return a generic 403 or 404 response that does not reveal whether the item exists. (b) The system shall write an audit-log entry with user ID, timestamp and action for every login (successful and failed), upload, training, deletion and Admin action. The log shall contain no raw dataset values and no credentials.	Confidentiality, Integrity	Information disclosure, Repudiation	Test: TC-SEC-01

ID	Requirement	Objective	Threat	Verified by
MLE-SR-006 (new)	The system shall (a) reject a request body larger than 10 MB with HTTP 413; (b) allow at most 120 requests per minute per authenticated user, and per IP address for anonymous requests, and answer any excess with HTTP 429; (c) allow each user at most 2 queued or running training jobs (1 for the Student role) and refuse further jobs with a message; and (d) stop any training job that runs longer than 300 seconds and set the run to Failed with the reason "time-out".	Availability	Denial of service	Test: SV-06
MLE-SR-007 (new)	The system shall (a) end a session after 30 minutes of inactivity; (b) mark session cookies HttpOnly, and Secure on HTTPS deployments; (c) block login for an account for 15 minutes after 5 consecutive failed logins within 10 minutes; and (d) refuse, with HTTP 403, every state-changing request (POST, PUT, PATCH, DELETE) that does not carry a valid CSRF token.	Confidentiality	Spoofing	Test: TC-AUTH-01 (cookie flag), SV-07, SV-08

5.1.3 Mapping to the SAD 3.9 threat model

STRIDE threat (SAD 3.9)	Mitigation named in SAD 3.9	SRS requirement
Spoofing	Hashed passwords, session expiry, login throttling, secure and HttpOnly cookies	MLE-SR-001, MLE-SR-007
Tampering	File type, size and content validation; artifacts outside the web root; load only system-generated artifacts; no unpickling of user files	MLE-SR-003, MLE-SR-004
Repudiation	Audit log of logins, uploads, trainings, deletions and admin actions with user ID and timestamp	MLE-SR-005(b)
Information disclosure	Ownership check on every query and file path; HTTPS (TLS 1.2+); generic error messages; no raw data in logs	MLE-SR-002, MLE-SR-005(a)
Denial of service	Upload size limit, row and column limits, rate limiting, per-user job quota, training time-out	MLE-SR-006; row and column limits in MLE-F-003 (Table 4.2-1)
Elevation of privilege	Role-based access control on every view and endpoint; admin routes separated; deny by default	MLE-F-002 (also MLE-F-016, MLE-SR-004)

5.2 Performance requirements

Rationale: Students and data scientists work interactively, so the limits keep waiting time short at the supported dataset sizes. All timings are taken on one fixed reference test machine, whose specification is recorded in the Test Plan (section 6).

ID	Requirement	Priority	Verification
MLE-NF-001	For a valid CSV file of up to 10 MB, the time from submitting the upload until the dataset profile is displayed shall be 5 seconds or less in each of five consecutive runs, on the reference test machine with one active user.	High	Test: TC-PERF-01
MLE-NF-002	Training any catalogue model with its default parameters on a dataset of up to 50,000 rows and 20 feature columns shall complete in 60 seconds or less, and the dashboard shall stay responsive while the job runs.	High	Test: TC-PERF-02
MLE-NF-003	With 20 concurrent logged-in users, every application page shall load in 3 seconds or less, for both the average and the 95th percentile, over a run of 5 minutes, and the run shall produce no server errors (HTTP 5xx).	Medium	Test: TC-PERF-03

5.3 Reliability requirements

Rationale: Training depends on user-supplied data, so failures are expected. They must not affect other users or lose saved results.

ID	Requirement	Priority	Verification
MLE-NF-006 (new)	When a training job fails (invalid data, time-out or internal error), the system shall set the run to Failed with a plain-language reason, shall store no partial model, and shall stay available to other users. Users, datasets and runs saved before a server restart shall all be present after it.	Medium	Test: fault-injection test and restart test (planned, Sprint 2)

5.4 Scalability requirements

Rationale: The history and dataset lists grow with every experiment and must stay fast.

ID	Requirement	Priority	Verification
MLE-NF-007 (new)	The system shall support at least 20 stored datasets and 100 stored runs per user and shall keep the page-load limit of MLE-NF-003 for the history and dataset lists, which shall be paginated at 20 items per page.	Low	Test: load test with seeded data (planned, Sprint 2)

5.5 Portability requirements

Rationale: Team members develop on different operating systems. Docker gives one reproducible environment (SAD 3.6).

ID	Requirement	Priority	Verification
MLE-NF-004	The system shall build and start from the repository with Docker on Windows, Linux and macOS using one documented command, and its pages shall work in the current versions of Google Chrome and Mozilla Firefox.	Medium	Test: build and smoke test on each OS (planned, Sprint 2)

5.6 Usability requirements

Rationale: The Student user class has limited machine-learning experience (SRS 2.3), so the interface must guide them.

ID	Requirement	Priority	Verification
MLE-NF-005	A first-time user with no training shall be able to log in, upload a dataset, train a model and view its metrics within 10 minutes without help. In a test with five first-time users, at least four shall succeed. Every error message shall use plain language and state what the user can do next.	Medium	Test: usability test with five first-time users (planned, Sprint 2)

6. Quality attributes and acceptance tests

6.1 Relative priority of quality attributes

Rank	Quality attribute	Basis
1	Security and data protection	Datasets belong to users. Objectives MLE-SO-001 to 003 (section 5.1.1).
2	Correctness of results	Displayed metrics equal the reference values within 0.001 (MLE-F-010).
3	Usability	The Student class needs clear guidance (MLE-NF-005).
4	Performance	MLE-NF-001 to 003.
5	Maintainability and testability	Layered, modular design (SAD 3.5); unit-test coverage of 70% or more for service modules (Test Plan section 14); static analysis in the CI pipeline.
6	Portability	MLE-NF-004.

6.2 Acceptance criteria

The system is accepted when each scenario below is met. The test cases are defined in the Test Plan (Appendix A) and the security checks in Test Plan section 5.1.

ID	Scenario	Accepted when	Requirements	Tests
AC-1	A Data Scientist logs in, uploads a valid CSV, sets the split, trains a model, views the metrics and finds the run in the history.	Every step completes without error; displayed metrics match the reference within 0.001.	MLE-F-001, F-003, F-004, F-006 to F-011, F-013	TC-AUTH-01, TC-DATA-01, TC-MODEL-01, TC-EVAL-01, TC-EXP-01
AC-2	Invalid files and out-of-range parameters are submitted.	All are refused with a clear message and nothing is stored.	MLE-F-003, F-008, SR-003	TC-DATA-02, TC-MODEL-01
AC-3	A Student tries to read another user's data and to open admin pages.	Access is denied and the attempts appear in the audit log.	MLE-F-002, F-016, SR-005	TC-SEC-01
AC-4	Upload, training and page-load timings are measured.	All three thresholds are met.	MLE-NF-001 to 003	TC-PERF-01 to 03
AC-5	The security checks are run on the deployed build.	SV-01 to SV-10 pass and no High alert is open.	MLE-SR-001 to 007	Test Plan 5.1

7. UML use-case diagrams

Two diagrams are given: one for the User (a Student or a Data Scientist, who have the same use cases) and one for the Administrator. Each use case has an ID that is traced to requirements in Table 7-1 and in the traceability matrix (section 8).

7.1 User use cases




Figure 7-1: Use case diagram for the Student and Data Scientist roles

7.2 Administrator use cases




Figure 7-2: Use case diagram for the Administrator role

7.3 Use case summary

Table 7-1: Use cases and the requirements they realise

ID	Use case	Actor	Requirements
UC-01	Register account	User	MLE-F-001
UC-02	Log in / log out	User, Administrator	MLE-F-001, F-002, SR-001, SR-007
UC-03	Upload CSV dataset	User	MLE-F-003, SR-003
UC-04	Preview and profile dataset	User	MLE-F-004
UC-05	Prepare data	User	MLE-F-005
UC-06	Configure train/test split	User	MLE-F-006
UC-07	Select model and set hyperparameters	User	MLE-F-007, F-008
UC-08	Train model	User	MLE-F-009, SR-006
UC-09	View metrics and confusion matrix	User	MLE-F-010, F-011
UC-10	View feature importance	User	MLE-F-012
UC-11	Export report	User	MLE-F-015

ID	Use case	Actor	Requirements
UC-12	View run history	User	MLE-F-013
UC-13	Compare runs	User	MLE-F-014
UC-14	Manage user accounts	Administrator	MLE-F-016
UC-14a	Change user role	Administrator	MLE-F-016
UC-14b	Deactivate / reactivate account	Administrator	MLE-F-016
UC-15	Manage datasets	Administrator	MLE-F-016
UC-15a	Delete dataset	Administrator	MLE-F-016, SR-005
UC-16	View audit log	Administrator	MLE-F-016, SR-005

8. Requirements Traceability Matrix (RTM)

Each requirement is traced forward to a use case, an architecture component (SAD 3.4), a design reference (SAD 3.8) and a test case or security check. Code file references are completed during implementation, as pull requests are merged. Test case IDs are those in Test Plan Appendix A; SV-nn are the security checks in Test Plan section 5.1. Test Plan section 13 shows the same mapping from the test side.

Req ID	Requirement (short)	Use case	Architecture component	Design reference	Code file	Test case(s) / check
MLE-F-001	User registration and login	UC-01, UC-02	Auth & Access Control	DS-Auth-01 (SAD 4.2 login sequence)	TBD	TC-AUTH-01
MLE-F-002	Role-based access (Data Scientist, Student, Admin)	UC-02 (all use cases)	Auth & Access Control	DS-Auth-02	TBD	TC-SEC-01
MLE-F-003	Upload CSV dataset with validation	UC-03	Data Workspace, File Store	DS-Data-01 (SAD 4.2 upload sequence, /api/upload)	TBD	TC-DATA-01, TC-DATA-02
MLE-F-004	Preview and profile the dataset	UC-04	Data Workspace	DS-Data-02	TBD	TC-DATA-01
MLE-F-005	Handle missing values and encode categories	UC-05	Data Workspace	DS-Data-03	TBD	Planned (Sprint 1)
MLE-F-006	Configure target column and train/test split	UC-06	Data Workspace	DS-Data-04	TBD	TC-MODEL-01
MLE-F-007	Select a model from the catalogue	UC-07	Model Selection & Training	DS-Model-01	TBD	TC-MODEL-01
MLE-F-008	Configure hyperparameters	UC-07	Model Selection & Training	DS-Model-02	TBD	TC-MODEL-01
MLE-F-009	Train a model and show status	UC-08	Model Selection & Training	DS-Model-03 (/api/train)	TBD	TC-MODEL-01
MLE-F-010	Compute accuracy, precision, recall, F1	UC-09	Evaluation & Explainability	DS-Eval-01 (/api/evaluate)	TBD	TC-EVAL-01
MLE-F-011	Show confusion matrix and plots	UC-09	Evaluation & Explainability, Web UI	DS-Eval-02	TBD	TC-EVAL-01
MLE-F-012	Feature importance / explanation	UC-10	Evaluation & Explainability	DS-Eval-03	TBD	Planned (Sprint 2)
MLE-F-013	Save each run (history)	UC-12	Experiment Mgmt & Reporting, Relational DB	DS-Exp-01	TBD	TC-EXP-01

Req ID	Requirement (short)	Use case	Architecture component	Design reference	Code file	Test case(s) / check
MLE-F-014	Compare runs side by side	UC-13	Experiment Mgmt & Reporting	DS-Exp-02	TBD	TC-EXP-01
MLE-F-015	Export results report	UC-11	Experiment Mgmt & Reporting	DS-Exp-03	TBD	TC-DATA-02 (step 3) (planned, Sprint 2)
MLE-F-016	Admin manages users and datasets	UC-14, UC-14a, UC-14b, UC-15, UC-15a, UC-16	Auth & Access Control, Web UI	DS-Admin-01	TBD	TC-SEC-01
MLE-NF-001	Upload of up to 10 MB processed in 5 s or less	-	Data Workspace	Performance budget in SAD 3.7 (R1)	TBD	TC-PERF-01
MLE-NF-002	Training of standard models on up to 50,000 rows in 60 s or less	-	Model Selection & Training	Background job design (SAD 3.6)	TBD	TC-PERF-02
MLE-NF-003	Pages load in 3 s or less for 20 concurrent users	-	API Gateway, Web UI	Layered stateless API (SAD 3.5)	TBD	TC-PERF-03
MLE-NF-004	Runs on Windows, Linux and macOS via Docker	-	Packaging / Deployment	SAD 3.6 (Docker)	TBD	Planned (Sprint 2)
MLE-NF-005	Usable by a first-time user without training	-	Web UI	SAD 4.5 UX Design	TBD	Planned (Sprint 2)
MLE-NF-006 (new)	Failed jobs are contained; saved data survives restart	-	Model Selection & Training, Relational DB	Background job design (SAD 3.6, 3.7 R1)	TBD	Planned (Sprint 2)
MLE-NF-007 (new)	Keeps page-load limits with 20 datasets and 100 runs per user	-	Experiment Mgmt & Reporting, Relational DB	TBD (SAD 4.x)	TBD	Planned (Sprint 2)
MLE-SR-001	Passwords stored hashed	-	Auth & Access Control	SAD 3.9 Spoofing	TBD	TC-AUTH-01, SV-01
MLE-SR-002	All traffic over HTTPS (TLS 1.2+)	-	Deployment / Gateway	SAD 3.9 Information disclosure	TBD	SV-02 (planned, Sprint 2)
MLE-SR-003	Uploads validated for type, size and content	-	Input Validation & Security Controls	SAD 3.9 Tampering	TBD	TC-DATA-02, SV-03
MLE-SR-004	Only system-created model artifacts are loaded	-	Model Selection & Training	SAD 3.9 Tampering / EoP	TBD	SV-04 (planned, Sprint 2)

Req ID	Requirement (short)	Use case	Architecture component	Design reference	Code file	Test case(s) / check
MLE-SR-005	Per-user data isolation and audit log of actions	UC-16	Auth, Logging & Audit	SAD 3.9 Repudiation, Information disclosure	TBD	TC-SEC-01, SV-05
MLE-SR-006 (new)	Request, job and run-time limits against abuse	-	Input Validation & Security Controls, API Gateway, Model Selection & Training	SAD 3.9 Denial of service	TBD	SV-06 (planned, Sprint 2)
MLE-SR-007 (new)	Session expiry, login throttling and CSRF protection	-	Auth & Access Control, Input Validation & Security Controls	SAD 3.9 Spoofing	TBD	TC-AUTH-01 (cookie flag only), SV-07, SV-08 (planned, Sprint 2)

Totals: 16 functional requirements, 7 non-functional requirements (3 performance, 1 portability, 1 usability, 1 reliability, 1 scalability), 7 security requirements and 3 security objectives (section 5.1.1).