

Release Secret Preflight

External readiness blockers, evidence, and controlled resume conditions

PLATFORM PROGRESS BLOCKER REPORT

Prepared 2026-08-10

Evidence-bound | secret-safe | approval-gated | resumable

No readiness claim without target-observed evidence.

Generated: 2026-08-10T13:32:13.269Z Mode: report Status: blocked

Summary

- 1 Checks ready: 5/21
- 1 Release enforcement: on
- 1 Blockers: 16
- 1 Warnings: 0
- 1 Secret value printed: no

Checks

blocked	public_identity_secret_present	PUBLIC_IDENTITY_ABUSE_HASH_SECRET	Configure the dedicated public-identity HMAC secret in the production environment.
blocked	public_identity_secret_strong	PUBLIC_IDENTITY_ABUSE_HASH_SECRET	Use a random secret with at least 32 characters and 12 distinct characters.
blocked	public_receipt_secret_present	AQSTOQFLOW_RECEIPT_TOKEN_SECRET	Configure the dedicated public-receipt signing secret in the production environment.
blocked	public_receipt_secret_strong	AQSTOQFLOW_RECEIPT_TOKEN_SECRET	Use a random secret with at least 32 characters and 12 distinct characters.
blocked	history_cursor_secret_present	AQSTOQFLOW_HISTORY_CURSOR_SECRET	Configure the dedicated transaction-history cursor signing secret in the production environment.
blocked	history_cursor_secret_strong	AQSTOQFLOW_HISTORY_CURSOR_SECRET	Use a random, purpose-specific secret that meets the release strength policy.
blocked	statement_token_secret_present	AQSTOQFLOW_STATEMENT_TOKEN_SECRET	Configure the dedicated customer-statement signing secret in production.
blocked	statement_token_secret_strong	AQSTOQFLOW_STATEMENT_TOKEN_SECRET	Use a strong, random, purpose-specific statement signing secret.
blocked	statement_delivery_encryption_key_present	AQSTOQFLOW_STATEMENT_DELIVERY_ENCRYPTION_KEY	Configure the AES-256 key used to seal statement delivery envelopes.
blocked	statement_delivery_encryption_key_valid	AQSTOQFLOW_STATEMENT_DELIVERY_ENCRYPTION_KEY	Use exactly 32 random bytes encoded as base64 or 64 hexadecimal characters.
blocked	accountant_invite_encryption_key_present	AQSTOQFLOW_ACCOUNTANT_INVITE_ENCRYPTION_KEY	Configure the AES-256 key used to seal accountant invitation envelopes.
blocked	accountant_invite_encryption_key_valid	AQSTOQFLOW_ACCOUNTANT_INVITE_ENCRYPTION_KEY	Use exactly 32 random bytes encoded as base64 or 64 hexadecimal characters.
blocked	public_app_url_present	NEXT_PUBLIC_BASE_URL	Configure the canonical public application URL used in signed referral links.
blocked	public_app_url_https	NEXT_PUBLIC_BASE_URL	Use a valid HTTPS origin for production referral links.
blocked	statement_live_delivery_channel_enabled	n/a	Enable at least one live customer-statement channel: email or WhatsApp.
ready	statement_email_provider_configured	RESEND_API_KEY	When statement email sends are enabled, configure RESEND_API_KEY and RESEND_FROM_EMAIL.
ready	statement_whatsapp_provider_configured	WHATSAPP_ACCESS_TOKEN	When statement WhatsApp sends are enabled, configure WHATSAPP_PHONE_NUMBER_ID and WHATSAPP_ACCESS_TOKEN.

blocked	accountant_invite_live_delivery_enabled	STOQUIFY_ACCOUNTANT_INVITE_LIVE_SENDS	Enable live accountant invitation delivery for production onboarding.
ready	accountant_invite_provider_configured	RESEND_API_KEY	When accountant invitation sends are enabled, configure RESEND_API_KEY and an accountant or default Resend sender.
ready	dedicated_secrets_are_distinct	n/a	Use separate random values for every signing, hashing, cursor, and envelope-encryption boundary.
ready	dedicated_secrets_are_not_auth_secrets	n/a	Do not reuse AUTH_SECRET or NEXTAUTH_SECRET for any dedicated boundary secret.

Safety

- 1 This preflight reads secret values only from the process environment.
- 1 It never writes, hashes, serializes, or prints secret values.
- 1 Local and preview environments report missing production secrets without blocking; release mode fails closed.