Point of sale and cash accountability

Evidence: source reviewed 2026-09-06. Dashboard interaction is blocked by sign-in. Instructions below describe implementation, not a completed live walkthrough.

The current checkout exposes cash tender and no receipt delivery. Opening a shift, editing a cart, charging a sale and closing a shift all persist state. The cash drawer workspace helps reconcile the resulting physical-cash evidence.

Pages in this chapter

- /en/dashboard/cashDrawer
- Cash drawer management
- Point of sale

Redirect: /cashDrawer

Open: /en/dashboard/cashDrawer. **Reach it:** Direct/contextual link; no exact sidebar entry. **Evidence state:** redirect; runtime blocked.

This route redirects after its access checks. Use /en/dashboard/finance/cash-drawer and the canonical guide.

Access: finance.cash-drawer.read OR finance.read. The destination performs its own checks.

Evidence: app/[locale]/(dashboard)/dashboard/cashDrawer/page.tsx:1.

Cash drawer management

Open: /en/dashboard/finance/cash-drawer. **Reach it:** Cash Drawer. **Evidence state:** source-only; runtime blocked.

Audience. Cashiers, store managers and cash-control staff.

Prerequisites and access. finance.cash-drawer.read OR finance.read. An accessible location and relevant cash-drawer/session read authority. Viewing evidence does not require an active shift or sellable stock.

What it shows. Overview, Drawers, Movement, Sessions and Journal views, with location/date filters, balances, sessions and variance information.

How to use it.

1. Choose location/dates and Refresh.
2. Search sessions by cashier/terminal and sort by Time, Sales or Variance.
3. Expand session/journal details, then follow Open POS, Reconciliation, Manage terminals, Cash flow or Cash and payment history to the owning workflow.

Confirm the outcome. Check the refreshed session/drawer/variance evidence. Charge and Close take place through the separate POS workflow.

Get value from it. Use unexplained variance to identify the specific shift requiring a count/evidence review.

Limits and recovery. A cash drawer is physical cash accountability; it is not a bank balance. A current balance and a dated session total can have different time bases. A failed close retains inputs for correction. Inspect current session/order state before repeating a submission; hardware readiness labels alone do not prove a device is connected. Shared recovery guidance covers empty, denied, stale and failed states.

Connections. Workflows · Role routines · Control evidence · Technical notes.

Page source · Access definition.

Point of sale

Open: /en/dashboard/pos. **Reach it:** POS. **Evidence state:** partial; runtime blocked.

Audience. Cashiers, store managers and cash-control staff.

Prerequisites and access. OPERATE_POS. Accessible location, configured available terminal, assigned cashier/drawer as applicable, active shift and stock eligible for sale. Server permissions and current session state govern actions.

What it shows. Location/terminal setup, shift state, customer, catalog in grid/list form, cart quantities/totals, cash tender, receipt history controls and offline-sync status.

How to use it.

1. Choose location and terminal, open a shift with the actual Opening float, then scan barcode or search SKU/item/category.
2. Add items, confirm quantities and customer, enter the cash tender and review the sale before committing.
3. At shift end enter Counted cash and a Variance explanation when required; close the shift and inspect the session record.

Confirm the outcome. After Charge, inspect order number, total/change and returned posting evidence. After Close, confirm the session closed and the counted cash/variance persisted.

Get value from it. Tie each sale to stock, a cashier session and accountable payment evidence.

Limits and recovery. The current selectable tender/receipt arrays expose CASH and NONE only: cash checkout with no delivery receipt. Electronic tender and email/SMS/WhatsApp branches exist in source but are not offered by this configuration. Park sale and Manager override only show a backend-gated warning. Do not describe those as working sale-management actions. A failed close retains inputs for correction. Inspect current session/order state before repeating a submission; hardware readiness labels alone do not prove a device is connected. Shared recovery guidance covers empty, denied, stale and failed states.

Connections. Workflows · Role routines · Control evidence · Technical notes.

Page source · Access definition.