POS workflow and architecture

The full current-source trace, support classifications, persona-permission mapping, graph node references, and every reviewer disposition are in architecture review. Route inventory enumerates 13 localized page patterns / 26 English and French targets, plus receipt/media APIs. A new public receipt page is reviewed separately during this run.

```
flowchart LR
  UI[Cashier / manager interface] --> H[Scoped hooks and checkout lifecycle]
  H --> A[Authenticated actions]
  A --> S[POS domain services]
  S --> TX[Database transaction]
  TX --> SO[Sale and payment records]
  TX --> ST[Stock and valuation events]
  TX --> CD[Shift and drawer evidence]
  TX --> LE[Ledger and source links]
  TX --> RR[Durable request/result registry]
  S --> PC[After-commit receipt and cache work]
  RR --> REC[Check / review / recover]
  SO --> READ[Reports, reconciliation and close]
  CD --> READ
  LE --> READ
```

Operational journeys

Journey / actor	Prerequisites and authority	Approval / effect / outcome	Failure and recovery
Configure terminal / authorized manager	Organization/location and `pos.session.start`; revision-aware service	Create/update/archive configuration; audit preserved	Active shift/drawer, historical location movement or stale revision rejects unsafe edits.
Open shift / cashier	Active terminal, permission and module admission, opening balance	Server binds actor, terminal, session and opening drawer event	Existing active session or mismatched location is rejected.
Browse/scan/cart / cashier	Current location and lease; server catalog and stock	Server prices/taxes, add/update/remove draft lines	Keep failed input; resume after stale price/stock changes. No cashier arbitrary-price/discount setter verified.
Select customer / cashier	Scoped compatible active customer	Walk-in or identified sale association	Location mismatch rejected. Credit display does not make on-account checkout available.
Tender / cashier	Reviewed cart, valid cash amounts	Exact cash, cash splits, change and due previews; authoritative commit totals	Short/invalid tender blocks Charge with explanation. Current cashier method list is CASH.
Submit/recover / cashier	Durable request identity, revision and verified ownership	Atomic sale and integration evidence; registry records outcome	Duplicate, late/lost response and changed-cart paths preserve request and evidence.

Journey / actor	Prerequisites and authority	Approval / effect / outcome	Failure and recovery
Park/resume / cashier	Current ownership, no incompatible pending/offline state	Service changes active/parked cart with revalidation	No assumed cross-cashier transfer or manual lock override.
Receipt / cashier, customer, authorized revoker	Recorded sale; scoped management access or registered public bearer token	Safe receipt presentation, print from browser, revocation/history	Delivery failure does not undo sale. Checkout still exposes NONE; unsupported provider channels remain unavailable.
Refund/void / specifically authorized operator	Actual refund/void permission and fresh authentication; supported payment rail	Compensating stock, ledger, payment and drawer records	No complete cashier refund/partial-return UI verified. Unsupported provider reversal must fail without changing recorded money.
Count/close / session operator	Counted balance, variance reason if needed; no unresolved offline/recovery blocker	Close evidence, drawer journal and Z-report/accounting linkage	Concurrency and evidence failure must roll back; closed shift cannot reopen.
Offline review / controls-authorized manager	Scoped enrolled device/queue/policy/hash-chain evidence	Review/acknowledge or supported resolution with audit	No complete cashier enrollment/capture/flush UI verified; provisional capture is not a posted sale.
Finance/audit/support	Assigned read/export/reconciliation/close capabilities	Source-linked history, settlement, stock-to-cash and close reports	Same-scope errors are explicit; no previous tenant's drawer report displayed.

Domain boundaries and product limits

Purchasing/AP enters through upstream stock/valuation and downstream snapshots; HR/payroll has no direct POS mutation dependency. No AI model authorizes or executes POS payments in the inspected path. Country rules and statutory certification remain expert-reviewed external prerequisites, not labels inferred from a successful test.

The design preserves service-owned rules and existing contracts. The focused structural changes address ownership sequencing, scoped reads, after-commit cache handling and receipt presentation rather than replacing the framework or reformatting unrelated code.

Verified environment and journey scope

The required `ledger_posting_batches.postingCycle` schema is now present on the specifically authorized local application database `stoquify_replay_next_20260830`. The application migration result verifies its column/default, validated check, replacement unique index, preserved unrelated schema and matching migration history. This resolves that environment prerequisite without establishing a new sale outcome.

The accountant's French drawer journey has browser evidence for completed rendering, a location filter narrowing 13 drawers to one, a localized no-session state, keyboard period selection of “7 derniers jours”, session expansion and links retaining `/fr`. The expanded open session now distinguishes its unavailable final balance from a recorded numeric balance. English drawer rendering was also observed. These were read-only observations at the available viewport; the authorized cashier journey, broader responsive coverage and

hardware workflows are not implied. See the browser follow-up and verification matrix for the current account-handoff and source-validation limits.