Evidence index

All paths below are local artifacts. Failed originals remain evidence of the defect, not a failed final implementation. Historical POS financial/browser results stay in the prior run and are not counted as fresh execution.

Evidence	Scope/result
Inventory after / exit	Fail mode, 0 active
Inventory guard/tests	3 suites, 38 passes; mock/VM clients, no real DB execution
Inventory original failures	Two expected pre-edit scanner failures
G1 after	Expected exit 1, missing authentic approvals
Program after	Expected exit 1, dependency/external/closure requirements
Governance verification	45 tests, scoped lint, source hashes, unchanged business artifacts
Governance original failures	Five demonstrated original false passes
Build wrapper first red	Five original isolated-output regressions
Parent-link red	Independent review finding reproduced
Final wrapper tests / exits	23 pass, scoped lint clean
Typecheck / log	Final edited source after configuration restoration; exit 0
Prisma validation	Exit 0, no migration
Build log / start	**FAILED**, wrapper exit 1, child exit 1; output cleanup disabled/not performed
Packet provenance	11 decisions, nine procedures, exact frozen hash
Final source hashes	Changed-scope inventory/governance/build files and verified-source drift

Execution brief: requested scope. Git baseline and HEAD were recorded before edits. The initial default Jest discovery runs produced no results and were stopped; focused Node configurations supplied the actual test evidence. Initial filesystem-denied writes did not execute. The fixture-manifest auto-review rejection was resolved through the same mechanism after individual evidence was completed; no remaining permission block exists.