Stoquify Workflow Atlas — 2026-08-03

Purpose

This atlas traces representative current-source workflows from user surface to durable truth and back to UI. It distinguishes implemented flow, strong controls, and unresolved authority/recovery gaps. It does not claim exhaustive runtime execution.

Workflow family summary

Family	Entry → owner → durable truth	Happy path	Failure/correction path	Assessment
Identity/tenant	Auth/settings → user/organization services → identity models/audit	Register/invite/session/membership/role	denial, expiry, recovery, offboarding	Partial; plaintext invite, MFA, audit durability, DB tenant backstop
POS	POS UI → tender action → POS service transaction → sale/stock/drawer/payment/ledger/event/receipt	Strong atomic sale composition	refund/void/offline/fiscalization	Strong core; provider finality and balance concurrency dangerous
Inventory	Inventory workbench → stock/count/transfer services → levels/movements/events/ledger	CAS-protected movement and proof	reversal, blocker, replay, reconciliation	Strong
Purchasing	PO UI → action → PO service → order/approval/receipt/event	Maker-checker approval and receipt	cancel, rejection, duplicate/concurrent approval	Strong; approval CAS residual
AP	Payables UI → AP action/service → invoice/match/approval/payment/reconciliation	Three-way match and segregated release	exception, suspense, correction	Strong; active-exception race
Payments/recon	Provider/statement input → payment/recon services → events/statements/matches/suspense/certification	Verify, ingest, match, sign	duplicate, missing evidence, suspense, retry	Strong independently; not POS final authority
Accounting/close	Source event/action → posting/close services → batches/journals/source links/evidence	Balanced posting and close checks	reversal, stale evidence, blocked close	Strong; upstream/provider/statutory dependencies
HR/payroll	People/payroll UI → HR/payroll services → employee/run/payment/declaration/evidence	Readiness, run, approval, release, declare, reconcile	correction, provider retry, exception, close blocker	Strong design; external/statutory proof blocked
Public receipt	Public route/token → receipt service/registry → redacted receipt	Verify signed/hashed token and serve	expiry, revocation, invalid scope	Strongest public boundary
Assurance/agents	Protected action/scheduler → assurance/agent services → proposals/incidents/outbox	Detect, propose, review, evidence	retry, reject, recover, kill switch	Strong static contracts; runtime operations unproven

POS sale, provider, receipt, and refund

```
sequenceDiagram
  actor Cashier
  participant UI as POS UI / TanStack
  participant Action as tender.actions
  participant POS as commitPOSSale
  participant DB as Prisma transaction
  participant Acct as Accounting posting
  participant Event as Business event/outbox
  participant Provider as Provider/reconciliation
  participant Receipt as Receipt delivery

  Cashier->>UI: complete cart and submit tenders
  UI->>Action: server action with tenant/session/location
  Action->>POS: authenticated module-scoped command
  POS->>POS: reject STORE_CREDIT; validate references
  POS->>DB: claim session/sale; stock, drawer, payment, customer
  POS->>Acct: sale/payment postings
  POS->>Event: finalized sale + fiscalization request
  DB-->>POS: commit
  POS->>Receipt: load and deliver receipt
  Receipt-->>UI: redacted receipt/result
  Note over POS,Provider: Non-cash payment is currently marked PAID before provider-authoritative
finality
  Provider-->>DB: separate signed event/statement/reconciliation evidence
```

Strong controls: tenant/location/session predicates, sale claim, transactional stock/payment/ledger/evidence composition, unique local references, receipt token controls, pending non-authoritative fiscalization watermark.

Gaps:

- Electronic references are derived from tender input and persisted as final payment.
- Signed provider evidence is not the transition authority.
- Customer/drawer balances use read-compute-write.
- Non-cash refunds become processed without provider refund execution.
- Store credit is safely disabled, not implemented.

Required correction path:

`PROVISIONAL → AUTHORIZED → CAPTURED → SETTLED`, with `FAILED/EXPIRED/REVERSED`, clearing/suspense posting, idempotent provider commands, reconciliation, and evidence-preserving refunds.

Offline POS replay

```
flowchart TD
  D["Registered device/session"] --> I["Ingest signed/hashed offline batch"]
  I --> V{"Sequence/hash/idempotency valid?"}
  V -- no --> Q["Quarantine/conflict evidence"]
  V -- yes --> A["Accepted offline event"]
  A --> R["Replay worker/current operator"]
  R --> C["Canonical POS commit"]
  C --> P["Proof, receipt, event, reconciliation"]
```

Strong controls: device/session/location claims, sequence hash, idempotency, quarantine, canonical POS execution, assurance checks.

Gap: original actor is not immutable per event and replay uses the current replayer; offline action entitlement is incomplete. Record original actor and replayer separately and require explicit replay authority.

Inventory movement and reversal

```
flowchart LR
  U["Inventory role"] --> A["Protected action"]
  A --> S["Stock/count/transfer service"]
  S --> O{"Open period and valid stock?"}
  O -- no --> B["Blocker/exception evidence"]
  O -- yes --> CAS["Quantity/version CAS"]
  CAS --> M["Movement and valuation"]
  M --> E["Business event / close invalidation"]
  E --> R["Read model and reconciliation"]
  M --> REV["Linked reversal/correction"]
```

Assessment: one of the strongest domain implementations. Preserve CAS, immutable movement evidence, reversal lineage, event idempotency, and close invalidation. Add real concurrency and tenant-boundary proof.

Purchase order and AP

```
sequenceDiagram
  actor Maker
  actor Checker
  participant PO as Purchase-order service
  participant Inv as Inventory receipt
  participant AP as AP control service
  participant Acct as Accounting
  participant Pay as Payment/reconciliation

  Maker->>PO: create and submit order
  Checker->>PO: canonical approval
  PO->>PO: reject self-approval and bulk APPROVED
  PO->>Inv: receive goods and stock evidence
  Maker->>AP: create invoice and three-way match
  Checker->>AP: approve invoice/payment destination
  AP->>Acct: post payable/payment evidence
  AP->>Pay: release pending transaction
  Pay-->>AP: statement/reconciliation proof or exception
```

Resolved: generic bulk approval bypass.

Residual:

- PO approval lacks status/version CAS inside the transaction.
- AP active exception creation is find-then-create without a uniqueness invariant.
- Provider/statement truth remains externally unverified.

Payment reconciliation and suspense

```
stateDiagram-v2
  [*] --> Ingested
  Ingested --> Verified: signature/schema/replay checks pass
  Ingested --> Rejected: invalid or duplicate evidence
  Verified --> Matched
  Verified --> Suspense: missing/duplicate/mismatch
  Suspense --> Proposed
  Proposed --> Posted: independent checker + ledger proof
  Proposed --> Rejected
  Matched --> Certified: no open exceptions/suspense
  Posted --> Certified
```

Strengths: HMAC verification, constant-time comparison, provider inbox, statement imports, duplicate/missing evidence detection, suspense maker-checker, ledger link, certification blockers.

Gaps: CSV parsing robustness, explicit timestamp contract, encrypted/redacted raw payload retention, runtime provider proof, POS integration.

Accounting and close

```
flowchart TD
  SRC["Sale, payment, AP, payroll, adjustment"] --> B["Posting batch"]
  B --> V{"Balanced, open period, same tenant, idempotent?"}
  V -- no --> X["Typed failure / visible blocker"]
  V -- yes --> J["Journal and source link"]
  J --> D["Data-trust checks"]
  D --> C{"Evidence current and reconciled?"}
  C -- no --> BL["Close blocked / stale evidence"]
  C -- yes --> PACK["Draft/certified close pack"]
  J --> REV["Reversal/supersession"]
```

Assessment: strong control architecture. Readiness remains conditional on canonical payment truth, migration history, provider statements, statutory sources, expert approval, and production observability.

HRIS and payroll

```
flowchart LR
  E["Employee/contract/time/compensation"] --> RDY["Payroll readiness"]
  RDY --> RUN["Calculate run"]
  RUN --> APP["Independent approval"]
  APP --> POST["Accounting posting"]
  POST --> PAY["Payment release/provider inbox"]
  PAY --> REC["Payment reconciliation"]
  APP --> DEC["Declaration lifecycle"]
  DEC --> AUTH["Authority/provider evidence"]
  REC --> CLOSE["Accounting close/data trust"]
  AUTH --> CLOSE
```

Strengths: identity scope, approvals, hashes, correction/provenance, leases, retries, payment/declaration evidence, payslip self-service, close blockers.

Gaps: production provider/authority credentials, expert-reviewed statutory sources, MFA for privileged actions, broad privacy and runtime certification.

Identity, invitation, and access

```
flowchart TD
  R["Register/invite"] --> S["Session and membership"]
  S --> T["Trusted tenant context"]
  T --> P["DB-fresh permission"]
  P --> M["Module entitlement"]
  M --> F["Fresh-auth / maker-checker"]
  F --> CMD["Domain command"]
  CMD --> AUD["Audit/evidence"]
```

Current weak links: raw invite tokens, MFA not connected, module observe/legacy access, fail-open audit, and no persistence-level tenant backstop.

TanStack Query lifecycle

```
flowchart LR
  CTX["Session + organization + location + module"] --> KEY["Canonical query key"]
  KEY --> FETCH["Protected action/API"]
  FETCH --> READ["Service-owned read model"]
  READ --> CACHE["QueryClient cache"]
  MUT["Mutation"] --> WRITE["Protected service command"]
  WRITE --> INV["Invalidate/set/remove affected keys"]
  INV --> CACHE
  CTX --> RESET["Context-change cache reset"]
  RESET --> CACHE
```

Current finding: the global QueryClient exists, but many keys omit organization identity and no context-change reset was proven. The required contract is a trusted context prefix plus a mutation-to-projection invalidation registry and organization-switch tests.

Public receipt and uploads

Public receipt:

`public route → signed/hashed token registry → tenant/sale/jti/time binding → scoped receipt → redacted response → revocation/expiry`

Assessment: strong.

Uploads:

`authenticated route → organization equality → module/filename/path containment → full file read → extension MIME → public cache response`

Assessment: access boundary has useful controls, but response caching, streaming, content validation, and retention are weak.

Assurance and agent boundaries

Protected actions derive server-side actor/tenant context; deterministic agent tools are read-only; proposals use status CAS and human review; workflow assurance has a static registry, indexes, scheduler policy, and incident concepts. Do not expand execution authority until creator self-approval, entitlement, audit durability, runtime scheduler, alert delivery, secrets, and production evidence are resolved.

Recovery matrix

Failure	Current recovery	Status
Duplicate business event/offline batch	idempotency/sequence detection	Strong in mocked tests
Invalid provider signature/replay	reject and alert/inbox evidence	Strong service contract; runtime unverified
Worker lease expiry	lease/retry patterns in payroll/payment workers	Tested mocked behavior; production unverified
Ledger posting failure	transaction/blocker/suspense paths	Strong
Audit sink failure	swallowed/best effort	DANGEROUS
Concurrent balances	no CAS on key POS paths	DANGEROUS
Concurrent PO approvals	no state/version CAS in canonical approval	Residual risk
Cache organization switch	no proven global reset/context prefix	Likely risk
Migration failure	static safety/approval logic and rollback planning	Production environment blocked
Statutory uncertainty	blocked/expert-review state	Strong fail-closed behavior