All required information and accompanying timestamps

This consolidates the previously identified gate inputs, existing people/roles/IDs, database dates, external evidence dates, validity periods, freshness rules and missing user inputs. It covers the audited workflows and does not claim a complete inventory of every application endpoint.

Snapshot and date convention

Fact	Recorded value
Database	localhost:5432/stoquify_replay_next_20260830
Database observed at (UTC)	2026-09-27T13:09:52.689Z
Same instant in Europe/Paris	27/09/2026, 15:09:52 GMT+2
Same instant in Africa/Douala	27/09/2026, 14:09:52 GMT+1
Latest applied migration	20260920060000_pos_checkout_lifecycle
Migration started_at	2026-09-20T11:56:54.247Z
Migration finished_at	2026-09-20T11:56:54.247Z
Migration rolled_back_at	NOT RECORDED
Data access	Enforced read-only transaction; ROLLBACK; no database or approval changes

Use ISO 8601 with an explicit timezone for instants. Keep date-only business dates as dates. Existing timestamps are evidence of what is stored, not proof of genuine appointment, review or historical business truth. The full source query and database column type accompany every extracted date.

Complete information files

- Complete fill-in worksheet, including each required date
- All 23 existing named candidate assignments and stored dates
- All 180 users, IDs, role/employee links and dates
- All 174 tenant roles, permissions and creation/update dates
- Every extracted record-level timestamp, including UTC/Paris/Douala display
- All selected required fields, exact types, constraints, current values and IDs
- All external contract fields, current values, formats and destinations
- Exact external review/approval/validity/expiry timestamp paths
- All 11 G1 decisions and 33 nominated role approvals
- Exact chronological and freshness rules
- Complete structured request for missing information

Required dates by input

Input	What accompanies the information
INPUT-01 Your decision	Business decision record: record the actual decision date. If an AI activation window is selected, use AgentActivationPackage.activationStartsAt and activationEndsAt. Other pilot planning dates are planning metadata, not newly invented database columns.
INPUT-02 Appointments and identity resolution	Genuine appointment/delegation document effective-from/effective-to and date of signing/acceptance, where its contract requires them. AccountantAccessGrant uses consentGrantedAt/effectiveFrom/expiresAt; HrisManagerDelegation uses effectiveFrom/effectiveTo and existing evidence references. No generic appointmentAt or _UserRoles.assignedAt column is implemented.
INPUT-03 Qualified expert evidence	requiredApproval.reviewedAt, effectiveFrom, effectiveTo (optional/open-ended only when justified); actual document dates and source effective period. ComplianceAdapterConfig reviewedAt/approvedAt/officialSpecPublishedAt/officialSpecEffectiveFrom are separate fields.
INPUT-04 Accountable product/control decisions	For each of 33 G1 role obligations: actual freshAuthenticatedAt and approvedAt. For each of 11 decisions: future reviewOrExpiryAt. Attestation verifiedAt/reviewOrExpiryAt and signing-key validFrom/validUntil are also required by the evidence contract.
INPUT-05 Real company, workforce and product inputs	Employer/product classification source-effective dates and genuine review date in its evidence document; current schema does not provide a complete per-product tax-approval record. HR uses PayrollEmployee.hireDate/terminationDate, PayrollContract.effectiveFrom/effectiveTo, HrisWorkCalendar.reviewedAt/effectiveFrom/effectiveTo, HrisLeavePolicy.approvedAt/effectiveFrom/effectiveTo. Preserve business dates and period timezone.
INPUT-06 Provider and integration inputs	ComplianceAdapterConfig officialSpecPublishedAt/officialSpecEffectiveFrom, reviewedAt, approvedAt, credentialExpiresAt and actual credentialRotatedAt if applicable. SettlementAccount approvedAt/effectiveFrom/effectiveTo. Provider dates and managed-secret expiry come from the provider/operator, not invented defaults.
INPUT-07 Conditional AI pilot / operations	Product/security decidedAt/expiresAt; six owner acceptedAt/coverageStartsAt/coverageEndsAt (plus runtime owner validUntil when used); release activationStartsAt/activationEndsAt; certification passedAt/expiresAt; CI/governance/deployment/scheduler/alert/rotation times listed in TIME_RULES.md and external-required-timestamps.csv.
INPUT-08 Deployment inputs	Actual deployment, attestation, credential rotation/review and operational test timestamps from the deployment/evidence systems. Generated audit or file-modification time is not deployment/approval time.
INPUT-09 Four existing stocking-unit choices	Record the catalog decision and its intended effective business date in supporting evidence if a change is authorized. Item.updatedAt/Unit.updatedAt are written by the system and do not prove user approval. There is no dedicated stocking-unit approval timestamp in the inspected Item/Unit schema.

Existing gate-owner nominations

Existing name	Role	User ID	Account created (UTC)	Account updated (UTC)
Yongwa Eli	accounting_owner	rds_org_001_compliance_user_accounting_owner	2026-08-30T19:51:55.366Z	2026-08-30T19:51:55.366Z

Existing name	Role	User ID	Account created (UTC)	Account updated (UTC)
Yonga Springfield	checker	rds_org_001_compliance_user_checker	2026-08-30T19:51:54.935Z	2026-08-30T19:51:54.935Z
Kouatchoua Marceline	controller_approver	rds_org_001_compliance_user_controller_approver	2026-08-30T19:51:55.022Z	2026-08-30T19:51:55.022Z
Sango Malo	database_migration_operator	rds_org_001_compliance_user_database_migration_operator	2026-08-30T19:51:54.868Z	2026-08-30T19:51:54.868Z
Tchami Jennifer	financial_controller	rds_org_001_compliance_user_financial_controller	2026-08-30T19:51:55.001Z	2026-08-30T19:51:55.001Z
Yonga Lysette	fulfillment_owner	rds_org_001_compliance_user_fulfillment_owner	2026-08-30T19:51:55.339Z	2026-08-30T19:51:55.339Z
Maximilliano Bonga	independent_migration_checker	rds_org_001_compliance_user_independent_migration_checker	2026-08-30T19:51:54.893Z	2026-08-30T19:51:54.893Z
Tchana Rose	inventory_controller	rds_org_001_compliance_user_inventory_controller	2026-08-30T19:51:55.315Z	2026-08-30T19:51:55.315Z
Tamen Marceline	maker	rds_org_001_compliance_user_maker	2026-08-30T19:51:54.914Z	2026-08-30T19:51:54.914Z
Tamen Marceline	order_to_cash_product_owner	rds_org_001_compliance_user_order_to_cash_product_owner	2026-08-30T19:51:55.246Z	2026-08-30T19:51:55.246Z
Yonga Junie	payments_owner	rds_org_001_compliance_user_payments_owner	2026-08-30T19:51:55.046Z	2026-08-30T19:51:55.046Z
tchakoumiLorrain	pos_architect	rds_org_001_compliance_user_pos_architect	2026-08-30T19:51:55.091Z	2026-08-30T19:51:55.091Z
Kouatchoua Mark	product_approver	rds_org_001_compliance_user_product_approver	2026-08-30T19:51:54.980Z	2026-08-30T19:51:54.980Z
Arielle Yongwa	product_owner	rds_org_001_compliance_user_product_owner	2026-08-30T19:51:54.958Z	2026-08-30T19:51:54.958Z
Sonkeng Steve	qa_owner	rds_org_001_compliance_user_qa_owner	2026-08-30T19:51:55.179Z	2026-08-30T19:51:55.179Z

Existing name	Role	User ID	Account created (UTC)	Account updated (UTC)
Tchana Nikita	qualified_accounting_reviewer	rds_org_001_compliance_user_qualified_accounting_reviewer	2026-08-30T19:51:55.266Z	2026-08-30T19:51:55.266Z
Kouatchouamark	qualified_cameroon_country_pack_reviewer	rds_org_001_compliance_user_qualified_cameroon_country_pack_reviewer	2026-08-30T19:51:55.289Z	2026-08-30T19:51:55.289Z
Tamen Max	retail_operations_owner	rds_org_001_compliance_user_retail_operations_owner	2026-08-30T19:51:55.067Z	2026-08-30T19:51:55.067Z
Tamen Martial	risk_owner	rds_org_001_compliance_user_risk_owner	2026-08-30T19:51:55.155Z	2026-08-30T19:51:55.155Z
Yonga Springfield	security_owner	rds_org_001_compliance_user_security_owner	2026-08-30T19:51:55.113Z	2026-08-30T19:51:55.113Z
Ronald Djakou	sre_owner	rds_org_001_compliance_user_sre_owner	2026-08-30T19:51:55.221Z	2026-08-30T19:51:55.221Z
Etoo Naomie	support_owner	rds_org_001_compliance_user_support_owner	2026-08-30T19:51:55.200Z	2026-08-30T19:51:55.200Z
Tamen Stanick	treasury_owner	rds_org_001_compliance_user_treasury_owner	2026-08-30T19:51:55.134Z	2026-08-30T19:51:55.134Z

Dates that cannot be truthfully filled from the current database

- Role-assignment time: `_UserRoles` has only the role/user keys, no assignment timestamp. `Role.createdAt` is the creation of the role definition, not membership time.
- Genuine appointment, professional qualification/review and external signature dates: no verified authority was established by seeded accounts. The relevant signer/reviewer must provide authentic dated evidence.
- POS G1: the current detached decision approval register has no approval entries. The prefilled worksheet contains nominees and technical decisions; authentication/approval/expiry dates remain empty.
- Generic product-tax classification and stocking-unit approvals: the inspected Item/TaxRate/Unit contracts lack complete dated approval/provenance storage. Their required real evidence cannot be represented by inventing a column.
- Session fresh-authentication times: derived from the actual live protected session when an action occurs. They are not manual values to submit in this worksheet.
- Activation/revocation/deletion/termination: no event means no event timestamp. Null does not automatically mean a missing requirement.

Current blockers and scope

The prior decision brief and gate register retain their original audit times and the 13-pass/8-blocked gate outcomes; those validators were not rerun just to add dates. The new extraction refreshes database information only. Further development can continue while engineering repairs data/access/configuration gaps and authorized owners provide missing decisions/evidence.

Identity conflicts remain: checker Yonga Claude in supplied documentation versus Yonga Springfield in the database; confirm Kouatchoua mMark versus Kouatchoua Mark. Separate accounts with repeated Tamen Marceline/Yonga Springfield names do not prove independent people.

External field contracts

The complete field tables below retain the original exact storage paths and required formats. Some composite rows summarize several implemented fields; exact date rows are expanded in the external timestamp CSV. Fields marked prior contract/grouped remain definitions, not newly observed values.

CM_CNPS_PRODUCTION_APPROVAL

Stage: Production CNPS authority; not a development-code prerequisite. Destination: docs/HR-Payroll/evidence/country-packs/CM/2026-07-19/manifest.json.

Field	Type	Current value / definition	Required format / rule
requiredApproval.reviewerIdentity	string	NOT RECORDED	Nonempty. Must resolve to an actual appointed qualified reviewer; plain seed display name is not sufficient authority.
requiredApproval.reviewedAt	string	NOT RECORDED	Gate checks nonempty only; supply actual ISO-8601 UTC timestamp of review.
requiredApproval.effectiveFrom	string	NOT RECORDED	Gate checks nonempty only; document YYYY-MM-DD effective date tied to reviewed law/pack.
requiredApproval.effectiveTo	string|null	NOT RECORDED	Present in manifest but NOT enforced by this static gate; document end date or explicit open-ended validity.
requiredApproval.approvalArtifactFile	string	NOT RECORDED	Existing basename only, co-located with manifest; no path traversal.
requiredApproval.approvalArtifactHash	string	NOT RECORDED	64 lowercase hexadecimal SHA-256 of actual artifact bytes, WITHOUT sha256: prefix.
requiredApproval.approvedFixtureFamilies	string[]	[]	All four distinct families: payroll.cnps.pensionRatesBps, payroll.cnps.familyAllowanceRatesBps, payroll.cnps.occupationalRiskRatesBps, payroll.cnps.employerRules.
reviewStatus	enum	PENDING_EXPERT_REVIEW	EXPERT_REVIEWED or REGULATOR_CONFIRMED only after authentic review.
productionUseAllowed	boolean	false	true only after authentic approval; current false is intentional.
artifacts[0].file	string	CNPS-Decree-2016-072-contribution-rates.pdf	Existing local basename; SHA256 must match declared sourceEvidenceHash in runtime pack.

Field	Type	Current value / definition	Required format / rule
artifacts[0].sha256	string	1e88f488d96e163ded9e204c100c5bbce9e8d4917e6e72387ec6af52e0c90b61	64 lowercase hex SHA256 of artifact bytes, without prefix.
artifacts[0].reviewStatus	enum	PENDING_EXPERT_REVIEW	EXPERT_REVIEWED or REGULATOR_CONFIRMED after actual review.
artifacts[0].productionUseAllowed	boolean	false	true after authentic approval.
artifacts[1].file	string	CNPS-employer-general-rules.html	Existing local basename; SHA256 must match declared sourceEvidenceHash in runtime pack.
artifacts[1].sha256	string	bc51f74de8dd3b0c7babd86e8f98d92dbdbece214480f66ac89c42d3e894a868	64 lowercase hex SHA256 of artifact bytes, without prefix.
artifacts[1].reviewStatus	enum	PENDING_EXPERT_REVIEW	EXPERT_REVIEWED or REGULATOR_CONFIRMED after actual review.
artifacts[1].productionUseAllowed	boolean	false	true after authentic approval.

AGENT_EXTERNAL_INPUTS

Stage: Internal pilot evidence capture and independent operational release; not generic local development.
Destination: docs/agents-runtime/STOQUIFY_AGENT_RUNTIME_EXTERNAL_INPUTS_2026-07-25.json.

Field	Type	Current value / definition	Required format / rule
schemaVersion	number	1	Gate-bounded integer; see family-specific rules
environment	string	INTERNAL_PILOT	Nonempty identifier/version/text tied to the actual scope
release.packageId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
release.releaseVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
release.commitSha	string	NOT RECORDED	40 hexadecimal commit SHA (operational evaluator also accepts 64); same across release/CI/governance/deployment
release.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.artifactReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.deploymentReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.manifestHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release

Field	Type	Current value / definition	Required format / rule
release.evidenceBundleHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.browserReportHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.pilotAllowlistReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.roleAllowlistReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
approvers.product.decision	string	PENDING	APPROVED only after deliberate genuine human decision
approvers.product.actorDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
approvers.product.approvalReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
approvers.product.decidedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
approvers.product.expiresAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
approvers.security.decision	string	PENDING	APPROVED only after deliberate genuine human decision
approvers.security.actorDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
approvers.security.approvalReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
approvers.security.decidedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
approvers.security.expiresAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[0].role	string	ROLLOUT	Nonempty identifier/version/text tied to the actual scope
owners[0].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[0].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[0].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[0].acceptedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules

Field	Type	Current value / definition	Required format / rule
owners[0].coverageStartsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[0].coverageEndsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[0].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[1].role	string	ROLLBACK	Nonempty identifier/version/text tied to the actual scope
owners[1].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[1].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[1].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[1].acceptedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[1].coverageStartsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[1].coverageEndsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[1].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[2].role	string	SUPPORT	Nonempty identifier/version/text tied to the actual scope
owners[2].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[2].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[2].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[2].acceptedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[2].coverageStartsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[2].coverageEndsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[2].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content

Field	Type	Current value / definition	Required format / rule
owners[3].role	string	PILOT	Nonempty identifier/version/text tied to the actual scope
owners[3].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[3].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[3].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[3].acceptedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[3].coverageStartsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[3].coverageEndsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[3].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[4].role	string	SECURITY_INCIDENT	Nonempty identifier/version/text tied to the actual scope
owners[4].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[4].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[4].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[4].acceptedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[4].coverageStartsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[4].coverageEndsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[4].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[5].role	string	ON_CALL_BACKUP	Nonempty identifier/version/text tied to the actual scope
owners[5].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately

Field	Type	Current value / definition	Required format / rule
owners[5].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[5].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[5].acceptedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[5].coverageStartsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[5].coverageEndsAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[5].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
evidenceEndpoints.ci.url	string	NOT RECORDED	https URL without username, password, query or fragment
evidenceEndpoints.ci.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
evidenceEndpoints.ci.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
evidenceEndpoints.governance.url	string	NOT RECORDED	https URL without username, password, query or fragment
evidenceEndpoints.governance.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
evidenceEndpoints.governance.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
evidenceEndpoints.scheduler.url	string	NOT RECORDED	https URL without username, password, query or fragment
evidenceEndpoints.scheduler.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
evidenceEndpoints.scheduler.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
evidenceEndpoints.reconciler.url	string	NOT RECORDED	https URL without username, password, query or fragment
evidenceEndpoints.reconciler.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
evidenceEndpoints.reconciler.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
evidenceEndpoints.alert.url	string	NOT RECORDED	https URL without username, password, query or fragment

Field	Type	Current value / definition	Required format / rule
evidenceEndpoints.alert.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
evidenceEndpoints.alert.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
evidenceEndpoints.credential.url	string	NOT RECORDED	https URL without username, password, query or fragment
evidenceEndpoints.credential.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
evidenceEndpoints.credential.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
managedCredentials.workloadIdentityReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
managedCredentials.collectorIdentityReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
managedCredentials.secretManagerNamespaceReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
managedCredentials.rotationAuthorityReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
managedCredentials.credentialInventoryReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
statutoryApproval.decision	string	PENDING	APPROVED only after deliberate genuine human decision
statutoryApproval.reviewerDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
statutoryApproval.qualificationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
statutoryApproval.sourceArtifactHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
statutoryApproval.approvalArtifactReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
statutoryApproval.approvalArtifactHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
statutoryApproval.reviewedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
pilot.cohortReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
pilot.tenantScopeHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
pilot.roleScopeHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release

Field	Type	Current value / definition	Required format / rule
pilot.supportCoverageReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
pilot.rollbackPlanReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
pilot.activationAuthorityDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
pilot.activationDecision	string	PENDING	Nonempty identifier/version/text tied to the actual scope
pilot.activationDecisionReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
pilot.activationDecidedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
safety.activationRequested	boolean	false	Exact documented safety/control value; never change solely to make audit pass
safety.activationAuthorized	boolean	false	Exact documented safety/control value; never change solely to make audit pass
safety.activatedAt	string |null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
safety.phase3Authorized	boolean	false	Exact documented safety/control value; never change solely to make audit pass
safety.secretValuesIncluded	boolean	false	Exact documented safety/control value; never change solely to make audit pass

AGENT_OPERATIONAL_RELEASE

Stage: Internal pilot evidence capture and independent operational release; not generic local development. Destination: docs/agents-runtime/STOQUIFY_AGENT_RUNTIME_OPERATIONAL_RELEASE_EVIDENCE_2026-07-25.json.

Field	Type	Current value / definition	Required format / rule
schemaVersion	number	1	Gate-bounded integer; see family-specific rules
registerId	string	stoquify-agent-runtime-operational-release-2026-07-25	Nonempty identifier/version/text tied to the actual scope
declaredStatus	string	BLOCKED	Gate enum; actual evidence required for ready states
release.environment	string	INTERNAL_PILOT	Nonempty identifier/version/text tied to the actual scope
release.packageId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
release.releaseVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
release.packageState	string	PILOT_CERTIFIED	Nonempty identifier/version/text tied to the actual scope
release.commitSha	string	NOT RECORDED	40 hexadecimal commit SHA (operational evaluator also accepts 64); same across release/CI/governance/deployment
release.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.artifactReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.deploymentReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.packageCertificationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.packageCertificationHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.manifestHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.evidenceBundleHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.browserReportHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.pilotAllowlistReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.roleAllowlistReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
release.ciEvidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
release.activatedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
ci.status	string	PENDING	Gate enum; actual evidence required for ready states
ci.sourceTreeClean	boolean	false	Exact documented safety/control value; never change solely to make audit pass
ci.commitSha	string	NOT RECORDED	40 hexadecimal commit SHA (operational evaluator also accepts 64); same across release/CI/governance/deployment
ci.branchReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content

Field	Type	Current value / definition	Required format / rule
ci.runReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
ci.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
ci.artifactReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
ci.browserReportHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
ci.completedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
ci.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
ci.attestationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
ci.attestationDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
ci.attestedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
ci.evidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
ci.invalidAuthEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
governance.environment	string	INTERNAL_PILOT	Nonempty identifier/version/text tied to the actual scope
governance.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
governance.attestationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
governance.attestationDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
governance.attestedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
governance.evidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
governance.invalidAuthEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
governance.packageId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
governance.releaseVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
governance.commitSha	string	NOT RECORDED	40 hexadecimal commit SHA (operational evaluator also accepts 64); same across release/CI/governance/deployment
governance.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
governance.manifestHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
governance.evidenceBundleHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
approvals.product.decision	string	PENDING	APPROVED only after deliberate genuine human decision
approvals.product.actorDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
approvals.product.approvalReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
approvals.product.decidedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
approvals.product.expiresAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
approvals.product.manifestHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
approvals.product.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
approvals.product.evidenceBundleHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
approvals.security.decision	string	PENDING	APPROVED only after deliberate genuine human decision
approvals.security.actorDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
approvals.security.approvalReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
approvals.security.decidedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules

Field	Type	Current value / definition	Required format / rule
approvals.security.expiresAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
approvals.security.manifestHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
approvals.security.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
approvals.security.evidenceBundleHash	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
owners[0].role	string	ROLLOUT	Nonempty identifier/version/text tied to the actual scope
owners[0].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[0].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[0].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[0].acceptedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[0].coverageStartsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[0].coverageEndsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[0].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[1].role	string	ROLLBACK	Nonempty identifier/version/text tied to the actual scope
owners[1].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[1].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[1].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
owners[1].acceptedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[1].coverageStartsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[1].coverageEndsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[1].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[2].role	string	SUPPORT	Nonempty identifier/version/text tied to the actual scope
owners[2].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[2].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[2].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[2].acceptedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[2].coverageStartsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[2].coverageEndsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[2].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[3].role	string	PILOT	Nonempty identifier/version/text tied to the actual scope
owners[3].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[3].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[3].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
owners[3].acceptedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[3].coverageStartsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[3].coverageEndsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[3].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[4].role	string	SECURITY_INCIDENT	Nonempty identifier/version/text tied to the actual scope
owners[4].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[4].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[4].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
owners[4].acceptedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[4].coverageStartsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[4].coverageEndsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[4].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
owners[5].role	string	ON_CALL_BACKUP	Nonempty identifier/version/text tied to the actual scope
owners[5].primaryDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[5].backupDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
owners[5].acceptedRunbookVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
owners[5].acceptedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[5].coverageStartsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[5].coverageEndsAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
owners[5].escalationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.provider	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
scheduler.scheduleReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.workloadReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.authType	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
scheduler.managedCredentialReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.intervalMinutes	number	5	Gate-bounded integer; see family-specific rules
scheduler.singleConcurrency	boolean	false	Exact documented safety/control value; never change solely to make audit pass
scheduler.leaseSafe	boolean	true	Exact documented safety/control value; never change solely to make audit pass
scheduler.concurrencyEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.timeoutMs	number	120000	Gate-bounded integer; see family-specific rules
scheduler.deployedCommitSha	string	NOT RECORDED	40 hexadecimal commit SHA (operational evaluator also accepts 64); same across release/CI/governance/deployment
scheduler.deployedArtifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
scheduler.deployedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.deploymentSourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content

Field	Type	Current value / definition	Required format / rule
scheduler.deploymentAttestationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.deploymentAttestationDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
scheduler.deploymentAttestedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.deploymentEvidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
scheduler.deploymentAuthorityInvalidAuthEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.readinessStatus	string	PENDING	Gate enum; actual evidence required for ready states
scheduler.readinessCheckedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.readinessEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.readinessEvidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
scheduler.heartbeatFreshUntil	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.invalidAuthEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.missingConfigEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.failureAlertReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.windows[0].runId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
scheduler.windows[0].scheduledAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.windows[0].completedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.windows[0].status	string	PENDING	Gate enum; actual evidence required for ready states

Field	Type	Current value / definition	Required format / rule
scheduler.windows[0].evidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.windows[1].runId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
scheduler.windows[1].scheduledAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.windows[1].completedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.windows[1].status	string	PENDING	Gate enum; actual evidence required for ready states
scheduler.windows[1].evidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
scheduler.windows[2].runId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
scheduler.windows[2].scheduledAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.windows[2].completedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
scheduler.windows[2].status	string	PENDING	Gate enum; actual evidence required for ready states
scheduler.windows[2].evidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.transportStatus	string	PENDING	Gate enum; actual evidence required for ready states
alerting.evidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
alerting.transportReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.managedSecretReference	string	NOT RECORDED	Value-free secret-manager://, vault:// or keyvault:// controlled reference; never secret bytes
alerting.httpsDeliveryReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.externalRequestReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.deliveredAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules

Field	Type	Current value / definition	Required format / rule
alerting.acknowledgementSloMinutes	number	15	Gate-bounded integer; see family-specific rules
alerting.acknowledgedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
alerting.acknowledgedByDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
alerting.acknowledgementReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.retryEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.deadLetterEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.recoveryEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.escalationTestedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
alerting.escalatedToDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
alerting.escalationEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
alerting.secretRotationEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
credentialRotation.registerReference	string	docs/agents-runtime/STOQUIFY_AGENT_RUNTIME_CREDENTIAL_ROTATION_REGISTER_2026-07-25.json	Value-free scheme:// reference matching gate regex; no query strings or credential content
credentialRotation.registerSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
credentialRotation.securityApprovalReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
credentialRotation.evidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
credentialRotation.attestationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
activation.requested	boolean	false	Exact documented safety/control value; never change solely to make audit pass

Field	Type	Current value / definition	Required format / rule
activation.authorized	boolean	false	Exact documented safety/control value; never change solely to make audit pass
activation.activatedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules

CREDENTIAL_CLASSIFICATION_AND_ROTATION

Stage: Internal pilot evidence capture and independent operational release; not generic local development. Destination: docs/agents-runtime/STOQUIFY_AGENT_RUNTIME_CREDENTIAL_ROTATION_REGISTER_2026-07-25.json.

Field	Type	Current value / definition	Required format / rule
schemaVersion	number	1	Gate-bounded integer; see family-specific rules
registerId	string	stoquify-agent-runtime-credential-response-2026-07-25	Nonempty identifier/version/text tied to the actual scope
incidentReference	string	unsafe-local-browser-report-environment-scope	Value-free scheme:// reference matching gate regex; no query strings or credential content
declaredStatus	string	BLOCKED	Gate enum; actual evidence required for ready states
securityOwnerDirectoryId	string	NOT RECORDED	directory:// or identity:// URI for actual identity; rejects e2e/test/seed/fixture/demo segments; appointment/qualification verified separately
securityApprovalReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
authority.environment	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
authority.sourceSystemReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
authority.attestationReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
authority.attestationDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
authority.attestedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
authority.evidenceSha256	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
authority.invalidAuthEvidenceReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content

Field	Type	Current value / definition	Required format / rule
releaseBinding.environment	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
releaseBinding.packageId	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
releaseBinding.releaseVersion	string	NOT RECORDED	Nonempty identifier/version/text tied to the actual scope
releaseBinding.packageState	string	PILOT_CERTIFIED	Nonempty identifier/version/text tied to the actual scope
releaseBinding.commitSha	string	NOT RECORDED	40 hexadecimal commit SHA (operational evaluator also accepts 64); same across release/CI/governance/deployment
releaseBinding.artifactDigest	string	NOT RECORDED	sha256: followed by 64 hex digits; compute from authoritative bytes and bind exact release
releaseBinding.deploymentReference	string	NOT RECORDED	Value-free scheme:// reference matching gate regex; no query strings or credential content
releaseBinding.activatedAt	string|null	NOT RECORDED	Actual ISO-8601 timestamp; accepted/decided/verified times not future, expiry/coverage end future; see family freshness rules
entries[0].id	string	primary-database-credential	Nonempty identifier/version/text tied to the actual scope
entries[0].purpose	string	Primary PostgreSQL application and migration access	Nonempty identifier/version/text tied to the actual scope
entries[0].environmentVariables	array	["DATABASE_URL"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[0].dependentWorkloads	array	["web-application","migration-runner","agent-reconciler"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[0].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[1].id	string	payroll-immutability-database-credential	Nonempty identifier/version/text tied to the actual scope
entries[1].purpose	string	Payroll immutability verification database access	Nonempty identifier/version/text tied to the actual scope
entries[1].environmentVariables	array	["PAYROLL_IMMUTABILITY_DATABASE_URL"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[1].dependentWorkloads	array	["payroll-immutability-verifier"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[1].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[2].id	string	application-auth-signing-secret	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
entries[2].purpose	string	Application authentication and session signing	Nonempty identifier/version/text tied to the actual scope
entries[2].environmentVariables	array	["AUTH_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[2].dependentWorkloads	array	["web-application","authentication-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[2].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[3].id	string	legacy-nextauth-signing-secret	Nonempty identifier/version/text tied to the actual scope
entries[3].purpose	string	Legacy or compatibility authentication signing	Nonempty identifier/version/text tied to the actual scope
entries[3].environmentVariables	array	["NEXTAUTH_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[3].dependentWorkloads	array	["web-application","authentication-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[3].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[4].id	string	google-oauth-client-secret	Nonempty identifier/version/text tied to the actual scope
entries[4].purpose	string	Google OAuth client authentication	Nonempty identifier/version/text tied to the actual scope
entries[4].environmentVariables	array	["GOOGLE_CLIENT_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[4].dependentWorkloads	array	["authentication-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[4].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[5].id	string	email-server-credential	Nonempty identifier/version/text tied to the actual scope
entries[5].purpose	string	Transactional email server authentication	Nonempty identifier/version/text tied to the actual scope
entries[5].environmentVariables	array	["EMAIL_SERVER_USER","EMAIL_SERVER_PASSWORD"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[5].dependentWorkloads	array	["web-application","email-delivery-worker"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[5].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[6].id	string	redis-connection-credential	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
entries[6].purpose	string	Redis cache, rate-limit, or queue access	Nonempty identifier/version/text tied to the actual scope
entries[6].environmentVariables	array	["REDIS_URL"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[6].dependentWorkloads	array	["web-application","background-workers"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[6].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[7].id	string	public-identity-hmac-secret	Nonempty identifier/version/text tied to the actual scope
entries[7].purpose	string	Public identity abuse-protection hashing	Nonempty identifier/version/text tied to the actual scope
entries[7].environmentVariables	array	["PUBLIC_IDENTITY_ABUSE_HASH_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[7].dependentWorkloads	array	["web-application"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[7].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[8].id	string	public-receipt-signing-secret	Nonempty identifier/version/text tied to the actual scope
entries[8].purpose	string	Public receipt token signing	Nonempty identifier/version/text tied to the actual scope
entries[8].environmentVariables	array	["AQSTOQFLOW_RECEIPT_TOKEN_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[8].dependentWorkloads	array	["web-application","receipt-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[8].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[9].id	string	history-cursor-signing-secret	Nonempty identifier/version/text tied to the actual scope
entries[9].purpose	string	Transaction-history cursor signing	Nonempty identifier/version/text tied to the actual scope
entries[9].environmentVariables	array	["AQSTOQFLOW_HISTORY_CURSOR_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[9].dependentWorkloads	array	["web-application","transaction-history-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[9].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[10].id	string	payroll-destination-hmac-secret	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
entries[10].purpose	string	Payroll payment-destination integrity hashing	Nonempty identifier/version/text tied to the actual scope
entries[10].environmentVariables	array	["PAYROLL_PAYMENT_DESTINATION_HASH_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[10].dependentWorkloads	array	["web-application","payroll-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[10].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[11].id	string	upload-provider-secret	Nonempty identifier/version/text tied to the actual scope
entries[11].purpose	string	Managed upload-provider authentication	Nonempty identifier/version/text tied to the actual scope
entries[11].environmentVariables	array	["UPLOADTHING_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[11].dependentWorkloads	array	["web-application","upload-service"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[11].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[12].id	string	error-monitoring-dsn	Nonempty identifier/version/text tied to the actual scope
entries[12].purpose	string	Error-monitoring ingestion authentication	Nonempty identifier/version/text tied to the actual scope
entries[12].environmentVariables	array	["SENTRY_DSN"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[12].dependentWorkloads	array	["web-application","background-workers"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[12].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[13].id	string	agent-reconciler-credential	Nonempty identifier/version/text tied to the actual scope
entries[13].purpose	string	Five-minute Agent Runtime reconciler authentication	Nonempty identifier/version/text tied to the actual scope
entries[13].environmentVariables	array	["STOQUIFY_AGENT_RECONCILER_SECRET","STOQUIFY_AGENT_RECONCILER_SECRET_PREVIOUS"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[13].dependentWorkloads	array	["web-application","agent-reconciler-scheduler"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[13].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states
entries[14].id	string	workflow-assurance-webhook-secret	Nonempty identifier/version/text tied to the actual scope

Field	Type	Current value / definition	Required format / rule
entries[14].purpose	string	Workflow Assurance webhook authentication	Nonempty identifier/version/text tied to the actual scope
entries[14].environmentVariables	array	["STOQUIFY_ASSURANCE_ALERT_WEBHOOK_SECRET"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[14].dependentWorkloads	array	["web-application","agent-reconciler","alert-endpoint"]	Authentic scope/evidence entries; an empty evidence array does not satisfy execution proof
entries[14].disposition	string	UNRESOLVED	Gate enum; actual evidence required for ready states

POS_G1_ACCOUNTABLE_APPROVAL

Stage: G1 architecture/control promotion; limited local development remains contract-scoped. Destination: docs/pos-enterprise-grade-audit/EXECUTION_06_G1_CONTRACT_APPROVAL_REGISTER.json.

Field	Type	Current value / definition	Required format / rule
contractArtifactId / contractVersion / contractPath / contractSha256	string	{"contractArtifactId":"STOQUIFY-POS-G1-CONTRACT-FREEZE-0.2.0-20260817","contractVersion":"0.2.0","contractPath":"docs/pos-enterprise-grade-audit/EXECUTION_06_G1_CONTRACT_FREEZE_V0_2_0.json","contractSha256":"11434eb3e1af1826516426e90d2d53a2faa47ade361d91191b5f3e0c950a36db"}	Must equal exact frozen contract artifact/version/path and SHA256 of unchanged bytes.
decisionApprovals[].decisionId	enum	NOT RECORDED	D-01 through D-11, unique, all represented.
decisionApprovals[].selectedOption / rationale / effectiveVersion	string	NOT RECORDED	Exact selected option; nonempty rationale; effectiveVersion equals contractVersion.
decisionApprovals[].reviewOrExpiryAt	UTC timestamp	NOT RECORDED	Future strict ISO UTC timestamp.
decisionApprovals[].evidenceLinks / affectedCapabilities	string[]	NOT RECORDED	Nonempty arrays of nonempty strings.
decisionApprovals[].rollbackOrDisablePolicy	string	NOT RECORDED	Nonempty concrete policy.
decisionApprovals[].approvalStatus	enum	NOT RECORDED	APPROVED only when authentic obligations have completed.
decisionApprovals[].approvals[].accountableApprover / approverRole / authorityReference	string	NOT RECORDED	Actual identified appointed person, required exact role and authentic scoped authority reference.

Field	Type	Current value / definition	Required format / rule
decisionApprovals[].approvals[].freshAuthenticatedAt / approvedAt	UTC timestamps	NOT RECORDED	Strict ISO UTC; approvedAt not future, >=freshAuthenticatedAt, within 10 minutes.
decisionApprovals[].approvals[].signatureReference	relative file path	NOT RECORDED	Existing file contained in workspace; valid trusted ARTIFACT_BOUND_APPROVAL envelope.
decisionApprovals[].approvals[].signatureEvidenceSha256	string	NOT RECORDED	64 lowercase hex SHA256 of actual envelope bytes, no prefix.
POS_GATE_TRUSTED_PUBLIC_KEYS_PATH	absolute filesystem path	TRUST_ANCHORS_NOT_CONFIGURED	Operator-managed JSON file OUTSIDE candidate repository; values are public keys only.
trustedKeys[keyId].publicKeyPem / evidenceClasses / validFrom / validUntil	object	NOT RECORDED	Ed25519 PEM, authorized evidenceClasses, strict UTC validity covering envelope verification and expiry.
envelope.schemaVersion / keyId / signature / payload	object	NOT RECORDED	schemaVersion 1.0.0; known keyId; Ed25519 signature base64; canonical JSON payload.
payload.result / evidenceClass / binding / verifiedAt / reviewOrExpiryAt / artifacts	object	NOT RECORDED	VERIFIED; ARTIFACT_BOUND_APPROVAL; exact contract/decision/person/time binding; nonexpired; every relative artifact path unique, contained and hash-matching.

MODULE_SETUP_AND_ENTITLEMENT

Stage: Operation-specific module readiness; not corporate appointment. Destination: Domain tables via canonical services, TenantModuleLifecycleOperation.setupInputs and evidence.

Field	Type	Current value / definition	Required format / rule
organizationAccountingSettings.accountingEnabled / setupStatus	boolean / enum	NOT RECORDED	true / READY and zero collectAccountingSetupReadinessIssues: required active leaf mappings with type/normal balance/SYSCOHADA refs, default journals, open current period, balanced posting scaffolds.
ProviderAccount.status / paymentRail.isActive / settlementLedgerAccountId / suspenseLedgerAccountId	enum / boolean / IDs	NOT RECORDED	ACTIVE, active rail, same-tenant active leaf mapped accounts.

Field	Type	Current value / definition	Required format / rule
SettlementAccount.approvalStatus / effectiveFrom / effectiveTo	enum / dates	NOT RECORDED	APPROVED and current effective window, through genuine destination controls.
setupInputs.payrollPeriodId	string	NOT RECORDED	Existing same-tenant non-CLOSED period; user has one payroll.runs.calculate/approve/post; getPayrollSetupReadiness must return READY.
setupInputs.complianceAdapterId	string	NOT RECORDED	Existing same-tenant CM sandbox adapter; user has compliance.documents.read.
ComplianceAdapterConfig.environment / adapterKey / status	enum / string	NOT RECORDED	SANDBOX / CAMEROON DGI sandbox constant / ACTIVE, never production for this readiness path.
ComplianceAdapterConfig.credentialReference / credentialExpiresAt	string / Date|null	NOT RECORDED	Valid vault reference and unexpired; no secret stored in report.
ComplianceAdapterConfig.officialSpecHash / officialSpecVersion / officialSpecPublishedAt / officialSpecReference	strings / date	NOT RECORDED	Actual official-spec artifact/version/date/reference; all present.
ComplianceAdapterConfig.reviewStatus / reviewEvidenceHash / reviewedAt / reviewedById	enum / string / Date / User.id	NOT RECORDED	EXPERT_APPROVED or REGULATOR_CONFIRMED plus real scoped review proof; matching countryPackVersion/capabilityStatus.
module composition expectedRevision / previewHash / idempotencyKey / selectedModules	integer / hash / string / string[]	NOT RECORDED	Fresh canonical preview, current user permissions, existing entitlements/dependencies; cannot purchase/grant entitlement via workspace selection.

RELEASE_ENVIRONMENT_INPUTS

Stage: Deployment/release only. Destination: Managed deployment environment; never include secret values.

Field	Type	Current value / definition	Required format / rule
PUBLIC_IDENTITY_ABUSE_HASH_SECRET	secret environment variable	NOT RECORDED	At least 32 characters in intended runtime; provided through managed deployment secrets; never supplied in chat/docs.
AQSTOQFLOW_RECEIPT_TOKEN_SECRET	secret environment variable	NOT RECORDED	At least 32 characters in intended runtime; provided through managed deployment secrets; never supplied in chat/docs.
AQSTOQFLOW_HISTORY_CURSOR_SECRET	secret environment variable	NOT RECORDED	At least 32 characters in intended runtime; provided through managed deployment secrets; never supplied in chat/docs.

Identifier and authentication details

Record IDs follow actual primary keys, including `POSCheckoutWorkspace.sessionId` and `TenantModuleConfiguration.organizationId`. This corrects the previous audit field view that used organization ID as the checkout workspace display identifier. All migration timestamps and Server-owned authentication timestamp contracts are included. Authentication dates were not read from live session records and must be produced by the real authentication workflow.