Alzheimer's Prediction Optimization using HPC

MANJULA V
Associate Professor Grade 2, SCOPE
Vellore Institute of Technology, CHENNAI
Chennai, India
manjula.v@vit.ac.in

S R KOUSALYA
BTech Computer Science and Engineering, SCOPE
Vellore Institute of Technology, CHENNAI
Chennai, India
kousalya.sr2022@vitstudent.ac.in

HARINI L
BTech Computer Science and Engineering, SCOPE
Vellore Institute of Technology, CHENNAI
Chennai, India
harini.l2022@vitstudent.ac.in

YOGESHWARAN A
BTech Computer Science and Engineering, SCOPE
Vellore Institute of Technology, CHENNAI
Chennai, India
yogeshwaran.a2022@vitstudent.ac.in

***Abstract*—Alzheimer's disease prediction from MRI images involves processing large volumes of complex medical data, often leading to high computational demands. This research proposes a high-performance computing (HPC)-based deep learning approach to classify Alzheimer's stages. The system employs parallel processing, MPI-based distributed training, automated hyperparameter tuning, and CNN optimization, implemented via scripts such as parallel_processing.py and mpi_distributed_processing.py, benchmark_parallel_training.py, and cnn_training_hpc.py, predict_image.py, parallel_tuning_simulation.py. The model is trained on a labeled MRI dataset with four classes: Mild Demented, Very Mild Demented, Moderate Demented, and Non-Demented. Performance is evaluated using prediction accuracy, execution time, and confusion matrix analysis. Speedup efficiency, analysed through Amdahl's Law, offers insights into scalability and computational limits. Efficiency graphs further illustrate trade-offs between computational cost and performance. This integrated HPC framework delivers accurate, fast, and scalable predictions, enhancing early diagnosis of Alzheimer's disease.**

Keywords—Alzheimer's Disease Prediction, High-Performance Computing (HPC), MRI Image Classification, Convolutional Neural Network (CNN), Parallel Processing, MPI (Message Passing Interface)

I. INTRODUCTION

Alzheimer's disease (AD) is a progressive neurodegenerative disorder that affects millions of people worldwide, with early detection being critical for effective intervention and treatment planning. Traditional diagnostic methods often rely on clinical assessments, cognitive tests, and manual analysis of neuroimaging data, which can be time-consuming, subjective, and less scalable for large populations. With the growing availability of medical imaging data, particularly Magnetic Resonance Imaging (MRI), there is an increasing need for automated and efficient computational systems to support early and accurate diagnosis. Recent advancements in deep learning, particularly Convolutional Neural Networks (CNNs), have shown promising results in the classification and analysis of medical images. These models can automatically learn complex patterns and features from raw image data, making them ideal for tasks such as Alzheimer's classification. However, training deep learning models on high-dimensional MRI datasets is computationally intensive and often suffers from issues related to processing time, memory consumption, and scalability—especially when working with large datasets or tuning complex models.

To overcome these challenges, this research integrates High-Performance Computing (HPC) techniques into the model development and deployment pipeline. By employing parallel processing, MPI-based distributed training, and automated hyperparameter tuning, we aim to significantly reduce training time and enhance model performance. The proposed system is built using a series of HPC-enabled modules (parallel_processing.py, parallel_tuning.py, mpi_distributed_processing.py, and cnn_training_hpc.py) and is trained on a publicly available MRI dataset containing four Alzheimer's-related categories: Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented.

The final model is capable of accurately predicting the Alzheimer's stage from unseen MRI images, offering a reliable and efficient solution for early disease detection. This research contributes to the growing body of work in medical image analysis by demonstrating how HPC frameworks can optimize deep learning workflows and improve diagnostic accuracy in real-world healthcare settings.

II. PROBLEM STATEMENT

Alzheimer's disease remains one of the most challenging neurodegenerative disorders to diagnose in its early stages due to the subtle progression of brain changes and the complexity of analysing high-dimensional neuroimaging data. Conventional machine learning approaches for classifying MRI brain scans often face limitations related to computational efficiency, scalability, and model accuracy, especially when processing large datasets with multiple disease stages. These challenges are further exacerbated by the need for extensive training time, manual hyperparameter tuning, and insufficient hardware optimization.

Moreover, the increasing volume of medical imaging data demands faster, more accurate, and automated prediction systems capable of supporting early diagnosis. There is a critical need for a solution that not only enhances model

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

performance but also reduces computational bottlenecks during the training and prediction phases.

This research addresses these challenges by proposing a High-Performance Computing (HPC)-based deep learning framework that leverages parallel processing, distributed training using MPI, and automated hyperparameter tuning to improve the classification of MRI images into four categories: Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented. The aim is to develop an optimized system that supports real-time, scalable, and accurate Alzheimer's disease prediction.

III. PROJECT GOALS

The primary aim of this research is to enhance the predictive accuracy and computational efficiency of Alzheimer's disease diagnosis by integrating advanced High-Performance Computing (HPC) techniques with deep learning models. Specifically, the project focuses on developing an HPC-optimized convolutional neural network (CNN) framework capable of classifying MRI brain scans into four Alzheimer's stages: Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented. This system leverages parallel processing, MPI-based distributed training, and automated hyperparameter tuning—implemented through dedicated scripts such as parallel_processing.py, predict_image, parallel_tuning.py, mpi_distributed_processing.py and cnn_training_hpc.py, benchmark_parallel_training.py to significantly reduce computation time while improving model performance. The framework is designed to optimize the training process for large-scale MRI datasets, enabling faster processing, better scalability, and real-time prediction capabilities. In addition, the model supports multi-class classification with high accuracy, allowing it to differentiate effectively between various stages of Alzheimer's progression. By minimizing manual trial-and-error in parameter selection and enhancing computational throughput, the proposed system serves as a scalable and efficient early detection tool for Alzheimer's disease, suitable for integration into clinical diagnostic workflows.

IV. SIGNIFICANCE OF THE PROJECT

The significance of this research lies in its potential to revolutionize the early and accurate diagnosis of Alzheimer's disease through the integration of High-Performance Computing (HPC) and deep learning. By addressing the challenges associated with processing high-dimensional MRI datasets, the proposed system leverages parallel processing, MPI-based distributed training, and automated hyperparameter tuning to significantly improve both computational efficiency and predictive accuracy. This combination allows for the rapid and reliable classification of MRI brain scans into four clinically relevant stages—Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented—enabling more precise diagnostic support. The scalable architecture of the system ensures real-time analysis capability, making it suitable for deployment in clinical settings that require timely interventions. Furthermore, the integration of HPC techniques reduces training time and optimizes CNN performance, allowing for more efficient handling of large-scale medical imaging data. By enhancing the speed, scalability, and diagnostic performance of Alzheimer's prediction models, this research contributes significantly to advancing AI-assisted medical diagnostics and supports improved patient care through early intervention.

V. SCOPE OF THE PROJECT

The scope of this project encompasses the development of an advanced, high-performance computing (HPC)-enabled deep learning framework for the classification of Alzheimer's disease stages using MRI brain scans. The system is designed to accurately categorize scans into four diagnostic stages—Non-Demented, Very Mild Demented, Mild Demented, and Moderate Demented—by training convolutional neural networks (CNNs) on labeled MRI datasets. To address the computational challenges posed by large-scale medical imaging data, the project integrates HPC techniques such as parallel processing, MPI-based distributed computing, and automated hyperparameter tuning, implemented through specialized scripts. These technologies significantly reduce execution time, enhance model training efficiency, and enable real-time prediction, making the system highly practical for clinical applications. Additionally, the project supports scalable deployment across various hardware environments and contributes to personalized medicine by facilitating early detection and stage-specific treatment planning. The system's modular and flexible design also provides a foundation for future research and broader medical imaging applications.

VI. ABBREVIATIONS, UNITS AND EQUATIONS

A. Abbreviations and Acronyms

ADP – Alzheimer's Disease Prediction
MPI – Message Passing Interface
CPU – Central Processing Unit
GPU – Graphics Processing Unit
HPPO – Hyperparameter Parallel Optimization
PP – Parallel Processing
RAM – Random Access Memory
FLOPs – Floating Point Operations Per Second
CNN – Convolution Neural Network
HPC – High-Performance Computing
SM – Shared Memory
DM – Distributed Memory
ROC – Receiver Operating Characteristic
AUC – Area Under Curve

B. Units

- **Prediction Accuracy** – Measured in Percentage
- **Loss Value** – Unitless
- **Processing / Execution Time** – Seconds (s)

- **Model Inference Time** – Milliseconds (ms)
- **Speedup Ratio** (HPC Performance) – Unitless (Speedup = T_1 / T_n)
- **Image Resolution** – Measured in Pixels (px)
- **Memory Usage** – Measured in Megabytes (MB) or Gigabytes (GB)
- **Learning Rate** – Unitless (hyperparameter tuning)
- **Batch Size** – Unitless (number of samples per gradient update)
- **Number of Epochs** – Unitless (iterations over the dataset)
- **Precision / Recall / F1-Score** – Percentage (%)
- **Confusion Matrix Elements** (TP, FP, TN, FN) – Unitless counts
- **Data Size** – Measured in Megabytes (MB) or Gigabytes (GB)

C. Equations

1) Evaluation Metrics (from Confusion Matrix):

Accuracy:

$$\frac{TP + TN}{TP + TN + FP + FN}$$

Evaluated in the context of MPI and multiprocessing (parallel_processing.py, parallel_tuning.py) to assess how efficiently cores/nodes are used. Helps in tuning workloads for optimal usage.

Precision:

$$\frac{TP}{TP + FP}$$

Calculated during model evaluation using cnn_training_hpc.py to assess how many positively predicted dementia stages (e.g., Mild Demented) are actually correct. This helps ensure that false positives are minimized, important for clinical decision-making.

Recall:

$$\frac{TP}{TP + FN}$$

Recall is computed to ensure early-stage dementia is not missed (low false negatives). High recall means the model successfully detects patients who truly belong to each stage, especially vital for early diagnosis in medical imaging.

F1-Score:

$$2 \times \frac{P \times R}{P + R}$$

Used as a balance between precision and recall. The F1-Score is computed in cnn_training_hpc.py during validation to give a comprehensive view of the model's performance, particularly when class imbalance is present.

2) Training and Performance Metrics:

Total Training Time:

$$T_{\text{total}} = N_{\text{epochs}} \times T_{\text{epoch}}$$

Unit: Seconds / Minutes / Hours

Measured in cnn_training_hpc.py using time logging. The usage of HPC (multi-GPU, DataLoader workers, etc.) reduces total training time significantly.

Throughput:

$$\text{Throughput} = \frac{\text{Total Samples}}{\text{Training Time}}$$

Unit: Images/Second

Throughput is monitored to assess how many MRI images are processed per second. Parallel loading in DataLoader and GPU acceleration in cnn_training_hpc.py maximizes throughput.

Model Parameters (CNN):

$$\text{Total Parameters} = \sum (C_{\text{in}} \times C_{\text{out}} \times K^2) + \text{Bias}$$

Unit: Count

Each CNN layer's trainable parameters are calculated and logged during model summary. Helps in understanding model complexity and memory needs.

FLOPs (Floating Point Operations per Layer):

$$\text{FLOPs} = 2 \times H \times W \times C_{\text{in}} \times C_{\text{out}} \times K^2$$

Unit: Giga FLOPs

Used for estimating compute cost per forward pass. Helps in optimizing model design for HPC environments to ensure feasible training on limited resources.

3) HPC Performance Metrics:

Amdahl's Law (Speedup with Parallelism):

$$S_{\max} = \frac{1}{(1-P) + \frac{P}{N}}$$

Where:

PPP: parallelizable portion

NNN: number of processors

Unit: Unitless (Speedup factor)

Used in mpi_distributed_processing.py to estimate the theoretical speedup when distributing computations across multiple nodes using MPI.

Parallel Efficiency:

$$E = \frac{T_{\text{sequential}}}{P \times T_{\text{parallel}}}$$

Unit: Unitless or %

Evaluated in the context of MPI and multiprocessing (parallel_processing.py, parallel_tuning.py) to assess how efficiently cores/nodes are used. Helps in tuning workloads for optimal usage.

CPU/GPU Utilization:

$$\text{Utilization } (\%) = \frac{\text{Active Time}}{\text{Total Time}} \times 100$$

Unit: Percentage (%)

Monitored during model training and inference using system utilities and PyTorch APIs. Ensures full utilization of resources when training CNN on GPU and performing parallel tasks.

Memory Usage:

$$\text{Memory Usage} = \frac{\text{Used Memory}}{\text{Total Memory}} \times 100$$

Unit: MB, GB, or %

Tracked using system monitors and libraries like psutil. Ensures memory constraints are respected during parallel preprocessing (parallel_processing.py) and training.

VII. BLOCK DIAGRAM



Fig. 1: HPC–Based Alzheimer's Disease Prediction from MRI Images

The process starts with input MRI data labeled into four classes. Preprocessing is done using parallel processing to prepare the data efficiently. Model training includes hyperparameter tuning and CNN optimization, both enhanced by parallel and distributed computing. MPI-based distributed training ensures scalability, while performance monitoring optimizes resource usage. The trained model undergoes evaluation using validation metrics, and then it predicts the Alzheimer's stage. The final diagnostic output delivers high-accuracy predictions, all powered by a high-performance computing (HPC) infrastructure.

VIII. ARCHITECTURE DIAGRAM



Fig. 2: Alzheimer's Disease Prediction from MRI Images using HPC and Deep Learning

The architecture for Alzheimer's Disease Prediction from MRI Images using HPC and Deep Learning starts with loading the MRI dataset, followed by preprocessing the images to prepare them for model training. The dataset is then divided into training and test sets. A deep learning model is defined and trained using high-performance computing (HPC) strategies to accelerate and optimize the process. These HPC strategies include parallel processing, CNN optimization, automated hyperparameter tuning, and MPI-based distributed training. Each strategy is implemented using specific Python scripts: parallel_processing.py, and cnn_training_hpc.py, parallel_tuning.py, and mpi_distributed_processing.py. The model is trained on labeled MRI data that is categorized into four classes: Mild Demented, Very Mild Demented, Moderate Demented, and Non-Demented. After training, the model's performance is evaluated, and it is used to predict the stage of Alzheimer's for new MRI scans. After training, the model is evaluated using metrics like accuracy, precision, recall, and F1-score.

The final output is a prediction with high accuracy, providing a powerful tool for early detection and diagnosis of Alzheimer's disease. Finally, new MRI scans are input into the trained model to predict the Alzheimer's stage with high accuracy, making the system suitable for potential clinical applications.

IX. SYSTEM REQUIREMENTS

Hardware Requirements:

Processor: Multi-core CPU
RAM: Minimum 16 GB (recommended for parallel processing)
Storage: SSD with at least 50 GB free space (for datasets and model files)
GPU: NVIDIA GPU with CUDA support for faster CNN training and inference
Internet Connectivity: Required for package installations and dataset access
Cluster/Node Access): For distributed MPI-based execution

Software Requirements:

Operating System: Windows 10/11 or Ubuntu 20.04+ (64-bit)
Development Environment: Visual Studio Code (VS Code) or Jupyter Notebook
Programming Language: Python 3.7 or higher
Libraries/Frameworks:

- NumPy, OpenCV, Matplotlib, Seaborn
- scikit-learn (for evaluation metrics)
- PyTorch (for CNN model training)
- multiprocessing, mpi4py (for HPC implementation)
- torchvision (for data transformations)

CUDA Toolkit: Required if GPU acceleration is used

Dataset Requirements:

Input Data: MRI brain scan images labeled under four categories:

1. Non-Demented
2. Very Mild Demented
3. Mild Demented
4. Moderate Demented

Format: JPEG/PNG images

Functional Capabilities Required:

Ability to run parallel scripts:

parallel_processing.py
parallel_tuning.py
mpi_distributed_processing.py
cnn_training_hpc.py
predict_image.py

Real-time prediction of Alzheimer's stage from MRI input

Model performance evaluation using confusion matrix, accuracy, precision, and recall, F1 score

X. LITERATURE SURVEY

[1] Adaptive 3DCNN-Based Interpretable Ensemble Model for Early Diagnosis of Alzheimer's Disease

This paper presents an adaptive ensemble model, 3DCNN+EL+GA, combining 3D Convolutional Neural Networks and Genetic Algorithms for early Alzheimer's and MCI diagnosis. It outperforms existing deep learning methods on ADNI and OASIS datasets. The model identifies key brain regions contributing to classification using gradient-based attribution. These regions are linked to behavioral domains affected early in AD. The approach may also extend to diagnosing other brain disorders using neuroimaging data.

[2] Risk Prediction of Alzheimer's Disease Conversion in Mild Cognitive Impaired Population Based on Brain Age Estimation

This study proposes a Conversion Risk Estimation System (CRES) to predict Alzheimer's disease (AD) risk in Mild Cognitive Impairment (MCI) patients using MRI-based brain age estimation. CRES distinguishes between NC, sMCI, pMCI, and AD groups based on age gap (AG). A significant correlation is found: each extra AG year increases AD conversion risk by 4.57%. The model also incorporates gender and MMSE for accurate risk analysis. A nomogram provides personalized risk predictions up to 8 years from baseline.

[3] Leveraging Brain MRI for Biomedical Alzheimer's Disease Diagnosis Using Enhanced Manta Ray Foraging Optimization Based Deep Learning

This research introduces the ADD-EMRFODL model for Alzheimer's Disease (AD) diagnosis using brain MRI and deep learning. The method begins with Gabor Filtering (GF) for preprocessing, followed by feature extraction using DenseNet-121. A Back Propagation Neural Network (BPNN) is used for classification, with its parameters optimized through Enhanced Manta Ray Foraging Optimization (EMRFO). This eliminates the need for manual feature extraction and improves diagnostic efficiency. Experimental results demonstrate that the ADD-EMRFODL model achieves superior classification accuracy compared to existing techniques.

The use of EMRFO for optimizing BPNN parameters further boosts classification accuracy, ensuring robust and reliable Alzheimer's diagnosis from MRI scans.

[4] Deep Learning-Based Diagnosis of Alzheimer's Disease Using Structural Magnetic Resonance Imaging: A Survey

This paper presents an Alzheimer's Disease (AD) is the most prevalent form of dementia, and early diagnosis is key to delaying its progression. Structural MRI (sMRI) is effective in detecting brain abnormalities associated with AD. With advancements in deep learning, numerous models have been applied to sMRI for AD detection with promising results. This paper reviews deep learning approaches categorized by input type, highlighting their strengths and limitations. It also discusses current challenges and proposes future research directions for improving AD diagnosis using deep learning.

[5] Graph-based deep learning models in the prediction of early-stage Alzheimer's

This study explores early-stage Alzheimer's prediction using graph-based deep learning models on rs-fMRI data. A comparative analysis of rs-fMRI time points and functional connectivity (FC) reveals FC's superior predictive value. A novel graph transformer with self-clustering enhances classification accuracy. Experiments on 830 subjects from the ADNI dataset validate the model's effectiveness. Results highlight the potential of clustering-based attention in advancing Alzheimer's diagnosis.

[6] Advancements in High-Performance Computing in Early Diagnosis of Alzheimer's Disease: A Systematic Review

This paper Alzheimer's disease (AD) involves complex neurodegenerative changes like amyloid beta plaques and tau tangles. High-Performance Computing (HPC) plays a vital role in modeling these complexities for early diagnosis. This systematic review analyzes 298 studies from 2014–2023 focusing on HPC applications in AD research. It highlights how HPC enhances diagnostic speed, visualization, and brain simulations. The review also identifies ongoing efforts and challenges in leveraging HPC for AD detection and treatment.

[7] Transfer Learning for Classification of Alzheimer's Disease Based on Genome wide Data

This paper addresses the early diagnosis of Alzheimer's Disease (AD), a progressive neurodegenerative disorder, by analysing genome-wide data using advanced machine learning techniques. It emphasizes the significance of Single Nucleotide Polymorphisms (SNPs) as critical biomarkers for identifying genetic susceptibility to AD.

The study introduces a deep transfer learning approach where a Convolutional Neural Network (CNN) is initially trained on one GWAS dataset to learn generic genomic features and is subsequently fine-tuned on another dataset to capture AD-specific patterns. These refined features are then input into a Support Vector Machine (SVM) classifier for final prediction. The combined CNN-SVM model achieves an accuracy of 89%, outperforming conventional classification methods and demonstrating the effectiveness of integrating deep learning with traditional machine learning for genetic-based disease classification.

[8] Diagnosis and Detection of Alzheimer's Disease Using Learning Algorithm

This study focuses on Alzheimer's disease (AD) detection using learning algorithms and pre-processed MRI data. Brain scans from the ADNI dataset were transformed from 4D to 2D and enhanced using techniques like clipping, grayscale conversion, and histogram equalization. Three models—Random Forest, XGBoost, and CNN—were applied for classification. The proposed approach improved both training efficiency and diagnostic accuracy. It achieved 97.57% accuracy and 97.60% sensitivity, outperforming existing methods.

[9] Classification of Alzheimer's Disease using Ensemble Convolutional Neural Network with LFA Algorithm

This paper proposes an ensemble CNN model for Alzheimer's disease (AD) classification based on MRI brain shape features. The model integrates VGGNet with a 1D CNN using Line Segment Feature Analysis (LFA) to capture brain shape characteristics. LFA transforms MRI line segment data into vectors, enhancing feature representation. The combined features from VGGNet and LFA improve classification accuracy. Experimental results on Kaggle MRI data show superior performance with 98.6% accuracy and 0.0385 loss.

[10] Improving Alzheimer's Detection with Deep Learning and Image Processing Techniques

This study enhances Alzheimer's Disease (AD) detection using advanced image processing and deep learning techniques on brain MRI scans. CLAHE and ESRGAN are applied to improve image contrast and resolution. An ensemble of MobileNetV2 and DenseNet121 is used for classification. Image enhancements significantly improved accuracy, with MobileNetV2 reaching 92.34% and DenseNet121 89.38%. Results demonstrate the effectiveness of combining preprocessing and deep learning for early AD diagnosis.

XI. EXPERIMENTAL RESULTS

```
PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL    PORTS

PS C:\Users\kousa\OneDrive\Desktop\alzhimers> & C:/Python312/python.exe c:/Users/kousa/
OneDrive/Desktop/alzhimers/parallel_processing.py

Starting parallel processing with 4 cores...

--- Processing Summary ---
Total images processed: 6400
Total time taken: 8.08 seconds
Average time per image: 0.0032 seconds

Average time per class:
Class
MildDemented        0.002543
ModerateDemented    0.002571
NonDemented         0.003114
VeryMildDemented    0.003475
Name: Time, dtype: float64

Starting parallel processing with 8 cores...

--- Processing Summary ---
Total images processed: 6400
Total time taken: 8.27 seconds
Average time per image: 0.0047 seconds

Average time per class:
Class
ModerateDemented    0.003706
VeryMildDemented    0.004492
NonDemented         0.004697
MildDemented        0.005191
Name: Time, dtype: float64
```

```
PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL    PORTS

Starting parallel processing with 12 cores...

--- Processing Summary ---
Total images processed: 6400
Total time taken: 9.23 seconds
Average time per image: 0.0065 seconds

Average time per class:
Class
ModerateDemented    0.004796
VeryMildDemented    0.005608
NonDemented         0.006849
MildDemented        0.007423
Name: Time, dtype: float64

Starting parallel processing with 16 cores...

Name: Time, dtype: float64

Starting parallel processing with 16 cores...

--- Processing Summary ---
Total images processed: 6400
Total time taken: 10.76 seconds
Average time per image: 0.0091 seconds

Average time per class:
Class
ModerateDemented    0.005948
MildDemented        0.007029
VeryMildDemented    0.007867
Name: Time, dtype: float64
```

Fig. 3: parallel_processing.py

OUTPUT:



```
PS C:\Users\kousa\OneDrive\Desktop\alzhimers> & C:/Python312/python.exe c:/Users/kousa/
OneDrive/Desktop/alzhimers/parallel_tuning_simulation.py
Config: LR=0.001, Batch=32 => Accuracy=0.8311
Config: LR=0.001, Batch=64 => Accuracy=0.8208
Config: LR=0.0001, Batch=32 => Accuracy=0.7671
Config: LR=0.0001, Batch=64 => Accuracy=0.8101
```

Fig. 4: parallel_tuning_simulation.py

The image shows the output of a Python script (parallel_tuning_simulation.py) used for hyperparameter tuning in a machine learning model, specifically evaluating different learning rate and batch size configurations. The script was executed in a Windows PowerShell environment using Python 3.12. Results indicate that a learning rate (LR) of 0.001 with a batch size of 32 achieved the highest accuracy (0.8311), followed by similar configurations. Lower learning rates (0.0001) showed reduced performance. This Output highlights how parallel tuning helps in identifying optimal training parameters for improved model accuracy in classification tasks, such as those related to Alzheimer's research.

mpi_distributed_processing.py

OUTPUT:

Fig. 6: Work Distribution across each Process



Fig. 7: Speedup vs Cores

The graph shows how efficiency varies with the number of CPU cores. Efficiency increases from 4 to 8 cores, peaking at 8, but then declines as more cores are added. This suggests that while parallelism helps initially, too many cores can reduce efficiency due to overhead and resource contention.



Fig. 8: Efficiency vs Cores

The graph shows that efficiency improves as the number of cores increases from 4 to 8, but drops significantly when more than 8 cores are used. This indicates that adding too many cores can reduce performance due to system overhead.



Fig. 9: Amdahl's Law vs Cores

The graph illustrates the application of Amdahl's Law, showing how speedup improves with an increasing number of processor cores. The speedup rises significantly from 4 to 16 cores but with diminishing returns, indicating a saturation point due to the serial fraction of the workload. This confirms the theoretical limit on parallel performance gains in multi-core systems.



Fig. 10: Model Accuracy vs Cores

The graph illustrates that as the number of cores increases, the model accuracy tends to decrease. Accuracy slightly drops from 0.89% at 4 cores to 0.87% at 8 cores, but falls sharply to 0.73% at 12 cores. A minor improvement to 0.74% is observed at 16 cores, indicating that higher core counts may introduce parallelism overhead, affecting model performance.

```
PS C:\Users\kousa\OneDrive\Desktop\alzhimers> & C:/Python312/python.exe c:/Users/kousa/
OneDrive/Desktop/alzhimers/cnn_training_hpc.py
Epoch 1/10, Loss: 1.0197
Accuracy: 0.5539, Precision: 0.5837, Recall: 0.5539, F1 Score: 0.5489
Epoch 2/10, Loss: 0.8070
Accuracy: 0.6930, Precision: 0.7214, Recall: 0.6930, F1 Score: 0.6619
Epoch 3/10, Loss: 0.4250
Accuracy: 0.8891, Precision: 0.8927, Recall: 0.8891, F1 Score: 0.8897
Epoch 4/10, Loss: 0.1704
Accuracy: 0.9414, Precision: 0.9415, Recall: 0.9414, F1 Score: 0.9414
Epoch 5/10, Loss: 0.0607
Accuracy: 0.9594, Precision: 0.9606, Recall: 0.9594, F1 Score: 0.9595
Epoch 6/10, Loss: 0.0182
Accuracy: 0.9367, Precision: 0.9435, Recall: 0.9367, F1 Score: 0.9370
Epoch 7/10, Loss: 0.0067
Accuracy: 0.9828, Precision: 0.9830, Recall: 0.9828, F1 Score: 0.9828
Epoch 8/10, Loss: 0.0023
Accuracy: 0.9820, Precision: 0.9822, Recall: 0.9820, F1 Score: 0.9820
Epoch 9/10, Loss: 0.0011
Accuracy: 0.9844, Precision: 0.9845, Recall: 0.9844, F1 Score: 0.9844
Epoch 10/10, Loss: 0.0007
Accuracy: 0.9844, Precision: 0.9844, Recall: 0.9844, F1 Score: 0.9844
```

Fig. 11: cnn_training_hpc.py

OUTPUT:



Fig. 12: Confusion Matrix Heatmap

The confusion matrix heatmap illustrates the classification performance across four dementia categories. High values along the diagonal indicate strong model accuracy, particularly for NonDemented (617 correct) and VeryMildDemented (474 correct) classes. Minimal misclassifications suggest robust and reliable diagnostic predictions by the model.



Fig. 13: Model Performance Over Epoch

The graph shows the model's performance metrics—accuracy, precision, recall, and F1 score—across training epochs. All metrics improve rapidly in the initial epochs and stabilize around epoch 6, indicating convergence. This trend confirms effective learning and consistent generalization capability of the model over time.

WEBPAGE FOR ALZHEIMER DETECTION USING HPC AND DEEP LEARNING (FRONT END)



TABLE FORMAT:

Loss	Accuracy	Precision	Recall	F1 Score
1.0934	**0.5602**	**0.5403**	**0.5602**	**0.5026**
0.9040	**0.5930**	**0.7307**	**0.5930**	**0.5662**
0.7377	**0.7297**	**0.7422**	**0.7297**	**0.7123**
0.5053	**0.7727**	**0.8050**	**0.7727**	**0.7598**
0.3392	**0.8602**	**0.8671**	**0.8602**	**0.8607**
0.2142	**0.8914**	**0.8954**	**0.8914**	**0.8903**
0.1514	**0.8969**	**0.9128**	**0.8969**	**0.8983**
0.0956	**0.9391**	**0.9491**	**0.9391**	**0.9393**
0.0539	**0.9602**	**0.9615**	**0.9602**	**0.9603**
0.0276	**0.9695**	**0.9696**	**0.9695**	**0.9695**

CONCLUSION:

This research demonstrates the effectiveness of integrating High-Performance Computing (HPC) strategies into the deep learning pipeline for Alzheimer's disease classification using MRI scans. By leveraging parallel processing, MPI-based distributed training, and automated hyperparameter tuning, the system achieved significant gains in both computational efficiency and model performance. The CNN model trained through the cnn_training_hpc.py script achieved a high accuracy of 96.95% with an F1 Score of 0.9695 by the 10th epoch. This indicates strong model generalization and balanced classification across the four Alzheimer's stages: Mild Demented, Very Mild Demented, Moderate Demented, and Non-Demented. The progressive improvement in training metrics across epochs—such as precision, recall, and F1 score—reflects the stability and robustness of the proposed architecture and training methodology. The reduction in loss from 1.0934 in epoch 1 to 0.0276 in epoch 10 further supports the model's convergence and efficacy. By combining HPC methods with deep learning, this work provides a scalable and time-efficient solution for early Alzheimer's diagnosis. Such a system has strong potential for deployment in clinical environments, enabling faster and more accurate screening, especially in large-scale medical imaging datasets.

XII. REFERENCES

[1] D. Pan *et al.*, "Adaptive 3DCNN-Based Interpretable Ensemble Model for Early Diagnosis of Alzheimer's Disease," in *IEEE Transactions on Computational Social Systems*, vol. 11, no. 1, pp. 247-266, Feb. 2024
DOI: 10.1109/TCSS.2022.3223999

[2] W. Liu, Q. Dong, S. Sun, J. Shen, K. Qian and B. Hu, "Risk Prediction of Alzheimer's Disease Conversion in Mild Cognitive Impaired Population Based on Brain Age Estimation," in *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, vol. 31, pp. 2468-2476, 2023
DOI: 10.1109/TNSRE.2023.3247590

[3] R. S. Jamalullah *et al.*, "Leveraging Brain MRI for Biomedical Alzheimer's Disease Diagnosis Using Enhanced Manta Ray Foraging Optimization Based Deep Learning," in *IEEE Access*, vol. 11, pp. 81921-81929, 2023
DOI: 10.1109/ACCESS.2023.3294711

[4] T. Wang and L. Cao, "Deep Learning Based Diagnosis of Alzheimer's Disease Using Structural Magnetic Resonance Imaging: A Survey," *2021 3rd International Conference on Applied Machine Learning (ICAML)*, Changsha, China, 2021
DOI: 10.1109/ICAML54311.2021.00092

[5] B. Thapaliya *et al.*, "Graph-based deep learning models in the prediction of early-stage Alzheimer's," *2024 46th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, Orlando, FL, USA, 2024
DOI: 10.1109/EMBC53108.2024.10782267

[6] A. Kirimtat, O. Krejcar, P. Maresova, A. Selamat and K. Kuca, "Advancements in High-Performance Computing in Early Diagnosis of Alzheimer's Disease: A Systematic Review," in *IEEE Access*, vol. 12, pp. 156492-156504, 2024
DOI: 10.1109/ACCESS.2024.3484928

[7] A. S. Alatrany, W. Khan, A. J. Hussain, J. Mustafina, D. Al-Jumeily and for the Alzheimer's Disease Neuroimaging Initiative, "Transfer Learning for Classification of Alzheimer's Disease Based on Genome wide Data," in *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, vol. 20, no. 5, pp. 2700-2711, 1 Sept.-Oct. 2023
DOI: 10.1109/TCBB.2022.3233869

[8] G. P. Shukla, S. Kumar, S. K. Pandey, R. Agarwal, N. Varshney and A. Kumar, "Diagnosis and Detection of Alzheimer's Disease Using Learning Algorithm," in *Big Data Mining and Analytics*, vol. 6, no. 4, pp. 504-512, December 2023
DOI: 10.26599/BDMA.2022.9020049

[9] C. -M. Kim and W. Lee, "Classification of Alzheimer's Disease Using Ensemble Convolutional Neural Network with LFA Algorithm," in *IEEE Access*, vol. 11, pp. 143004-143015, 2023
DOI: 10.1109/ACCESS.2023.3342917

[10] G. N. Alwakid, S. Tahir, M. Humayun, W. Gouda, "Improving Alzheimer's Detection with Deep Learning and Image Processing Techniques," in *IEEE Access*, vol. 12, pp. 153445-153456, 2024
DOI: 10.1109/ACCESS.2024.3481238