



800 S. Polk, Suite 103
Amarillo, Texas 79109
(806) 779-2461

ACH Transaction Status API

Integration Guide

Version 1.0 | May 2026

CONFIDENTIAL



Contents

Contents

Contents	2
1. Introduction	4
Relationship to the Upload API	4
Who should read this guide	4
2. Getting Started	5
Prerequisites.....	5
Base URL	5
Authentication	5
3. Choosing a Query Method	6
File ID lookup	6
File name lookup	6
Date range lookup	6
4. Filtering Results	7
Example: date range with trace filter	7
Example: file ID with individual ID filter.....	7
5. Understanding the Response	8
Successful response (200 OK)	8
File-level fields	8
Entry-level fields.....	9
Event fields	10
6. Entry Lifecycle and Status Values	11
Returned event details	11
On-us entries	12
7. Error Reference	13
Error response format.....	13



Authentication and authorization errors	13
Query validation errors.....	13
Data errors.....	14
8. Best Practices	15
Choosing a query method	15
Polling for updates.....	15
Reconciliation	16
Error handling.....	16
Security	16
9. Limits and Configuration	17
10. Support.....	18

1. Introduction

BOC Bank provides a read-only RESTful API for querying the lifecycle status of ACH transactions submitted through the ACH File Upload API. This guide covers everything you need to integrate with the Transaction Status endpoint, including authentication, query methods, response interpretation, and error handling.

The Status API allows you to look up files and individual entries by file ID, file name, or date range. Each entry includes its full event history—from initial receipt through transmission, settlement, or return—so you always have a complete picture of where your transactions stand.

Relationship to the Upload API

The Status API is the read counterpart of the Upload API. The file ID returned in your upload response is the primary key for status lookups. Both endpoints share the same authentication infrastructure (API keys, network allowlisting, organization configuration), but require separate roles on your API key: Ach.Upload for uploads and Ach.Status for status queries.

Who should read this guide

This guide is intended for developers and technical staff responsible for building reconciliation, reporting, or monitoring features on top of BOC Bank's ACH services. Familiarity with RESTful APIs and the ACH File Upload API is assumed.

2. Getting Started

Prerequisites

Before you begin, ensure the following are in place:

- Your organization has been onboarded with BOC Bank and has an active ACH configuration.
- You have received your API key from BOC Bank. Keys follow the format `boc_XXXXXXXX_...` and should be stored securely.
- Your API key has been granted the `Ach.Status` role. A single key can hold both `Ach.Upload` and `Ach.Status` roles.
- Your server's public IP address has been registered with BOC Bank for network allowlisting (if applicable).

Base URL

Your BOC Bank representative will provide the production base URL during onboarding. All API calls use HTTPS (TLS 1.2 or higher is required). The status endpoint path is:

```
GET /api/v1/ach/status
```

Authentication

Every request must include your API key in the `X-API-Key` header. The API key is the sole authentication mechanism. No additional tokens, sessions, or OAuth flows are required.

```
X-API-Key: boc_XXXXXXXX_your_secret_key_here
```

Your key is tied to your organization and determines which files and entries you can query. You can only see data belonging to your own organization—there is no way to access another organization's files through this endpoint.

Note: If you already have an API key for the Upload API, contact BOC Bank to have the `Ach.Status` role added to your existing key. There is no need for a separate key.

3. Choosing a Query Method

The Status API supports three ways to look up your ACH files and entries. You must use exactly one of these methods per request—they cannot be combined.

Method	Parameter	Use when
File ID	fileId	You want the status of a specific file and you have its BOC file ID (e.g., F-00123) from your upload response.
File Name	fileName	You want to look up a file using the original file name you submitted at upload (e.g., rent_20260507.ach).
Date Range	fromDate + toDate	You want to see all files received within a date range for reconciliation or end-of-period reporting.

File ID lookup

Pass the file ID returned in your upload response. The ID must be in the F-{number} format (e.g., F-00123). This is the most direct lookup method.

```
GET /api/v1/ach/status?fileId=F-00123
```

File name lookup

Pass the file name you provided in the x-file-name header at upload time. If you uploaded a file named rent_20260507.ach, you can query its status using that same name.

```
GET /api/v1/ach/status?fileName=rent_20260507.ach
```

Date range lookup

Provide a start date and end date (inclusive) to retrieve all files your organization uploaded within that period. Both dates are required, and the range may not exceed 90 days.

```
GET /api/v1/ach/status?fromDate=2026-05-01&toDate=2026-05-31
```

Note: Dates are in local Central time (matching the BOC Bank system convention). If no files were uploaded during the specified range, the response will contain an empty files array—this is a valid 200 response, not an error.

4. Filtering Results

In addition to the query method, you can narrow your results using optional filters. Filters must always be combined with one of the three query methods—they cannot be used alone.

Filter	Parameter	Description
Trace Number	traceNumber	Matches entries by either the trace number you submitted at upload or the bank-assigned outbound trace number.
Individual ID	individualId	Matches entries by the Individual Identification field from your NACHA entry detail records (positions 40–54).

Example: date range with trace filter

```
GET /api/v1/ach/status?fromDate=2026-05-01&toDate=2026-05-31
    &traceNumber=091000010000001
```

This returns all files from May 2026, but only includes entries whose trace number matches 091000010000001. Files that have no matching entries will still appear in the response with an empty items array.

Example: file ID with individual ID filter

```
GET /api/v1/ach/status?fileId=F-00123
    &individualId=UNIT-101
```

This returns file F-00123, but only includes entries where the Individual ID matches UNIT-101.

5. Understanding the Response

Successful response (200 OK)

A successful status query returns a JSON object containing an array of files, each with its entries and their event histories:

```
{
  "files": [
    {
      "fileId": "F-00123",
      "fileName": "rent_20260507.ach",
      "status": "Accepted",
      "receivedDate": "2026-05-07T14:32:11",
      "totalEntries": 42,
      "totalDebitAmount": 52500.00,
      "items": [
        {
          "bankReference": "BPY-98765",
          "customerTraceNumber": "111308440000001",
          "assignedOutboundTraceNumber": "091000014000001",
          "individualId": "UNIT-101",
          "individualName": "JOHN Q TENANT",
          "amount": 1250.00,
          "transactionCode": "27",
          "effectiveDate": "2026-05-10",
          "currentStatus": "Transmitted",
          "events": [
            { "eventType": "Received", "eventDate": "2026-05-07T14:32:11",
"eventData": null },
            { "eventType": "Accepted", "eventDate": "2026-05-07T16:00:00",
"eventData": null },
            { "eventType": "Transmitted", "eventDate": "2026-05-08T02:15:00",
"eventData": null }
          ]
        }
      ]
    }
  ]
}
```

File-level fields

Field	Description
fileId	BOC file identifier in F-{number} format. Matches the upload response.



fileName	Original file name from upload. May be absent if no x-file-name header was provided.
status	File-level status: Received, Accepted, or Rejected.
receivedDate	Timestamp when BOC Bank received the file (local Central time).
totalEntries	Number of entry detail records parsed from the file. Absent from JSON when not yet calculated.
totalDebitAmount	Sum of all debit entry amounts in dollars. Absent from JSON when not yet calculated.
totalCreditAmount	Sum of all credit entry amounts in dollars. Absent from JSON when not applicable.
items	Array of individual entry statuses. May be empty if filters excluded all entries.

Entry-level fields

Field	Description
bankReference	BOC bank reference in BPY-{number} format. Same as the upload response.
customerTraceNumber	Trace number you submitted in the NACHA file.
assignedOutboundTraceNumber	Bank-assigned trace for the outbound NACHA file. Null until the entry is transmitted. Also null for on-us entries (settled internally without going through the Fed).
individualId	Individual Identification from your entry detail (NACHA positions 40–54).
individualName	Payee name from your entry detail (NACHA positions 55–76).
amount	Entry amount in dollars, always positive. The direction (debit or credit) is indicated by transactionCode.
transactionCode	NACHA transaction code: 27 = checking debit, 22 = checking credit, 37 = savings debit, 32 = savings credit.
effectiveDate	Effective entry date from your NACHA file (YYYY-MM-DD).
currentStatus	The most recent event type for this entry (e.g., Transmitted, Settled, Returned).
events	Complete event history in chronological order, oldest first.



Event fields

Field	Description
eventType	The lifecycle event: Received, Accepted, Rejected, Transmitted, Settled, Returned, or NOCApplied.
eventDate	Timestamp when the event occurred (local Central time).
eventData	Additional event detail as a JSON object. Present for Returned events (carries the return code and description). Null for most other events.

6. Entry Lifecycle and Status Values

Each ACH entry moves through a series of lifecycle stages after it is uploaded. The `currentStatus` field on each entry reflects the most recent event.

Status	Meaning	Typical timing
Received	The file has been uploaded and the entry parsed from the NACHA file.	Immediate (synchronous with upload)
Accepted	The file passed validation and was approved by a bank administrator.	Generally by 3:00–3:30 PM Central
Rejected	Bank admin rejected the file, or the entry failed a pre-transmission check (e.g., NSF).	Generally by 3:00–3:30 PM Central
Transmitted	The entry was included in an outbound NACHA file sent to the Federal Reserve.	Generally 3:30–4:00 PM Central, no later than 5:00 PM
Settled	The return window has passed with no return received. Funds are considered settled.	T+2 business days after transmission
Returned	The receiving bank returned the entry (e.g., insufficient funds, account closed). The <code>eventData</code> field contains the return code.	T+1 to T+2 business days
NOCApplied	A Notification of Change was received with corrected account information for future transactions.	T+1 to T+2 business days

Returned event details

When an entry is returned, the events array will include a Returned event with an `eventData` object containing the reason:

```
{
  "eventType": "Returned",
  "eventDate": "2026-05-12T09:15:00",
  "eventData": {
    "returnCode": "R01",
    "returnDescription": "Insufficient Funds",
    "originalTrace": "091000014000001",
    "amount": 1250.00
  }
}
```



On-us entries

Entries between two accounts at BOC Bank (on-us transactions) are settled internally without being transmitted to the Federal Reserve. These entries will show a Settled status but the assignedOutboundTraceNumber field will remain null. This is normal and expected behavior.

Note: A returned entry will not settle. An NOC can be received on either a settled or unsettled entry and indicates corrected information for future transactions—it does not affect the current transaction.

7. Error Reference

When a status query fails, the response includes an HTTP status code and a JSON body in RFC 9457 Problem Details format with an error code and human-readable message.

Error response format

```
{
  "type": "https://tools.ietf.org/html/rfc9110#section-15.5.1",
  "title": "Bad Request",
  "status": 400,
  "detail": "Human-readable description of what went wrong.",
  "error": "INVALID_QUERY",
  "requestId": "0HN8....",
  "traceId": "4bf92f3577b34da6a3ce929d0e0e4736"
}
```

Authentication and authorization errors

HTTP	Error Code	Meaning	What to do
401	MISSING_API_KEY	No X-API-Key header was provided.	Include your API key in the X-API-Key header.
401	INVALID_API_KEY	Key not recognized, revoked, or inactive.	Verify the key is correct. Contact BOC Bank if revoked.
401	API_KEY_EXPIRED	Key has passed its expiration date.	Contact BOC Bank to issue a new key.
403	NETWORK_RESTRICTED	Your IP is not in the allowed range for this key.	Verify you are calling from the registered IP.
403	ACH_NOT_CONFIGURED	No active ACH configuration for your organization.	Contact BOC Bank to complete ACH setup.
403	(standard)	Key lacks the Ach.Status role.	Contact BOC Bank to add Ach.Status to your key.

Query validation errors

HTTP	Error Code	Condition
400	INVALID_QUERY	An unrecognized query parameter was included (e.g., a typo like ?fileid instead of ?fileld).
400	INVALID_QUERY	The fileld is not in F-{number} format (e.g., passing 123 instead of F-00123).

400	INVALID_QUERY	No query method was supplied (no fileId, fileName, or date range).
400	INVALID_QUERY	Only one of fromDate or toDate was provided (both are required together).
400	INVALID_QUERY	Multiple query methods were combined (e.g., fileId with fileName).
400	INVALID_QUERY	The toDate is before the fromDate.
400	INVALID_QUERY	The date range exceeds 90 days.
400	INVALID_QUERY	A filter (traceNumber or individualId) was used without a query method.

Data errors

HTTP	Error Code	Condition	What to do
404	FILE_NOT_FOUND	The fileId or fileName did not match any file for your organization.	Verify the file ID or name. This also occurs if the file belongs to a different organization.
400	RESULT_SET_TOO_LARGE	The query would return more than 1,000 entries.	Narrow your query using a smaller date range, a specific file ID, or add a trace/individual filter.

Note: When a file ID or file name lookup fails, the 404 response echoes back the value you supplied so you can confirm what was sent. When a date range returns no files, the response is a successful 200 with an empty files array—not a 404.

8. Best Practices

Choosing a query method

- Use fileId for immediate post-upload confirmation of a specific file. This is the fastest and most precise lookup.
- Use fileName when you need to look up a file using identifiers you already track internally, such as your file naming convention.
- Use a date range for end-of-day or end-of-period reconciliation across all uploads. Keep the range as narrow as practical to stay within the 1,000-entry limit.

Polling for updates

Most organizations submit one ACH file per day. The typical lifecycle for a submitted file follows a predictable daily timeline:

- After uploading a file, the initial status will be Received. A bank administrator will review the file and either accept or reject it. This review is typically completed by 3:00–3:30 PM Central time on the day the file is uploaded.
- Once the file is accepted, it will be included in the next outbound NACHA file to the Federal Reserve. File transmission typically occurs between 3:30 PM and 4:00 PM Central time. In some cases, transmission may take longer but should be complete before 5:00 PM Central.
- Settlement detection occurs at T+2 business days after transmission. Schedule a reconciliation check at the end of each business day to catch new Settled and Returned events.

Given this timeline, a reasonable polling strategy is:

- Check once after upload to confirm the file was received successfully.
- Check again around 3:00 PM Central to see whether the file has been accepted or rejected.
- If accepted, check again around 4:00 PM Central to confirm the file has been transmitted. If it has not yet moved to Transmitted, check once more at 5:00 PM.
- For settlement and return monitoring, check once per business day at end-of-day (starting T+2 after transmission).
- Do not poll more frequently than once per minute. The endpoint is rate-limited per your organization's configuration.

Reconciliation

- The bankReference (BPY-{number}) returned on each entry can be used to correlate entries with your internal records, but it is not a queryable parameter on the Status API.
- Use the customerTraceNumber to correlate entries back to your original NACHA file records.
- The assignedOutboundTraceNumber links to the Federal Reserve's outbound file—use this when communicating with receiving banks about specific transactions.
- For daily reconciliation, query by date range (e.g., yesterday's date) and compare the results against your records.

Error handling

- Always check the HTTP status code first. A 200 means the query succeeded (even if the files array is empty).
- Parse the error code from the JSON response body for programmatic error handling.
- For RESULT_SET_TOO_LARGE errors, narrow your query. Use a smaller date range or add a trace/individual filter.
- Save the requestId and traceId from any error response—these are essential for BOC Bank support to investigate issues.

Security

- Store your API key securely. Never embed it in client-side code or commit it to source control.
- Use HTTPS for all API calls. The API enforces TLS 1.2 or higher.
- The status endpoint is read-only—it cannot modify, create, or delete any data.

9. Limits and Configuration

The following limits apply to the Status API. Contact your BOC Bank representative if you need adjustments.

Parameter	Value	Description
Maximum entries per response	1,000	If a query would return more than 1,000 entries, a <code>RESULT_SET_TOO_LARGE</code> error is returned. Narrow your query.
Maximum date range	90 days	The <code>fromDate-to-toDate</code> span may not exceed 90 calendar days.
Time zone	Central (local)	All dates and timestamps are in local Central time. There is no UTC indicator in the response.
Rate limiting	Per organization	Configured during onboarding. Do not exceed your allowed request rate.

10. Support

If you encounter issues during integration or production use, contact BOC Bank through your designated relationship manager or the channels provided during onboarding.

When reporting an issue, please include:

- The full HTTP status code and error code from the response.
- The requestId and traceId from the error response (included in every error payload).
- The query parameters you used (fileId, fileName, or date range).
- The approximate date and time of the request.

This document is confidential and intended solely for the use of the organization to which it is addressed. Unauthorized distribution or reproduction is prohibited.