





Bootstrap

부트스트랩(Bootstrap)

- 반응형 웹사이트 제작을 위한 프론트엔드 <u>프레임워크</u>
 - HTML, CSS 기반 디자인 템플릿과 JavaScript 플러인 포함

■ 탄생 배경

- 서로 다른 인터페이스를 사용한 여러 개발자들의 공동 작업
- 디자인 불일치, 관리 어려움, 방대한 코드량 → 일관성 유지 불가
- 문제점 개선을 위해 트위터의 개발자와 UI 디자이너가 개발
- 2011년 8월 깃허브 오픈

■ 오픈 소스, 상업적 이용 가능

부트스트랩의 장점

Easy to use

• HTML, CSS 기본지식을 가진 누구나 쉽게 접근이 가능

Responsive features:

• 반응형 CSS를 포함한 단일코드로 모든 디바이스에 적용 가능

Mobile-first approach

• 부트스트랩3 부터 모바일 겸용이 아닌 , 모바일 퍼스트 정책 반영

Browser compatibility

• 모든 최신 브라우저와 호환 (크롬 파이어 폭스, 인터넷 익스플로러, 사파리, 오페라)


부트스트랩 설치

Include Bootstrap 5 from a CDN(Content Delivery Network)

```
<!-- Latest compiled and minified CSS -->
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
<!-- Latest compiled JavaScript -->
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>
```

- Download Bootstrap 5 from getbootstrap.com
 - https://getbootstrap.com/docs/5.3/getting-started/download/
 - 부트스트랩 다운로드
 - 부트스트랩 예제 다운로드

https://getbootstrap.kr/docs/5.1/examples/



Bootstrap 5 Containers

.container

.container-fluid

```
.container-fluid
<!DOCTYPE html>
<html lang="en">
<head>
  <title>Bootstrap Example</title>
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
 <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
 <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>
</head>
<body>
<div class="container">
  <h1>My First Bootstrap Page</h1>
 This part is inside a .container class.
 The .container class provides a responsive fixed width container.
</div>
</body>
</html>
```

.container

Bootstrap 5 Containers

Container Padding

- 예제 <div class="container pt-5"></div>
 - pt-5 : add a large top padding

Container Border and Color

```
<div class="container p-5 my-5 border"></div>
<div class="container p-5 my-5 bg-dark text-white"></div>
<div class="container p-5 my-5 bg-primary text-white"></div>
```

My First Bootstrap Page

This container has a border and some extra padding and margins.

My First Bootstrap Page

This container has a dark background color and a white text, and some extra padding and margins.

My First Bootstrap Page

is container has a blue background color and a white text, and some extra padding and margins.

Bootstrap 5 Containers

Responsive Containers

| Class | Extra small <576px | Small ≥576px | Medium ≥768px | Large ≥992px | Extra large ≥1200px | XXL ≥1400px |
|----------------|-----------------------|-----------------|------------------|-----------------|------------------------|----------------|
| .container-sm | 100% | 540px | 720px | 960px | 1140px | 1320px |
| .container-md | 100% | 100% | 720px | 960px | 1140px | 1320px |
| .container-lg | 100% | 100% | 100% | 960px | 1140px | 1320px |
| .container-xl | 100% | 100% | 100% | 100% | 1140px | 1320px |
| .container-xxl | 100% | 100% | 100% | 100% | 100% | 1320px |

```
<div class="container-sm">.container-sm</div>
<div class="container-md">.container-md</div>
<div class="container-lg">.container-lg</div>
<div class="container-xl">.container-xl</div>
<div class="container-xxl">.container-xxl</div></div</tr>
```

Responsive Containers

Resize the browser window to see the effect.

.container-sm

.container-md

.container-lg


.container-xl

.container-xxl

Bootstrap 5 Grids

Grid Classes

- .col-
- .col-sm-
- .col-md-
- .col-lg-
- .col-xl-
- .col-xxl-



```
.col .col .col
```

```
<div class="row">
    <div class="col">.col</div>
    <div class="col">.col</div>
    <div class="col">.col</div>
    </div>
```

```
.col-sm-4 .col-sm-8
```

```
<div class="row">
    <div class="col-sm-4">.col-sm-4</div>
    <div class="col-sm-8">.col-sm-8</div>
</div>
```

Bootstrap 5 Text/Typography

- <h1> <h6>
 - .h1 ~ .h6

```
h1 Bootstrap heading
h2 Bootstrap heading
h3 Bootstrap heading
h4 Bootstrap heading
h4 Bootstrap heading
h5 Bootstrap heading
h6 Bootstrap heading
```

- Display Headings
 - .display-1 ~ .display-6

- <small>:.small
- <mark>:.mark
- <blockquote>:.blockquote

- 다음 태그에 스타일 지원
 - <abbr>, <dl>, <code>, <kbd>,

More Typography Classes

| Class | Description | Example |
|-----------------------|--|---------|
| .lead | Makes a paragraph stand out | Try it |
| .text-start | Indicates left-aligned text | Try it |
| .text-break | Prevents long text from breaking layout | Try it |
| .text-center | Indicates center-aligned text | Try it |
| .text-decoration-none | Removes the underline from a link | Try it |
| .text-end | Indicates right-aligned text | Try it |
| .text-nowrap | Indicates no wrap text | Try it |
| .text-lowercase | Indicates lowercased text | Try it |
| .text-uppercase | Indicates uppercased text | Try it |
| .text-capitalize | Indicates capitalized text | Try it |
| .initialism | Displays the text inside an <abbr> element in a slightly smaller font size</abbr> | Try it |
| .list-unstyled | Removes the default list-style and left margin on list items (works on both and This class only applies to immediate children list items (to remove the default list-style from any nested lists, apply this class to any nested lists as well) | Try it |
| .list-inline | Places all list items on a single line (used together with .list-inline-item on each elements) | Try it |

Bootstrap 5 Colors

text-muted, .text-primary, .text-success, .text-info,
 .text-warning, .text-danger, .text-secondary,
 .text-white, .text-dark, .text-body , .text-light

text-black-50, .text-white-50

Black text with 50% opacity on white background

White text with 50% opacity on black background

- .bg-primary, .bg-success, .bg-info, .bg-warning,
 .bg-danger, .bg-secondary, .bg-dark , .bg-light
- .text-bg-color

This text is muted.

This text is important.

This text indicates success.

This text represents some information.

This text represents a warning.

This text represents danger.

Secondary text.

Dark grey text.

Body text.



Bootstrap 5 Tables

Basic Table: .table

| Firstname | Lastname | Email |
|-----------|----------|------------------|
| John | Doe | john@example.com |
| Mary | Moe | mary@example.com |
| July | Dooley | july@example.com |

Striped Rows: .table-striped

| Firstname | Lastname | Email |
|-----------|----------|------------------|
| John | Doe | john@example.com |
| Mary | Moe | mary@example.com |
| July | Dooley | july@example.com |

- .table-dark
- .table-borderless

Bordered Table: .table-bordered

| Firstname | Lastname | Email |
|-----------|----------|------------------|
| John | Doe | john@example.com |
| Mary | Moe | mary@example.com |
| July | Dooley | july@example.com |

Hover Rows: .table-hover

| Firstname | Lastname | Email |
|-----------|----------|------------------|
| John | Doe | john@example.com |
| Mary | Moe | mary@example.com |
| July | Dooley | july@example.com |

• .table-*color*

| Default | Defaultson | def@somemail.com |
|---------|------------|------------------|
| Primary | Joe | joe@example.com |
| Success | Doe | john@example.com |
| Danger | Moe | mary@example.com |
| Info | Dooley | july@example.com |
| Warning | Refs | bo@example.com |

Bootstrap 5 Images

.rounded, .rounded-circle, .img-thumbnail



• Aligning Images: .float-start, .float-end





Centered Image: .mx-auto and .d-block



Responsiver Images: .img-fluid

Bootstrap 5 Buttons

Button Styles

```
Basic Primary Secondary Success Info Warning Danger Dark Light <u>Lin</u>
```

```
<button type="button" class="btn">Basic</button>
<button type="button" class="btn btn-primary">Primary</button>
<button type="button" class="btn btn-secondary">Secondary</button>
<button type="button" class="btn btn-success">Success</button>
<button type="button" class="btn btn-info">Info</button>
<button type="button" class="btn btn-warning">Warning</button>
<button type="button" class="btn btn-danger">Danger</button>
<button type="button" class="btn btn-dark">Dark</button>
<button type="button" class="btn btn-light">Light</button>
<button type="button" class="btn btn-light">Light</button>
<button type="button" class="btn btn-light">Light</button>
<button type="button" class="btn btn-light">Light</button>
<button type="button" class="btn btn-link">Link</button></button>
```

```
<button type="button" class="btn btn-outline-primary">Primary</button>
<button type="button" class="btn btn-outline-secondary">Secondary</button>
<button type="button" class="btn btn-outline-success">Success</button>
<button type="button" class="btn btn-outline-info">Info</button>
<button type="button" class="btn btn-outline-warning">Warning</button>
<button type="button" class="btn btn-outline-danger">Danger</button>
<button type="button" class="btn btn-outline-dark">Dark</button>
<button type="button" class="btn btn-outline-dark">Dark</button>
<button type="button" class="btn btn-outline-light text-dark">Light</button></button>
```

Primary | Secondary | Success | Info | Warning | Danger | Dark | Light

Bootstrap 5 Buttons

Button Sizes



Spinner Buttons



• .btn-lg, .btn-sm

.spinner-border

Block Level Buttons

```
• .d-grid

- div class="d-grid gap-3">

- class="btn btn-primary btn-block">Full-Width Button</button>

- class="btn btn-primary btn-block">Full-Width Button</br>
```

Active/Disabled Buttons

```
Primary Button Active Primary
```

Full-Width Button

Full-Width Button

Disabled Primary

Disabled Link

Button Groups

- .btn-group
- .btn-group-vertical



Badges

.badge

Example heading New

- Contextual Badges
 - .bg-*

```
<span class="badge bg-primary">Primary</span>
<span class="badge bg-secondary">Secondary</span>
<span class="badge bg-success">Success</span>
<span class="badge bg-danger">Danger</span>
<span class="badge bg-warning">Warning</span>
<span class="badge bg-info">Info</span>
<span class="badge bg-light">Light</span>
<span class="badge bg-dark">Dark</span>
<span class="badge bg-dark">Dark</span>
<span class="badge bg-dark">Dark</span>

Primary Secondary Success Danger Warning Info Dark
```

- Pill Badges
 - .rounded-pill

```
Primary Secondary Success Danger Warning Info Dark
```

Progress Bars

Basic Progress Bars



```
<div class="progress">
    <div class="progress-bar" style="width:70%"></div>
</div>
```

Label, Color




```
<div class="progress">
    <div class="progress-bar bg-danger" style="width:70%">70%</div>
</div>
```

Multiple Progress Bars

Free Space Warning Danger

Pagination

Basic Pagination



.pagination, .page-item, .page-link

active

Previous 1 2 3 Next

Previous 1

class="page-item active">2

Pagination Alignment

Breadcrumbs

Photos / Summer 2017 / Italy / Rome

```
     class="breadcrumb-item"><a href="#">Photos</a>
     class="breadcrumb-item"><a href="#">Summer 2017</a>
     class="breadcrumb-item"><a href="#">Italy</a>
     class="breadcrumb-item"><a href="#">Italy</a>
```

3 Hext

Previous 1 2 3 Next

Previous 1 2 3 Next

List Groups

Basic List Groups

```
     Active item
     Second item
     class="list-group-item">Third item
```



List Group With Linked Items

• .list-group-item-action



Flush/Remove Borders

• .list-group-flush



Numbered List Groups

.list-group-numbered



Horizontal List Groups

.list-group-horizontal



Cards

Basic Card

• .card

```
<div class="card">
    <div class="card-body">Basic card</div>
</div>
```

Header and Footer

```
<div class="card">
  <div class="card-header">Header</div>
  <div class="card-body">Content</div>
  <div class="card-footer">Footer</div>
</div>
```

Header Content

Footer

Titles, text, and links

```
<div class="card">
    <div class="card-body">
        <h4 class="card-title">Card title</h4>
        Some example text. Some example text.
        <a href="#" class="card-link">Card link</a>
        <a href="#" class="card-link">Another link</a>
        </div>
        </div>
        </div>
        <a Card title</pre>
```

Some example text. Some example text.

Card link Another link

Card Images

```
<div class="card" style="width:400px">
  <img class="card-img-top" src="img_avatar1.png" alt="Card image">
  <div class="card-body">
        <h4 class="card-title">John Doe</h4>
        Some example text.
        <a href="#" class="btn btn-primary">See Profile</a>
        </div>
</div>
```



Collapse

- 버튼/링크를 누를때마다 내용 show/hidden 전환
- 예제

```
<button data-bs-toggle="collapse" data-bs-target="#demo">Collapsible</button>

<div id="demo" class="collapse">
   Lorem ipsum dolor text....
</div>
```

```
<a href="#demo" data-bs-toggle="collapse">Collapsible</a>
<div id="demo" class="collapse">
Lorem ipsum dolor text....
</div>
```

Click Me

```
<div id="demo" class="collapse show">
Lorem ipsum dolor text....
</div>
```

Click Me

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

Collapse _ Accordion

■ data-bs-parent 속성 사용 → 축소 가능한 항목중 하나가 표시될 때 지정된 상위 아래의 모든 축소 가능 한 요소가 닫히도록 설정

Collapsible Group Item #1

Collapsible Group Item #2

Collapsible Group Item #3

Collapsible Group Item #1

Collapsible Group Item #2

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

Collapsible Group Item #3

```
<div id="accordion">
 <div class="card">
   <div class="card-header">
     <a class="btn" data-bs-toggle="collapse" href="#collapseOne">
       Collapsible Group Item #1
     </a>
   </div>
   <div id="collapseOne" class="collapse show" data-bs-parent="#accordion">
     <div class="card-body">
       Lorem ipsum...
     </div>
   </div>
 </div>
 <div class="card">
   <div class="card-header">
     <a class="collapsed btn" data-bs-toggle="collapse" href="#collapseTwo">
       Collapsible Group Item #2
     </a>
   </div>
   <div id="collapseTwo" class="collapse" data-bs-parent="#accordion">
     <div class="card-body">
       Lorem ipsum..
     </div>
   </div>
 </div>
 <div class="card">
   <div class="card-header">
     <a class="collapsed btn" data-bs-toggle="collapse" href="#collapseThree">
       Collapsible Group Item #3
     </a>
   </div>
   <div id="collapseThree" class="collapse" data-bs-parent="#accordion">
     <div class="card-body">
       Lorem ipsum...
     </div>
   </div>
 </div>
```

Navs

■ Nav Menus Link Link Link Disabled

■ Tabs: nav-tabs

Active Link Link Disabled

Pills: nav-pills



정렬: justify-content-center, justify-content-end

- flex-column Link
 - 세로로 배치 Link

Link

Disabled

- nav-justified
 - 동일 너비를 사용하여 정렬

```
..
..
```

Toggleable Tabs

```
<div class="container mt-3">
 <h2>Toggleable Pills</h2>
                                                                        Home
 <br>
 <!-- Nav pills -->
 <a class="nav-link active" data-bs-toggle="pill" href="#home">Home</a>
   <a class="nav-link" data-bs-toggle="pill" href="#menu1">Menu 1</a>
   <a class="nav-link" data-bs-toggle="pill" href="#menu2">Menu 2</a>
   <!-- Tab panes -->
 <div class="tab-content">
   <div id="home" class="container tab-pane active"><br>
     <h3>HOME</h3>
     Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor
incididunt ut labore et dolore magna aliqua.
   </div>
   <div id="menu1" class="container tab-pane fade"><br>
     <h3>Menu 1</h3>
     Vt enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip
ex ea commodo consequat.
   </div>
   <div id="menu2" class="container tab-pane fade"><br>
     <h3>Menu 2</h3>
     Sed ut perspiciatis unde omnis iste natus error sit voluptatem accusantium
doloremque laudantium, totam rem aperiam.
   </div>
 </div>
</div>
```

Menu 2 Menu 1

Menu 1

Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo conseguat.

Navbars

```
<nav class="navbar navbar-expand-sm navbar-dark bg-dark">
 <div class="container-fluid">
   <a class="navbar-brand" href="javascript:void(0)">Logo</a>
   <button class="navbar-toggler" type="button" data-bs-toggle="collapse" data-bs-target="#mynavbar">
     <span class="navbar-toggler-icon"></span>
   </button>
   <div class="collapse navbar-collapse" id="mynavbar">
     class="nav-item">
        <a class="nav-link" href="javascript:void(0)">Link</a>
      <a class="nav-link" href="javascript:void(0)">Link</a>
      <a class="nav-link" href="javascript:void(0)">Link</a>
       <form class="d-flex">
      <input class="form-control me-2" type="text" placeholder="Search">
       <button class="btn btn-primary" type="button">Search</button>
     </form>
   </div>
 </div>
</nav>
```

Logo Link Link

Search

Search


Carousel

Carousel/Slideshow

```
<!-- Carousel -->
<div id="demo" class="carousel slide" data-bs-ride="carousel">
 <!-- Indicators/dots -->
 <div class="carousel-indicators">
   <button type="button" data-bs-target="#demo" data-bs-slide-to="0" class="active"></button>
   <button type="button" data-bs-target="#demo" data-bs-slide-to="1"></button>
   <button type="button" data-bs-target="#demo" data-bs-slide-to="2"></button>
  </div>
   <!-- The slideshow/carousel -->
  <div class="carousel-inner">
   <div class="carousel-item active">
     <img src="la.jpg" alt="Los Angeles" class="d-block" style="width:100%">
   </div>
   <div class="carousel-item">
     <img src="chicago.jpg" alt="Chicago" class="d-block" style="width:100%">
   </div>
    <div class="carousel-item">
                                                                                             </div>
     <img src="ny.jpg" alt="New York" class="d-block" style="width:100%">
   </div>
  </div>
   <!-- Left and right controls/icons -->
  <button class="carousel-control-prev" type="button" data-bs-target="#demo" data-bs-slide="prev">
   <span class="carousel-control-prev-icon"></span>
  </button>
  <button class="carousel-control-next" type="button" data-bs-target="#demo" data-bs-slide="next">
   <span class="carousel-control-next-icon"></span>
 </button>
</div>
```



caption 추가 가능



Modal

Modal Example

Click on the button to open the modal.

Open modal

■ 대화상자/팝업창

</div> </div> </div>

```
<div class="container mt-3">
 <h3>Modal Example</h3>
 Click on the button to open the modal.
 <button type="button" class="btn btn-primary" data-bs-toggle="modal" data-bs-target="#myModal">
   Open modal
 </button>
</div>
                                                                                                                             X
                                                                                      Modal Heading
<!-- The Modal -->
<div class="modal" id="myModal">
                                                                                      Modal body..
 <div class="modal-dialog">
   <div class="modal-content">
     <!-- Modal Header -->
                                                                                                                         Close
     <div class="modal-header">
       <h4 class="modal-title">Modal Heading</h4>
       <button type="button" class="btn-close" data-bs-dismiss="modal"></button>
     </div>
     <!-- Modal body -->
     <div class="modal-body">
       Modal body..
     </div>
     <!-- Modal footer -->
      <div class="modal-footer">
        <button type="button" class="btn btn-danger" data-bs-dismiss="modal">Close</button>
     </div>
```


Modal

Modal Size

• modal-sm, modal-lg, modal-xl, modal-fullscreen

Scrolling Modal

modal-dialog-scrollable



Form

```
<form action="/action page.php">
                                                                                                        Email:
  <div class="mb-3 mt-3">
                                                                                                         Enter email
    <label for="email" class="form-label">Email:</label>
                                                                                                        Password:
    <input type="email" class="form-control" id="email" placeholder="Enter email" name="email">
                                                                                                         Enter password
  </div>
  <div class="mb-3">
                                                                                                          Remember me
    <label for="pwd" class="form-label">Password:</label>
                                                                                                        Submit
    <input type="password" class="form-control" id="pwd" placeholder="Enter password" name="pswd">
  </div>
  <div class="form-check mb-3">
    <label class="form-check-label">
      <input class="form-check-input" type="checkbox" name="remember"> Remember me
    </label>
                                                                                         Comments:
  </div>
  <button type="submit" class="btn btn-primary">Submit</button>
</form>
<label for="comment">Comments:</label>
<textarea class="form-control" rows="5" id="comment" name="text"></textarea>
                                                                                          Submit
```

Select

```
<form action="/action page.php">
 <label for="sel1" class="form-label">Select list (select one):</label>
 <select class="form-select" id="sel1" name="sellist1">
    <option>1</option>
    <option>2</option>
    <option>3</option>
    <option>4</option>
 </select>
  <br>
 <label for="sel2" class="form-label">Mutiple select list (hold shift to select more than one):</label>
  <select multiple class="form-select" id="sel2" name="sellist2">
    <option>1</option>
    <option>2</option>
                                                                                     Select list (select one):
    <option>3</option>
    <option>4</option>
    <option>5</option>
 </select>
 <button type="submit" class="btn btn-primary mt-3">Submit</button>
                                                                                     Mutiple select list (hold shift to select more than one):
</form>
                                                                                      Submit
```


Checkboxes, Radio buttons

Checkboxes

```
<div class="form-check">
    <input class="form-check-input" type="checkbox" id="check1"
name="option1" value="something" checked>
    <label class="form-check-label">Option 1</label>
</div>
```

- Option 1
- Option 2
- Disabled Option

Toggle Switches



```
<div class="form-check form-switch">
    <input class="form-check-input" type="checkbox" id="mySwitch"
name="darkmode" value="yes" checked>
    <label class="form-check-label" for="mySwitch">Dark Mode</label>
</div>
```


Radio buttons

Option 2


Option 3

Floating Labels


default label



floating label



Form Validation



Basic Template

My First Bootstrap 5 Page

Resize this responsive page to see the effect!

Active Link Link Disabled

Some Links

Lorem ipsum dolor sit ame.

Link

LITIK

Disabled

elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco.

TITLE HEADING

Title description, Sep 2, 2020

Fake Image

Some text..

Sunt in culpa qui officia deserunt mollit anim id est laborum consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco.

About Me

Photo of me:

Fake Image

Some text about me in culpa qui officia deserunt mollit anim..

Some Links

Lorem ipsum dolor sit ame.

Active

TITLE HEADING

Title description, Dec 7, 2020

Fake Image

Some text...

Sunt in culpa qui officia deserunt mollit anim id est laborum consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco.

TITLE HEADING