

Aim:

Write a program to **sort** the given elements using insertion sort technique.

At the time of execution, the program should print the message on the console as:

Enter value of n :

For example, if the user gives the **input** as:

Enter value of n : 3

Next, the program should print the messages one by one on the console as:

Enter element for a[0] :
Enter element for a[1] :
Enter element for a[2] :

if the user gives the **input** as:

Enter element for a[0] : 22
Enter element for a[1] : 33
Enter element for a[2] : 12

then the program should **print** the result as:

Before sorting the elements in the array are
Value of a[0] = 22
Value of a[1] = 33
Value of a[2] = 12
After sorting the elements in the array are
Value of a[0] = 12
Value of a[1] = 22
Value of a[2] = 33

Fill in the missing code so that it produces the desired result.

Source Code:

InsertionSortDemo3.c

```
#include<stdio.h>
void main() {
    int a[20],i,n,j,temp;
    printf("Enter value of n : ");
    scanf("%d",&n);
    for(i=0;i<n;i++)
    {
        printf("Enter element for a[%d] : ",i);
        scanf("%d",&a[i]);
    }
    printf("Before sorting the elements in the array are\n");
    for(i=0;i<n;i++)
    {
        printf("Value of a[%d] = %d\n",i,a[i]);
    }
```

```

    }
    for(i=1;i<n;i++)
    {
        temp=a[i];
        j=i-1;
        while(j>=0&& a[j]>temp)
        {
            a[j+1]=a[j];
            j--;
        }
        a[j+1]=temp;
    }
    printf("After sorting the elements in the array are\n");
    for(i=0;i<n;i++)
    {
        printf("Value of a[%d] = %d\n",i,a[i]);
    }
}

```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Enter value of n : 6
Enter element for a[0] : 5
Enter element for a[1] : 9
Enter element for a[2] : 2
Enter element for a[3] : 5
Enter element for a[4] : 1
Enter element for a[5] : 3
Before sorting the elements in the array are
Value of a[0] = 5
Value of a[1] = 9
Value of a[2] = 2
Value of a[3] = 5
Value of a[4] = 1
Value of a[5] = 3
After sorting the elements in the array are
Value of a[0] = 1
Value of a[1] = 2
Value of a[2] = 3
Value of a[3] = 5
Value of a[4] = 5
Value of a[5] = 9

Test Case - 2
User Output
Enter value of n : 3
Enter element for a[0] : 5
Enter element for a[1] : 9
Enter element for a[2] : 4

Before sorting the elements in the array are
Value of a[0] = 5
Value of a[1] = 9
Value of a[2] = 4
After sorting the elements in the array are
Value of a[0] = 4
Value of a[1] = 5
Value of a[2] = 9