

Q. Jenkins with Docker

The image displays two screenshots of a Jenkinsfile repository on GitHub, specifically the file `Jenkinsfile` in the `jenkins-docker` repository by `KPkm25`. The screenshots show the file content in a web browser, with a file explorer on the left and a code editor on the right.

Top Screenshot: Shows the first three stages of the pipeline:

```
1 pipeline{
2   agent any
3   environment{
4     DOCKER_IMAGE = "kpk25/my-jenkins-app"
5     DOCKER_CREDENTIALS_ID = "docker-creds"
6   }
7   stages {
8     stage('Clone Repository') {
9       steps {
10        echo "Cloning repository..."
11        git url: 'https://github.com/KPkm25/jenkins-docker.git', branch: 'main'
12        echo "Repository cloned successfully."
13      }
14    }
15  }
16  stage('Build Docker Image') {
17    steps {
18      echo "Starting Docker build..."
19      sh "docker build -t ${DOCKER_IMAGE} ."
20      echo "Docker image built successfully."
21    }
22  }
23  stage('Run Container Locally'){
24    steps {
25      script {
26        sh "docker run -d -p 8081:80 --name jenkins-docker ${DOCKER_IMAGE}:latest"
27      }
28    }
29  }
30 }
31 }
```

Bottom Screenshot: Shows the continuation of the pipeline, including the 'Push Docker Image' and 'Deploy to server' stages:

```
31 }
32
33 stage('Push Docker Image') {
34   steps {
35     script {
36       echo "Logging into Docker Hub..."
37       docker.withRegistry('https://index.docker.io/v1/', 'docker-creds') {
38         echo "Pushing Docker Image..."
39         sh "docker push ${DOCKER_IMAGE}"
40         echo "Docker image pushed successfully."
41       }
42     }
43   }
44 }
45
46 stage('Deploy to server') {
47   steps {
48     script {
49       withCredentials([usernamePassword(credentialsId: 'docker-creds', usernameVariable: 'DOCKER_USER', password
50       sh '''
51       echo "${DOCKER_PASS}" | docker login -u "${DOCKER_USER}" --password-stdin
52       docker pull kpk25/my-jenkins-app:latest
53       '''
54     }
55   }
56 }
57
58 }
59
60 }
```

