

Relating Justification Logic Modality and Type Theory in Curry–Howard fashion

Konstantinos Pouliasis

October 9, 2017

Abstract

This thesis is a work in the intersection of *Justification Logic* (JL) and *Curry–Howard Isomorphism* (CHI). Justification logic is an umbrella of modal logics of knowledge with explicit evidence. Justification logics have been used to tackle traditional problems in proof theory (in relation to Godel’s provability), philosophy (Gettier examples, Russel’s barn paradox). The Curry–Howard Isomorphism or *proofs-as-programs* is an understanding of logic that places logical studies in conjunction to type theory and – in current developments – category theory. The point being that the understanding a system as a logic, as a typed calculus and as a language of a class of categories constitutes a useful discovery that can have many applications. The application that we will be mainly concerned with is type systems for useful programming language constructions. This work is structured in two parts: The first part (CHAPTERS x,y,x) is a revision of my second examination paper and constitutes a bird’s eye view into my research topics: Logic, Constructive Modality and Type Theory. The relevant systems are introduced syntactically together with main metatheoretic proof techniques which will be useful in the rest of the thesis. The second part constitutes my main contributions: I will propose a modal type system that extends simple type theory (or, speaking from the logical side of CHI, intuitionistic propositional logic) with elements of justification logic and will argue about its computational significance.

More specifically, I will show that the obtained calculus characterizes certain computational phenomena that abound in modern programming language semantics. I will present full metatheoretic results obtained for this logic/calculus using and extending techniques from the first part and will provide proofs in the Appendix. In Chapter X, I will show the first steps in extending the calculus towards the full propositional universe of justification logic and will provide some obtained metatheoretic results. Finally, the fourth part exercises an implementation of the calculus as a programming language (to showcase the concept of *proofs-as-programs* in practice). To achieve this “proof of concept” result we define our language together with its type system in the metaprogramming framework “MAKAM”, which we will discuss briefly, and we obtain a type checker for our calculus. Finally, we conclude this work with a small “outro” where we discuss possibilities for future work and relations of the calculus with other current developments in the theory of functional programming.

This work is my thesis requirement for my PhD candidacy under the supervision of Distinguished Professor Sergei Artemov at the Department of Computer Science of the Graduate Center, CUNY.

Acknowledgements

This thesis would have been impossible without my supervisor Prof. Sergei Artemov. He introduced me to the beauty of epistemic logic and its deep relations to proof theory back at my first years as a graduate student. He inspired and helped shape my topic of research and has not stopped being a source of inspiration ever since. He has provided guidance, support and encouragement through our numerous meetings. I want to thank him deeply.

In addition, I want to thank my committee members: Prof. Fitting and Prof. Shankar. Prof. Fitting's classes at the Graduate Center have been a tremendous experience and source of knowledge whereas, the clarity of both his writings and presentations helped me realize the level of academic quality a young student should be striving and aiming toward. Prof. Shankar has been a great teacher and an inspiring advisor. We spent hours discussing topics related to my thesis or to the formal methods area at large. He was one of the people that invigorated my interest in programming language theory that has proven very valuable for my research work and my post-graduate career developments.

Prof. Zachos, my external committee member, has been one of the most important chapters of academic life. It is thanks to him that I attended the PhD program at CUNY and his guidance in all walks of my academic and non-academic life has contributed the most to its successful completion. He has been an inspiring scientist, a great mentor and a friend for the last fifteen

years that I have known him.

During my studies at the Graduate Center I had the chance to meet prominent scientists both from CUNY and worldwide. These people helped me expand my scientific horizon and improve the quality of my work. I would like to thank explicitly Rohit Parikh, Thomas Wies, Mark Tuttle and the late Kristofer Rose for inspiring classes, discussions and collaborations. In particular, I want to give special thanks to Giuseppe Primiero who believed in this work since its early stages and co-authored the first related publication with me.

Moreover, I want to thank my wonderful friends both in NYC and back home. I want to thank Danai Dragonea, Dafni Anesti, Antonis Bouchagiar and Michalis Agathos for taking care of me every summer after my teaching obligations had turned me to a jaded new yorker. All our beautiful excursions into under the gorgeous greek sun have helped me stay happy and healthy throughout eight intense academic years. I want to thank Krystal Raydo and George Rabanca for being a family and showing me immense support through the thick and thin in New York. Cagil Tasdemir has been the best friend and a great source of knowledge and wisdom. I want to thank fellow graduate students: Marios Georgiou, Nikos Melissaris and Ivo Vigan for our great time inside and outside school.

Finally, I want to thank my kinfolk. Wilson Sherwin's love and understanding has been one of my most important motivations for completing this work and for looking forward to our future together. My family Alik, Doria,

Vaso and Spyros deserve most of the credit for all my achievements including this work. I had the luck to have two amazing sisters and two loving parents and that's all the wealth a man could ask for.

This dissertation is dedicated to my late grandparents and grandaunt: Alikí Giannioti, a tuberculosis survivor, Theodoros (Lolos) Gianniotis, a fisherman, and Labro Mitsiali, a factory worker, for raising me and my elder sister at their home in Anemomylos, Corfu and showing me that can build beauty with as little as a small house, a well-kept garden painted fresh every spring and a fish boat.

Contents

1	Introduction	8
2	Intuitionistic Logic	14
2.1	Intuitionism	14
2.1.1	A bird's eye view	15
2.2	IPL	17
2.2.1	Basic Properties of Intuitionistic Entailment	20
2.3	Order Theoretic Semantics: <i>Heyting Algebras</i>	21
3	Lambda Calculus With Types	25
3.1	From intuitionistic provability to proof trees	26
3.1.1	Properties of Intuitionistic Entailment Redux	29
3.1.2	Equating Proof Trees	30
3.2	Linear representation of trees with proof terms: λ calculus . .	31

3.2.1	Definitional Equality: Proof tree equalities as term equalities	34
3.3	Operational (a.k.a “term”) Semantics	36
3.3.1	The essence of Proofs as program	42
3.3.2	Propositions as Types	43
3.4	Categories for proof relevant <i>IPL</i>	43
3.4.1	Definitions and Axioms of a Category	44
3.4.2	Terminal, Co-Terminal objects, Products and Co-Products	45
4	Justification Logic	50
4.1	A bird’s eye view	51
4.2	Minimal Justification Logic J_0	52
4.3	Epistemic motivation	56
4.4	Proof theoretic view	58
4.5	The Logic of Proofs	60
4.6	Metatheoretic Results	60
4.6.1	Realization	62
4.6.2	Kripke - Fitting Semantics	64
5	Curry – Howard view of justification logic	66
5.1	Introduction: Necessity and Constructive Semantics	67
5.1.1	Deductive Systems, Validity and Necessity	68
5.2	Judgments of $J\text{calc}^-$	71
5.2.1	Natural Deduction for $J\text{calc}^-$	74

5.2.2	Logical Completeness, Admissibility of Necessitation and Completeness with respect to Hilbert Axiomatization	78
5.2.3	Harmony: Local Soundness and Local Completeness . .	80
5.2.4	(Global) Soundness	82
5.3	Order theoretic semantics	83
6	The computational side of Jcalc [−]	84
6.0.1	Proof term assignment	85
6.0.2	Strong Normalization and small-step semantics	90
6.1	A programming language view: Dynamic Linking and separate compilation	93
6.2	Related and Future Work	99
7	Jcalc and dependent typing	101
7.1	A road map for the type system	106
7.2	Reasoning without foundational assumptions: IPC	108
7.3	Reasoning in the Presence of Foundations: A calculus of Justi- fications J	110
7.3.1	Minimal Justification Logic J- Calc_1	111
7.4	The Full Calculus: J- Calc	117
7.4.1	Justificational (Validity) Judgments	119
7.4.2	Proof Links	122
7.5	Further Results and Conclusions	124

8 An implementation of Jcalc in a modern metaprogramming framework	127
---	------------

Appendices	128
-------------------	------------

.1 Theorems	129
.2 Linking on the function space	134
.3 Gentzen's reduction Principle for \square (General)	135
.4 Notes on the cut elimination proof and normalization of natural deduction	136

Appendices	129
-------------------	------------

1

Introduction

The CHI [29, 45] was first established as a deep connection between explicit proofs in intuitionistic logic and programs of a simple programming language that includes pairs, functions and union types [65, 72]. This relation has been a central topic of study in the field of type theory and has turned into the standard foundational approach to studying and designing programming

languages especially of the functional paradigm. Since this relation has been established the isomorphism has been extended to more complex logics and correspondingly to more complex programming language constructs. In the following I will be using *Curry-Howard Isomorphism* (CHI) and *proofs-as-programs* interchangeably.

There are great benefits both for a logician and the programming language designer in viewing things through the lenses of such a relation. On the programming language perspective certain linguistic phenomena are given categorical characterizations that do not depend on implementation specifics. For example the designer of the next hot programming language knows that adding pairs would have to adhere to the corresponding constructs of logical conjunction (conjunction introduction as pairing, conjunction eliminations as projections). In addition, adding more complex design features (e.g. state, concurrency, exceptions etc) can be done in a structured, orthogonal, and modular way by enriching the underlying logic and, correspondingly, the type system (see e.g. [38, 28, 59, 30]).

It should not be a surprise that languages of the typed functional paradigm have been gaining traction and more functional design principles are being added to languages of the object oriented paradigm. There are two main reasons for this, an old and a new. The older reason is mathematical correctness which is strongly related to the fact that reasoning about programs (of the lambda calculus and its extensions) can be done in an *equational way*, a property that is heavily connected to their underlying foundational principles

as we will see. Another reason is that the addition of features such as side effects or concurrency to the language is reflected in the typing. For example, a program that changes global state has a type that has to say so, a program that uses explicitly goto mechanisms - if permitted - would also say so in its type. Even “unpure”, non-functional constructs (state, mutable references) are added in a mathematical/ algebraic fashion under the **CHI** discipline. As a result reasoning about properties of such programs is significantly simpler. Moreover, under a strongly typed doctrine, important properties of programs are checked statically by the type-checker and prior to their execution. As a result, the need for testing is reduced to verify only non-trivial properties.

The renewed interest in functional programming owes a lot to the difficulties of scaling concurrent programs in traditional programming paradigms. It is very hard to scale programs that make unlimited use of side effects (such as state change) in an implicit way (i.e. without leaving any trace in their typing) from sequential to multithreaded computation. Programming freedoms in traditional languages (plus the easiness and textbook familiarity with the Von Neumann model of computation) come at large cost regarding (reasoning about) correctness and need for testing. The “purity” of programs in the lambda calculus – and delimited “impurity” in its extensions – makes writing high-quality concurrent code an easier task. It is exciting to see that important metatheoretic results in the area of combinatory logic as e.g. the Church–Rosser property are the backbone of models for concurrent computation in modern functional languages.

On the other hand, the logician has good reasons to study logics as rules of program formation and reduction. First of all, such designs make logics implementable “for free” in modern theorem provers using the programmistic side of the correspondence. Secondly the study of logic in such a way has put upfront a Gentzen-style treatment of logical connectives where emphasis is given to the notion of proof, proof geometry and proof reduction. This has sparked studies for more refined versions of proof relevant deduction than the ones discovered under the standard “axiomatic” approach (i.e. linear logics, substructural logics etc). As we will see, the Gentzen– Brouwer initiative to logic does not merely call for change of axiomatization but for a “proof relevant” interpretation of connectives that comes with a computational taste. Metatheory is also standardized once one studies logic this way; scalable techniques have been developed within the area of “proof-theoretic” semantics that make the passing from natural deduction of a logic to its cut free calculus pretty standard [70, 61]. In other words, by trying to recast known logics within a Curry – Howard environment gives to logic a great organizing principle. Finally, proof relevant treatments of logic – pushed further by ideas of *Martin-Löf Type Theory* [55] have sparked a renewed interest in a foundations of mathematics that begins from a treatment of proofs as *the* primitive objects of mathematics. Programs like *Homotopy Type Theory* (HoTT) promise a future in which submission of proofs that accompany conference and journal papers would no longer be hand-written or typeset arguments but executables that can run and be tested within a theorem

prover.

In this work, we are interested in the study of extending *Curry–Howard Isomorphism* (CHI) with basic constructive necessity of justification logic. There is a good reason to believe that this should be doable. Justification logic is a logic that relates the concept of necessity with the existence of a proof construct and that is exactly what working in realm of proof relevancy and CHI calls for. There are challenges to this task, both syntactical and semantical. First of all, there is a resemblance of the justification logic syntax with that of simple type theory (e.g. the use of the semicolon $a : A$) that initially might call for an antagonistic relation between the two systems. Of course, this is not a substantial issue since the two typing relations can be “colored” in a syntactical way. But resolving the syntactical overload would still leave a “meaning” question open; namely, how can one read, both intuitively and formally, the need of having two proofs of the “same thing” in a system. In the last Chapter of this work I will introduce my research work [66] and show how such a relation of binding two kinds of proof systems is quite natural and gives a basic reading of validity and necessity on first, proof-theoretic principles. We will treat justification logic as a logic of *proof relevant validity*. To give a hint, one should trace justification logic back to its origin as an explicit, classical semantics to *Brouwer–Heyting–Kolmogorov* (BHK) proof constructs. We will present a modal logic that is based on this relation and we will argue that such phenomena of binding two kinds of constructions abound both in the realm of mathematical proofs (and corresponding logics)

but also in programming language design when related constructs such as modules and dynamic linkers.

This text is structured as follows: the first chapter gives a working account of Brouwer’s approach to logic and its connections with Gentzen’s work as it is being understood within the realm of modern type theory. We make the proofs-as-programs relation clear by showing how the programming constructs of the lambda calculus transliterate the proof constructs of natural deduction for intuitionistic propositional logic and, correspondingly, how lambda terms obtain computational value based on proof tree reduction and composition in such a system. In chapter 2, we make this relation in even bolder terms by showing the correspondence between proof normalization (cut-elimination) and computation (as program reduction). In Chapter 3 we give an account of justification logic, present established results about its connection with standard modal logic axiomatizations and go through its Kripkean semantics. Finally, in Chapter 4, I introduce my own work in establishing a reading of basic necessity under Curry–Howard correspondence utilizing justification logic.

2

Intuitionistic Logic

2.1 Intuitionism

In this Chapter, I will be presenting foundational work in the intersection of *Intuitionistic Logic* and *Type Theory*. The presentation is scaffolding following Prof. Robert Harper’s lecture videos in *Homotopy Type Theory* [39] and the

accompanying notes by students of the class [43]. I will often deviate to standard textbooks in the field [18], [35], [65] to present further important results.

2.1.1 A bird’s eye view

In a nutshell, *Intuitionistic mathematics* is a program in foundations of mathematics that extends *Brouwer’s program* [26]. Brouwer, in an almost Kantian fashion, viewed mathematical reasoning as a human faculty and mathematics as a language of the “creative subject” aiming to communicate mathematical concepts. The concept of *algorithm* as a step-by-step constructive process is brought in the foreground in Brouwer’s program. As a result, intuitionistic theories are amenable to computational interpretations. In the following I will be using the terms intuitionistic and *constructive* interchangeably.

For the purposes of this paper, the main diverging point of Brouwer’s program, later explicated by Heyting [44] and Kolmogorov [47] [15], lies in the treatment of proofs. In contrast to classical approaches to foundations that treat proof objects as external to theories, the constructive approach treats proofs as the fundamental forms of construction and hence, as first class citizens. As a result, the constructive view of logic draws heavily from proof theory and Gentzen’s developments [34]. For the reader interested also in the philosophical implications of constructive foundations and *antirealism*, Dummet’s treatment is a classic in the field [31].

It has to be emphasized that proofs in the intuitionistic approach are

treated as stand-alone and are not bound to formal systems (i.e the notion of proof *precedes* that of a formal system). It is necessary, hence, to draw a distinction between the notion of *proof as construction* and the typical notion of *proof in a formal system* [42, 41].

A *formal proof* is a proof given in a fixed formal system, such as Peano Arithmetic, and arises from the application of the inductively defined rules in that system. Formal proofs can, thus, be viewed as strings or gödelizations of textual derivation in some fixed system.

Although every formal proof (in a specific system) is also a proof (assuming soundness of the system) the converse is not true. This conforms with Gödel's Incompleteness Theorem, which precisely states that there exist true propositions (with a proof in *some* formal system), but for which there cannot be given a formal proof within the formal system in question. This *openness* of the nature of proofs is necessary for a foundational treatment of proofs that respects Gödelian phenomena.

Following the same line of thought, and adopting the doctrine of *proof relevance* for obtaining true judgments, leads to another main difference of the constructive approach and the classical one i.e the (default) absence of the *law of excluded middle*. More specifically, systems that rely on *Martin-Löf Type Theory* [55] do not necessarily exclude *LEM* but they might permit its delimited usage, locally, in a proof.

2.2 IPL

Intuitionistic Propositional Logic (IPL) can be viewed as “the logic of *proof relevance*” conforming with the intuitionistic view described in 2.1. To judge a fact as *true* one may provide a *proof* appropriate of the fact. *Proofs* can be synthesized to obtain proofs for more complex facts (*introduction rules*) and consumed to provide proofs relevant for other facts (*elimination rules*). The importance of the interplay between introduction and elimination rules was developed by Gentzen. A discussion on the meaning of the logical connectives that is prevalent in *MLTT* can be found in [51] Following the presentation style by Martin-Löf we split the notions of *judgment* and *proposition*. We have two main kinds of judgments:

- *Judgments* that are logical arguments about the truth(or, equivalently, proof) of a *proposition*. They might, optionally, involve assumptions on the truth (or, equivalently, proof) of other propositions. We might call these *logical judgments*.
- Judgments on *propositionality* or typeability. *Propositions* are the *subjects* of *logical judgments*. If something is judged to be a proposition then it belongs to the universe of discourse and can be mentioned in *logical judgments*.

In addition, since a *logical judgment* might involve a set Γ of assumptions (or a *context*), it is convenient to add a third kind of judgment of the form $\Gamma \text{ ctx}$

Thus, in IPL, we get the judgments $\phi \in \mathbf{Prop}$, $\phi \text{ true}$ and $\Gamma \text{ ctx}$:

$\phi \in \mathbf{Prop}$ ϕ is a (well-formed) proposition

$\phi \text{ true}$ Proposition ϕ is true

i.e., has a proof.

$\Gamma \text{ ctx}$ Γ is a (well-formed) context of assumptions

The natural deduction system of IPL is given below:

Prop Formation

————— ATOM
 $P_i \in \mathbf{Prop}$

————— TOP
 $\top \in \mathbf{Prop}$

————— BOTTOM
 $\perp \in \mathbf{Prop}$

$\frac{\phi_1 \in \mathbf{Prop} \quad \phi_2 \in \mathbf{Prop}}{\phi_1 \supset \phi_2 \in \mathbf{Prop}}$ ARR

$\frac{\phi_1 \in \mathbf{Prop} \quad \phi_2 \in \mathbf{Prop}}{\phi_1 \wedge \phi_2 \in \mathbf{Prop}}$ CONJ

$\frac{\phi_1 \in \mathbf{Prop} \quad \phi_2 \in \mathbf{Prop}}{\phi_1 \vee \phi_2 \in \mathbf{Prop}}$ DISJ

Context Formation

————— NIL
 nil ctx

$\frac{\Gamma \text{ ctx} \quad \phi \in \mathbf{Prop}}{\Gamma, \phi \text{ true ctx}}$ $\Gamma\text{-ADD}$

Context Reflection

$$\frac{\Gamma \text{ ctx} \quad \phi \text{ true} \in \Gamma}{\Gamma \vdash \phi \text{ true}} \Gamma\text{-REFL}$$

Top Introduction – Bottom Elimination

$$\frac{}{\Gamma \vdash \top \text{ true}} \top\text{I} \qquad \frac{\Gamma \vdash \perp \text{ true}}{\Gamma \vdash \phi \text{ true}} \perp\text{E}$$

Implication Introduction and Elimination

$$\frac{\Gamma, \phi_1 \text{ true} \vdash \phi_2 \text{ true}}{\Gamma \vdash \phi_1 \supset \phi_2 \text{ true}} \supset\text{I} \qquad \frac{\Gamma \vdash \phi_1 \supset \phi_2 \text{ true} \quad \Gamma \vdash \phi_1 \text{ true}}{\Gamma \vdash \phi_2 \text{ true}} \supset\text{E}$$

Conjunction Introduction and Elimination

$$\frac{\Gamma \vdash \phi_1 \text{ true} \quad \Gamma \vdash \phi_2 \text{ true}}{\Gamma \vdash \phi_1 \wedge \phi_2 \text{ true}} \wedge\text{I}$$

$$\frac{\Gamma \vdash \phi_1 \wedge \phi_2 \text{ true}}{\Gamma \vdash \phi_1 \text{ true}} \wedge\text{EL} \qquad \frac{\Gamma \vdash \phi_1 \wedge \phi_2 \text{ true}}{\Gamma \vdash \phi_2 \text{ true}} \wedge\text{ER}$$

Disjunction Introduction and Elimination

$$\frac{\Gamma \vdash \phi_1 \text{ true}}{\Gamma \vdash \phi_1 \vee \phi_2 \text{ true}} \vee\text{IL} \qquad \frac{\Gamma \vdash \phi_2 \text{ true}}{\Gamma \vdash \phi_1 \vee \phi_2 \text{ true}} \vee\text{IR}$$

$$\frac{\Gamma \vdash \phi_1 \vee \phi_2 \text{ true} \quad \Gamma, \phi_1 \text{ true} \vdash \phi \text{ true} \quad \Gamma, \phi_2 \text{ true} \vdash \phi \text{ true}}{\Gamma \vdash \phi \text{ true}} \vee\text{E}$$

2.2.1 Basic Properties of Intuitionistic Entailment

Reflexivity

$$\frac{}{\Gamma, \phi \text{ true} \vdash \phi \text{ true}}$$

Transitivity

$$\frac{\Gamma \vdash \psi \text{ true} \quad \Gamma, \psi \text{ true} \vdash \phi \text{ true}}{\Gamma, \phi \text{ true} \vdash \phi \text{ true}}$$

Contraction

$$\frac{\Gamma, \phi \text{ true}, \phi \text{ true} \vdash \psi \text{ true}}{\Gamma, \phi \text{ true} \vdash \psi \text{ true}}$$

Exchange

$$\frac{\Gamma \vdash \phi \text{ true}}{\pi(\Gamma) \vdash \phi \text{ true}}$$

2.3 Order Theoretic Semantics: *Heyting Algebras*

IPL viewed order theoretically gives rise to a *Heyting Algebra* (*HA*). To define *HA* we need the notion of a *lattice*. For our purposes we define it as follows¹:

Definition: A *lattice* is a non-empty *pre-order* with finite meets and joins.

In addition, we define *bounded lattice* as follows:

¹One can take a lattice being a partial order. The same results hold with slight modifications.

Definition: A *bounded lattice* (L, \leq) is a lattice that additionally has a greatest element 1 and a least element 0, which satisfy

$$0 \leq x \leq 1 \text{ for every } x \text{ in } L$$

Finally, we can define *HA*:

Definition: A *HA* is a bounded lattice $(L, \leq, 0, 1)$ s.t. for every $a, b \in L$ there exists an x (we name it $a \rightarrow b$) with the properties:

1. $a \wedge x \leq b$
2. x is the greatest such element

Axiomatization of HAs

We can axiomatize the meet (i.e. greatest lower bound)(\wedge) of ϕ, ψ for any lower bound χ .

$$\frac{}{\phi \wedge \psi \leq \phi} \qquad \frac{}{\phi \wedge \psi \leq \psi}$$

$$\frac{\chi \leq \phi \quad \chi \leq \psi}{\chi \leq \phi \wedge \psi}$$

We can axiomatize the join (\vee)(i.e. the least upper bound) of ϕ, ψ for any upper bound χ as follows .

$$\overline{\phi \leq \phi \vee \psi} \qquad \overline{\psi \leq \phi \vee \psi}$$

$$\frac{\phi \leq \chi \quad \psi \leq \chi}{\phi \vee \psi \leq \chi}$$

We can axiomatize the existence of a greatest element as follows:

$$\overline{\chi \leq 1}$$

which says that 1 is the greatest element.

We can axiomatize the existence of a least element as follows:

$$\overline{0 \leq \chi}$$

which says that 0 is the least element.

Finally, to axiomatize *HAs* we require the existence of exponentials for every ϕ, ψ as follows:

$$\overline{\phi \wedge (\phi \supset \psi) \leq \psi} \qquad \frac{\phi \wedge \chi \leq \psi}{\chi \leq \phi \supset \psi}$$

Soundness and Completeness

Theorem. $\Gamma \vdash_{IPL} \phi \text{ true}$ iff for any *Heyting Algebra* H we have $\Gamma^+ \leq \phi^*$ where $*$ is defined as the lifting of any map of **Props** to elements of H and $(+)$ is defined inductively on the length of Γ as follows

$$\begin{aligned} nil^+ &= \top \\ (\Gamma, \phi)^+ &= \Gamma^+ \wedge \phi^* \end{aligned}$$

3

Lambda Calculus With Types

3.1 From intuitionistic provability to proof trees

IPL can be viewed as a declarative axiomatization of proof constructs. Take the introduction rule for conjunction as an example:

$$\frac{\Gamma \vdash \phi_1 \text{ true} \quad \Gamma \vdash \phi_2 \text{ true}}{\Gamma \vdash \phi_1 \wedge \phi_2 \text{ true}} \wedge\text{I}$$

The rule says, “given the existence a proof of ϕ and a proof of ψ from assumptions Γ , there exists a proof of $\phi \wedge \psi$ from assumptions Γ at hand ”.

We used the description “declarative” because in this format *IPL* sequents $\Gamma \vdash \text{true}$ do not describe how such existentials are realized. It is in essence a logic of “proof relevant truth” but it does not involve the proofs themselves as first class objects.

An alternative presentation is to explicate proof constructs by directly providing a system of “proof trees”. Such, an approach was actually championed in Gentzen’s natural deduction systems and is the necessary move to obtain

proof calculi. Once we have proof explicit proof objects (either as trees, or as we will, see as terms) the system is enriched with equality principles involving such objects. Such rules give computational value (“proof dynamics”) to the constructs and are the driver idea in the “Curry–Howard Isomorphism” and its extensions.

Here we provide such a formulation in proof trees of judgments together with the equality rules on trees, essentially following Gentzen. Proof trees of judgments have the following shape:

$$\begin{array}{c} J_1, \dots, J_i \\ \vdots \\ J \end{array}$$

We focus on judgments J of the form $A \text{ true}$. Here are the rules for constructing proof trees with labeled assumptions¹. First, the deductions using reflection on hypothesis are valid:

$$\begin{array}{ccc} x_1 : A_1 \text{ true}, \dots, x_i : A_i \text{ true} & & x_1 : A_1 \text{ true}, \dots, x_i : A_i \text{ true} \\ \vdots & & \vdots \\ A_{j \in 1 \dots i} \text{ true} & & \top \text{ true} \end{array}$$

¹Essentially the constructs are directed acyclic graphs since assumptions with the same label are “bind” and substitutable together but we will be cavalier with such a details

$$\begin{array}{cc}
 \mathcal{D} & \mathcal{E} \\
 A \text{ true} & B \text{ true} \\
 \hline
 A \wedge B \text{ true}
 \end{array}$$

$$\begin{array}{cc}
 \mathcal{D} & \mathcal{D} \\
 A \wedge B \text{ true} & A \wedge B \text{ true} \\
 \hline
 A \text{ true} & B \text{ true}
 \end{array}$$


$$\begin{array}{cc}
 \mathcal{D} & \mathcal{D} \\
 A \text{ true} & B \text{ true} \\
 \hline
 A \vee B \text{ true} & A \vee B \text{ true}
 \end{array}$$


$$\begin{array}{ccc}
 & A \text{ true} & B \text{ true} \\
 \mathcal{D} & \mathcal{E} & \mathcal{F} \\
 A \vee B \text{ true} & C \text{ true} & C \text{ true} \\
 \hline
 C \text{ true}
 \end{array}$$

$$\frac{\mathcal{D} \quad \perp \text{ true}}{C \text{ true}}$$

3.1.1 Properties of Intuitionistic Entailment Redux

Proof trees by their nature satisfy the properties of entailment in 2.2.1. We will not bother with reflection and contraction. The first is trivial and the second can be shown by simple induction on the structure of trees with the proof highlighting that reflection on hypothesis is order-irrelevant. Transitivity is established by *compositionality* of proof trees and reflects the essence of hypothetical reasoning: proof trees of the appropriate proposition can be “plugged in” for assumptions to create new valid trees.

$x : A$
 \mathcal{D}
 $B \text{ true}$


\mathcal{E}
 $A \text{ true}$


Theorem. If \mathcal{D} and \mathcal{E} are valid proof trees their composition denoted as $A \text{ true}$, defined by substituting all occurrences of \mathcal{D} for E in \mathcal{E} , is a valid proof tree for $B \text{ true}$.

3.1.2 Equating Proof Trees

Having proof objects as first class citizens, permits for developing logics, essentially, as theories of (typed) equality among such objects. This idea stemmed from Gentzen's work on natural deduction and cut elimination and it is what gives to proofs computational content. Here are the proposed equalities for the proof relevant *IPL* introduced initially by Gentzen as the driver of the proof cut elimination. We will be revisiting these very same equalities and reframe them as equalities among proof terms in the next section. Nevertheless, they can be expressed in proof tree form. We show indicatively the equalities regarding the \supset connective proofs reserving the rest for the more concise notation.

$$\begin{array}{c}
 \begin{array}{c}
 x : A \\
 \mathcal{D} \\
 \hline
 B \text{ true} \\
 \hline
 A \supset B \text{ true}
 \end{array}
 \quad
 \begin{array}{c}
 \mathcal{E} \\
 A \text{ true} \\
 \mathcal{D} \\
 \hline
 B \text{ true}
 \end{array}
 \quad
 =
 \quad
 \begin{array}{c}
 \mathcal{E} \\
 A \text{ true} \\
 \mathcal{D} \\
 \hline
 B \text{ true}
 \end{array}
 \end{array}$$

$$\frac{\frac{\mathcal{D} \quad A \supset B \text{ true} \quad \overline{x : A}}{B \text{ true}}}{A \supset B} = \frac{\mathcal{D} \quad A \supset B \text{ true}}{A \supset B}$$

3.2 Linear representation of trees with proof terms: λ calculus

Proof terms provide an alternative linear representation for proof trees. The simply typed lambda calculus and its equational system can, thus, be viewed as a calculus for proof trees and proof reductions for intuitionistic logic. What's more, following the doctrine of proof relevance and of characterizing connectives by their proof reductions, i.e. working in the realm of Curry – Howard Isomorphism, we hit two birds with one stone: we both develop proof relevant logics and we get typed programming languages that reflect their computational content. The “simplest” language obtained within this program is the simply typed lambda calculus, but we will see that the same doctrine extends to different logics with different judgmental constructs.

Simply typed lambda calculus

Type Formation

$$\begin{array}{c}
\frac{}{P_i \in \text{Type}} \text{ATOM} \qquad \frac{}{\top \in \text{Type}} \text{TOP} \qquad \frac{}{\perp \in \text{Type}} \text{BOTTOM} \\
\\
\frac{\phi_1 \in \text{Type} \quad \phi_2 \in \text{Type}}{\phi_1 \rightarrow \phi_2 \in \text{Type}} \text{ARR} \qquad \frac{\phi_1 \in \text{Type} \quad \phi_2 \in \text{Type}}{\phi_1 \times \phi_2 \in \text{Type}} \text{PROD} \\
\\
\frac{\phi_1 \in \text{Type} \quad \phi_2 \in \text{Type}}{\phi_1 + \phi_2 \in \text{Type}} \text{UNION}
\end{array}$$

Context Formation

$$\frac{}{\text{nil ctx}} \text{NIL} \qquad \frac{\Gamma \text{ ctx} \quad \phi \in \text{Type} \quad x \text{ fresh in } \Gamma}{\Gamma, x : \phi \text{ ctx}} \text{\(\Gamma\)-ADD}$$

Context Reflection

$$\frac{\Gamma \text{ ctx} \quad x : \phi \in \Gamma}{\Gamma \vdash x : \phi} \text{\(\Gamma\)-REFL}$$

Top Introduction – Bottom Elimination

$$\frac{}{\Gamma \vdash \langle \rangle : \top} \top\text{I} \qquad \frac{\Gamma \vdash M : \perp}{\Gamma \vdash \text{abort}[\phi](M) : \phi} \perp\text{E}$$

Function Construction and Application

$$\frac{\Gamma, x : \phi_1 \vdash M : \phi_2}{\Gamma \vdash \lambda x.M : \phi_1 \rightarrow \phi_2} \lambda\text{-ABS} \qquad \frac{\Gamma \vdash M : \phi_1 \rightarrow \phi_2 \quad \Gamma \vdash M' : \phi_1}{\Gamma \vdash (MM') : \phi_2} \text{APP}$$

Tuple Construction and Projections

$$\frac{\Gamma \vdash M : \phi_1 \quad \Gamma \vdash M' : \phi_2}{\Gamma \vdash \langle M, M' \rangle : \phi_1 \times \phi_2} \text{TUP}$$

$$\frac{\Gamma \vdash M : \phi_1 \times \phi_2}{\Gamma \vdash \text{fst}(M) : \phi_1} \text{LPRJ} \qquad \frac{\Gamma \vdash M : \phi_1 \times \phi_2}{\Gamma \vdash \text{snd}(M) : \phi_2} \text{RPRJ}$$

Union Construction and Elimination

$$\frac{\Gamma \vdash M : \phi_1}{\Gamma \vdash \text{inj}_l[\phi_2](M) : \phi_1 + \phi_2} \text{INJL} \qquad \frac{\Gamma \vdash M : \phi_2}{\Gamma \vdash \text{inj}_r[\phi_1](M) : \phi_1 + \phi_2} \text{INJR}$$

$$\frac{\Gamma \vdash M : \phi_1 + \phi_2 \quad \Gamma, x : \phi_1 \vdash N : \phi \quad \Gamma, y : \phi_2 \vdash O : \phi}{\Gamma \vdash \text{case } M \text{ of } \text{inj}_l(x) \mapsto N \mid \text{inj}_r(y) \mapsto O : \phi} \text{VE}$$

3.2.1 Definitional Equality: Proof tree equalities as term equalities

Gentzen’s principles transliterate to an equational system for terms. In the following we are defining a congruence relation on proof terms which is usually coined as *definitional equality* and denoted $M \equiv M' : A$. We want definitional equality \equiv to be the least congruence closed under the β, η rules that directly reflect Gentzen’s principles in term form.

Definition A *congruence* is

- an equivalence relation (i.e. reflexive, symmetric and transitive)
- that commutes with operators E.g.

$$\frac{\Gamma \vdash M \equiv M' : A \wedge B}{\Gamma \vdash \text{fst}(M) \equiv \text{fst}(M') : A}$$

Informally , we should be able to replace “equals with equals” everywhere in a term.

Inversion Principle

Gentzen’s Inversion Principle captures the idea that “elim is post-inverse to intro,” or “local soundness”, which is the informal notion that the elimination rules should cancel the introduction rules. The so called β equality rules are as follows:

$$\begin{array}{c}
\frac{\Gamma \vdash M : \phi_1 \quad \Gamma \vdash N : \phi_2}{\Gamma \vdash \text{fst}(\langle M, N \rangle) \equiv M : \phi_1} \beta\wedge_1 \\
\\
\frac{\Gamma \vdash M : \phi_1 \quad \Gamma \vdash N : \phi_2}{\Gamma \vdash \text{snd}(\langle M, N \rangle) \equiv N : \phi_2} \beta\wedge_2 \quad \frac{\Gamma, x : A \vdash M : B \quad \Gamma \vdash N : A}{\Gamma \vdash (\lambda x.M)(N) \equiv [N/x]M : B} \beta\supset \\
\\
\frac{\Gamma, x : \phi_1 \vdash N : \psi \quad \Gamma, y : \phi_2 \vdash O : \psi \quad \Gamma \vdash P : \phi_1}{\Gamma \vdash (\text{case } \text{inj}_l(P) \text{ of } \text{inj}_l(x) \mapsto N \mid \text{inj}_r(y) \mapsto O) \equiv [P/x]N : \psi} \beta\vee_1 \\
\\
\frac{\Gamma, x : \phi_1 \vdash N : \psi \quad \Gamma, y : \phi_2 \vdash O : \psi \quad \Gamma \vdash Q : \phi_2}{\Gamma \vdash (\text{case } \text{inr}_r(Q) \text{ of } \text{inj}_l(x) \mapsto N \mid \text{inj}_r(y) \mapsto O) \equiv [Q/y]O : \psi} \beta\vee_2
\end{array}$$

Uniqueness of Forms

Gentzen's Uniqueness Principles on the other hand capture the idea that “intro is post-inverse to elim” (a.k.a “local completeness”). There should be only one way – modulo definitional equivalence – to prove something. The “ β ” rules give rise to computational dynamics via reduction. The so called “ η ” equality rules impose properties that the computational model should satisfy.

The η rules (a.k.a. *identity expansion*) are given below:

$$\begin{array}{c}
\frac{\Gamma \vdash M : \top}{\Gamma \vdash M \equiv \langle \rangle : \top} \eta^\top \qquad \frac{\Gamma \vdash M : A \wedge B}{\Gamma \vdash M \equiv \langle \text{fst}(M), \text{snd}(M) \rangle : A \wedge B} \eta^\wedge \\
\\
\frac{\Gamma \vdash M : \phi \supset \psi}{\Gamma \vdash M \equiv \lambda x. Mx : \phi \supset \psi} \eta^\supset \\
\\
\frac{\Gamma \vdash M : \phi_1 + \phi_2}{\Gamma \vdash M \equiv \text{case } M \text{ of } \quad \begin{array}{l} | \text{inj}_l(x) \mapsto \text{inj}_l(x) \\ | \text{inj}_r(y) \mapsto \text{inj}_r(y) \end{array} : \psi} \eta^\vee
\end{array}$$

3.3 Operational (a.k.a “term”) Semantics

It is obvious that the system is consistent in terms of provability. It’s forgetful projection is exactly IPL for which we have provided order-theoretic models. We would like to show consistency for the proof relevant model. One way is operational semantic.

The first step toward operational semantics is to break the symmetry of the definitional equivalence and construct a one-way reduction relation on lambda terms. Towards this definition we first define the notion of a *redex*:

Definition. • A β -redex is every term of the form:

$$(\lambda x : \phi. N)M \mid \text{fst}\langle M, N \rangle \mid \text{snd}\langle M, N \rangle$$

- An η -redex is every term of the form:

$$\lambda x : Mx | \langle \text{fst}, M \text{ snd } M \rangle$$

A *normal form* is a term where no redex occurs. To make the term surrounding the redex explicit, we can use a *term context*, i.e. a term with a single term hole, such as $\lambda x : []$, $(e[\bullet])$, $[\bullet]e$, where a hole can be substituted for a term to give a larger term. To be strict all single hole terms have the following diagram:

$$H := [\bullet] | (M[\bullet]) | ([\bullet]M) | \lambda x : A.H | \langle H, M \rangle | \langle M, H \rangle$$

Now we have enough tools to define the (*one-step*) $\beta\eta$ -reduction between two terms can be defined on terms that include redexes as subterms as follows :

One-step $\mapsto_{\beta\eta}$ reduction

$$\begin{aligned} & (\lambda x : \phi.N)M \mapsto [M/x]N \ (\beta) & \text{fst} \langle M, N \rangle \mapsto M \ (\beta) \\ & \text{snd} \langle M, N \rangle \mapsto N \ (\beta) & \lambda x : Mx \mapsto M \ (\eta) & \langle \text{fst } M \text{ snd } M \rangle \mapsto M \ (\eta) \\ & \frac{M \mapsto M'}{H[M] \mapsto H[M']} \text{ (SUBTERM)} \end{aligned}$$

Now we can define the reflexive, transitive closure of the previous relation as $\mapsto_{\beta\eta}^*$ to denote zero or more reduction steps. The following facts – leading

to a computational proof of consistency – hold:

Theorem. Church – Rosser for $\mapsto_{\beta\eta}$ For every term M , if $M \mapsto_{\beta\eta} N_1$ and $M \mapsto_{\beta\eta} N_2$ then there exists N' s.t. $N_1 \mapsto N'$ and $N_2 \mapsto N'$

Theorem. Church – Rosser for $\mapsto_{\beta\eta}^*$ For every term M , if $M \mapsto_{\beta\eta}^* N_1$ and $M \mapsto_{\beta\eta}^* N_2$ then there exists N' s.t. $N_1 \mapsto_{\beta\eta}^* N'$ and $N_2 \mapsto_{\beta\eta}^* N'$

The first consistency result for the equational system comes straight from the Church–Rosser properties. Since, it is easy to show that for any terms M, N s.t. where $\Gamma \vdash M \equiv N : A$ based on the \equiv axiomatization there exists a finite sequence of terms N_0, \dots, N_i such that $M \mapsto_{\beta\eta}^* N_0 \leftarrow_{\beta\eta}^* N_1 \mapsto_{\beta\eta}^* N_2 \leftarrow_{\beta\eta}^* \dots \leftarrow_{\beta\eta}^* N_i$. Now we can obtain:

Theorem. Definitional equality implies common contractum For any terms, M, N if $\Gamma \vdash M \equiv N : A$ then there exists term L s.t. $M, N \mapsto_{\beta\eta}^* L$

And as a result:

Theorem. Consistency of definitional equality of terms The definitional equality \equiv is not trivial i.e. it won't equate any two terms.

Moving toward consistency of the whole system (i.e. there is not term of type \perp), we prove a theorem for the existence of normal forms.

Theorem. Weak normalization theorem For any term M , there exists a finite sequence of terms s.t. $M \mapsto_{\beta} N_0 \mapsto_{\beta} N_1 \mapsto_{\beta} N_2 \mapsto_{\beta} \dots \mapsto_{\beta} N_i$ where N_i is a β normal form.

It is common place in metatheoretic proofs for such systems that induction on the structure of the term does not “go through”. Intuitively, a reduction can be “enlarging” the term but, yet, it is doing progress based on a different kind of metric. We build this metric based on the following definitions and facts. The idea is that we can choose a reduction strategy such that the number of *redexes of a specific type* (to be defined soon) reduce. Here are the steps towards the proof. We omit redexes related to disjunction but the proof extends to such cases pretty easily.

Definition The *degree of a type* A is defined as follows:

- $\theta(P_i) = 1$ if P_i is atomic
- $\theta(A \times B) = \theta(A \rightarrow B) = \theta(A) + \theta(B) + 1$

Definition The *degree of a redex* is defined as follows:

- Given that the type of $\lambda x.M$ is of type $A \rightarrow B$ then $d((\lambda x.M)N) = \theta(A \rightarrow B)$
- Similarly, $d(\text{fst}\langle M, N \rangle) = \theta(A \times B)$ where $A \times B$ is the type of $\langle M, N \rangle$
- Similarly for the other kinds of redexes.

Definition The *degree of a term* $d(t)$ is defined as the supremum of the degrees of its redexes.

Now we can prove the following facts:

Theorem. 1. The degree of redex r is strictly larger than the degree of its type A : $\theta(A) < d(r)$

2. The degree of a redex (r) seen as term (t) can be smaller than its redex degree since it might include other redexes: $d(r) \leq d(t)$.

3. The term resulting from a substitution $M[N/x]$ has degree: $d(M[N/x]) \leq \max(d(M), d(N), \theta(A))$ where A is the declared type of x in the type context.

Which give us the following fact that suggests the induction principle that succeeds toward the proof.

Theorem. If $M \mapsto M'$ then $d(M) < d(N)$ and hence, if $M \mapsto^+ N$ then $d(M) < d(N)$.

As a result we get a weak normalization theorem by induction on pairs $(d(M), k)$ where k is the number of redexes with degree $d(M)$.

Theorem. Weak Normalization Theorem For every term $\Gamma \vdash M : A$ there exists a normalization strategy such that $M \mapsto_{\beta}^* N$ and N is a normal form.

Combining with previous results we get:

Theorem. Consistency There is no (closed) term M for which $\vdash M : \perp$

Suppose the opposite and obtain a contradiction using the previous theorem: there is no way to obtain a normal form of a bottom type from the rules.

A stronger result is the strong normalization theorem that says that *every* strategy in normalizing. This result is important in concurrent implementations of reduction since it implies that the order in which redexes are consumed does not matter during the evaluation of expression.

The important idea behind the technique – that generalizes to proof of strong normalization for more complex calculi– is the concept of reducibility predicates. Reducibility predicates give a stronger induction principle that delivers the desired result as a lemma. Reducibility predicates are sets of terms classified by their type. and are defined by induction on the structure of their type. We show strong normalization only for the \rightarrow, \times fragment of the calculus but the technique generalizes (see, e.g. [69]).

Definition We define the predicate Red_A for a type A as follows and for closed terms M as follows:

- $M \in Red_{P_i}$ iff M is of atomic type P_i and M is normalizable.
- $M \in Red_{A \rightarrow B}$ iff M is of type $A \rightarrow B$ and $\forall N. N \in Red_A \implies (MN) \in Red_B$
- $M \in Red_{A \wedge B}$ iff M is of type $A \wedge B$, $\text{fst}(M) \in Red_A$ and $\text{snd}(M) \in Red_B$

Reducibility has the important following properties below where by *neutral*

we mean terms of the form $\langle M, N \rangle, \lambda x.M$

- Theorem.** 1. $M \in Red_A$ implies that M is normalizable.
2. $M \in Red_A$ and $M \mapsto_{\beta}^* N$ then $N \in Red_A$
3. If M is neutral then, $\forall Ns. tM \mapsto^{\beta} N.N \in Red_A \implies M \in Red_A$
4. If M is neutral and normal, then $M \in Red_A$

The proof goes by induction on the structure of type A . Now we are able to prove the following theorems:

- Theorem.** • If M, N are reducible then so is $\langle M, N \rangle$
- For all reducible M of type A if $N[M/x]$ is reducible then so is $\lambda x.N$

These results suffice to show the following theorem: Given $x_1 : A_1, \dots, x_i : A_i \vdash M : A$ then and reducible terms $v_1 \in Red_{A_1}, \dots, v_i \in Red_{A_i}$ then $M[v_1/x_1 \dots v_i/x_i] \in Red_A$ Out of which we get:

Theorem. Strong Normalization Theorem

Every term $\vdash M : A$ is strongly normalizing

3.3.1 The essence of Proofs as program

The proofs of normalization above are essentially of the same "proof strength" (induction principles) as the logical proof of cut elimination. In a nutshell, eliminating cuts is the same as normalizing proof terms (and the corresponding proof trees).

In reality, the slogan of the Curry-Howard isomorphism and, in general, of a type theoretic treatment to logic should be "Normalization as Cut Elimination". This aspect of the isomorphism can be shown explicitly follow Sieg's extraction method [70], that showcases how a construction of the Cut-free sequent calculus comes naturally from an analysis of normal proofs in the natural deduction. This result has been extremely useful through my research and I am expecting to revisit it in more detail at my thesis work.

3.3.2 Propositions as Types

There is a correspondence between propositions and types:

Propositions	Types
\top	1
$A \wedge B$	$A \times B$
$A \supset B$	function $A \rightarrow B$ or B^A
\perp	0
$A \vee B$	$A + B$

3.4 Categories for proof relevant *IPL*

In a Heyting Algebra, we have a preorder (or, partial order in the "textbook" definition) $\phi \leq \psi$ when ϕ implies ψ . *HAs* are insufficient, however, for the treatment of proof objects (there can be at most one instance of $\phi \leq \psi$ for specific ϕ, ψ). We can keep track of proofs, so if M is a proof from Γ to ψ , we want to think of it as a map $M : \Gamma + \rightarrow \psi +$. In category theory [16], the analog

of a Heyting Algebra is that of a Bi-Cartesian Closed Category (*BiCCC*). That is a category with all finite products, co-products and exponentials. For an exposition of BiCCCs and their relation with intuitionistic logic [49]. The axiomatization of a category (in general), finite (and nullary) products and co-products and exponentials is given in this section.

3.4.1 Definitions and Axioms of a Category

A category has *objects* ϕ, ψ, \dots and *arrows* $f, g, h \dots$. Each arrow goes from an object to an object. To say that g goes from ϕ to ψ we write $g : \phi \rightarrow \psi$, or say that ϕ is the domain of g , and ψ the *co-domain*. We write $Dom(g) = \phi$ and $Cod(g) = \psi$. We say that two arrows f and g are *composable* with $Dom(f) = Cod(g)$. If f and g are composable, they have a *composite*, an arrow called $f \circ g$. There is an *identity* for every object ϕ .

$\frac{}{\text{id} : \phi \rightarrow \phi} \text{ID}_{ex}$	$\frac{f : \phi \rightarrow \psi \quad g : \psi \rightarrow \chi}{g \circ f : \phi \rightarrow \chi} \text{COMP}$
$\frac{f : \phi \rightarrow \psi}{\text{id}_\psi \circ f = f : \phi \rightarrow \psi} \text{ID}_t$	$\frac{f : \phi \rightarrow \psi}{f \circ \text{id}_\phi = f : \phi \rightarrow \psi} \text{ID}_r$
$\frac{f : \phi \rightarrow \psi \quad g : \psi \rightarrow \chi \quad h : \chi \rightarrow \omega}{h \circ (g \circ f) = (h \circ g) \circ f : \phi \rightarrow \omega} \text{IDR}$	

3.4.2 Terminal, Co-Terminal objects, Products and Co-Products

Now we can think about objects in the category that correspond to propositions given in the correspondence.

Terminal Object 1 is the terminal object, also called the final object, which corresponds to \top . For any object Γ there is a unique map $\Gamma \rightarrow 1$.

$\frac{}{\langle \rangle : \phi \rightarrow 1} \text{ EXISTENCE}$	$\frac{M : \Gamma \rightarrow 1}{M = \langle \rangle : \Gamma \rightarrow 1} \text{ UNICITY}(\eta)$
---	---

Product For any objects ϕ and ψ there is an object $\chi = \phi \times \psi$ equipped with arrows $\text{fst} : \phi \times \psi \rightarrow \phi$ and $\text{snd} : \phi \times \psi \rightarrow \psi$ that is the *product* of ϕ and ψ , which corresponds to the join $\phi \wedge \psi$. For any other object Γ with arrows $M : \Gamma \rightarrow \phi$ and $\Gamma \rightarrow \psi$ there exists *unique* arrow, $\langle M, N \rangle$ s.t. $\text{fst} \circ \langle M, N \rangle = M(\beta \times_1)$ and $\text{snd} \circ \langle M, N \rangle = N(\beta \times_2)$.


$$\frac{M : \Gamma \rightarrow \phi \quad N : \Gamma \rightarrow \psi}{\langle M, N \rangle : \Gamma \rightarrow \phi \times \psi} \text{EXIST}_1$$

$$\frac{M : \Gamma \rightarrow \phi \quad N : \Gamma \rightarrow \psi}{\text{fst} \circ \langle M, N \rangle : \Gamma \rightarrow \phi} \text{EXIST}_2(\beta_1)$$

$$\frac{M : \Gamma \rightarrow \phi \quad N : \Gamma \rightarrow \psi}{\text{snd} \circ \langle M, N \rangle : \Gamma \rightarrow \psi} \text{EXIST}_3(\beta_2)$$

$$\frac{P : \Gamma \rightarrow \phi \times \psi \quad \text{fst} \circ P = M : \Gamma \rightarrow \phi \quad \text{snd} \circ P = N : \Gamma \rightarrow \psi}{P = \langle M, N \rangle : \Gamma \rightarrow \phi \times \psi} \text{UN}(\eta)$$

Diagrammatically:



Exponentials Given objects A and B , an exponential B^A (which corresponds to $A \supset B$) is an object with the following universal property:

$$\begin{array}{ccccc}
 C & & C \times A & & \\
 \downarrow \lambda(h) & & \downarrow \lambda(h) \times \text{id}_A & \searrow h & \\
 B^A & & B^A \times A & \xrightarrow{\text{ap}} & B
 \end{array}$$

such that the diagram commutes.

This means that there exists a map $\text{ap} : B^A \times A \rightarrow B$ (application map) that corresponds to implication elimination.

The universal property is that for all objects C that have a map $h : C \times A \rightarrow B$, there exists a unique map $\lambda(h) : C \rightarrow B^A$ such that

$$\text{ap} \circ (\lambda(h) \times \text{id}_A) = h : C \times A \rightarrow B$$

This means that the diagram commutes. Another way to express the induced map is $\lambda(h) \times \text{id}_A = \langle \lambda(h) \circ \text{fst}, \text{snd} \rangle$.

The map $\lambda(h) : C \rightarrow B^A$ is unique, meaning that

$$\frac{\text{ap} \circ (g \times \text{id}_A) = h : C \times A \rightarrow B}{g = \lambda(h) : C \rightarrow B^A}$$

Co-Products For any objects ϕ and ψ there is an object $\chi = \phi + \psi$ equipped with arrows $\text{inl} : \phi \rightarrow \phi + \psi$ and $\text{inr} : \psi \rightarrow \phi + \psi$ that is the

co-product of ϕ and ψ , which corresponds to the meet $\phi \wedge \psi$. For any other object ω with arrows $M : \omega \rightarrow \phi \vee \psi$ and $N : \omega \rightarrow \phi \vee \psi$ there exists *unique* arrow, M, N s.t. $\{M, N\} \circ \text{inl} = M$ and $\{M, N\} \circ \text{inr} = N$.

$$\frac{O : \Gamma \rightarrow \phi}{\text{inl} \circ O : \Gamma \rightarrow \phi + \psi} \text{EXIST}_1 \qquad \frac{P : \Gamma \rightarrow \psi}{\text{inr} \circ P : \Gamma \rightarrow \phi + \psi} \text{EXIST}_2$$


$$\frac{O : \Gamma \rightarrow \phi \quad M : \phi \rightarrow \omega \quad N : \psi \rightarrow \omega}{\{M, N\} \circ \text{inl} \circ O = M \circ O : \Gamma \rightarrow \omega} \text{EXIST}_3(\beta_1)$$

$$\frac{P : \Gamma \rightarrow \psi \quad M : \phi \rightarrow \omega \quad N : \psi \rightarrow \omega}{\{M, N\} \circ \text{inr} \circ P = N \circ P : \Gamma \rightarrow \omega} \text{EXIST}_3(\beta_2)$$

$$\frac{M : \Gamma \rightarrow \phi \quad N : \Gamma \rightarrow \psi}{\text{snd} \circ \langle M, N \rangle : \Gamma \rightarrow \phi} \text{EXIST}_3(\beta_2)$$

$$\frac{\begin{array}{cccc} O : \Gamma \rightarrow \phi & P : \Gamma \rightarrow \psi & U : \phi + \psi \rightarrow \omega & M : \phi \rightarrow \omega \\ N : \psi \rightarrow \omega & U \circ \text{inl} \circ O = M & U \circ \text{inr} \circ N = M & \end{array}}{U = \{M, N\}} \text{UN}(\eta)$$

Diagrammatically:



4

Justification Logic

In the second part of this paper I will give an overview of **JL** highlighting the parts that are closely related to constructivity to remain coherent with 2. I will emphasize **LP**, the very first logic of justification, and its deep relation with **IPL**. My scaffolding will be based upon [9], [8] that reflect this relation. Beforehand, I will allow for a more general discussion on **JL** following [5] and

other relevant papers.

4.1 A bird’s eye view

According to [5]

Justification logics are epistemic logics which allow knowledge and belief modalities to be “unfolded” into justification terms.

More specifically, in **JL** the modality in question is witnessed by a reason and propositions of the kind $\Box\phi$ become $t : \phi$ that reads “ ϕ is justified by reason t ”. Witnesses in **JL** have structure and operations. Different choices of operators result in logics that explicate different modalities ($K, T, S4, S5$). In general, there is an infinite family of justification logics. For our purposes, and in addition to type theoretic approaches to logic, **JL** reveals a computational content for *validity* in classical terms. As we will see following [3], **JL** and especially its $S4$ counterpart *The Logic of Proofs* (**LP**), can provide a unified classical *semantics* for type theoretic formulations of intuitionistic logic. In addition, following TODO and [67], **JL** mechanics can be viewed type theoretically to provide for modal typed systems that enrich computational type theories with “semantical” notions such as explicit reflection and modular binding.

4.2 Minimal Justification Logic J_0

To permit for an account of reasons, the logic is enriched with an extra sort for j for justifications. The sort of propositions is then enriched with propositions of the kind $j : \phi$ with ϕ being a proposition. Here is the abstract syntax:

$$j := s_i \mid C_i \mid j_1 * j_2 \mid j_2 + j_2$$

$$\phi := P_i \mid \perp \mid \phi_1 \wedge \phi_2 \mid \phi_1 \vee \phi_2 \mid \phi_2 \supset \phi_2 \mid \neg \phi \mid j : \phi$$

Constants C_i are symbols that can be assigned to logic axioms that are assumed to be necessary. Weaker justifications logics exist without any assignment of constants (empty *constant specifications*) or with partial constant specifications. Nevertheless, in order for the *rule of necessitation* to be admissible each axiom instance of the underlying propositional logic has to be assigned a constant. We will be coming back to this topic in later sections. Symbols s_i stand for variables.

A Hilbert-style axiomatization of J_0 is given below. Its components are Hilbert's axioms for propositional logic together with two basic rules for justification: *applicativity* and *concatenation*. Concatenation internalizes weakening of proofs.

Propositional Axioms

$$\text{P1. } \vdash \phi \supset (\psi \supset \phi)$$

$$\text{P2. } \vdash (\phi \supset (\psi \supset \chi)) \supset ((\phi \supset \psi) \supset (\phi \supset \chi))$$

$$\text{P3. } \vdash \phi \supset \psi \supset \phi \wedge \psi$$

$$\text{P4. } \vdash \phi \supset \psi \supset \psi \wedge \phi$$

$$\text{P5. } \vdash \phi \supset \phi \vee \psi$$

$$\text{P6. } \vdash \psi \supset \phi \vee \psi$$

$$\text{P7. } \vdash (\phi \supset \psi) \supset (\neg\psi \supset \neg\phi)$$

Justification Axioms

$$\text{Times. } \vdash j : (\phi \supset \psi) \supset (j' : \phi \supset j * j' : \psi)$$

$$\text{PlusL. } \vdash j : \phi \supset (j + j' : \phi)$$

$$\text{PlusR. } \vdash j : \phi \supset (j' + j : \phi)$$

The rule of the system is *Modus Ponens*.

Modus Ponens

$$\frac{\phi \supset \psi \quad \phi}{\psi} \text{ MP}$$

For the rule of necessitation to be admissible, we need necessitation of axioms to be admissible. For that reason a constant specification is required. We focus here on axiomatically appropriate constant specification **CS** because of its relation to combinatorial calculi. An axiomatization of axiomatically appropriate **CS** given below. Elements of **CS** are pairs (C, ϕ) of polymorphic (i.e. *parametrized* over propositions) constants and propositions:

Axiomatic CS

$$\begin{array}{c}
 \frac{}{\vdash (C_1[\phi, \psi], \phi \rightarrow (\psi \rightarrow \phi)) \in CS} C_1 \\
 \\
 \frac{}{\vdash (C_2[\phi, \psi, \chi], (\phi \supset (\psi \supset \chi)) \supset ((\phi \supset \psi) \supset (\phi \supset \chi))) \in CS} C_2 \\
 \\
 \frac{}{\vdash (C_3[\phi, \psi], \phi \supset \psi \supset \phi \wedge \psi) \in CS} C_3 \\
 \\
 \frac{}{\vdash (C_4[\phi, \psi], \phi \supset \psi \supset \psi \wedge \phi) \in CS} C_4 \\
 \\
 \frac{}{\vdash (C_5[\phi, \psi], \phi \supset \phi \vee \psi) \in CS} C_5 \quad \frac{}{\vdash (C_6[\phi, \psi], \psi \supset \phi \vee \psi) \in CS} C_6 \\
 \\
 \frac{}{\vdash (C_7[\phi, \psi], (\phi \supset \psi) \supset (\neg \psi \supset \neg \phi)) \in CS} C_7 \\
 \\
 \frac{}{\vdash (C_8[\phi, \psi, j, j'], j : (\phi \supset \psi) \supset (j' : \phi \supset j * j' : \psi)) \in CS} C_8 \\
 \\
 \frac{\vdash (C, \phi) \in CS}{\vdash (C!, C : \phi) \in CS} C!
 \end{array}$$

Finally we require reflection on CS:

Specification Reflection

$$\frac{\vdash (C, \phi) \in CS}{\vdash C : \phi} CSR$$

The system can be given a Natural Deduction formulation a la IPL since the following theorem holds:

Deduction Theorem For any set of propositional assumptions Γ ,
 $\Gamma, \phi \vdash \psi$ implies $\Gamma \vdash \phi \supset \psi$

4.3 Epistemic motivation

JL as an epistemic logic departs from previous traditions of logic of knowledge based on universality judgments. From [5]

The modal approach to the logic of knowledge is, in a sense, built around the universal quantifier: X is known in a situation if X is true in all situations indistinguishable from that one. Justifications, on the other hand, bring an existential quantifier into the picture: X is known in a situation if there exists a justification for X in that situation

This fresh approach on epistemic tradition has been utilized to solve many problems in formal epistemology (see [6]). We give here a solution to the famous 'Red barn problem' that is also a pedagogical example on how deduction in the system works.

The red barn problem can be stated as follows:

Suppose I am driving through a neighborhood in which, unbeknownst to me, papier-mâché barns are scattered, and I see that

the object in front of me is a barn. Because I have barn-before-me percepts, I believe that the object in front of me is a barn. Our intuitions suggest that I fail to know barn. But now suppose that the neighborhood has no fake red barns, and I also notice that the object in front of me is red, so I know a red barn is there. This juxtaposition, being a red barn, which I know, entails there being a barn, which I do not, “is an embarrassment”

The red barn example can be represented in a system of modal logic where $\Box\phi$ represents knowledge of ϕ that, in contrast to the the justified approach, is forgetful with respect to reasons. The formalization and the accompanying problem go as follows:

1. $\Box B$, ‘I believe that the object in front of me is a red barn’.
2. $\Box(B \wedge R)$, ‘I believe that the object in front of me is a red barn’.

At the metalevel, 2 is actually knowledge, whereas by the problem description, 1 is not knowledge.

3. $\Box(B \wedge R \supset B)$, a knowledge assertion of a logical axiom.

Within this formalization, it appears that epistemic closure in its modal form (2) is violated: line 2, $\Box(B \wedge R)$, and line 3, $(B \wedge R \supset B)$ are cases of knowledge whereas $\Box B$ (line 1) is not knowledge. The modal language here does not seem to help resolving this issue.

Of course, one can resolve this by introducing a second modality (e.g. for ‘I believe that’). But then similar problems can occur (e.g. by adding a third

modality read as ‘it should be’). Indexing of modalities with reasons solves this problem in its generality: by permitting the applicative closure only on reasons of the same sort one can overcome this defect.

1. $u : B$, ‘ u is a reason to believe that the object in front of me is a barn’;
2. $v : (B \wedge R)$, ‘ v is a reason to believe that the object in front of me is a red barn’;
3. $a : (B \wedge R \supset B)$, because of logical awareness.

On the metalevel, the problem description states that 2 and 3 are cases of knowledge, and not merely belief, whereas 1 is belief which is not knowledge. Here is how the formal reasoning goes:

4. $a : (B \wedge R \supset B) \supset (v : (B \wedge R) \supset a * v : B)$, by Times
5. $v : (B \wedge R) \supset a * v : B$, from 3 and 4, by propositional logic; $a * v : B$, from 2 and 5, by propositional logic.

4.4 Proof theoretic view

In 2 we gave an analytic account of the BHK principles of constructive proofs. In the paper “Eine Interpretation des intuitionistischen Aussagenkalküls”, Gödel gave a classical provability interpretation of BHK using the modal system S4.

The standard axiomatization of S4 is given below:

The system S4

P1 – P7

K. $\vdash \Box(\phi \supset \psi) \supset (\Box\phi \supset \Box\psi)$

T. $\vdash \Box\phi \supset \phi$

4. $\vdash \Box\phi \supset \Box\Box\phi$

Modus Ponens

$$\frac{\phi \supset \psi \quad \phi}{\psi} \text{ MP}$$

Gödel's result can be summarized in the following theorem:

Gödel-Tarski Translation of Intuitionistic Logic

$$\Gamma \vdash_{\text{IPL}} \phi \rightarrow \Gamma \vdash_{\text{S4}} \text{tr}(\phi)$$

where $\text{tr}(\phi)$ is obtained by ϕ by \Box -ing its subformulas.

After this result the state of the project of a classical interpretation of BHK semantics was as follows: $\text{IPC} \leftrightarrow \text{S4} \leftrightarrow ? \leftrightarrow \text{CLASSICAL PROOFS}$. Filling the missing part was the motivation behind LP, the first Justification Logic.

4.5 The Logic of Proofs

An axiomatization of LP with axiomatically appropriate constant specification as defined in 4.2 can be given as follows:

The system LP

P1 – P7

Times. $\vdash j : (\phi \supset \psi) \supset (j' : \phi \supset j * j' : \psi)$

PlusL. $\vdash j : \phi \supset (j + j' : \phi)$

PlusR. $\vdash j : \phi \supset (j' + j : \phi)$

T. $\vdash j : \phi \supset \phi$

4. $\vdash j : \phi \supset (j! : j : \phi)$

4.6 Metatheoretic Results

The *Deduction Theorem* holds for LP

Deduction Theorem Any deduction of the kind $\Gamma, \phi \vdash \psi$ implies $\Gamma \vdash \phi \supset \psi$.

Also, the lifting property can be obtained:

Lifting Lemma

Any deduction of the kind $\vec{j} : \Gamma, \Delta \vdash \phi$ implies $\vec{j} : \Gamma, \vec{s} : \Delta \vdash j'(\vec{j}, \vec{s}) : \phi$ where \vec{j} is a vector metavariables to be substituted for arbitrary

polynomials and \vec{s} is a vector of (object) variables.

In addition, **LP** is the forgetful projection of **S4**. More specifically, consider and formula of **LP** ϕ and the transformation $F_{\Box}(\phi)$ that replaces all subformulae of ϕ of the kind $j : \phi'$ with $\Box\phi'$. The following theorem holds:

Forgetful Projection Property

$\Gamma \vdash_{\text{LP}} \phi$ implies $\Gamma \vdash_{\text{S4}} F_{\Box}(\phi)$

The inverse also holds as the realization theorem says. Before introducing the realization procedure we give a motivating example.

Example: Realization of $\vdash_{\text{S4}} \Box\phi \vee \Box\psi \supset \Box(\phi \vee \psi)$

1. $\phi \supset \phi \vee \psi, \psi \supset \phi \vee \psi$ Prop. Axioms;
2. $C : (\phi \supset \phi \vee \psi), C' : (\psi \supset \phi \vee \psi)$ From **CS** rules.
3. $s : \phi \supset C * s : \phi \vee \psi$, From 1,2 and **Times** and **MP**
4. $t : \psi \supset C' * t : \phi \vee \psi$, Similarly
5. $C*s : \phi \vee \psi \supset (C*s + C'*t) : \phi \vee \psi$ and $C'*t : \phi \vee \psi \supset (C*s + C'*t) : \phi \vee \psi$,
From **Rplus**, **Lplus**
6. $s : \phi \supset (C * s + C' * t) : \phi \vee \psi$, From 3,5 by Propositional Logic.
7. $t : \psi \supset (C * s + C' * t) : \phi \vee \psi$, From 4,5 by Propositional Logic.
8. $s : \phi \vee t : \psi \supset (C * s + C' * t) : \phi \vee \psi$, From 6,7 and Propositional Logic.

4.6.1 Realization

The realization theorem gives an algorithmic process for transforming cut-free deductions in **S4** to **LP**. By an **LP**-realization of a modal formula ϕ we mean an assignment of proof polynomials to all occurrences of the modality in ϕ . Let ϕ^r be the image of ϕ under a realization r .

The polarity of \Box s in a formula is relevant in realizations. We define positive and negative occurrences of modality in a formula and a sequent.

\Box Polarities

1. The indicated occurrence of \Box in $\Box\phi$ is of positive polarity;
2. any occurrence of \Box in the subformula ϕ of $\psi \supset \phi, \psi \wedge \phi, \phi \wedge \psi, \psi \vee \phi, \phi \vee \psi, \Box\phi, \Gamma \Rightarrow \Delta, \phi$ – we will be defining \Rightarrow momentarily – has the same polarity as the same occurrence of \Box in ϕ .
3. any occurrence of \Box in the subformula ϕ of $\neg\phi, \phi \supset \psi, \Gamma, \phi \Rightarrow \Delta$, has polarity opposite to the polarity of the very same occurrence of \Box in ϕ .

Next we give a cut-free sequent formulation of **S4** (reference) with sequents $\Gamma \vdash \Delta$, where Γ and Δ are finite multisets of modal formulas. The left hand multisets are to be read conjunctively and the right hand ones disjunctively. The rules are the rules given below together with the typical structural ones.

$$\begin{array}{c}
\frac{}{\Gamma, \phi \vdash \phi, \Delta} \text{REFL} \qquad \frac{\Gamma \vdash \phi, \Delta}{\Gamma, \neg \phi \vdash \Delta} \neg\text{L} \qquad \frac{\phi, \Gamma \vdash \Delta}{\Gamma \vdash \neg \phi, \Delta} \neg\text{R} \\
\\
\frac{\Gamma, \phi, \psi \vdash \Delta}{\Gamma, \phi \wedge \psi \vdash \Delta} \wedge\text{L} \qquad \frac{\Gamma \vdash \phi, \Delta \quad \Gamma \vdash \psi, \Delta}{\Gamma \vdash \phi \wedge \psi, \Delta} \wedge\text{R} \\
\\
\frac{\Gamma, \phi \vdash \Delta \quad \Gamma, \psi \vdash \Delta}{\Gamma, \phi \vee \psi \vdash \Delta} \vee\text{L} \qquad \frac{\Gamma \vdash \phi, \psi, \Delta}{\Gamma \vdash \phi \vee \psi \vdash \Delta} \vee\text{R} \\
\\
\frac{\Gamma \vdash \phi, \Delta \quad \Gamma \psi \vdash \Delta}{\Gamma, \phi \supset \psi \vdash \Delta} \supset\text{L} \qquad \frac{\Gamma \vdash \phi, \Delta \quad \Gamma \psi \vdash \Delta}{\Gamma, \phi \supset \psi \vdash \Delta} \supset\text{R} \\
\\
\frac{\phi, \Gamma \vdash \Delta}{\Box \phi, \Gamma \vdash \Delta} \Box\text{L} \qquad \frac{\Box \Gamma \vdash \phi, \Delta}{\Box \Gamma \vdash \Box \phi, \Delta} \Box\text{R}
\end{array}$$

Relevant in the realization proof is the sequent formulation of **LP**, the system **LPG** which enjoys the cut-elimination property resulting in the system **LPG**[−]. The rules relevant to justifications are given below.

$$\begin{array}{c}
\frac{\Gamma, \phi \vdash \phi, \Delta}{\Gamma, t : \phi \vdash \phi, \Delta} :L \quad \frac{\Gamma \vdash t : \phi, \Delta}{\Gamma \vdash !t : t : \phi, \Delta} !R \quad \frac{\Gamma \vdash t : \phi, \Delta}{\Gamma \vdash (t + s) : \phi, \Delta} +L \\
\\
\frac{\Gamma \vdash t : \phi, \Delta}{\Gamma \vdash (s + t) : \phi, \Delta} +R \quad \frac{\Gamma \vdash s : \phi \supset \psi, \Delta \quad \Gamma \vdash t : \phi, \Delta}{\Gamma \vdash s * t : \psi, \Delta} *R \\
\\
\frac{\Gamma \vdash \phi, \Delta}{\Gamma \vdash c : \phi, \Delta} cR
\end{array}$$

Utilizing the previous systems the realization theorem shows:

Realization Theorem If $\Gamma \vdash_{S4} \phi$ then there is a *normal* realization s.t. $\Gamma \vdash_{LP} \phi^r$. By normal we mean a realization for which all occurrences of \Box are realized by proof variables and the corresponding constant specification is injective.

4.6.2 Kripke - Fitting Semantics

In this section I will be discussing Kripke – Fitting Semantics[33] for Justification Logic $J_0 + CS$ very briefly.

A possible world justification logic model for the system $J_0 + CS$ is a structure $M = \langle G, R, E, V \rangle$. $\langle G, R \rangle$ is a standard K frame, where G is a set of possible worlds and R is a binary relation on it. V is a mapping from propositional variables to subsets of G , specifying atomic truth at possible

worlds. E is an evidence function that maps pairs of justification terms and formulas to sets of worlds.

Given such a model, we define the \models relation as follows:

$\forall \Gamma \in G$

$M, \Gamma \models P$ iff $\Gamma \in V(P)$ for P a propositional letter

- It is not the case that $M, \Gamma \models \perp$
- $M, \Gamma \models \phi \supset \psi$ iff it is not the case that $M, \Gamma \models \phi$ or $M, \Gamma \models \psi$
- $M, \Gamma \models (j : \phi)$ if and only if $\Gamma \in E(j, \phi)$ and, $\forall \Delta \in G$ with $\Gamma R \Delta$, we have that $M, \Delta \models \phi$.

The following conditions on evidence functions are assumed:

$$E(j, \phi \supset \psi) \cap E(j', \phi) \subseteq E(j * j', \psi)$$

$$E(j, \phi) \cup E(j', \phi) \subseteq E(j + j', \phi)$$

Finally, the Constant Specification CS should be taken into account. Recall that constants are intended to represent reasons for basic assumptions that are accepted outright. A model $M = \langle G, R, E, V \rangle$ meets Constant Specification CS provided: if $(C, \phi) \in CS$ then $E(c, \phi) = G$.

Typical, soundness and completeness results can be shown for such models. They can also be extended for all other justification logics.

5

Curry – Howard view of justification logic

In this paper we suggest reading a constructive necessity of a formula ($\Box A$) as internalizing a notion of constructive truth of A (a proof within a deductive system I) and validity of A (a proof under an interpretation $\llbracket A \rrbracket_I$ within

some system J). An example of such a relation is provided by the simply typed lambda calculus (as I) and its implementation in SK combinators (as J). We utilize justification logic to axiomatize the notion of validity-under-interpretation and, hence, treat a “semantical” notion in a purely proof-theoretic manner. We present the system in Gentzen-style natural deduction formulation and provide reduction and expansion rules for the \Box connective. Finally, we add proof-terms and proof-term equalities to obtain a corresponding calculus (\mathbf{Jcalc}^-) that can be viewed as an extension of the Curry–Howard isomorphism with justifications. We provide standard metatheoretic results and suggest a programming language interpretation in languages with foreign function interfaces (*FFIs*).

5.1 Introduction: Necessity and Constructive Semantics

In his seminal “Explicit Provability and Constructive Semantics” [4] Artemov developed a constructive, proof-theoretic semantics for **BHK** proofs [74] in what turned out to be the first development of a family of logics that we now call justification logic. The general idea, upon which we build our calculus, is that semantics of a deductive system I can be viewed in a solely proof-theoretic manner as mappings of proof constructs of I into another proof system J (which we call justifications). As an example one could think I being Heyting arithmetic and J some “stronger” system (e.g. a classical

axiomatization of Peano arithmetic, a classical or intuitionistic set theory etc). In Artemov’s work I is assumed to be based on intuitionistic logic and J on classical logic. We, initially, mute such assumptions to focus exclusively on the mechanics of necessity in this framework. We recover them later and study their relation to the Rule of Necessitation for our system. What’s more, such a semantic relation can be treated logically giving rise to a modality of explicit necessity. Different sorts of necessity (K , D , $S4$, $S5$) have been offered an explicit counterpart under the umbrella of justification logic. Some of them have been studied within a Curry–Howard setting [14]. Our paper focuses on K modality and should be viewed as the counterpart of [21] with justifications as we explain in 6.2.

5.1.1 Deductive Systems, Validity and Necessity

Following a framework championed by Lambek [48, 50], let us assume two deductive systems I (with propositional universe U_I , a possibly non-empty signature of axioms Σ_I and an entailment relation $\Sigma_I; \Gamma \vdash_I A$) and J (resp. with U_J , Σ_J and $\Sigma_J; \Delta \vdash_J \phi$). We will be using Latin letters for the formulae of I and Greek letters for the formulae of J . We will be omitting the Σ signatures when they are not relevant.

For the entailment relations of the two systems we require the following elementary principles¹:

¹We are not excluding other connectives but by imposing such minimal requirements we show that “necessity” (\Box) connective can be treated generically and orthogonally of the presence of other connectives

1. *Reflexivity.* In both relations Γ and Δ are multisets of formulas (contexts) that enjoy reflexivity:

$$A \in \Gamma \implies \Gamma \vdash_I A$$

$$\phi \in \Delta \implies \Delta \vdash_J \phi$$

2. *Compositionality.* Both relations are closed under deduction composition:

$$\Gamma \vdash_I A \text{ and } \Gamma', A \vdash_I B \implies \Gamma, \Gamma' \vdash_I B$$

$$\Delta \vdash_J \phi \text{ and } \Delta', \phi \vdash_J \psi \implies \Delta, \Delta' \vdash_J \psi$$

3. *Top.* Both systems have a distinguished top formula \top for which under any Γ, Δ :

$$\Gamma \vdash_I \top_I \text{ and } \Delta \vdash_J \top_J$$

Now we can define:

Definition. Given a deductive system I , an *interpretation for I* , noted by $\llbracket \bullet \rrbracket_J$, is a pair $(J, \llbracket \bullet \rrbracket)$ of a deductive system J together with a (functional) mapping $\llbracket \bullet \rrbracket : U_I \rightarrow U_J$ on propositions of I into propositions of J extended to multisets of formulae of U_I with the following properties:

1. *Top preservation.* $\llbracket \top_I \rrbracket = \top_J$
2. *Structural interpretation of contexts.* For Γ contexts of the form A_1, \dots, A_n :

$$\llbracket \Gamma \rrbracket = \llbracket A_1 \rrbracket, \dots, \llbracket A_n \rrbracket$$

(trivially empty contexts map to empty contexts. As in [48] they can be treated as the \top element).

Definition. Given a deductive system I and an interpretation $\llbracket \bullet \rrbracket_J$ for I we define a *corresponding validation of a deduction* $\Sigma_I; \Gamma \vdash_I A$ as a deduction $\Sigma_J; \Delta \vdash_J \phi$ in J such that $\llbracket A \rrbracket = \phi$ and $\Delta = \llbracket \Gamma \rrbracket$. We will be writing $\llbracket \Sigma_I; \Gamma \vdash_I A \rrbracket_J$ to denote such a validation.

Definition. Given a deductive system I , we say that an interpretation $\llbracket \bullet \rrbracket_J$ is *logically complete* when for all purely logical deductions \mathcal{D} (i.e. deductions that make no use of Σ_I) in I there exists a corresponding (purely logical) validation $\llbracket \mathcal{D} \rrbracket$ in J . i.e.

$$\forall \mathcal{D}. \mathcal{D} : \Gamma \vdash_I A \implies \exists \llbracket \mathcal{D} \rrbracket : \llbracket \Gamma \vdash A \rrbracket_J$$

2

Examples of triplets $(I, J, \llbracket \bullet \rrbracket_J)$ of logical systems that fall under the definition above are: any intuitionistic system mapped to a classical one under the embedding $\llbracket A \supset B \rrbracket = \tilde{\neg} A \tilde{\vee} B$ where $\tilde{\neg}$ and $\tilde{\vee}$ are classical connectives, the opposite direction under double negation translation, an intuitionistic

²Note, that we require existence but not uniqueness. Nevertheless, if we treat deductive systems in a proof irrelevant manner as preorders the above definition gives uniqueness vacuously. In a more refined approach where I and J are viewed as categories of proofs the above “logical completeness” translates to the requirement that if the set of (purely logical) arrows $Hom_I(\Gamma, A)$ is non empty then $Hom_J(\llbracket \Gamma \rrbracket, \llbracket A \rrbracket_J)$ cannot be empty (i.e. that $\llbracket \bullet \rrbracket_J$ can be extended to a functor). We leave a complete categorical semantics of our logic for future work but we expect a generalization of the endofunctorial interpretations of K modality appearing in [21, 46].

system mapped to another intuitionistic system (i.e. a mapping of atomic formulas of I to atomic formulas of J extended naturally to the intuitionistic connectives or, simply, the identity mapping) etc. A vacuous validation (when $\llbracket \bullet \rrbracket_J$ maps everything to \top) gives another example.

The main thesis that is exposed in this chapter is that this notion of “double proof” (reasoning about proofs that exists in two related systems) provides for an understanding of necessity in proof theoretic terms. In addition, we argue, that this is the driver of (at least) the simplest form of necessity (K) that appears in justification logic (*necessity as internalization*). We will focus on the case where I (the propositional part of our logic) is based on the implicative fragment of intuitionistic logic and show how justification logic provides for an axiomatization of such logically complete interpretations $\llbracket \bullet \rrbracket_J$ of implicative intuitionistic logic. In what follows we provide a natural deduction for an intuitionistic system I (truth), an axiomatization/specification of $\llbracket \bullet \rrbracket_J$ (treated abstractly as a function symbol on types) and a treatment of basic necessity that relates the two deductions by internalizing a notion of “double truth” (proof in I and existence of corresponding validation in J).

5.2 Judgments of \mathbf{Jcalc}^-

We aim for a reading of necessity that internalizes a notion of “double proof” in two deductive systems. Motivated by the discussion and definitions in the previous section we will treat the notion of interpretation abstractly – as a

function symbol on types – and axiomatize in accordance. Intuitively we want:

$$\Box A \text{ true} := A \text{ true} \ \& \ A \text{ valid} = A \text{ true in } I \ \& \ \llbracket A \rrbracket \text{ true in } J$$

We will be dropping indexes I, J since they can be inferred by the different kinds of assumption contexts. In addition, we omit signatures Σ since they do not offer anything from a logical perspective.

Logical entailment for the proposed \Box connective can be summarized easily given our previous discussion. Given a deduction $\mathcal{D} : A \vdash B$ and the existence of validation $\llbracket \mathcal{D} \rrbracket : \llbracket A \rrbracket \vdash \llbracket B \rrbracket$ then given $\Box A$ (i.e. a proof of a $\vdash A$ and a validation $\vdash \llbracket A \rrbracket$) we obtain a double proof of B (and hence, $\Box B$) by *compositionality* of the underlying systems. Using standard, proof tree notation with labeled assumptions we formulate our rule of the connective in natural deduction:

$$\frac{\begin{array}{ccc} \vdots & \vdots & \vdots \\ \Box A & B & \llbracket B \rrbracket \end{array}}{\Box B} \quad \begin{array}{c} \text{--- } x \\ A \\ \vdots \\ \vdots \end{array} \quad \begin{array}{c} \text{--- } s \\ \llbracket A \rrbracket \\ \vdots \\ \vdots \end{array} \quad I_{\Box B} E_{\Box A}^{x,s}$$

We can, easily, generalize to \Box ed contexts (of the form $\Box A_1, \dots, \Box A_i$) of arbitrary length:

[illegible]

We read as “Introducing $\Box B$ after eliminating $\Box A_1 \dots \Box A_i$ crossing out (vectors of) labels \vec{x}, \vec{s} ”. Interestingly, the same rule eliminates boxes and introduces new ones. This is not surprising for K modality (it is a left-right rule as we will see (5.2.4). See also discussion in [21, 23]). We will be referring to this rule as “ \Box Intro–After–Elim” or, simply \Box_{IE} , from now on.

Note that we define the \Box connective negatively, yet (pure) introduction rules for the \Box connective are derivable. Such are instances of the previous Intro–After–Elim rule when Γ' is empty which conforms exactly with the idea of necessity internalizing double theoremhood.

$$\frac{\vdash B \quad \vdash \llbracket B \rrbracket}{\square B} I_{\square B}$$

In the next section, we provide the whole calculus in natural deduction format. As expected we will extend the implicative fragment of intuitionistic logic with

- Judgments about validity (justification logic).
- Judgments that relate truth and validity (modal judgments).

5.2.1 Natural Deduction for \mathbf{Jcalc}^-

The treatment of necessity in the previous section is completely orthogonal to the underlying systems (it just assumes the basic requirements stated for the behavior $\llbracket \cdot \rrbracket$). *In this section we will provide a full calculus and in congruence with justification logic we will*

Following type theory conventions, we first provide rules underlying type construction, then rules for well-formedness of (labeled) assumption contexts and rules introducing and eliminating connectives. The rules below should be obvious except for small caveat. On the one hand, the type universe of U_I and the proof trees of I are inductively defined as usual; on the other hand, the host theory J (its corresponding universe, connectives and proof trees) is “black boxed”. What we actually axiomatize are the properties that all (logic preserving) interpretations of I should conform to, independently of the specifics of the host theory. Validity judgments should thus be read as specifications of provability (existence of proofs) of any candidate J .

When we write $\llbracket \Gamma \rrbracket \vdash \llbracket \phi \rrbracket$ it reads as there exists derivation $\mathcal{D} : \Delta \rrbracket \vdash_J \psi \rrbracket$ s.t. $\Delta = \llbracket \Gamma \rrbracket$ and $\psi = \llbracket \phi \rrbracket$)

We use \mathbf{Prop}_0 to denote the type universe of I and $\llbracket \mathbf{Prop}_0 \rrbracket$ to denote its image under an interpretation, \mathbf{Prop}_1 denotes modal (“boxed”) types and \mathbf{Prop} the union of $\mathbf{Prop}_0, \mathbf{Prop}_1$. We write P_k with k ranging in some subset of natural numbers to denote atomic propositions in I .

Judgments on Type Universe(s)

$$\begin{array}{c}
\frac{}{P_k \in \mathbf{Prop}_0} \text{ATOM} \qquad \frac{}{\top \in \mathbf{Prop}_0} \text{TOP} \qquad \frac{A \in \mathbf{Prop}_0}{\Box A \in \mathbf{Prop}_1} \text{BOX} \\
\\
\frac{A \in \mathbf{Prop}_0 \quad B \in \mathbf{Prop}_0}{A \supset B \in \mathbf{Prop}_0} \text{ARR}_0 \qquad \frac{A \in \mathbf{Prop}_1 \quad B \in \mathbf{Prop}_1}{A \supset B \in \mathbf{Prop}_1} \text{ARR}_1 \\
\\
\frac{A \in \mathbf{Prop}_0}{\llbracket A \rrbracket \in \llbracket \mathbf{Prop}_0 \rrbracket} \text{BRC}
\end{array}$$

For labeled contexts of assumptions we require standard wellformedness conditions (i.e. uniqueness of labels). We use letters x_i , or simply x , for labels of contexts with assumptions in \mathbf{Prop}_0 , x'_i or simply x' for contexts with assumptions in \mathbf{Prop}_1 and s_i , or simply s , for $\llbracket \mathbf{Prop}_0 \rrbracket$ contexts. We use \circ for the empty context of \mathbf{Prop}_0 and \mathbf{Prop}_1 and \dagger for the empty context of $\llbracket \mathbf{Prop}_0 \rrbracket$. We abuse notation and write $x : A \in \Gamma$ (or, similarly, $s : \llbracket A \rrbracket \in \Delta$) to denote that the label x is assigned type A in Γ ; or $\Gamma \in \mathbf{Prop}_0$ (resp. $\Gamma \in \mathbf{Prop}_1$, $\Delta \in \llbracket \mathbf{Prop}_0 \rrbracket$) to denote that Γ is a wellformed context with co-domain of elements in \mathbf{Prop}_0 (resp. in \mathbf{Prop}_1 , $\llbracket \mathbf{Prop}_0 \rrbracket$). For $\Gamma \in \mathbf{Prop}_0$ we define $\llbracket \Gamma \rrbracket$ as the lifting of the context Γ through the $\llbracket \bullet \rrbracket$ symbol (with appropriate renaming of variables – e.g. $x_i \rightsquigarrow s_i$). For the vacuous case when Γ is empty we require $\llbracket \circ \rrbracket = \dagger$ to be well formed.

In the following entry we define proof trees (in turnstile representation) of the intuitionistic source theory I . For all following rules we assume

$\Gamma, A, B \in \text{Prop}_0$:

Judgments on Truth $\Gamma, A, B \in \text{Prop}_0$		
$\frac{x : A \in \Gamma}{\Gamma \vdash_{\text{IPC}} A} \Gamma_0\text{-REFL}$	$\frac{}{\Gamma \vdash_{\text{IPC}} \top} \top_0\text{I}$	$\frac{\Gamma, x : A \vdash_{\text{IPC}} B}{\Gamma \vdash_{\text{IPC}} A \supset B} \supset_0\text{I}$
$\frac{\Gamma \vdash_{\text{IPC}} A \supset B \quad \Gamma \vdash_{\text{IPC}} A}{\Gamma \vdash_{\text{IPC}} B} \supset_0\text{E}$		

For the calculus of interpretation (validity) we demand context reflexivity, compositionality and logical completeness with respect to intuitionistic implication. Logical completeness is specified axiomatically, since the host theory is “black boxed”. Following justification logic, we use an axiomatic characterization of combinatory logic (for \supset) together with the requirement that the interpretation preserves modus ponens:

Judgments on Validity with $\Delta \in \llbracket \text{Prop}_0 \rrbracket$		
$\frac{s : \llbracket A \rrbracket \in \Delta}{\Delta \vdash_{\text{IPC}} \llbracket A \rrbracket} \Delta\text{-REFL}$	$\frac{}{\Delta \vdash_{\text{IPC}} \llbracket \top \rrbracket} \text{AX}_1$	$\frac{A, B \in \text{Prop}_0}{\Delta \vdash \llbracket A \supset (B \supset A) \rrbracket} \text{AX}_2$
$\frac{A, B, C \in \text{Prop}_0}{\Delta \vdash \llbracket A \supset (B \supset C) \supset ((A \supset B) \supset (A \supset C)) \rrbracket} \text{AX}_3$		
$\frac{\Delta \vdash_{\text{IPC}} \llbracket A \supset B \rrbracket \quad \Delta \vdash_{\text{IPC}} \llbracket A \rrbracket}{\Delta \vdash_{\text{IPC}} \llbracket B \rrbracket} \text{MP}$		

Finally, we have judgments in the \Box ed universe (Prop_1). These are

context reflection, the \Box Intro-After-Elim rule, and the rules for intuitionistic implication between \Box ed types ³.

Judgments on Necessity with $\Gamma \in \text{Prop}_1$, $\text{length}(\Gamma) = i$, $1 \leq k \leq i$ and, $\Gamma', A, A_k, B \in \text{Prop}_0$	
$\frac{x' : \Box A \in \Gamma}{\Gamma \vdash_{\text{IPC}} \Box A} \Gamma_1\text{-REFL}$	
$\frac{(\forall A_i \in \Gamma'. \Gamma \vdash_{\text{IPC}} \Box A_i) \quad \Gamma' \vdash_{\text{IPC}} B \quad \llbracket \Gamma' \rrbracket \vdash_{\text{IPC}} \llbracket B \rrbracket}{\Gamma \vdash_{\text{IPC}} \Box B} I_{\Box B} E_{\Box A_1 \dots \Box A_i}^{\vec{x}, \vec{s}}$	
$\frac{\Gamma, x' : \Box A \vdash_{\text{IPC}} \Box B}{\Gamma \vdash_{\text{IPC}} \Box A \supset \Box B} \supset_1 I$	$\frac{\Gamma \vdash_{\text{IPC}} \Box A \supset \Box B \quad \Gamma \vdash_{\text{IPC}} \Box A}{\Gamma \vdash_{\text{IPC}} \Box B} \supset_1 E$

(Pure) $\Box I$ as derivable rule

We stress here that \Box can be introduced positively with the previous rule with $\Gamma' = \circ$. The first premise reduces to a simple requirement that $\Gamma \in \text{Prop}_1$.

$$\frac{\circ \vdash_{\text{IPC}} A \quad \dagger \vdash_{\text{IPC}} \llbracket A \rrbracket}{\Gamma \vdash_{\text{IPC}} \Box A} I_{\Box A}$$

³The implication and elimination rules in Prop_1 actually coincide with the ones in Prop_0 since we are focusing on the case where I is intuitionistic. This need not necessarily be the case as we have explained. Intuitionistic implication among \Box types should be read as “double proof of A implies double proof of B ” and would still be defined even if we did not observe any kind of implication in I . Similarly, one could provide intuitionistic conjunction or disjunction between \Box types independently of I and, vice versa, one could add connectives in I that are not observed between \Box ed types.

A simple derivation

We show here that the K axiom of modal logic is a theorem (omitting some obvious steps). In the following

$$\Gamma := x'_1 : \Box(A \supset B), x'_2 : \Box A, \Gamma' = x_1 : A \supset B, x_2 : A, \llbracket \Gamma' \rrbracket = s_1 : \llbracket A \supset B \rrbracket, s_2 : \llbracket A \rrbracket$$

$$\frac{\frac{\Gamma \vdash \Box(A \supset B) \quad \Gamma \vdash \Box A \quad \Gamma' \vdash B \quad \llbracket \Gamma' \rrbracket \vdash \llbracket B \rrbracket}{\Box(A \supset B), \Box A \vdash \Box B} I_{\Box A} E_{\Box A \supset B, \Box A}^{x_1, x_2, s_1, s_2}}{\Box(A \supset B) \vdash \Box A \supset \Box B} \supset_1 I$$

$$\frac{\Box(A \supset B) \vdash \Box A \supset \Box B}{\circ \vdash \Box(A \supset B) \supset \Box A \supset \Box B} \supset_1 I$$

5.2.2 Logical Completeness, Admissibility of Necessitation and Completeness with respect to Hilbert Axiomatization

Here we give a Hilbert axiomatization of the \supset fragment of intuitionistic K logic in order to compare it with our system. Here $\vdash^{\mathcal{H}}$ captures the textbook (metatheoretic) notion of “deduction from assumptions” in a Hilbert style axiomatization. We assume the restriction of the system to formulas up to modal degree 1.

Hilbert Style Formulation

$$\begin{array}{ll}
\text{AX1. } A \supset (B \supset A) & \text{AX2. } (A \supset (B \supset C)) \supset ((A \supset B) \supset (A \supset C)) \\
\\
\text{K. } \Box(A \supset B) \supset \Box A \supset \Box B & \text{MP } \frac{A \supset B \quad A}{B} \quad \text{NEC } \frac{\vdash^{\mathcal{H}} A}{\Box A}
\end{array}$$

It is easy to verify that axioms 1, 2 are derived theorems of $\mathcal{J}\text{calc}^-$ in Prop_0 . The rule Modus Ponens is also admissible trivially, whereas axiom K was shown to be a theorem in the previous section (5.2.1). The rule of Necessitation is not obviously admissible though. In our reading of necessity the admissibility of this rule is directly related to the requirement of “logical completeness of the interpretation” i.e. preservation of logical theoremhood. In general, adding more connectives in I would require additional specifications for the host theory to obtain necessitation.

The steps of the proof are given in the Appendix, but this is essentially the “lifting lemma” in justification logic [4]. The proof fully depends on the provability requirements imposed in the $\llbracket \text{Prop}_0 \rrbracket$ fragment.

\Box Lifting Lemma In $\mathcal{J}\text{calc}^-$, for every $\Gamma, A \in \text{Prop}_0$ if $\Gamma \vdash A$ then $\llbracket \Gamma \rrbracket \vdash \llbracket A \rrbracket$ and, hence, $\Box \Gamma \vdash \Box A$.

We get admissibility of necessitation as a lemma for Γ empty:

As a result:

Completeness $\mathcal{J}\text{calc}^-$ is complete with respect to the Hilbert style formulation of degree-1 intuitionistic K modal logic.

5.2.3 Harmony: Local Soundness and Local Completeness

Before we move on to show (Global) Soundness we provide evidence for the so called “local soundness” and “local completeness” of the \Box connective following Gentzen’s dictum. The local soundness and completeness for the \supset connective is given elsewhere (e.g. [68]) and in Gentzen’s original [?]. Gentzen’s program can be described with the following two slogans:

- a. Elim is left-inverse to Intro
- b. Intro is right-inverse to Elim

Applied to the \Box connective, the first principle says that introducing a $\Box A$ (resp. many $\Box A_1, \dots, \Box A_i$) only to eliminate it (resp. them) directly is redundant. In other words, the elimination rule cannot give you more data than what were inserted in the introduction rule(s) (“elimination rules are not *too* strong”). We show first the “Elim-After-Singleton-Intro” sub-case.

$$\begin{array}{c}
 \begin{array}{ccc}
 \begin{array}{c} \nabla \text{ D} \\ \hline A \end{array} & \begin{array}{c} \nabla \text{ E} \\ \hline \llbracket A \rrbracket \end{array} & \begin{array}{cc} -x & -s \\ A & \llbracket A \rrbracket \\ \vdots & \vdots \\ B & \llbracket B \rrbracket \end{array} \\
 \hline
 \Box A & & \\
 \hline
 \Box B
 \end{array}
 \quad \Longrightarrow_R \quad
 \begin{array}{ccc}
 \begin{array}{c} \nabla \text{ D} \\ \hline A \end{array} & \begin{array}{c} \nabla \text{ E} \\ \hline \llbracket A \rrbracket \end{array} & \begin{array}{cc} A & \llbracket A \rrbracket \\ \vdots & \vdots \\ B & \llbracket B \rrbracket \end{array} \\
 \hline
 & & \Box B
 \end{array}
 \end{array}$$

The exact same principle applies in the “Elim-after-Intro” of multiple \Box s:

$$\begin{array}{c}
\begin{array}{ccccccc}
\begin{array}{c} \triangle D_1 \\ A_1 \end{array} &
\begin{array}{c} \triangle E_1 \\ \llbracket A_1 \rrbracket \end{array} &
\begin{array}{c} \triangle D_i \\ A_i \end{array} &
\begin{array}{c} \triangle E_i \\ \llbracket A_i \rrbracket \end{array} &
\begin{array}{c} \text{---} \vec{x} \\ A_1 \dots A_i \\ \vdots \\ B \end{array} &
\begin{array}{c} \text{---} \vec{s} \\ \llbracket A_1 \dots A_i \rrbracket \\ \vdots \\ \llbracket B \rrbracket \end{array} &
\end{array} \\
\hline
\begin{array}{ccccccc}
\Box A_1 & & \dots & & \Box A_i & &
\end{array} \\
\hline
\Box B \quad I_{\Box B} E_{\Box A}^{x,s}
\end{array}
\quad \Longrightarrow_R \quad
\begin{array}{c}
\begin{array}{cccc}
\begin{array}{c} \triangle D_1 \\ A_1 \dots \dots A_i \\ \vdots \\ B \end{array} &
\begin{array}{c} \triangle D_i \\ \vdots \\ B \end{array} &
\begin{array}{c} \triangle E_1 \\ \llbracket A_1 \dots \dots A_i \rrbracket \\ \vdots \\ \llbracket B \rrbracket \end{array} &
\begin{array}{c} \triangle E_i \\ \vdots \\ \llbracket B \rrbracket \end{array}
\end{array} \\
\hline
\Box B \quad I_{\Box B}
\end{array}$$

These equalities are of importance since they dictate (together with the corresponding principles for the \supset , \wedge connectives) the proof dynamics of the calculus. The proof term assignment and the corresponding computational (β -)rules are directly instructed by these reduction principles. We see that eliminating (using) an introduced \Box corresponds to double substitution in the corresponding judgments.

Dually, the second principle says eliminating a $\Box A$, should give enough information to directly reintroduce it (“elimination rules are not *too weak*”). This is an expansion principle.

$$\frac{\begin{array}{c} \mathcal{D} \\ \square A \end{array} \quad \frac{\begin{array}{c} \mathcal{D} \\ \square A \end{array} \quad \frac{\begin{array}{c} - \ x \\ A \end{array} \quad \frac{\begin{array}{c} \text{---} \ s \\ \llbracket A \rrbracket \end{array}}{I_{\square A} E_{\square A}^{x,s}}}{\square A} \Rightarrow_E \square A$$

5.2.4 (Global) Soundness

Soundness is shown by proof theoretic techniques. Standardly, we add the bottom type (\perp) to \mathbf{Jcalc}^- together with its elimination rule and show that the system is consistent ($\not\vdash \perp$) by devising a sequent calculus and showing admissibility of cut. We only present the calculus here and collect the theorems towards consistency in the Appendix.

In the following we use $\Gamma \Rightarrow A$ (where $\Gamma, A \in \mathbf{Prop}_0 \cup \mathbf{Prop}_1$) to denote sequents modulo Γ permutations where Γ is a multiset of \mathbf{Prop} (no labels) and $\Delta \Rightarrow \llbracket A \rrbracket$ for sequents corresponding to $\llbracket \text{judgments} \rrbracket$ of the calculus modulo Δ permutations (with Δ (unlabeled) multiset of $\llbracket \mathbf{Prop}_0 \rrbracket$). The multiset/ modulo permutation approach is instructed by standard structural properties. All properties are stated formally and proved in the Appendix.

The $\llbracket \Gamma \rrbracket \Rightarrow \llbracket A \rrbracket$ relation is defined directly from \vdash :

Sequent Calculus ($\llbracket \mathbf{Prop}_0 \rrbracket$)

$$\llbracket \Gamma \rrbracket \Rightarrow \llbracket A \rrbracket := \exists \Gamma' \in \pi(\llbracket \Gamma \rrbracket) \text{ s.t. } \Gamma' \vdash \llbracket A \rrbracket$$

where $\pi(\llbracket \Gamma \rrbracket)$ is the collection of permutations of $\llbracket \Gamma \rrbracket$.

Sequent Calculus (Prop)

$$\begin{array}{c}
\frac{}{\Gamma, A \Rightarrow A} Id \qquad \frac{\Gamma, A \supset B, B \Rightarrow C \quad \Gamma, A \supset B \Rightarrow A}{\Gamma, A \supset B \Rightarrow C} \supset_L \\
\\
\frac{\Gamma, A \Rightarrow B}{\Gamma \Rightarrow A \supset B} \supset_R \qquad \frac{}{\Gamma, \perp \Rightarrow A} \perp_L \qquad \frac{\Box \Gamma, \Gamma \Rightarrow A \quad \llbracket \Gamma \rrbracket \Rightarrow \llbracket A \rrbracket}{\Box \Gamma \Rightarrow \Box A} \Box_{LR}
\end{array}$$

Standardly, we extend the system with the **Cut** rule and we obtain the extended system $\Gamma \Rightarrow^+ A := \Gamma \Rightarrow A + \text{Cut}$. We show Completeness of \Rightarrow^+ with respect to Natural Deduction and Admissibility of Cut that leads to the consistency result

Consistency of Jcalc⁻ theoremfirstcon $\not\vdash \perp$

5.3 Order theoretic semantics

6

The computational side of Jcalc [−]

In this section we add proof terms to represent natural deduction constructions. The meaning of these terms emerges naturally from Gentzen's principles that give reduction (computational β -rules) and expansion (i.e. extensionality η -rules) equalities for the each construct. We focus on the new constructs of the calculus that emerge from the judgmental interpretation of the \square

connective as explained in section 5.2.

There will be no computational (reduction) rules on provability terms. This conforms with our reading of these terms as *references* to proof constructs of an *abstracted* theory J that can be realized differently for a concrete J .

6.0.1 Proof term assignment

The following rules and their correspondence with natural deduction constructs (5.2.1) should be obvious to the reader familiar with the simply typed λ -calculus and basic justification logic. We do not repeat here the corresponding β, η equality rules since they are standard.

Judgments on Truth $\Gamma, A, B \in \text{Prop}_0$ and $M := x_i \mid \langle \rangle \mid \lambda x : A. M \mid (MM)$	
$\frac{x : A \in \Gamma}{\Gamma \vdash_{\text{IPC}} x : A} \Gamma_0\text{-REFL}$	$\frac{}{\Gamma \vdash_{\text{IPC}} \langle \rangle : \top} \top_0\text{I}$
$\frac{\Gamma, x : A \vdash_{\text{IPC}} M : B}{\Gamma \vdash_{\text{IPC}} \lambda x : A. M : A \supset B} \supset_0\text{I}$	$\frac{\Gamma \vdash_{\text{IPC}} M : A \supset B \quad \Gamma \vdash_{\text{IPC}} M' : A}{\Gamma \vdash_{\text{IPC}} (MM') : B} \supset_0\text{E}$
+ $\beta\eta$ equalities for \top, \supset	

For judgments of $\llbracket \text{Prop}_0 \rrbracket$, we assume a countable set of constant names and demand that every combinatorial axiom of intuitionistic logic has a witness under the interpretation $\llbracket \bullet \rrbracket$. This is what justification logicians call “axiomatically appropriate constant specification”. As usual we demand

reflection of contexts in J and preservation of modus ponens – closedness under some notion of application (which we denote as $*$).

Judgments on Validity $\Delta \in \llbracket \text{Prop}_0 \rrbracket$ and $J := s_i \mid C_i \mid J * J$

$$\begin{array}{c}
\frac{s : \llbracket A \rrbracket \in \Delta}{\Delta \vdash_{\text{IPC}} s : \llbracket A \rrbracket} \Delta\text{-REFL} \qquad \frac{}{\Delta \vdash C_{\top} : \llbracket \top \rrbracket} \text{Ax}_1 \\
\\
\frac{A, B \in \text{Prop}_0}{\Delta \vdash C_{K^{A,B}} : \llbracket A \supset (B \supset A) \rrbracket} \text{Ax}_2 \\
\\
\frac{A, B, C \in \text{Prop}_0}{\Delta \vdash C_{S^{A,B,C}} : \llbracket A \supset (B \supset C) \supset ((A \supset B) \supset (A \supset C)) \rrbracket} \text{Ax}_3 \\
\\
\frac{\Delta \vdash_{\text{IPC}} J : \llbracket A \supset B \rrbracket \quad \Delta \vdash_{\text{IPC}} J' : \llbracket A \rrbracket}{\Delta \vdash_{\text{IPC}} J * J' : \llbracket B \rrbracket} \text{APP}
\end{array}$$

If J is a proof calculus and $\llbracket \bullet \rrbracket_J$ is an interpretation such that the specifications above are realized, then J can witness intuitionistic provability. This can be shown by the proof relevant version of the lifting lemma that states:

$\llbracket \bullet \rrbracket$ Lifting Lemma Given $\Gamma, A \in \text{Prop}_0$ s.t. and a term M s.t. $\Gamma \vdash M : A$ then there exists J s.t. $\llbracket \Gamma \rrbracket \vdash J : \llbracket A \rrbracket$.

Proof term assignment and Gentzen Equalities for \square Judgments

Before we proceed, we will give a small primer of *let*-bindings as used in modern programming languages to provide for some intuition on how such terms

work. Let us assume a rudimentary programming language that supports some basic types, say integers (`int`), as well as pairs of such types. Moreover, let us define a datatype `Point` as a pair of `int` i.e. as `(int, int)`. In a language with *let*-bindings one can define a simple function that takes a `Point` and “shifts” it by adding 1 to each of its x and y coordinates as follows:

```
def shift (p: Point) =
  let (x,y) be p
  in
    (x+1,y+1)
```

If we call this function on the point `(2,3)`, then the computation `let (x,y) be (2,3) in (x+1,y+1)` is invoked. This expression reduces following the *let* reduction rule (i.e. pattern matching and substitution) to `(2+1,3+1)`; and as a result we obtain the value `(3,4)`. As we will see, *let* bindings – with appropriate typing restrictions for our system – are used in the assignment of proof terms for the \Box_{IE} rule. Moreover, the reduction principle for such terms (β -rule) – obtained following Gentzen’s equalities for the \Box connective – is exactly the one that we just informally described.

We can now move forward with the proof term assignment for the \Box_{IE} rule. We show first the sub-cases for Γ' empty (pure \Box_I) and Γ' singleton and explain the computational significance utilizing Gentzen’s principles appropriated for the \Box connective. We are directly translating proof tree equalities from 5.2.3 to proof term equalities. We generalize for arbitrary Γ' in the following subsection. We have, respectively, the following instances:

$$\frac{\Gamma \in \text{Prop}_1 \quad \circ \vdash_{\text{IPC}} M : B \quad \dagger \vdash_{\text{IPC}} J : \llbracket B \rrbracket}{\Gamma \vdash_{\text{IPC}} M \& J : \Box B}$$

$$\frac{\Gamma \vdash_{\text{IPC}} N : \Box A \quad x : A \vdash_{\text{IPC}} M : B \quad s : \llbracket A \rrbracket \vdash_{\text{IPC}} J : \llbracket B \rrbracket}{\Gamma \vdash_{\text{IPC}} \text{let } (x \& s \text{ be } N) \text{ in } (M \& J) : \Box B}$$

Gentzen's Equalities for (\Box terms)

Gentzen's reduction and expansion principles give computational meaning (dynamics) and an extensionality principle for linking terms. We omit naming the empty contexts for economy.

$$\frac{\begin{array}{c} \Gamma \in \text{Prop}_1 \quad \vdash M : A \quad \vdash j : \llbracket A \rrbracket \\ \hline \Box_I \end{array} \quad \frac{\Gamma \vdash M \& j : \Box A \quad x : A \vdash M' : B \quad s : \llbracket A \rrbracket \vdash j' : \llbracket B \rrbracket}{\Gamma \vdash \text{let } (x \& s) \text{ be } (M \& J) \text{ in } (M' \& J') : \Box B} I_{\Box B} E_{\Box A}^{x,s}$$

$$\Longrightarrow_R$$

$$\frac{\Gamma \in \text{Prop}_1 \quad \vdash M'[M/x] : B \quad \vdash J'[J/s] : \llbracket B \rrbracket}{\Gamma \vdash M'[M/x] \& J'[J/s] : \Box B} I_{\Box B}$$

Where the expressions $M'[M/x]$ and $J'[J/s]$ denote capture avoiding substitution, reflecting proof compositionality of the two calculi.

Following the expansion principle we obtain:

$$\Gamma \vdash M : \Box A \implies_E$$

$$\frac{\Gamma \vdash_{\text{IPC}} M : \Box A \quad x : A \vdash_{\text{IPC}} x : A \quad s : \llbracket A \rrbracket \vdash_{\text{IPC}} s : \llbracket A \rrbracket}{\Gamma \vdash_{\text{IPC}} \text{let } (x \& s \text{ be } M) \text{ in } (x \& s) : \Box A} I_{\Box A} E_{\Box A}^{x,s}$$

That gives an η -equality as follows:

$$M : \Box A =_{\eta} \text{let } (x \& s \text{ be } M) \text{ in } (x \& s) : \Box A$$

The η equality demands that every $M : \Box A$ should be reducible to a form $M' \& J'$.

Proof term assignment for the \Box rule (Generically)

After understanding the computational meaning of let expressions in the \Box_{IE} rule we can now give proof term assignment for the rule in the general case (i.e. for Γ' of arbitrary length). We define a helper syntactic construct $\text{--let}^* \dots \text{in --}$ as syntactic sugar for iterative let bindings based on the structure of contexts. The let^* macro takes four arguments: a context $\Gamma \in \mathbf{Prop}_0$, a context $\Delta \in \llbracket \mathbf{Prop}_1 \rrbracket$, a possibly empty ($[]$) list of terms $Ns := N_1, \dots, N_i$ - all three of the same length - and a term M . It is defined as follows for the empty and non-empty cases:

$\text{let}^* (\circ; \dagger; [\]) \text{ in } M := M$

$\text{let}^* (x_1 : A_1, \dots, x_i : A_i ; s_1 : \phi_1, \dots, s_i : \phi_i; N_1, \dots, N_i) \text{ in } M :=$

$\text{let } \{(x_1 \& s_1) \text{ be } N_1, \dots, (x_i \& s_i) \text{ be } N_i\} \text{ in } M$

Using this syntactic definition the rule \Box_{IE} rule can be written compactly:

$\Box_{IE} \quad \textbf{With } \Gamma \in \text{Prop}_1, \Gamma' \in \text{Prop}_0, \text{length}(\Gamma) = i, Ns := N_1 \dots N_i, 1 \leq k \leq i$ $\frac{\forall A_k \in \Gamma'. \Gamma \vdash N_k : \Box A_k \quad \Gamma' \vdash_{\text{IPC}} M : B \quad \llbracket \Gamma' \rrbracket \vdash_{\text{IPC}} J : \llbracket B \rrbracket}{\Gamma \vdash_{\text{IPC}} \text{let}^* (\Gamma', \llbracket \Gamma' \rrbracket, Ns) \text{ in } (M \& J) : \Box B} I_{\Box B} E_{\Box A_1 \dots \Box A_i}^{\vec{x}, \vec{s}}$
--

It is obvious that all previously mentioned cases are captured with this formulation. The rule of β -equality can be given for multi-let bindings directly from Gentzen's reduction principle (5.2.3) generalized for the multiple intro case shown in the appendix (.3).

$$\begin{aligned} & \text{let}\{(x_1 \& s_1) \text{ be } (M_1 \& J_1), \dots, (x_i \& s_i) \text{ be } (M_i \& J_i)\} \text{ in } (M \& J) \quad =_{\beta} \\ & M[M_1/x_1, \dots, M_i/x_i] \& J[J_1/s_1, \dots, J_i/s_i] \end{aligned}$$

6.0.2 Strong Normalization and small-step semantics

In the appendix (.4) we provide a proof of normalization for natural deduction (via cut elimination). This is “essentially” a strong normalization result for the proof term system also. In general we have shown the congruence obtained

from $=_{\beta\eta}$ rules gives a consistent equational system. Nevertheless, we leave this for an extended version of this paper. Instead, we sketch briefly a weaker result: normalization under a deterministic, “call-by-value” reduction strategy for β -rules. This gives an idea of how the system computes and we can use it in the applications in the next section. As usual we characterize a subset of the closed terms as values and we provide rules for the reduction of the non-value closed terms. Note that for the constants of validity and their applicative closure we do not observe reduction properties but treat them as values – again conforming with the idea of J (and its reduction principles) being “black boxed”.

Small step, call-by-value reduction \rightarrow

$$\begin{array}{c}
 \frac{}{\lambda x.M \text{ value}} \quad \frac{}{C_i \text{ value}} \quad \frac{J_1 \text{ value} \quad J_2 \text{ value}}{J_1 * J_2 \text{ value}} \\
 \\
 \frac{M \text{ value} \quad J \text{ value}}{M \& J \text{ value}} \quad \frac{M \rightarrow M'}{M \& J \rightarrow M' \& J} \\
 \\
 \frac{N_1 \text{ value} \dots N_{k-1} \text{ value} \quad N_k \rightarrow N'_k}{\text{let}\{(x_1 \& s_1) \text{ be } N_1, \dots, (x_k \& s_k) \text{ be } N_k, \dots\} \text{ in } M \rightarrow \text{let}\{(x_1 \& s_1) \text{ be } N_1, \dots, (x_k \& s_k) \text{ be } N'_k, \dots\} \text{ in } M} \\
 \\
 \frac{M_1 \& J_1 \text{ value} \dots M_i \& J_i \text{ value}}{\text{let}\{(x_1 \& s_1) \text{ be } (M_1 \& J_1), \dots, (x_i \& s_i) \text{ be } (M_i \& J_i)\} \text{ in } (M \& J) \rightarrow M[M_1/x_1, \dots, M_i/x_i] \& J[J_1/s_1, \dots, J_i/s_i]} \\
 \\
 \frac{M \rightarrow M'}{(MN) \rightarrow (M'N)} \quad \frac{N \rightarrow N'}{((\lambda x.M)N) \rightarrow ((\lambda x.M)N')} \\
 \\
 \frac{N \text{ value}}{((\lambda x.M)N) \rightarrow [N/x]M}
 \end{array}$$

Using the reducibility candidates proof method [35]) we show:

Termination Under Small Step Reduction With \rightarrow^* being the reflex-

ive transitive closure of \rightarrow : for every closed term M and $A \in \text{Prop}$ if $\vdash M : A$ then there exists N **value** s.t. $\vdash N : A$ and $M \rightarrow^* N$.

6.1 A programming language view: Dynamic Linking and separate compilation

Our type system can be related to programming language design when considering *Foreign Function Interfaces*. This is a typical scenario in which a language I interfaces another language J which is essentially “black boxed”. For example, OCaml code might call C code to perform certain computations. In such cases I is a client and J is a host that provides implementations for an interface utilized by the client. Through software development, often the implementations of such an interface might change (i.e. a new version of the host language, or more dramatically, a complete switch of host language). We want a language design that satisfies two interconnected properties. First, *separate compilation* i.e. when implementations change we do not have to recompile client code and, yet, secondly, *dynamic linking* we want the client code to be linked dynamically to its new “meaning”.

We will assume that both languages are functional and based on the lambda calculus. I.e. our interpretation function should have the property $\llbracket A \supset B \rrbracket_J = \llbracket A \rrbracket_J \llbracket \supset \rrbracket_J \llbracket B \rrbracket_J$ where $\llbracket \supset \rrbracket_J$ is the implication type constructor in J . The specifics of the host J and the concrete implementations are unknown to I but during the linker construction we assume that both languages share

some basic types for otherwise typed “communication” of the two languages would be impossible. Simplifying, we consider that the only shared type is (int) , i.e. the linker construction assumes $\bar{n} : \llbracket \text{int} \rrbracket$ for every integer $n : \text{int}$. Let us now assume source code in I that is interfacing a simple data structure, say an integer stack, with the following signature Σ :

```
using type intstack
empty: intstack , push: int -> intstack
pop: intstack -> int
```

And let us consider a simple program in I that is using the signature say,

```
pop(push (1+1) empty):int
```

This program involves two kinds of computations: a redex $(1 + 1)$ that can be reduced using the internal semantics of the language $1 + 1 \rightsquigarrow_I 2$ and the signature calls `pop (push 2 empty)` that are to be performed externally in whichever host language implements them. We treat dynamic linkers as “term re-writers” that map a computation to its meaning(s) based on different implementations. In the following we consider Σ to be the signature of the interface. Here are the steps towards the linker construction.

1. Reduce the source code based on the operational semantics of I until it doesn't have a redex: $\Sigma; \bullet \vdash \text{pop}(\text{push } (1 + 1) \text{ Empty}) \rightsquigarrow \text{pop}(\text{push } 2 \text{ Empty}) : \text{int}$

2. Contextualize the use of the signature at the final term in step 1:

$$\Sigma; x_1 : \text{intstack}, x_2 : \text{int} \rightarrow \text{intstack} \rightarrow \text{intstack}, x_3 : \text{intstack} \rightarrow \text{int} \vdash x_3(x_2 \ 2 \ x_1) : \text{int}$$

3. Rewrite the previous judgment assuming (abstract) implementations for the corresponding missing elements using the “known” specification for the shared elements.

$$s_1 : \llbracket \text{instack} \rrbracket, s_2 : \llbracket \text{int} \rightarrow \text{intstack} \rightarrow \text{intstack} \rrbracket, s_3 : \llbracket \text{intstack} \rightarrow \text{int} \rrbracket \vdash s_3 * (s_2 * \bar{2} * s_1) : \llbracket \text{int} \rrbracket$$

4. Combine the two previous judgments using the \Box_{IE} rule.

$$\Sigma; x'_1 : \Box \text{intstack}, x'_2 : \Box(\text{int} \rightarrow \text{intstack} \rightarrow \text{intstack}), x'_3 : \Box(\text{intstack} \rightarrow \text{int}) \vdash$$

$$\text{let}\{x_1 \& s_1 \text{ be } x'_1, x_2 \& s_2 \text{ be } x'_2, x_3 \& s_3 \text{ be } x'_3\} \text{ in } (x_3(x_2 \ 2 \ x_1) \ \& \ s_3 * (s_2 * \bar{2} * s_1)) : \Box \text{int}$$

5. Using λ -abstraction three times we obtain the dynamic linker:

$$\Sigma; \circ \vdash$$

$$\text{linker} = \lambda x'_1. \lambda x'_2. \lambda x'_3.$$

$$\text{let}\{x_1 \& s_1 \text{ be } x'_1, x_2 \& s_2 \text{ be } x'_2, x_3 \& s_3 \text{ be } x'_3\} \text{ in } (x_3(x_2 \ 2 \ x_1) \ \& \ s_3 * (s_2 * \bar{2} * s_1))$$

$$: \Box(\text{instack}) \rightarrow \Box(\text{int} \rightarrow \text{intstack} \rightarrow \text{intstack}) \rightarrow \Box(\text{intstack} \rightarrow \text{int}) \rightarrow \Box \text{int}$$

Let us see how it can be used in the presence of different implementations:

1. Suppose the developer responsible for the implementation of the interface is providing an array based implementation for the stack in some language

J i.e. we get references to typechecked code fragments of J as follows¹:

```
create() : intarray, add_array : intJ →J intarray →J intarray
pop_array : intarray →J int
```

2. A unification algorithm check is performed to verify the conformance of the implementations to the signature taking into account fixed type sharing equalities ($\llbracket \text{int} \rrbracket = \text{int}_J$). In our case it produces:

$$\llbracket \rightarrow \rrbracket = \rightarrow_J, \llbracket \text{intstack} \rrbracket = \text{intarray}$$

3. We thus obtain typechecked links using the \Box_I rule. For example:

$$\frac{\begin{array}{l} \Sigma; \circ \vdash_{\text{IPC}} \text{push} : \text{int} \rightarrow \text{intstack} \rightarrow \text{intstack} \\ \bullet \vdash_{\text{IPC}} \text{add_array} : \llbracket \text{int} \rightarrow \text{intstack} \rightarrow \text{intstack} \rrbracket \end{array}}{\Sigma; \circ \vdash_{\text{IPC}} \text{push} \ \& \ \text{add_array} : \Box(\text{int} \rightarrow \text{intstack} \rightarrow \text{intstack})}$$

And analogously:

$$\Sigma; \circ \vdash \text{pop} \ \& \ \text{pop_array} : \Box(\text{intstack} \rightarrow \text{int})$$

$$\Sigma; \circ \vdash \text{empty} \ \& \ \text{create}() : \Box \text{intstack}$$

4. Finally we can compute the next step in the computation for the expression applying the linker to the obtained pairings:

$$\Sigma; \bullet \vdash (\text{linker} (\text{empty} \ \& \ \text{create}()) (\text{push} \ \& \ \text{add_array}) (\text{pop} \ \& \ \text{pop_array})) : \Box \text{int}$$

¹We have changed the return type of `pop` to avoid products. This is just for economy and products can easily be handled.

which reduces to:

$$\Sigma; \bullet \vdash \text{let}\{(x_1 \& s_1) \text{ be } (\text{empty} \& \text{create}()), (x_2 \& s_2) \text{ be } (\text{push} \& \text{add_array}), (x_3 \& s_3) \text{ be } (\text{pop} \& \text{pop_array}) \\ \text{in } (x_3(x_2 \ 2 \ x_1) \& s_3 * (s_2 * \bar{2} * s_1)) : \Box \text{int}$$

The last expression reduces to (β -reduction for let):

$$\Sigma; \bullet \vdash \text{pop}(\text{push } 2 \ \text{empty}) \& \text{pop_array} * (\text{add_array} * \bar{2} * \text{empty}) : \Box \text{int}$$

giving exactly the next step of the computation for the source expression. The good news is that the linker computes correctly the next step given any conforming set of implementations. It is easy to see that given a list implementation the very same process would produce a different computation step:

$$\Sigma; \bullet \vdash \text{pop}(\text{push } 2 \ \text{empty}) \& \text{pop_list} * (\text{Cons} * \bar{2} * []) : \Box \text{int}$$

We conclude with some remarks that:

- The construction gives a mechanism of abstractions that works not only over different implementations in the same language but even for implementations in different (applicative) languages.
- We assumed in the example that the two languages are based on the lambda calculus and implement a curried, higher-order function space. It is easy to see that such host satisfies the requirements for the $\llbracket \bullet \rrbracket$ (with C_S, C_K being the S, K combinators in λ form and $*$ translating to λ application).

- Often, the host language of a foreign call is not a language that satisfies such specifications. This situation occurs when we have bindings from a functional language to a lower level language ². Such cases can be captured by adding conjunction (and pairs), tuning the specifications of J accordingly and loosening the assumption that $\llbracket \bullet \rrbracket$ is total on types.
- Introduction of modal types is clearly relative to the $\llbracket \bullet \rrbracket$ function on types. It would be interesting to consider examples where $\llbracket \bullet \rrbracket$ is realized by non-trivial mappings such as $\llbracket A \supset B \rrbracket = !A \multimap B$ from the embedding on intuitionistic logic to intuitionistic linear logic [?]. That will showcase an example of modality that works when lifting to a completely different logic or, correspondingly, to an essentially different computational model.
- Finally, it should be clear from the operational semantics and this example that we did not demand any equalities (or, reduction rules) for the proofs in J , but mere existence of specific terms. This is in accordance to justification logic. Analogously, we did not observe computation in the host language but only the construction of the linkers as program transformers. We were careful, to say that our calculus corresponds to the dynamic linking part of separate compilation. This, of course, does not tell the whole story of program execution in such cases. Foreign function calls, return the control to the client after the result gets calculated in the external language. For example, the execution of the program `pop (push 2 empty) + 2` should “escape” the client to compute the stack calls and then return for the last

²In this setting the type signature of `push` would be: $\text{int} \times \text{intstack} \rightarrow \text{intstack}$

addition. Our modality is concerned only with passing the control from the client to the host dynamically and, as such, is a K (non-factive) modality. Capturing the continuation of the computation and the return of the control back to the source would require a factive modality and a notion of “reverse” of the mapping $\llbracket \bullet \rrbracket$. We would like to explore such an extension in future work.

6.2 Related and Future Work

Directly related work with our calculus, in the same fashion that justification logic and LP [4] are related to modal logic, is [21]. The work in [21] provides a calculus for explicit assignments (substitutions) which is actually a sub-case of \mathbf{Jcalc}^- with $\llbracket \bullet \rrbracket$ identity. This sub-case captures dynamic linking where the host language is the very same one; such need appears in languages with module mechanisms (i.e. implementation hiding and separate compilation within the very same language). In general, the judgmental approach to modality is heavily influenced by [64]. In a sense, our treatment of validity-as-explicit-provability also generalizes the approach there without having to commit to a “factive” modality. Finally, important results on programming paradigms related to justification logic have been obtained in [14, 24, 20]. Immediate future developments would be to interpret modal formulas of higher degree under the same principles. This corresponds to dynamic linking in two or more steps (i.e., when the host becomes itself a client of another

interface that is implemented dynamically in a third level and, so on). Some preliminary results towards this direction have been developed in [67].

7

Jcalc and dependent typing

A plausible reading of Gödel’s incompleteness results ([36]) is that the notion of “validity” diverges from that of “truth within a specific theory”: given a theory that includes enough arithmetic, there are statements whose validity can only be established in a theory of larger proof-strength. This phenomenon can be shown even with non-Gödelian arguments in the relation e.g. between

$\mathsf{I}\Delta_0$ and $\mathsf{I}\Sigma_1$ arithmetic [60], $\mathsf{I}\Sigma_1$ and PA, PA and ZF, etc. [71, 27]. The very same issues arise in automated theorem proving. A good example is given by type systems and interactive theorem provers (e.g. Coq, Agda) of the typed functional paradigm. In such systems, when termination of functions has to be secured, one might need to invoke stronger proof principles. The need for reasoning about two kinds of proof objects within a type system is apparent most of all when one wants to establish non-admissibility results for a theory T that can, in contrast, be proved in some stronger T' . The type system, then, has to reconcile the existence of a proof object of some type ϕ in some T' and a proof object of type $\neg\exists s. \mathit{Prov}_T(s, \phi)$ that witnesses the non-provability of ϕ (in T).

In this work, we argue that the explicit modality of Justification Logic [11] can be used to axiomatize relations between objects of two different calculi such as those mentioned above. It is well known that the provability predicate can be axiomatized using a modality [25], [13]. The Logic of Proofs LP [7] goes further and provides explicit proof terms (*proof polynomials*) to inhabit judgments on validity. By translating reasoning in Intuitionistic Propositional Calculus (IPC) to classical proofs, LP obtains a classical semantics for IPC through a modality (inducing a BHK semantics). In this paper we axiomatize the relation between the two kinds of proof objects explicitly, by creating a modal type theory that reasons about bindings or linking of objects from two calculi: a lower-level theory T , formulated as IPC with Church-style λ -terms representing intuitionistic proof objects; and a higher-level, possibly stronger

and classical (co-)theory T' fixed as foundational, with *justifications* expressing its proof objects. The axiomatization of such a (co-)theory follows directly the proof system of Justification Logic (here restricted to its applicative K -fragment) and is used to interpret classically (meaning *truth-functionally*) the constructions of the intuitionistic natural deduction. The underlying principle of our linking system is as follows:

$$\text{constructive necessity} = \text{admissible validity} = \text{truth (in } T) + \text{validity (in } T')$$

Necessity of a true (in T) proposition P is, thus, sensitive to the existence of a proof (witnessed by a justification) of its intended interpretation within T' . We assume an interpretation function on types $Just$ that maps the type universe of T into the type universe of T' . We employ judgments of the kind $M : P$ (read as “ M is a proof of type P in T ”) that represent truths in T and judgments of the kind $j : \mathbf{Just} P$ (to be read as “ j is a justification of the interpretation of P in T' ”) that represent truth in T' (validity). Incorporating them, the principle can be rewritten in a judgmental fashion:

$$M : P + j : \mathbf{Just} P \Rightarrow \Box^j P \text{ true}$$

Notice that the \Box -types are indexed by justifications ($\Box^j P$) being sensitive to the interpretation (T') chosen. To complete the picture we need canonical elements of \Box^j -types. Naturally, witnesses of this kind are *links* between proof objects from T and T' with corresponding types (P and $\mathbf{Just} P$). For that

reason we introduce a *linking witness* constructor *Link*. This is how necessity is introduced: by proof-checking deductions of T with deductions of T' , we reason constructively about admissibility of valid (via T') statements in T . The principle thus becomes:

$$M : P + j : \mathbf{Just} \ P \Rightarrow \mathit{Link}(M, j) : \Box^j P$$

We show how this principle is admissible in our system.

A possible application of the presented type theory can be a refined type system for programming languages with modular programming constructs or external function calls as we show in section ?? . In these kinds of languages (e.g. of the **ML** family) a program or module can call for external definitions that are implemented elsewhere (in another module or, even in another language)¹. We can read functions within \Box -types indexed by justifications as linking processes for such languages that perform the mapping of well-typed constructs importing and using module signatures into their residual programs. By residual programs we mean programs where all instances of module types and function calls are replaced by (i.e. *linked* to) their actual implementations, which remain hidden in the module. We show with a real example how, with slight modifications, our type system can find a natural application in this setting. Here we focus on the type system itself and not on its operational semantics.

The backbone of this work is the idea of representing the proof theoretic

¹See [40].

semantics for IPC through modality that stems from [9],[10]. An operational approach to modality related to this work can be found in [8]. The modularity of LP, i.e. its ability to realize other kinds of modal reasoning with proper changes in the axiomatization of proof polynomials, was shown with the development of the family of Justification Logics [11]. This ability is easily seen to be preserved here. Our work incorporates the rich type system and modularity of Justification Logic within the proofs-as-programs doctrine. For that reason, we obtain an extension of the Curry-Howard correspondence ([73], [35]) and adopt the judgmental approach of Intuitionistic Type Theory ([52], [53], [54], [57], [17]). Our system borrows from other modal calculi developed within the judgmental approach (e.g. [64], [37],[1] and especially [22] for the modal logic K). A main difference of our system with those systems, as well as with previous λ -calculi for LP ([2], [14]) is that our type system hosts a two-kinded typing relation for proof objects of corresponding formulae. It can be viewed as an attempt to add proof terms for validity judgments as presented in [64]. The resulting type system adopts dependent typing ([19], [58]) to relate the two kinds of proof objects with modality. The construction of the type universe as well as of justificational terms draws a lot from ideas in [12] and from [32]. Extending typed modal calculi with additional (contextual) terms of dependent typing can be also found in [56].

7.1 A road map for the type system

The present system can be viewed as a calculus of reasoning in three interleaving phases. Firstly, reasoning about proof objects in the implicational fragment of an intuitionistic theory T in absence of any metatheoretic assumptions of validity, introduced in Section 7.2. This calculus is formalized by the turnstile $\Gamma \vdash_{\text{IPC}}^2$ where Γ contains assumptions on proofs of sentences in T . The underlying logic is intuitionistic, the system corresponding to the implicational fragment of simply typed lambda calculus. Secondly, reasoning with justifications, corresponding to reasoning about proof objects in some fixed foundational system: the (co-)theory T' . We suppose that T' provides the intended semantics for the intuitionistic system T . The corresponding turnstile is $\Delta \vdash_J$. Abstracting from any specific metatheory, all that matters from a purely logical point of view is that the theory of the interpretation should – at least – include as much logic as the implicational fragment of T and it should satisfy some minimal conditions for the provability predicate of T .

Finally, reasoning about existence of *links* between proof objects in the implicational fragment of *both* axiomatic systems, introduced in Section 7.4. This mode of reasoning is axiomatized within the full turnstile $\Delta; \Gamma \vdash_{\text{JC}}$. The core of this system is the \Box -Introduction rule, which allows to express constructive reasoning on linking existence. The idea is – ignoring contextual

²One could alternatively use an additional constant symbol `null` and write `null; $\Gamma \vdash_{\text{IPC}}$` to denote reasoning purely in T and, thus, in absence of any metatheoretic environment.

reasoning for simplicity – that linking a construction in T with a justification of its corresponding type in T' we obtain a proof of a constructive (or, admissible in T) validity. The rule in full (i.e. including contexts) corresponds to the construction of a link for a compound term based on existing link on its subterms. The full turnstile $\Gamma; \Delta \vdash$ is, hence, a modal logic that “zips” mutual reasoning between the two calculi. Within this framework we obtain a computational reading for justification logic restricted to K modal reasoning. Before presenting this mutual reasoning at any arbitrary level of nesting (i.e. arbitrary modal types), we first introduce \mathbf{JCalc}_1 which is a restriction of the type universe up to 1 level of \Box -nesting.

We fix a countable universe of propositions (P_i) that corresponds to sentences of T . The elements of this universe can be inhabited either by constructions or justifications. We will need, accordingly, two kinds of inhabitation relations for each proposition. We will be writing $M : \phi$ for a construction M of type ϕ in T . We will be writing $j : \mathbf{Just} \phi$ to express the fact that j is a justification (proof in T') of the proposition ϕ . When there is no confusion we will be abbreviating this by $j :: \phi$. A construction in $M : \phi$ in T does not entail its necessity: to this aim, a corresponding justification $j : \mathbf{Just} \phi$ from T' has to be obtained. Vice versa, the justification (j) of ϕ in T' alone entails its validity but not its admissibility in T (*constructive necessity*). This is expressed by the proposition – type $\Box^j \phi$. A construction of $\Box^j \phi$ can be obtained only when the (weaker) theory T actually “responds” with a construction M of the type ϕ to the valid fact ϕ known from T' by

deducing j . Hence, once (and only if) we have $j :: \phi$ then $\Box^j \phi$ can be regarded as a well formed proposition. The stronger theory might be able to judge about $\Box^j \phi$ (given $j :: \phi$) and prove e.g, $u :: \Box^j \phi$. In that case T' “knows” that ϕ is admissible in T . In other words, when reasoning with justifications, the universe of types is *contextual*. To speak about an admissible (or, constructive) necessity of a proposition we require the existence of a corresponding proof object j in T' that establishes its validity.

7.2 Reasoning without foundational assumptions: IPC

Reasoning about the implicational fragment of the constructive theory (T), without formulating provability statements, is done within the implicational fragment of the simply typed lambda calculus. We start by giving the grammar for the metavariable ϕ used in the rules.

$$\phi := P_i | \phi \rightarrow \phi$$

The calculus is presented by introducing: the universe of types \mathbf{Prop}_0 ; rules for constructing well-formed contexts of simple propositional assumptions Γ_0 ; the rules governing \vdash_{IPC} .

$$\frac{}{P_i \in \text{Prop}_0} \text{ATOM}_0 \qquad \frac{\phi_1 \in \text{Prop}_0 \quad \phi_2 \in \text{Prop}_0}{\phi_1 \rightarrow \phi_2 \in \text{Prop}_0} \text{IMPL}_0$$

$$\frac{}{\text{nil} \vdash_{\text{IPC}} \text{wf}} \text{NIL}_0 \qquad \frac{\Gamma_0 \vdash_{\text{IPC}} \text{wf} \quad \phi \in \text{Prop}_0}{\Gamma_0, x : \phi \vdash_{\text{IPC}} \text{wf}} \Gamma_0\text{-EXP}$$

$$\frac{\Gamma_0 \vdash_{\text{IPC}} \text{wf} \quad x : P_i \in \Gamma_0}{\Gamma_0 \vdash_{\text{IPC}} x : P_i} \Gamma\text{-REFL}$$

$$\frac{\Gamma_0, x : \phi_1 \vdash_{\text{IPC}} M : \phi_2}{\Gamma_0 \vdash_{\text{IPC}} \lambda x : \phi_1. M : \phi_1 \rightarrow \phi_2} \rightarrow\text{I}$$

$$\frac{\Gamma_0 \vdash_{\text{IPC}} M : \phi_1 \rightarrow \phi_2 \quad \Gamma_0 \vdash_{\text{IPC}} M' : \phi_1}{\Gamma_0 \vdash_{\text{IPC}} (MM') : \phi_2} \rightarrow\text{E}$$

7.3 Reasoning in the Presence of Foundations:

A calculus of Justifications J

Reasoning in the presence of minimal foundations corresponds to reasoning on the existence of proof objects in the foundational theory T' . The minimal foundational assumptions from the logical point of view is that T' “knows” at least as much logic as T does. The more non-logical axioms in T , the more the specifications T' should satisfy (one needs stronger foundations to justify stronger theories). Abstracting from any particular T and T' , and assuming only that T incorporates minimal logic, the specifications about existence of proofs in T' are:

- to have “enough” types to provide – at least – an intended interpretation of every type ϕ of T to a unique type **Just** ϕ . In other words a subset of the types of T' should serve as interpretations of types in T ;
- to have – at least – proof objects for all the instances of the axiomatic characterization of the IPC fragment described above;³
- to include some modus ponens rule which translates as: the existence of proof objects of types **Just** $(\phi \rightarrow \psi)$ and of type **Just** ϕ in T' should imply the existence of a proof object of the type **Just** ϕ .

³If we extend our fragment we should extend our specifications accordingly but this can be easily done directly as in full justification logic. We choose to remain within this fragment for economy of presentation.

7.3.1 Minimal Justification Logic J- Calc_1

Under these minimal requirements, we develop a minimal justification logic that is able to realize modal reasoning as reasoning on the existence of links between proofs of T and T' . We first realize modal reasoning restricted to formulae of degree (i.e. level of \Box -nesting) 1. Such a calculus will be used as a base to build a full modal calculus with justifications for formulae of arbitrary degree. Here is the grammar for the metavariables appearing below:

$$\phi := P_i | \Box^j \phi | \phi_1 \rightarrow \phi_2$$

$$j := s_i | C | j_1 * j_2$$

$$t := x_i | \lambda x_i : \phi. t | Js :: \phi. t$$

$$C := K[\phi_1, \phi_2] | S[\phi_1, \phi_2, \phi_3] | C_1 * C_2$$

$$\pi := \Pi s :: \phi_1. \phi_2 | \Pi s :: \phi_1. \pi$$

$$\top := \phi | \text{Just } \phi | \pi$$

$$s := s_i$$

$$x := x_i$$

Reasoning on minimal foundations J_0

Reasoning about such a minimal metatheory is axiomatized in its own turnstile (\vdash_{J_0}) .⁴ Henceforth, judgments on the justificational type universe of J_0 (corresponding to formulae in the (co-)theory T') together with **wf** predicate for Δ_0 contexts go as follows:

$$\begin{array}{c}
\frac{}{\text{nil} \vdash_{J_0} \text{wf}} \text{NIL} \qquad \frac{\Delta_0 \vdash_{J_0} \text{wf} \quad \Delta_0 \vdash_{J_0} \phi \in \text{Prop}_0}{\Delta_0 \vdash_{J_0} \text{Just } \phi \in \text{jtype}_0} \text{SIMPLE} \\
\\
\frac{\Delta_0 \vdash_{J_0} \text{Just } \phi \in \text{jtype}_0 \quad s \notin \Delta_0}{\Delta_0, s :: \phi \vdash_{J_0} \text{wf}} \Delta_0\text{-APP} \\
\\
\frac{\Delta_0 \vdash_{J_0} \text{wf} \quad s :: \phi \in \Delta}{\Delta_0 \vdash_{J_0} s :: \phi} \Delta_0\text{-REFL}
\end{array}$$

We add logical constants to satisfy the requirement that J_0 includes an axiomatic characterization of – at least – a fragment of **IPC**. Following justification logic, we define a signature of polymorphic constructors including **K**, **S** from combinatory logic. The values of those constructors are axiomatic constants that witness existence of proofs in T' of all instances of the corresponding logical validities. This axiomatic characterization of intuitionistic

⁴This is the part of the calculus that corresponds directly to the algebra of justifications restricted to the applicative fragment.

logic in J_0 together with rule scheme **Times** (*applicativity of justifications*) satisfy the minimal requirement for T' to reason logically.

Right= $K\Delta_0 \vdash_{J_0} \text{Just } \phi_1 \rightarrow \phi_2 \rightarrow \phi_1 \in \text{jtype}_0 \Delta_0 \vdash_{J_0} K[\phi_1, \phi_2] :: \phi_1 \rightarrow \phi_2 \rightarrow \phi_1$

$$\frac{\Delta_0 \vdash_{J_0} \text{Just } (\phi_1 \rightarrow \phi_2 \rightarrow \phi_3) \rightarrow (\phi_1 \rightarrow \phi_2) \rightarrow (\phi_1 \rightarrow \phi_3) \in \text{jtype}_0}{\Delta_0 \vdash_{J_0} S[\phi_1, \phi_2, \phi_3] :: (\phi_1 \rightarrow \phi_2 \rightarrow \phi_3) \rightarrow (\phi_1 \rightarrow \phi_2) \rightarrow (\phi_1 \rightarrow \phi_3)} S$$

$$\frac{\Delta_0 \vdash_{J_0} j_2 :: \phi_1 \rightarrow \phi_2 \quad \Delta_0 \vdash_{J_0} j_1 :: \phi_1}{\Delta_0 \vdash_{J_0} j_2 * j_1 :: \phi_2} \text{Times}$$

Zippping: $\text{J-Calc}_1 = \text{IPC} + J_0 + \Box\text{-Intro}$

In this section we introduce J-Calc_1 for reasoning on the existence of links i.e. constructions that witness the existence of proofs both in IPC (T) and J_0 (T'). By constructing a link we have a proof of a constructive necessity of a formula, showing that it is true and valid. Links have types of the form $\Box^j \phi$ where j is a justification of the appropriate type. J-Calc_1 realizes modal logic theoremhood in K up to degree 1 (i.e. formulae where its subformula includes up to 1 level of \Box).

We start by importing well-formedness judgments for contexts and justificational types ($\Delta_0 \text{Wf}$, JustWf respectively), and for the Prop_1 universe and its contexts:

$$\begin{array}{c}
\frac{\Delta_0 \vdash_{J_0} \mathbf{wf}}{\Delta_0; \mathbf{nil} \vdash_{JC_1} \mathbf{wf}} \Delta_0 \mathbf{WF} \qquad \frac{\Delta_0; \Gamma_1 \vdash_{JC_1} \mathbf{wf} \quad \Delta_0 \vdash_{J_0} j :: \phi}{\Delta_0; \Gamma_1 \vdash_{JC_1} j :: \phi} \mathbf{JUST}_0 \mathbf{WF} \\
\\
\frac{\phi \in \mathbf{Prop}_0 \quad \Delta_0; \Gamma_1 \vdash_{JC_1} j :: \phi}{\Delta_0; \Gamma_1 \vdash_{JC_1} \Box^j \phi \in \mathbf{Prop}_1} \mathbf{PROP}_1\text{-INTRO} \\
\\
\frac{\Delta_0; \Gamma_1 \vdash_{JC_1} \phi \in \{\mathbf{Prop}_0, \mathbf{Prop}_1\} \quad x \notin \Gamma_1}{\Delta_0; \Gamma_1, x : \phi \vdash_{JC_1} \mathbf{wf}} \Gamma_1\text{-APP}
\end{array}$$

From justifications of formulas in \mathbf{Prop}_0 , we can reason about their admissibility in T . Hence, Γ_1 might include assumptions from the sorts \mathbf{Prop}_0 and \mathbf{Prop}_1 . For the inhabitation of $\mathbf{Prop}_0, \mathbf{Prop}_1$, we first accumulate intuitionistic reasoning extended to the new type universe (\mathbf{Prop}_1), adapting the rules from Section 7.2:

$$\begin{array}{c}
\frac{\Delta_0; \Gamma_1 \vdash_{\text{JC}_1} \mathbf{wf} \quad x : \phi \in \Gamma_1}{\Delta_0; \Gamma_1 \vdash_{\text{JC}_1} x : \phi} \Gamma_1\text{-REFL} \\
\\
\frac{\Delta_0; \Gamma_1, x : \phi_1 \vdash_{\text{JC}_1} M : \phi_2}{\Delta_0; \Gamma_1 \vdash_{\text{JC}_1} \lambda x : \phi_1. M : \phi_1 \rightarrow \phi_2} \rightarrow\text{I} \\
\\
\frac{\Delta_0; \Gamma_1 \vdash_{\text{JC}_1} M : \phi_1 \rightarrow \phi_2 \quad \Delta_0; \Gamma_1 \vdash_{\text{JC}_1} M' : \phi_1}{\Delta_0; \Gamma_1 \vdash_{\text{JC}_1} (MM') : \phi_2} \rightarrow\text{E}
\end{array}$$

For relating the two calculi, a lifting rule is formulated for turning strictly **Prop**₀ judgments to judgments on proof links (**Prop**₁). In the rule, the \downarrow -operator ensures that context list $\downarrow \Gamma$ includes assumptions strictly in **Prop**₀. The operator \downarrow can be viewed as the opposite of *lift* operation applied on context lists erasing one level of boxed assumptions at the top level as described below.

$\downarrow \Gamma := \mathbf{match} \Gamma \mathbf{with}$

$\mathbf{nil} \Rightarrow \mathbf{nil}$

$\downarrow \Gamma', x'_i : \Box^j \phi_i \Rightarrow \downarrow \Gamma', x_i : \phi_i$

$\downarrow \Gamma', _ \Rightarrow \downarrow \Gamma'$

A corresponding iterative *let-binding* construct (*let*^{*}) is introduced simultane-

ously with the context lifting. The purpose of the iterative let binding is to extract the target(s) (T' terms) of existing links on subterms $(x_1 \dots x_n)$ of some composite term M in T and compose them to the target of the whole term M creating its residual. We show the operation of this construct in the example from section ??.

$$\begin{aligned}
 & \text{let}^* \Gamma := \\
 & \text{match } \Gamma \text{ with} \\
 & \quad \text{nil} \Rightarrow \text{let } () = () \\
 & \quad | \Gamma', x'_i : \Box^j \phi_i \Rightarrow (\text{let}^* \Gamma') \text{ in } \text{let link}(x_i, j_i) = x'_i \\
 & \quad | \Gamma', _ \Rightarrow \text{let}^* \Gamma'
 \end{aligned}$$

The \Box -Introduction rule goes as follows:

$$\frac{; \downarrow \Gamma_1 \vdash_{\text{JC}_1} M : \phi \quad \Delta_0; \Gamma_1 \vdash_{\text{JC}_1} j :: \phi}{\Delta_0; \Gamma_1 \vdash_{\text{JC}_1} (\text{let}^* \Gamma) \text{ in link } (M, j) : \Box^j \phi} \Box\text{-INTRO}$$

Finally, under empty Γ_1 , we are permitting abstraction from a non-empty Δ_0 . The resulting abstractions (J -terms), as we will see, are the inhabitants of modal types and correspond to linking processes. Their typing is, naturally, of Π -kind since the typing of a link is sensitive to its target code. We introduce

Π -formation and inhabitation rules:

$$\frac{\Delta_0, s :: \phi_1; \vdash_{\text{JC}_1} \phi_2 \in \{\text{Prop}_0, \text{Prop}_1\}}{\Delta_0; \vdash_{\text{JC}_1} \Pi s :: \phi_1. \phi_2 \in \Pi} \Pi \text{ TYPE}_0$$

$$\frac{\Delta_0, s :: \phi_1; \vdash_{\text{JC}_1} \pi \in \Pi}{\Delta_0; \vdash_{\text{JC}_1} \Pi s :: \phi_1. \pi \in \Pi} \Pi \text{ TYPE}_1$$

$$\frac{\Delta_0, s :: \phi; \vdash_{\text{JC}_1} t : \mathsf{T}}{\Delta_0; \vdash_{\text{JC}_1} Js :: \phi. t : \Pi s :: \phi. \mathsf{T}} \Pi\text{-INTRO}$$

$$\frac{\Delta_0; \vdash_{\text{JC}_1} t : \Pi s :: \phi. \mathsf{T} \quad \Delta_0; \vdash_{\text{JC}_1} j :: \phi}{\Delta_0; \vdash_{\text{JC}_1} (t \ j) : \mathsf{T}[s := j]} \Pi\text{-ELIM}$$

7.4 The Full Calculus: J-Calc

J-Calc₁ motivates the generalization to modal reasoning of arbitrary nesting: J-Calc. To allow such generalization, we need justifications of types of the form **Just** $\Box^j \phi$. Let us revise: If ϕ is a proposition (or, a sentence in the language of T), then **Just** ϕ corresponds to the intended interpretation of ϕ in some (co-)theory T' . In J-Calc₁ we could reason logically about the constructive

admissibility of (valid according to T') facts of T . The existence of a link of a proof in T with an existing proof of the same type in T' would lead to constructions of a type of the form $\Box^j \phi$ with ϕ a simple type. To get modal theoremhood of degree 2 or more we have to assume that T' can express the existence of such links in itself. That is to say that T' can express the provability predicates both of T *and* of itself. Hence, supposing that $j :: \phi$, we can read a justification term of type $\mathbf{Just} \Box^j \phi$ as a witness of a proof in T' of the fact $\exists x. \text{Proof}_T(x, \underline{\phi}) \wedge \exists x. \text{Proof}_{T'}(x, \underline{\mathbf{Just} \phi})$ expressed in T' . We will specify which of those types T' is expected to *capture* by introducing additional appropriate constants. Having this kind of justifications we can obtain \mathbf{Prop}_i for any finite i as slices of a type universe in a mutual inductive construction. Schematically: $\mathbf{Prop}_0 \Rightarrow \mathbf{Just} \mathbf{Prop}_0 \Rightarrow \mathbf{Prop}_1 \Rightarrow \mathbf{Just} \mathbf{Prop}_1$ and so on. This way we obtain full minimal justification logic. As different kinds of judgments are kept separated by the different typing relations, we do not need to provide distinct calculi as we did for J- Calc_1 but we provide one “zipped” calculus directly.⁵

⁵In fact, adjoining Γ contexts when reasoning within justifications is pure weakening so we could have kept those judgments separated in a single-context \vdash relation. We gain something though: we can squeeze two premises $(\Delta \vdash j :: \phi, \Delta; \Gamma \vdash \mathbf{wf})$ to a single one $(\Delta; \Gamma \vdash j :: \phi)$.

7.4.1 Justificational (Validity) Judgments

The justificational type system has to include: judgments on the wellformedness of contexts (**wf**);⁶ judgments on what T' can reason about (**jtype**) under the requirement that it is a metatheory of T ; judgments on the construction of the justificational type universe (**jtype**) and minimal requirements about its inhabitation (i.e, *a minimal signature of logical constants*). The grammar of terms is the same as in section 7.3.1, the difference now is that the restrictions on the *Prop* universe are dropped.

We introduce progressively: formation rules for **Prop**; the formation rule for **jtype**; rules to build well-formed contexts of propositions and justifications (where we will be abbreviating using the following equational rule: $\text{nil}, s_1 :: \phi_1, s_2 :: \phi_2, \dots =^{def} s_1 :: \phi_1, s_2 :: \phi_2, \dots$).

⁶Analogous treatments of judgments on the validity of contexts can be found e.g. in [58].

$$\begin{array}{c}
\frac{}{\text{nil}; \text{nil} \vdash_{\text{JC}} \text{wf}} \text{NIL} \qquad \frac{\Delta; \Gamma \vdash_{\text{JC}} \text{wf}}{\Delta; \Gamma \vdash_{\text{JC}} P_i \in \text{Prop}} \text{ATOM} \\
\\
\frac{\Delta; \Gamma \vdash_{\text{JC}} \phi_1 \in \text{Prop} \quad \Delta; \Gamma \vdash_{\text{JC}} \phi_2 \in \text{Prop}}{\Delta; \Gamma \vdash_{\text{JC}} \phi_1 \rightarrow \phi_2 \in \text{Prop}} \text{IMPL} \\
\\
\frac{\Delta; \Gamma \vdash_{\text{JC}} j :: \phi}{\Delta; \Gamma \vdash_{\text{JC}} \Box^j \phi \in \text{Prop}} \text{BOX} \qquad \frac{\Delta; \Gamma \vdash_{\text{JC}} \phi \in \text{Prop}}{\Delta; \Gamma \vdash_{\text{JC}} \text{Just } \phi \in \text{jtype}} \text{JTYPE} \\
\\
\frac{\Delta; \Gamma \vdash_{\text{JC}} \text{Just } \phi \in \text{jtype} \quad s \notin \Delta}{\Delta, s :: \phi; \Gamma \vdash_{\text{JC}} \text{wf}} \Delta\text{-APP} \\
\\
\frac{\Delta; \Gamma \vdash_{\text{JC}} \phi \in \text{Prop} \quad x \notin \Gamma}{\Delta_0; \Gamma, x : \phi \vdash \text{wf}} \Gamma\text{-APP}
\end{array}$$

Prop Inhabitation

Here is the first part of logical propositional reasoning of the system.

$$\frac{\Delta; \Gamma \vdash_{\text{JC}} \text{wf} \quad x : \phi \in \Gamma}{\Delta; \Gamma \vdash_{\text{JC}} x : \phi} \Gamma\text{-REFL}$$

$$\begin{array}{c}
\frac{\Delta; \Gamma, x : \phi_1 \vdash_{\text{JC}} M : \phi_2}{\Delta; \Gamma \vdash_{\text{JC}} \lambda x : \phi_1. M : \phi_1 \rightarrow \phi_2} \rightarrow\text{I} \\
\\
\frac{\Delta; \Gamma \vdash_{\text{JC}} M : \phi_1 \rightarrow \phi_2 \quad \Delta; \Gamma \vdash_{\text{JC}} M' : \phi_1}{\Delta; \Gamma \vdash_{\text{JC}} (MM') : \phi_2} \rightarrow\text{E}
\end{array}$$

jtype Inhabitation

Now we move to the core of the system. In the judgments below we provide the constructions of canonical elements of justificational types (**jtype**). The judgments reflect the minimal requirements for T' to be a metatheory of some T as presented in Section 7.3.1 together with specifications on internalizing proof links reasoning in itself. More specifically, we demand that T' can *capture* reasoning on links (between proof objects of T and itself) *within* itself and also, internalize modus ponens of T . To capture these provability conditions we add the constant constructors **!** (*bang*) and **Kappa**. Although introduction of links is axiomatized in the next section, the judgments concerning the **!** and **Kappa** constructors should be viewed in conjunction with \Box – *Intro*. They witness the fact that T' internalizes modus ponens (of T) and linking existence (again of T).

$$\frac{\Delta; \Gamma \vdash_{\text{JC}} \text{Just } \phi_1 \rightarrow \phi_2 \rightarrow \phi_1 \in \text{jtype}}{\Delta; \Gamma \vdash_{\text{JC}} K[\phi_1, \phi_2] :: \phi_1 \rightarrow \phi_2 \rightarrow \phi_1} \text{K}$$

$$\frac{\Delta; \Gamma \vdash_{\text{JC}} \text{Just } (\phi_1 \rightarrow \phi_2 \rightarrow \phi_3) \rightarrow (\phi_1 \rightarrow \phi_2) \rightarrow (\phi_1 \rightarrow \phi_3) \in \text{jtype}}{\Delta; \Gamma \vdash_{\text{JC}} S[\phi_1, \phi_2, \phi_3] :: (\phi_1 \rightarrow \phi_2 \rightarrow \phi_3) \rightarrow (\phi_1 \rightarrow \phi_2) \rightarrow (\phi_1 \rightarrow \phi_3)} \text{S}$$

$$\frac{\Delta; \Gamma \vdash_{\text{JC}} j_2 :: \phi_1 \rightarrow \phi_2 \quad \Delta; \Gamma \vdash_{\text{JC}} j_1 :: \phi_1}{\Delta \vdash_{\text{J}} j_2 * j_1 :: \phi_2} \text{T}_{\text{IMES}}$$

$$\frac{\Delta; \text{nil} \vdash_{\text{JC}} M : \Box^{\text{C}} \phi}{\Delta; \Gamma \vdash_{\text{JC}} !C :: \Box^{\text{C}} \phi} \text{BANG}$$

$$\frac{\Delta; \Gamma \vdash_{\text{JC}} \text{Just } \Box^{j'} \phi_1 \in \text{jtype} \quad \Delta; \Gamma \vdash_{\text{JC}} \text{Just } \Box^j (\phi_1 \rightarrow \phi_2) \in \text{jtype}}{\Delta; \Gamma \vdash_{\text{JC}} \text{Kappa}[j, j', \phi_1, \phi_2] :: \Box^j (\phi_1 \rightarrow \phi_2) \rightarrow \Box^{j'} \phi_1 \rightarrow \Box^{j*j'} \phi_2} \text{KAPPA}$$

7.4.2 Proof Links

Our next task is to formulate the main rule for the K modality as a lifting rule for going from reasoning about constructions to reasoning about admissibility of validities via proof linking. To reflect the modal axiom K in Natural Deduction we have to obtain a rule that reflects the following provability principle:

$$\frac{\phi_1 \text{ true}, \dots, \phi_n \text{ true} \vdash \phi \text{ true} \quad \phi_1 \text{ valid}, \dots, \phi_n \text{ valid} \vdash \phi \text{ valid}}{\Box \phi_1 \text{ true}, \dots, \Box \phi_n \text{ true}, \dots \vdash \Box \phi \text{ true}} \Box\text{-INTRO}$$

We proceed with giving inhabitants analogously to what was explained in Section 7.3.1:⁷

$$\frac{\Delta; \downarrow \Gamma \vdash_{\text{JC}} M : \phi \quad \Delta; \Gamma \vdash_{\text{JC}} j :: \phi}{\Delta; \Gamma \vdash_{\text{JC}} (\text{let}^* \Gamma) \text{ in link } (M, j) : \Box^j \phi} \Box\text{-INTRO}$$

Finally, abstraction from Δ contexts over empty Γ contexts applies in the extended type universe:

$$\frac{\Delta, s :: \phi; \vdash_{\text{JC}} t : \mathsf{T}}{\Delta; \vdash_{\text{JC}} Js :: \phi. t : \Pi s :: \phi. \mathsf{T}} \Pi\text{-INTRO}$$

$$\frac{\Delta; \vdash_{\text{JC}} t : \Pi s :: \phi. \mathsf{T} \quad \Delta_0; \vdash_{\text{JC}} j :: \phi}{\Delta; \vdash_{\text{JC}} (t \ j) : \mathsf{T}[s := j]} \Pi\text{-ELIM}$$

⁷We prefer this to the mouthful but equivalent:

$$\frac{\begin{array}{c} \Delta; x_1 : \phi_1, \dots, x_i : \phi_i \text{ as } \Gamma \vdash M : \phi \\ \forall \phi_i \in \Gamma. \Delta'; \text{nil} \vdash j_i :: \phi_i \quad \Delta'; \text{nil} \vdash j :: \phi \quad \Delta'; x_1 : \Box^{j_1} \phi_i, \dots, \Box^{j_i} \phi_i \vdash \text{wf} \end{array}}{\Delta'; x_1 : \Box^{j_1} \phi_i, \dots, \Box^{j_i} \phi_i \vdash JBox \ j : \Box^j \phi} \Box\text{-INTRO}$$

7.5 Further Results and Conclusions

Standard meta-theoretical results can be proven for J-Calc. We just mention here that the iterative *let* operator satisfies standard commutativity with the substitution rule for justifications and that structural rules can be proven. We will be skipping the index in \vdash_{JC} .

Weakening J-Calc satisfies Weakening in both modes of reasoning:

1. If $\Delta; \text{nil} \vdash j :: \phi$, and $\Delta; \Gamma \vdash \mathbf{wf}$ then, $\Delta; \Gamma \vdash j :: \phi$.
2. If $\Delta; \Gamma \vdash j :: \phi$, then $\Delta, s :: \phi'; \Gamma \vdash j :: \phi$, with s fresh.
3. If $\Delta; \Gamma \vdash M : \phi$, then $\Delta; \Gamma, x : \phi' \vdash M : \phi$, with x fresh.

Proof. For all items by structural induction on the derivation trees of the two kinds of constructions. The proof of the first is vacuous since Γ contexts are irrelevant in justification formation. As a result, its inverse can also be shown. \square

Contraction J-Calc satisfies Contraction:

1. If $\Delta, s :: \phi, t :: \phi; \text{nil} \vdash j :: \phi'$, then $\Delta, u :: \phi; \text{nil} \vdash j[s \equiv t/u] :: \phi'$.
2. If $\Delta, s :: \phi, t :: \phi; \Gamma \vdash \mathbf{wf}$, then, $\Delta, u :: \phi; \Gamma[s \equiv t/u] \vdash \mathbf{wf}$.
3. If $\Delta, s :: \phi, t :: \phi; \Gamma \vdash M : \phi'$, then, $\Delta, u :: \phi; \Gamma[s \equiv t/u] \vdash M[s \equiv t/u] : \phi'[s \equiv t/u]$.
4. If $\Delta; \Gamma, x : \phi, y : \phi \vdash M : \phi'$, then $\Delta; \Gamma, z : \phi \vdash M[x \equiv y/z] : \phi'$.

Proof. First item by structural induction on the derivation trees of justifications (validity judgments). Note, as mentioned in the previous theorem, that it can be shown for arbitrary Γ . For the second, nested induction on the structure of context Γ (treated as list) and the complexity of formulas. Vacuously in the *nil* case. For the non-empty case: case analysis on the complexity of the head formula using the inductive hypothesis on the tail. Cases of interest are with $\Box^s\phi$ or $\Box^t\phi$ as subformulae. Use the previous item and judgments for *wf* contexts. For the third and the fourth, again by structural induction on the derivation. \square

In a similar fashion we can show the more general:

Preservations of Types under Substitution J-Calc preserves types under substitution and simultaneous substitution:

1. If $\Delta; \Gamma, x : \phi \vdash t : \mathsf{T}$, and $\Delta; \Gamma \vdash M : \phi$ then $\Delta; \Gamma \vdash t[x/M] : \mathsf{T}$
2. If $\Delta, s :: \phi, \Delta'; \Gamma \vdash t : \mathsf{T}$, and $\Delta; \vdash j :: \phi$ then $\Delta, \Delta'[s/j]; \Gamma[s/j] \vdash t[s/j] : \mathsf{T}[s/j]$

We additionally mention that the calculus satisfies *permutation* for both contexts Δ and Γ with the restriction that the permutations in Δ should not break the chain of dependencies. Lastly, we mention here that under standard *let*-binding evaluation and application as β -reduction within a dependently typed framework, a small step operational semantics has been developed and progress and preservation can be shown.

For future work, we plan to extend the computational relevance of the full calculus (JCalc) by establishing its connection with higher-order module systems (e.g. where module signatures can refer to other module signatures which, in turn, are implemented by a third module). Linking processes in such systems would utilize our type system in full. Cut-elimination results are currently under development.

8

An implementation of Jcalc in a
modern metaprogramming framework

Appendices

.1 Theorems

Basic Facts about the type universe With A, U metavariables ranging over the following grammar

$$A := P_i | A \supset A | \Box A | \llbracket A \rrbracket$$

and

$$U := \text{Prop}_0 | \text{Prop}_1 | \llbracket \text{Prop}_0 \rrbracket$$

1. Given any judgment of the scheme $\frac{\mathcal{D}}{A \in U}$ then \mathcal{D} is the **unique** derivation of $A \in U$.

From now on we will be omitting the type construction derivations and write, informally, $A \in U$ (resp, $\Gamma \in U$) denoting the unique such derivation(s).

2. If $A \in \text{Prop}$ then one of the following holds exclusively : $A \in \text{Prop}_0$ or $A \in \text{Prop}_1$.
3. If $A \in \text{Prop}$ then $A \notin \llbracket \text{Prop}_0 \rrbracket$.
4. If $\Box A \in \text{Prop}$ then $\Box A \in \text{Prop}_1$.
5. If $\Box A \in \text{Prop}_1$ then $A \in \text{Prop}_0$.
6. If $\Box A \in \text{Prop}_1$ then $\llbracket A \rrbracket \in \llbracket \text{Prop}_0 \rrbracket$.
7. If $\llbracket A \rrbracket \in U$ then $U = \llbracket \text{Prop}_0 \rrbracket$ and $A \in \text{Prop}_0$.
8. If $A \in \text{Prop}_1$ then $\llbracket A \rrbracket \notin U$ for any U .
9. If A is of the form $\Box \Box A'$ then $A \notin U$ for any U .

10. If $A \in U$ then A cannot have any subformula of the form $\Box\Box A'$.

Proof. 1. By double induction on the structure of the formula and the structure of the appropriate derivations.

2. For the exclusive argument by double induction on the structure of the formula and the structure of the appropriate derivations.
3. By contradiction. If $A \in \llbracket \mathbf{Prop}_0 \rrbracket$ then A is of the form $\llbracket A' \rrbracket$. By induction on the derivations: if $A \in \mathbf{Prop}_{0,1}$ it cannot be of such form. Using item 1 we arrive in contradiction.
4. Trivially by case analysis.
5. Directly by the previous item.
6. Trivial by previous item.
7. Trivial by case analysis on the derivation
8. By contradiction. Using the previous item and item 2.
9. By contradiction. Assume that $\Box\Box A' \in U$ is derivable. The only rule that could have been applied is *BOX* which requires a proof of the premise $\Box A' \in \mathbf{Prop}_0$. That is impossible based on previous item.
10. By induction on the derivations $A \in U$ and using the – standard – definition of subformula relation.

□

Basic Facts on Context Wellformedness For every derived judgment of the scheme $\mathcal{CX} \vdash \mathcal{WF}$ with $\mathcal{WF} := \mathbf{wf} \mid \llbracket \mathbf{wf} \rrbracket$ and \mathcal{CX} a metavariable ranging over lists of labeled formulae.

1. If $\mathcal{WF} = \mathbf{wf}$ then $\mathcal{CX} = \Gamma$ where, exclusively, either $\Gamma \in \mathbf{Prop}$ or $\Gamma = \bullet$, and $\Gamma \not\vdash \llbracket \mathbf{wf} \rrbracket$.
2. If $\mathcal{WF} = \llbracket \mathbf{wf} \rrbracket$ then $\mathcal{CX} = \Delta$ where exclusively, either $\Delta \in \llbracket \mathbf{Prop}_0 \rrbracket$ or $\Delta = \circ$, and $\Delta \not\vdash \mathbf{wf}$.
3. If $\mathcal{CX} = \Gamma, x : A$ then $\mathcal{WF} = \mathbf{wf}$, $A \in \mathbf{Prop}$ and, $\Gamma \vdash \mathbf{wf}$.
4. If $\mathcal{CX} = \Delta, s : A$ then $\mathcal{WF} = \llbracket \mathbf{wf} \rrbracket$, $A \in \llbracket \mathbf{Prop}_0 \rrbracket$ and $\Delta \vdash \llbracket \mathbf{wf} \rrbracket$.
5. If $\mathcal{CX} = \llbracket \Gamma \rrbracket$ for some $\Gamma \vdash \mathbf{wf}$ then $\mathcal{WF} = \llbracket \mathbf{wf} \rrbracket$ and either, $\Gamma = \bullet$ or $\Gamma \in \mathbf{Prop}_0$.

Proof. • Items 1, 2 are trivial by case analysis on the derivations for context wellformedness. For items 3, 4 notice that x, x_i labels can only be part of a \mathbf{Prop} context and similarly for s, s_1 labels.

- By contradiction, assume $A \in \Gamma$ s.t. $A \notin \mathbf{Prop}_0$ from 1 it can only be $A \in \mathbf{Prop}$. Hence $A \in \mathbf{Prop}_1$ (using item 1 in .1) but then $\llbracket A \rrbracket$ is not an element of any universe (using item 8 in .1) and hence it cannot be in the co-domain of any well formed context.

□

Guarded \Box_{IE} rule application All instances of the \Box_{IE} rule apply with context $\Gamma' \in \mathbf{Prop}_0$.

Proof. Trivially by the previous item.

□

Separation of Judgments For every judgment of the scheme $Ctx \vdash A$ with a derivation in JCalc one of the two holds exclusively:

1. (**Prop Judgments**) $Ctx = \Gamma$ with $\Gamma \vdash \mathbf{wf}$ and $\Gamma, A \in \mathbf{Prop}$ or,
2. ($\llbracket \mathbf{Prop}_0 \rrbracket$ **Judgments**) $Ctx = \Delta$ with $\Delta \vdash \llbracket \mathbf{wf} \rrbracket$ and $\Delta, A \in \llbracket \mathbf{Prop}_0 \rrbracket$

Proof. By induction on the derivations of this scheme. Using some obvious inversion facts such as if $\llbracket A_1 \supset A_2 \rrbracket \in \llbracket \mathbf{Prop}_0 \rrbracket$ then $A \supset A_2 \in \mathbf{Prop}_0$ and whence, $A_2 \in \mathbf{Prop}_0$ and $\llbracket A_2 \rrbracket \in \llbracket \mathbf{Prop}_0 \rrbracket$ and facts in .1. \square

Deduction Theorem for Validity Judgments With $\Delta \vdash \llbracket \mathbf{wf} \rrbracket$, if $\Delta, s : \llbracket A \rrbracket \vdash \llbracket B \rrbracket$ then $\Delta \vdash \llbracket A \supset B \rrbracket$.

Proof. The proof is essentially the deduction theorem for a Hilbert style formulation of the corresponding fragment of propositional logic and we do not show it here for economy. Note that this theorem cannot be proven without the logical specification Ax_1, Ax_2 . I.e. it is exactly the requirements of the logical specification that ensure that all interpretations should adequately embed intuitionistic implication. \square

$\llbracket \cdot \rrbracket$ Lifting Lemma Given any wellformed context of assumptions $\Gamma \vdash \mathbf{wf}$ and $\Gamma, A \in \mathbf{Prop}_0$ then $\Gamma \vdash A \implies \llbracket \Gamma \rrbracket \vdash \llbracket A \rrbracket$.

Proof. The proof goes by induction on the derivations trivially for all the cases (\supset_E is treated using the **App** rule that internalizes Modus ponens). For the $\supset I$ the previous theorem has to be used. \square

\Box Lifting Lemma For $\Gamma, A \in \mathbf{Prop}_0$, then $\Gamma \vdash A$ implies $\Box \Gamma \vdash \Box A$.

Proof. Assuming a derivation $\mathcal{D} :: \Gamma \vdash A$ from .1 there exists corresponding validity derivation $\mathcal{E} :: \llbracket \Gamma \rrbracket \vdash \llbracket A \rrbracket$. Using the two as premises in the \Box_{IE} with $\Gamma := \Box \Gamma$ we obtain $\Box \Gamma \vdash \Box A$. \square

From the previous we get: Let us show an inverse principle to the \Box Lifting Lemma. We define for A in **Prop**:

$$\begin{aligned} \downarrow P_i &= P_i \\ \downarrow (A_1 \supset A_2) &= \downarrow A_1 \supset \downarrow A_2 \\ \downarrow \Box A &= \downarrow A \end{aligned}$$

And the lifting of the \downarrow over $\Gamma \in \mathbf{Prop}$. We get:

Collapse \Box Lemma If $\Gamma \vdash A$ for $\Gamma, A \in \mathbf{Prop}$ then $\downarrow \Gamma \vdash \downarrow A$.

Weakening For the N.D. system of JCalc, with $\Gamma, \Gamma' \vdash \mathbf{wf}$ and $\Delta, \Delta' \vdash \llbracket \mathbf{wf} \rrbracket$.

1. If $\Gamma \vdash A$ then $\Gamma, \Gamma' \vdash A$.
2. If $\Delta \vdash \llbracket A \rrbracket$ then $\Delta, \Delta' \vdash \llbracket A \rrbracket$.

Proof. By induction on derivations. \square

Contraction For the N.D. system of JCalc, with $\Gamma, x : A, x' : A, \Gamma' \vdash \mathbf{wf}$ and $\Delta, s : \llbracket A \rrbracket, s' : \llbracket A \rrbracket, \Delta' \vdash \llbracket \mathbf{wf} \rrbracket$.

1. If $\Gamma, x : A, x' : A, \Gamma' \vdash B$ then $\Gamma, x : A, \Gamma' \vdash B$.
2. If $\Delta, s : \llbracket A \rrbracket, s' : \llbracket A \rrbracket, \Delta' \vdash \llbracket B \rrbracket$ then $\Delta, s : \llbracket A \rrbracket, \Delta' \vdash \llbracket B \rrbracket$.

Proof. By induction on derivations. \square

Permutation For the N.D. system of JCalc, with $\Gamma \vdash \mathbf{wf}$ and $\Delta \vdash \llbracket \mathbf{wf} \rrbracket$ and $\pi\Gamma$ and $\pi\Delta$ the collection of well-formed contexts of assumptions with the same co-domain of Γ, Δ we get

1. If $\Gamma \vdash A$ and $\Gamma' \in \pi\Gamma$ then $\Gamma' \vdash A$.
2. If $\Delta \vdash \llbracket A \rrbracket$ and $\Delta' \in \pi\Delta$ then $\Delta' \vdash \llbracket A \rrbracket$.

Proof. By induction on derivations. □

Substitution Principle The following hold for both kinds of judgments:

1. If $\Gamma, x : A \vdash B$ and $\Gamma \vdash A$ then $\Gamma \vdash B$
2. If $\Delta, s : \llbracket A \rrbracket \vdash \llbracket B \rrbracket$ and $\Delta \vdash \llbracket A \rrbracket$ then $\Delta \vdash \llbracket B \rrbracket$

All previous 9 theorems can be stated for proof terms too. We should discuss the following:

Deduction Theorem / Emulation of λ abstraction With $\Delta \vdash \llbracket \mathbf{wf} \rrbracket$, if $\Delta, s : \llbracket A \rrbracket \vdash j : \llbracket B \rrbracket$ then there exists j' s.t. $\Delta \vdash j' : \llbracket A \supset B \rrbracket$.

$\llbracket \cdot \rrbracket$ Lifting Lemma for terms If $\Gamma A \in \mathbf{Prop}_0$ and $\Gamma \vdash M : A$ then there exists j s.t. $\llbracket \Gamma \rrbracket \vdash j : \llbracket A \rrbracket$.

In both theorems the existence of this j, j' is algorithmic following the induction proof.

.2 Linking on the function space


The above mentioned algorithms permit for translating λ abstractions to polynomials of S, K combinators which is a standard result in the literature.

We do not give the details here but the translation is syntax driven as it can be seen by the inductive nature of the proofs.

Henceforth, we can generalize the construction in 6.1 so that it permits for dynamic linking of functions of the client (with missing implementations) such as $\lambda n : \text{int. push } n \text{ empty}$ dynamically given that the host actually implements a higher-order function space (that is it implements the combinators S, K in, say, own lambda calculus λ^J). Given implementations of `push_impl`, `empty_impl` the linker produces an application expression consisting of `push_impl`, `empty_impl`, S and K . The execution of the target expression will happen in the host after dereferencing `push_impl`, `empty_impl` (dynamic part) and the combinators S, K (constant part) as, say, lambdas (e.g. $K = \lambda^J x. \lambda^J y. x$).

.3 Gentzen's reduction Principle for \Box (General)

$$\begin{array}{c}
 \begin{array}{cccc}
 \begin{array}{c} \nabla D_1 \\ A_1 \end{array} & \begin{array}{c} \nabla E_1 \\ \llbracket A_1 \rrbracket \end{array} & \begin{array}{c} \nabla D_i \\ A_i \end{array} & \begin{array}{c} \nabla E_i \\ \llbracket A_i \rrbracket \end{array} \\
 \hline
 \Box A_1 & \dots & \Box A_i &
 \end{array}
 \quad
 \begin{array}{cc}
 \frac{}{A_1 \dots A_i} \vec{x} & \frac{}{\llbracket A_1 \dots A_i \rrbracket} \vec{s} \\
 \vdots & \vdots \\
 B & \llbracket B \rrbracket
 \end{array}
 \\
 \hline
 \Box B & I_{\Box B} E_{\Box A}^{x,s}
 \end{array}
 \Rightarrow_R$$



.4 Notes on the cut elimination proof and normalization of natural deduction

Standardly, we add the bottom type and elimination rule in the natural deduction and show that in $\text{Jcalc} + \perp$: $\not\vdash \perp$. The addition goes as follows:

$$\begin{array}{c}
\frac{}{\perp \in \text{Prop}_0} \text{BOT} \qquad \frac{\Gamma \vdash \perp \quad A \in \text{Prop}}{\Gamma \vdash A} E_{\perp}
\end{array}$$

Our proof strategy follows directly [?]. We construct an intercalation calculus [?] corresponding to the **Prop** fragment with the following two judgments:

$A \uparrow$ for “Proposition A has normal deduction”.

$A \downarrow$ for “Proposition A is extracted from hypothesis”.

This calculus is, essentially, restricting the natural deduction to canonical derivations. The $\llbracket \text{judgments} \rrbracket$ are not annotated and are directly ported from the natural deduction since we observe consistency in **Prop**. The construction

is identical to [?] (Chapter 3) for the **Hypotheses**, **Coercion**, \supset , \perp cases, we add the \Box case.

$$\begin{array}{c}
\frac{x : A \downarrow \in \Gamma^\downarrow}{\Gamma^\downarrow \vdash^- A \downarrow} \Gamma\text{-HYP} \qquad \frac{\Gamma^\downarrow \vdash^- A \downarrow}{\Gamma^\downarrow \vdash^- A \uparrow} \downarrow\uparrow \\
\\
\frac{\Gamma^\downarrow, x : A \downarrow \vdash^- B \uparrow}{\Gamma^\downarrow \vdash^- A \supset B \uparrow} \supset I^x \quad \frac{\Gamma^\downarrow \vdash^- A \supset B \downarrow \quad \Gamma^\downarrow \vdash^- A \uparrow}{\Gamma^\downarrow \vdash^- B \downarrow} \supset E \\
\\
\frac{\Gamma^\downarrow \vdash^- \perp \downarrow \quad A \in \mathbf{Prop}}{\Gamma^\downarrow \vdash^- A \uparrow} E_\perp \\
\\
\frac{\Gamma^\downarrow \vdash \Box \Gamma' \downarrow \quad \Gamma'^\downarrow \vdash A \uparrow \quad \llbracket \Gamma' \rrbracket \vdash \llbracket A \rrbracket}{\Gamma^\downarrow \vdash \Box A \uparrow} \Box_{IE}
\end{array}$$

Where $\Gamma^\downarrow \vdash \Box \Gamma'$ abbreviates $\forall A_i \in \Gamma'. \Gamma^\downarrow \vdash \Box A_i \downarrow$. We prove simultaneously by induction:

Soundness of Normal Deductions The following hold:

1. If $\Gamma^\downarrow \vdash^- A \uparrow$ then $\Gamma \vdash A$, and
2. If $\Gamma^\downarrow \vdash^- A \downarrow$ then $\Gamma \vdash A$.

Proof. Simultaneously by induction on derivations. □

It is easy to see that this restricted proof system $\not\vdash \neg \perp \uparrow$. It is hard to show its completeness to the non-restricted natural deduction $(\vdash + \perp_E)$ of

Jcalc) directly. For that reason we add a rule to make it complete (\vdash^+) preserving soundness and get a system of Annotated Deductions. We show the correspondence of the restricted system (\vdash^-) to a cut-free sequent calculus (JSeq), the correspondence of the extended system (\vdash^+) to Jseq + Cut and show cut elimination.¹

To obtain completeness we add the rule:

$$\frac{\Gamma^\downarrow \vdash A \uparrow}{\Gamma^\downarrow \vdash A \downarrow} \uparrow\downarrow$$

We define $\vdash^+ := \vdash^-$ with $\uparrow\downarrow$ Rule. We show:

Soundness of Annotated Deductions The following hold:

1. If $\Gamma^\downarrow \vdash^+ A \uparrow$ then $\Gamma \vdash A$, and
2. If $\Gamma^\downarrow \vdash^+ A \downarrow$ then $\Gamma \vdash A$.

Proof. As previous item. □

Completeness of Annotated Deductions The following hold:

1. If $\Gamma \vdash A$ then, $\Gamma \downarrow \vdash^+ A \uparrow$, and
2. If $\Gamma \vdash A$, then $\Gamma \downarrow \vdash^+ A \downarrow$.

Proof. By induction over the structure of the $\Gamma \vdash A$ derivation. □

¹In reality, the sequent calculus formulation is built exactly upon intuitions on the intercalation calculus. We refer the reader to the references.

Next we move with devising a sequent calculus formulation corresponding to normal proofs $\Gamma^\downarrow \vdash^- A \uparrow$. The calculus that is given in the main body of this theorem. We repeat it here for completeness.

Sequent Calculus ($\llbracket \text{Prop}_0 \rrbracket$)

$$\Delta \Rightarrow \llbracket A \rrbracket := \exists \Delta' \in \pi(\Delta) \text{ s.t } \Delta' \vdash \llbracket A \rrbracket$$

where $\pi(\Delta)$ is the collection of wellformed $\llbracket \text{Prop}_0 \rrbracket$ contexts $\Delta' \vdash \llbracket \text{wf} \rrbracket$ with some permutation of the multiset Δ as co-domain.

Sequent Calculus (Prop)

$$\begin{array}{c} \frac{}{\Gamma, A \Rightarrow A} Id \qquad \frac{\Gamma, A \supset B, B \Rightarrow C \quad \Gamma, A \supset B \Rightarrow A}{\Gamma, A \supset B \Rightarrow C} \supset_L \\[2ex] \frac{\Gamma, A \Rightarrow B}{\Gamma \Rightarrow A \supset B} \supset_R \qquad \frac{}{\Gamma, \perp \Rightarrow A} \perp_L \\[2ex] \frac{\Box \Gamma', \Gamma' \Rightarrow A \quad \llbracket \Gamma' \rrbracket \Rightarrow \llbracket A \rrbracket \quad \Gamma \in \text{Prop}}{\Gamma, \Box \Gamma' \Rightarrow \Box A} \Box_{LR} \end{array}$$

We want to show correspondence of the sequent calculus w.r.t normal proofs (\vdash^-). Two lemmas are required to show soundness.

Substitution principle for extractions The following hold:

1. If $\Gamma_1^\downarrow, x : A^\downarrow, \Gamma_2^\downarrow \vdash^- B \uparrow$ and
 $\Gamma_1^\downarrow \vdash^- A \uparrow$ then $\Gamma_1^\downarrow, \Gamma_2^\downarrow \vdash^- B \uparrow$

2. If $\Gamma_1^\downarrow, x : A^\downarrow, \Gamma_2^\downarrow \vdash^- B \downarrow$ and $\Gamma_1^\downarrow \vdash^- A \downarrow$ then $\Gamma_1^\downarrow, \Gamma_2^\downarrow \vdash^- B \uparrow$

Proof. Simultaneously by induction on the derivations $A \downarrow$ and $A \uparrow$. \square

And making use of the previous we can show, with $(\downarrow A$ defined previously):

Collapse principle for normal deductions The following hold:

1. If $\Gamma^\downarrow, \vdash^- A \uparrow$ then $\downarrow \Gamma^\downarrow \vdash^- \downarrow A \uparrow$ and,
2. If $\Gamma^\downarrow \vdash^- A \downarrow$ then $\downarrow \Gamma^\downarrow \vdash^- \downarrow A \downarrow$

Using the previous lemmas and by induction we can show :

Soundness of the Sequent Calculus If $\Gamma \Rightarrow B$ then $\Gamma^\downarrow \vdash^- B \uparrow$.

Soundness of the Sequent Calculus with Cut If $\Gamma \Rightarrow^+ B$ then $\Gamma^\downarrow \vdash^+ B \uparrow$.

Next we define the $\Gamma \Rightarrow^+ A$ as $\Gamma \Rightarrow A$ plus the rule:

$$\frac{\Gamma \Rightarrow^+ A \quad \Gamma, A \Rightarrow^+ B}{\Gamma \Rightarrow^+ B} \text{CUT}$$

Proof. As before. The cut rule case is handled by the $\uparrow\downarrow$ and substitution for extractions principle showcasing that the correspondence of the cut rule to the coercion from normal to extraction derivations. \square

Standard structural properties (*Weakening, Contraction*) to show completeness. We do not show these here but they hold.

Completeness of the Sequent Calculus The following hold:

1. If $\Gamma^\downarrow \vdash^- B \Uparrow$ then $\Gamma \Rightarrow B$ and,
2. If $\Gamma^\downarrow \vdash^- A \Downarrow$ and $\Gamma, A \Rightarrow B$ then $\Gamma \Rightarrow B$

Proof. Simultaneously by induction on the given derivations making use of the structural properties. \square

Similarly we show for the extended systems.

Completeness of the Sequent Calculus with Cut The following hold:

1. If $\Gamma^\downarrow \vdash^+ B \Uparrow$ then $\Gamma \Rightarrow^+ B$ and,
2. If $\Gamma^\downarrow \vdash^+ A \Downarrow$ and $\Gamma, A \Rightarrow^+ B$ then $\Gamma \Rightarrow^+ B$.

Proof. As before. The extra case is handled by the Cut rule. \square

After establishing the correspondence of \vdash^- with \Rightarrow and of \vdash^+ with \Rightarrow^+ we move on with:

Admissibility of Cut If $\Gamma \Rightarrow A$ and $\Gamma, A \Rightarrow B$ then $\Gamma \Rightarrow B$.

The proof is by triple induction on the structure of the formula, and the given derivations and we leave it for a technical report. This gives easily:

Cut Elimination If $\Gamma \Rightarrow^+ A$ then $\Gamma \Rightarrow A$.

Which in turn gives us:

Normalization for Natural Deduction If $\Gamma \vdash A$ then $\Gamma^\downarrow \vdash^- A \Uparrow$

Proof. From assumption $\Gamma \vdash A$ which by .4 gives $\Gamma \vdash^+ A \uparrow$. By .4 and Cut Elimination we obtain $\Gamma \Rightarrow A$ which by .4 completes the proof. \square

As a result we obtain:

Proof. By contradiction, assume $\vdash \perp$ then $\Rightarrow \perp$ which is not possible. \square

Bibliography

- [1] Zine El abidine Benaissa, Eugenio Moggi, Walid Taha, and Tim Sheard. Logical modalities and multi-stage programming, 1999.
- [2] Jesse Alt and Sergei Artemov. Reflective λ -calculus. Technical Report CFIS 2000-06, Cornell University, 2000.
- [3] S Artemov. Unified semantics for modality and lambda terms via proof polynomials. *Logic, Language and Computation*, 97.
- [4] S. Artemov. Explicit provability and constructive semantics. *Bulletin of Symbolic Logic*, 7(1):1–36, 2001.
- [5] Sergei Artemov and Melvin Fitting. Justification logic. In Edward N. Zalta, editor, *The Stanford Encyclopedia of Philosophy*. Fall 2012 edition, 2012.

- [6] Sergei Artemov and Roman Kuznets. Logical omniscience as infeasibility. *Annals of Pure and Applied Logic*, 165(1):6–25, 2014.
- [7] Sergei [N.] Artëmov. Logic of proofs. *Annals of Pure and Applied Logic*, 67(1–3):29–59, May 1994.
- [8] Sergei N. Artemov. Operational modal logic. Technical Report MSI 95–29, Cornell University, December 1995.
- [9] Sergei N. Artemov. Explicit provability and constructive semantics. *Bulletin of Symbolic Logic*, 7(1):1–36, March 2001.
- [10] Sergei N. Artemov. Unified semantics for modality and λ -terms via proof polynomials. In Kees Vermeulen and Ann Copestake, editors, *Algebras, Diagrams and Decisions in Language, Logic and Computation*, volume 144 of *CSLI Lecture Notes*, pages 89–118. CSLI Publications, Stanford, 2002.
- [11] Sergei N. Artëmov. Justification logic. In *JELIA*, pages 1–4, 2008.
- [12] Sergei N. Artemov. The ontology of justifications in the logical setting. *Stud. Log.*, 100(1-2):17–30, April 2012.
- [13] Sergei N. Artemov and Lev D. Beklemishev. Provability logic. In D[ov] M. Gabbay and F. Guenther, editors, *Handbook of Philosophical Logic, 2nd Edition*, volume 13, pages 189–360. Springer, 2005.

- [14] Sergei [N.] Artemov and Eduardo Bonelli. The intensional lambda calculus. In Sergei N. Artemov and Anil Nerode, editors, *Logical Foundations of Computer Science, International Symposium, LFCS 2007, New York, NY, USA, June 4–7, 2007, Proceedings*, volume 4514 of *Lecture Notes in Computer Science*, pages 12–25. Springer, 2007.
- [15] Sergei Nikolaevich Artemov. Kolmogorov and gödel’s approach to intuitionistic logic: current developments. *Russian Mathematical Surveys*, 59(2):203, 2004.
- [16] Steve Awodey. *Category theory*. Oxford University Press, 2010.
- [17] Steven Awodey and Florian Rabe. Kripke semantics for martin-löf’s extensional type theory. In *TLCA’09*, pages 249–263, 2009.
- [18] H. P. Barendregt. *The Lambda Calculus: Its Syntax and Semantics*. Sole Distributors for the U.S.A. And Canada, Elsevier Science Pub. Co., 1984.
- [19] Gilles Barthe and Thierry Coquand. An Introduction to Dependent Type Theory. *Lecture Notes in Computer Science*, pages 1–41.
- [20] Francisco Bavera and Eduardo Bonelli. Justification logic and history based computation. In *International Colloquium on Theoretical Aspects of Computing*, pages 337–351. Springer, 2010.
- [21] G. Bellin, V. de Paiva, and E. Ritter. Extended Curry-Howard Correspondence for a Basic Constructive Modal Logic. preprint; presented at M4M-2, ILLC, UvAmsterdam, 2001, 2001.

- [22] Gianluigi Bellin, Valeria de Paiva, and Eike Ritter. Extended curry-howard correspondence for a basic constructive modal logic. In *In Proceedings of Methods for Modalities*, 2001.
- [23] G.M. Bierman and V. de Paiva. On an intuitionistic modal logic. *Studia Logica*, (65):383–416, 2000.
- [24] Eduardo Bonelli and Federico Feller. Justification logic as a foundation for certifying mobile computation. *Annals of Pure and Applied Logic*, 163(7):935 – 950, 2012.
- [25] George S. Boolos. *The Logic of Provability*.
- [26] Luitzen Egbertus Jan Brouwer and A Heyting. *Collected Works: Vol.: 1.: Philosophy and Foundations of Mathematics*. North-Holland Publishing Company, American Elsevier Publishing Company, Incorporated, 1975.
- [27] Samuel R. Buss. Chapter ii first-order proof theory of arithmetic. In Samuel R. Buss, editor, *Handbook of Proof Theory*, volume 137 of *Studies in Logic and the Foundations of Mathematics*, pages 79 – 147. Elsevier, 1998.
- [28] Iliano Cervesato and Andre Scedrov. Relating state-based and process-based concurrency through linear logic (full-version). *Information and Computation*, 207(10):1044 – 1077, 2009.
- [29] Haskell B Curry. Functionality in combinatory logic. *Proceedings of the National Academy of Sciences*, 20(11):584–590, 1934.

- [30] Newton C.A. da Costa and Steven French. Inconsistency in science. A partial perspective. pages 105–118.
- [31] Michael AE Dummett. *Elements of intuitionism*, volume 39. Oxford University Press, 2000.
- [32] Melvin Fitting. The logic of proofs, semantically.
- [33] Melvin Fitting. The logic of proofs, semantically. *Annals of Pure and Applied Logic*, 132(1):1–25, 2005.
- [34] Gerhard Gentzen. The collected papers of gerhard gentzen. 1970.
- [35] Jean Y. Girard, Paul Taylor, and Yves Lafont. *Proofs and types*. Cambridge University Press, New York, NY, USA, 1989.
- [36] Kurt Gödel. *On Formally Undecidable Propositions of Principia Mathematica and Related Systems*. Dover Publications, April 1992.
- [37] Jean Goubault-Larrecq and Jean Goubault-larrecq. On computational interpretations of the modal logic $S4$ ii. the. Technical report, Institut für Logik, Komplexität und Deduktionssysteme, Universität, 1996.
- [38] Professor Robert Harper. *Practical Foundations for Programming Languages*. Cambridge University Press, New York, NY, USA, 2012.
- [39] Robert Harper. Homotopy type theory seminar. http://www.cs.cmu.edu/~rwh/courses/hott/notes/notes_week1.pdf.

- [40] Robert Harper. *Programming in Standard ML*. 1998.
- [41] Robert Harper. Extensionality, intensionality, and Brouwer's dictum. <http://existentialtype.wordpress.com/2012/08/11/extensionality-intensionality-and-brouwers-dictum/>, August 2012.
- [42] Robert Harper. Constructive mathematics is not metamathematics. <http://existentialtype.wordpress.com/2013/07/10/constructive-mathematics-is-not-meta-mathematics/>, July 2013.
- [43] S.Balzer H.DeYoung. Homotopy type theory seminar. <http://http://www.cs.cmu.edu/~rwh/courses/hott/>.
- [44] Arend Heyting. *Intuitionism: an introduction*, volume 41. Elsevier, 1966.
- [45] William A Howard. The formulae-as-types notion of construction. 1995.
- [46] GA Kavvos. System k: a simple modal $\{\backslash \text{lambda}\}$ -calculus. *arXiv preprint arXiv:1602.04860*, 2016.
- [47] Andrey Kolmogorov. O principe tertium non datur. *matematicheskij sbornik* 32: 646–667. *English trans. in van Heijenoort [1967, 414–437]*, 1925.
- [48] J. Lambek. Deductive systems and categories I. Syntactic calculus and residuated categories. 2(4):287–318, 1968.

- [49] J. Lambek and P. Scott. *Introduction to Higher-Order Categorical Logic*. Cambridge University Press, 1985.
- [50] Joachim Lambek. *Deductive systems and categories II. Standard constructions and closed categories*, pages 76–122. Springer Berlin Heidelberg, Berlin, Heidelberg, 1969.
- [51] Per Martin-Löf. On the meanings of the logical constants and the justifications of the logical laws. *Nordic Journal of Philosophical Logic*, 1(1):11–60.
- [52] Per Martin-Löf. Constructive Mathematics and Computer Programming. In *6-th International Congress for Logic, Methodology and Philosophy of Science, 1979*, pages 153–175. North-Holland, 1982.
- [53] Per Martin-Löf. *Intuitionistic Type Theory*. Bibliopolis, Naples, 1984.
- [54] Per Martin-Löf. On the Meanings of the Logical Constants and the Justifications of the Logical Laws. *Nordic Journal of Philosophical Logic*, 1(1):11–60, May 1996.
- [55] Per Martin-Lof and Giovanni Sambin. *Intuitionistic type theory*, volume 17. Bibliopolis Naples, 1984.
- [56] Aleksandar Nanevski, Frank Pfenning, and Brigitte Pientka. Contextual modal type theory. *ACM Trans. Comput. Logic*, 9(3):23:1–23:49, June 2008.

- [57] Bengt Nordstrom, Kent Petersson, and Jan M. Smith. *Programming in Martin-Löf's Type Theory: An Introduction*. Oxford University Press, USA, July 1990.
- [58] Ulf Norell. Dependently typed programming in agda. In *In Lecture Notes from the Summer School in Advanced Functional Programming*, 2008.
- [59] C.-H. L. Ong and C. A. Stewart. A curry-howard foundation for functional computation with control. In *Proceedings of the 24th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '97, pages 215–227, New York, NY, USA, 1997. ACM.
- [60] Rohit Parikh. Existence and feasibility in arithmetic. *J. Symb. Log.*, pages 494–508, 1971.
- [61] Frank Pfenning. Structural cut elimination: I. intuitionistic and classical logic. *Information and Computation*, 157(1):84–141, 2000.
- [62] Frank Pfenning. Lecture notes on harmony. <http://www.cs.cmu.edu/~fp/courses/15317-f09/lectures/03-harmony.pdf>, September 2009.
- [63] Frank Pfenning. Lecture notes on natural deduction. <http://www.cs.cmu.edu/~fp/courses/15317-f09/lectures/02-natded.pdf>, August 2009.
- [64] Frank Pfenning and Rowan Davies. A judgmental reconstruction of modal logic. *Mathematical Structures in Comp. Sci.*, 11(04):511–540, August 2001.

- [65] Benjamin C. Pierce. *Types and Programming Languages*. MIT Press, Cambridge, MA, USA, 2002.
- [66] Konstantinos Pouliasis. *A Curry–Howard View of Basic Justification Logic*, pages 316–337. Springer Berlin Heidelberg, Berlin, Heidelberg, 2016.
- [67] Konstantinos Pouliasis and Giuseppe Primiero. J-calc: A typed lambda calculus for intuitionistic justification logic. *Electr. Notes Theor. Comput. Sci.*, 300:71–87, 2014.
- [68] Dag Prawitz. Natural deduction: A proof-theoretical study. *AMC*, 10:12.
- [69] Dag Prawitz. Ideas and results in proof theory. *Studies in Logic and the Foundations of Mathematics*, 63:235–307, 1971.
- [70] Wilfried Sieg and John Byrnes. Normal natural deduction proofs (in classical logic). *Studia Logica*, 60(1):67–106, 1998.
- [71] Peter Smith. An introduction to gödel’s theorems, 2007.
- [72] Morten Heine B. Sørensen and Pawel Urzyczyn. Lectures on the curry-howard isomorphism, 1998.
- [73] Morten Heine B. Sørensen and Pawel Urzyczyn. *Lectures on the Curry–Howard Isomorphism*, volume 149 of *Studies in Logic and the Foundations of Mathematics*. Elsevier, 2006.

- [74] A.S. Troelstra and D. van Dalen. *Constructivism in Mathematics: An Introduction*, volume I,II. North-Holland, Amsterdam, 1988.