


We will now upload multiple commits to github from another directory.



Create a directory by name 'dev_flowers'

```
fms@git_practice:~$ mkdir dev_flowers
fms@git_practice:~$ cd dev_flowers
fms@git_practice:~/dev_flowers$
```

Clone the project from github. This should fetch our first commit that we made which is fruits.c file.

```
fms@git_practice:~/dev_flowers$ git clone https://github.com/srivalli-projects/sample-project.git
Cloning into 'sample-project'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 3 (delta 0), pack-reused 0
Unpacking objects: 100% (3/3), done.
fms@git_practice:~/dev_flowers$
```

```
fms@git_practice:~/dev_flowers$ ls
sample-project
fms@git_practice:~/dev_flowers$ cd sample-project
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ ls -al
total 16
drwxr-xr-x 3 fms fms 4096 Nov  6 13:21 .
drwxr-xr-x 3 fms fms 4096 Nov  6 13:21 ..
```

```
-rw-r--r-- 1 fms fms   6 Nov  6 13:21 fruits.c
drwxr-xr-x 8 fms fms 4096 Nov  6 13:21 .git
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git log
commit 36c5a24d35f6103fb391139008161f938bcefba (HEAD -> master,
origin/master, origin/HEAD)
Author: Dev-Fruits <dev_fruits@FRUITS.com>
Date:   Mon Nov 5 17:33:09 2018 +0530
```

```
    created a file fruits.c
fms@git_practice:~/dev_flowers/sample-project$
```

Cool, we got our first commit in this new folder.

```
fms@git_practice:~/dev_flowers/sample-project$ git status
On branch master
Your branch is up to date with 'origin/master'.
```

```
nothing to commit, working tree clean
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git branch
* master
fms@git_practice:~/dev_flowers/sample-project$
```

Now create a new file flowers.cpp

```
fms@git_practice:~/dev_flowers/sample-project$ vi flowers.cpp
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ cat flowers.cpp
Rose
Lilly
Jasmine
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git status
On branch master
Your branch is up to date with 'origin/master'.
```

Untracked files:
(use "git add <file>..." to include in what will be committed)

flowers.cpp

nothing added to commit but untracked files present (use "git add" to track)

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git add flowers.cpp
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git status
```

On branch master

Your branch is up to date with 'origin/master'.

Changes to be committed:

(use "git reset HEAD <file>..." to unstage)

new file: flowers.cpp

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ cat ~/.gitconfig
```

```
[user]
```

```
email = dev_fruits@FRUITS.com
```

```
name = Dev-Fruits
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

We do not want to commit with the name Dev-Fruits. So change the config file and update name to 'Dev-Flowers'.

```
fms@git_practice:~/dev_flowers/sample-project$ vi .git/config
```

```
fms@git_practice:~/dev_flowers/sample-project$ cat .git/config
```

```
[core]
```

```
repositoryformatversion = 0
```

```
filemode = true
```

```
bare = false
```

```
logallrefupdates = true
```

```
[remote "origin"]
```

```
url = https://github.com/srivalli-projects/sample-project.git
```

```
fetch = +refs/heads/*:refs/remotes/origin/*
```

```
[branch "master"]
```

```
remote = origin
```

```
merge = refs/heads/master
```

```
[user]
```

email = dev_flowers@FLOWERS.com

name = Dev-Flowers

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git commit -m "created flowers.cpp"
```

```
[master a135ee5] created flowers.cpp
```

```
1 file changed, 3 insertions(+)
```

```
create mode 100644 flowers.cpp
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git log
```

```
commit a135ee5c3e032c5120641d80efa7cf05ab1a73ad (HEAD -> master)
```

```
Author: Dev-Flowers <dev_flowers@FLOWERS.com>
```

```
Date: Tue Nov 6 13:26:04 2018 +0530
```

```
created flowers.cpp
```

```
commit 36c5a24d35f6103fb391139008161f938bcefbaf (origin/master,  
origin/HEAD)
```

```
Author: Dev-Fruits <dev_fruits@FRUITS.com>
```

```
Date: Mon Nov 5 17:33:09 2018 +0530
```

```
created a file fruits.c
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

We got 2 commits now in log. The latest commit will be always on the top which is referred to as HEAD.

Check the author in these 2 commits. Notice that whatever we update in config file is for our identity – who changed what.

```
fms@git_practice:~/dev_flowers/sample-project$ git status
```

```
On branch master
```

```
Your branch is ahead of 'origin/master' by 1 commit.
```

```
(use "git push" to publish your local commits)
```

```
nothing to commit, working tree clean
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

Branch is ahead of origin?

It means that our master branch has two commits and our origin in github has only one commit.

Now we will modify the file that is uploaded by Dev-Fruits. Our identity in commit will be Dev-Flowers.

```
fms@git_practice:~/dev_flowers/sample-project$ vi fruits.c
fms@git_practice:~/dev_flowers/sample-project$ git add fruits.c
fms@git_practice:~/dev_flowers/sample-project$ git commit -m "updated fruits.c"
```

```
[master 49a0f6b] updated fruits.c
1 file changed, 1 insertion(+)
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git log
commit 544e581fbb2e10e90fe64e6cb1567b48b22e1a44 (HEAD -> master)
Author: Dev-Flowers <dev_flowers@FLOWERS.com>
Date: Tue Nov 6 13:27:18 2018 +0530
```

updated [fruits.c](#)

```
commit a135ee5c3e032c5120641d80efa7cf05ab1a73ad
Author: Dev-Flowers <dev_flowers@FLOWERS.com>
Date: Tue Nov 6 13:26:04 2018 +0530
```

created [flowers.cpp](#)

```
commit 36c5a24d35f6103fb391139008161f938bcefbaf (origin/master,
origin/HEAD)
Author: Dev-Fruits <dev_fruits@FRUITS.com>
Date: Mon Nov 5 17:33:09 2018 +0530
```

created a file [fruits.c](#)

```
fms@git_practice:~/dev_flowers/sample-project$
```

```
fms@git_practice:~/dev_flowers/sample-project$ git push origin master
```

```
Username for 'https://github.com': srivalli-projects
```

```
Password for 'https://srivalli-projects@github.com':
```

```
Counting objects: 6, done.
```

```
Delta compression using up to 4 threads.
```

```
Compressing objects: 100% (4/4), done.
```

```
Writing objects: 100% (6/6), 580 bytes | 580.00 KiB/s, done.
```

```
Total 6 (delta 0), reused 0 (delta 0)
```

```
To https://github.com/srivalli-projects/sample-project.git
```

```
36c5a24..544e581 master -> master
```

```
fms@git_practice:~/dev_flowers/sample-project$
```

↔ Code

⚠ Issues 0

🔗 Pull requests 0

📁 Projects 0

Sample project to understand git

[Manage topics](#)

🕒 3 commits

🌿 1 branch

Branch: master ▼

New pull request



Dev-Flowers and Dev-Flowers updated fruits.c



flowers.cpp

created flowers.cpp



fruits.c

updated fruits.c

Branch: master ▼



Commits on Nov 6, 2018

updated fruits.c



Dev-Flowers authored and Dev-Flowers committed 12 minutes ago



544e581



created flowers.cpp



Dev-Flowers authored and Dev-Flowers committed 14 minutes ago



a135ee5



Commits on Nov 5, 2018

created a file fruits.c



Dev-Fruits authored and Dev-Fruits committed 20 hours ago



36c5a24

