

Let us start exploring some more git commands.

```
fms@git_practice:~$ mkdir dev_colors
```

```
fms@git_practice:~$ cd dev_colors
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git remote add
```

```
origin https://github.com/srivalli-projects/sample-project.git
```

```
fatal: not a git repository (or any of the parent directories): .git
```

```
fms@git_practice:~/dev_colors$
```

Since this is a normal dir, it will not recognize git commands.

```
fms@git_practice:~/dev_colors$ git init
```

```
Initialized empty Git repository in /home/fms/dev_colors/.git/
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git remote add
```

```
origin https://github.com/srivalli-projects/sample-project.git
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ ls
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ cat .git/config
```

```
[core]
```

```
    repositoryformatversion = 0
```

```
    filemode = true
```

```
    bare = false
```

```
    logallrefupdates = true
```

```
[remote "origin"]
```


```
    url = https://github.com/srivalli-projects/sample-project.git
```

```
    fetch = +refs/heads/*:refs/remotes/origin/*
```

```
fms@git_practice:~/dev_colors$
```

After adding the remote, the url got copied to .git/config automatically. So git knows where to push the changes.

Let us now pull the changes from git hub to this new dir 'dev\_colors'



```
fms@git_practice:~/dev_colors$ git pull origin master
remote: Enumerating objects: 9, done.
remote: Counting objects: 100% (9/9), done.
remote: Compressing objects: 100% (5/5), done.
Unpacking objects: 100% (9/9), done.
remote: Total 9 (delta 0), reused 9 (delta 0), pack-reused 0
From https://github.com/srivalli-projects/sample-project
* branch      master    -> FETCH_HEAD
* [new branch] master    -> origin/master
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ ls
flowers.cpp fruits.c
```

We got the two files.

```
fms@git_practice:~/dev_colors$ git branch
* master
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git log
commit 544e581fbb2e10e90fe64e6cb1567b48b22e1a44 (HEAD -> master,
origin/master)
Author: Dev-Flowers <dev_flowers@FLOWERS.com>
Date: Tue Nov 6 13:27:18 2018 +0530
```

updated fruits.c

commit a135ee5c3e032c5120641d80efa7cf05ab1a73ad  
Author: Dev-Flowers <dev\_flowers@FLOWERS.com>  
Date: Tue Nov 6 13:26:04 2018 +0530

created flowers.cpp

commit 36c5a24d35f6103fb391139008161f938bcefba  
Author: Dev-Fruits <dev\_fruits@FRUITS.com>  
Date: Mon Nov 5 17:33:09 2018 +0530

created a file fruits.c  
fms@git\_practice:~/dev\_colors\$

Create one more file.

fms@git\_practice:~/dev\_colors\$ **vi colors.java**  
fms@git\_practice:~/dev\_colors\$ **cat colors.java**  
Red  
Pink  
Yellow  
Blue  
fms@git\_practice:~/dev\_colors\$

One more.

fms@git\_practice:~/dev\_colors\$ **vi sweets.py**  
fms@git\_practice:~/dev\_colors\$ **cat sweets.py**  
Gulab Jamun  
fms@git\_practice:~/dev\_colors\$

fms@git\_practice:~/dev\_colors\$ **git status**  
On branch master  
Untracked files:  
(use "git add <file>..." to include in what will be committed)

colors.java  
sweets.py

nothing added to commit but untracked files present (use "git add" to track)

fms@git\_practice:~/dev\_colors\$ **git add colors.java**  
fms@git\_practice:~/dev\_colors\$

fms@git\_practice:~/dev\_colors\$ **git commit -m "created colors.java"**  
[master 66c27af] created colors.java  
1 file changed, 4 insertions(+)

```
create mode 100644 colors.java
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git add sweets.py
fms@git_practice:~/dev_colors$
fms@git_practice:~/dev_colors$ git commit -m "created sweets.py"
[master 7d8d1d6] created sweets.py
1 file changed, 1 insertion(+)
create mode 100644 sweets.py
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git status
On branch master
nothing to commit, working tree clean
fms@git_practice:~/dev_colors$
```

One more file please.

```
fms@git_practice:~/dev_colors$ vi vegetables.html
fms@git_practice:~/dev_colors$ cat vegetables.html
carrot
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git status
On branch master
Untracked files:
(use "git add <file>..." to include in what will be committed)
```

```
vegetables.html
```

```
nothing added to commit but untracked files present (use "git add" to track)
fms@git_practice:~/dev_colors$
```

We already added 2 files to staging area. Although we created a third file, we do not want to track this in git. So we can ignore this file using below command.

```
fms@git_practice:~/dev_colors$ vi .gitignore
fms@git_practice:~/dev_colors$ cat .gitignore
*.html
fms@git_practice:~/dev_colors$
```

It means that whichever file we do not want to keep track of, we can include them in .gitignore. In this case we are excluding all html files.

```
fms@git_practice:~/dev_colors$ git status
```

```
On branch master
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
.gitignore
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
fms@git_practice:~/dev_colors$
```

.gitignore is again a file. So we need to add this file to staging area and commit.

```
fms@git_practice:~/dev_colors$ git add .gitignore
```

```
fms@git_practice:~/dev_colors$ git status
```

```
On branch master
```

```
Changes to be committed:
```

```
(use "git reset HEAD <file>..." to unstage)
```

```
new file: .gitignore
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git commit -m "update .gitignore to ignore html files"
```

```
[master 32960a2] update .gitignore to ignore html files
```

```
1 file changed, 1 insertion(+)
```

```
create mode 100644 .gitignore
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git status
```

```
On branch master
```

```
nothing to commit, working tree clean
```

```
fms@git_practice:~/dev_colors$
```

```
fms@git_practice:~/dev_colors$ git log
```

```
commit 32960a24dfab357b4fdf63f201781c8e89639c44 (HEAD -> master)
```

```
Author: Dev-Colors <dev_colors@COLORS.com>
```

```
Date: Tue Nov 6 13:55:13 2018 +0530
```

update .gitignore to ignore html files

```
commit 7d8d1d6b906cdca9272f52c1afda8873add4cbdd
Author: Dev-Colors <dev_colors@COLORS.com>
Date: Tue Nov 6 13:52:02 2018 +0530
```

```
created sweets.py
```

```
commit 66c27af89135ff0e8b045d8be0b425165960f704
Author: Dev-Colors <dev_colors@COLORS.com>
Date: Tue Nov 6 13:51:28 2018 +0530
```

```
created colors.java
```

```
commit 544e581fbb2e10e90fe64e6cb1567b48b22e1a44 (origin/master)
Author: Dev-Flowers <dev_flowers@FLOWERS.com>
Date: Tue Nov 6 13:27:18 2018 +0530
```

```
updated fruits.c
```

```
commit a135ee5c3e032c5120641d80efa7cf05ab1a73ad
Author: Dev-Flowers <dev_flowers@FLOWERS.com>
Date: Tue Nov 6 13:26:04 2018 +0530
```

```
created flowers.cpp
```

```
commit 36c5a24d35f6103fb391139008161f938bcefbaf
Author: Dev-Fruits <dev_fruits@FRUITS.com>
Date: Mon Nov 5 17:33:09 2018 +0530
```

```
created a file fruits.c
fms@git_practice:~/dev_colors$
```

Push all these 3 commits.

```
fms@git_practice:~/dev_colors$ git push origin master
Username for 'https://github.com': srivalli-projects
Password for 'https://srivalli-projects@github.com':
Counting objects: 9, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (6/6), done.
Writing objects: 100% (9/9), 817 bytes | 817.00 KiB/s, done.
Total 9 (delta 2), reused 0 (delta 0)
```

remote: Resolving deltas: 100% (2/2), done.

To <https://github.com/srivalli-projects/sample-project.git>  
544e581..32960a2 master -> master

fms@git\_practice:~/dev\_colors\$

Branch: master ▼

#### Commits on Nov 6, 2018

**update .gitignore to ignore html files**



Dev-Colors authored and Dev-Colors committed 5 minutes ago

**created sweets.py**



Dev-Colors authored and Dev-Colors committed 8 minutes ago

**created colors.java**



Dev-Colors authored and Dev-Colors committed 9 minutes ago

**updated fruits.c**



Dev-Flowers authored and Dev-Flowers committed 33 minutes ago

**created flowers.cpp**



Dev-Flowers authored and Dev-Flowers committed 34 minutes ago

#### Commits on Nov 5, 2018

**created a file fruits.c**



Dev-Fruits authored and Dev-Fruits committed 20 hours ago