AlgoFlow Project Report

Personal DSA revision and solution history

Submitted by Krish Sondagar | 15 October 2026

Source repository https://github.com/KRISH141006/AlgoFlow

1 Project overview

AlgoFlow is a local web application that stores accepted DSA solutions, schedules revision, and records how a solution changes over time. This report describes the current application, its system design, database schema, implementation, screenshots, and test results.

Problem statement

Coding platforms record submissions, but the student still needs a practical way to revisit an approach, locate an earlier solution, and distinguish a saved attempt from an accepted submission. Local code files and topic notes do not provide a consistent revision schedule. Repeated imports can also create duplicate records if problem and submission identity are not handled explicitly.

Objectives

- Consolidate exported LeetCode and GeeksforGeeks solutions in a searchable library.
- Preserve exact source code, problem descriptions, topic tags, and solution assessments.
- Schedule explicit problem and theory reviews without altering existing revision history.
- Provide persistent storage, duplicate protection, and complete backup and additive restore.

Key features

My custom DSA Universal Sync extension collects solved problems and code from LeetCode and GeeksforGeeks. It supports fetching solved problems together and saving newly accepted submissions automatically as JSON files. AlgoFlow imports these files into a searchable collection. The application provides four views: Today, Library, Problem Detail, and Progress. Users can import JSON, add problems and topics, view stored solutions, save a new version, complete a due review, and export or restore a backup. Acceptance status and review status are separate: an accepted problem can still be pending revision.

Implementation scope

I chose this project to organize my DSA practice and make revision easier. The application uses FastAPI, React, and a local SQLite database. I wrote the Universal Sync extension to collect my solutions, and the web application was developed with AI assistance. The current workflow uses JSON files to transfer data from the extension to AlgoFlow. It is designed for one local user.

2 System design

The system has two main parts: the browser extension that collects solutions and the web application that organizes them. The frontend and backend are served from one local address. HTTP requests enter FastAPI routes, pass through request validation and service functions, and read or update the selected SQLite database. The original tracker is read only during preparation.




Figure 1 Local application architecture

Component responsibilities

Component	Responsibility
Universal Sync extension	Collects solved problems in batches and captures newly accepted code as JSON.
React interface	Displays queues, filters, descriptions, code snapshots, forms, and progress.
FastAPI routes	Expose /api/v1 endpoints and translate HTTP requests into application operations.
Pydantic schemas	Validate required values, lengths, difficulty, problem URLs, and expected review stage.
Domain services	Normalize platform exports, deduplicate submissions, create snapshots, and apply revision rules.
SQLite access	Use parameterized queries, foreign keys, repeatable migrations, and write transactions.
Backup service	Export all five tables and restore with validation and parent ID remapping.

Data flow

The extension exports problem details and code to JSON. The user imports the file through AlgoFlow, then each submission is normalized into a common internal format. Valid records are stored together in a transaction. The backend returns counts of created, updated, skipped, and invalid records. The interface refreshes its library and statistics from the database after the operation.

Data preservation

The original tracker is backed up before its records are copied into the application. Migration preserves existing problem labels, review stages, dates, and topic history. Backup export and restoration provide a way to recover records without losing saved solution versions.

3 Database schema for problems and topics

SQLite stores five related tables. Integer primary keys identify records inside AlgoFlow; platform IDs and URL slugs identify external problems. JSON tags are stored as TEXT and decoded for API responses.

Problems table

Fields	SQLite type	Purpose
id	INTEGER primary key	Local problem identifier.
name difficulty link	TEXT	Display label, Easy/Medium/Hard classification, and reference URL.
date_added	TEXT	Original tracker addition date or administrative creation date.
stage status next_review_date	INTEGER and TEXT	Revision stage 0 to 4, pending/mastered state, and due date.
platform slug platform_id	TEXT	Platform identity and external metadata.
topic_tags company_tags	TEXT containing JSON	Topic and company labels.
problem_html	TEXT	Sanitized question description for local reading.
imported_at solved_at	TEXT nullable	Import timestamp; solve timestamp is left unavailable when absent.
historical_import	INTEGER	Distinguishes historical collection imports from manual additions for activity counting.
solve_state	TEXT	Accepted or unverified solution state.

Topics table

Fields	SQLite type	Purpose
id	INTEGER primary key	Local theory topic identifier.
name category notes link	TEXT	Concept name, grouping, personal explanation, and reference.
date_added	TEXT	Date the topic was added.
stage status next_review_date	INTEGER and TEXT	Theory revision progression and due date.

Identity and migration rules

Problems are matched by platform and canonical URL slug. Existing labels, IDs, stages, and dates are retained when an import enriches a tracker record. Schema upgrades add columns and tables rather than deleting the original records. The problems identity index supports lookup; ingestion serializes writes to prevent competing duplicate inserts.

4 Database schema for versions and reviews

Problem versions table

Fields	SQLite type	Purpose
id problem_id	INTEGER	Snapshot identifier and foreign key to problems.
version_number	INTEGER	Sequential number within one problem.
commit_message code language	TEXT	Explanation, exact submitted code, and programming language.
what_is_good what_is_bad	TEXT	Self-assessment of the approach and improvements.
time_complexity space_complexity	TEXT	Optional time and space complexity notes.
created_at accepted source	TEXT and INTEGER	Snapshot creation time, acceptance flag, and import/manual origin.
submission_id	TEXT nullable	External submission identity when available.
fingerprint delivery_key	TEXT	Code digest and repeat-delivery identity.

The database enforces unique (problem_id, version_number) and (problem_id, delivery_key) pairs. A foreign key associates every snapshot with a problem. There is no endpoint that edits a saved code snapshot.

Review history tables

Field	Type	Meaning
id	INTEGER primary key	Review event identifier.
problem_id or topic_id	INTEGER foreign key	Links to problems or topics respectively.
review_date	TEXT	Completion date in Asia/Kolkata.
stage_completed	INTEGER	Stage reached after completing the review.
was_on_time	INTEGER	1 when completed on its scheduled day, otherwise 0.

review_history belongs to problems; topic_review_history belongs to topics. One problem can have many versions and reviews. One theory topic can have many reviews. Versions and reviews are independent records, so saving code does not silently complete a review.

Consistency guarantees

Every connection enables foreign keys. Related writes run in a transaction using BEGIN IMMEDIATE. Unexpected database errors roll back the operation. Backup restoration validates parent references and remaps identifiers when the receiving database already contains different records.

5 Implementation details

Submission import

The normalizer accepts a single object or an array. LeetCode exports use userCode and problem_html; older GFG exports can use submission.code and problem_question. Names, platform identity, slugs, difficulty, code, language, and tag lists are validated. Ambiguous platform information is reported rather than guessed.

A supplied submission ID is used for duplicate detection. Without one, the backend hashes the language and exact code within the problem. Distinct submission IDs preserve separate submissions. Deliberate manual commits may keep identical code with a different assessment.

Review completion

State after action	Next review	Task
Added at stage 0	Tomorrow	First recall
Stage 1 completed	7 days later	Second recall
Stage 2 completed	30 days later	Re-solve
Stage 3 completed	180 days later	Long-term re-solve
Stage 4 completed	None	Mastered

A completion request includes expected_stage. The service checks that the item exists, is due, is not mastered, and still matches that stage. It logs the review and advances exactly one stage in the same transaction. A repeated or stale request receives a conflict response.

Forms and validation

React forms support problem entry, theory notes, solution versions, and file uploads. Required fields and URL controls provide browser feedback; Pydantic performs backend validation. Missing or invalid values produce a validation response. Saving a manual version does not establish platform acceptance.

Backend interfaces

The /api/v1 endpoints cover problems, due queues, topics, version lists and commits, explicit review completion, JSON ingestion, statistics, heatmaps, and backup export/restore. FastAPI provides interactive documentation at /docs. The interface and API use the same local origin.

Security and user management

Descriptions are sanitized with Bleach, problem links accept HTTP/HTTPS, and SQL values are parameterized. Uploads are limited to 25 MB and batches to 10,000 records. The server binds to loopback. This release has no authentication or multi-user isolation; it is intended for one local user.

6 Testing results and achieved outcome

The automated suite was rerun on 15 October 2026. All 13 tests passed in approximately 3 seconds. Tests use temporary databases. The real export and read-only tracker are used for integration checks when those files are available.

Test scenario	Verified behavior	Result
Real batch and repeat import	274 exact code snapshots; repeat import skips all records.	Pass
Original tracker migration	Original IDs, labels, dates, stages, and history retained.	Pass
GFG export variants	Nested and universal formats; distinct submission IDs retained.	Pass
Invalid records and HTML	Invalid JSON reported; executable HTML removed.	Pass
Review cycle and replay	7/30/180-day intervals; stale completion rejected.	Pass
Concurrent review requests	Exactly one request advances the stage.	Pass
Version persistence	Manual code survives restart without a review change.	Pass
Backup round trip	Versions and reviews restored with remapped parent IDs.	Pass
Invalid backup	Orphan references rejected without partial changes.	Pass
Import write failure	Simulated failure rolls back the entire valid import.	Pass
Manual entries and topics	Required values validated; future reviews rejected.	Pass
Identity and URL checks	Platform mismatch and unsafe manual link rejected.	Pass
Existing activity enrichment	Import enrichment preserves manual addition activity.	Pass

Browser verification


Browser checks confirmed search, imported descriptions and code, manual version saving, explicit due-review completion, repeat upload of the 274-record batch, a real GFG import, backup download and additive restore. Restarting the server preserved the saved version and completed review. The frontend TypeScript build passed.

Achieved outcome

AlgoFlow imports JSON files generated by the custom extension and organizes the problem details and submitted code in a searchable library. The dashboard shows due reviews and a summary of progress. The application schedules newly imported problems for revision and updates the next review date when a review is completed. Users can revisit saved solutions, record improved versions, and back up their data. This provides a clear workflow for collecting solutions and revising them regularly.

7 Dashboard and searchable library

The dashboard separates due reviews, accepted solutions, completed reviews, and streaks. The library distinguishes accepted and unverified records and provides filters for locating a stored solution. The screenshots show the working application in a browser.







Figure 2 Today dashboard with one due item and 274 accepted solutions; Figure 3 Library filtered to Valid Parentheses with difficulty platform and topic controls.

8 Problem description and saved code

Problem Detail provides an offline question reader and version selector. The accepted snapshot retains exact code from the export. Import dates are shown separately from solve dates, which remain unavailable when the export contains no solve timestamp.







Figure 4 Sanitized Valid Parentheses description and examples; Figure 5 Exact imported C++ code and its initial solution version.

9 Solution form and progress view

The version form accepts code, language, a commit message, self-assessment, and complexity notes. The progress view summarizes the collection and actual recorded activity. Historical batch imports do not create synthetic solve events or review activity.






Figure 6 Form for saving a manual version with message and assessment; Figure 7 Collection statistics and revision activity heatmap.

10 Conclusion and future scope

Conclusion

AlgoFlow addresses a problem I face during DSA practice: solved questions and saved code are easy to collect but difficult to revise regularly. The application brings problem descriptions, source code, personal notes, and review dates into one place. Earlier solutions remain available when a new version is saved, which makes it easier to compare my approach over time.

The custom Universal Sync extension supports the collection process by fetching solved problems in batches and capturing code after accepted submissions on LeetCode and GeeksforGeeks. These records are exported as JSON and imported into AlgoFlow. Together, the extension and application reduce the manual work needed to maintain a personal solution collection.

The application was checked using the 274-problem export and the existing tracker records. Testing confirmed duplicate protection, review progression, persistent solution versions, and backup restoration. The project meets its main objective of providing a practical workspace for organizing solutions and planning revision.

Current limitations

Data transfer from the extension to AlgoFlow currently requires importing a JSON file. The application does not run or judge saved code, and a manually saved version is not marked as accepted by a coding platform. It stores data locally and does not yet include user accounts or synchronization between devices. Historical records without solve timestamps are kept without assigning an invented solve date.

Future scope

- Connect the extension directly to AlgoFlow, with a retry queue for submissions that cannot be delivered immediately.
- Add a comparison view to highlight changes between saved solution versions.
- Support selected local code files so that practice drafts can be stored alongside accepted solutions.
- Add accounts and cloud synchronization if the application is extended for use across devices.

Project repositories

AlgoFlow application https://github.com/KRISH141006/AlgoFlow

DSA Universal Sync extension https://github.com/KRISH141006/dsa_universal_sync

The application repository contains the backend, frontend, database migration logic, and automated tests. The extension repository contains the browser scripts used for bulk collection and accepted-submission capture.