Summary | Programming Fundamentals

Introduction

Definitions

Algorithm

Finite sequence of well-defined instructions for solving a problem. Flowcharts or pseudocode can be used ot explain it.

Interpreter

A software that reads a source code file, goes through each line and runs the code.

Compiler

A software that reads a source code file, builds the software into a runnable version.

Interning

Interning is re-using objects of equal value on-demand instead of creating new objects. This is done for memory efficiency. Frequently used for numbers and strings in different programming languages.

```python
a = 120
b = 120

print(a is b) # True

c = 2000
d = 2000

print(c is d) # False
```

In the above code, `120` is intered by the Python interpreter but not `2000`. Python's integer interning is done only for numbers in the range: `[-5, 256]`

Python interpreter also interns small strings.

```python
a = "abcd"
b = "abcd"

print(a is b) # True

# Both text are the same
c = "Lorem ipsum dolor sit amet consectetur adipisicing elit. Consequuntur perferendis iste ipsa n
d = "Lorem ipsum dolor sit amet consectetur adipisicing elit. Consequuntur perferendis iste ipsa n

print(c is d) # False
```

Strings in python can be manually interned using `sys.intern` function.

```python
a,b=8,8
c=8
d=8
```

Likewise, in the above code, only 1 integer object is created.

Practice Resources

Programs

The programs are listed in no specific order.

1. **is prime number**: A program that takes in a number n and outputs whether its a [prime number](#) or not.

2. **factors**: Take in a number from user. Output all of its factors.

3. **n-th factorial**: A program that takes in a number n and outputs n-th [factorial](#).

4. **is perfect number**: A program that takes in a number n and outputs whether its a [perfect number](#).

5. **fibonacci numbers**: A program that takes in a number n and prints all [fibonacci numbers](#) less than or equal to n.

6. **determinant of matrix**: Take in a matrix from user. Output the determinant of the matrix. First try for 2×2. Then go higher-ordered matrices.

7. **pascal's triangle**: Take n from user input. Print [pascal's triangle](#) to n rows.

8. **is valid palindrome**: Take a string input from user. Output if the input is palindrome or not. A phrase is a palindrome if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers. Try not to use `[::-1]`.

9. **armstrong numbers**: Take n from user input. Print all armstrong numbers (in base 10, of course) between 0 and n (inclusive).

10. **letter analysis**: Take a text input from user. Find how many times each letter is being used in that string. Use a `dictionary` to store the data. Output the final results. Try to read the text from a `.txt` file as well.

11. **word length analysis**: Take a string input from user. Print length of each word separated by a space. Try to include the summary using a `dictionary`.

12. **letter expanding**: A program that converts *b3j8k2* to *bbbjjjjjjjjkk*. The number can be 1 to 99.

13. **binary addition**: Take in 2 numbers in binary (as strings) and output the sum of both numbers. Try not to use `bin` function.

14. **big integer addition**: Given *a very large integer* represented as a list, where each `digits[i]` is the i^{th} digit of the integer. The digits are ordered from most significant to least significant in left-to-right order. Increment the large integer by one and return the resulting array of digits. Don't construct a `int` object.

15. **stack implementation**

16. **queue implementation**

Platforms

- Codewars – https://codewars.com (my most preferred one)
- HackerRank – https://hackerrank.com
- Leetcode – https://leetcode.com (my least preferred one)

> ⚠️ **Hard Problems**
>
> If a problem from one of these platforms feels too hard for you, you can just skip and do another problem.