

METHOD OVERLOADING AND METHOD OVERRIDING

Aim:

To understand and implement method overloading and method overriding.

PRE LAB EXERCISE

QUESTIONS

- ✓ What is method overloading?

Method overloading is a concept in which multiple methods in the same class have the same method name but different parameter lists. The difference may be in the number, type, or order of parameters. It improves code readability and is resolved at compile time.

- ✓ What is method overriding?

Method overriding occurs when a subclass provides its own implementation of a method that is already defined in its parent class. The method signature must be the same in both classes. It supports runtime polymorphism and is resolved at runtime.

- ✓ Difference between overloading and overriding.

Method overloading occurs within the same class and involves methods with the same name but different parameters, whereas method overriding occurs between parent and child classes with the same method signature. Overloading is decided at compile time, while overriding is decided at runtime. Overloading does not require inheritance, but overriding always requires inheritance.

IN LAB EXERCISE

Objective:

To demonstrate compile-time and runtime polymorphism.

PROGRAMS:

1.Student Result System (Method Overriding)

Description:

- Base class Student has method displayResult().
- Subclasses UGStudent and PGStudent override the method to show different grading systems.

Code :

```
import java.util.Scanner;
```

```
// Base class
```

```
class Student {  
    String name;  
  
    void displayResult() {  
        System.out.println("Student Result");  
    }  
}
```

```
// UG Student subclass
```

```
class UGStudent extends Student {  
    int marks;  
  
    UGStudent(String n, int m) {  
        name = n;  
        marks = m;  
    }  
}
```

```
@Override
```

```
void displayResult() {  
    double percentage = (marks / 100.0) * 100;  
    System.out.println("UG Student: " + name);  
    System.out.println("Marks: " + marks);  
    System.out.println("Percentage: " + percentage + "%");  
}
```

```
}  
}
```

```
// PG Student subclass
```

```
class PGStudent extends Student {  
    double gpa;
```

```
    PGStudent(String n, double g) {  
        name = n;  
        gpa = g;  
    }  
}
```

```
@Override
```

```
void displayResult() {  
    System.out.println("PG Student: " + name);  
    System.out.println("GPA: " + gpa + " / 10");  
}  
}
```

```
// Main class
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
  
        // Input for UG student  
        System.out.print("Enter UG Student Name: ");  
        String ugName = sc.nextLine();  
        System.out.print("Enter UG Student Marks (out of 100): ");  
        int ugMarks = sc.nextInt();  
        sc.nextLine(); // consume newline
```

```

// Input for PG student
System.out.print("Enter PG Student Name: ");
String pgName = sc.nextLine();
System.out.print("Enter PG Student GPA (0-10): ");
double pgGpa = sc.nextDouble();

// Create objects
Student s1 = new UGStudent(ugName, ugMarks);
Student s2 = new PGStudent(pgName, pgGpa);

System.out.println("\n--- Student Results ---");
s1.displayResult();
System.out.println();
s2.displayResult();

sc.close();
}
}

```

OUTPUT:

Sample Input:

Enter UG Student Name: sanjula

Enter UG Student Marks (out of 100): 99

Enter PG Student Name: sanju

Enter PG Student GPA (0-10): 9

Output:

--- Student Results ---

UG Student: sanjula

Marks: 99

Percentage: 99.0%

PG Student: sanju

GPA: 9 / 10

```

[qwaesz@archlinux JAVA]$ cd /home/qwaesz/Documents/ST
rt=dt_socket,server=n,suspend=y,address=localhost:3630
ode\ -\ OSS\User\workspaceStorage\7135af0db7e650a731cc
Enter UG Student Name: sanjula
Enter UG Student Marks (out of 100): 99
Enter PG Student Name: sanju
Enter PG Student GPA (0-10): 9

--- Student Results ---
UG Student: sanjula
Marks: 99
Percentage: 99.0%

PG Student: sanju
GPA: 9.0 / 10
[qwaesz@archlinux JAVA]$

```

2. Calculator Program (Method Overloading)

Description:

Create a Calculator class with multiple add() methods to calculate:

- Addition of 2 integers
- Addition of 3 integers
- Addition of 2 double numbers

Code:

```

import java.util.Scanner;

class Calculator {

    int add(int a, int b) {
        return a + b;
    }

    int add(int a, int b, int c) {
        return a + b + c;
    }

    double add(double a, double b) {
        return a + b;
    }
}

```

```

}
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        Calculator calc = new Calculator();

        System.out.print("Enter two integers: ");
        int x = sc.nextInt();
        int y = sc.nextInt();
        System.out.println("Sum of two integers: " + calc.add(x, y));

        System.out.print("Enter three integers: ");
        int p = sc.nextInt();
        int q = sc.nextInt();
        int r = sc.nextInt();
        System.out.println("Sum of three integers: " + calc.add(p, q, r));

        System.out.print("Enter two decimal numbers: ");
        double a = sc.nextDouble();
        double b = sc.nextDouble();
        System.out.println("Sum of two doubles: " + calc.add(a, b));

        sc.close();
    }
}

```

Output:

Sample Input:

Enter two integers: 44 77

Enter three integers: 11 22 33

Enter two decimal numbers: 32 54

Output:

Sum of two integers: 121

Sum of three integers: 66

Sum of two doubles: 86.0

```
cd /home/user1/workspace/storage/7133a16a7e636a731e
Enter two integers: 44
77
Sum of two integers: 121
Enter three integers: 11
22
33
Sum of three integers: 66
Enter two decimal numbers: 32
54
Sum of two doubles: 86.0
[qwaesz@archlinux JAVA]$
```

POST LAB EXERCISE

- ✓ Is return type important in method overloading and method overriding?
In method overloading, the return type is not important because overloading depends on the parameter list, not on the return type. In method overriding, the return type must be the same or a compatible (covariant) return type to ensure proper runtime method execution.
- ✓ Can you overload a method by changing only the return type?
No, a method cannot be overloaded by changing only the return type. The parameter list must be different; otherwise, the compiler cannot distinguish between the methods.
- ✓ Can static methods be overridden? Can they be overloaded?
Static methods cannot be overridden because they belong to the class, not to the object. However, static methods can be overloaded by changing the parameter list.

- ✓ Can a method be overridden if the parameter list is different?

No, a method cannot be overridden if the parameter list is different. For overriding, the method name and parameter list must be exactly the same; otherwise, it is treated as method overloading.

Result:

Thus the method overloading and overriding concepts were implemented and executed successfully.

ASSESSMENT

Description	Max Marks	Marks Awarded
Pre Lab Exercise	5	
In Lab Exercise	10	
Post Lab Exercise	5	
Viva	10	
Total	30	
Faculty Signature		