


# CS 580: Algorithm Design and Analysis

---

# Finding the maximum


**Input:**



**Goal:** find the maximum element (or one of them if multiple ones exist) using comparison queries.

# Finding the maximum

Input:




**Goal:** find the maximum element (or one of them if multiple ones exist) using comparison queries.

**Q:** How many comparisons are needed?



# Finding the maximum

Input:



**Goal:** find the maximum element (or one of them if multiple ones exist) using comparison queries.


**Q:** How many comparisons are needed?



**A:** Depends on the number of **rounds** allowed.

# Algorithms in rounds

Algorithm that runs in  $k$  rounds can also be seen as: central machine issues in each round  $j$  a set of queries, one to each processor, then waits for the answers before issuing the next set of parallel queries in round  $j+1$ .



Query complexity in  $k$  rounds informs how many processors are needed to achieve a parallel time of  $k$ .


# Why rounds?

- Minimizing the number of rounds is important when computation is done by many (small) computers that interact over a network - e.g. phones, laptops
- Scenarios where rounds are expensive: crowdsourcing, blockchain

# Recall the comparison model

- An algorithm  $A$  in the comparison model gets input vector  $x$
- $A$  can do anything except open up the contents of the entries  $x_i$
- Algorithm  $A$  has access to an oracle  $O$  that, given any query  $x_i < x_j?$  can return True/False (i.e.,  $O$  does the work of inspecting the elements)

Is  larger than  ?



**NO**



# Algorithms with rounds

Input: vector  $x = (x_1, \dots, x_n)$

{Internal computation}

Submit set of queries  $S_1$  to  $O$ , then get back the answers

{Internal computation}

Submit set of queries  $S_2$  to  $O$ , then get back the answers

. . .

Submit set of queries  $S_k$  to  $O$ , then get back the answers


{Internal computation}

Output



# Finding the maximum

Input:




**Goal:** given input vector  $x$  and upper bound  $k$  on the allowed number of rounds of interaction, find the maximum element

- using as few comparisons as possible (count total)
- using at most  $k$  rounds of interaction with the oracle

**Question:** Given vector  $x = (x_1, \dots, x_n)$  and number  $k \in \{1, \dots, n\}$ , how many comparisons do we need to find the maximum of  $x$  in  $k$  rounds?

# Finding the maximum


Input:



Unlimited number of rounds (fully adaptive)?

# Finding the maximum

Input:




Unlimited number of rounds (fully adaptive):

- Upper bound:
- Lower bound:

# Finding the maximum

Input:




Unlimited number of rounds (fully adaptive):

- **Upper bound:** Go through each element and remember the max seen so far  $\Rightarrow n-1$  comparisons.
- **Lower bound:**

# Finding the maximum

Input:




Unlimited number of rounds (fully adaptive):

- **Upper bound:** Go through each element and remember the max seen so far  $\Rightarrow n-1$  comparisons.
- **Lower bound:** If an element is not compared to anything, then it could be the maximum. The comparisons give a graph on  $n$  elements that must be connected  $\Rightarrow$  need at least  $n-1$  comparisons.

# Finding the maximum

Input:




Unlimited number of rounds (fully adaptive):  $\Theta(n)$

- **Upper bound:** Go through each element and remember the max seen so far  $\Rightarrow n-1$  comparisons.
- **Lower bound:** If an element is not compared to anything, then it could be the maximum. The comparisons give a graph on  $n$  elements that must be connected  $\Rightarrow$  need at least  $n-1$  comparisons.



# Finding the maximum

Input:




$r = 1$  rounds: How many comparisons?



# Finding the maximum

Input:



$r = 1$  rounds:


Upper bound:

Lower bound:



# Finding the maximum

Input:




$r = 1$  rounds:

**Upper bound:** Ask for all pairwise comparisons  $\binom{n}{2}$  and output the maximum after receiving the answers.

**Lower bound:**

# Finding the maximum

Input:



**r = 1 rounds:**


**Upper bound:** Ask for all pairwise comparisons  $\binom{n}{2}$  and output the maximum after receiving the answers.

**Lower bound:** If even one comparison is missing, that can be enough to return the wrong maximum:

- Suppose there is a comparison missing between elements  $x_i$  and  $x_j$  in the input vector  $x$ .
- Then adversary can answer the queries so that  $x_i$  and  $x_j$  are greater than all the other elements  $\rightarrow$  not enough info to determine the max.

# Finding the maximum

Input:



**r = 1 rounds:**  $\Theta(n^2)$ .


**Upper bound:** Ask for all pairwise comparisons  $\binom{n}{2}$  and output the maximum after receiving the answers.

**Lower bound:** If even one comparison is missing, that can be enough to return the wrong maximum:

- Suppose there is a comparison missing between elements  $x_i$  and  $x_j$  in the input vector  $x$ .
- Then adversary can answer the queries so that  $x_i$  and  $x_j$  are greater than all the other elements  $\rightarrow$  not enough info to determine the max.

# Finding the maximum

Input:



$r = 2$  rounds: How many comparisons?






# Finding the maximum

$r = 2$  rounds. *Upper bound:*

# Finding the maximum

**r = 2 rounds.** *Upper bound:*





**Round 1.** Divide the items into  $k$  groups of size  $n/k$  and select the max from each group  $\Rightarrow \binom{n/k}{2}$  comparisons inside each group  $\Rightarrow$  at most  $k * \frac{n^2}{k^2}$  comparisons overall.



# Finding the maximum

$r = 2$  rounds. *Upper bound:*

**Round 1.** Divide the items into  $k$  groups of size  $n/k$  and select the max from each group  $\Rightarrow \binom{n/k}{2}$  comparisons inside each group  $\Rightarrow$  at most  $k * \frac{n^2}{k^2}$  comparisons overall.






# Finding the maximum

**r = 2 rounds.** *Upper bound:*

**Round 1.** Divide the items into  $k$  groups of size  $n/k$  and select the max from each group  $\Rightarrow \binom{n/k}{2}$  comparisons inside each group  $\Rightarrow$  at most  $k * \frac{n^2}{k^2}$  comparisons overall.

**Round 2.** Select the maximum among the group maxima  $\Rightarrow$  round 1 protocol for finding the max of  $k$  elements  $\Rightarrow k^2$  comparisons





# Finding the maximum

**r = 2 rounds. Upper bound:**

**Round 1.** Divide the items into  $k$  groups of size  $n/k$  and select the max from each group  $\Rightarrow \binom{n/k}{2}$  comparisons inside each group  $\Rightarrow$  at most  $k * \frac{n^2}{k^2}$  comparisons overall.

**Round 2.** Select the maximum among the group maxima  $\Rightarrow$  round 1 protocol for finding the max of  $k$  elements  $\Rightarrow k^2$  comparisons.

The total number of comparisons is at most  $k * \frac{n^2}{k^2} + k^2$ .

Set  $k$  to equalize the work for rounds 1 and 2:

$$k * \frac{n^2}{k^2} = k^2 \Rightarrow k = n^{2/3}.$$

Total number of comparisons is  $2 \cdot k^2 = 2 \cdot n^{4/3}$ .

# Finding the maximum

**r = 2 rounds.** **Upper bound:**  $O(n^{\frac{4}{3}})$

**Round 1.** Divide the items into  $k$  groups of size  $n/k$  and select the max from each group  $\Rightarrow \binom{n/k}{2}$  comparisons inside each group  $\Rightarrow$  at most  $k * \frac{n^2}{k^2}$  comparisons overall.

**Round 2.** Select the maximum among the group maxima  $\Rightarrow$  round 1 protocol for finding the max of  $k$  elements  $\Rightarrow k^2$  comparisons.

The total number of comparisons is at most  $k * \frac{n^2}{k^2} + k^2$ .


Set  $k$  to equalize the work for rounds 1 and 2:

$$k * \frac{n^2}{k^2} = k^2 \Rightarrow k = n^{2/3}.$$

Total number of comparisons is  $2 * k^2 = 2 * n^{4/3}$ .

## Finding the max: lower bound in 2 rounds


**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.



# Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.




# Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.

**Case 2:** Otherwise, suppose it has  $< n^{\frac{4}{3}}$  edges.



## Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.

**Case 2:** Otherwise, suppose it has  $< n^{\frac{4}{3}}$  edges.

**Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

## Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.

**Case 2:** Otherwise, suppose it has  $< n^{\frac{4}{3}}$  edges.

**Lemma 1:** A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .

- The graph has  $< n^{\frac{4}{3}}$  edges, by **Lemma 1**, it has an independent set  $U$  of size  $k$  such that

$$k \geq \frac{n^2}{8 * n^{\frac{4}{3}}} = \frac{n^{\frac{2}{3}}}{8} (*)$$

## Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.

**Case 2:** Otherwise, suppose it has  $< n^{\frac{4}{3}}$  edges.

**Lemma 1:** A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .

- The graph has  $< n^{\frac{4}{3}}$  edges, by **Lemma 1**, it has an independent set  $U$  of size  $k$  such that

$$k \geq \frac{n^2}{8 * n^{\frac{4}{3}}} = \frac{n^{\frac{2}{3}}}{8} (*)$$

- Make the items in  $U$  win all pairwise comparisons.



## Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.

**Case 2:** Otherwise, suppose it has  $< n^{\frac{4}{3}}$  edges.

**Lemma 1:** A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .

- The graph has  $< n^{\frac{4}{3}}$  edges, by **Lemma 1**, it has an independent set  $U$  of size  $k$  such that

$$k \geq \frac{n^2}{8 * n^{\frac{4}{3}}} = \frac{n^{\frac{2}{3}}}{8} (*)$$

- Make the items in  $U$  win all pairwise comparisons. These items must be compared in round 2  $\Rightarrow$  at least  $\binom{k}{2}$  comparisons in round 2.

## Finding the max: lower bound in 2 rounds

**Proof:** Consider graph on  $n$  vertices, one for each element. Draw an edge if a comparison query is asked b.w. those elements in round 1.

**Case 1:** If the graph has more than  $n^{\frac{4}{3}}$  edges, we are done.

**Case 2:** Otherwise, suppose it has  $< n^{\frac{4}{3}}$  edges.

**Lemma 1:** A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .

- The graph has  $< n^{\frac{4}{3}}$  edges, by **Lemma 1**, it has an independent set  $U$  of size  $k$  such that

$$k \geq \frac{n^2}{8 * n^{\frac{4}{3}}} = \frac{n^{\frac{2}{3}}}{8} (*)$$

- Make the items in  $U$  win all pairwise comparisons. These items must be compared in round 2  $\Rightarrow$  at least  $\binom{k}{2}$  comparisons in round 2.  
Since  $k \geq \frac{1}{8} * n^{\frac{2}{3}}$  by **(\*)**, round 2 makes  $\Omega(n^{\frac{4}{3}})$  comparisons.

## Finding the max: lower bound in 2 rounds

Proof of Lemma 1: *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

Thus: the **average** degree is  $\leq \frac{2 \cdot s}{n}$ . ★

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

Thus: the **average** degree is  $\leq \frac{2 \cdot s}{n}$ . ★

Then not that many nodes can exceed this value by a lot.

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

Thus: the **average** degree is  $\leq \frac{2 \cdot s}{n}$ . ★

**Then not that many nodes can exceed this value by a lot.**

Let  $q$  be the number of nodes with degree  $\geq 4 \cdot \frac{s}{n}$ .

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

Thus: the **average** degree is  $\leq \frac{2 \cdot s}{n}$ . ★

**Then not that many nodes can exceed this value by a lot.**

Let  $q$  be the number of nodes with degree  $\geq 4 \cdot \frac{s}{n}$ .

Upper bounding the sum of degrees of the  $q$  nodes by the upper bound on the sum of degrees, we get

$$q \cdot \left(4 \cdot \frac{s}{n}\right) \leq 2 \cdot s \Rightarrow q \leq \frac{n}{2}$$



## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

Thus: the **average** degree is  $\leq \frac{2 \cdot s}{n}$ . ★

**Then not that many nodes can exceed this value by a lot.**

Let  $q$  be the number of nodes with degree  $\geq 4 \cdot \frac{s}{n}$ .

Upper bounding the sum of degrees of the  $q$  nodes by the upper bound on the sum of degrees, we get

$$q \cdot \left(4 \cdot \frac{s}{n}\right) \leq 2 \cdot s \Rightarrow q \leq \frac{n}{2}$$

Let  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ .

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

Since the number of edges is  $\leq s \Rightarrow$  the sum of degrees is  $\leq 2 \cdot s$ .

Thus: the **average** degree is  $\leq \frac{2 \cdot s}{n}$ . ★

**Then not that many nodes can exceed this value by a lot.**

Let  $q$  be the number of nodes with degree  $\geq 4 \cdot \frac{s}{n}$ .

Upper bounding the sum of degrees of the  $q$  nodes by the upper bound on the sum of degrees, we get

$$q \cdot \left(4 \cdot \frac{s}{n}\right) \leq 2 \cdot s \Rightarrow q \leq \frac{n}{2}$$

Let  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ . We get  $|W| \geq \frac{n}{2}$ .

## Finding the max: lower bound in 2 rounds

Proof of Lemma 1 (cont): *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

**Recap:**  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ . Also  $|W| \geq \frac{n}{2}$ .

**Select independent set from  $W$  greedily:** select a node, eliminate all its neighbours, repeat.

What is an upper bound on how many nodes each removal eliminates?

## Finding the max: lower bound in 2 rounds

Proof of Lemma 1 (cont): *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

**Recap:**  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ . Also  $|W| \geq \frac{n}{2}$ .

**Select independent set from  $W$  greedily:** select a node, eliminate all its neighbours, repeat.

Each removal eliminates  $\leq 4 \cdot \frac{s}{n}$  vertices, but  $W$  has at least  $\frac{n}{2}$  nodes

## Finding the max: lower bound in 2 rounds

Proof of Lemma 1 (cont): *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

**Recap:**  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ . Also  $|W| \geq \frac{n}{2}$ .

**Select independent set from  $W$  greedily:** select a node, eliminate all its neighbours, repeat.

Each removal eliminates  $\leq 4 \cdot \frac{s}{n}$  vertices, but  $W$  has at least  $\frac{n}{2}$  nodes

=> the number of iterations is at least...?



## Finding the max: lower bound in 2 rounds

Proof of Lemma 1 (cont): *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

**Recap:**  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ . Also  $|W| \geq \frac{n}{2}$ .

**Select independent set from  $W$  greedily:** select a node, eliminate all its neighbours, repeat.

Each removal eliminates  $\leq 4 \cdot \frac{s}{n}$  vertices, but  $W$  has at least  $\frac{n}{2}$  nodes

=> the number of iterations is at least:

$$\frac{|W|}{\text{max \# vertices removed per round}} = \frac{n/2}{4 \cdot \frac{s}{n}} = \frac{n^2}{8s}.$$

## Finding the max: lower bound in 2 rounds

**Proof of Lemma 1 (cont):** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*

**Recap:**  $W$  = set of nodes with degree  $\leq 4 \cdot \frac{s}{n}$ . Also  $|W| \geq \frac{n}{2}$ .

**Select independent set from  $W$  greedily:** select a node, eliminate all its neighbours, repeat.

Each removal eliminates  $\leq 4 \cdot \frac{s}{n}$  vertices, but  $W$  has at least  $\frac{n}{2}$  nodes

$\Rightarrow$  the number of iterations is at least:

$$\frac{|W|}{\text{max \# vertices removed per round}} = \frac{n/2}{4 \cdot \frac{s}{n}} = \frac{n^2}{8s}.$$

Thus the graph has an independent set of size at least  $\frac{n^2}{8s}$ . This completes the proof of the lemma.

# Finding the maximum in 3 rounds

Exercise.



# Finding the maximum in 3 rounds

## Upper bound:

- Divide the elements into groups of  $k$  [TBD] and find the maximum element in each group

# Finding the maximum in 3 rounds

## Upper bound:

- Divide the elements into groups of  $k$  [TBD] and find the maximum element in each group  $\rightarrow$  in round 1 can obtain the maximum  $y_i$  for each group  $i$ . We get  $k * \frac{n^2}{k^2} = \frac{n^2}{k}$  comparisons in round 1.

# Finding the maximum in 3 rounds

## Upper bound:

- Divide the elements into groups of  $k$  [TBD] and find the maximum element in each group  $\rightarrow$  in round 1 can obtain the maximum  $y_i$  for each group  $i$ . We get  $k * \frac{n^2}{k^2} = \frac{n^2}{k}$  comparisons in round 1.
- By 2 round protocol, the maximum of the  $y_i$ 's can be obtained using  $2 \cdot k^{\frac{4}{3}}$  comparisons in the remaining two rounds.

# Finding the maximum in 3 rounds

## Upper bound:

- Divide the elements into groups of  $k$  [TBD] and find the maximum element in each group  $\rightarrow$  in round 1 can obtain the maximum  $y_i$  for each group  $i$ . We get  $k * \frac{n^2}{k^2} = \frac{n^2}{k}$  comparisons in round 1.
- By 2 round protocol, the maximum of the  $y_i$ 's can be obtained using  $2 \cdot k^{\frac{4}{3}}$  comparisons in the remaining two rounds.
- The total number of comparisons is  $\leq \frac{n^2}{k} + 2 \cdot k^{\frac{4}{3}}$ .

# Finding the maximum in 3 rounds

## Upper bound:

- Divide the elements into groups of  $k$  [TBD] and find the maximum element in each group  $\rightarrow$  in round 1 can obtain the maximum  $y_i$  for each group  $i$ . We get  $k * \frac{n^2}{k^2} = \frac{n^2}{k}$  comparisons in round 1.
- By 2 round protocol, the maximum of the  $y_i$ 's can be obtained using  $2 \cdot k^{\frac{4}{3}}$  comparisons in the remaining two rounds.
- The total number of comparisons is  $\leq \frac{n^2}{k} + 2 \cdot k^{\frac{4}{3}}$ .
- By setting  $k = n^{\frac{6}{7}}$ , we get at most  $\frac{n^2}{k} + k^{\frac{4}{3}} = 3 \cdot n^{\frac{8}{7}} \in O(n^{\frac{8}{7}})$  comparisons.

# Finding the maximum in 3 rounds

Lower bound:

# Finding the maximum in 3 rounds

## Lower bound:

- Use same technique as for  $r=2$  rounds: assume the first round uses at most  $k$  comparisons (if it uses less we are done).

# Finding the maximum in 3 rounds

## Lower bound:

- Use same technique as for  $r=2$  rounds: assume the first round uses at most  $k$  comparisons (if it uses less we are done).
- Find large independent set  $S$  (By Lemma 1, can find of size  $\geq \frac{n^2}{8 \cdot k}$  )

**Recall Lemma 1:** *A graph with  $n$  nodes and fewer than  $s$  edges has an independent set of size at least  $\frac{n^2}{8s}$ .*



# Finding the maximum in 3 rounds

## Lower bound:

- Use same technique as for  $r=2$  rounds: assume the first round uses at most  $k$  comparisons (if it uses less we are done).
- Find large independent set  $S$  (By Lemma 1, can find of size  $\geq \frac{n^2}{8 \cdot k}$  )
- By applying the lower bound for  $r=2$  rounds, it follows we need at least  $\left(\frac{n^2}{8k}\right)^{4/3}$  comparisons to find the max in  $S$  in 2 rounds.

# Finding the maximum in 3 rounds

## Lower bound:

- Use same technique as for  $r=2$  rounds: assume the first round uses at most  $k$  comparisons (if it uses less we are done).
- Find large independent set  $S$  (By Lemma 1, can find of size  $\geq \frac{n^2}{8 \cdot k}$  )
- By applying the lower bound for  $r=2$  rounds, it follows we need at least  $\left(\frac{n^2}{8k}\right)^{4/3}$  comparisons to find the max in  $S$  in 2 rounds.
- Thus any 3 round protocol uses either  $\geq k$  comparisons in the first round or  $\geq \left(\frac{n^2}{8k}\right)^{4/3}$  in the next 2 rounds.

# Finding the maximum in 3 rounds

## Lower bound:

- Use same technique as for  $r=2$  rounds: assume the first round uses at most  $k$  comparisons (if it uses less we are done).
- Find large independent set  $S$  (By Lemma 1, can find of size  $\geq \frac{n^2}{8 \cdot k}$ )
- By applying the lower bound for  $r=2$  rounds, it follows we need at least  $\left(\frac{n^2}{8k}\right)^{4/3}$  comparisons to find the max in  $S$  in 2 rounds.
- Thus any 3 round protocol uses either  $\geq k$  comparisons in the first round or  $\geq \left(\frac{n^2}{8k}\right)^{4/3}$  in the next 2 rounds.
- By setting  $k = n^{8/7}$ , we get a lower bound of  $\Omega(n^{8/7})$ .