KSP FULFILLMENT

Client API Integration Guide

connect.ksp3plhq.com — Gateway API v1

Revised October 15, 2026

KSP 3PL — API Integration Guide

Overview

KSP provides a secure API gateway for submitting and tracking orders, querying inventory, and managing purchase orders within our WMS (Warehouse Management System).

All API access goes through our gateway at `https://connect.ksp3plhq.com`. You will be provided with an API key for authentication. You do **not** need WMS credentials, client identifiers, or warehouse identifiers — the gateway handles all of that on your behalf.

Authentication

Every request requires your API key in the `X-API-Key` header:

```
X-API-Key: your-api-key-here
Content-Type: application/json
```

Your API key will be provided during onboarding. Keep it secure — it grants full access to your account's endpoints.

Base URL

```
https://connect.ksp3plhq.com
```

Rate Limits

Each API key has a configurable rate limit (default: 60 requests/minute). Rate limit status is returned in response headers:

```
X-RateLimit-Limit: 60
X-RateLimit-Remaining: 58
X-RateLimit-Reset: 60
```

If you exceed the limit, you'll receive a `429 Too Many Requests` response with a `Retry-After` header indicating how many seconds to wait before retrying.

Available Endpoints

Method	Endpoint	Description
POST	`/v1/orders`	Submit a single order
POST	`/v1/orders/bulk`	Submit up to 50 orders at once
GET	`/v1/orders`	List orders (paginated, filterable)
GET	`/v1/orders/{orderId}`	Get full order details
GET	`/v1/orders/{orderId}/tracking`	Get tracking information
GET	`/v1/inventory`	List all inventory (paginated, filterable)
GET	`/v1/inventory/availability`	Available-to-promise (sellable) per SKU
POST	`/v1/inventory/query`	Query inventory by specific SKU(s)
GET	`/v1/products`	List products/SKUs (paginated, filterable)
POST	`/v1/products`	Create a new product/SKU
POST	`/v1/purchase-orders`	Submit a purchase order
GET	`/v1/purchase-orders`	List purchase orders (paginated, filterable)
GET	`/v1/purchase-orders/{id}`	Get purchase order details
GET	`/v1/purchase-orders/{code}/receipts`	Get PO receiving history
GET	`/v1/health`	Health check (no auth required)

---

1. Submit a Single Order

```
POST /v1/orders
```

Submit a shipment order. The gateway automatically assigns the correct client, warehouse, and order type — you just provide the order details.

Example Payload

```
{
  "code": "77671",
  "customer": {
    "firstName": "Jane",
    "lastName": "Doe",
    "email": "jane@example.com"
  },
  "companyName": "Acme Corp",
  "shipmentAddress": {
    "country": "US",
    "state": "New Mexico",
    "addressLine1": "4 Sherry Lane",
    "addressLine2": "",
    "city": "Peralta",
    "postalCode": "87042",
    "phoneNumber": "505-555-0100"
  },
  "useSameAddress": true,
  "clientReferenceCode": "PO-8834",
  "note": "Deliver to loading dock B",
  "shipmentOrderLineList": [
    {
      "sku": "9415995",
      "packType": "Unit",
      "packQuantity": 1,
      "unitPrice": 29.99
    },
    {
      "sku": "D802N",
      "packType": "Unit",
      "packQuantity": 1,
      "unitPrice": 45.00
    },
    {
      "sku": "9415994",
      "packType": "Unit",
      "packQuantity": 2,
      "unitPrice": 12.50
    }
  ]
}
```

Required Fields

Field	Description
`code`	Your unique order number (must be unique per order)
`shipmentOrderLineList`	Array of line items (at minimum `sku` and `packQuantity`)

Complete Field Reference — Order

The full schema is available. Only `code` and `shipmentOrderLineList` are required — include any other fields you have data for, omit the rest.

Field	Type	Description
`code`	string	**Required.** Your unique order number
`customer.firstName`	string	Customer first name
`customer.lastName`	string	Customer last name
`customer.email`	string	Customer email
`companyName`	string	Company name
`carrierReasonForExport`	string	Reason for export (international orders)
`shipmentAddress.type`	string	Address type (e.g. "Residential", "Commercial")
`shipmentAddress.country`	string	Country code (e.g. "US")
`shipmentAddress.state`	string	State name or abbreviation
`shipmentAddress.addressLine1`	string	Street address
`shipmentAddress.addressLine2`	string	Suite, unit, etc.
`shipmentAddress.city`	string	City
`shipmentAddress.postalCode`	string	ZIP/postal code
`shipmentAddress.phoneNumber`	string	Phone number
`billingAddress.type`	string	Address type
`billingAddress.country`	string	Country code
`billingAddress.state`	string	State
`billingAddress.addressLine1`	string	Street address
`billingAddress.addressLine2`	string	Suite, unit, etc.
`billingAddress.city`	string	City
`billingAddress.postalCode`	string	ZIP/postal code
`billingAddress.phoneNumber`	string	Phone number
`billingAddress.firstName`	string	Billing first name
`billingAddress.lastName`	string	Billing last name

Field	Type	Description
`billingAddress.email`	string	Billing email
`billingAddress.companyName`	string	Billing company name
`useSameAddress`	boolean	Use shipping as billing (default: `true`)
`shipmentOrderDate`	string	Order date, ISO format (default: today)
`expectedShipmentDate`	string	Requested ship date
`expectedDeliveryDate`	string	Requested delivery date
`clientReferenceCode`	string	Your internal reference/PO number
`discount`	number	Order-level discount
`note`	string	Order notes
`extraNote1`	string	Additional note field 1
`extraNote2`	string	Additional note field 2
`extraNote3`	string	Additional note field 3
`extraNote4`	string	Additional note field 4
`extraNote5`	string	Additional note field 5
`giftNote`	string	Gift message
`fraud`	string	Fraud check flag
`isSkipAddressVerification`	boolean	Skip address validation (default: `false`)
`gift`	boolean	Gift order flag
`currencyId`	integer	Currency ID
`isPrimeOrder`	boolean	Priority/Prime order flag
`tags`	array	Array of tag identifier GUIDs
`scheduledPickupDate`	string	Scheduled pickup date
`actualPickupDate`	string	Actual pickup date
`carrierId`	integer	Carrier ID
`carrierSetupIdentifier`	string	Carrier setup GUID
`shippingOptionIdentifier`	string	Shipping option GUID
`internationalChargedAccountNumber`	string	International billing account

Field	Type	Description
`internationalChargedAccountCountryCode`	string	International billing country
`internationalChargedAccountPostalCode`	string	International billing postal code
`carrierBillingTypeId`	integer	Carrier billing type ID
`carrierBillingTypeName`	string	Carrier billing type (e.g. "Prepaid")
`carrierIntBillingTypeId`	integer	International carrier billing type ID
`carrierIntBillingTypeName`	string	International carrier billing type name
`chargedAccountNumber`	string	Domestic billing account number
`chargedAccountCountryCode`	string	Domestic billing country
`chargedAccountPostalCode`	string	Domestic billing postal code
`packingInstructions`	string	Special packing instructions
`currentTrackingNumber`	string	Pre-assigned tracking number
`trackingNumbers`	array	Array of tracking number strings
`totalShippingCost`	number	Total shipping cost
`carrierPackageIdentifier`	string	Carrier package type GUID
`carrierPackageName`	string	Carrier package type name
`isAllowSaturdayDelivery`	boolean	Allow Saturday delivery
`priority`	integer	Order priority
`customFieldDateTime1`	string	Custom date field 1
`customFieldDateTime2`	string	Custom date field 2
`customFieldDateTime3`	string	Custom date field 3
`customFieldToggle1`	boolean	Custom toggle field 1
`customFieldToggle2`	boolean	Custom toggle field 2
`customFieldDropDown1`	string	Custom dropdown field 1
`customFieldDropDown2`	string	Custom dropdown field 2
`customFieldTextBox1`	string	Custom text field 1
`customFieldTextBox2`	string	Custom text field 2
`customFieldTextBox3`	string	Custom text field 3

Field	Type	Description
`channelOrderNumber`	string	Your channel/marketplace order number
`channelSetupIdentifier`	string	Channel setup GUID
`isManualChargedAccount`	boolean	Manual domestic billing account flag
`isManualIntChargedAccount`	boolean	Manual international billing account flag
`packingWarningTypeIdentifier`	string	Packing warning type GUID
`packingWarningTypeName`	string	Packing warning type name

Shipping Option Details (nested object)

Field	Type	Description
`shippingOptionDetails.shippingOptionName`	string	Shipping method name (e.g. "Ground")
`shippingOptionDetails.carrierName`	string	Carrier name (e.g. "UPS")
`shippingOptionDetails.carrierSetupName`	string	Carrier setup name (e.g. "UPS Standard")
`shippingOptionDetails.isSetUnmatchedShippingOptionAsRequested`	boolean	If `true`, unmatched methods are recorded as requested

> **Per-account carrier mapping:** KSP can configure a translation table for your account so the carrier setup names you already use (e.g. `"Cheapest"`) are automatically mapped to the correct KSP rate-shop or carrier configuration. If your shipping method names don't match KSP's, ask us to set up a mapping instead of changing your export.

Return Shipping Details (nested object)

Field	Type	Description
`returnShippingOptionDetails.returnCarrierId`	integer	Return carrier ID
`returnShippingOptionDetails.returnCarrierName`	string	Return carrier name
`returnShippingOptionDetails.returnShippingOptionIdentifier`	string	Return shipping option GUID
`returnShippingOptionDetails.returnShippingOptionName`	string	Return shipping option name
`returnShippingOptionDetails.returnCarrierSetupIdentifier`	string	Return carrier setup GUID
`returnShippingOptionDetails.returnCarrierSetupName`	string	Return carrier setup name

Field	Type	Description
`returnShippingOptionDetails.returnCost`	number	Return shipping cost
`returnShippingOptionDetails.returnTrackingNumbers`	array	Array of return tracking numbers
`returnShippingOptionDetails.returnAddressName`	string	Return address name

Tax Details (array of objects)

Field	Type	Description
`taxDetails[].taxId`	string	Tax identifier
`taxDetails[].taxTypeName`	string	Tax type name

Retailer Details (nested object)

Field	Type	Description
`retailerDetails.retailerIdentifier`	string	Retailer GUID
`retailerDetails.pro`	string	PRO number
`retailerDetails.bol`	string	Bill of lading
`retailerDetails.po`	string	Retailer PO number
`retailerDetails.dept`	string	Department
`retailerDetails.markFor`	string	Mark for
`retailerDetails.retailerCustomerAccountNumber`	string	Retailer customer account

> `retailerIdentifier` **must be a KSP retailer GUID.** If your system only has your own retailer/customer numbers, KSP can configure a per-account mapping that translates them to the correct GUID automatically (this is what drives retailer-specific packing slips). Unmapped values are safely preserved in `retailerCustomerAccountNumber` rather than rejecting the order.

Complete Line Item Field Reference

Field	Type	Required	Description
`sku`	string	**Yes**	Product SKU (must exist in the system)
`packQuantity`	integer	**Yes**	Quantity to ship
`packType`	string	No	Pack type (e.g. "Unit", "Case") — uses product default if omitted

Field	Type	Required	Description
`unitPrice`	number	No	Unit price
`unitTax`	number	No	Tax per unit
`unitDiscount`	number	No	Discount per unit
`taxIncluded`	boolean	No	Whether unitPrice includes tax
`lotBatchNumber`	string	No	Lot/batch number
`expiryDate`	string	No	Product expiry date
`productionDate`	string	No	Product production date
`warehouseLocationCode`	string	No	Specific warehouse location
`licensePlate`	string	No	License plate number
`damageReason`	string	No	Damage reason
`customFieldDateTime1`	string	No	Custom date field 1
`customFieldDateTime2`	string	No	Custom date field 2
`customFieldDateTime3`	string	No	Custom date field 3
`customFieldToggle1`	boolean	No	Custom toggle 1
`customFieldToggle2`	boolean	No	Custom toggle 2
`customFieldDropDown1`	string	No	Custom dropdown 1
`customFieldDropDown2`	string	No	Custom dropdown 2
`customFieldTextBox1`	string	No	Custom text 1
`customFieldTextBox2`	string	No	Custom text 2
`customFieldTextBox3`	string	No	Custom text 3
`lineNotes1`	string	No	Line notes 1
`lineNotes2`	string	No	Line notes 2
`lineNotes3`	string	No	Line notes 3

Note: Available carriers and shipping methods depend on your account configuration. Contact your KSP account representative for a list of carriers and methods available for your account.

Example Response

```
{
  "orderId": "e30faaa3-c510-4df7-9506-996a40be2bd9",
  "code": "77671",
  "logiwaOrderId": "d53e3316-3788-4f8b-93c8-97901f579da2",
  "status": "sent",
  "message": "Order created and sent to Logiwa"
}
```

Fields You Do NOT Need to Send

The gateway automatically handles these — do not include them in your payload:

Field	Why
`clientIdentifier`	Assigned by the gateway based on your API key
`warehouseIdentifier`	Assigned by the gateway
`shipmentOrderType`	Defaults to "Shipment Order"
`channelName`	Set automatically to identify orders from the API

Important Notes

- **Order codes must be unique.** Submitting a duplicate code will return an error.
- **SKUs must exist in the system.** Contact KSP to have products set up before sending orders.
- **Only include fields you have data for.** Do not send fields with empty strings or placeholder values — omit them entirely.

---

2. Submit Bulk Orders

```
POST /v1/orders/bulk
```

Submit up to 50 orders in a single request. Same payload structure as single orders, wrapped in an array. Bulk orders are processed asynchronously.

Example Payload

```
[
  {
    "code": "ORD-001",
    "customer": { "firstName": "John", "lastName": "Doe" },
    "shipmentAddress": {
      "country": "US",
      "state": "IL",
      "addressLine1": "123 Main St",
      "city": "Chicago",
      "postalCode": "60601"
    },
    "shipmentOrderLineList": [
      { "sku": "9415995", "packType": "Unit", "packQuantity": 2 }
    ]
  },
  {
    "code": "ORD-002",
    "customer": { "firstName": "Jane", "lastName": "Smith" },
    "shipmentAddress": {
      "country": "US",
      "state": "TX",
      "addressLine1": "456 Oak Ave",
      "city": "Dallas",
      "postalCode": "75201"
    },
    "shipmentOrderLineList": [
      { "sku": "D802N", "packType": "Unit", "packQuantity": 1 }
    ]
  }
]
```

Example Response

```
{
  "bulkId": "b53e6d25-5eae-4304-b754-bfe81419904f",
  "count": 2,
  "results": {
    "requestId": "dc3882a9-28c9-475a-a51d-c372696e2709"
  },
  "message": "Bulk order submission complete"
}
```

Bulk orders are processed asynchronously. The `requestId` confirms acceptance.

How to Check Bulk Results

You do **not** need to set up webhooks — the gateway handles that. To check if your bulk orders were processed:

1. **List your orders** using `GET /v1/orders` and filter by date or code to find the orders you submitted
2. **Check individual order status** using `GET /v1/orders/{orderId}` for any specific order
3. Any orders that failed validation will appear with error details in the list response

Limits

- Maximum **50 orders** per bulk request
- Subject to the standard per-key rate limit (default 60 requests/minute)

---

3. List Orders

```
GET /v1/orders?page=1&size=50
```

List your orders with pagination and filtering. Results are automatically scoped to your account — you will only see your own orders.

Query Parameters

Parameter	Default	Description
`page`	0	Page index (starts at 0)
`size`	50	Results per page

Filtering

Filter with `Key.operator=value` query parameters. **Never pull the full order list on a schedule — filter by date.** The two patterns most integrations need:

```
# Orders created in a date range
GET /v1/orders?CreatedDateTime.bt=2026-10-01,2026-10-15

# Orders CHANGED since a date (new, shipped, cancelled — anything updated):
# poll this with your last sync time to pick up all changes incrementally
GET /v1/orders?UpdatedDateTime.bt=2026-10-14,2026-10-16
```

Supported filter keys:

Key	Type	Operators
`Code`	string	`eq`
`Identifier`	guid	`eq`
`Sku`	string	`eq`
`UpdatedDateTime`	date	`bt`
`CreatedDateTime`	date	`bt`
`ShipmentOrderDate`	date	`bt`
`ExpectedShipmentDate`	date	`bt`
`ActualShipmentDate`	date	`bt`
`Status`	numeric	`eq` , `in`
`ChannelOrderNumber`	string	`eq`
`ShipmentOrderTypeName`	string	`eq`
`PO`	string	`eq` , `in`
`CustomFieldTextBox1-3`	string	`eq` , `in`
`CustomFieldDateTime1-3`	date	`bt`
`CustomFieldToggle1-2`	bool	`eq`
`CustomFieldDropDown1-2`	string	`eq` , `in`

Operator syntax: `eq` (equals), `in` (comma-separated list), `bt` (between — two dates separated by a comma, inclusive). More examples:

```
GET /v1/orders?Code.eq=ORD-001
GET /v1/orders?Status.in=5,20
GET /v1/orders?ActualShipmentDate.bt=2026-03-01,2026-03-31&page=1&size=100
```

`ClientIdentifier` and `WarehouseIdentifier` are controlled by the gateway and ignored if supplied — results are always scoped to your account only.

Example Response

Returns the full Logiwa order list response including order details, statuses, tracking numbers, etc.

---

4. Get Order Details

```
GET /v1/orders/{orderId}
```

Retrieve full order details. You can pass either the gateway `orderId` returned when the order was submitted, or the `logiwaOrderId`. Returns the complete Logiwa order record including status, tracking, shipping details, and all fields.

Example Response

Returns the full Logiwa order record with all fields including:

- Order code, status, dates
- Customer and address details
- Line items with SKUs and quantities
- Tracking numbers, carrier info
- All custom fields

If the Logiwa system is temporarily unavailable, falls back to cached gateway status.

Order Statuses (Gateway)

Status	Meaning
`received`	Order received by gateway, pending submission
`sent`	Successfully submitted to the warehouse
`fulfilled`	Order has been shipped
`closed`	Order completed or cancelled
`error`	Submission failed (see error message for details)

---

5. Get Tracking Information

```
GET /v1/orders/{orderId}/tracking
```

Retrieve tracking details for a shipped order. You can pass any of: the gateway `orderId` returned when the order was submitted, the `logiwaOrderId`, or your own `code` (external order id).

Example Response


```
{
  "orderId": "e30faaa3-c510-4df7-9506-996a40be2bd9",
  "status": "fulfilled",
  "tracking": {
    "logiwaStatus": "Shipped",
    "shipmentDate": "2026-03-22T14:30:00Z",
    "trackingNumbers": ["1Z999AA10123456784"],
    "carrier": "UPS",
    "shippingCost": 12.50
  },
  "carrier": "UPS",
  "trackingNumber": "1Z999AA10123456784",
  "estimatedDelivery": "2026-03-25T00:00:00Z",
  "shipments": [
    {
      "items": [
        {
          "sku": "881508",
          "name": "Pressure Gauge",
          "packType": "Unit",
          "quantity": 1,
          "expiryDate": null,
          "lotBatchNumber": null
        }
      ],
      "carrier": "Usps",
      "packageType": "6x6x4",
      "shipmentDate": "2026-04-15T15:36:16.147Z",
      "packageWeight": 0.5,
      "trackingNumber": "9400136206249357431403",
      "shippingService": "KSPEhub-USPS Ground Advantage",
      "packageWeightUnit": "Pound"
    }
  ]
}
```


Tracking information is updated periodically. If the order hasn't shipped yet, `tracking` will be `null` and `shipments` will be an empty array. Orders that ship in multiple packages produce one entry per package in `shipments`, each with its own tracking number and item list.

---

6. List All Inventory

```
GET /v1/inventory?page=1&size=200
```

Page through all inventory for your account. Results are automatically scoped to your account — you will only see your own inventory.

This is useful for syncing your full inventory with your own system. You can page through all SKUs at the warehouse, not just specific ones.

Query Parameters

Parameter	Default	Description
`page`	0	Page index (starts at 0)
`size`	200	Results per page (max 200)

LQL Filtering

```
GET /v1/inventory?page=1&size=200&Sku.eq=WIDGET-100
GET /v1/inventory?page=1&size=200&WarehouseIdentifier.eq={uuid}
```

Example Response

Returns the full Logiwa inventory list including:

- `productSku`, `productName`
- `availableQuantity`, `totalQuantity`, `allocatedQuantity`, `freeQuantity`
- `warehouseCode`, `warehouseLocationCode`
- `lotBatchNumber`, `expiryDate`
- `inventoryStatusName`

Page through by incrementing `page` until you get fewer results than `size`.

---

7. Query Inventory by SKU

```
POST /v1/inventory/query
```

Check available inventory for one or more SKUs.

Example Payload

```
{
  "skus": ["9415995", "D802N", "9415994"]
}
```

Example Response

```
{
  "items": [
    { "sku": "9415995", "quantity": 150, "lastSyncedAt": "2026-03-20T18:00:00Z" },
    { "sku": "D802N", "quantity": 42, "lastSyncedAt": "2026-03-20T18:00:00Z" },
    { "sku": "9415994", "quantity": null, "lastSyncedAt": null }
  ]
}
```

A `null` quantity means the SKU was not found in inventory. Query up to 100 SKUs per request.

Inventory Availability (Sellable / ATP)

```
GET /v1/inventory/availability?page=1&size=100
```

Returns per-SKU **available-to-promise** — the true *sellable* quantity after accounting for **all** order commitments (including backordered/unallocated demand), not just pickable stock. Use this to answer "what can I sell right now," versus `GET /v1/inventory` which shows physical stock by location. Results are scoped to your account.

Query Parameters

Parameter	Default	Description
`page`	0	Page index (starts at 0)
`size`	100	Results per page

LQL Filtering

```
GET /v1/inventory/availability?Sku.eq=431
GET /v1/inventory/availability?InventoryATPQuantity.gt=0
```

Example Response


```
{
  "data": [
    {
      "productSku": "431",
      "productName": "Widget 431",
      "warehouseCode": "MAIN",
      "onHandQuantity": 12,
      "pickableQuantity": 12,
      "totalOpenShipmentOrderItemQuantity": 4,
      "totalUnallocatedShipmentOrderItemQuantity": 4,
      "totalOpenPurchaseOrderItemQuantity": 0,
      "inventoryATPQuantity": 8,
      "sellableQuantity": 8,
      "plannedATPQuantity": 8
    }
  ],
  "totalCount": 1
}
```


Field Reference

Field	Meaning
`onHandQuantity`	Physical units in the warehouse
`pickableQuantity`	On-hand units currently in a pickable state
`totalOpenShipmentOrderItemQuantity`	Units committed to open orders
`totalUnallocatedShipmentOrderItemQuantity`	Committed demand not yet allocated (backorders)
`totalOpenPurchaseOrderItemQuantity`	Units inbound on open purchase orders
`inventoryATPQuantity` / `sellableQuantity`	**Sellable now** — on-hand minus all commitments (this is the number to promise against)
`plannedATPQuantity`	Available-to-promise including inbound PO stock

Use `sellableQuantity` / `inventoryATPQuantity` for availability decisions — unlike a raw "free" quantity, it correctly reflects backordered/unallocated demand.

---

8. List Products

```
GET /v1/products?page=1&size=100
```

List all products/SKUs in your account. Results are automatically scoped to your account. This is useful for checking which products exist before submitting purchase orders or shipment orders.

Query Parameters

Parameter	Default	Description
`page`	0	Page index (starts at 0)
`size`	100	Results per page

LQL Filtering

```
GET /v1/products?page=1&size=100&Sku.eq=WIDGET-100
GET /v1/products?page=1&size=100&ProductTypeName.eq=T-Shirt
GET /v1/products?page=1&size=100&ProductGroupName.eq=Apparel
GET /v1/products?page=1&size=100&CreatedDateTime.bt=2026-01-01,2026-03-31
```

Example Response

Returns the full product list including:

- `identifier`, `sku`, `name`, `description`
- `clientDisplayName`
- `salesPrice`, `purchasePrice`, `taxRate`
- `uomPackTypeName` (e.g. "Unit", "Case")
- `productGroupName`, `productTypeName`
- `isActive`, `isFragile`, `isOversized`, `isHazardous`
- `isTrackLotBatchNumber`, `isTrackExpiryDate`
- Custom fields

Page through by incrementing `page` until you get fewer results than `size`.

---

9. Create a Product (SKU)

```
POST /v1/products
```

Create a new product/SKU. This should be used when you need to add a product to the system before submitting purchase orders or shipment orders referencing that SKU.

Note: Product modification and deletion are not available through the API. Contact KSP for changes to existing products.

Example Payload (Minimal)

```
{
  "sku": "PRD-WIDGET-100",
  "name": "Widget 100",
  "description": "Standard widget, blue",
  "uomPackTypeName": "Unit",
  "packingSettings": {
    "uomPackTypeWeightUnitId": 1,
    "uomPackTypeWeight": 1.0,
    "uomPackTypeDimensionUnitId": 1,
    "uomPackTypeLength": 10,
    "uomPackTypeWidth": 10,
    "uomPackTypeHeight": 5
  }
}
```

Example Payload (Full)


```
{
  "sku": "PRD-RED-TSHIRT-M-2025",
  "fnsku": "FN-RED-TSHIRT-M-2025",
  "name": "Red T-Shirt M",
  "description": "100% cotton red t-shirt, Size Medium",
  "upc": ["0123456789012"],
  "salesPrice": 19.99,
  "purchasePrice": 10.50,
  "taxRate": 18,
  "uomPackTypeName": "Unit",
  "productGroupName": "Apparel",
  "productTypeName": "T-Shirt",
  "isActive": true,
  "isDigitalProduct": false,
  "isPackagingMaterial": false,
  "currencyId": 1,
  "minimumSafetyStock": 10,
  "imageList": [
    { "imageLink": "https://example.com/images/product-front.jpg" },
    { "imageLink": "https://example.com/images/product-back.jpg" }
  ],
  "packingSettings": {
    "uomPackTypeWeightUnitId": 1,
    "uomPackTypeWeight": 0.3,
    "uomPackTypeDimensionUnitId": 1,
    "uomPackTypeLength": 30,
    "uomPackTypeWidth": 25,
    "uomPackTypeHeight": 2,
    "isFragile": false,
    "isOversized": false,
    "isHazardous": false,
    "isPoster": false,
    "isLiquid": false,
    "isFoldable": true,
    "isStackable": true,
    "isUseItemsOwnBoxForShipping": false,
    "packingInstructions": "Place in poly bag before packing"
  },
  "customsDeclaration": {
    "declaredValue": 19.99,
    "hsTariffCode": "6109.10.0012",
    "originCountryCode": "US",
    "isIgnoreCustomsDeclaration": false,
    "customsDescription": "Cotton T-Shirt"
  },
  "lotBatchNumberSettings": {
    "isTrackLotBatchNumber": false,
    "isAutoCreateLotBatchNumber": false
  },
  "expiryDateSettings": {
    "isTrackExpiryDate": false
```

```
  },
  "serialNumberSettings": {
    "isTrackSerialNumber": false
  }
}
```

Required Fields

Field	Description
`sku`	Unique product SKU
`name`	Product name
`description`	Product description
`uomPackTypeName`	Unit of measure — must be one of KSP's configured pack types: `Unit`, `Case`, `Master Case`, or `Pack`. Unknown values are rejected (400 INVALID_PACK_TYPE).
`packingSettings`	Packing dimensions/weight (see Packing Settings below)

Complete Field Reference — Product

Field	Type	Description
`sku`	string	**Required.** Unique product SKU
`name`	string	Product name
`description`	string	Product description
`fnsku`	string	FNSKU (Amazon)
`upc`	array	Array of UPC barcodes
`salesPrice`	number	Sales price
`purchasePrice`	number	Purchase/cost price
`taxRate`	number	Tax rate percentage
`uomPackTypeName`	string	Default pack type (e.g. "Unit", "Case")
`productGroupName`	string	Product group
`productTypeName`	string	Product type
`isActive`	boolean	Whether product is active
`isDigitalProduct`	boolean	Digital product flag
`isPackagingMaterial`	boolean	Packaging material flag

Field	Type	Description
`isNonReturnable`	boolean	Non-returnable flag
`isInsert`	boolean	Insert item flag
`currencyId`	integer	Currency ID
`minimumSafetyStock`	integer	Minimum safety stock level
`maxReplenishmentLevel`	integer	Max replenishment level
`minReplenishmentLevel`	integer	Min replenishment level
`uomPackTypeVolumeUnitId`	integer	Volume unit ID
`uomPackTypeVolume`	number	Volume
`carrierPackageIdentifier`	string	Carrier package GUID
`returnInstructions`	string	Return instructions
`kitTypeId`	integer	Kit type ID (for kit products)
`imageList`	array	Array of `{ imageLink: "url" }` objects

Packing Settings (nested object)

Field	Type	Description
`packingSettings.uomPackTypeWeightUnitId`	integer	Weight unit (1=Pound, 2=Kilogram)
`packingSettings.uomPackTypeWeight`	number	Weight
`packingSettings.uomPackTypeDimensionUnitId`	integer	Dimension unit (1=Inch, 2=Centimeter)
`packingSettings.uomPackTypeLength`	number	Length
`packingSettings.uomPackTypeWidth`	number	Width
`packingSettings.uomPackTypeHeight`	number	Height
`packingSettings.isFragile`	boolean	Fragile flag
`packingSettings.isOversized`	boolean	Oversized flag
`packingSettings.isHazardous`	boolean	Hazardous flag
`packingSettings.isPoster`	boolean	Poster/tube flag
`packingSettings.isLiquid`	boolean	Liquid flag
`packingSettings.isFoldable`	boolean	Foldable flag

Field	Type	Description
`packingSettings.isStackable`	boolean	Stackable flag
`packingSettings.isUseItemsOwnBoxForShipping`	boolean	Ship in own box
`packingSettings.packingInstructions`	string	Packing instructions

Customs Declaration (nested object)

Field	Type	Description
`customsDeclaration.declaredValue`	number	Declared value
`customsDeclaration.hsTariffCode`	string	HS tariff code
`customsDeclaration.originCountryCode`	string	Country of origin
`customsDeclaration.isIgnoreCustomsDeclaration`	boolean	Skip customs
`customsDeclaration.customsDescription`	string	Customs description

Lot/Batch Settings (nested object)

Field	Type	Description
`lotBatchNumberSettings.isTrackLotBatchNumber`	boolean	Track lot/batch numbers
`lotBatchNumberSettings.isAutoCreateLotBatchNumber`	boolean	Auto-create lot numbers
`lotBatchNumberSettings.lotBatchNumberRegex`	string	Validation regex

Expiry Date Settings (nested object)

Field	Type	Description
`expiryDateSettings.isTrackExpiryDate`	boolean	Track expiry dates
`expiryDateSettings.expiryDateFormat`	string	Date format
`expiryDateSettings.isCalculateExpiryFromProduction`	boolean	Calculate from production date
`expiryDateSettings.shelfLife`	integer	Shelf life in days

Serial Number Settings (nested object)

Field	Type	Description
`serialNumberSettings.isTrackSerialNumber`	boolean	Track serial numbers

Field	Type	Description
`serialNumberSettings.isScanSerialNumberDuringPacking`	boolean	Scan during packing
`serialNumberSettings.isScanSerialNumberDuringReceiving`	boolean	Scan during receiving
`serialNumberSettings.serialNumberRegex`	string	Validation regex

Custom Fields

Field	Type	Description
`customFieldDateTime1` through `3`	string	Custom date fields
`customFieldToggle1` through `2`	boolean	Custom toggle fields
`customFieldDropDown1` through `2`	string	Custom dropdown fields
`customFieldTextBox1` through `3`	string	Custom text fields

Fields You Do NOT Need to Send

Field	Why
`clientIdentifier`	Assigned by the gateway based on your API key

Example Response

```
{
  "productId": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "logiwaIdentifier": "f18d8f61-fb5d-45ec-b2ef-21e57b9ed0c1",
  "sku": "PRD-WIDGET-100",
  "status": "created",
  "message": "Product created in Logiwa"
}
```

Important Notes

- **SKUs must be unique.** Creating a product with an existing SKU will return an error.
- **Product modification and deletion are not available** through the API. Contact KSP for changes.
- **Dimensions and weight** go in the `packingSettings` object — `uomPackTypeWeight`, `uomPackTypeLength`, `uomPackTypeWidth`, `uomPackTypeHeight`.

---

10. Submit a Purchase Order

```
POST /v1/purchase-orders
```

Submit an inbound purchase order (ASN) to notify the warehouse of incoming inventory.

Example Payload

```
{
  "code": "93024-HI",
  "vendor": "Hitachi",
  "purchaseOrderDate": "2026-03-20",
  "plannedReceivingDate": "2026-03-25",
  "referenceNumber": "VENDOR-REF-123",
  "purchaseOrderLineList": [
    { "sku": "881469", "packType": "Unit", "packQuantity": 1 },
    { "sku": "890354", "packType": "Unit", "packQuantity": 1 },
    { "sku": "888940", "packType": "Unit", "packQuantity": 5, "unitPrice": 12.50 }
  ]
}
```

Required Fields

Field	Description
`code`	Your unique PO number
`vendor`	Vendor name (must match an existing vendor in the system)
`purchaseOrderLineList`	Array of line items (requires `sku`, `packType`, and `packQuantity`)

Complete Field Reference — Purchase Order

Field	Type	Description
`code`	string	**Required.** Your unique PO number
`vendor`	string	**Required.** Vendor/supplier name (must match an existing vendor)
`purchaseOrderDate`	string	PO date, ISO format (default: today)
`actualReceivingDate`	string	Actual receiving date
`plannedReceivingDate`	string	Expected receiving date
`plannedArrivalDate`	string	Expected arrival date
`actualArrivalDate`	string	Actual arrival date

Field	Type	Description
`referenceNumber`	string	Vendor reference number
`currencyId`	string	Currency ID (defaults to USD if not provided)
`note`	string	PO notes
`customFieldDateTime1`	string	Custom date field 1
`customFieldDateTime2`	string	Custom date field 2
`customFieldDateTime3`	string	Custom date field 3
`customFieldToggle1`	boolean	Custom toggle 1
`customFieldToggle2`	boolean	Custom toggle 2
`customFieldDropDown1`	string	Custom dropdown 1
`customFieldDropDown2`	string	Custom dropdown 2
`customFieldTextBox1`	string	Custom text 1
`customFieldTextBox2`	string	Custom text 2
`customFieldTextBox3`	string	Custom text 3

Vendor Address Fields (vendorBillingAddress / vendorShipmentAddress)

Both vendor address objects share the same structure:

Field	Type	Description
`country`	string	Country code
`state`	string	State
`addressName`	string	Address name/label
`companyName`	string	Company name
`firstName`	string	First name
`lastName`	string	Last name
`email`	string	Email
`addressLine1`	string	Street address
`addressLine2`	string	Suite, unit, etc.
`city`	string	City

Field	Type	Description
`postalCode`	string	ZIP/postal code
`phoneNumber`	string	Phone number
`fax`	string	Fax number

Complete PO Line Item Field Reference

Field	Type	Required	Description
`sku`	string	**Yes**	Product SKU (must exist in the system)
`packQuantity`	integer	**Yes**	Quantity expected
`packType`	string	**Yes**	Pack type — one of: `Unit`, `Case`, `Master Case`, `Pack`
`unitPrice`	number	No	Unit cost
`taxRate`	number	No	Tax rate
`note`	string	No	Line item note
`lotBatchNumber`	string	No	Lot/batch number
`expiryDate`	string	No	Product expiry date
`productionDate`	string	No	Product production date
`licensePlateType`	string	No	License plate type
`licensePlateNumber`	string	No	License plate number
`warehouseLocation`	string	No	Specific warehouse location

Fields You Do NOT Need to Send

Field	Why
`clientIdentifier`	Assigned by the gateway based on your API key
`warehouseIdentifier`	Assigned by the gateway
`purchaseOrderTypeName`	Handled by the gateway
`currencyId`	Defaults to USD

Example Response

```
{
  "purchaseOrderId": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "logiwaIdentifier": "f18d8f61-fb5d-45ec-b2ef-21e57b9ed0c1",
  "code": "93024-HI",
  "status": "sent",
  "message": "Purchase order created in Logiwa"
}
```

---

11. List Purchase Orders

```
GET /v1/purchase-orders?page=1&size=50
```

Page through your purchase orders. Results are automatically scoped to your account.

Query Parameters

Parameter	Default	Description
`page`	0	Page index (starts at 0)
`size`	50	Results per page

LQL Filtering

```
GET /v1/purchase-orders?page=1&size=50&Code.eq=PO-001
GET /v1/purchase-orders?page=1&size=50&CreatedDate.bt=2026-01-01,2026-01-31
```

Example Response

Returns the full Logiwa purchase order list including PO code, vendor, status, line items, dates, and receiving progress.

---

12. Get Purchase Order Details

```
GET /v1/purchase-orders/{identifier}
```

Retrieve details for a purchase order using the `logiwaIdentifier` from the submission response.

13. Get Purchase Order Receipts

```
GET /v1/purchase-orders/{code}/receipts
```

Retrieve line-level receiving status for a purchase order using the PO `code`. Returns per-SKU ordered vs. received totals plus the individual receipt events (with dates, quantities, and any damage).

Example Response


```
{
  "purchaseOrderCode": "93024-HI",
  "purchaseOrderIdentifier": "f18d8f61-fb5d-45ec-b2ef-21e57b9ed0c1",
  "status": "Pending",
  "totalOrdered": 10,
  "totalReceived": 6,
  "totalShort": 4,
  "totalDamaged": 0,
  "isFullyReceived": false,
  "lineItems": [
    {
      "sku": "881469",
      "name": "Pressure Gauge",
      "orderedQuantity": 5,
      "receivedQuantity": 5,
      "shortQuantity": 0,
      "packType": "Unit",
      "isFullyReceived": true,
      "lastReceivedDate": "2026-03-25T10:30:00Z",
      "receiptEvents": [
        {
          "receiptDate": "2026-03-25T10:30:00Z",
          "receivedQuantity": 5,
          "packQuantity": 5,
          "packType": "Unit",
          "receiptDifference": 0,
          "damagedQuantity": 0,
          "warehouseCode": "A-01-01"
        }
      ]
    }
  ]
}
```


Each `lineItems[]` entry summarizes one SKU on the PO; `receiptEvents[]` lists each physical receipt against it (newest first). Top-level totals roll up the whole PO.

Error Responses

All errors return a consistent format:

```
{
  "error": {
    "message": "Description of what went wrong",
    "code": "ERROR_CODE"
  }
}
```

Code	HTTP Status	Meaning
`UNAUTHORIZED`	401	Invalid or missing API key
`BAD_REQUEST`	400	Validation failed or malformed request
`NOT_FOUND`	404	Resource or route not found
`METHOD_NOT_ALLOWED`	405	Wrong HTTP method for this endpoint
`RATE_LIMITED`	429	Exceeded your rate limit — wait and retry
`INTERNAL_ERROR`	500	Unexpected server error
`LOGIWA_API_ERROR`	502	Warehouse system returned an error (details in message)

Common Error Scenarios

Scenario	Error
Duplicate order code	`"This shipment order code already exists (CODE)"`
SKU not in system	`"Entered product is not correct."`
Invalid pack type	`"Packtype doesn't belong to selected product."`
Empty/placeholder fields	Various validation errors — omit fields you don't have data for

---

What Is NOT Available Through the API

The following operations are managed by KSP and are not available through the API:

- **Product updates/deletion** — Managed by KSP. You can create products but cannot modify or delete them
- **Order cancellation** — Contact KSP to cancel orders

- **Order deletion** — Contact KSP
- **Webhook management** — Managed by KSP
- **Warehouse/client configuration** — Managed by KSP

Onboarding Checklist

1. KSP provides your API key
2. Confirm your products/SKUs are set up in the system
3. Test with a single order submission
4. Verify order appears and status is `sent`
5. Test inventory query for your SKUs
6. Test purchase order submission if applicable
7. Move to bulk orders if needed for high volume

Support

For questions, product setup requests, or issues with the API, contact your KSP account representative.