

Fuzzy Logic

GA

Sabah Sayed

Department of Computer Science

Faculty of Computers and Artificial Intelligence

Cairo University

Egypt

Evolving Fuzzy Systems using Genetic Algorithms

- We want to evolve a fuzzy rule system using a GA.
- **Things to consider:**
 - What will be evolved (what parts of the fuzzy system)
 - How system elements are represented
 - Population initialization
 - Fitness evaluations
 - Operators used

What will we evolve?

- Usually the rule base is evolved to get the best rules representing a dataset of a particular problem.
- We can also evolve the membership functions used to find the best types (triangular, trapezoidal, ...etc) and ranges.

Representing Fuzzy Rules

- Each chromosome will represent a single rule set
- Our system will use Mamdani-type fuzzy rules, for example:

`if input_1 is not Low, and input_2 is High, then the output is Medium`
`if input_2 is Low, then the output is High`

- but computers generally can't handle this kind of input (yet)
- Assuming each variable has three fuzzy sets; Low, Medium, High:

Let Low=1 Medium=2 High=3

The above two rules can be numerically represented as:

`-1 3 2 and 0 1 3` (0 means "don't care")

Population Initialization

- Random initialization of the population.
- Rules are checked for feasibility.
- Each rule must have a non-zero antecedent, *and* a non-zero consequent.
- A rule such as 2 3 1 1 0 is thus non feasible, and is not included in the rule set.
- Re-generate individuals to compensate for the infeasible chromosomes.

Fitness Evaluation

- Percent correct and mean-square error are often used.
- Additional components of fitness may include the number of rules (minimize).

Steps of Evolving a Fuzzy Rule System

- Given a history of data (dataset), to a particular problem:

x1	x2	x3	xm	y
....
....
....

it is required to evolve a fuzzy system that will classify or predict y.


Evolving a Fuzzy Rule System

- **Step 1:**

Get min and max of each X_i (column) in dataset $\Rightarrow X_{i-\min}, X_{i-\max}$

- **Step 2:**

Design fuzzy sets (select them)



Evolving a Fuzzy Rule System

- **Step 3:**

Design chromosomes composed of random set of fuzzy rules as follows:

- R_j :
if $x_1=M$ and $x_2=L$
then $y=H$
- R_k :
if $x_1=H$
then $y=L$

key

Low : 1

not L : -1


Med : 2

not M : -2

High : 3

not H : -3

and \emptyset if entry not applicable



Evolving a Fuzzy Rule System

- **Step 3:**

Note that number of rules in chromosome is variable => variable-length chromosome

chromosome 1:

R1	R2	R3	R4

- **chromosome 2:**

R5	R6	R7

Evolving a Fuzzy Rule System

- **Step 4:**

Design of crossover operator

R1	R2	R3	R4

↑
Random crossover
point

R1	R6	R7


R5	R6	R7

↑
Random crossover
point

R5	R2	R3	R4

Evolving a Fuzzy Rule System

- **Step 5:**
Design of mutation operator
- According to random number r , for each entry in rule, either:
 - Add 1 (r : 0- 0.33)
ex. L to M
 - Subtract 1 (r : 0.34 – 0.66)
ex. H to M
 - Negate (r : 0.67 - 1)
ex. L to Not L



Evolving a Fuzzy Rule System

- **Step 6:**
Fitness function
- Run each fuzzy system (chromosome) as usual on dataset
- $\text{Fitness}_i = (\text{number of correctly predicted rows})_i$
- Or $\text{Fitness}_i = 1/\text{MSE}_i$
(mean square error)

	x_1	x_2	x_3	-----	x_m	y
r_1	-	-	-	-----		y_1
r_2	-	-	-	-----		y_2
r_3	-	-	-	-----		y_3
...		
r_i	-	-	-	-----		y_i
...		
r_p	-	-	-	-----		y_p

A red circle highlights the row r_i and its corresponding output y_i , with the value 50 written next to y_i and 45 written next to r_i .

Calculate Fitness of Chromosome k: Mean Square Error

chr_k Ruleset

R_1	R_2	R_3	R_4
-------	-------	-------	-------

{ for each chromosome chr_k in GA Population:
 Sum-of-SEs = 0
 for each record r_i in the dataset $[r_1, r_2, \dots, r_p]$:
 {

- * Use values of $x_{1i}, x_{2i}, x_{3i}, \dots, x_{mi}$ to perform:
 - ① Fuzzification
 - ② Inference \rightarrow Rules R_1, R_2, R_3, \dots in chr_k
 - ③ Defuzzification \rightarrow to get $Y_i(\text{predicted})$
- * Calculate square error (SE) = $(Y_i(\text{predicted}) - Y_i(\text{actual}))^2$

* Sum-of-SEs += SE

}

$$MSE_k = \text{Sum-of-SEs} / p$$

$p = \text{num. of records in data set}$

{ Fitness of $\text{chr}_k = 1 / MSE_k$

Evolving a Fuzzy Rule System

- **Step 7:**
Selection Strategy:
Roulette wheel selection
- **Step 8:**
Replacement strategy:
Elitism Strategy

