

Genetic Algorithms

Answer ALL Qusetions:

1- Crossover and mutation are the main operators of a Genetic Algorithm.

a- Differentiate between single-point and multiple-point crossover, on both binary and floating point representations.

b- Show by example- using binary strings- how can a 2-point crossover be carried out.

c- Explain the operation of the mutation operator on both binary and floating point representations.

d- Discuss the mechanics of non-uniform mutation on floating point representation- Apply using the following function:

$$\Delta(t, y) = y \cdot (1 - r^{(1-t/T)})$$

where r is a random number from [0..1].

(8 points)

2- Taking the reproductive schema growth equation of schema theory,

$$\eta(S, t+1) = \eta(S, t) \cdot \text{eval}(S, t) / \text{averagePopFitness}(t) [1 - P_c \cdot d(S) / (m-1) - o(S) \cdot P_m]$$

assume that $o(S) \cdot P_m = 0$ and $d(S) = m-1$, then the equation becomes:

$$\eta(S, t+1) = \eta(S, t) \cdot \text{eval}(S, t) / \text{averagePopFitness}(t) [1 - P_c]$$

Discuss the mechanics of the algorithm when $P_c = 0$ and $P_c = 1$ under the following conditions:

a- low population size

b- high population size

c- Elitism

(8 points)

3- a- Prove that any string of length m is an instance of 2^m different schemas.

b- Define the fitness f of bit string x with length m = 4, to be the integer represented by the binary number x. (eg. $f(0011)=3$, $f(1111)=15$). What is the average fitness of the schema 1*** under f? What is the average fitness of schema 0*** under f?

(8 points)


4- Given a population of PopSize Individuals, which are bit-strings of length L. Let the frequency of allele 1 be 0.3 at position i, that is 30% of all individuals contains a 1 and 70% a 0. How does this allele frequency change after performing k crossover operations with one-point crossover?

(8 points)

5- Calculate the probability that a binary chromosome with length L will not be changed by applying the usual bit-flip mutation with $P_m=1/L$.

(8 points)

6- Given the following feedforward neural network with weights,



and applying the following activation function,

$$f(x) = \begin{cases} 1 & x > 0 \\ 0 & x \leq 0 \end{cases}$$

Compute the outputs Y for inputs (X1, X2) equal to the following,
(0,0), (0,1), (1,0), (1,1).

What function do you think this network emulates.

(8 points)

7- Given the following exemplars to be encoded in a BAM,

X1 = (101010) Y1 = (1100)

X2 = (111000) Y2 = (1010)

a- Compute the weights matrix M.

b- Recall the output of the BAM when presented with X = (111010). Comment on the result.

c- Recall the output of the BAM when presented with X = (000111). Comment on the result.

d- Why do you get a zero in the recall vector and what value [-1 or 1] do you take for it if at the first iteration? On what basis is this taken?

8- Design a fuzzy controller with two input variables:

SPEED with range: 0 to 120 and 5 fuzzy sets: Stopped, Very Slow, Slow, Medium Fast and Fast.

And

DISTANCE with range: 0 to 2500 and 5 fuzzy sets: At, Very Near, Near, Medium Far and Far.

The output variable is BRAKE with range: 0% to 100% and fuzzy sets: No, Very Slight, Slight, Medium and Full.

The following fuzzy rules govern the actions of the system:

IF SPEED=Very Slow and DISTANCE=At THEN BRAKE = Full.

IF SPEED= Slow and DISTANCE=At THEN BRAKE = Full.

IF SPEED=Very Slow and DISTANCE=Very Near THEN BRAKE = Medium.

IF SPEED= Slow and DISTANCE=Very Near THEN BRAKE = Medium.

Using a Mamdani approach, show how the output is computed.

(8 points)

9- Show how fuzzy rules that model a particular system can be evolved using genetic algorithms. **(Note: This question is bonus!)**

(6 points)

AMR BADR