A decorative graphic on the left side of the slide consisting of two overlapping parallelograms. The front one is blue and the back one is light green. They are positioned diagonally, with the blue one partially covering the green one.

Handling multiple services in a monorepo using **Docker**



Agenda

1. Background
2. Why use Monorepos?
3. Using Docker with monorepos
4. Mentimeter questions
5. Conclusion

Background

What is a monorepo & why should we care about it?



Github



Repository


1,679 commits 22 branches 44 releases 33 contributors 2.63 MB

Branch: master New pull request Create new file Upload files Find file Clone or download


gigabo committed on GitHub Better module lookup during client compilation (#581) Latest commit bdf3819 13 hours ago

docs	Fix broken link in docs readme		a day ago
images	Fix #234 Add svg logo (#270)		2 months ago
packages	Better module lookup during client compilation (#581)		13 hours ago
.dockerignore	Adding Dockerfile to repository root	49 Bytes	23 days ago
.editorconfig	Updating .editorconfig: moar spaces per tab	169 Bytes	4 months ago
.eslintrc	Lint the generator with eslint (#496)	2.1 KB	15 days ago
.gitattributes	Force Linguist to exclude `.md` and `.py` files from our stats. (#529)	63 Bytes	7 days ago
.gitignore	Ignore IntelliJ .idea directory	76 Bytes	29 days ago
.travis.yml	Added proper indentation (#556)	1.63 KB	3 days ago
CHANGELOG.md	v0.4.4	11.86 KB	16 hours ago
CODE_OF_CONDUCT.md	Update Code of Conduct to Contributor Covenant	3.15 KB	6 months ago
CONTRIBUTING.md	Move chat to slack (#477)	3.66 KB	17 days ago
Dockerfile	Adding Dockerfile to repository root	214 Bytes	23 days ago
LICENSE	Add LICENSE	11.09 KB	6 months ago
MAINTAINING.md	Update maintaining guide to include how to update annotated src code (#...	1.23 KB	24 days ago
README.md	Making link to react-server.io go to HTTPS (#567)	3.42 KB	2 days ago
lerna.json	v0.4.4	331 Bytes	16 hours ago
package.json	chore(package): update eslint-plugin-react to version 6.1.2	1.73 KB	13 hours ago

Mono repository



Architecture





So.. are there other alternatives?

Polyrepo





Why use Monorepos?

Polyrepo

- Isolated teams
- Has its own dependencies
- Easy pipelines

Monorepo


- Easy onboarding
- Transparency
- Simplified dependency management

Monorepos also has it's cons....





A solution



docker

Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```

Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```

Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```

Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```

Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```

Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```


Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```


Dockerfile example (vote)

```
1  # Using official python runtime base image
2  FROM python:3.9-slim
3
4  # add curl for healthcheck
5  RUN apt-get update \
6      && apt-get install -y --no-install-recommends \
7      curl \
8      && rm -rf /var/lib/apt/lists/*
9
10 # Set the application directory
11 WORKDIR /app
12
13 # Install our requirements.txt
14 COPY requirements.txt /app/requirements.txt
15 RUN pip install -r requirements.txt
16
17 # Copy our code from the current folder to /app inside the container
18 COPY . .
19
20 # Make port 80 available for links and/or publish
21 EXPOSE 80
22
23 # Define our command to be run when launching the container
24 CMD ["gunicorn", "app:app", "-b", "0.0.0.0:80", "--log-file", "-", "--access-logfile", "-"]
```

Managing multiple containers



Docker
Compose

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21   result:
22     build: ./result
23     # use nodemon rather than node for local dev
24     command: nodemon server.js
25     depends_on:
```

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```


Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```

Docker-compose.yml

```
1  # version is now using "compose spec"
2  # v2 and v3 are now combined!
3  # docker-compose v1.27+ required
4
5  services:
6    vote:
7      build: ./vote
8      # use python rather than gunicorn for local dev
9      command: python app.py
10     depends_on:
11       redis:
12         condition: service_healthy
13     volumes:
14       - ./vote:/app
15     ports:
16       - "5000:80"
17     networks:
18       - front-tier
19       - back-tier
20
21     result:
22       build: ./result
23       # use nodemon rather than node for local dev
24       command: nodemon server.js
25       depends_on:
```

Mentimeter time





Take-home

Having trouble managing all your different services?

Consider using docker-compose in a Monorepo