

Basic Linux Commands

Part1



Day 2 Task: Basics Linux command



Kunal Maurya · Feb 23, 2023 · 📖 4 min read

Listing commands

Here are some examples of different `ls` commands in Linux with explanations:

- `ls` - This command lists the files and directories in the current working directory:

```
$ ls
Desktop  Documents  Downloads  Music  Pictures  Public  Templates
```

- `ls -a` - This command lists all files and directories, including hidden files:

```
$ ls -a
.  ..  .bash_history  .bashrc  .config  Desktop  Documents  Downlo
```

- `ls -l` - This command lists files and directories in long format, which includes details like permissions, ownership, size, and modification date/time:

```
$ ls -l
total 16
-rw-r--r-- 1 user user  11 Feb 23 14:02 file1.txt
-rw-r--r-- 1 user user  22 Feb 23 14:02 file2.txt
-rw-r--r-- 1 user user  23 Feb 23 14:02 file3.txt
drwxr-xr-x 2 user user 4096 Feb 23 14:02 dir1
drwxr-xr-x 2 user user 4096 Feb 23 14:02 dir2
```

The output is displayed in multiple columns, with each column separated by whitespace. The first column shows the file type and permissions, followed by the number of hard links, the owner name, the group name, the size of the file in bytes, the modification time, and finally the file name.

For example, the first line shows `-rw-r--r--` in the first column, which indicates that the file `file1.txt` has read and write permissions for the owner, and read-only permissions for the group and others. The number `1` in the second column indicates that there is one hard link to this file. The owner and group names are both `user`. The size of the file is `11` bytes. The modification time is `Feb 23 14:02`, and the file name is `file1.txt`.

- `ls -lh` - This command lists files and directories in long format with human-readable file sizes:

```
$ ls -lh
total 68K
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Desktop
drwxr-xr-x 3 user user 4.0K Feb 10 15:08 Documents
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Downloads
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Music
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Pictures
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Public
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Templates
drwxr-xr-x 2 user user 4.0K Feb 10 15:10 Videos
```

- `ls -t` - This command lists files and directories sorted by modification time, with the newest files first:

```
$ ls -t
Downloads Documents Pictures Public Videos Music Templates
```

- `ls -r` - This command lists files and directories in reverse order:

```
$ ls -r
Videos Templates Public Pictures Music Downloads Documents
```

- `ls -R` - This command lists files and directories recursively, i.e., it also lists the contents of subdirectories:

```
$ ls -R
.:
Desktop Documents Downloads Music Pictures Public Templates

./Desktop:
file1.txt file2.txt

./Documents:
file3.txt file4.txt

./Downloads:
file5.txt file6.txt

./Music:
file
```

- `ls -li` : Lists files and directories with their inode numbers.

```
$ ls -l
3957718 file1.txt
3957720 file2.txt
3957722 file3.txt
3957719 dir1
3957721 dir2
```

- `ls -S`: Lists files and directories sorted by size, with the largest files first.

```
$ ls -S
total 162M
-rw-r--r-- 1 user user 120M Feb 15 10:45 large_file.iso
-rw-r--r-- 1 user user  20M Feb 15 10:47 medium_file.mp4
-rw-r--r-- 1 user user   2M Feb 15 10:48 small_file.txt
drwxr-xr-x 2 user user 4.0K Feb 15 10:49 scripts
drwxr-xr-x 3 user user 4.0K Feb 15 10:50 documents
```

- `ls *.sh`: list all the files having .sh extension.

```
$ ls *.sh
script1.sh  script2.sh  script3.sh
```

Directory commands

Some commonly used Linux directory commands with examples:

Current Working

`pwd`: This command displays the current working directory.

```
$ pwd
/home/user/Documents
```

Change Directory Commands:

- `cd [directory]`: Change to a specific directory

```
$ cd /usr/local/bin
```

- `cd ~`: Change to the home directory

```
$ cd ~
```

- `cd -`: Change to the previous directory

```
$ cd -
```

- `cd ..` : Change to the parent directory

```
$ cd ..
```

- `cd [relative_directory_path]` : Change to the directory relative to the current directory

```
$ cd ../my_directory
```

Make Directory Commands:

- `mkdir [directory]` : Create a single directory

```
[root@localhost demo]# mkdir my_directory
[root@localhost demo]# ls
my_directory
```

- `mkdir [directory1] [directory2] [directory3] ...` : Create multiple directories

```
[root@localhost demo]# mkdir D1 D2 D3
[root@localhost demo]# ls
D1          D2          D3
```

- `mkdir -m [permission] [directory]` : Create a directory with a specific permission

```
$ mkdir -m 755 my_directory
```

- `mkdir -p [parent_directory]/[child_directory]` : Create a directory with multiple parent directories

```
mkdir -p my_parent_directory/my_child_directory
```

- `mkdir -m [permission] -o [owner] -g [group] [directory]` : Create a directory with a specific owner and group

```
$ mkdir -m 755 -o user -g group my_directory
```

This will create a directory named `my_directory` with the permission `755`, owned by the user `user` and the group `group`.

Move and Rename Commands:

- `mv [old_name] [new_name]` : Rename a file or directory

```
mv file1.txt file2.txt
```

- `mv [source] [destination]` : Move a file or directory to a new location

- ```
$ mv file1.txt /home/user/Documents/
```

- `mv [old_name] [new_name] [destination]` : Move a file or directory and rename it

- ```
$ mv file1.txt file2.txt /home/user/Documents/
```

Thank you for reading! Hope you find this article helpful.

~Kunal



Subscribe to my newsletter

Read articles from directly inside your inbox.
Subscribe to the newsletter, and don't miss out.

SUBSCRIBE

Linux

linux for beginners


linux-basics

Devops

DevOps Journey

MORE ARTICLES

Kunal Maurya



Day 1: Getting Started with DevOps

Introduction In today's world, software development has become an integral part of businesses of all...



Publish with Hashnode

Powered by [Hashnode](#) - Home for tech writers and readers