

Recording Errata in L^AT_EX Documents*

Michael Kohlhase
Computer Science, Jacobs University, Bremen, Germany
<http://kwarc.info/kohlhase>

Bendik Rønning Opstad
(bro.devel@gmail.com)

April 30, 2015

Abstract

This package provides a simple infrastructure for recording errata in L^AT_EX documents. This allows to maintain an updated version of the document (with all errors corrected) and automatically generate an errata document highlighting the difference to the published version.

1 Introduction

The life-cycle of a document does not end with its publication. After that, errors will be discovered, and have to be managed. The best way to do this is by marking errata in the text and generating the errata document from that.

2 Package Options

The `errata` package can be called with a variety of package options.

`show`= $\langle true/false \rangle$ (boolean, initially `false`)

Governs the general visibility of the errata markup. This option enables the options `footnote`^{P. 2}, `margins`, `inlinechanges`^{P. 2}, and `inlinemarks`^{P. 2}.

`hide`= $\langle true/false \rangle$ (complementary option to `show`)

Will do the opposite of `show`, ensuring that the errata markup is totally invisible in the formatted document.

`margins`= $\langle true/false \rangle$ (boolean, initially `false`)

Enables decorations in the margin for each erratum. Setting `margins=false` will globally disable all margin notes.

*Version v1.0 (last revised 2015/04/16)

foots= $\langle true/false \rangle$ (boolean, initially **false**)

Enables footnote decorations for each erratum.

inlinemarks= $\langle true/false \rangle$ (boolean, initially **true**)

By default, each errata change is marked in the document with the correction encapsulated by paranthesis as shown in example 1. By setting **inlinemarks**=**false**, the inline marks will not be added.

inlinechanges= $\langle true/false \rangle$ (boolean, initially **true**)

The default behavior is to make the errata changes visible in the document inlined in the text. By setting **inlinechanges**=**false**, the document text will stay unchanged.

record= $\langle true/false \rangle$ (boolean, default **true**)

The errata entries will be written to a file named $\langle jobname \rangle$ -errata.tex so that they can be included in an errata document (see section 6).

hyperref= $\langle true/false \rangle$ (boolean, initially **true**)

This option is used to control whether the **hyperref** package will be used to create hyperlinks between each erratum, the margin notes and the errata list.

cleveref= $\langle true/false \rangle$ (boolean, initially **true**)

This package option will require the **cleveref** package, and changes how labels are created so that the registered errata corrections can be referenced with **cleveref** commands¹.

marginnote= $\langle true/false \rangle$ (boolean, initially **true**)

The default behavior is to use the **\marginpar** macro to create the errata reference in the margins. In some environments, such as floating environments, the **\marginpar** macro cannot not be used. By default, **\marginnote** from the **marginnote** package will be used to handle margin notes when necessary.

styles= $\langle style\ name \rangle$ (string, initially default)

The default styling of the errata markup in the errata list and the footnotes is very simple. This package option can be used to specify one or more predefined styles. Available styles are: **default**, **detailed**, **tablelist**.

requirecmddescription= $\langle true/false \rangle$ (boolean, initially **true**)

By setting this package option to **false**, the errata command macros (**\erratumAdd**^{→P.3}, **\erratumDelete**^{→P.3}, **\erratumReplace**^{→P.4} and **\erratumNote**^{→P.4}) are defined without the mandatory description argument, i.e. **\erratumAdd**[$\langle keys \rangle$]{ $\langle add \rangle$ }

¹See **Cleveref support**^{→P.21} for the code definition.

2.1 Default command arguments

The following package options can be used to specify a set of default settings to be passed to the errata commands described in section 5. The different settings are described in section 4.

The default arguments may be changed using the following package options:

defaultargs={*<command options>*} (key/values, default described below)

This option allows setting a set of the default arguments to be passed to the errata commands `\erratumAdd`, `\erratumReplace`^{→ P. 4}, `\erratumDelete`, and `\erratumNote`^{→ P. 4}.

The default values passed to all the commands are as follows²:

```
margin=true
foot=true
inlinemark=true
inlinechange=true
record=true
marginargs={}
```

defaultargsadd={*<command options>*} (key/values, initially empty)

This option allows setting a set of the default arguments to be passed to the `\erratumAdd` command. Any arguments set will override the respective argument set with **defaultargs**.

defaultargsdelete={*<command options>*} (key/values, initially empty)

This option allows setting a set of the default arguments to be passed to the `\erratumDelete` command. Any arguments set will override the respective argument set with **defaultargs**.

defaultargsreplace={*<command options>*} (key/values, initially empty)

This option allows setting a set of the default arguments to be passed to the `\erratumReplace`^{→ P. 4} command. Any arguments set will override the respective argument set with **defaultargs**.

defaultargsnote={*<command options>*} (key/values, initially empty)

This option allows setting a set of the default arguments to be passed to the `\erratumNote`^{→ P. 4} command. Any arguments set will override the respective argument set with **defaultargs**.

3 Errata commands

Marking errata changes in the L^AT_EX text is done using a few simple macros.

\erratumAdd[*<keys>*]{*<desc>*}{*<add>*}

marks up a correction by adding the text *<add>* for addition with *<desc>* describing the intended correction.

\erratumDelete[*<keys>*]{*<desc>*}{*<delete>*}

marks up a correction by deleting the text *<delete>* with *<desc>* describing the intended correction.

²The code defining the default settings are defined in **Default command arguments**^{→ P. 15}.

`\erratumReplace[⟨keys⟩]{⟨desc⟩}{⟨old⟩}{⟨new⟩}`

marks up a correction by replacing the text `⟨old⟩` with `⟨new⟩`.

`\erratumNote[⟨keys⟩]{⟨desc⟩}{⟨note⟩}`

creates a note entry that cannot be described by the other commands.

3.1 Errata example

Example 1 shows all editing operations in action.

Example

```
Here we have \erratumAdd{forgotten word}{three} errata in one \erratumDelete{
superfluous phrase}{darned} long \erratumReplace{translated}{Zeile}{line}.
```

Example 1: Some short errata

All of these macros mark the location of the errata in the margin and document the changes in footnote-like structures. The text in example 1 is rendered as follows:

Here we have [three]_a¹ errata in one []_a² long [line]_r³

Err(1)
Err(2)
Err(3)

If the package option `hyperref`^{→P. 2} is enabled, the margin note will link to the entry in the errata list produced by calling `\PrintErrata`^{→P. 8}.

3.2 Errata environment

```
\begin{erratum}[⟨keys⟩]{⟨desc⟩}
  ⟨environment content⟩
\end{erratum}
```

Extended errata group multiple editing operations into a coherent group via the `erratum` environment. The first argument of this environment is an explanation as for the short errata above. The `erratum` environment provides local versions of the editing markup macros, which behave like those, but lack the first (explanation) argument, which is already given in the environment that contains them.

Example

```
\begin{erratum}[date=2006-07-19,reported-by=Michael Kohlhase]{old should be new}
This is a test of a long erratum
\begin{enumerate}
  \item We can replace \eReplace{oldtext}{newtext}
  \item and \eAdd{new text}
  \item and finally delete old text\eDelete{alltogether}
\end{enumerate}
\end{erratum}
```

¹ERRATUM! forgotten word (added text)

²ERRATUM! superfluous phrase (deleted “darned”)

³ERRATUM! translated (original text was: “Zeile”)

Example 2: An extended erratum with local correction markers

BErr(4)

The text in example 2 would be rendered as

this is a test of a long erratum

1. We can replace [newtext]_r^{4:1}
2. and [new text]_a
3. and finally delete old text []_d^{4:2}

EErr(4)

The `erratum` environment should also be used in situations where the error occurs in an environment, where normal $\text{T}_\text{E}\text{X}$ / $\text{L}^{\text{A}}\text{T}_\text{E}\text{X}$ processing is suspended, e.g. a `verbatim` environment. In this case, we can use it to attach correction information via the environment, but do not use the local change documentations.

4 Command Options

Each of the errata commands take an optional list of comma separated key/values as argument. This can be used to specify per-command options for each errata entry.

margin= $\langle true/false \rangle$ (boolean, defaults to **true**)

Allows to override the default **margin** value for this erratum.

foot= $\langle true/false \rangle$ (boolean, defaults to **true**)

Allows to override the default **foot** value for this erratum.

inlinechange= $\langle true/false \rangle$ (boolean, defaults to **true**)

Allows to override the default **inlinechange** value for this erratum.

inlinemark= $\langle true/false \rangle$ (boolean, defaults to **true**)

Allows to override the default **inlinemark** value for this erratum.

label= $\langle name\ of\ label \rangle$ (initially empty)

Allows specifying a custom label name to be registered for this errata entry.

uselabel= $\langle name\ of\ label \rangle$ (string, defaults to `errata<X>`)

Allows specifying a label to use instead of the default label generated for each registered erratum entry (`errata<X>` where X is the erratum number). This is necessary in environments where only one label may exist, such as in the `equation` environment.

marginargs= $\{ \langle key/valoptions \rangle \}$ (list, initially empty)

Allows specifying custom arguments to be passed to the marginnote formatter.

usemarginnote[$= \langle length \rangle$] (length, initially **0pt**)

Forces the use of `\marginnote` for the errata command. An optional value can be specified which denotes how much to vertically shift the margin note.

⁴ERRATUM! OLD SHOULD BE NEW

4:1 was: oldtext

4:2 deleted: altogether

5 Errata metadata

5.1 Data keys

For each errata command, a set of meta-data can be specified for an errata entry. The following keys can be used to registered additional data:

date=*<date when registered>* (string, initially empty)

Allows specifying the date when the erratum was registered.

reported-by=*<name of reporter>* (string, initially empty)

Allows specifying the name of the reporter.

description=*<description>* (string, initially empty)

Allows specifying the description of the change.

If the package option `requirecmddescription`^{P.2} is true (the default), This key defaults to the value specified in the *<desc>* field.

location=*<location hint>* (string, initially empty)

Used to specify the location in the text where the change is made.

type=*<type of correction>* (string, initially empty)

Used to specify what type of change is registered, e.g. grammar, clarification, layout.

Remember to encapsulate any of values in curly braces if it contains a comma.

5.2 Formatter keys

For each of the metadata keys specified in section 5.1, a formatter is defined for the errata list and the footnotes. The formatter defines a custom formatting rule which will be applied to the input value before being used.

Additionally, the following formatter keys exist which may **not** be passed as argument to the errata commands:

pageref (name of label, errata<X>)

Formats a reference to the page number where the erratum is located.

actiondescription

the formatted description of the action

action

The action name

erratumlistitem

This key is used to insert an `\item[]` in the errata list.

erratumlistitemtitle

The title for the erratum in the errata list

erratumlisttarget

The name used when creating a `\label` target in the errata list.

marginfmt/marginnote

Formats the marginnote

5.3 Setting the format for footnotes and errata list

The formatting of the footnotes and errata list can be changed using the two macros `\errataSetListFormat` and `\errataSetFootFormat`.

The argument $\langle keys \rangle$ should specify a comma separated list of keys as specified in section 5³.

\errataSetFootFormat $\{\langle keys \rangle\}$

Allows changing how the footnotes are formatted.

```
\errataSetFootFormat{+description, +actiondescription}
```

\errataSetListFormat $\{\langle keys \rangle\}$

The default format for the errata list is defined with:

```
\errataSetListFormat{+erratumlistitem, +erratumlisttarget, +description}
```

5.4 Formatting the keys

The format of each of the keys can be set using the macro `\errataSetKeyFormat`.

\errataSetKeyFormat $\{\langle key \rangle\}\{\langle format \rangle\}$

should be used to set the formatter key for a meta data key.

The default format for the keys are as follows⁴:

³See `Errata default style definition` → P. 17 for the code definition

⁴This code is defined at `Default formatters` → P. 18.

```

%%
\erratareset{%
  defaultkeyformats/.style={%
    %% Formats for the footnotes
    footformats/description/.setStrKeyFmt={##1}{~##1},
    footformats/action/.setStrKeyFmt={##1}{~##1},
    footformats/actiondescription/.setStrKeyFmt={##1}{~##1},
    %% Set the format for the action description for each erratum command
    actionformat/add/.setStrKeyFmt={##1}{ (added text)},
    actionformat/delete/.setStrKeyFmt={##1}{(deleted ‘‘##1’’)},
    actionformat/replace/.setStrKeyFmt={##1+##2}{ (original text was: ‘‘##2’’)},
    actionformat/note/.setStrKeyFmt={##1}{##1},
    %% Errata list format
    listformats/description/.setStrKeyFmt={##1}{~##1},
    listformats/erratumlistitemtitle/.setStrKeyFmt={##1}{%
      \@errata@hlink{\@errata@getvalue{labelref}}%
      {\protect\makebox[\@errata@groupindent][l]{\@errata@labelname}}},
    listformats/pageref/.setStrKeyFmt={##1}{Page~\pageref{##1} },
    listformats/type/.setStrKeyFmt={##1}{Type: ##1 },
    listformats/date/.setStrKeyFmt={##1}{ (Date reported: ##1)},
    listformats/reported-by/.setStrKeyFmt={##1}{Reported by: ##1},
    listformats/action/.setStrKeyFmt={##1}{~##1},
    listformats/actiondescription/.setStrKeyFmt={##1}{~##1},
    listformats/erratumlistitem/.setStrKeyFmt={##1}{\item[##1]},
    listformats/erratumlabel/.setStrKeyFmt={##1}{\@errata@labelname},
    listformats/erratumname/.setStrKeyFmt={##1}{##1},
    listformats/erratumnamedlink/.setStrKeyFmt={##1+##2}{%
      \@errata@hlink{##1}{\protect\makebox[\@errata@groupindent][l]{##2}}}%
    },
    listformats/erratumlisttarget/.setStrKeyFmt={##1}{\@errata@targeterratum{##1}{}},
    %% The name of the errata labels
    errformats/errfmt/.setStrKeyFmt={##1}{Err(##1)},
    errformats/eerrbeginfmt/.setStrKeyFmt={##1}{BErr(##1)},
    errformats/eerrrendfmt/.setStrKeyFmt={##1}{EErr(##1)},
    %%
    actionidformat/add/.setStrKeyFmt={##1}{Addition},
    actionidformat/delete/.setStrKeyFmt={##1}{Deletion},
    actionidformat/note/.setStrKeyFmt={##1}{Note},
    actionidformat/replace/.setStrKeyFmt={##1}{Correction},
    %%
    listformats/onnewgroup/.setStrKeyFmt={##1}{},
    listformats/onsamegroup/.setStrKeyFmt={##1}{},
  },
}

```

6 Generating Statistics and Errata Documents

\PrintErrata

This command inserts the errata list at the current position.

\printerrata[⟨postfix(-errata.tex)⟩]{⟨prefix⟩}

This command allows to print the errata for another document. This command is useful when generating errata documents for published works. Say we have a book with a driver file `thebook.tex`, into which we have incorporated errata markup using the infrastructure detailed above. Then we have a new document called e.g. `theerrata.tex` which has the form given in example 3. Note that we have used `\printerrata{thebook}` to include the errata notices generated from `thebook.tex`.


```
\begin{errata}
  <environment content>
\end{errata}
```

The errata list produced when the `record`^{P.2} option is enabled is placed inside this environment.

```
\erratumItem[<macro>]{<title>}{<text>}
```

Errata can be marked up using the `\erratumItem` macro in the `errata` environment. `\erratumItem` takes one optional, and two required arguments.

The first argument (`[<macro>]`) can be used to specify a macro containing a value that will be expanded after the other values, i.e. at the end.

The second argument `{<title>}` will be formatted using the `listformats/erratumlistitem`^{P.6} key formatter. For the default formatting of the errata list this is used to insert a `\item[<title>]` before the remaining errata meta data specified in the third argument `{<text>}`

Normally it is not necessary to manually use this macro, as the `record`^{P.2} option will write an `erratumItem` to the errata for each registered erratum.

```
\erratamessage
```

Putting the macro `\erratamessage` just before the `\end{document}` will generate a message with cardinality information for the errata into the log file.

In the errata document in example 3 we postulate that we keep an updated version of The Book online⁵ using the infrastructure provide by the `errata` package. In the updated version of `thebook.tex`, it can be useful to tabulate the errata as well, e.g. in a section in the appendix. This can be done by the `\PrintErrata`^{P.8} command. Note that this command needs to close the errata file `thebook-errata.tex` therefore we need a `\newpage` to clear the queue of waiting `\writes` before `thebook-errata.tex` can be loaded (otherwise we may be missing the errata from the last page).

⁵And indeed it is good practice to do so if the copyright agreement with the publisher allows this.

Example

```

\documentclass{article}
\usepackage[hide]{errata}
\title{Errata for The Book}
\begin{document}
\maketitle
\begin{abstract} This document tracks the errata in The Book. \end{abstract}
\section{Introduction}
The errata of The Book are tracked in this document, whose newest version
can be found at \url{../berrata.pdf}. A version of The Book that contains
all errata corrections (and markup of what changed) can be found at
\url{../book.pdf}.

In the following we will tabulate the errata in document order. Their
location will be referenced by the section they appear in rather than the
page number, since we do not expect the former to change in the errata
correction process.

\section{The Errata in The Book}
\printerrata{thebook}
\end{document}

```

Example 3: A Sample Errata Document

7 Limitations

If you want to contribute, please contact the author or make a pull request at <https://github.com/KWARC/LaTeX-errata>

7.1 Support for special environments

When registering an erratum in environments such as `equation` (from `amsmath` package), labels cannot be created freely, therefore the label already registered in the environment must be passed to the errata command.

Example 4 shows example where the label is specified manually.

Err(5)

Title

```
\begin{equation}\label{customlabel}
\begin{split}
a=a \quad \backslash\backslash
b=b \quad \backslash erratumAdd[uselabel=customlabel]{label}{custom label example}
\end{split}
\end{equation}
```

$a = a$

$b = b[customlabel example]_a^5$
(1)

⁵ERRATUM! label (added text)
⁵ERRATUM! label (added text)

Example 4: Some short errata

7.2 Floating environments

When registering errata corrections inside floating environments, some manual adjustments may be required. Example 5 shows how the margins can be adjusted manually.

Title	
<p>In this sentence<code>\erratumAdd[inline mark=false,label={comma1}]{added comma}{,}</code> we added a comma with inline mark disabled<code>\erratumAdd[inline mark=true,label={comma2}]{added another comma}{,}</code> as well as a comma with inlinemarking.</p> <p>Inside environments where <code>\refAuxcs{marginnote}</code> must be used, it may be necessary to manually adjust the vertical placement of the margin note when multiple notes overlap.</p> <p>As this code is processed inside a <code>\refAux{tcolorbox}</code>, <code>\refAuxcs{marginnote}</code> must be used instead of <code>\refAuxcs{marginpar}</code>. As we can see, <code>\Cref{comma1}</code> and <code>\cref{comma2}</code> are overlapping in the margin as <code>\refAuxcs{marginnote}</code> does not handle stacking multiple notes. Therefore, we must manually ask <code>\refAuxcs{marginnote}</code> to shift the second margin value, such as with <code>\erratumAdd[inline mark=true]{added missing word}{these}</code> two <code>\erratumAdd[inline mark=true,usemarginnote=20pt]{added another missing word}{corrections}</code>.</p>	
<p>In this sentence, we added a comma with inline mark disabled⁷_a as well as a comma with inlinemarking.</p> <p>Inside environments where <code>\marginnote</code> must be used, it may be necessary to manually adjust the vertical placement of the margin note when multiple notes overlap.</p> <p>As this code is processed inside a <code>tcolorbox</code>, <code>\marginnote</code> must be used instead of <code>\marginpar</code>. As we can see, Err(6) and Err(7) are overlapping in the margin as <code>\marginnote</code> does not handle stacking multiple notes. Therefore, we must manually ask <code>\marginnote</code> to shift the second margin value, such as with ⁸_a [these] two ⁹_a [corrections].</p>	<p>Err(6)</p> <p>Err(8)</p>
<p>⁶ERRATUM! added comma (added text)</p> <p>⁷ERRATUM! added another comma (added text)</p> <p>⁸ERRATUM! added missing word (added text)</p> <p>⁹ERRATUM! added another missing word (added text)</p>	<p>Err(9)</p>

Example 5: Example showing how to adjust the margin notes

8 The Implementation

```

\NeedsTeXFormat{LaTeX2e}[1999/12/01]
\ProvidesPackage{errata}[2015/04/16 v1.0 Errata Management]
\RequirePackage{xifthen}
\RequirePackage{pgfkeys}
\RequirePackage{etoolbox}
\RequirePackage{xpatch}
\RequirePackage{xparse}
\RequirePackage{xinttools} % defines \xintFor macro
\RequirePackage[family=@errata@]{strkeyformatter}
\RequirePackage{kvoptions}[2009/07/21]

```

Setup package options

```

\SetupKeyvalOptions {
  family = Errata,
  prefix = @errataOpt@,
}

```

show The **show** package option shows everything

```
\DeclareBoolOption{show}
```

hide The **hide** package option hides everything

```
\DeclareComplementaryOption{hide}{show}
```

margins The **margins** package option

```
\DeclareBoolOption{margins}
```

foots The **foots** package option

```
\DeclareBoolOption{foots}
```

record The **record** package option shows everything

```
\DeclareBoolOption[true]{record}
```

requirecmddescription The **requirecmddescription** package option

```
\DeclareBoolOption[true]{requirecmddescription}
```

hyperref The **hyperref** package option

```
\DeclareBoolOption[true]{hyperref}
```

cleveref The **cleveref** package option

```
\DeclareBoolOption[true]{cleveref}
```

marginnote The **marginnote** package option

```
\DeclareBoolOption[true]{marginnote}
```

<code>environmenttestmode</code>	<p>The <code>environmenttestmode</code> package option allows to set when <code>\marginnote</code> is used instead of <code>\marginpar</code>. Errata will try to detect when <code>\marginnote</code> should be used instead of <code>\marginpar</code>, and this option allows for finetuning how safe the test is. The default (<code>environmenttestmode=0</code>) will only use <code>\marginnote</code> when it knows for certain that it cannot use <code>\marginpar</code>. This is in <code>math</code> mode, in <code>inner</code> mode, and in <code>tcolorbox</code>'s <code>tcb@savebox</code> environment. There are certainly many more that should be added to this list. By setting <code>environmenttestmode=1</code>, <code>\marginnote</code> will be used whenever <code>\@captive</code> is defined, which should include most floating environments such as <code>table</code> and <code>figure</code>. The strictest mode <code>environmenttestmode=2</code> will force <code>\marginnote</code> to be used whenever the current environment is not 'document', which means any environment outside of the root document.</p> <pre>\DeclareStringOption[0]{environmenttestmode}</pre>
<code>uniquelistlabels</code>	<p>The <code>uniquelistlabels</code> package option Disabled by default (0), if option set, default level is 3.</p> <pre>\DeclareStringOption[0]{uniquelistlabels}[3]</pre>
<code>inlinemarks</code>	<p>The <code>inlinemarks</code> package option</p> <pre>\DeclareBoolOption[true]{inlinemarks}</pre>
<code>inlinechanges</code>	<p>The <code>inlinechanges</code> package option</p> <pre>\DeclareBoolOption[true]{inlinechanges}</pre>
<code>styles</code>	<p>The <code>styles</code> package option</p> <pre>\DeclareStringOption[default]{styles}</pre>
<code>defaultargs</code>	<p>The <code>defaultargs</code> package option</p> <pre>\DeclareStringOption[]{defaultargs}</pre>
<code>defaultargsadd</code>	<p>The <code>defaultargsadd</code> package option</p> <pre>\DeclareStringOption[]{defaultargsadd}</pre>
<code>defaultargsdelete</code>	<p>The <code>defaultargsdelete</code> package option</p> <pre>\DeclareStringOption[]{defaultargsdelete}</pre>
<code>defaultargsreplace</code>	<p>The <code>defaultargsreplace</code> package option</p> <pre>\DeclareStringOption[]{defaultargsreplace}</pre>
<code>defaultargsnote</code>	<p>The <code>defaultargsnote</code> package option</p> <pre>\DeclareStringOption[]{defaultargsnote}</pre>

```

\ProcessKeyvalOptions{Errata}
%% Utility macros
\input{erratapgfkeysextra}
\def\errataset{\pgfkeys{/@errata@}}
\DeclareExpandableDocumentCommand{\@errata@setvalue}{ m } {\pgfkeys{/@errata@/#1}}
\DeclareExpandableDocumentCommand{\@errata@setvalues}{ 0{ } m } {\pgfkeys{/@errata@/#1.cd, #2}}
\DeclareExpandableDocumentCommand{\@errata@getvalue}{ m } {\pgfkeysvalueof{/@errata@/#1}}
\NewDocumentCommand{\@errata@isnotempty}{ m m } {\ifthenelse{\equal{#1}{}}{#2}}
\NewDocumentCommand{\@errata@isempty}{ m m } {\ifthenelse{\equal{#1}{}}{#2}}
\NewDocumentCommand{\@errata@ifstrequal}{ m m m } {\ifthenelse{\equal{#1}{#2}}{#3}}
%%

```

Default command arguments

Define the custom default arguments for the errata command

```

\pgfkeys{
  /@errata@/cmdkeys/.is family, /@errata@/cmdkeys,
  defaultargs/.style={record=true, foot=true, margin=true,
    marginargs={}, inlinemark=true, inlinechange=true},
  defaultargsadd/.style={},
  defaultargsreplace/.style={},
  defaultargsdelete/.style={},
  defaultargsnote/.style={},
  /handlers/.errataapplystyles/.code={\xintFor ##9 in {#1} \do {\errataset{styles/##9}}},
}
%% Add any default arguments specified by the user
\@errata@setvalues[cmdkeys/]{defaultargs/.append style/.expand once={\@errataOpt@defaultargs}}
\@errata@setvalues[cmdkeys/]{defaultargsadd/.append style/.expand once={\@errataOpt@defaultargsadd}}
\@errata@setvalues[cmdkeys/]{defaultargsreplace/.append style/.expand once={\@errataOpt@defaultargsreplace}}
\@errata@setvalues[cmdkeys/]{defaultargsdelete/.append style/.expand once={\@errataOpt@defaultargsdelete}}
\@errata@setvalues[cmdkeys/]{defaultargsnote/.append style/.expand once={\@errataOpt@defaultargsnote}}
%%
\if@errataOpt@show
\@errataOpt@margintrue%
\@errataOpt@footstrue%
\@errataOpt@inlinemarktrue%
\@errataOpt@inlinechangestrue%
\fi
%%
\ifpackageloaded{hyperref}{\@errataOpt@hyperreffalse }
\ifpackageloaded{cleveref}{\@errataOpt@clevereffalse }
\if@errataOpt@marginnote
\ifpackageloaded{marginnote}{\RequirePackage{marginnote}}
\fi
\fi
%%
\newcounter{@errata@erratum}
\newcounter{erratum@note}[@errata@erratum]
\if@errataOpt@record\newwrite\@errata@file
\immediate\openout\@errata@file=\jobname-errata.tex
\AtEndDocument{\closeout\@errata@file}\fi
%%
\newlength{\@errata@groupindent}

```

```

\setlength\@errata@groupindent{14.7pt}
\newcounter{\@errata@uniquelistlabels}
\setcounter{\@errata@uniquelistlabels}{\@errata@opt@uniquelistlabels}
\newcounter{\@errata@environmenttestmode}
\setcounter{\@errata@environmenttestmode}{\@errata@opt@environmenttestmode}

\NewDocumentCommand{\@errata@declareKey}{O{UNDEF} m }
{%\@errata@setvalue{#2/.initial={#1}}}%
%%
\NewDocumentCommand{\@errata@declareStoreKey}{O{UNDEF} m }
{%% Basically 'estore in', but must build macro name from argument
\pgfkeys{\@errata@/#2/.code={\expandafter\edef\csname \@errata@#2\endcsname{##1}}}%
\pgfkeys{\@errata@/#2={#1}}%
}
%%
\NewDocumentCommand{\@errata@setcmdkeys}{O{0} m }{%
\xintFor ##9 in {#2} \do {%
\edef\@errata@key{##9}%
\@errata@isnotempty{##9} {%
\@errata@setvalue{cmdkeys/\@errata@key/.initial=#1}%
}}}
%%
\NewDocumentCommand{\errataSetFootFormat}{m }{%
\@errata@declareStoreKey[#1]{footformat}%
}
\NewDocumentCommand{\errataSetListFormat}{m }{%
\@errata@declareStoreKey[#1]{listformat}%
}
\@errata@declareStoreKey[type, description, location, date, id, pageref,
inlinemark, inlinechange, uselabel, label, margin, foot, record,
marginargs, usemarginnote, reported-by, actionid, action, actionargs, actiondescription,
erratumlistitem, erratumlistitemtitle, erratumlisttarget, onnewgroup, onsamegroup,
erratumlabel, erratumname, erratumnamedlink, customvalue]{formatkeys}% Defines \@errata@formatkeys
%%
\@errata@setcmdkeys{\@errata@formatkeys}
\@errata@setvalue{cmdkeys/usemarginnote/.default={0pt}}
%%

```

`\errataSetKeyFormat` Macro for setting the format of a key

```

\NewDocumentCommand{\errataSetKeyFormat}{O{} m m }{% PGF argument pattern, key, formatted output
\StrFmtSetKeyFormat[#1]{#2}{#3}%
}

\DeclareExpandableDocumentCommand{\@errata@getformatted}{m m m }{% key, args, macroname
\StrFmtgetformatted{#1}{#2}{#3}%
}
\DeclareExpandableDocumentCommand{\@errata@getformattede}{m m m }{% key, args, macroname
\StrFmtgetformattede{#1}{#2}{#3}%
}
%% Set default formater for all keys
\SetDefaultKeylistFormat[#1]{listformats}{\@errata@formatkeys}
\SetDefaultKeylistFormat[#1]{footformats}{\@errata@formatkeys}
\SetDefaultKeylistFormat[#1]{errformats}{errfmt, eerrbeginfmt, eerrendfmt}
\errataSetKeyFormat[#1+#2]{marginfmt/marginnote}{#2}%

```



```
%%
\@errata@declareKey[{\@errata@erratum}]{footnoteprefix}
\@errata@declareKey[{\scshape{Erratum!}}]{footnotebegin}
%%
%% Used internally to track label and label references
\@errata@declareKey{labelref}
\@errata@declareStoreKey{erratumname}
\@errata@setvalue{labelname/.gstore in=\@errata@labelname}
\@errata@setvalue{labelname={}}
\@errata@setvalue{prevlabel/.gstore in=\@errata@prevlabel}
\@errata@setvalue{prevlabel={}}
\@errata@setvalue{lastuniqueidlabel/.gstore in=\@errata@lastuniqueidlabel}
\@errata@setvalue{lastuniqueidlabel={}}
%%
\@errata@setvalue{lastcommandinlinevalue/.gstore in=\@errata@lastcommandinlinevalue}
\@errata@setvalue{lastcommandinlinevalue={}}
\@errata@setvalue{inlinevalue/.initial={}}
```

Errata default style definition

Define the default errata formatting

```
%%
\erratareset{%
  defaultkeyformats/.style={%
    %% Formats for the footnotes
    footformats/description/.setStrKeyFmt={##1}{~##1},
    footformats/action/.setStrKeyFmt={##1}{~##1},
    footformats/actiondescription/.setStrKeyFmt={##1}{~##1},
    %% Set the format for the action description for each erratum command
    actionformat/add/.setStrKeyFmt={##1}{ (added text)},
    actionformat/delete/.setStrKeyFmt={##1}{(deleted ‘‘##1’’)},
    actionformat/replace/.setStrKeyFmt={##1+##2}{ (original text was: ‘‘##2’’)},
    actionformat/note/.setStrKeyFmt={##1}{##1},
    %% Errata list format
    listformats/description/.setStrKeyFmt={##1}{~##1},
    listformats/erratumlistitemtitle/.setStrKeyFmt={##1}{%
      \@errata@hlink{\@errata@getvalue{labelref}}%
      {\protect\makebox[\@errata@groupindent][l]{\@errata@labelname}}},
    listformats/pageref/.setStrKeyFmt={##1}{Page~\pageref{##1} },
    listformats/type/.setStrKeyFmt={##1}{Type: ##1 },
    listformats/date/.setStrKeyFmt={##1}{ (Date reported: ##1)},
    listformats/reported-by/.setStrKeyFmt={##1}{Reported by: ##1},
    listformats/action/.setStrKeyFmt={##1}{~##1},
    listformats/actiondescription/.setStrKeyFmt={##1}{~##1},
    listformats/erratumlistitem/.setStrKeyFmt={##1}{\item[##1]},
    listformats/erratumlabel/.setStrKeyFmt={##1}{\@errata@labelname},
    listformats/erratumname/.setStrKeyFmt={##1}{##1},
    listformats/erratumnamedlink/.setStrKeyFmt={##1+##2}{%
      {\@errata@hlink{##1}{\protect\makebox[\@errata@groupindent][l]{##2}}}%
    },
    listformats/erratumlisttarget/.setStrKeyFmt={##1}{\@errata@htargeterratum{##1}{}},
    %% The name of the errata labels
    errformats/errfmt/.setStrKeyFmt={##1}{Err(##1)},
```

```

errformats/eerrbeginfmt/.setStrKeyFmt={##1}{BErr(##1)},
errformats/eerrendfmt/.setStrKeyFmt={##1}{EErr(##1)},
%%
actionidformat/add/.setStrKeyFmt={##1}{Addition},
actionidformat/delete/.setStrKeyFmt={##1}{Deletion},
actionidformat/note/.setStrKeyFmt={##1}{Note},
actionidformat/replace/.setStrKeyFmt={##1}{Correction},
%%
listformats/onnewgroup/.setStrKeyFmt={##1}{},
listformats/onsamegroup/.setStrKeyFmt={##1}{},
},
defaultlistandfootstyle/.code={%

```

Default formatters

Define the default format of the errata list and footnotes

```

\errataSetListFormat{+erratumlistitem, +erratumlisttarget, +description}
\errataSetFootFormat{+description, +actiondescription}
},
styles/default/.style={defaultkeyformats, defaultlistandfootstyle},
}
%%
%% END style: default
%%

```

Errata detailed style definition

Define the detailed formatting

```

%%
\errataSet{%
  detailedstylekeyformats/.style={%
    %% Errata list format
    listformats/description/.setStrKeyFmt={##1}{~(##1)},
    listformats/erratumlistitemtitle/.setStrKeyFmt={##1}{%
      {\@errata@hlink{\@errata@getvalue{labelref}}}{%
        \protect\makebox[\@errata@groupindent][l]{\@errata@labelname}}%
      \@errata@hlinkerratum{\the@errata@erratum}{\@errata@erratumname}}},
    listformats/actiondescription/.setStrKeyFmt={##1}{\newline ##1},
    %% Foot format
    footformats/description/.setStrKeyFmt={##1}{~(##1)},
    footformats/action/.setStrKeyFmt={##1}{~##1},
    footformats/actiondescription/.setStrKeyFmt={##1}{~##1},
    %% Action format
    actionformat/replace/.setStrKeyFmt={##1+##2}{##1 (original text was: ‘‘##2’’)},
    actionformat/add/.setStrKeyFmt={##1}{##1 (added)},
    actionformat/delete/.setStrKeyFmt={##1}{##1 (deleted)},
  },
  margintcolorboxformat/.style={
    marginfmt/marginnote/.setStrKeyFmt={##1+##2}{%
      {\vspace{-4pt}}%
    }
  }
}

```

```

        {\begin{tcolorbox}[size=fbox,nobeforeafter,
            colframe=red!50!white,colback=red!25!yellow!5!white,%
            leftrule=0pt,riglhrule=0pt,bottomrule=1pt,toprule=1pt,
            arc=0cm, outer arc=0mm, % Remove the rounded corners
            fontupper=\scriptsize,%
            code={\pgfkeysalsofrom##1}
            ]##2\end{tcolorbox}}},%
    },
    detailedlistandfootstyle/.code={%
        \errataSetListFormat{+erratumlistitem, +erratumlisttarget, +pageref, +action, +description, +date, +actiondescription}
        \errataSetFootFormat{+action, -description, :, +actiondescription}
    },
    detailedstylesetupcode/.code={%
        \newlength{\@errata@listindent}
        \setlength{\@errata@listindent}{33mm}
        \setlength{\@errata@groupindent}{16mm}
        \setcounter{@errata@uniquelistlabels}{3}
        \ifpackageloaded{tcolorbox}{\%
            \RequirePackage[most]{tcolorbox}
        }
        \AtBeginEnvironment{errata} {
            \setlist[description]{labelindent=0pt,labelwidth=\@errata@listindent,leftmargin=!}%
        }
    },
    styles/detailed/.style={detailedstylekeyformats, detailedlistandfootstyle,
        detailedstylesetupcode, margintcolorboxformat},
}
%%
%% END style: detailed
%%

```

Errata list table style definition

Define the tablelist style for formatting the errata list as a table

```

%%
\NewDocumentCommand{\errataamersand}{-}{&}
\NewDocumentCommand{\erratacustomhline}{-}{\\\hline }
\NewDocumentCommand{\erratacustomendline}{-}{\\}
\errataSet{
    liststyletablekeyformats/.style={%
        listformats/pageref/.setStrKeyFmt={##1}{\pageref{##1} },
        listformats/description/.setStrKeyFmt={##1}{##1},
        listformats/type/.setStrKeyFmt={##1}{Type: ##1},
        listformats/date/.setStrKeyFmt={##1}{ (Date reported: ##1)},
        listformats/reported-by/.setStrKeyFmt={##1}{Reported by: ##1},
        listformats/actiondescription/.setStrKeyFmt={##1}{ ##1},
        listformats/erratumlistitem/.setStrKeyFmt={##1}{},
        listformats/erratumlistitemtitle/.setStrKeyFmt={##1+##2}{%
            {\@errata@hlink{##1}{\protect\makebox[\@errata@groupindent][l]{##2}}}},
        listformats/onnewgroup/.setStrKeyFmt={##1}{\noexpand\erratacustomhline},
        listformats/onsamegroup/.setStrKeyFmt={##1}{\noexpand\erratacustomendline},
        listformats/erratalistbegin/.setStrKeyFmt={##1}{\makeatletter%
            \begin{longtable}{ c c c p{6cm} c }%

```

```

        & Title & Type & Action Desc & Page \\\hline%
    },
    listformats/erratalistend/.setStrKeyFmt={#1}{\end{longtable}\makeatother},
},
renewerrataenvfortable/.code={%
    \AtBeginDocument{%
        \renewenvironment{errata}{%
            \@errata@getformatted{listformats/erratalistbegin}{\@errata@tmp@erratalistbegin}%
            \@errata@tmp@erratalistbegin%
        }{\@errata@getformatted{listformats/erratalistend}{\@errata@tmp@erratalistend}%
            \@errata@tmp@erratalistend%
        }%
    },
    liststylefortable/.code={
        \errataSetListFormat{erratumlistitemtitle,+erratumlisttarget,\noexpand\errataamersand,%
            +erratumnamedlink,\noexpand\errataamersand,+action,\noexpand\errataamersand,%
            +actiondescription,\noexpand\errataamersand,+pageref}%
    },
    styles/tablelist/.style={liststyletablekeyformats, renewerrataenvfortable, liststylefortable},
}
%%
%% END style tablelist
%%

\input{erratastyles}
\erratareset{\errataapplystyles={\@errataOpt@styles}}
%%
\DeclareExpandableDocumentCommand{\@errata@htargetname}{ m } {errata#1}%
\DeclareExpandableDocumentCommand{\@errata@htargetlistname}{ m } {erratalist#1}%
\NewDocumentCommand{\@errata@hlink}{ m m } {#2}%
\NewDocumentCommand{\@errata@label}{ m } {\label{#1}}%
\NewDocumentCommand{\@errata@targeterratum}{ O{} m m } {\@errata@label{#1}#2}
\NewDocumentCommand{\@errata@hlinkerratum}{ m m } {\@errata@hlink{\@errata@htargetname{#1}}{#2}}
\NewDocumentCommand{\@errata@hlinkerratumlist}{ m m } {\@errata@hlink{\@errata@htargetlistname{#1}}{#2}}
%%
%% Enable internal linking if hyperref
\if@errataOpt@hyperref
\RenewDocumentCommand{\@errata@hlink}{ m m } {%
\protected@edef\@errata@expanded@arg{#1}%
\hyperlink{\@errata@expanded@arg}{#2}}%
%%
%% \@errata@htargeterratum
%% ARG1: Optional argument to indicate whether to add labels,
%% ARG2: The target name of the primary label/hyperlink
%% ARG3: The target name of the optional custom label
%% ARG4: The text to insert after the label/hypertarget
%% Hypertarget creates a hyper-link anchor, used to link to this location with \hyperlink
%% The label is needed for such as ref/pageref/cref
\RenewDocumentCommand{\@errata@htargeterratum}{ O{} O{} m m }{%
{\Hy@raisedlink{\hypertarget{#3}}}%
\@errata@isempty{#1}{% Add labels
\@errata@label{#3}% Primary label
\@errata@isnotempty{#2}{\@errata@label{#2}}% Seconday custom label
}{#4}}%

```

```
\fi
%%
```

Cleveref support

Code for cleveref support

```
\if@errataOpt@cleveref
\AtBeginDocument{%
  \Crefname{errata}{Err}{Errata}
  \crefname{errata}{err}{errata}
  \crefformat{errata}{Err(#2#1#3)}
  \Crefformat{errata}{Err(#2#1#3)}
}
\RenewDocumentCommand{\@errata@label}{ m } {%
  \protected@edef\@errata@expanded@arg{#1}\label[errata]{\@errata@expanded@arg}}%
\fi
%%
\NewDocumentCommand{\@errata@FormatKeywords}{ 0{ } m m m }{% key, keys/values, format-string
\@StrFmt@FormatKeywords[#1]{#2}{cmdkeys}{#3}{#4}%
}
%%
\newcounter{errata@lowerlabellim}
\setcounter{errata@lowerlabellim}{0}
%% Return true of the label name can be set
\newcommand\ifuniquelabeltest[1]{%
%% Current document class doesn't have chapters.
  \setcounter{errata@lowerlabellim}{#1}%
  \@ifundefined{thechapter}{%
    \stepcounter{errata@lowerlabellim}%
  }{}%
  \ifboolexpr{test {\ifnumcomp{\value{errata@uniquelistlabels}}{=}{0}} or test {\ifnumcomp{\value{errata@
%%
\DeclareExpandableDocumentCommand{\@errata@setlabelref}{ } {%
\@ifundefined{thechapter}{}%
  \ifnumcomp{\value{chapter}}{>}{0}{%
    \@errata@setvalue{labelname=\thechapter}%
    \@errata@setvalue{labelref={chapter.\thechapter}}%
  }{}%
}%
%% Check section
\@ifundefined{thesection}{}%
  \ifnumcomp{\value{section}}{>}{0}{%
    \@errata@setvalue{labelref={section.\thesection}}%
    \ifboolexpr{test {\ifuniquelabeltest{1}} }{\@errata@setvalue{labelname=\thesection}}{}%
    %% Check subsection
    \@ifundefined{thesubsection}{}%
      \ifnumcomp{\value{subsection}}{>}{0}{%
        \@errata@setvalue{labelref={subsection.\thesubsection}}%
        \ifboolexpr{test {\ifuniquelabeltest{2}} }{\@errata@setvalue{labelname=\thesubsection}}{}%
        %% Check subsubsection
        \@ifundefined{thesubsubsection}{}%
          \ifnumcomp{\value{subsubsection}}{>}{0}{%
            \@errata@setvalue{labelref={subsubsection.\thesubsubsection}}%
```

```

        \ifbool{test {\ifunique{labeltest}{3}} }{\@errata@setvalue{labelname=\thesubsubsection}}{}%
      }{}%
    }%
  }{}% END subsection
}% END subsection
}{}%
}% END section
}
%%

\erratumItem Macro for adding an item to the errata list
%% ARG1: Optional value to add to the end
%% ARG2: Item title
%% ARG2: errata-format-text
\DeclareDocumentCommand{\erratumItem}{ O{} m m } {%
  \@errata@getformatted{listformats/erratumlistitem}{#2}{\@errata@tmplistitem}%
  \@errata@tmplistitem#3#1%
}
%%

\printerrata Macro for inserting an existing errata list into the current document.
\DeclareDocumentCommand{\printerrata}{ O{-errata.tex} m } {%
  \IfFileExists{#2#1}{%
    \begin{errata}\input{#2#1}\end{errata}}{}%
  }

\PrintErrata Macro for inserting the errata list produced for the current document.
\DeclareDocumentCommand{\PrintErrata}{} {%
  \if@errata@opt@record\immediate\closeout\@errata@file\fi%
  \printerrata{\jobname}%
}

%%
\newcommand\ifdomargin[0]{
  \ifbool{bool{\@errata@opt@margin}} and test{\ifthenelse{\equal{\@errata@getvalue{cmdkeys/margin}}{true}}{true}}%
\newcommand\ifdofoot[0]{
  \ifbool{bool{\@errata@opt@foot}} and test{\ifthenelse{\equal{\@errata@getvalue{cmdkeys/foot}}{true}}{true}}%
\newcommand\ifdorecord[0]{
  \ifbool{bool{\@errata@opt@record}} and test{\ifthenelse{\equal{\@errata@getvalue{cmdkeys/record}}{true}}{true}}%
\newenvironment{errata}{\makeatletter%
\begin{description}}{\end{description}%
\makeatother
}
%%

erratum The erratum environment used for creating an extended errata.
\DeclareDocumentEnvironment{erratum}{ O{} m }% keys, explanation
{\@erratum@cmd}{#1}{action={Long errata}, description={#2}}%
\expandafter\@errata@htargeterratum{\@errata@htargetname{\the@errata@erratum}}{}%
\if@errata@opt@foot%
\footnotetext[\value{\@errata@erratum}]{\@errata@getvalue{footnotebegin} #2}%
\fi%
\protected@edef\@errata@tmp@marginargs{\@errata@getvalue{cmdkeys/marginargs}}%

```

```

\ifbool{test {\ifdomargin} }%
{\@errata@getformatted{errformats/eerrbeginfmt}{\@errata@hlinkerratumlist{\the@errata@erratum}{\arabic{errata@erratum}}}%
\errata@marginnote[\@errata@tmp@marginargs]{\@errata@tmp@fmtvalue}%
}%}%
\@errata@dorecord[\@errata@listformats]{\@errata@listformat}{\@errata@argsstring}%
\def\errata@add##1{[#1]$_a$}%
\def\errata@delete##1{\erratum@mark[$_d^{\@thefnmark}$\if@errata@opt@footnotes\@footnotetext{deleted: ##1}\fi}%
\def\errata@replace##1##2{\erratum@mark[##2]$_r^{\@thefnmark}$\if@errata@opt@footnotes\@footnotetext{was: ##1}\fi}%
\ignorespaces}%
\ifbool{test {\ifdomargin} }%
{\@errata@getformatted{errformats/eerrendfmt}{\@errata@hlinkerratumlist{\the@errata@erratum}{\arabic{errata@erratum}}}%
\errata@marginnote[\@errata@tmp@marginargs]{\@errata@tmp@fmtvalue}%
}%}%
}%%

%%
\def\erratum@mark{\stepcounter{erratum@note}}
\def\@thefnmark{\arabic{errata@erratum}:\arabic{erratum@note}}

```

```

\errata@message Write info to log file
\NewDocumentCommand{\errata@message}{ m } {% erratakeyvalues
\ifnum\value{errata@erratum}>0\typeout{}%
\typeout{This document contains \arabic{errata@erratum} Errata; see \jobname-errata.tex!}%
\typeout{}%
\fi}

```

```

\@errata@dorecord

\NewDocumentCommand{\@errata@dorecord}{ O{} m m m } {% formattype, listformat, argsstring
\ifbool{test {\ifdorecord} }{%
%% Get the formatted code for a new group
\ifbool{not test {\ifthenelse{\equal{\@errata@getvalue{cmdkeys/onnewgroup}}{}}}{%
{%
\@errata@getformatted{listformats/onnewgroup}{\@errata@labelname}{\@errata@tmp@ongroup}%
}%
{\@errata@getformatted{listformats/onsamegroup}{\@errata@labelname}{\@errata@tmp@ongroup}}}%
\@errata@FormatKeywords[errata@formatted@output]{#2}{#4}{#3}%
\errata@record[\@errata@tmp@ongroup]{\expandonce{\errata@formatted@output}}%
}%}%
}

```

```

\@errata@record Create an entry in the errata list produced by PrintErrata
\NewDocumentCommand{\@errata@record}{ O{} m } {% erratakeyvalues
\@errata@getformatted{errformats/errfmt}{\arabic{errata@erratum}}{\@errata@erratumname}%
\@errata@setvalue{cmdkeys/erratumlistitemtitle/.get=\@errata@tmp@itemtitle}%
\@errata@getformattede{listformats/erratumlistitemtitle}{\@errata@tmp@itemtitle}{\@errata@tmp@formatteditemtitle}%
\protected@write\errata@file{%
{\string\erratumItem[#1]{\@errata@tmp@formatteditemtitle}{#2}}%
}

\newif\if@errata@inbadenvironment
\newif\if@errata@inknownbadenvironment
%%
\NewDocumentCommand{\@erratum@checkenvironment}{-}{%
\@errata@inknownbadenvironmentfalse%

```

```

\@errata@inbadenvironmentfalse%
%%
\ifinner%
\@errata@inknownbadenvironmenttrue%
\fi%
\ifmmode%
\@errata@inknownbadenvironmenttrue%
\fi%
\ifthenelse{\equal{\@currenvir}{tcb@savebox}}%
{\@errata@inknownbadenvironmenttrue}%
}%
%%
\ifnumgreater{\value{@errata@environmenttestmode}}{0}%
{% At least 1, so lets consider any environment with \@capytype dangerous
\ifx\@capytype\undefined%
\else%
\@errata@inbadenvironmenttrue%
\fi%
\ifnumequal{\value{@errata@environmenttestmode}}{2}%
{%
\ifthenelse{\equal{\@currenvir}{document}}%
{{\@errata@inbadenvironmenttrue}%
}%}% End == 2
}%}% End > 0
}
\edef\emptyval{%
%% Create the margin note
\NewDocumentCommand{\@errata@marginnote}{O{\emptyval} m }{%
%% We use marginpar if we can, as it handles stacking multiple values vertically
\let\@errata@marginnote@cmd\marginpar%
%% If captype is defined, we're probably inside a float
\if@errata@inknownbadenvironment%
\let\@errata@marginnote@cmd\marginnote%
\fi
\if@errata@inbadenvironment%
\let\@errata@marginnote@cmd\marginnote%
\fi
%% If user provided argument 'usemarginnote', we use \marginnote macro
\protected@edef\@errata@tmp@marginshift{\@errata@getvalue{cmdkeys/usemarginnote}}%
\@errata@isnotempty{\@errata@tmp@marginshift}{%
\let\@errata@marginnote@cmd\marginnote%
\renewcommand*{\marginnoteadjust}{\@errata@tmp@marginshift}%
}%
\@errata@getformatted{marginfmt/marginnote}{\#1}+\#2}{\@errata@tmp@marginfmtvalue}%
\@errata@marginnote@cmd{\@errata@tmp@marginfmtvalue}%
}
%% Do the pagelayout of the errata (inline changes, margin, and footnote)
\NewDocumentCommand{\@errata@dolayoutonpage}{m m m m }{% type(a,r,d), original, change, errata-formatted-t
\ifbool{test {\ifdomargin}}%
{\@errata@getformatted{errformats/errfmt}{\@errata@hlinkerratumlist{\the@errata@erratum}}{\arabic{@errata@err
\protected@edef\@errata@tmp@marginargs{\@errata@getvalue{cmdkeys/marginargs}}%
\@errata@marginnote[\@errata@tmp@marginargs]{\@errata@tmp@marginfmtvalue}%
}%}%

```



```

%% Handle inline changes
\ifbool{bool{\errataOpt@inlinechanges} and
  test {\ifthenelse{\equal{\errata@getvalue{cmdkeys/inlinechange}}{true}}}{true}} }%
  {% Make inline change
  %%\errata@setvalues{lastcommandinlinevalue={#3}, inlinevalue={#3}}
  \errata@setvalue{lastcommandinlinevalue={#3}}%
  \errata@setvalue{inlinevalue={#3}}%
  }%
  {% Use original value
  \errata@setvalue{lastcommandinlinevalue={#2}}%
  \errata@setvalue{inlinevalue={#2}}%
  }%
  %% If trying to set lastcommandinlinevalue=inlinevalue here with
  %% (\errata@setvalue{lastcommandinlinevalue=\errata@getvalue{inlinevalue}}),
  %% it adds an unwanted space to lastcommandinlinevalue for some reason. Therefore,
  %% both lastcommandinlinevalue and inlinevalue are set to the same value separately.
  %%
  \ifbool{bool{\errataOpt@inlinemarks} and
    test {\ifthenelse{\equal{\errata@getvalue{cmdkeys/inlinemark}}{true}}}{true}} }%
    {% Use add inlinemark
    \errata@setvalue{lastcommandinlinevalue={[]}}%
    \errata@setvalue{inlinevalue/.prefix={[]}}%
    \errata@setvalue{inlinevalue/.append={\ensuremath{_{#1}\arabic{\errata@erratum}}}}}%
    }{%
    \protected@edef\errata@tmp@dolabel{}%
    \ifmode% In math mode, we can't add a label
    \eappto\errata@tmp@dolabel{nolabel}%
    \fi%
    \errata@htargeterratum[\errata@tmp@dolabel][\errata@getvalue{cmdkeys/label}]{\errata@htargetname{\theerratum}}%
    %%
    \ifbool{test {\ifdofoot}} }{%
      \protected@edef\errata@tmp@footprefix{\arabic{\errata@getvalue{footnoteprefix}}}% Expand the formatting
      \expandafter\footnotetext\expandafter[\errata@tmp@footprefix]%
      {\errata@getvalue{footnotebegin}}%
      \errata@isnotempty{#4}{#4}%
    }{%
    }%
    }%
    %%
    \NewDocumentCommand{\erratum@cmdinit}{}{}%
    \erratum@setprevispace% Handle if there was a previous white space glue
    \erratum@checkenvironment%
  }
  %% ARG1: cmddefaultargs string
  %% ARG2: Key/Args from cmd
  %% ARG3: extra Key/Args
  \NewDocumentCommand{\erratum@cmd}{ m m m } {%
    \refstepcounter{\errata@erratum}%
    \errata@setcmdkeys[\errata@formatkeys]% Reset all values
    %% Apply the default args
    \errata@setvalues[cmdkeys/]{defaultargs, #1}%
    %%
    \errata@setvalue{cmdkeys/uselabel={\errata@htargetname{\theerrata@erratum}}}%
    \errata@getformatted{errformats/errfmt}{\arabic{\errata@erratum}}{\errata@erratumname}%
  }

```

```

\errata@setvalue{cmdkeys/erratumname/.expand once=\errata@erratumname}%
%%
\errata@setvalues[cmdkeys/]{#2, #3}%
\errata@setvalues{cmdkeys/actionid/.get=\errata@tmp@actionid}%
%% Set 'action' and 'actiondescription' based on actionid
\errata@isnotempty{\errata@tmp@actionid}{%
  \errata@setvalues{cmdkeys/actionargs/.get=\errata@tmp@actionargs}%
  \errata@getformattede{actionformat/\errata@tmp@actionid}{\errata@tmp@actionargs}{\errata@tmp@tmpfmtvalue}%
  \errata@setvalues[cmdkeys/]{actiondescription/.expanded={\errata@tmp@tmpfmtvalue}}%
  \errata@getformattede{actionidformat/\errata@tmp@actionid}{\errata@tmp@tmpfmtvalue}%
  \errata@setvalues[cmdkeys/]{action/.expanded={\errata@tmp@tmpfmtvalue}}%
}%
%% Define macro for the args string
\protected@edef\errata@argsstring{#2}%
\errata@isnotempty{\errata@argsstring}{%
  \eappto\errata@argsstring{, }%
}%
\errata@setvalue{prevlabel=\errata@labelname}%
\errata@setlabelref{}%
\ifboolexpr{ test {\ifdorecord} }{%
  %% Compare current label with previous. Print only if not already printed
  \ifnumcomp{\value{\errata@uniquelistlabels}}{>}{0}%
  {% True
    \ifthenelse{\expandafter\equal{\errata@lastuniquelabel}{\errata@labelname}}%
    {\errata@setvalue{labelname={}}}% Hide the label, if it equals the previous label
    {\errata@setvalue{cmdkeys/onnewgroup={}}}%
  }%
  {\errata@setvalue{prevlabel/.expanded=\errata@labelname}%
    \errata@setvalue{cmdkeys/onnewgroup/.expanded=\errata@labelname}%
  }%
  \errata@setvalue{lastuniquelabel/.expanded=\errata@labelname}%
  {\errata@setvalue{prevlabel=\errata@labelname}}%
}%}%
%%
\errata@setvalue{cmdkeys/erratumlistitemtitle={\errata@getvalue{labelref}}+\errata@labelname}}%
\errata@setvalue{cmdkeys/erratumnamedlink/.expand once={\errata@getvalue{labelref}}+\errata@erratumname}%
\protected@eappto\errata@argsstring{#3}%
%% Add action description
\protected@eappto\errata@argsstring{, actiondescription={\errata@getvalue{cmdkeys/actiondescription}}}%
\protected@eappto\errata@argsstring{, action={\errata@getvalue{cmdkeys/action}}}%
%% Handle pageref reference
\errata@isnotempty{\errata@getvalue{cmdkeys/uselabel}}{%
  \protected@eappto\errata@argsstring{, pageref={\errata@getvalue{cmdkeys/uselabel}}}%
}%
\protected@eappto\errata@argsstring{, erratumlistitemtitle={\errata@getvalue{cmdkeys/erratumlistitemtitle}}}%
\protected@eappto\errata@argsstring{, erratumnamedlink={\errata@getvalue{cmdkeys/erratumnamedlink}}}%
%% Set the link target for this errata in the errata list (erratalist<number>)
\xappto\errata@argsstring{, erratumlisttarget={\errata@htargetlisttname{\the\errata@erratum}}}%
}
%%
%% Macros for handling spacing
%%
\newcommand\ifstrequalexpand{\expandafter\ifstrequal\expandafter}%

```

```

%%
%% Handle if space after macro call should be ignored
\NewDocumentCommand{\@erratum@handleprevisspace}{-}{%
\ifhmode%
\ifbool{expr{ bool \@errata@prevspace} and test {\ifstrequal{expand{\lastcommandinlinevalue}}{}} }{%
\ignorespaces}{-}%
\fi%
}
%%
\newif\if@errata@prevspace
%%
\NewDocumentCommand{\@erratum@setprevspace}{-}{%
\ifhmode%
\ifdim \lastskip=\z@%
\@errata@prevspacefalse%
\else%
\@errata@prevspace true%
\fi%
\fi%
}

```

User commands for registering errata changes

`\erratumAdd` Macro for creating an Addition

```

\NewDocumentCommand{\@erratum@Add}{0}{m}{-}{% keyvals, new
\@erratum@cmdinit%
{% Group is necessary here to handle cref reference format for label type '@errata@erratum'.
%% \@erratum@cmd must be within the group, as pgfkeys are group local
\@erratum@cmd{defaultargsadd}{#1}{actionid={add}, actionargs={#2}}%
\@errata@dolayoutonpage{a}{-}{#2}{\@errata@FormatKeywords{footformats}}{\@errata@argsstring}{\@errata@footform
\@errata@dorecord[\]{listformats}}{\@errata@listformat}{\@errata@argsstring}%
}%
%% Handle if the space after the macro call should be ignored
\@erratum@handleprevisspace%
}

```

`\erratumReplace` Macro for creating a Replacement

```

\NewDocumentCommand{\@erratum@Replace}{0}{m m}{-}{% keyvals, old, new
\@erratum@cmdinit%
{% Group is necessary here to handle cref reference format for label type '@errata@erratum'.
%% \@erratum@cmd must be within the group, as pgfkeys are group local
\@erratum@cmd{defaultargsreplace}{#1}{actionid={replace}, actionargs={#3+#2}}%
\@errata@dolayoutonpage{r}{-}{#2}{#3}{\@errata@FormatKeywords{footformats}}{\@errata@argsstring}{\@errata@footf
\@errata@dorecord[\]{listformats}}{\@errata@listformat}{\@errata@argsstring}%
}%
%% Handle if the space after the macro call should be ignored
\@erratum@handleprevisspace%
}

```

`\erratumDelete` Macro for creating a Deletion

```

\NewDocumentCommand{\@erratum@Delete}{0}{m}{-}{% keyvals, removed
\@erratum@cmdinit%
{% Group is necessary here to handle cref reference format for label type '@errata@erratum'.

```

```

%% \@erratum@cmd must be within the group, as pgfkeys are group local
\@erratum@cmd{defaultargsdelete}{#1}{actionid={delete}, actionargs={#2}}%
\@errata@dolayoutonpage{d}{#2}{\@errata@FormatKeywords{footformats}{\@errata@argsstring}{\@errata@footform
\@errata@dorecord[\]{listformats}{\@errata@listformat}{\@errata@argsstring}%
}%
\@erratum@handleprevisspace%
}

\erratumNote Macro for creating a Note entry

\NewDocumentCommand{\@erratum@Note}{0}{m}{% keyvals, message
\@erratum@cmdinit%
{% Group is necessary here to handle cref reference format for label type '@errata@erratum'.
%% \@erratum@cmd must be within the group, as pgfkeys are group local
\@erratum@cmd{defaultargsnote}{#1}{actionid={note}, actionargs={#2}}%
\@errata@dolayoutonpage{n}{#2}{\@errata@FormatKeywords{footformats}{\@errata@argsstring}{\@errata@footform
\@errata@dorecord[\]{listformats}{\@errata@listformat}{\@errata@argsstring}%
}%
%% Handle if the space after the macro call should be ignored
\@erratum@handleprevisspace%
}

%% Define with mandatory description argument if the requirecmddescription option is true
\if@errata@opt@requirecmddescription
\NewDocumentCommand{\erratumAdd}{0}{m m}{% keyvals, description, new
\@erratum@Add[#1,description={#2}]{#3}}%
\NewDocumentCommand{\erratumReplace}{0}{m m m}{% keyvals, description, old, new
\@erratum@Replace[#1,description={#2}]{#3}{#4}}%
\NewDocumentCommand{\erratumDelete}{0}{m m}{% keyvals, description, removed
\@erratum@Delete[#1,description={#2}]{#3}}%
\NewDocumentCommand{\erratumNote}{0}{m m}{% keyvals, description, note
\@erratum@Note[#1,description={#2}]{#3}}%
%% And define without description if the requirecmddescription option is false
\else
\let\erratumDelete\@erratum@Delete
\let\erratumAdd\@erratum@Add
\let\erratumReplace\@erratum@Replace
\let\erratumNote\@erratum@Note
\fi

```

9 The Errata of this Document

3.1 forgotten word

3.1 superfluous phrase

3.1 translated

3.2 old should be new

7.1 label

7.2 added comma

7.2 added another comma

7.2 added missing word

7.2 added another missing word

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

Symbols	erratumlisttarget key . . . 7	marginargs 5
\@errata@dorecord	\erratumNote 4, 28, 28	marginfmt/marginnote . 7
. 23, 23, 27, 28	\erratumReplace . . 4, 27, 28	marginnote 2
\@errata@record 23, 23		margins 1
	F	pageref 6
A	foot key 5	record 2
action key 6	foots key 2	reported-by 6
actiondescription key . . . 6	foots (pkgoption) 13	requirecmddescription
	 2
C	H	show 1
cleveref key 2	hide key 1	styles 2
cleveref (pkgoption) 13	hide (pkgoption) 13	type 6
	hyperref key 2	uselabel 5
D	hyperref (pkgoption) 13	usemarginnote 5
date key 6		
defaultargs key 3	I	L
defaultargs (pkgoption) . . 14	inlinechange key 5	label key 5
defaultargsadd key 3	inlinechanges key 2	location key 6
defaultargsadd (pkgoption) 14	inlinechanges (pkgoption) 14	
defaultargsdelete key . . . 3	inlinemark key 5	M
defaultargsdelete (pkgoption) 14	inlinemarks key 2	margin key 5
defaultargsnote key 3	inlinemarks (pkgoption) . . 14	marginargs key 5
defaultargsnote (pkgoption) 14		marginfmt/marginnote key . 7
defaultargsreplace key . . . 3	K	marginnote key 2
defaultargsreplace (pkgoption) 14	Keys	marginnote (pkgoption) . . 13
description key 6	action 6	margins key 1
	actiondescription 6	margins (pkgoption) 13
E	cleveref 2	
environments:	date 6	P
errata 9	defaultargs 3	package options:
erratum 4, 22	defaultargsadd 3	cleveref 13
environmenttestmode	defaultargsdelete 3	defaultargs 14
(pkgoption) 14	defaultargsnote 3	defaultargsadd 14
errata (environment) 9	defaultargsreplace 3	defaultargsdelete . . . 14
\erratamessage 9	description 6	defaultargsnote 14
\errataSetFootFormat 7	erratumlistitem 6	defaultargsreplace . . 14
\errataSetKeyFormat 7, 16, 16	erratumlistitemtitle . . . 6	environmenttestmode . 14
\errataSetListFormat 7	erratumlisttarget 7	foots 13
\erratamessage 23	foot 5	hide 13
erratum (environment) . . . 4, 22	foots 2	hyperref 13
\erratumAdd 3, 27, 28	hide 1	inlinechanges 14
\erratumDelete 3, 27, 28	hyperref 2	inlinemarks 14
\erratumItem 9, 22, 23	inlinechange 5	marginnote 13
erratumlistitem key 6	inlinechanges 2	margins 13
erratumlistitemtitle key . 6	inlinemark 5	record 13
	inlinemarks 2	requirecmddescription
	label 5 13
	location 6	show 13
	margin 5	styles 14

<code>uniquelistlabels</code> 14	<code>requirecmddescription</code>	T
<code>pageref</code> key 6	key 2	<code>type</code> key 6
<code>\PrintErrata</code> 8 , 22	<code>requirecmddescription</code>	
<code>\printerrata</code> 8 , 22 , 22	(pkgoption) 13	U
R	S	<code>uniquelistlabels</code> (pkgop-
<code>record</code> key 2	<code>show</code> key 1	tion) 14
<code>record</code> (pkgoption) 13	<code>show</code> (pkgoption) 13	<code>uselabel</code> key 5
<code>reported-by</code> key 6	<code>styles</code> key 2	<code>usemarginnote</code> key 5
	<code>styles</code> (pkgoption) 14	

Change History

v0.1		defaultargs package option added . . .	14
General: First Version with Documenta-		defaultargsadd package option added	14
tion	1	defaultargsdelete package option added	14
v0.2		defaultargsreplace package option	
General: More Documentation and Key-		added	14
words Management	1	environmenttestmode package option	
v0.3		added	13
General: adding type Keyword	1	hyperref package option added	13
v0.4		inlinechanges package option added . .	14
General: moved to GIT, fixing switches . .	1	inlinemarks package option added . . .	14
v1.0		marginnote package option added . . .	13
General: Added support for links with hy-		requirecmddescription package option	
perref, and customization through for-		added	13
matters	1	styles package option added	14
cleveref package option added	13	uniquelistlabels package option added	14