

# Slides and Course Notes for Jacobs University\*

Michael Kohlhasse  
Jacobs University, Bremen  
<http://kwarc.info/kohlhasse>

October 22, 2015

## Abstract

We present a document class from which we can generate both course slides and course notes in a transparent way. Furthermore, we present a set of  $\text{\LaTeX}$ XML bindings for these, so that we can also generate OMDoc-based course materials, e.g. for inclusion in the ACTIVEMATH system.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>The User Interface</b>	<b>2</b>
2.1	Package Options . . . . .	2
2.2	Notes and Slides . . . . .	2
2.3	Header and Footer Lines . . . . .	3
2.4	Colors and Highlighting . . . . .	3
2.5	Front Matter, Titles, etc . . . . .	3
2.6	Miscellaneous . . . . .	3
2.7	Support for MathHub . . . . .	3
<b>3</b>	<b>Limitations</b>	<b>4</b>
<b>4</b>	<b>The Implementation</b>	<b>5</b>
4.1	Initialization and Class Options . . . . .	5
4.2	Notes and Slides . . . . .	7
4.3	Header and Footer Lines . . . . .	10
4.4	Colors and Highlighting . . . . .	11
4.5	Front Matter, Titles, etc . . . . .	13
4.6	Sectioning . . . . .	14
4.7	Miscellaneous . . . . .	15
4.8	Support for MathHub . . . . .	17
4.9	Finale . . . . .	17

---

\*Version ? (last revised ?)

# 1 Introduction

This Document class is derived from `beamer.cls` [Tana], specializes it with Jacobs stuff and adds a notes version that is more suited to printing than the one supplied by `beamer.cls`.

## 2 The User Interface

The `mikoslides` class takes the notion of a slide frame from Till Tantau's excellent `beamer` class and adapts its notion of frames for use in the `STEX` and `OMDoc`. To support semantic course notes, it extends the notion of mixing frames and explanatory text, but rather than treating the frames as images (or integrating their contents into the flowing text), the `mikoslides` package displays the slides as such in the course notes to give students a visual anchor into the slide presentation in the course (and to distinguish the different writing styles in slides and course notes).

In practice we want to generate two documents from the same source: the slides for presentation in the lecture and the course notes as a narrative document for home study. To achieve this, the `mikoslides` class has two modes: *slides mode* and *notes mode* which are determined by the package option.

### 2.1 Package Options

The `mikoslides` class takes a variety of class options:<sup>1</sup>

- The options `slides` and `notes` switch between slides mode and notes mode (see Section 2.2).
- If the option `sectocframes` is given, then special frames with section table of contents are produced headers<sup>2</sup>
- `showmeta`. If this is set, then the metadata keys are shown (see [Koh15] for details and customization options).
- If the option `frameimages` is set, then slide mode also shows the `\frameimage`-generated frames.

### 2.2 Notes and Slides

Slides are represented with the `frame` just like in the `beamer` class, see [Tanb] for details. The `mikoslides` class adds the `note` environment for encapsulating the course note fragments.<sup>1</sup>

 Note that it is essential to start and end the `notes` environment at the start of the line – in particular, there may not be leading blanks – else `LATEX` becomes confused and throws error messages that are difficult to decipher.

<sup>1</sup>EDNOTE: leaving out `noproblems` for the moment until we decide what to do with it.

<sup>2</sup>EDNOTE: document the functionality

<sup>1</sup>MK: it would be very nice, if we did not need this environment, and this should be possible in principle, but not without intensive `LaTeX` trickery. Hints to the author are welcome.

```

\begin{note}
  We start this course with ...
\end{note}

\begin{frame}
  \frametitle{The first slide}
  ...
\end{frame}
\begin{note}
  ... and more explanatory text
\end{note}

\begin{frame}
  \frametitle{The second slide}
  ...
\end{frame}
...

```

**Example 1:** A typical Course Notes File

By interleaving the `frame` and `note` environments, we can build course notes as shown in Figure 1.

Sometimes, we want to integrate slides as images after all – e.g. because we already have a PowerPoint presentation, to which we want to add `STEXnotes`. In this case we can use `\frameimage[⟨opt⟩]{⟨path⟩}`, where `⟨opt⟩` are the options of `\includegraphics` from the `graphicx` package [CR99] and `⟨path⟩` is the file path (extension can be left off like in `\includegraphics`).

`\frameimage`

## 2.3 Header and Footer Lines

## 2.4 Colors and Highlighting

`\textwarning` The `\textwarning` macro generates a warning sign: 

## 2.5 Front Matter, Titles, etc

## 2.6 Miscellaneous

## 2.7 Support for MathHub

Much of the `STEX` content is hosted on MathHub (<http://MathHub.info>), a portal and archive for flexiformal mathematics. MathHub offers GIT repositories (public and private escrow) for mathematical documentation projects, online and offline authoring and document development infrastructure, and a rich, interactive reading interface. The `modules` package supports repository-sensitive operations on MathHub.

Note that **MathHub** has two-level repository names of the form  $\langle group \rangle / \langle repo \rangle$ , where  $\langle group \rangle$  is a **MathHub**-unique repository group and  $\langle repo \rangle$  a repository name that is  $\langle group \rangle$ -unique. The file and directory structure of a repository is arbitrary – except that it starts with the directory **source** because they are Math Archives in the sense of [Hor+11]. But this structure can be hidden from the  $\text{\texttt{\textbackslash STeXauthor}}$  with **MathHub**-enabled versions of the **modules** macros.

**\mhframeimage** The **\mhframeimage** macro is a variant of **\frameimage** with repository support. Instead of writing

```
\defpath{MathHub}{/user/foo/lmh/MathHub}
\frameimage{\MathHub{fooMH/bar/source/baz/foobar}}
```

we can simply write (assuming that **\MathHub** is defined as above)

```
\mhframeimage[fooMH/bar]{baz/foobar}
```

Note that the **\mhframeimage** form is more semantic, which allows more advanced document management features in **MathHub**.

If **baz/foobar** is the “current module”, i.e. if we are on the **MathHub** path **...MathHub/fooMH/bar...**, then stating the repository in the first optional argument is redundant, so we can just use

```
\mhframeimage{baz/foobar}
```

Of course, neither  $\text{\texttt{\textbackslash LATEX}}$  nor  $\text{\texttt{\textbackslash LATEXML}}$  know about the repositories when they are called from a file system, so we can use the **\mhcurrentrepos** macro from the **modules** package to tell them. But this is only needed to initialize the infrastructure in the driver file. In particular, we do not need to set it in each module, since the **\importmhmodule** macro sets the current repository automatically.

**Caveat** if you want to use the **MathHub** support macros (let’s call them **mh**-variants), then every time a module is imported or a document fragment is included from another repos, the **mh**-variant **\importmhmodule** must be used, so that the “current repository” is set accordingly. To be exact, we only need to use **mh**-variants, if the imported module or included document fragment use **mh**-variants.

### 3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the  $\text{\texttt{\textbackslash STEXGitHub}}$  repository [sTeX].

1. the class should be divided into concerns. [sTeX:online], issue 1684
2. when option **book** or **report** is given together with **sectocframes** chapter-level omgroups generate a spurious slide with a bare heading. This has something to do with the fact that beamer does not support **\chapter**

## 4 The Implementation

The `mikoslides` package generates two files: the  $\text{\LaTeX}$  package (all the code between `\package` and `\endpackage`) and the  $\text{\LaTeX}$ XML bindings (between `\beginltxml` and `\endltxml`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

### 4.1 Initialization and Class Options

For the  $\text{\LaTeX}$ XML bindings, we make sure the right perl packages are loaded.

```
1 \ltxml.cls | ltxml.sty
2 # -*- CPERL -*-
3 package LaTeXXML::Package::Pool;
4 use strict;
5 use LaTeXXML::Package;
6 \ltxml.cls | ltxml.sty
7 \ltxml.cls
8 DeclareOption('notes', '');
9 DeclareOption('slides', '');
10 DeclareOption('nopproblems', '');
11 DeclareOption('sectocframes', '');
12 DeclareOption('frameimages', '');
13 DeclareOption('report', sub {PassOptions('omdoc','cls',ToString(Digest(T_CS('\CurrentOption'))));
14 DeclareOption('book', sub {PassOptions('omdoc','cls',ToString(Digest(T_CS('\CurrentOption'))));
15 DeclareOption(undef, sub {PassOptions('omdoc','cls',ToString(Digest(T_CS('\CurrentOption'))));
16 PassOptions('beamer','cls',ToString(Digest(T_CS('\CurrentOption'))));
17 DeclareOption(undef, sub {PassOptions('mikoslides','sty',ToString(Digest(T_CS('\CurrentOption'))));
18 \ltxml.cls
19 \ltxml.sty
20 DeclareOption('showmeta', sub {PassOptions('metakeys','sty',ToString(Digest(T_CS('\CurrentOption'))));
21 DeclareOption('defindex', sub {PassOptions('statements','sty',ToString(Digest(T_CS('\CurrentOption'))));
22 \ltxml.sty
23 \ltxml.cls | ltxml.sty
24 ProcessOptions();
25 \ltxml.cls | ltxml.sty
```

For  $\text{\LaTeX}$  we define some Package Options and switches for the `mikoslides` class and activate them by passing them on to `beamer.cls` the appropriate packages.

```
26 \cls
27 \newif\ifnotes\notesfalse
28 \DeclareOption{notes}{\notestruetrue}
29 \DeclareOption{slides}{\notestruetrue}
30 \newif\ifsectocframes\sectocframesfalse
31 \DeclareOption{sectocframes}{\sectocframestrue}
32 \newif\ifframeimages\frameimagesfalse
33 \DeclareOption{frameimages}{\frameimagestrue}
34 \newif\if@part\@partfalse
```

```

35 \DeclareOption{report}{\@parttrue\PassOptionsToClass{\CurrentOption}{omdoc}}
36 \DeclareOption{book}{\@parttrue\PassOptionsToClass{\CurrentOption}{omdoc}}
37 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{omdoc}}
38 \PassOptionsToClass{\CurrentOption}{beamer}}
39 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{mikoslides}}
40 \</cls>
41 \<*package>
42 \DeclareOption{showmeta}{\PassOptionsToPackage{\CurrentOption}{metakeys}}
43 \DeclareOption{defindex}{\PassOptionsToPackage{\CurrentOption}{statements}}
44 \newif\ifnotes\notesfalse
45 \DeclareOption{notes}{\notesttrue}
46 \DeclareOption{slides}{\notesfalse}
47 \newif\ifproblems\problemstrue
48 \DeclareOption{nopproblems}{\problemsfalse}
49 \DeclareOption*{}% accept anything
50 \</package>
51 \<cls | package>\ProcessOptions
52 \<*ltxml.sty>
53 RawTeX('newif\ifnotes\notesfalse');
54 RawTeX('newif\ifproblems\problemsfalse');
55 \</ltxml.sty>

```

Depending on the options, we either load the `article`-based `omdoc` or the `beamer` class. In the first case, we also have to make the `beamer`-specific things available to `article` via the `beamerarticle` package. We use options to avoid loading theorem-like environments, since we want to use our own from the `TeX` packages.

```

56 \<cls>
57 \ifnotes
58 \LoadClass{omdoc}
59 \RequirePackage{a4wide}
60 \RequirePackage{marginnote}
61 \RequirePackage{mdframed}
62 \RequirePackage[notheorems,noamsthm,noxcolor]{beamerarticle}
63 \else
64 \LoadClass[notheorems,noamsthm,10pt]{beamer}
65 \newcounter{Item}
66 \newcounter{paragraph}
67 \newcounter{subparagraph}
68 \newcounter{Hfootnote}
69 \usetheme{Jacobs}
70 \fi
71 \RequirePackage{mikoslides}
72 \</cls>
73 \<*ltxml.cls>
74 LoadClass('omdoc');
75 RequirePackage('mikoslides');
76 RequirePackage('tikzinput');
77 DefConstructor('usetheme{'','');
78 \</ltxml.cls>

```

now, we load the remaining packages for both versions.<sup>3</sup>

```

79 <*package>
80 \RequirePackage{stex}
81 \RequirePackage{tikzinput}
82 \RequirePackage{latexml}
83 \RequirePackage{amssymb}
84 \usepgflibrary{shapes}
85 \usetikzlibrary{arrows}
86 \usetikzlibrary{positioning}
87 \usetikzlibrary{tikzmark}%experimental/beta but very useful
88 \usetikzlibrary{fit}
89 \RequirePackage{url}
90 \RequirePackage{amsmath}
91 \RequirePackage{comment}
92 \RequirePackage{standalone}
93 \RequirePackage{textcomp}
94 </package>
95 <*ltxml.sty>
96 \RequirePackage('stex');
97 \RequirePackage('latexml');
98 \RequirePackage('amssymb');
99 \RequirePackage('graphicx');
100 \RequirePackage('tikz');
101 \RequirePackage('url');
102 \RequirePackage('amsmath');
103 </ltxml.sty>

```

## 4.2 Notes and Slides

We define the sizes of slides in the notes. Somehow, we cannot get by with the same here.

```

104 <*package>
105 \newcounter{slide}
106 \newlength{\slidewidth}\setlength{\slidewidth}{12.8cm}
107 \newlength{\slideheight}\setlength{\slideheight}{9cm}
108 </package>
109 <*ltxml.sty>
110 \DefRegister('\slidewidth'      => Dimension('13.6cm'));
111 \DefRegister('\slideheight'    => Dimension('9cm'));
112 </ltxml.sty>

```

**note** The `note` environment is used to leave out text in the `slides` mode. It does not have a counterpart in OMDoc. So for course notes, we define the `note` environment to be a no-operation otherwise we declare the `note` environment as a comment via the `comment` package.

```

113 <*package>

```

---

<sup>3</sup>EDNOTE: MK: eventually (when tikz support is fully realized in  $\text{\LaTeX ML}$ ) get rid of the standalone package

```

114 \ifnotes%
115   \renewenvironment{note}{%
116     \ignorespaces%
117   }{}%
118 \else%
119   \excludecomment{note}%
120 \fi%
121 \</package>
122 \< *!xml.sty>
123 DefEnvironment('{note}', '#body');
124 \</!xml.sty>

```

We start by giving the L<sup>A</sup>T<sub>E</sub>XML binding for the `frame` environment from the `beamer` class. We first set up the slide boxes in `article` mode. We set up sizes and provide a box register for the frames and a counter for the slides.

```

125 \< *package>
126 \ifnotes
127   \newlength{\slideframewidth}
128   \setlength{\slideframewidth}{1.5pt}

```

**frame** We first define the keys.

```

129   \addmetakey{frame}{label}
130   \addmetakey[yes]{frame}{allowframebreaks}
131   \addmetakey{frame}{allowdisplaybreaks}
132   \addmetakey[yes]{frame}{fragile}
133   \addmetakey[yes]{frame}{shrink}
134   \addmetakey[yes]{frame}{squeeze}

```

We redefine the `itemize` environment so that it looks more like the one in `beamer` with `Jacobs` theme. We create the box with the `mdframed` environment from the `equinymous` package. Then we define the environment, read them, and construct the slide number and label.

```

135   \renewenvironment{frame}[1] []{%
136     \metasetkeys{frame}{#1}%
137     \stepcounter{slide}%
138     \def\@currentlabel{\theslide}%
139     \ifx\frame@label\@empty%
140     \else%
141       \label{\frame@label}%
142     \fi%

```

We redefine the `itemize` environment so that it looks more like the one in `beamer` with `Jacobs` theme.

```

143   \def\itemize@level{outer}%
144   \def\itemize@outer{outer}%
145   \def\itemize@inner{inner}%
146   \renewcommand\newpage{}%
147   \renewcommand\metakeys@show@keys[2]{\marginnote{\scriptsize ##2}}%
148   \renewenvironment{itemize}{%
149     \ifx\itemize@level\itemize@outer%

```



```

150     \def\itemize@label{$\rhd$}%
151     \fi%
152     \ifx\itemize@level\itemize@inner%
153         \def\itemize@label{$\scriptstyle\rhd$}%
154         \fi%
155     \begin{list}%
156     {\itemize@label}%
157     {\setlength{\labelsep}{.3em}%
158     \setlength{\labelwidth}{.5em}%
159     \setlength{\leftmargin}{1.5em}%
160     }%
161     \edef\itemize@level{\itemize@inner}%
162 }{%
163     \end{list}%
164 }%

```

We create the box with the `mdframed` environment from the `equinymous` package.

```

165     \begin{mdframed}[linewidth=\slideframewidth,skipabove=1ex,skipbelow=1ex,userdefinedwidth=\s
166     ]{%
167         \medskip\miko@slidelabel\end{mdframed}%
168     }%
169 \end{package}
170 \ltxml.sty
171 DefEnvironment('frame')[],
172     "<omdoc:omgroup layout='slide'>"
173     . "#body\n"
174     . "</omdoc:omgroup>\n\n",
175 afterDigestBegin=>sub {
176     $_[1]->setProperty(theory=>LookupValue('current_module')); });
177 \ltxml.sty)#$

```

Now, we need to redefine the `frametitle` (we are still in course notes mode).

`\frametitle`

```

178 \package
179 \renewcommand{\frametitle}[1]{\Large\bf\sf\color{blue}{#1}}\medskip}%
180 \fi %ifnotes
181 \end{package}
182 \ltxml.sty
183 DefConstructor('\frametitle{}',
184     "\n<omdoc:metadata><dc:title>#1</dc:title></omdoc:metadata>");
185 \ltxml.sty

```

`\frameimage`

We have to make sure that the width is overwritten, for that we check the `\Gin@ewidth` macro from the `graphicx` package<sup>4</sup>

```

186 \package
187 \newrobustcmd\frameimage[2][{}%
188     \stepcounter{slide}%

```

---

<sup>4</sup>EDNOTE: MK@DG; we need to do that in the LaTeXML binding as well!

```

189 \iffameimages%
190 \def\Gin@ewidth{}\setkeys{Gin}{#1}%
191 \ifnotes%
192 \else%
193 \vfill%
194 \fi%
195 \ifx\Gin@ewidth\@empty%
196 \mycgraphics[width=\slidewidth,#1]{#2}\else\mycgraphics[#1]{#2}%
197 \fi%
198 \par\strut\hfill{\footnotesize Slide \arabic{slide}}}%
199 \ifnotes%
200 \else%
201 \vfill%
202 \fi%
203 \fi%
204 }% iffameimages
205 \</package>
206 \<*ltxml.sty>
207 DefMacro(' \frameimage[]{}', '\@frameimage{\includegraphics[#1,width=\slidewidth]{#2}}');
208 DefConstructor(' \@frameimage{}', "<omdoc:omgroup layout='slide'>#1</omdoc:omgroup>\n");
209 \</ltxml.sty>

```

### 4.3 Header and Footer Lines

Now, we set up the infrastructure for the footer line of the slides, we use boxes for the logos, so that they are only loaded once, that considerably speeds up processing.

```

\setslidelogo The default logo is the logo of Jacobs University. Customization can be done by
\setslidelogo{\logo name}.
210 \<*package>
211 \newlength{\slidelogoheight}
212 \ifnotes%
213 \setlength{\slidelogoheight}{.4cm}%
214 \else%
215 \setlength{\slidelogoheight}{1cm}%
216 \fi%
217 \newsavebox{\slidelogo}%
218 \sbox{\slidelogo}{\includegraphics[height=\slidelogoheight]{jacobs-logo}}%
219 \newrobustcmd{\setslidelogo}[1]{%
220 \sbox{\slidelogo}{\includegraphics[height=\slidelogoheight]{#1}}%
221 }%

\setsource \source stores the writer's name. By default it is Michael Kohlhase since he is
the main user and designer of this package. \setsource{\name} can change the
writer's name.
222 \def\source{Michael Kohlhase}% customize locally
223 \newrobustcmd{\setsource}[1]{\def\source{#1}}%

```

`\setlicensing` Now, we set up the copyright and licensing. By default we use the Creative Commons Attribution-ShareAlike license to strengthen the public domain. If package `hyperref` is loaded, then we can attach a hyperlink to the license logo. `\setlicensing[⟨url⟩]{⟨logo name⟩}` is used for customization, where `⟨url⟩` is optional.

```

224 \def\copyrightnotice{\footnotesize\copyright:\hspace{.3ex}{\source}}%
225 \newsavebox{\cclogo}%
226 \sbox{\cclogo}{\includegraphics[height=\slidelogoheight]{cc_somerights}}%
227 \newif\ifcchref\cchreffalse%
228 \AtBeginDocument{%
229   \ifpackageloaded{hyperref}{\cchreftrue}{\cchreffalse}
230 }%
231 \def\licensing{%
232   \ifcchref%
233     \href{http://creativecommons.org/licenses/by-sa/2.5/}{\usebox{\cclogo}}%
234   \else%
235     {\usebox{\cclogo}}%
236   \fi%
237 }%
238 \newrobustcmd{\setlicensing}[2][]{%
239   \def\@url{#1}%
240   \sbox{\cclogo}{\includegraphics[height=\slidelogoheight]{#2}}%
241   \ifx\@url\@empty%
242     \def\licensing{{\usebox{\cclogo}}}%
243   \else%
244     \def\licensing{%
245       \ifcchref%
246         \href{#1}{\usebox{\cclogo}}%
247       \else%
248         {\usebox{\cclogo}}%
249       \fi%
250     }%
251   \fi%
252 }%

```

EdN:5

`\slidelabel` Now, we set up the slide label for the `article` mode.<sup>5</sup>

```

253 \newrobustcmd\miko@slidelabel{%
254   \vbox to \slidelogoheight{%
255     \vss\hbox to \slidewidth%
256       {\licensing\hfill\copyrightnotice\hfill\arabic{slide}\hfill\usebox{\slidelogo}}%
257   }%
258 }%

```

## 4.4 Colors and Highlighting

Now, we set up an infrastructure for highlighting phrases in slides. Note that we use content-oriented macros for highlighting rather than directly using color

<sup>5</sup>EdNOTE: see that we can use the themes for the slides some day. This is all fake.

markup. The first thing to to is to adapt the green so that it is dark enough for most beamers

```
259 \AtBeginDocument{%
260   \definecolor{green}{rgb}{0,.5,0}%
261   \definecolor{purple}{cmyk}{.3,1,0,.17}%
262 }%
```

We customize the `\defemph`, `\notemph`, and `\stDMemph` macros with colors for the use in the `statements` package. Furthermore we customize the `\@@lec` macro for the appearance of line end comments in `\lec`.

```
263 % \def\STpresent#1{\textcolor{blue}{#1}}
264 \def\defemph#1{\textcolor{magenta}{#1}}
265 \def\notemph#1{\textcolor{magenta}{#1}}
266 \def\stDMemph#1{\textcolor{blue}{#1}}
267 \def\@@lec#1{\textcolor{green}{#1}}
268 \end{package}
269 \end{*txml.sty}
270 \DefMacro('defemph','\textcolor{magenta}{#1}');
271 \DefMacro('notemph','\textcolor{magenta}{#1}');
272 \end{*txml.sty}
```

I like to use the dangerous bend symbol for warnings, so we provide it here.

`\textwarning` as the macro can be used quite often we put it into a box register, so that it is only loaded once.

```
273 \begin{package}
274 \pgfdeclareimage[width=.9em]{miko@small@dbend}{dangerous-bend}
275 \def\smalltextwarning{%
276   \pgfuseimage{miko@small@dbend}%
277   \xspace%
278 }%
279 \pgfdeclareimage[width=1.5em]{miko@dbend}{dangerous-bend}
280 \newrobustcmd\textwarning{%
281   \raisebox{-.05cm}{\pgfuseimage{miko@dbend}}%
282   \xspace%
283 }%
284 \pgfdeclareimage[width=2.5em]{miko@big@dbend}{dangerous-bend}%
285 \newrobustcmd\bigtextwarning{%
286   \raisebox{-.05cm}{\pgfuseimage{miko@big@dbend}}%
287   \xspace%
288 }%
289 \end{package}
290 \end{*txml.sty}
291 \DefMacro('textwarning','\@textwarning\xspace');
292 \DefConstructor('textwarning',"");
293 \end{*txml.sty}
```

## 4.5 Front Matter, Titles, etc

We need to redefine the frontmatter macros inherited from the `beamer` class for LaTeXML, since there they take an optional argument.

```
294 <*ltxml.sty>
295 DefMacro('title[]{}', '\@add@frontmatter{ltx:title}{#1}');
296 DefMacro('date[]{}', '\@add@frontmatter{ltx:date}[role=creation]{#1}');
297 DefMacro('author[]{}', sub { andSplit(T_CS('@author'),$_[1]); });#$
298 </ltxml.sty>
```

Now, we specialize the slide environment that we have implemented above or inherited from `seminar.cls` for some abbreviations, e.g. separator slides and title slides.

```
299 <*package>
300 \ifnotes%
301   \newrobustcmd\titleframe{\maketitle}%
302 \else%
303   \newrobustcmd\titleframe{%
304     \begin{frame}%
305       \titlepage%
306     \end{frame}%
307   }%
308 \fi%
309 \newenvironment{titleframewith}{%
310   \begin{frame}%
311     \titlepage%
312   }{%
313     \end{frame}%
314   }%
315 \newenvironment{ttitle}{%
316   \begin{center}%
317     \LARGE%
318     \begin{tabular}{|c|}%
319       \hline%
320     }{%
321       \\ \hline%
322     \end{tabular}%
323     \end{center}%
324     \vspace{1ex minus 1ex}%
325   }%
326 \newenvironment{ttitlejoint}[1]{%
327   \newbox\boxwith%
328   \setbox\boxwith\hbox{%
329     \begin{tabular}{c}{\em joint work with}\#1\end{tabular}%
330   }%
331   \begin{center}%
332     \LARGE%
333     \begin{tabular}{c}%
334       \color{red}%
335     }{%
```

```

336   \\box\boxwith%
337   \end{tabular}%
338   \end{center}%
339   \vspace{1ex minus 1ex}%
340 }%
341 \end{package}
342 \end{*lxml.sty}
343 DefConstructor('\titleframe',"<omdoc:ignore>titleframe elided here</omdoc:ignore>");
344 DefEnvironment('{titleframewith}',
345               "<omdoc:ignore>begin elided titleframe</omdoc:ignore>"
346               . "#body"
347               . "<omdoc:ignore>end elided titleframe</omdoc:ignore>");
348 DefEnvironment('{titleslide}', "");
349 DefEnvironment('{titleslide}', "<omdoc:omgroup>#body</omdoc:omgroup>");
350 DefEnvironment('{title}', "\n<dc:title>#body</dc:title>");
351 \end{*lxml.sty}

352 %      Must be first command on slide to make positioning work.
353 \end{*package}
354 \newrobustcmd\putgraphicsat[3]{%
355   \begin{picture}(0,0)\put(#1){\includegraphics[#2]{#3}}\end{picture}%
356 }%
357 \newrobustcmd\putat[2]{%
358   \begin{picture}(0,0)\put(#1){#2}\end{picture}%
359 }%
360 \end{package}

```

## 4.6 Sectioning

If the `sectocframes` option is set, then we make section frames.

```

361 \end{*cls}
362 \ifsectocframes%
363   \if@part%
364     \newcounter{mpart}%
365     \newcounter{mchapter}%
366     \newcounter{msection}[mchapter]%
367   \else%
368     \newcounter{msection}%
369   \fi%
370   \newcounter{msubsection}[msection]%
371   \newcounter{msubsubsection}[msubsection]%
372   \newcounter{msubsubsubsection}[msubsubsection]%
373   \ifnotes\else% only in slides
374     \renewcommand\at@begin@omgroup[3][]{%
375       \begin{frame}%
376       \vfill\Large\centering%
377       \red{%
378         \ifcase\section@level\or%
379           \stepcounter{mpart}Part \Roman{mpart}\or%
380           \stepcounter{mchapter}Chapter \arabic{mchapter}\or

```

```

381         \stepcounter{msection}\if@part\arabic{mchapter}.\fi\arabic{msection}\or
382         \stepcounter{msubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msubsection}
383         \stepcounter{msubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msubsection}
384         \stepcounter{msubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msubsection}
385     \fi% end ifcase
386     \quad #3%
387 }%
388 \vfill%
389 \end{frame}%
390 }%
391 \fi% ifnotes
392 \fi% ifsectocframes
393 \</cls>

```

## 4.7 Miscellaneous

The following fixes an error I do not understand, this has something to do with beamer compatibility, which has similar definitions but only up to 1.

```

394 <*package>
395 \expandafter\def\csname Parent2\endcsname{}
396 % \begin{macrocode}
397 %
398 % We need to disregard the columns macros introduced by the |beamer| class
399 % \begin{macrocode}
400 \ifnotes%
401 \renewenvironment{columns}{%
402 \par\noindent%
403 \begin{minipage}%
404 \linewidth\centering\leavevmode%
405 }{%
406 \end{minipage}\par\noindent%
407 }%
408 \newsavebox\columnbox%
409 \renewenvironment{column}[1]{%
410 \begin{lrbox}{\columnbox}\begin{minipage}{#1}%
411 }{%
412 \end{minipage}\end{lrbox}\usebox\columnbox%
413 }%
414 \fi%
415 </package>
416 <*ltxml.sty>
417 DefEnvironment('{columns}','#body');
418 DefEnvironment('{column}','#body');

```

We also need to deal with overlay specifications introduced by the beamer class.<sup>6</sup>

<sup>7</sup>

<sup>6</sup>EDNOTE: this is just to keep latexml quiet, no real functionality here.

<sup>7</sup>EDNOTE: Deyan: We reuse the CMP itemizations defined in the omdoc.cls.ltxml binding, adjusting the parameters to be overlay-sensitive

```

419 DefConstructor('\uncover', '#1');
420 #Define a Beamer Overlay Parameter type
421 DefParameterType('BeamerOverlay', sub {
422   my ($gullet) = @_;
423   my $tok = $gullet->readXToken;
424   if (ref $tok && ToString($tok) eq '<') {
425     $gullet->readUntil(T_OTHER('>'));
426   } else {
427     $gullet->unread($tok) if ref $tok;
428     undef; },
429   reversion=> sub {
430     (T_OTHER('<'), $_[0]->revert, T_OTHER('>'));
431   });
432
433 #Take the "from" field of the overlay range
434 sub overlayFrom {
435   return "" unless defined $_[0];
436   my $overlay=ToString($_[0]); $overlay =~ /\^(\\d+)/; $1;}
437
438 #Reuse the CMP itemizations, only adjust the \item constructors.
439 DefMacro('\beamer@group@item[] OptionalBeamerOverlay IfBeginFollows', sub {
440   my($gullet,$tag,$overlay,$needwrapper)=@_;
441   $overlay=$overlay||T_OTHER("");
442   ( T_CS('\group@item@maybe@unwrap'),
443     ($needwrapper ? (Invocation(T_CS('\beamer@group@item@wrap'),$tag,$overlay)->unlist) : ()))
444 DefConstructor('\beamer@group@item@wrap {} OptionalBeamerOverlay',
445   "<omdoc:omtext ?#2(overlay='&overlayFrom(#2)')()>"
446   . "?#1(<dc:title>#1</dc:title>())"
447   . "<omdoc:CMP>",
448   beforeDigest=>sub {
449     Let('\group@item@maybe@unwrap', '\group@item@unwrap');
450     #$_[0]->bgroup;
451   return; },
452   properties=>sub{ RefStepItemCounter(); });
453 #DefConstructor('\beamer@itemize@item[] OptionalBeamerOverlay',
454 #   "<omdoc:li ?#2(overlay='&overlayFrom(#2)')() >"
455 #   . "?#1(<dc:title>#1</dc:title>())",
456 #   properties=>sub{ RefStepItemCounter(); });
457 DefConstructor('\beamer@enumerate@item[] OptionalBeamerOverlay',
458   "<omdoc:li ?#2(overlay='&overlayFrom(#2)')() >"
459   . "?#1(<dc:title>#1</dc:title>())",
460   properties=>sub{ RefStepItemCounter(); });
461 DefConstructor('\beamer@description@item[] OptionalBeamerOverlay',
462   "<omdoc:di ?#2(overlay='&overlayFrom(#2)')() >"
463   . "?#1(<omdoc:dt>#1</omdoc:dt>())<omdoc:dd>", # trust di and dt to autoclose
464   properties=>sub{ RefStepItemCounter(); });
465 </ltxml.sty>#

```

Now, some things that are imported from the pgf and beamer packages:

```

466 <*ltxml.sty>

```



```

467 DefMacro('putgraphicsat{}{}{}','mygraphics[#2]{#3}');
468 DefMacro('putat{}{}','#2');
469 </ltxml.sty>

470 <*package>
471 \ifproblems%
472   \newenvironment{problems}{}{}%
473 \else%
474   \excluedecomment{problems}%
475 \fi%
476 </package>
477 <*ltxml.sty>
478 DefEnvironment('{problems}','#body');
479 </ltxml.sty>

```

## 4.8 Support for MathHub

`\mhframeimage` Use the current value of `\mh@currentrepos` or the value of the `mhrepos` key if it is given in `\frameimage`.

```

480 <package>\addmetakey{Gin}{mhrepos}
481 <ltxml.sty>DefKeyVal('Gin','mhrepos','Semiverbatim');
482 <ltxml.sty>RawTeX(
483 <*ltxml.sty | package>
484 \newcommand\mhframeimage[2][]{%
485   \metasetkeys{Gin}{#1}%
486   \edef\mh@crepos{\mh@currentrepos}%
487   \ifx\Gin@mhrepos\empty%
488     \frameimage[#1]{\MathHub{\mh@currentrepos/source/#2}}%
489   \else%
490     \frameimage[#1]{\MathHub{\Gin@mhrepos/source/#2}}%
491   \fi%
492 }%
493 </ltxml.sty | package>
494 <ltxml.sty>');

```

## 4.9 Finale

Finally, we set the slide body font to the sans serif, and we terminate the  $\text{\LaTeX}$ ML bindings file with a success mark for perl.

```

495 <package>\ifnotes\else\sfffi
496 <ltxml.sty | ltxml.cls>1;

```

## References

- [CR99] David Carlisle and Sebastian Rathz. *The graphicx package*. Part of the T<sub>E</sub>X distribution. The Comprehensive T<sub>E</sub>X Archive Network. 1999. URL: <https://www.tug.org/texlive/devsrc/Master/texmf-dist/doc/latex/graphics/graphicx.pdf>.
- [Hor+11] Fulya Horozal et al. “Combining Source, Content, Presentation, Narration, and Relational Representation”. In: *Intelligent Computer Mathematics*. Ed. by James Davenport et al. LNAI 6824. Springer Verlag, 2011, pp. 212–227. ISBN: 978-3-642-22672-4. URL: [http://kwarc.info/frabe/Research/HIJKR\\_dimensions\\_11.pdf](http://kwarc.info/frabe/Research/HIJKR_dimensions_11.pdf).
- [Koh15] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in L<sup>A</sup>T<sub>E</sub>X*. Tech. rep. Comprehensive T<sub>E</sub>X Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/metakeys/metakeys.pdf>.
- [sTeX] *KWARC/sTeX*. URL: <https://svn.kwarc.info/repos/stex> (visited on 05/15/2015).
- [Tana] Till Tantau. *beamer – A LaTeX class for producing presentations and slides*. URL: <http://www.ctan.org/pkg/beamer> (visited on 01/07/2014).
- [Tanb] Till Tantau. *User Guide to the Beamer Class*. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/beamer/doc/beameruserguide.pdf>.