

# Semantic Markup for Mathematical Statements<sup>\*</sup>

Michael Kohlhase  
Jacobs University, Bremen  
<http://kwarc.info/kohlhase>

October 22, 2015

## Abstract

The `statements` package is part of the  $\text{\LaTeX}$  collection, a version of  $\text{\TeX}/\text{\LaTeX}$  that allows to markup  $\text{\TeX}/\text{\LaTeX}$  documents semantically without leaving the document format, essentially turning  $\text{\TeX}/\text{\LaTeX}$  into a document format for mathematical knowledge management (MKM).

This package provides semantic markup facilities for mathematical statements like Theorems, Lemmata, Axioms, Definitions, etc. in  $\text{\LaTeX}$  files. This structure can be used by MKM systems for added-value services, either directly from the  $\text{\LaTeX}$  sources, or after translation.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>The User Interface</b>	<b>2</b>
2.1	Package Options . . . . .	2
2.2	Statements . . . . .	2
2.3	Cross-Referencing Symbols and Concepts . . . . .	9
<b>3</b>	<b>Configuration of the Presentation</b>	<b>10</b>
<b>4</b>	<b>Limitations</b>	<b>11</b>
<b>5</b>	<b>The Implementation</b>	<b>11</b>
5.1	Package Options . . . . .	11
5.2	Statements . . . . .	13
5.3	Cross-Referencing Symbols and Concepts . . . . .	25
5.4	Providing IDs for OMDoc Elements . . . . .	27
5.5	Auxiliary Functionality . . . . .	28
5.6	Deprecated Functionality . . . . .	29
5.7	Finale . . . . .	29

---

<sup>\*</sup>Version v1.2 (last revised 2015/04/03)

# 1 Introduction

The motivation for the `statements` package is very similar to that for semantic macros in the `modules` package: We want to annotate the structural semantic properties of statements in the source, but present them as usual in the formatted documents. In contrast to the case for mathematical objects, the repertoire of mathematical statements and their structure is more or less fixed.

This structure can be used by MKM systems for added-value services, either directly from the  $\text{\S}\text{\TeX}$  sources, or after translation. Even though it is part of the  $\text{\S}\text{\TeX}$  collection, it can be used independently, like its sister package `sproofs`.

$\text{\S}\text{\TeX}$  [`sTeX:online`; Koh08] is a version of  $\text{\TeX}$ / $\text{\LaTeX}$  that allows to markup  $\text{\TeX}$ / $\text{\LaTeX}$  documents semantically without leaving the document format, essentially turning  $\text{\TeX}$ / $\text{\LaTeX}$  into a document format for mathematical knowledge management (MKM). Currently the OMDOC format [Koh06] is directly supported.

## 2 The User Interface

The `statements` package supplies a semantically oriented infrastructure for marking up mathematical statements: fragments of natural language that state properties of mathematical objects, e.g. axioms, definitions, or theorems. The `statement` package provides an infrastructure for marking up the semantic relations between statements for the OMDOC transformation and uses the `ntheorem` package [MS] for formatting (i.e. transformation to PDF).

### 2.1 Package Options

The `statements` package provides the `defindex` option to  $\text{\S}\text{\TeX}$ . If this is set, then definienda are automatically passed into the index of the document. Furthermore, the `statements` package passes the `showmeta` to the `metakeys` package. If this is set, then the metadata keys are shown (see [Koh15a] for details and customization options).

### 2.2 Statements

All the statements are marked up as environments, that take a `KeyVal` argument that allows to annotate semantic information. Generally, we distinguish two forms of statements:

**block statements** have explicit discourse markers that delimit their content in the surrounding text, e.g. the boldface word “**Theorem:**” as a start marker and a little line-end box as an end marker of a proof.

**flow statements** do not have explicit markers, they are interspersed with the surrounding text.

Since they have the same semantic status, they must both be marked up, but styled differently. We distinguish between these two presentational forms with the `display=` key, which is allowed on all statement environments. If it has the value `block` (the default), then the statement will be presented in a paragraph of its own, have explicit discourse markers for its begin and end, possibly numbering, etc. If it has the value `flow`, then no extra presentation will be added the semantic information is invisible to the reader. Another key that is present on all statement environments in the `id` key it allows to identify the statement with a name and to reference it with the semantic referencing infrastructure provided by the `sref` package [Koh15c].

### 2.2.1 Axioms and Assertions

`assertion` The `assertion` environment is used for marking up statements that can be justified from previously existing knowledge (usually marked with the monikers “Theorem”, “Lemma”, “Proposition”, etc. in mathematical vernacular). The environment `assertion` is used for all of them, and the particular subtype of assertion is given in the `type` key. So instead of `\begin{Lemma}` we have to write `\begin{assertion}[type=lemma]` (see Example 1 for an example).

```
\begin{assertion}[id=sum-over-odds,type=lemma]
  $\sum_{i=1}^n 2i-1=n^2$
\end{assertion}
```

will lead to the result

**Lemma 2.1**  $\sum_{i=1}^n 2i - 1 = n^2$

**Example 1:** Semantic Markup for a Lemma in a `module` context

Whether we will see the keyword “Lemma” will depend on the value of the optional `display` key. In all of the `assertion` environments, the presentation expectation is that the text will be presented in italic font. The presentation (keywords, spacing, and numbering) of the `assertion` environment is delegated to a theorem styles from the `ntheorem` environment. For an assertion of type  $\langle type \rangle$  the `assertion` environment calls the `ST $\langle type \rangle$ AssEnv` environment provided by the `statements` package; see Figure 2 for a list of provided assertion types. Their formatting can be customized by redefining the `ST $\langle type \rangle$ AssEnv` environment via the `\renewtheorem` command from the `ntheorem` package; see [MS] for details.

`axiom` The `axiom` environment is similar to `assertion`, but the content has a different ontological status: axioms are assumed without (formal) justification, whereas assertions are expected to be justified from other assertions, axioms or definitions. This environment relegates the formatting to the `STaxiomEnv` environment, which can be redefined for configuration.

### 2.2.2 Symbols

`symboldec` The `symboldec` environment can be used for declaring concepts and symbols. Note

Value	Explanation
<b>theorem, proposition</b>	an important assertion with a proof
Note that the meaning of <b>theorem</b> (in this case the existence of a proof) is not enforced by OMDoc applications. It can be appropriate to give an assertion the <b>theorem</b> , if the author knows of a proof (e.g. in the literature), but has not formalized it in OMDoc yet.	
<b>lemma</b>	a less important assertion with a proof
The difference of importance specified here is even softer than the other ones, since e.g. reusing a mathematical paper as a chapter in a larger monograph, may make it necessary to downgrade a theorem (e.g. the main theorem of the paper) and give it the status of a lemma in the overall work.	
<b>corollary</b>	a simple consequence
An assertion is sometimes marked as a corollary to some other statement, if the proof is considered simple. This is often the case for important theorems that are simple to get from technical lemmata.	
<b>postulate, conjecture</b>	an assertion without proof or counter-example
Conjectures are assertions, whose semantic value is not yet decided, but which the author considers likely to be true. In particular, there is no proof or counter-example.	
<b>false-conjecture</b>	an assertion with a counter-example
A conjecture that has proven to be false, i.e. it has a counter-example. Such assertions are often kept for illustration and historical purposes.	
<b>obligation, assumption</b>	an assertion on which a proof of another depends
These kinds of assertions are convenient during the exploration of a mathematical theory. They can be used and proven later (or assumed as an axiom).	
<b>rule</b>	a normative assertion
These kinds of assertions can be interpreted procedurally to trigger actions	
<b>observation</b>	if everything else fails
This type is the catch-all if none of the others applies.	

**Example 2:** Types of Mathematical Assertions

the the `\symdef` forms from the `modules` package will not do this automatically (but the `\definition` environment and the `\inlinedef` macro will for all the definienda; see below). The `\symboldec` environment takes an optional keywords argument with the keys `id`, `role`, `title` and `name`. The first is for general identification, the `role` specifies the OPENMATH/OMDOC role, which is one of `object`, `type`, `sort`, `binder`, `attribution`, `application`, `constant`, `semantic-attribution`, and `error` (see the OMDOC specification for details). The `name` key specifies the OPENMATH name of the symbol, it should coincide with the control sequence introduced by the corresponding `\symdef` (if one is present). The `title` key is for presenting the title of this symbol as in other statements. Usually, `\axiom` and `\symboldec` environments are used together as in Figure 3.

### 2.2.3 Types

In many cases, we can give additional information for symbols in the form of type assignments.  $\TeX$  does not fix a type system, but allows types to be arbitrary mathematical objects that they can be defined in (imported) modules. The

`\symtype` `\symtype` macro can be used to assign a type to a symbol:

```
\symtype[\keys]{\sym}{\type}
```

assigns the type `\type` to a symbol with name `\sym`. For instance

```
\symtype[id=plus-nat.type,system=sts]{plus}{\fntype{\Nat,\Nat}\Nat}
```

assigns the type  $\mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$  (in the `sts` type system) to the symbol `plus`. This states (type assignments are statements epistemologically) that addition is a binary function on natural numbers. The `\symtype` macro supports the keys `id` (for identifiers) and `system` for the type system.

Often, type assignments occur in informal context, where the type assignment is given by a natural language sentence or phrase. For this, the `statements` package supplies the `typedec` environment and the `\inlinetypedec` macro. Both take an optional keyval argument followed by the type. The phrase/sentence is the body of the `typedec` environment and the last argument of the `\inlinetypedec` macro. The symbol name is given in via the `for` key. For convenience, the macro

`\thedectype`

`\thedectype` is bound to the type. So we can use

```
\begin{typedec}[for=plus,id=plus-nat.type]{\fntype{\Nat,\Nat}\Nat}
  $+:\thedectype$ is a binary function on $\Nat$
\end{typedec}
```

instead of the `\symtype` above in an informal setting.

### 2.2.4 Definitions, and Definienda

`definition` The `\definition` environment is used for marking up mathematical definitions. Its peculiarity is that it defines (i.e. gives a meaning to) new mathematical concepts or objects. These are identified by the `\definiendum` macro, which is used

```

\symdef{zero}{0}
\begin{symboldec}[name=zero,title=The number zero,type=constant]
  The number zero, it is used as the base case of the inductive definition
  of natural numbers via the Peano Axioms.
\end{symboldec}

\symdef{succ}[1]{\prefix{s}{#1}}
\begin{symboldec}[name=succ,title=The Successor Function,type=application]
  The successor function, it is used for the step case of the inductive
  definition of natural numbers via the Peano Axioms.
\end{symboldec}

\symdef{NaturalNumbers}{\mathbb{N}}
\begin{symboldec}[name=succ,title=The Natural Numbers,type=constant]
  The natural numbers inductively defined via the Peano Axioms.
\end{symboldec}

\begin{axiom}[id=peano.P1,title=P1]
  $\text{zero}$ is a natural number.
\end{axiom}
...
\begin{axiom}[id=peano.P5,title=P5]
  Any property $P$ such $P(\text{zero})$ and $P(\text{succ}\{k\})$ whenever $P(k)$
  holds for all $n$ in $\text{NaturalNumbers}$
\end{axiom}

```

will lead to the result

**Symbol zero: (The number zero)**

The number zero, it is used as the base case of the inductive definition of natural numbers via the Peano Axioms.

**Symbol succ: (The Successor Function)**

The successor function, it is used for the step case of the inductive definition of natural numbers via the Peano Axioms.

**Symbol succ: (The Natural Numbers)**

The natural numbers inductively defined via the Peano Axioms.

**Axiom 2.2 (P1)** 0 is a natural number.

...

**Axiom 2.6 (P5)** Any property  $P$  such  $P(0)$  and  $P(\succ k)$  whenever  $P(k)$  holds for all  $n$  in  $\mathbb{N}$

### Example 3: Semantic Markup for the Peano Axioms

as `\definiendum[<sysname>]{<text>}`. Here, *<text>* is the text that is to be emphasized in the presentation and the optional *<sysname>* is a system name of the symbol defined (for reference via `\termref`, see Section 2.3). If *<sysname>* is not given, then *<text>* is used as a system name instead, which is usually sufficient for most situations.

```
\symdef{one}{1}
\begin{definition}[id=one.def,for=one]
  $\notatiendum[one]{\one}$ is the successor of $\zero$
  (formally: $\one\colon=\succ\zero$)
\end{definition}
```

will lead to the result

**Definition 2.7** 1 is the successor of 0 (formally:  $1: =\succ 0$ )

**Example 4:** A Definition based on Figure 3

`defi`      The `\defi{<word>}` macro combines the functionality of the `\definiendum` macro with index markup from the `omdoc` package [Koh15b]: use

```
\defi[<name>]{<word>}[<indexkeys>]
```

to markup a `\definiendum` *<word>* with system name *<name>* that appear in the index (where *<indexkeys>* are passed to the `\omdoc@index` macro from the `omdoc` package) — in other words in almost all definitions of single-word concepts. We

`\defii`      also have the variants `\defii` and `\defiii` for (adjectivized) two-word compounds. Note that if the `\definiendum` contains semantic macros, then we need to  
`\defiii`      specify the `loadmodules` key and also protect the semantic macro. For instance if `\eset` is the semantic macro for  $\emptyset$ , then we would use

```
\defii[eset-comp]{$\protect\eset$}{compatible}[loadmodules]
```

`\adefi`      for the `\definiendum` markup. Finally, the variants `\adefi`, `\adefii`, and `\adefiii`  
`\adefii`      have an additional first argument that allows to specify an alternative text; see  
`\adefiii`      Figure 5. The main use of these is to mark up inflected forms as in

```
we speak of \adefi{lemmata}{lemma} in this case.
```

As the greatest number of these are plurals, which tends to be regular (e.g. adding a trailing “s” in English), we provide the variants `\defis`, `\defiis`, and  
`\defiis`      `\defiiis` for that case: `\defiis{simple}{group}` is equivalent to much longer  
`\defiiis`      `\adefii{simple groups}{simple}{group}`.

Note that the `\definiendum`, `\defi`, `\defii`, and `\defiii` macros can only be used inside the definitional situation, i.e. in a `definition` or `symboldec` environment or a `\inlinedef` macro. If you find yourself in a situation where you want to

source		
system name	result	index
\defi{concept}		
concept	concept	concept
\defi[csymbol]{concept}		
csymbol	concept	concept
\adefi[csymbol]{concepts}{concept}		
csymbol	concepts	concept
\defii{concept}{group}		
concept-group	concept group	concept group, group - , concept
\adefii{small}{concept}{group}		
small-concept-group	small concept group	small concept group, concept group - , small

**Example 5:** Some definienda with Index

use it outside, you will most likely want to wrap the appropriate text fragment in a `\begin{definition}[display=flow] ...` and `\end{definition}`. For instance, we could continue the example in Figure 3 with the `definition` environment in Figure 4.

`\inlinedef` Sometimes we define mathematical concepts in passing, e.g. in a phrase like “... $s(o)$  which we call **one**.”. For this we cannot use the `definition` environment, which presupposes that its content gives all that is needed to understand the definition. But we do want to make use of the infrastructure introduced for the `definition` environment. In this situation, we just wrap the phrase in an `\inlinedef` macro that makes them available. The `\inlinedef` macro accepts the same `id` and `for` keys in its optional argument, and additionally the `verbalizes` key which can be used to point to a full definition of the concept somewhere else.

Note that definienda can only be referenced via a `\term` element, if they are only allowed inside a named module, i.e. a `module` environment with a name given by the `id=` key or the `theory=` key on is specified on the definitional environment.

### 2.2.5 Examples

`example` The `example` environment is a generic statement environment, except that the `for` key should be given to specify the identifier what this is an example for. The `example` environment also expects a `type` key to be specified, so that we know whether this is an example or a counterexample.

`\inlineex` The `\inlineex` is analogous to `\inlinedef`, only that it is used for inline examples, e.g. “...mammals, e.g. goats”. Note that we have used an inline example for an inline example.

As examples need to import foreign vocabularies (those used to construct the example), the example environment provides the `\usevocab` command, a special



variant of `\importmodule` that is only available in the `example` environment and the argument of `\inlineex`.

## 2.3 Cross-Referencing Symbols and Concepts

If we have defined a concept with the `\definiendum` macro, then we can mark up other occurrences of the term as referring to this concept. Note that this process cannot be fully automatized yet, since that would need advanced language technology to get around problems of disambiguation, inflection, and non-contiguous phrases<sup>1</sup>. Therefore, the `\termref` can be used to make this information explicit. It takes the keys

`\termref`

`cdbase` to specify a URI (a path actually, since L<sup>A</sup>T<sub>E</sub>X cannot load from URIs) where the module can be found.

`cd` to specify the module in which the term is defined. If the `cd` key is not given, then the current module is assumed. If no `cdbase` is specified (this is the usual case), then the CD has to be imported via a `\importmodule` from the `modules` package [KGA15].

`name` to specify the name of the definiendum (which is given in the body of the `\definiendum` or the optional argument). If the `name` key is not specified, then argument of the `\termref` macro is used.

`role` is currently unused.

`\termref[cd=<cd>,name=<name>]{<text>}` will just typeset the link text `<text>` with (if the `hyperref` package is loaded) a hyperlink to the definition in module `<cd>` that defines the concept `<name>`, e.g. that contains `\defi[<name>]{<text>}`.

Just as the `\definiendum` macro has the convenience variants `\defi`, `\defii` and `\defiii`, the `\termref` has variants `\trefi`, `\trefii`, and `\trefiii` that take two and three arguments for the parts of the compositum. In the same module, concepts that are marked up by `\defi{<name>}` in the definition can be referenced by `\trefi{<name>}`. Here the link text is just `<name>`. Concepts defined via `\defii{<first>}{<second>}` can be referenced by `\trefii{<first>}{<second>}` (with link text “`<first> <second>`”) and analogously for `\defiii` and `\trefiii`.

`\trefi`

`\trefii`

`\trefiii`

`\atref*`

We have variants `\atrefi`, `\atrefii`, and `\atrefiii` with alternative link text. For instance `\atrefii{<text>}{<first>}{<second>}` references a concept introduced by `\defii{<first>}{<second>}` but with link text `<text>`. Of course, if the system identifier is given explicitly in the optional argument of the definition form, as in `\defii[<name>]{<first>}{<second>}`, then the terms are referenced by `\trefi{<name>}`.

For referencing terms outside the current module, the module name can be specified in the first optional argument of the `\*tref*` macros. To specify the `cdbase`, we have to resort to the `\termref` macro with the keyval arguments.

Note that the `\termref` treatment above is natural for “concepts” declared by the `\termdef` macro from the `modules` package [KGA15]. Concepts are natural language names for mathematical objects. For “symbols”, i.e. symbolic identifiers for mathematical objects used in mathematical formulae, we use the `\symdef`

<sup>1</sup>We do have a program that helps annotate larger text collections spotting the easy cases; see <http://kwarc.info/projects/stex> and look for the program `termin`.

macro from the `modules` package. Sometimes, symbols also have an associated natural language concept, and we want to use the symbol name to reference it (instead of specifying `cd` and `name` which is more inconvenient). For this the `statements` package supplies the `\symref` macro. Like `\termref`, and invocation of `\symref{<csseq>}{<text>}` will just typeset `<text>` with a hyperlink to the relevant definition (i.e. the one that has the declaration `for=<csseq>` in the metadata argument.)

`\symref`

`\term`

The `\term` macro is a variant of the `\termref` macro that marks up a phrase as a (possible) term reference, which does not have a link *yet*. This macro is a convenient placeholder for authoring, where a `\termref` annotation is (currently) too tedious or the link target has not been authored yet. It facilitates lazy flexiformalization workflows, where definitions for mathematical concepts are supplied or marked up by need (e.g. after a `grep` shows that the number of `\term` annotations of a concept is above a threshold). Editors or active documents can also support the `\term` macro like a wiki-like dangling link: a click on `\term{<phrase>}` could generate a new editor buffer with a stub definition (an `\definition` environment with `\definiendum` macro and appropriate metadata).<sup>1</sup>

EdN:1

### 3 Configuration of the Presentation

`\defemph`

The `\defemph` macro is a configuration hook that allows to specify the style of presentation of the definiendum. By default, it is set to `\bf` as a fallback, since we can be sure that this is always available. It can be customized by redefinition: For instance `\renewcommand{\defemph}[1]{\emph{#1}}`, changes the default behavior to italics.

`\termemph`

The `\termemph` macro does the same for the style for `\termref`, it is empty by default. Note the term might carry an implicit hyper-reference to the defining occurrence and that the presentation engine might mark this up, changing this behavior.

`\stdMemph`

The `\stdMemph` macro does the same for the style for the markup of the discourse markers like “Theorem”. If it is not defined, it is set to `\bf`; that allows to preset this in the class file.<sup>2</sup>

EdN:2

Some authors like to lowercase the semantic references, i.e. use “axiom 2.6” instead of the default “Axiom 2.6” to refer to the last axiom in Figure 3. This can be achieved by redefining the `\STpresent` macro, which is applied to the keyword of the `ST*Env` theorem environments.<sup>3</sup>

`\STpresent`

Finally, we provide configuration hooks in Figure 6 for the statement types provided by the `statement` package. These are mainly intended for package authors building on `statements`, e.g. for multi-language support. The language bindings are given in the `smultiling` [KG15] package not in `statements` itself.

EdN:3

<sup>1</sup>EdNOTE: MK: we probably need multi-part variants for `*tref*`

<sup>2</sup>EdNOTE: function declarations

<sup>3</sup>EdNOTE: this does not quite work as yet, since `STpresent` is applied when the label is written. But we would really like to have it applied when the reference is constructed. But for that we need to split the label into keyword and number in package `sref`.

Environment	configuration macro	value
STtheoremAssEnv	\st@theorem@kw	Theorem
STlemmaAssEnv	\st@lemma@kw	Lemma
STpropositionAssEnv	\st@proposition@kw	Proposition
STcorollaryAssEnv	\st@corollary@kw	Corollary
STconjectureAssEnv	\st@conjecture@kw	Conjecture
STfalseconjectureAssEnv	\st@falseconjecture@kw	Conjecture (false)
STpostulateAssEnv	\st@postulate@kw	Postulate
STobligationAssEnv	\st@obligation@kw	Obligation
STassumptionAssEnv	\st@assumption@kw	Assumption
STobservationAssEnv	\st@observation@kw	Observation
STruleAssEnv	\st@rule@kw	Rule
STexampleEnv	\st@example@kw	Example
STaxiomEnv	\st@axiom@kw	Axiom
STdefinitionEnv	\st@definition@kw	Definition
STnotationEnv	\st@notation@kw	Notation

**Example 6:** Configuration Hooks for statement types

## 4 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the  $\text{\LaTeX}$  GitHub repository [sTeX].

1. none reported yet

## 5 The Implementation

The `statements` package generates two files: the  $\text{\LaTeX}$  package (all the code between `<*package>` and `</package>`) and the  $\text{\LaTeX}$ ML bindings (between `<*ltxml>` and `</ltxml>`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

The general preamble for  $\text{\LaTeX}$ ML:

```

1 <*ltxml>
2 # -*- PERL -*-
3 package LaTeXML::Package::Pool;
4 use strict;
5 use LaTeXML::Package;
6 </ltxml>
```

### 5.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true

(otherwise they stay false). First we have the general options

```

7 <*package>
8 \newif\ifdef@index\def@indexfalse
9 \DeclareOption{defindex}{\def@indextrue}
10 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{omtext}
11                 \PassOptionsToPackage{\CurrentOption}{modules}}
12 \ProcessOptions
13 </package>
14 <*ltxml>
15 DefConditional('\if@defindex');
16 DeclareOption('defindex', sub{Digest(T_CS('\@defindextrue'))}; });
17 DeclareOption(undef, sub{PassOptions('omdoc', 'sty', ToString(Digest(T_CS('\CurrentOption'))));
18                                     PassOptions('omdoc', 'sty', ToString(Digest(T_CS('\CurrentOption'))));
19 ProcessOptions();
20 </ltxml>

```

The next measure is to ensure that some  $\text{\TeX}$  packages are loaded: `omdoc` for the statement keys, `modules` since we need module identifiers for referencing. Furthermore, we need the `ntheorem` package for presenting statements. For  $\text{\LaTeX}$  XML, we also initialize the package inclusions, there we do not need `ntheorem`, since the XML does not do the presentation.

```

21 <*package>
22 \RequirePackage{omtext}
23 \RequirePackage[base]{babel}
24 \RequirePackage{modules}
25 \RequirePackage[hyperref]{ntheorem}
26 \theoremstyle{plain}
27 </package>
28 <*ltxml>
29 RequirePackage('omtext');
30 RequirePackage('modules');
31 </ltxml>

```

Now, we define an auxiliary function that lowercases strings

```

32 <*ltxml>
33 sub lowercase {my ($string) = @_; $string ? return lc(ToString($string)) : return('')}##$
34 sub dashed { join('-', map($_->toString, @_)); }##$
35 </ltxml>

```

Sometimes it is necessary to fallback to symbol names in order to generate `xml:id` attributes. For this purpose, we define an auxiliary function which ensures the name receives a unique NCName equivalent.<sup>4</sup>

```

36 <*ltxml>
37 sub makeNCName {
38   my ($name) = @_;
39   my $ncname=$name;
40   $ncname=~s/\s/_/g; #Spaces to underscores
41   $ncname="_$ncname" if $ncname!~/^(\w|_)/; #Ensure start with letter or underscore

```

<sup>4</sup>EDNOTE: Hard to be unique here, e.g. the names "foo\_bar" and "foo bar" would receive the same `xml:id` attributes... of course we can devise a more complex scheme for the symbol replacement.

```
42 ##More to come...
```

```
43 $ncname;
```

```
44 }
```

```
45 </ltxml>
```

The following functions are strictly utility functions that makes our life easier later on

```
46 <*ltxml>
```

```
47 sub simple_wrapper {
```

```
48   #Deref if array reference
```

```
49   my @input;
```

```
50   foreach (@_) {
```

```
51     if (ref $_ && $_ =~ /ARRAY/ && $_ !~ /LaTeXML/) {
```

```
52       @input=(@input,@$_);
```

```
53     } else
```

```
54       { push (@input,$_); }
```

```
55   }
```

```
56   return '' if (!@input);
```

```
57   @input = map(split(/\s*,\s*/,ToString($_)),@input);
```

```
58   my $output=join(" ",@input);
```

```
59   $output=~s/(\^)|[\{\}]/g; #remove leading space and list separator brackets
```

```
60   $output||'';
```

```
61 }
```

```
62 sub hash_wrapper{
```

```
63   #Deref if array reference
```

```
64   my @input;
```

```
65   foreach (@_) {
```

```
66     if (ref $_ && $_ =~ /ARRAY/ && $_ !~ /LaTeXML/) {
```

```
67       @input=(@input,@$_);
```

```
68     } else
```

```
69       { push (@input,$_); }
```

```
70   }
```

```
71   return '' if (!@input);
```

```
72   @input = sort map(split(/\s*,\s*/,ToString($_)),@input);
```

```
73   my $output=join(".sym #",@input);
```

```
74   $output=~s/(\^\.sym)|[\{\}]/g; #remove leading space and list separator brackets
```

```
75   "#$output"||'';
```

```
76 }
```

```
77 </ltxml>
```

For the other languages, we set up triggers

```
78 <*package>
```

```
79 \AfterBabelLanguage{ngerman}{\input{statements-ngerman.ldf}}
```

```
80 </package>
```

## 5.2 Statements

\STpresent

```
81 <*package>
```

```
82 \providecommand\STpresent[1]{#1}
```

```

83 </package>

\define@statement@env We define a meta-macro that allows us to define several variants of statements.
Upon beginning this environment, we first set the KeyVal attributes, then we
decide whether to print the discourse marker based on the value of the display
key, then (given the right Options were set), we show the semantic annotations,
and finally initialize the environment using the appropriate macro. Upon ending
the environment, we just run the respective termination macro.

84 <*package>
85 \def\define@statement@env#1{%
86 \newenvironment{#1}[1][\metasetkeys{omtext}{#1}\sref@target%
87 \in@omtexttrue%
88 \ifx\omtext@display\st@flow\else%
89 \ifx\omtext@title\@empty\begin{ST#1Env}\else\begin{ST#1Env}[\omtext@title]\fi%
90 \ifx\sref@id\@empty\else\label{#1.\sref@id}\fi
91 \csname st@#1@initialize\endcsname\fi% display
92 \ifx\sref@id\@empty\sref@label@id{here}\else%
93 \sref@label@id{\STpresent{\csname ST#1EnvKeyword\endcsname}~\@currentlabel}\fi%
94 \ignorespaces}
95 {\csname st@#1@terminate\endcsname\ifx\omtext@display\st@flow\else\end{ST#1Env}\fi%
96 \omtext@post@skip\in@omtextfalse}}
97 </package>

assertion

98 <*package>
99 \newenvironment{assertion}[1][\metasetkeys{omtext}{#1}\sref@target%
100 \in@omtexttrue%
101 \ifx\omtext@display\st@flow\itshape\noindent\ignorespaces%
102 \else% display!=flow
103 \ifx\omtext@title\@empty\begin{ST\omtext@type AssEnv}%
104 \else\begin{ST\omtext@type AssEnv}[\omtext@title]\fi\fi%
105 \ifx\omtext@type\@empty\sref@label@id{here}\else%
106 \sref@label@id{\STpresent{\csname ST\omtext@type AssEnvKeyword\endcsname}~\@currentlabel}
107 \fi}%display=flow
108 {\ifx\omtext@display\st@flow\else\end{ST\omtext@type AssEnv}\in@omtextfalse\fi}
109 </package>
110 <*lxml>
111 DefStatement('{assertion} OptionalKeyVals:omtext',
112 " <omdoc:assertion "
113 . "?&GetKeyVal{#1,'id'}(xml:id='&GetKeyVal{#1,'id'}')() "
114 . "?&GetKeyVal{#1,'theory'}(theory='&GetKeyVal{#1,'theory'}')() "
115 . "type='&lowcase(&GetKeyVal{#1,'type'})'>"
116 . "?&GetKeyVal{#1,'title'}(<dc:title>&GetKeyVal{#1,'title'})</dc:title>() "
117 . " <omdoc:CMP>#body"
118 . "</omdoc:assertion>\n");
119 </lxml>

\st@*kw We configure the default keywords for the various theorem environments.

120 <*package>

```

```

121 \def\st@theorem@kw{Theorem}
122 \def\st@lemma@kw{Lemma}
123 \def\st@proposition@kw{Proposition}
124 \def\st@corollary@kw{Corollary}
125 \def\st@conjecture@kw{Conjecture}
126 \def\st@falseconjecture@kw{Conjecture (false)}
127 \def\st@postulate@kw{Postulate}
128 \def\st@obligation@kw{Obligation}
129 \def\st@assumption@kw{Assumption}
130 \def\st@rule@kw{Rule}
131 \def\st@observation@kw{Observation}

```

Then we configure the presentation of the theorem environments

```

132 \theorembodyfont{\itshape}
133 \theoremheaderfont{\normalfont\bfseries}

```

and then we finally define the theorem environments in terms of the statement keywords defined above. They are all numbered together with the section counter.

ST\*AssEnv

```

134 \newtheorem{STtheoremAssEnv}{\st@theorem@kw}[section]
135 \newtheorem{STlemmaAssEnv}[STtheoremAssEnv]{\st@lemma@kw}
136 \newtheorem{STpropositionAssEnv}[STtheoremAssEnv]{\st@proposition@kw}
137 \newtheorem{STcorollaryAssEnv}[STtheoremAssEnv]{\st@corollary@kw}
138 \newtheorem{STconjectureAssEnv}[STtheoremAssEnv]{\st@conjecture@kw}
139 \newtheorem{STfalseconjectureAssEnv}[STtheoremAssEnv]{\st@falseconjecture@kw}
140 \newtheorem{STpostulateAssEnv}[STtheoremAssEnv]{\st@postulate@kw}
141 \newtheorem{STobligationAssEnv}[STtheoremAssEnv]{\st@obligation@kw}
142 \newtheorem{STassumptionAssEnv}[STtheoremAssEnv]{\st@assumption@kw}
143 \newtheorem{STobservationAssEnv}[STtheoremAssEnv]{\st@observation@kw}
144 \newtheorem{STruleAssEnv}[STtheoremAssEnv]{\st@rule@kw}
145 \end{package}

```

EdN:5

example

```

5
146 \begin{package}
147 \let\usevocab=\usemodule
148 \let\usemhvocab=\usemhmodule
149 \def\st@example@initialize{}\def\st@example@terminate{}
150 \define@statement@env{example}
151 \def\st@example@kw{Example}
152 \theorembodyfont{\upshape}
153 \newtheorem{STexampleEnv}[STtheoremAssEnv]{\st@example@kw}
154 \end{package}
155 \begin{ltxml}
156 DefMacro('usevocab', 'usemodule');
157 DefMacro('usemhvocab', 'usemhmodule');
158 DefStatement('{example} OptionalKeyVals:omtext',
159             "<omdoc:example "

```

---

<sup>5</sup>EDNOTE: need to do something clever for the OMDoc representation of examples, in particular, the usevocab should only be defined in example

```

160 . "&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id'))()"
161 . "&GetKeyVal(#1,'for')(for='&hash_wrapper(&GetKeyVal(#1,'for'))')(>"
162 . "&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
163 . "#body"
164 . "</omdoc:example>\n";
165 </ltxml>

```

axiom

```

166 <*package>
167 \def\st@axiom@initialize{}\def\st@axiom@terminate{}
168 \define@statement@env{axiom}
169 \def\st@axiom@kw{Axiom}
170 \theorembodyfont{\upshape}
171 \newtheorem{STaxiomEnv}[STtheoremAssEnv]{\st@axiom@kw}
172 </package>
173 <*ltxml>
174 DefStatement('{axiom} OptionalKeyVals:omtext',
175   "<omdoc:axiom "
176   .   "&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id'))()"
177   .   "&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
178   .   "<omdoc:axiom>\n";
179   "</omdoc:axiom>\n");
180 </ltxml>

```

symboldec We use \symdef@type from the modules package as the visual cue.

```

181 <*package>
182 \srefaddidkey{symboldec}
183 \addmetakey{symboldec}{functions}
184 \addmetakey{symboldec}{role}
185 \addmetakey*{symboldec}{title}
186 \addmetakey*{symboldec}{name}
187 \addmetakey{symboldec}{subject}
188 \addmetakey*{symboldec}{display}
189 \newenvironment{symboldec}[1][\metasetkeys{symboldec}{#1}\sref@target\st@indeftrue%
190 \ifx\symboldec@display\st@flow\else\{noindent\stDMemph{\symdef@type} \symboldec@name:}\fi%
191 \ifx\symboldec@title\empty~\else~(\stDMemph{\symboldec@title})\par\fi{}
192 </package>
193 <*ltxml>
194 DefStatement('{symboldec} OptionalKeyVals:symboldec',
195   "<omdoc:symbol "
196   .   "&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id'))"
197   .   " (xml:id='&makeNCName(&GetKeyVal(#1,'name')).def.sym')"
198   .   " name='&GetKeyVal(#1,'name')>"
199   .   "&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
200   .   "<dc:description>\n";
201   "</omdoc:symbol>\n");
202 </ltxml>

```



### 5.2.1 Types

```

\syntype 6
203 \package
204 \srefaddidkey{syntype}
205 \addmetakey*{syntype}{system}
206 \addmetakey*{syntype}{for}
207 \newcommand\type@type{Type}
208 \newcommand\syntype[3][\metasetkeys{syntype}{#1}\sref@target%
209 \noindent\type@type \ifx\syntype@empty\else (\syntype@system)\fi #2: $#3$}
210 \package
211 \ltxml
212 DefConstructor('\syntype OptionalKeyVals:omtext {}{}',
213   "<omdoc:type for='#2'"
214   . " ?&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id').not')()"
215   . " ?&GetKeyVal(#1,'system')(xml:id='&GetKeyVal(#1,'system'))()>"
216   . "<ltx:Math><ltx:XMath>#3</ltx:XMath></ltx:Math>"
217   . "</omdoc:type>");
218 \ltxml

\inlinetypedec
219 \package
220 \newcommand\inlinetypedec[3][\metasetkeys{syntype}{#1}\sref@target{\def\thedectype{#2}#3}]
221 \package
222 \ltxml
223 DefConstructor('\inlinetypedec OptionalKeyVals:omtext {}{}',
224   "<omdoc:type for='#2'"
225   . " ?&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id').not')()"
226   . " ?&GetKeyVal(#1,'system')(xml:id='&GetKeyVal(#1,'system'))()>"
227   . "<ltx:Math><ltx:XMath>#2</ltx:XMath></ltx:Math>"
228   . "<omdoc:CMP>#body"
229   . "</omdoc:type>");
230 \ltxml

typedec We first define a theorem environment
231 \package
232 \def\st@typedec@kw{Type Declaration}
233 \theorembodyfont{\upshape}
234 \newtheorem{STtypedecEnv}[STtheoremAssEnv]{\st@typedec@kw}
and then the environment itself.
235 \newenvironment{typedec}[2][\metasetkeys{omtext}{#1}\sref@target%
236 \def\thedectype{#2}]%
237 \ifx\omtext@display\st@flow\else%
238 \ifx\omtext@title\empty\begin{STtypedecEnv}\else\begin{STtypedecEnv}[\omtext@title]\fi%
239 \ifx\sref@id\empty\else\label{typedec.\sref@id}\fi
240 \ifx\sref@id\empty\sref@label@id{here}\else%
241 \sref@label@id{\STpresent{\csname STtypedecEnvKeyword\endcsname}~\@currentlabel}\fi%

```

---

<sup>6</sup>EdNOTE: MK@DG; the type element should percolate up.

```

242 \ignorespaces}
243 {\ifx\omtext@display\st@flow\else\end{STtypedecEnv}\fi\omtext@post@skip}
244 \package}
245 \ltxml)
246 DefStatement('{typedec} OptionalKeyVals:omtext {}',
247   "<omdoc:type for='&GetKeyVal(#1,'for')'",
248   .   "?&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id').not')()"
249   .   "?&GetKeyVal(#1,'system')(xml:id='&GetKeyVal(#1,'system'))()>"
250   .   "?&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
251   .   "<ltx:Math><ltx:XMath>#2</ltx:XMath></ltx:Math>"
252   .   "<omdoc:CMP>#body"
253   . "</omdoc:type>");
254 \ltxml)

```

**definition** The definition environment itself is quite similar to the other's but we need to set the `\st@indef` switch to suppress warnings from `\st@def@target`.

```

255 \package}
256 \newif\ifst@indef\st@indeffalse
257 \newenvironment{definition}[1][\metasetkeys{omtext}{#1}\sref@target\st@indeftrue%
258 \ifx\omtext@display\st@flow\else%
259 \ifx\omtext@title\@empty\begin{STdefinitionEnv}\else\begin{STdefinitionEnv}[\omtext@title]\fi%
260 \ifx\sref@id\@empty\sref@label@id{here}\else%
261 \sref@label@id{\STpresent{\csname STdefinitionEnvKeyword\endcsname}~\@currentlabel}\fi%
262 \ignorespaces}
263 {\ifx\omtext@display\st@flow\else\end{STdefinitionEnv}\fi}
264 \def\st@definition@kw{Definition}
265 \theorembodyfont{\upshape}
266 \newtheorem{STdefinitionEnv}[STtheoremAssEnv]{\st@definition@kw}
267 \package}
268 \ltxml)
269 sub definitionBody {
270   my ($doc, $keyvals, %props) = @_;
271   my $for = $keyvals->getValue('for') if $keyvals;
272   my $type = $keyvals->getValue('type') if $keyvals;
273   my %for_attr=();
274   if (ToString($for)) {
275     $for = ToString($for);
276     $for =~ s/^(.+)$/$1/eg;
277     foreach (split(/,\s*/, $for)) {
278       $for_attr{$_}=1;
279     }
280   }
281   if ($props{theory}) {
282     my @symbols = @{$props{defs} || []};
283     my $signature = $props{signature};
284     foreach my $symb(@symbols) {
285       next if $for_attr{$symb};
286       my $qualified_symbol = $signature ? "$signature?$symb" : $symb;
287       $for_attr{$qualified_symbol}=1;
288       if (!$props{multiling}) {
289         $doc->insertElement('omdoc:symbol', undef, (name=>$symb, "xml:id"=>makeNCName("$symb.

```

```

289     }
290   }
291   my %attrs = ();
292   $for = join(" ",(sort keys %for_attr));
293   $attrs{'for'} = $for if $for;
294   my $id = $keyvals->getValue('id') if $keyvals;
295   $attrs{'xml:id'} = $id if $id;
296   $attrs{'type'} = $type if $type;
297   if ($props{theory}) {
298     $doc->openElement('omdoc:definition', %attrs);
299   } else {
300     $attrs{'type'}='definition';
301     $doc->openElement('omdoc:omtext', %attrs);
302   }
303   my $title = $keyvals->getValue('title') if $keyvals;
304   if ($title) {
305     $doc->openElement('omdoc:metadata');
306     $doc->openElement('dc:title');
307     $doc->absorb($title);
308     $doc->closeElement('dc:title');}
309   $doc->openElement('omdoc:CMP');
310   $doc->absorb($props{body}) if $props{body};
311   $doc->maybeCloseElement('omdoc:CMP');
312   if ($props{theory}) {
313     $doc->closeElement('omdoc:definition');
314   } else {
315     $doc->closeElement('omdoc:omtext');
316   }
317   return; }
318 # We use the standard DefEnvironment here, since
319 # afterDigestBegins would collide otherwise
320 DefEnvironment('{definition} OptionalKeyVals:omtext', \&definitionBody,
321 afterDigestBegin=>sub {
322   my ($stomach, $whatsit) = @_;
323   my @symbols = ();
324   $whatsit->setProperty(multiling=>LookupValue('multiling'));
325   $whatsit->setProperty(theory=>(LookupValue('modnl_signature') || LookupValue('current_modul
326   $whatsit->setProperty(defs=>\@symbols);
327   $whatsit->setProperty(signature=>LookupValue('modnl_signature'));
328   AssignValue('defs', \@symbols);
329   declareFunctions($stomach,$whatsit);
330   return; },
331 afterDigest => sub { AssignValue('defs', undef); return; });
332 </txml>%$

```

**notation** We initialize the `\def\st@notation@initialize{}` here, and extend it with functionality below.

```

333 <*package>
334 \def\notemph#1{#1}
335 \def\st@notation@terminate{

```

```

336 \def\st@notation@initialize{}
337 \define@statement@env{notation}
338 \def\st@notation@kw{Notation}
339 \theorembodyfont{\upshape}
340 \newtheorem{STnotationEnv}[STtheoremAssEnv]{\st@notation@kw}
341 \</package>
342 \*ltxml>
343 DefStatement('notation' OptionalKeyVals:omtext',
344   "<omdoc:definition "
345   .   "?&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id').not')()"
346   .   "?&GetKeyVal(#1,'for')(for='&simple_wrapper(&GetKeyVal(#1,'for'))')()>"
347   .   "?&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
348   .   "<omdoc:CMP>#body"
349   .   "</omdoc:definition>\n");
350 DefConstructor('\notatiendum OptionalKeyVals:notation {}',
351   "<ltx:text class='notatiendum'>#2</ltx:text>");
352 \</ltxml>

```

`\st@def@target` the next macro is a variant of the `\sref@target` macro provided by the `sref` package specialized for the use in the `\definiendum`, `\defi`, `\defii`, and `\defiii` macros. `\st@def@target{<opt>}{<name>}` makes a target with label `sref@<opt>@<module name>@target`, if `<opt>` is non-empty, else with the label `sref@<name>@<module name>@target`. Also it generates the necessary warnings for a `definiendum`-like macro.

```

353 \*package>
354 \def\st@def@target#1#2{\def\@test{#1}%
355 \ifst@indef% if we are in a definition or such
356 \@ifundefined{mod@id}% if we are not in a module
357 {\PackageWarning{statements}{definiendum in unidentified module\MessageBreak
358 \protect\definiendum, \protect\defi,
359 \protect\defii, \protect\defiii\MessageBreak
360 can only be referenced when called in a module with id key}}%
361 {\edef\@cd{\ifx\omtext@theory\@empty\mod@id\else\omtext@theory\fi}%
362 \edef\@name{\ifx\@test\@empty{#2}\else{#1}\fi}%
363 \expandafter\sref@target@ifh{sref@\@name @\@cd @target}{}%
364 \ifmetakeys@showmeta\metakeys@show@keys{\@cd}{name:\@name}\fi}%
365 \else% st@indef
366 \PackageError{statements}%
367 {definiendum outside definition context\MessageBreak
368 \protect\definiendum, \protect\defi,
369 \protect\defii, \protect\defiii\MessageBreak
370 do not make sense semantically outside a definition.\MessageBreak
371 Consider wrapping the defining phrase in a \protect\inlinedef}%
372 \fi}
373 \</package>

```

The `\definiendum` and `\notatiendum` macros are very simple.

`\@termdef` This macro is experimental, it is supposed to be invoked in `\definiendum` to define a macro with the `definiendum` text, so that can be re-used later in term



```

407 afterDigest => sub { defHelper(@_, 'defi'); },
408 alias=>'\\defi');
409 \\ltxml\\

\\defii
410 \\*package\\
411 \\newcommand\\defii[3] [] {\\def\\@name{#1}\\def\\@text{#2}\\def\\@verb{#3}%
412 \\ifx\\@name\\@empty\\st@def@target{#3}{#2}\\defemph{#2}%
413 \\else\\st@def@target{#1}{#2}\\defemph{#2}\\fi\\@defii}
414 \\newcommand\\@defii[1] [] {%
415 \\ifdef@index\\ifx\\@name\\@empty\\omdoc@index[#1]{\\@text}\\else\\omdoc@index[at=\\@name,#1]{\\@verb}\\fi
416 \\}
417 \\ltxml\\
418 DefConstructor('\\defii[]{}{} OptionalKeyVals:DEF',
419 "?#defindex(<omdoc:idx><omdoc:idt>)"
420 . " <omdoc:term role='definiendum' name='?#1(#1)(#3)' cd='#theory'>#2</omdoc:term>"
421 . "?#defindex(</omdoc:idt><omdoc:ide index='default'><omdoc:idp>#3</omdoc:idp></omdoc:ide
422 afterDigest => sub { defHelper(@_, 'defii'); },
423 alias=>'\\defii');
424 \\ltxml\\

\\defiii
425 \\*package\\
426 \\newcommand\\defiii[3] [] {\\def\\@pone{#2}\\def\\@ptwo{#3}%
427 \\st@def@target{#1}{#2-#3}\\defemph{#2 #3}\\@defiii}
428 \\newcommand\\@defiii[1] [] {\\ifdef@index\\@twin[#1]{\\@pone}\\@ptwo}\\fi\\xspace}
429 \\newcommand\\defiiis[3] [] {\\def\\@pone{#2}\\def\\@ptwo{#3}%
430 \\st@def@target{#1}{#2-#3}\\defemph{#2 #3s}\\@defiii}
431 \\ltxml\\
432 \\*package\\
433 DefConstructor('\\defiii[]{}{} OptionalKeyVals:DEF',
434 "?#defindex(<omdoc:idx><omdoc:idt>)"
435 . " <omdoc:term role='definiendum' name='?#1(#1)(\\&dashed{#2,#3})' cd='#theory'>"
436 . " #2 #3"
437 . " </omdoc:term>"
438 . "?#defindex(</omdoc:idt><omdoc:ide index='default'><omdoc:idp>#2</omdoc:idp><omdoc:idp>#3</om
439 afterDigest => sub { defHelper(@_, 'defiii'); },
440 alias=>'\\defiii');
441 DefConstructor('\\defiiis[]{}{} OptionalKeyVals:DEF',
442 "?#defindex(<omdoc:idx><omdoc:idt>)"
443 . " <omdoc:term role='definiendum' name='?#1(#1)(\\&dashed{#2,#3})' cd='#theory'>"
444 . " #2 #3s"
445 . " </omdoc:term>"
446 . "?#defindex(</omdoc:idt><omdoc:ide index='default'><omdoc:idp>#2</omdoc:idp><omdoc:idp>#3</om
447 afterDigest => sub { defHelper(@_, 'defiii'); },
448 alias=>'\\defiii');
449 \\ltxml\\

\\adefii

```



```

496 "?#defindex(<omdoc:idx><omdoc:idt>)"
497 . "<omdoc:term role='definiendum' cd='#theory' name='?#1(#1)(&dashed(#3,#4,#5))'>#2</omdoc:ter
498 ."?#defindex(</omdoc:idt><omdoc:ide index='default'><omdoc:idp>#3</omdoc:idp><omdoc:idp>#4</om
499         afterDigest => sub { defHelper(@_, 'adefiii')},
500         alias=>'adefiii');
501 </ltxml>

\inlineex
502 <*package>
503 \newcommand\inlineex[2][\metasetkeys{omtext}{#1}%
504 \sref@target\sref@label@id{here}#2}
505 </package>
506 <*ltxml>
507 DefConstructor('\inlineex OptionalKeyVals:omtext {}',
508               "<ltx:text class='example'>#2</ltx:text>");
509 </ltxml>

\inlineass
510 <*package>
511 \newcommand\inlineass[2][\metasetkeys{omtext}{#1}%
512 \sref@target\sref@label@id{here}#2}
513 </package>
514 <*ltxml>
515 DefConstructor('\inlineass OptionalKeyVals:omtext {}',
516               "<ltx:text "
517               . "&GetKeyVal(#1,'type')(class='&GetKeyVal(#1,'type') assertion')(class='assert
518               . "#2"
519               . "</ltx:text>");
520 </ltxml>

\inlinedef
521 <*package>
522 \newcommand\inlinedef[2][\metasetkeys{omtext}{#1}%
523 \if@in@omtext\else% we are not in an omtex or statement
524 \PackageError{modules}{\protect\inlinedef\space outside a statement!}%
525 {Try wrapping the paragraph in a\MessageBreak
526 \protect\begin{omtext}, \protect\begin{assertion}, \protect\begin{axiom}, ... \MessageBreak
527 whatever is suitable semantically}\fi%
528 \sref@target\sref@label@id{here}\st@indeftrue #2}
529 </package>
530 <*ltxml>
531 DefConstructor('\inlinedef OptionalKeyVals:omtext {}', sub {
532   my ($document, $keyvals, $body, %props) = @_;
533   my $for = $keyvals->getValue('for') if $keyvals;
534   my %for_attr=();
535   if (ToString($for)) {
536     $for = ToString($for);
537     $for =~ s/^(.+)$/$/1/eg;
538     foreach (split(/,\s*/, $for)) {

```



```

539     $for_attr{$_}=1;
540   }}
541   my @symbols = @{$props{defs} || []};
542   #Prepare for symbol insertion -insert before the parent of the closest ancestor CMP element
543   my $original_node = $document->getNode;
544   my $statement_ancestor = $document->findnode('./ancestor::omdoc:CMP/..', $original_node);
545   foreach my $symb(@symbols) {
546     next if $for_attr{$symb};
547     $for_attr{$symb}=1;
548     my $symbolnode = XML::LibXML::Element->new('symbol');
549     $symbolnode->setAttribute(name=>$symb);
550     $symbolnode->setAttribute("xml:id"=>makeNCName("$symb.def.sym"));
551     if ($statement_ancestor) {
552       $statement_ancestor->parentNode->insertBefore($symbolnode,$statement_ancestor);
553     } else {
554       Error('malformed', $statement_ancestor, $original_node, "\\inlinedef outside a statement!
555 Try wrapping the paragraph in a begin{omtext}, \\begin{assertion}, \\begin{axiom}...\nwhatever
556 #Restore the insertion point
557 $document->setNode($original_node);
558 my %attrs = ();
559 $for = join(" ",(sort keys %for_attr));
560 $attrs{'for'} = $for if $for;
561 my $id = $keyvals->getValue('id') if $keyvals;
562 $attrs{'xml:id'} = $id if $id;
563 $attrs{'class'} = 'inlinedef';
564 $document->openElement('ltx:text',%attrs);
565 $document->absorb($body);
566 $document->closeElement('ltx:text'); },
567 #Prepare 'defs' hooks for \defi and \definendum symbol names
568 beforeDigest=>sub {
569   my @symbols = ();
570   AssignValue('defs', \@symbols); return; },
571 #Adopt collected names as 'defs' property, remove hooks
572 afterDigest=>sub {
573   my ($stomach, $whatsit) = @_;
574   my $defsref = LookupValue('defs');
575   my @defs = @$defsref;
576   $whatsit->setProperty('defs',\@defs);
577   AssignValue('defs',undef);
578   return; };##$
579 </ltxml>

```

### 5.3 Cross-Referencing Symbols and Concepts

`\termref` We delegate to the worker macro `\st@termref` after setting the default for the `cd` key.

```

580 <*package>
581 \addmetakey*{termref}{cd}
582 \addmetakey*{termref}{cibase}

```

```

583 \addmetakey*{termref}{name}
584 \addmetakey*{termref}{role}
585 \newcommand\termref[2][]{\metasetkeys{termref}{#1}%
586 \ifx\termref@cd\@empty\def\termref@cd{\mod@id}\fi%
587 \st@termref{#2}}
588 \</package>
589 \<|xml>
590 DefConstructor('\termref OptionalKeyVals:termref {}',
591               "<omdoc:term "
592               . "?&GetKeyVal(#1,'cbase')(cbase='&GetKeyVal(#1,'cbase'))() "
593               . "cd='&GetKeyVal(#1,'cd')(&GetKeyVal(#1,'cd'))(#module)' "
594               . "name='&GetKeyVal(#1,'name')>"
595               . "#2"
596               . "</omdoc:term>",
597               afterDigest=>sub{$_[1]->setProperty(module=>(LookupValue('modnl_signature') || Lo
598 \</xml>)%$

```

The next macro is where the actual work is done.

`\st@termref` If the `cbase` is given, then we make a hyper-reference, otherwise we punt to `\mod@termref`, which can deal with the case where the `cbase` is given by the imported `cd`.

```

599 \<|xml>
600 \newcommand\st@termref[1]{\ifx\termref@name\@empty\def\termref@name{#1}\fi%
601 \ifx\termref@cbase\@empty\mod@termref\termref@cd\termref@name{#1}%
602 \else\sref@href@ifh\termref@cbase{#1}\fi}
603 \</package>

```

`\tref*`

```

604 \<|xml>RawTeX('
605 \<|xml>
606 \newcommand\atrefi[3][]{\def\@test{#1}%
607 \ifx\@test\@empty\termref[name=#3]{#2}\else\termref[cd=#1,name=#3]{#2}\fi}
608 \newcommand\atrefii[4][]{\atrefi[#1]{#2}{#3-#4}}
609 \newcommand\atrefiii[5][]{\atrefi[#1]{#2}{#3-#4-#5}}

```

`\tref*`

```

610 \newcommand\trefi[2][]{\atrefi[#1]{#2}{#2}}
611 \newcommand\trefii[3][]{\atrefi[#1]{#2 #3}{#2-#3}}
612 \newcommand\trefiii[4][]{\atrefi[#1]{#2 #3 #4}{#2-#3-#4}}
613 \newcommand\trefis[2][]{\atrefi[#1]{#2s}{#2}}
614 \newcommand\trefiis[3][]{\atrefi[#1]{#2 #3s}{#2-#3}}
615 \newcommand\trefiiis[4][]{\atrefi[#1]{#2 #3 #4s}{#2-#3-#4}}
616 \</package> \<|xml>
617 \<|xml>';

```

Now we care about the configuration switches, they are set to sensible values, if they are not defined already. These are just configuration parameters, which should not appear in documents, therefore we do not provide L<sup>A</sup>T<sub>E</sub>XML bindings for them.

`\*emph`

```
618 <*package>
619 \providecommand{\termemph}[1]{#1}
620 \providecommand{\defemph}[1]{\textbf{#1}}
621 \providecommand{\stDMemph}[1]{\textbf{#1}}
622 </package>
```

EdN:7

`\term` The `\term` macro is used for wiki-style dangling links with editor support.<sup>7</sup>

```
623 <*package>
624 \newcommand\term[2][\def\@test{#1}%
625 \ifx\@test\@empty\else
626 \@ifundefined{module@defs@#1}{\PackageWarning{statements}%
627 {\protect\term} specifies module #1 which is not in
628 scope\MessageBreak import it via e.g. via \protect\importmhmodule}}{}
629 \fi%
630 \PackageWarning{statements}%
631 {Dangling link (\protect\term) for "#2" still needs to be specified}%
632 \textcolor{blue}{\underline{#2}}
633 </package>
634 <*ltxml>
635 DefConstructor('\term{}', "<omdoc:term class='dangling-term-link' ?#1(cd='#1')()>#1</omdoc:term>
636 </ltxml>
```

`\symref` The `\symref` macros is quite simple, since we have done all the heavy lifting in the modules package: we simply apply `\mod@symref@<arg1>` to `<arg2>`.

```
637 <*package>
638 \newcommand\symref[2]{\@nameuse{mod@symref@#1}{#2}}
639 </package>
640 <*ltxml>
641 DefConstructor('\symref{}{}',
642               "<omdoc:term cd='&LookupValue('symdef.#1.cd')' name='&LookupValue('symdef.#1.nam
643               . \"#2\"
644               . "</omdoc:term>");
645 </ltxml>
```

## 5.4 Providing IDs for OMDoc Elements

To provide default identifiers, we tag all OMDoc elements that allow `xml:id` attributes by executing the `numberIt` procedure from `omdoc.sty.ltxml`.

```
646 <*ltxml>
647 Tag('omdoc:assertion', afterOpen=>\&numberIt, afterClose=>\&locateIt);
648 Tag('omdoc:definition', afterOpen=>\&numberIt, afterClose=>\&locateIt);
649 Tag('omdoc:example', afterOpen=>\&numberIt, afterClose=>\&locateIt);
650 Tag('omdoc:equation', afterOpen=>\&numberIt, afterClose=>\&locateIt);
651 Tag('omdoc:axiom', afterOpen=>\&numberIt, afterClose=>\&locateIt);
652 Tag('omdoc:symbol', afterOpen=>\&numberIt, afterClose=>\&locateIt);
653 Tag('omdoc:type', afterOpen=>\&numberIt, afterClose=>\&locateIt);
```

---

<sup>7</sup>EdNOTE: MK: document above

```

654 Tag('omdoc:term',afterOpen=>\&numberIt,afterClose=>\&locateIt);
655 </ltxml>

```

## 5.5 Auxiliary Functionality

```

656 <*ltxml>
657 # =====
658 #   Auxiliary Functions:                                     #
659 #   =====
660 sub DefStatement {
661   my ($definition,$replacement,%properties)=@_;
662   DefEnvironment($definition,$replacement,%properties,
663     afterDigestBegin=>\&declareFunctions,
664   );}
665
666 sub declareFunctions{
667   my ($stomach,$whatsit) = @_;
668   my $keyval = $whatsit->getArg(1);
669   my $funval = GetKeyVal($keyval,'functions') if GetKeyVal($keyval,'functions');
670   return unless $funval;
671   my @funsyms = $funval->unlist;
672   #Unread the function declarations at the Gullet
673   foreach (@funsyms) {
674     my $symb = UnTeX($_);
675     $stomach->getGullet->unread(Tokenize('\lxDeclare[role=FUNCTION]{$'.$symb.'$}')->unlist);
676   }
677   return; }
678 sub defHelper{
679   my ($stomach, $whatsit, $defOption) = @_;
680   my $addr = LookupValue('defs');
681   my $name = $whatsit->getArg(1);
682   $name = $name->toString if $name;
683   my %choose_option = (
684     definiendum => sub {$whatsit->getArg(2);},
685     defi => sub {$whatsit->getArg(2);},
686     adefi => sub {$whatsit->getArg(3);},
687     defii => sub {$whatsit->getArg(2)->toString.'-'. $whatsit->getArg(3)->toString},
688     adefii => sub {$whatsit->getArg(3)->toString.'-'. $whatsit->getArg(4)->toString},
689     defiii => sub {$whatsit->getArg(2)->toString.'-'. $whatsit->getArg(3)->toString},
690     adefiii => sub {$whatsit->getArg(3)->toString.'-'. $whatsit->getArg(4)->toString},
691   );
692   $name = $name || $choose_option{$defOption}->();
693   $whatsit->setProperty(name=>$name->toString) if ref($name);
694   push(@$addr, $name) if ($addr and $name);
695   $whatsit->setProperty('defindex', IfCondition(T_CS('if@defindex')));
696   $whatsit->setProperty(theory=>(LookupValue('modnl_signature') || LookupValue('current_module')));
697   return;}##
698 </ltxml>

```

## 5.6 Deprecated Functionality

In this section we centralize old interfaces that are only partially supported any more.

`\*def*`

```
699 <ltxml>##### Deprecated functionality:
700 <ltxml>RawTeX('
701 <*package | ltxml>
702 \newcommand\defin[2] [] {\defi[#1]{#2}%
703 \PackageWarning{statements}{\protect\defin\space is deprecated, use \protect\defi\space instead
704 \newcommand\twindef[3] [] {\defii[#1]{#2}{#3}%
705 \PackageWarning{statements}{\protect\twindef\space is deprecated, use \protect\defii\space inst
706 \newcommand\atwindef[4] [] {\defiii[#1]{#2}{#3}{#4}%
707 \PackageWarning{statements}{\protect\atwindef\space is deprecated, use \protect\defiii\space in
708 \newcommand\definalt[3] [] {\adefi[#1]{#2}{#3}%
709 \PackageWarning{statements}{\protect\definalt\space is deprecated, use \protect\adefi\space ins
710 \newcommand\twindefalt[4] [] {\adefii[#1]{#2}{#3}{#4}%
711 \PackageWarning{statements}{\protect\twindefalt\space is deprecated, use \protect\adefii\space
712 \newcommand\atwindefalt[5] [] {\adefiii[#1]{#2}{#3}{#4}{#5}%
713 \PackageWarning{statements}{\protect\atwindefalt\space is deprecated, use \protect\adefiii\spac
```

`\*def*`

```
714 \newcommand\twinref[3] [] {\trefii[#1]{#2}{#3}%
715 \PackageWarning{statements}{\protect\twinref\space is deprecated, use \protect\trefii\space ins
716 \newcommand\atwinref[4] [] {\atrefiii[#1]{#2}{#3}{#4}%
717 \PackageWarning{statements}{\protect\atwinref\space is deprecated, use \protect\trefiii\space i
718 </package | ltxml>
719 <ltxml>');;
```

## 5.7 Finale

Finally, we need to terminate the file with a success mark for perl.

```
720 <ltxml>1;
```

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<i>*</i> ,	10	statement,	2	OPENMATH,	5
block					
statement,	2	LATEXML, 11, 12, 21, 26	statement		
			block,		2
flow		OMDoc, 2, 4, 5, 27	flow,		2

## References

- [KG15] Michael Kohlhasse and Deyan Ginev. *smultiling.sty: Multilinguality Support for sTeX*. Tech. rep. 2015. URL: <https://github.com/KWARC/sTeX/raw/master/sty/smultiling/smultiling.pdf>.
- [KGA15] Michael Kohlhasse, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Tech. rep. Comprehensive T<sub>E</sub>X Archive Network (CTAN), 2015. URL: <http://www.ctan.org/get/macros/latex/contrib/stex/modules/modules.pdf>.
- [Koh06] Michael Kohlhasse. OMDOC – *An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh08] Michael Kohlhasse. “Using L<sup>A</sup>T<sub>E</sub>X as a Semantic Markup Format”. In: *Mathematics in Computer Science 2.2* (2008), pp. 279–304. URL: <https://svn.kwarc.info/repos/stex/doc/mcs08/stex.pdf>.
- [Koh15a] Michael Kohlhasse. *metakeys.sty: A generic framework for extensible Metadata in L<sup>A</sup>T<sub>E</sub>X*. Tech. rep. Comprehensive T<sub>E</sub>X Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/metakeys/metakeys.pdf>.
- [Koh15b] Michael Kohlhasse. *omdoc.sty/cls: Semantic Markup for Open Mathematical Documents in L<sup>A</sup>T<sub>E</sub>X*. Tech. rep. Comprehensive T<sub>E</sub>X Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/omdoc/omdoc.pdf>.
- [Koh15c] Michael Kohlhasse. *sref.sty: Semantic Crossreferencing in L<sup>A</sup>T<sub>E</sub>X*. Tech. rep. Comprehensive T<sub>E</sub>X Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/sref/sref.pdf>.
- [MS] Wolfgang May and Andreas Schedler. *An Extension of the L<sup>A</sup>T<sub>E</sub>X-Theorem Environment*. Self-documenting L<sup>A</sup>T<sub>E</sub>X package. URL: <http://dante.ctan.org/tex-archive/macros/latex/contrib/ntheorem/ntheorem.pdf> (visited on 01/11/2010).
- [sTeX] *KWARC/sTeX*. URL: <https://svn.kwarc.info/repos/stex> (visited on 05/15/2015).