

workaddress.sty: An Infrastructure for managing Addresses and Affiliations in L^AT_EX*

Michael Kohlhase John Doe
Jacobs University DFKI
<http://kwarc.info/kohlhase> <http://dfki.de/jdoe>

September 12, 2016

Abstract

The **workaddress** package allows manage addresses and Affiliations in a
bibT_EX-like manner.¹

EdN:1

Contents

1	Introduction	2
2	The User Interface	2
2.1	Package Options	2
2.2	Database Entries for Persons	2
2.3	Institutions	3
2.4	Applications	4
3	Limitations	4
4	The Implementation	4
4.1	Package Options	4
4.2	Persons	4
4.3	Institutions	6
4.4	Applications	7

*Version v0.5 (last revised 2016/07/06)

¹EdNOTE: continue

EdN:2

1 Introduction

The `workaddress` package allows manage Addresses and affiliations of persons in a `bibTeX`-like manner.²

2 The User Interface

2.1 Package Options

`showmeta` The `workaddress` package takes a single option: `showmeta`. If this is set, then the metadata keys are shown (see [Koh16] for details and customization options).

2.2 Database Entries for Persons

The `workaddress` package recognizes that from a metadata perspective, persons are complex entities. In particular, specifying metadata is a tedious and repetitive task that leads to embarrassing errors. Therefore the `workaddress` package takes a hint from `bibTeX` and allows to specify personal metadata in a database and use it by a database key. The `\WAperson` macro allows to specify personal metadata³

```
\WAperson[id=jdoe,affiliation=dfki,department=skss,
          url=http://dfki.de/jdoe]
{John Doe}
\WAperson[id=miko,affiliation=jacu,department=case,
          url=http://kwarc.info/kohlhase]
{Michael Kohlhase}
```

Example 1: A small database of Persons

EdN:3

`\WAperson`

with the following keys:

²EDNOTE: continue

³EDNOTE: This should be synchronized with the FOAF specification [BM07]

key	value	comment
id	string	identifier of this person
birthdate	date	birthdate
email		the primary e-mail address
url	URI	primary home page
affiliation	Inst. identifier	the primary professional affiliation
personaltitle	string	the personal title e.g. King
academictitle	string	the academic title e.g. Prof. Dr.
department	Inst. identifier	the department specified in the work address
workaddress	long string	the work address
privaddress	long string	the private address
worktel	string	work telephone number
privtel	string	private telephone number
workfax	string	work fax number
privfax	string	private fax number
worktelfax	string	if the phone and fax share a prefix, give this as well
privtelfax	string	dito

In Figure 1 we have specified (minimal) metadata for the authors of the **workaddress** package. The metadata can be accessed by specifying the identifiers (given by the **id** key) in the **workaddress** macros defined below, see for instance the **\WAcreeators** macro in Figure ??, which leads to the title block of this note.

Like in bibTeX [Pat], it is a good idea to collect the metadata in a separate file that is input in the document. In practice it may be possible to generate these files from conventional address databases.

2.3 Institutions

Institutions are treated analogously to persons. The **\Wainstitution** macro al-

```
\Wainstitution[id=case,partof=jacu,acronym=CASE,
               url=http://jacobs-university.de/ses/case]
               {Center for Advanced Systems Engineering}
\Wainstitution[id=jacu,url=http://jacobs-university.de]
               {Jacobs University Bremen}
\Wainstitution[id=skss,partof=dfki,url=http://dfki.de/sks,acronym=SKS]
               {Safe and Secure Cognitive Systems}
\Wainstitution[id=dfki,url=http://dfki.de,shortname=DFKI,acronym=DFKI]
               {German Research Center for Artificial Intelligence}
```

Example 2: A small Database of Institutions and their Parts

\Wainstitution

allows to specify personal metadata⁴ with the following keys:

⁴EdNOTE: This should be synchronized with the FOAF specification [BM07]

key	value	comment
id	string	identifier of this person
url	URI	primary home page
partof	Inst. identifier	parent institution

2.4 Applications

The data from the address database can be used in various ways. For instance, the `\WAauthorblock` macro creates a block of users and their affiliations. In the context of the database from Figures 1 and 2, `\WAauthorblock{miko,jdoe}` creates

Michael Kohlhase John Doe

`\wa@institution@logo` `\wa@institution@logo` creates the logo of an institution from the database, and (if that is not there create a box and a message instead.)

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `sTeX` GitHub repository [sTeX].

1. none reported yet

4 The Implementation

4.1 Package Options

The first step is to declare (a few) package options that handle whether certain information is printed or not. They all come with their own conditionals that are set by the options.

```

1 <*package>
2 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{sref}}
3 \ProcessOptions

```

The first measure is to ensure that the `KeyVal` package is loaded (in the right version). For `LATEXML` we also initialize the package inclusions.

```

4 \RequirePackage{sref}

```

4.2 Persons

To implement the `\WAperson` macro, we need to implement its keywords.

```

5 \addmetakey*{wa@person}{id}
6 \addmetakey*{wa@person}{birthdate}
7 \addmetakey*{wa@person}{email}
8 \addmetakey*{wa@person}{url}

```

```

9 \addmetakey*{wa@person}{affiliation}
10 \addmetakey*{wa@person}{personaltitle}
11 \addmetakey*{wa@person}{academictitle}
12 \addmetakey*{wa@person}{department}
13 \addmetakey*{wa@person}{workaddress}
14 \addmetakey*{wa@person}{privaddress}
15 \addmetakey*{wa@person}{worktel}
16 \addmetakey*{wa@person}{privtel}
17 \addmetakey*{wa@person}{workfax}
18 \addmetakey*{wa@person}{privfax}
19 \addmetakey*{wa@person}{worktelfax}
20 \addmetakey*{wa@person}{privtelfax}

```

\wa@def The next macro is an auxiliary one that puts the value into an appropriate token register.

```

21 \def\wa@def#1#2#3#4{\expandafter\xdef\csname wa@#1@#2@#3\endcsname{#4}}

```

\wa@ref This macro looks up the information specified in the three last arguments. The first argument determines the behavior if that information is undefined: **\wa@ref0** fails silently (no output, no message), **\waref1** raises a warning but outputs nothing, and **\wa@ref2{<a>}{}{<c>}** raises a warning and outputs **?<a>???**, Finally **\wa@ref3** gives an error and aborts.

```

22 \newcommand\wa@ref[4]{%
23   \ifundefined{wa@#2@#3@#4}{%
24     \ifcase#1 {} \or%
25     \PackageWarning{workaddress}{reference to undefined #4 of #2 #3\MessageBreak%
26       you must define a #2 with #3=#4\MessageBreak%
27       via the macro \protect\WA#2, before you can use it!}%
28     \or
29     \PackageWarning{workaddress}{reference to undefined #4 of #2 #3\MessageBreak%
30       you must define a #2 with #3=#4\MessageBreak%
31       via the macro \protect\WA#2, before you can use it!}%
32     ?#2?#3?#4?
33     \or
34     \PackageError{workaddress}{reference to undefined #4 of #2 #3}%
35     {you must define a #2 with #3=#4\MessageBreak%
36       via the macro \protect\WA#2, before you can use it!}
37     \else\PackageError{workaddress}{\protect\wa@ref#1 not defined}
38     \fi
39   }\csname wa@#2@#3@#4\endcsname}}%

```

With this we can define the **\WAperson** macro, it just clears the keys, sets them again, and stores them in token registers. Of course only if a **id** attribute is given, else we raise an error.

WAperson

```

40 \let\wa@persons=\relax
41 \newcommand\WAperson[2] [] {%
42   \metasetkeys{wa@person}{#1}%

```

```

43 \ifx\wa@person@id\@empty%
44 \latex@warning{key 'id' undefined in WAperson}%
45 \else%
46 \wa@def{person}\wa@person@id{id}{\wa@person@id}% redundant, but useful for checking
47 \wa@def{person}\wa@person@id{name}{#2}
48 \wa@def{person}\wa@person@id{email}{\wa@person@email}
49 \wa@def{person}\wa@person@id{birthdate}{\wa@person@birthdate}
50 \wa@def{person}\wa@person@id{url}{\wa@person@url}
51 \wa@def{person}\wa@person@id{affiliation}{\wa@person@affiliation}
52 \wa@def{person}\wa@person@id{workaddress}{\wa@person@workaddress}
53 \wa@def{person}\wa@person@id{privaddress}{\wa@person@privaddress}
54 \wa@def{person}\wa@person@id{personaltitle}{\wa@person@personaltitle}
55 \wa@def{person}\wa@person@id{academictitle}{\wa@person@academictitle}
56 \wa@def{person}\wa@person@id{department}{\wa@person@department}
57 \wa@def{person}\wa@person@id{workaddress}{\wa@person@workaddress}
58 \wa@def{person}\wa@person@id{privaddress}{\wa@person@privaddress}
59 \wa@def{person}\wa@person@id{worktel}{\wa@person@worktel}
60 \wa@def{person}\wa@person@id{privtel}{\wa@person@privtel}
61 \wa@def{person}\wa@person@id{workfax}{\wa@person@workfax}
62 \wa@def{person}\wa@person@id{privfax}{\wa@person@privfax}
63 \wa@def{person}\wa@person@id{worktelfax}{\wa@person@worktelfax}
64 \wa@def{person}\wa@person@id{privtelfax}{\wa@person@privtelfax}
65 \@ifundefined{wa@persons}{%
66 \xdef\wa@persons{\wa@person@id}%
67 }{%
68 \xdef\wa@persons{\wa@persons,\wa@person@id}%
69 }%
70 \fi%
71 }%
72 \newcommand\DCMperson[2][]{%
73 \WAperson[#1]{#2}%
74 \PackageWarning{workaddress}{\protect\DCMperson\space is deprecated, use \protect\WAperson\space}
75 }%

```

4.3 Institutions

To implement the \WAinstitution macro, we need to implement its keywords first.

```

76 \addmetakey*{wa@institution}{id}
77 \addmetakey*{wa@institution}{shortname}
78 \addmetakey*{wa@institution}{acronym}
79 \addmetakey*{wa@institution}{url}
80 \addmetakey*{wa@institution}{partof}
81 \addmetakey*{wa@institution}{countryshort}
82 \addmetakey*{wa@institution}{logo}
83 \addmetakey*{wa@institution}{streetaddress}
84 \addmetakey*{wa@institution}{townzip}
85 \addmetakey*{wa@institution}{type}
86 \addmetakey*{wa@institution}{country}

```

and we proceed as for \WAperson,

```
87 \let\wa@institutions=\relax
```

WAinstitution

```
88 \newcommand\WAinstitution[2] [] {%
89   \metasetkeys{wa@institution}{#1}%
90   \ifx\wa@institution@id\empty%
91     \@latex@warning{key 'id' undefined in WAinstitution}%
92   \else%
93     \wa@def{institution}\wa@institution@id{id}{\wa@institution@id}% redundant, but useful for c
94     \wa@def{institution}\wa@institution@id{name}{#2}
95     \wa@def{institution}\wa@institution@id{shortname}{\wa@institution@shortname}
96     \wa@def{institution}\wa@institution@id{acronym}{\wa@institution@acronym}
97     \wa@def{institution}\wa@institution@id{url}{\wa@institution@url}
98     \wa@def{institution}\wa@institution@id{partof}{\wa@institution@partof}
99     \wa@def{institution}\wa@institution@id{countryshort}{\wa@institution@countryshort}
100    \wa@def{institution}\wa@institution@id{logo}{\wa@institution@logo}
101    \wa@def{institution}\wa@institution@id{townzip}{\wa@institution@townzip}
102    \wa@def{institution}\wa@institution@id{streetaddress}{\wa@institution@streetaddress}
103    \wa@def{institution}\wa@institution@id{country}{\wa@institution@country}
104    \wa@def{institution}\wa@institution@id{type}{\wa@institution@type}
105    \@ifundefined{wa@institutions}{%
106      \xdef\wa@institutions{\wa@institution@id}%
107    }{%
108      \xdef\wa@institutions{\wa@institutions,\wa@institution@id}%
109    }%
110  \fi%
111}%
112 \newcommand\DCMinstitution[2] [] {%
113   \WAinstitution[#1]{#2}%
114   \PackageWarning{workaddress}{\protect\DCMinstitution\space is deprecated, use \protect\WAinst
115}%
```

4.4 Applications

\WAauthorblock This internal macro builds an author block from a list of \WAperson labels in \wa@creators.

```
116 \addmetakey[false]{WAauthorblock}{dept}[true]
117 \addmetakey[false]{WAauthorblock}{aff}[true]
118 \addmetakey[false]{WAauthorblock}{url}[true]
119 \def\@true{true}
120 \newcounter{authors}
121 \newcommand\WAauthorblock[2] [] {%
122   \metasetkeys{WAauthorblock}{#1}
123   {\let\tabularnewline\relax
124     \@for\@I:=#2\do{\stepcounter{authors}}
125     \def\@authors{}%
126     \def\@affs{}%
127     \def\@depts{}%
```

```

128 \def \@urls{}%
129 \@for \@I:=#2\do{%
130 \xdef \@authors{\@authors&\wa@ref2{person}\@I{name}}
131 \xdef \@dept{\wa@ref1{person}\@I{department}}
132 \xdef \@shortname{\csname wa@institution@ \@dept @shortname\endcsname}
133 \xdef \@dept{\ifx \@shortname \@empty \wa@ref0{institution}\@dept{name}\else \@shortname\fi}
134 \xdef \@depts{\@depts&\@dept}
135 \xdef \@aff{\wa@ref0{person}\@I{affiliation}}
136 \xdef \@shortname{\csname wa@institution@ \@aff @shortname\endcsname}
137 \xdef \@aff{\ifx \@shortname \@empty \wa@ref0{institution}\@aff{name}\else \@shortname\fi}
138 \xdef \@affs{\@affs&\@aff}
139 \xdef \@urls{\@urls&\wa@ref0{person}\@I{url}}
140 }%
141 \message{\theauthors authors: \@authors}%
142 }%
143 \begin{tabular}[t]{l*{\theauthors}{c}}
144 \@authors\\
145 \ifx \WAauthorblock@dept \@true \@depts\\ \fi
146 \ifx \WAauthorblock@aff \@true \@affs\\ \fi
147 \ifx \WAauthorblock@url \@true \@urls\\ \fi
148 \end{tabular}
149 }%
150 % \begin{macrocode}
151 % \end{macro}
152 %
153 % \begin{macro}{\wapname}
154 % \begin{macrocode}
155 \newcommand \wapname [1]{\wa@ref3{person}{#1}{name}}

```

\wapname

```

156 \newcommand \wapname [1]{\wa@ref3{person}{#1}{personaltitle} \wa@ref3{person}{#1}{name}}

```

\wa@institution@logo

```

157 \newcommand \wa@institution@logo [2] []{%
158 \IfFileExists{\wa@ref2{institution}{#2}{logo}}{%
159 \includegraphics{\wa@ref2{institution}{#2}{logo}}%
160 }{%
161 \fbox{#2 logo}\message{still need logo for #2}%
162 }%
163 }%
164 \</package>

```

References

- [BM07] Dan Brickley and Libby Miller. *FOAF Vocabulary Specification 0.91*. Tech. rep. ILRT Bristol, Nov. 2007. URL: <http://xmlns.com/foaf/spec/20071002.html>.

- [Koh16] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in \LaTeX* . Tech. rep. Comprehensive \TeX Archive Network (CTAN), 2016. URL: <http://mirror.ctan.org/macros/latex/contrib/stex/sty/metakeys/metakeys.pdf>.
- [Pat] Oren Patashnik. *bib \TeX ing*. URL: <http://mirrors.ctan.org/biblio/bibtex/base/btxdoc.pdf> (visited on 12/14/2009).
- [sTeX] *KWARC/sTeX*. URL: <https://github.com/KWARC/sTeX> (visited on 05/15/2015).