

stex-master.sty: \TeX 2.0*

Michael Kohlhase, Dennis Müller
FAU Erlangen-Nürnberg
<http://kwarc.info/>

November 24, 2020

Abstract

TODO

*Version v2.0 (last revised 2020/11/10)

Contents

1	Introduction	3
2	User commands	3
3	Implementation	3
3.1	sTeX base	3
3.2	Paths and URIs	4
3.3	Modules	15
3.4	Inheritance	19
3.5	Symbols/Notations/Verbalizations	28
3.6	Term References	40
3.7	sref	42
3.8	smultiling	45
3.9	smglom	45
3.10	mathhub	46
3.11	omdoc/omgroup	46
3.12	omtext	49
4	Things to deprecate	54

1 Introduction

TODO

2 User commands

- ✓ `\sTeX`
- ✓ `module`
- ✓ `\importmodule`
- ✓ `\usemodule`
- ✓ `\symdecl`
- ✓ `\notation`
- ✓ `verbalizations`
- ? `\inputref`
- ? `\libinput`
- × `\defi`
- × `\tref`
- × `omgroup/omtext`

3 Implementation

```
1 \langle *package\rangle
2 % TODO
3 \newif\if@modules@html@\@modules@html@true
4 \DeclareOption{omdocmode}{\@modules@html@false}
5 % Modules:
6 \newif\ifmod@show\mod@showfalse
7 \DeclareOption{showmods}{\mod@showtrue}
8 % sref:
9 \newif\ifextrefs\extrefsfalse
10 \DeclareOption{extrefs}{\extrefstrue}
11 %
12 \ProcessOptions
13 \RequirePackage{standalone}
14 \RequirePackage{xspace}
15 \RequirePackage{metakeys}
```

3.1 sTeX base

The sTeX logo:

```

16 \protected\def\stex{%
17   \@ifundefined{texorpdfstring}%
18   {\let\texorpdfstring\@firstoftwo}%
19   }%
20   \texorpdfstring{\raisebox{-.5ex}{S}\kern-.5ex\TeX}{sTeX}\xspace%
21 }
22 \def\sTeX{\stex}

```

and a conditional for LaTeXML:

```

23 \newif\if@latexml\@latexmlfalse

```

3.2 Paths and URIs

```

24 \RequirePackage{xstring}
25 \RequirePackage{etoolbox}

```

`\defpath` `\defpath[optional argument]{macro name}{base path}` defines a new macro which can take another path to form one integrated path. For example, `\MathHub` in every `localpaths.tex` is defined as:

```

\defpath{\MathHub}{/path/to/localmh/MathHub}

```

then we can use `\MathHub` to form other paths, for example,

```

\MathHub{source/smgglom/sets}

```

will generate `/path/to/localmh/MathHub/source/smgglom/sets`.

```

26 \newrobustcmd\defpath[3][]{%
27   \expandafter\newcommand\csname #2\endcsname[1]{#3/#1}%
28 }%

```

3.2.1 Path Canonicalization

We define two macros for changing the category codes of common characters in URIs, in particular `#`.

```

29 \def\pathsuris@setcatcodes{%
30   \edef\pathsuris@oldcatcode@hash{\the\catcode'\#}%
31   \catcode'\#=12\relax%
32   \edef\pathsuris@oldcatcode@slash{\the\catcode'\/%}
33   \catcode'\/=12\relax%
34   \edef\pathsuris@oldcatcode@colon{\the\catcode'\:%}
35   \catcode'\:=12\relax%
36   \edef\pathsuris@oldcatcode@qm{\the\catcode'\?}%
37   \catcode'\?=12\relax%
38 }
39 \def\pathsuris@resetcatcodes{%
40   \catcode'\#\pathsuris@oldcatcode@hash\relax%
41   \catcode'\%\pathsuris@oldcatcode@slash\relax%
42   \catcode'\:\pathsuris@oldcatcode@colon\relax%
43   \catcode'\?\pathsuris@oldcatcode@qm\relax%
44 }

```

We define some macros for later comparison.

```

45 \def\@ToTop{..}
46 \def\@Slash{/}
47 \def\@Colon{:}
48 \def\@Space{ }
49 \def\@QuestionMark{?}
50 \def\@Dot{.}
51 \catcode'\&=12
52 \def\@Ampersand{&}
53 \catcode'\&=4
54 \pathsuris@setcatcodes
55 \def\@Fragment{#}
56 \pathsuris@resetcatcodes
57 \catcode'\.=0
58 .catcode'\.=12
59 .let.\@BackSlash\
60 .catcode'\.=0
61 \catcode'\.=12
62 \edef\old@percent@catcode{\the\catcode'\%}
63 \catcode'\%=12
64 \let\@Percent%
65 \catcode'\%=\old@percent@catcode

```

\@cpath Canonicalizes (file) paths:

```

66 \def\@cpath#1{%
67   \edef\pathsuris@cpath@temp{#1}%
68   \def\@CanPath{}%
69   \IfBeginWith\pathsuris@cpath@temp\@Slash{%
70     \@cpath@loop%
71     \edef\@CanPath{\@Slash\@CanPath}%
72   }{%
73     \IfBeginWith\pathsuris@cpath@temp{\@Dot\@Slash}{%
74       \StrGobbleLeft\pathsuris@cpath@temp2[\pathsuris@cpath@temp]%
75       \@cpath@loop%
76     }{%
77       \ifx\pathsuris@cpath@temp\@Dot\else%
78       \@cpath@loop\fi%
79     }%
80   }%
81   \IfEndWith\@CanPath\@Slash{%
82     \ifx\@CanPath\@Slash\else%
83     \StrGobbleRight\@CanPath1[\@CanPath]%
84     \fi%
85   }{}%
86 }
87
88 \def\@cpath@loop{%
89   \IfSubStr\pathsuris@cpath@temp\@Slash{%
90     \StrCut\pathsuris@cpath@temp\@Slash\pathsuris@cpath@temp@a\pathsuris@cpath@temp%

```

```

91     \ifx\pathsuris@cpath@temp@a\@ToTop%
92         \ifx\@CanPath\@empty%
93             \edef\@CanPath{\@ToTop}%
94         \else%
95             \edef\@CanPath{\@CanPath\@Slash\@ToTop}%
96         \fi%
97         \@cpath@loop%
98     \else%
99     \ifx\pathsuris@cpath@temp@a\@Dot%
100         \@cpath@loop%
101     \else%
102     \IfBeginWith\pathsuris@cpath@temp\@ToTop{%
103         \StrBehind{\pathsuris@cpath@temp}{\@ToTop}[\pathsuris@cpath@temp]%
104         \IfBeginWith\pathsuris@cpath@temp\@Slash{%
105             \edef\pathsuris@cpath@temp{\@CanPath\pathsuris@cpath@temp}%
106         }{%
107             \ifx\@CanPath\@empty\else%
108                 \edef\pathsuris@cpath@temp{\@CanPath\@Slash\pathsuris@cpath@temp}%
109             \fi%
110         }%
111         \def\@CanPath{}%
112         \@cpath@loop%
113     }{%
114         \ifx\@CanPath\@empty%
115             \edef\@CanPath{\pathsuris@cpath@temp@a}%
116         \else%
117             \edef\@CanPath{\@CanPath\@Slash\pathsuris@cpath@temp@a}%
118         \fi%
119         \@cpath@loop
120     }%
121     \fi\fi%
122 }{
123     \ifx\@CanPath\@empty%
124         \edef\@CanPath{\pathsuris@cpath@temp}%
125     \else%
126         \edef\@CanPath{\@CanPath\@Slash\pathsuris@cpath@temp}%
127     \fi%
128 }%
129 }

```

Test:

path	canonicalized path	expected
aaa	aaa	aaa
.././aaa	.././aaa	.././aaa
aaa/bbb	aaa/bbb	aaa/bbb
aaa/..		
.././aaa/bbb	.././aaa/bbb	.././aaa/bbb
../aaa/./bbb	../bbb	../bbb
../aaa/bbb	../aaa/bbb	../aaa/bbb
aaa/bbb/./ddd	aaa/ddd	aaa/ddd
aaa/bbb/./ddd	aaa/bbb/ddd	aaa/bbb/ddd
./		
aaa/bbb/./..		

`\cpath` Implement `\cpath` to print the canonicalized path.

```

130 \newcommand\cpath[1]{%
131   \@cpath{#1}%
132   \@CanPath%
133 }
```

`\path@filename`

```

134 \def\path@filename#1#2{%
135   \edef\filename@oldpath{#1}%
136   \StrCount\filename@oldpath{@Slash[\filename@lastslash]}%
137   \ifnum\filename@lastslash>0%
138     \StrBehind[\filename@lastslash]\filename@oldpath{@Slash[\filename@oldpath]}%
139     \edef#2{\filename@oldpath}%
140   \else%
141     \edef#2{\filename@oldpath}%
142   \fi%
143 }
```

Test:

Path: /foo/bar/baz.tex

Filename: baz.tex

3.2.2 Windows

First, a conditional that tells us whether we have to use windows or unix file paths:

```

144 \newif\if@iswindows@\@iswindows@false
145 \IfFileExists{nul:}{\IfFileExists{/dev/null}}{\@iswindows@true}}{}
```

Test:

We are on windows: no.

`\windows@to@path` Converts a windows-style file path to a unix-style file path:

```

146 \newif\if@windowstopath@inpath@
147 \def\windows@to@path#1{
```

```

148 \@windowstopath@inpath@false
149 \def\windows@temp{}
150 \edef\windows@path{#1}
151 \ifx\windows@path\@empty\else
152 \expandafter\windows@path@loop\windows@path\windows@path@end
153 \fi
154 \let#1\windows@temp
155 }
156 \def\windows@path@loop#1#2\windows@path@end{
157 \def\windows@temp@b{#2}
158 \ifx\windows@temp@b\@empty
159 \def\windows@continue{}
160 \else
161 \def\windows@continue{\windows@path@loop#2\windows@path@end}
162 \fi
163 \if@windowstopath@inpath@
164 \ifx#1\@BackSlash
165 \edef\windows@temp{\windows@temp\@Slash}
166 \else
167 \edef\windows@temp{\windows@temp#1}
168 \fi
169 \else
170 \ifx#1:
171 \edef\windows@temp{\@Slash\windows@temp}
172 \@windowstopath@inpath@true
173 \else
174 \edef\windows@temp{\windows@temp#1}
175 \fi
176 \fi
177 \windows@continue
178 }

```

Test:

Input: C:\foo \bar .baz

Output: /C/foo/bar.baz

`\path@to@windows` Converts a unix-style file path to a windows-style file path:

```

179 \def\path@to@windows#1{
180 \@windowstopath@inpath@false
181 \def\windows@temp{}
182 \edef\windows@path{#1}
183 \edef\windows@path{\expandafter\@gobble\windows@path}
184 \ifx\windows@path\@empty\else
185 \expandafter\path@windows@loop\windows@path\windows@path@end
186 \fi
187 \let#1\windows@temp
188 }
189 \def\path@windows@loop#1#2\windows@path@end{
190 \def\windows@temp@b{#2}
191 \ifx\windows@temp@b\@empty

```



```

192     \def\windows@continue{}
193   \else
194     \def\windows@continue{\path@windows@loop#2\windows@path@end}
195   \fi
196   \if@windowstopath@inpath@
197     \ifx#1/
198       \edef\windows@temp{\windows@temp\@BackSlash}
199     \else
200       \edef\windows@temp{\windows@temp#1}
201     \fi
202   \else
203     \ifx#1/
204       \edef\windows@temp{\windows@temp:\@BackSlash}
205       \@windowstopath@inpath@true
206     \else
207       \edef\windows@temp{\windows@temp#1}
208     \fi
209   \fi
210   \windows@continue
211 }

```

Test:

Input: /C/fo0/bar.baz

Output: C:\fo0\bar.baz

3.2.3 Auxiliary methods

`\trimstring` Removes initial and trailing spaces from a string:

```

212 \def\trimstring#1{%
213   \edef\pathsuris@trim@temp{#1}%
214   \IfBeginWith\pathsuris@trim@temp\@Space{%
215     \StrGobbleLeft\pathsuris@trim@temp1[#1]%
216     \trimstring{#1}%
217   }{%
218     \IfEndWith\pathsuris@trim@temp\@Space{%
219       \StrGobbleRight\pathsuris@trim@temp1[#1]%
220       \trimstring{#1}%
221     }{%
222       \edef#1{\pathsuris@trim@temp}%
223     }%
224   }%
225 }

```

Test:

»bla blubb«

`\kpsewhich` Calls `kpsewhich` to get e.g. system variables:

```

226 \def\kpsewhich#1#2{\begingroup%
227   \edef\kpsewhich@cmd{"|kpsewhich #2"%
228   \everyeof{\noexpand}%

```

```

229 \catcode'\=12%
230 \edef#1{\@input\kpsewhich@cmd\@Space}%
231 \trimstring#1%
232 \if@iswindows@ \windows@to@path#1\fi%
233 \xdef#1{\expandafter\detokenize\expandafter{#1}}%
234 \endgroup}

```

Test:

</usr/share/texlive/texmf-dist/tex/latex/etoolbox/etoolbox.sty>

3.2.4 sTeX input hooks

We determine the PWD of the current main document:

```

235 \edef\pwd@cmd{\if@iswindows@ -expand-var \percent CD\percent\else -var-value PWD\fi}
236 \kpsewhich\stex@maindir\pwd@cmd
237 \edef\stex@mainfile{\stex@maindir\@Slash\jobname}
238 \edef\stex@mainfile{\expandafter\detokenize\expandafter{\stex@mainfile}}

```

Test:

</home/jazzpirate/work/Software/ext/sTeX/sty/stex-master>

We keep a stack of \inputed files:

```

239 \def\stex@currfile@stack{}
240
241 \def\stex@currfile@push#1{%
242   \edef\stex@temppath{#1}%
243   \edef\stex@temppath{\expandafter\detokenize\expandafter{\stex@temppath}}%
244   \edef\stex@currfile@stack{\stex@currfile\ifx\stex@currfile@stack\@empty\else,\stex@currfile@stack}%
245   \IfBeginWith\stex@temppath\@Slash{\@cpath{\stex@temppath}}{%
246     \@cpath{\stex@maindir\@Slash#1}%
247   }
248   \let\stex@currfile\@CanPath%
249   \path@filename\stex@currfile\stex@currfilename%
250   \StrLen\stex@currfilename[\stex@currfile@tmp]%
251   \StrGobbleRight\stex@currfile{\the\numexpr\stex@currfile@tmp+1 }[\stex@currpath]%
252   \global\let\stex@currfile\stex@currfile%
253   \global\let\stex@currpath\stex@currpath%
254   \global\let\stex@currfilename\stex@currfilename%
255 }
256 \def\stex@currfile@pop{%
257   \ifx\stex@currfile@stack\@empty%
258     \global\let\stex@currfile\stex@mainfile%
259     \global\let\stex@currpath\stex@maindir%
260     \global\let\stex@currfilename\jobname%
261   \else%
262     \StrCut\stex@currfile@stack,\stex@currfile\stex@currfile@stack%
263     \path@filename\stex@currfile\stex@currfilename%
264     \StrLen\stex@currfilename[\stex@currfile@tmp]%
265     \StrGobbleRight\stex@currfile{\the\numexpr\stex@currfile@tmp+1 }[\stex@currpath]%
266     \global\let\stex@currfile\stex@currfile%
267     \global\let\stex@currpath\stex@currpath%

```

```

268     \global\let\stex@currfilename\stex@currfilename%
269     \fi%
270 }

```

\stexinput Inputs a file by (if necessary) converting its path to a windows path first, and adding the file path to the input stack above:

```

271 \def\stexinput#1{%
272     \stexiffileexists{#1}{%
273         \stex@currfile@push\stex@temp@path%
274         \input{\stex@currfile}%
275         \stex@currfile@pop%
276     }%
277     {%
278         \PackageError{stex}{File does not exist (#1): \stex@temp@path}{}%
279     }%
280 }
281 \def\stexiffileexists#1#2#3{%
282     \edef\stex@temp@path{#1}%
283     \if@iswindows@\path@to@windows\stex@temp@path\fi%
284     \IfFileExists\stex@temp@path{#2}{#3}%
285 }
286 \stex@currfile@pop

```

Test:

This file: </home/jazzpirate/work/Software/ext/sTeX/sty/stex-master/stex-master>

A test file: </home/jazzpirate/work/Software/ext/sTeX/sty/stex-master/testfile.tex>

3.2.5 MathHub repositories

We read the MATHHUB system variable and set \MathHub accordingly:

```

287 \kpsewhich\mathhub@path{--var-value MATHHUB}
288 \if@iswindows@\windows@to@path\mathhub@path\fi
289 \ifx\mathhub@path\@empty%
290     \PackageWarning{stex}{MATHHUB system variable not found or wrongly set}{%
291         \defpath{MathHub}{%
292             \else\defpath{MathHub}\mathhub@path\fi

```

Test:

</home/jazzpirate/work/MathHub>

\findmanifest \findmanifest{<path>} searches for a file MANIFEST.MF up and over <path> in the file system tree.

```

293 \def\findmanifest#1{
294     \@cpath{#1}
295     \ifx\@CanPath\@Slash
296         \def\manifest@mf{}
297     \else\ifx\@CanPath\@empty
298         \def\manifest@mf{}
299     \else
300         \edef\@findmanifest@path{\@CanPath/MANIFEST.MF}

```

```

301 \if@iswindows@path@to@windows\@findmanifest@path\fi
302 \IfFileExists{\@findmanifest@path}{
303   \%message{MANIFEST.MF found at \@findmanifest@path}
304   \edef\manifest@mf{\@findmanifest@path}
305   \xdef\temp@archive@dir{\expandafter\detokenize\expandafter{\@CanPath}}
306 }{
307   \edef\@findmanifest@path{\@CanPath/META-INF/MANIFEST.MF}
308   \if@iswindows@path@to@windows\@findmanifest@path\fi
309   \IfFileExists{\@findmanifest@path}{
310     \%message{MANIFEST.MF found at \@findmanifest@path}
311     \edef\manifest@mf{\@findmanifest@path}
312     \xdef\temp@archive@dir{\expandafter\detokenize\expandafter{\@CanPath}}
313   }{
314     \edef\@findmanifest@path{\@CanPath/meta-inf/MANIFEST.MF}
315     \if@iswindows@path@to@windows\@findmanifest@path\fi
316     \IfFileExists{\@findmanifest@path}{
317       \%message{MANIFEST.MF found at \@findmanifest@path}
318       \edef\manifest@mf{\@findmanifest@path}
319       \xdef\temp@archive@dir{\expandafter\detokenize\expandafter{\@CanPath}}
320     }{
321       \findmanifest{\@CanPath/..}
322     }
323   \fi\fi
324 }

```

Test:

</home/jazzpirate/work/MathHub/smgglom/mv/META-INF/MANIFEST.MF>

the next macro is a helper function for parsing MANIFEST.MF

```

325 \def\split@manifest@key{
326   \IfSubStr{\manifest@line}{\@Colon}{
327     \StrBefore{\manifest@line}{\@Colon}[\manifest@key]
328     \StrBehind{\manifest@line}{\@Colon}[\manifest@line]
329     \trimstring\manifest@line
330     \trimstring\manifest@key
331   }{
332     \def\manifest@key{}
333   }
334 }

```

the next helper function iterates over lines in MANIFEST.MF

```

335 \def\parse@manifest@loop{
336   \ifeof\@manifest
337   \else
338     \read\@manifest to \manifest@line\relax
339     \edef\manifest@line{\expandafter\detokenize\expandafter{\manifest@line}}
340     \split@manifest@key
341     % id
342     \IfStrEq\manifest@key{\detokenize{id}}{
343       \xdef\manifest@mf{id}\manifest@line}

```

```

344     }{
345     % narration-base
346     \IfStrEq\manifest@key{\detokenize{narration-base}}{
347         \xdef\manifest@mf@narr{\manifest@line}
348     }{
349     % namespace
350     \IfStrEq\manifest@key{\detokenize{source-base}}{
351         \xdef\manifest@mf@ns{\manifest@line}
352     }{
353     \IfStrEq\manifest@key{\detokenize{ns}}{
354         \xdef\manifest@mf@ns{\manifest@line}
355     }{
356     % dependencies
357     \IfStrEq\manifest@key{\detokenize{dependencies}}{
358         \xdef\manifest@mf@deps{\manifest@line}
359     }{
360     }}}}
361     \parse@manifest@loop
362 \fi
363 }

```

`\parsemanifest` `\parsemanifest{<macroname>}{<path>}` finds MANIFEST.MF via `\findmanifest{<path>}`, and parses the file, storing the individual fields (id, narr, ns and dependencies) in `<macroname>id`, `<macroname>narr`, etc.

```

364 \newread\@manifest
365 \def\parsemanifest#1#2{%
366     \gdef\temp@archive@dir{}%
367     \findmanifest{#2}%
368     \begingroup%
369     \gdef\manifest@mf@id{}%
370     \gdef\manifest@mf@narr{}%
371     \gdef\manifest@mf@ns{}%
372     \gdef\manifest@mf@deps{}%
373     \openin\@manifest\manifest@mf%
374     \parse@manifest@loop%
375     \closein\@manifest%
376     \endgroup%
377     \if@iswindows@ \windows@to@path\manifest@mf\fi%
378     \cslet{#1id}\manifest@mf@id%
379     \cslet{#1narr}\manifest@mf@narr%
380     \cslet{#1ns}\manifest@mf@ns%
381     \cslet{#1deps}\manifest@mf@deps%
382     \ifcvoid\manifest@mf@id{-}%
383     \cslet{#1dir}\temp@archive@dir%
384 }%
385 }

```

Test:

id: FOO/BAR

ns: <http://mathhub.info/FOO/BAR>

dir: FOO

`\setcurrentreposinfo` `\setcurrentreposinfo{⟨id⟩}` sets the current repository to `⟨id⟩`, checks if the MANIFEST.MF of this repository has already been read, and if not, find it, parses it and stores the values in `\currentrepos@⟨key⟩@⟨id⟩` for later retrieval.

```

386 \def\setcurrentreposinfo#1{%
387   \edef\mh@currentrepos{#1}%
388   \ifx\mh@currentrepos\@empty%
389     \edef\currentrepos@dir{\@Dot}%
390     \def\currentrepos@narr{}%
391     \def\currentrepos@ns{}%
392     \def\currentrepos@id{}%
393     \def\currentrepos@deps{}%
394   \else%
395     \ifcsdef{mathhub@dir@\mh@currentrepos}{%
396       \@inmhrepostrue
397       \edef\mh@currentrepos{#1}%
398       \expandafter\let\expandafter\currentrepos@dir\csname mathhub@dir@#1\endcsname%
399       \expandafter\let\expandafter\currentrepos@narr\csname mathhub@narr@#1\endcsname%
400       \expandafter\let\expandafter\currentrepos@ns\csname mathhub@ns@#1\endcsname%
401       \expandafter\let\expandafter\currentrepos@deps\csname mathhub@deps@#1\endcsname%
402     }{%
403       \parsemanifest{currentrepos@}\MathHub{#1}}%
404     \@setcurrentreposinfo%
405     \ifcsvoid{currentrepos@dir}\PackageError{stex}{No archive with %
406       name #1 found!}{make sure that #1 is directly in your MATHHUB folder %
407       and contains a MANIFEST.MF, either directly in #1 or in a meta-inf %
408       subfolder.}}{\@inmhrepostrue}%
409   }%
410   \fi%
411 }
412
413 \def\@setcurrentreposinfo{%
414   \edef\mh@currentrepos{\currentrepos@id}%
415   \ifcsvoid{currentrepos@dir}{%
416     \csxdef{mathhub@dir@\currentrepos@id}\currentrepos@dir%
417     \csxdef{mathhub@narr@\currentrepos@id}\currentrepos@narr}%
418     \csxdef{mathhub@ns@\currentrepos@id}\currentrepos@ns}%
419     \csxdef{mathhub@deps@\currentrepos@id}\currentrepos@deps}%
420   }%
421 }

```

Finally – and that is the ultimate goal of all of the above, we set the current repos.

```

422 \newif\if@inmhrepos\@inmhreposfalse
423 \ifcsvoid{stex@maindir}{%
424   \parsemanifest{currentrepos@}\stex@maindir
425   \@setcurrentreposinfo
426   \ifcsvoid{currentrepos@dir}\PackageWarning{stex}{Not currently in a MathHub repository}{%
427     \message{Current repository: \mh@currentrepos}

```

```

428 }
429 }

```

3.3 Modules

```

430 \if@ltxml\else\ifmod@show\RequirePackage{mdframed}\fi\fi

```

Aux:

```

431 \def\ignorespacesandpars{\begingroup\catcode13=10\ifnextchar\relax{\endgroup}{\endgroup}}

```

and more adapted from <http://tex.stackexchange.com/questions/179016/ignore-spaces-and-pars-after-an-environment>

```

432 \def\ignorespacesandparsafterend#1\ignorespaces\fi{#1\fi\ignorespacesandpars}

```

```

433 \def\ignorespacesandpars{\ifhmode\unskip\fi\@ifnextchar\par{\expandafter\ignorespacesandpars\@g

```

Options for the module-environment:

```

434 \addmetakey*{module}{title}

```

```

435 \addmetakey*{module}{name}

```

```

436 \addmetakey*{module}{creators}

```

```

437 \addmetakey*{module}{contributors}

```

```

438 \addmetakey*{module}{srccite}

```

```

439 \addmetakey*{module}{ns}

```

```

440 \addmetakey*{module}{narr}

```

module@heading We make a convenience macro for the module heading. This can be customized.

```

441 \ifdef{\thesection}{\newcounter{module}[section]}{\newcounter{module}}%

```

```

442 \newrobustcmd\module@heading{%

```

```

443   \stepcounter{module}%

```

```

444   \ifmod@show%

```

```

445   \noindent{\textbf{Module} \thesection.\thetitle [\module@name]]%

```

```

446   \sref@label@id{Module \thesection.\thetitle [\module@name]]%

```

```

447   \ifx\module@title\empty : \quad\else\quad(\module@title)\hfill\\\fi%

```

```

448   \fi%

```

```

449 }%

```

Test:

Module 3.1[Test]: Foo

module Finally, we define the begin module command for the module environment. Much of the work has already been done in the keyval bindings, so this is quite simple.

```

450 \newenvironment{module}[1][{}]{%

```

```

451   \begin{@module}[#1]%

```

```

452   \module@heading% make the headings

```

```

453   \ignorespacesandpars\parsemodule@maybesetcodes}{%

```

```

454   \end{@module}%

```

```

455   \ignorespacesafterend%

```

```

456 }%

```

```

457 \ifmod@show\surroundwithmdframed{module@om@common}\fi%

```

Some auxiliary methods:

```

458 \def\g@addto@macro@safe#1#2{\ifx#1\relax\def#1{}\fi\g@addto@macro#1{#2}}

```

```

459 \def\addto@thismodule#1{%

```

```

460 \@ifundefined{this@module}{}{%
461   \expandafter\g@addto@macro@safe\this@module{#1}%
462 }%
463 }
464 \def\addto@thismodule#1{%
465 \ifundefined{this@module}{}{%
466   \edef\addto@thismodule@exp{#1}%
467   \expandafter\expandafter\expandafter\g@addto@macro@safe%
468   \expandafter\this@module\expandafter{\addto@thismodule@exp}%
469 }}

```

@module A variant of the `module` environment that does not create printed representations (in particular no frames).

To compute the $\langle uri \rangle$ of a module, `\set@default@ns` computes the namespace, if none is provided as an optional argument, as follows:

If the file of the module is `/some/path/file.tex` and we are not in a MathHub repository, the namespace is `file:///some/path`.

If the file of the module is `/some/path/in/mathhub/repo/sitory/source/sub/file.tex` and `repo/sitory` is an archive in the MathHub root, and the `MANIFEST.MF` of `repo/sitory` declares a namespace `http://some.namespace/foo`, then the namespace of the module is `http://some.namespace/foo/sub`.

```

470 \newif\ifarchive@ns@empty@\archive@ns@empty@false
471 \def\set@default@ns{%
472   \edef\@module@ns@temp{\stex@currpath}%
473   \if@iswindows@\windows@to@path\@module@ns@temp\fi%
474   \archive@ns@empty@false%
475   \ifcvoid{mh@currentrepos}{\archive@ns@empty@true}%
476   {\expandafter\ifx\curname mathhub@ns@\mh@currentrepos\endcsname\@empty\archive@ns@empty@true\fi%
477   }%
478   \ifarchive@ns@empty%
479     \edef\@module@ns@tempuri{file\@Colon\@Slash\@Slash\@module@ns@temp}%
480   \else%
481     \edef\@module@filepath@temppath{\@module@ns@temp}%
482     \edef\@module@ns@tempuri{\curname mathhub@ns@\mh@currentrepos\endcsname}%
483     \edef\@module@archivedirpath{\curname mathhub@dir@\mh@currentrepos\endcsname\@Slash source}%
484     \edef\@module@archivedirpath{\expandafter\detokenize\expandafter{\@module@archivedirpath}}%
485     \IfBeginWith\@module@filepath@temppath\@module@archivedirpath{%
486       \StrLen\@module@archivedirpath[\ns@temp@length]%
487       \StrGobbleLeft\@module@filepath@temppath\@module@filepath@temprest}%
488     \edef\@module@ns@tempuri{\@module@ns@tempuri\@module@filepath@temprest}%
489   }{}%
490 \fi%
491 \IfEndWith\@module@ns@tempuri\@Slash{\StrGobbleRight\@module@ns@tempuri1[\@module@ns@tempuri]}%
492 \setkeys{module}{ns=\@module@ns@tempuri}%
493 }

```

Test:

<file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master>

If the module is not given a name, `\set@next@moduleid` computes one by enumeration, e.g. `module0`, `module1`, etc.

```

494 \def\set@next@moduleid{%
495   \unless\ifcsname namespace@\module@ns @unnamedmodules\endcsname%
496     \csgdef{namespace@\module@ns @unnamedmodules}{0}%
497   \fi%
498   \edef\namespace@currnum{\csname namespace@\module@ns @unnamedmodules\endcsname}%
499   \edef\module@temp@setidname{\noexpand\setkeys{module}{name=module\namespace@currnum}}%
500   \module@temp@setidname%
501   \csxdef{namespace@\module@ns @unnamedmodules}{\the\numexpr\namespace@currnum+1}%
502 }

```

Test:

`module0`

`module1`

Finally, the `@module` environment does the actual work, i.e. setting metakeys, computing namespace/id, defining `\this@module`, etc.

For a module with name $\langle name \rangle$ (`\module@name`) and uri $\langle uri \rangle$ (`\module@uri`), this defines the following macros:

- `\module@defs@ $\langle uri \rangle$` that acts as a repository for semantic macros of the current module. It will be called by `\importmodule` to activate them.
- We will add the internal forms of the semantic macros whenever `\symdef` is invoked. To do this, we will need an unexpanded form `\this@module` that expands to `\module@defs@ $\langle uri \rangle$` ; we define it first and then initialize `\module@defs@ $\langle uri \rangle$` as empty.
- `\module@names@ $\langle uri \rangle$` will store all symbol names declared in this module.
- `\module@imports@ $\langle uri \rangle$` will store the URIs of all modules directly included in this module
- `\ $\langle uri \rangle$` that expands to `\invoke@module{ $\langle uri \rangle$ }` (see below).
- `\Module $\langle name \rangle$` that expands to `\ $\langle uri \rangle$` .

If we are currently in a mathhub repository, this information will also be stored in `\module@defs@ $\langle uri \rangle$` , so we can resolve includes properly when this module is activated.

```

503 \newenvironment{@module}[1][[]]{%
504   \metasetkeys{module}{#1}%
505   \ifcsvoid{module@name}{\let\module@name\module@id}{}% % TODO deprecate
506   \ifx\module@ns\@empty\set@default@ns\fi%
507   \ifx\module@narr\@empty%
508     \setkeys{module}{narr=\module@ns}%
509   \fi%
510   \ifcsvoid{module@name}{\set@next@moduleid}{}%
511   \let\module@id\module@name% % TODO deprecate
512   \edef\module@uri{\module@ns\@QuestionMark\module@name}%

```

```

513 \csgdef{module@names@\module@uri}{}%
514 \csgdef{module@imports@\module@uri}{}%
515 \csxdef{\module@uri}{\noexpand\@invoke@module{\module@uri}}%
516 \expandafter\global\expandafter\let\csname Module\module@name\expandafter\endcsname\csname\mo
517 \edef\this@module{%
518   \expandafter\noexpand\csname module@defs@\module@uri\endcsname%
519 }%
520 \csdef{module@defs@\module@uri}{}%
521 \ifcvoid{mh@currentrepos}{}{%
522   \@inmhrepostrue%
523   \addto@thismodule{\expandafter\edef\expandafter\noexpand\csname mh@old@repos@\module@uri\en
524     {\noexpand\mh@currentrepos}}%
525   \addto@thismodule{\noexpand\setcurrentreposinfo{\mh@currentrepos}}%
526 }%
527 }{%
528   \if@inmhrepos%
529   \@inmhreposfalse%
530   \addto@thismodule{\noexpand\setcurrentreposinfo{\expandafter\noexpand\csname mh@old@repos@m
531   \fi%
532 }%

```

Test:

Module 3.2[Foo]:

Name: Foo

URI: file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?Foo

this@module: macro:->

Test:

Faking a MathHub archive Foo/Bar with URI <http://foo.bar/baz>:

Module 3.3[Foo2]:

Name: Foo2

URI: <http://foo.bar/baz?Foo2>

this@module: macro:->\edef \mh@old@repos@<http://foo.bar/baz?Foo2> {\mh@currentrepos
}\setcurrentreposinfo {Foo/Bar}

Test:

Removing the /home/jazzpirate/work/MathHub/ system variable first:

Module 3.4[Foo]:

Name: Foo

URI: file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?Foo

this@module: macro:->Faking a MathHub archive Foo/Bar with URI <http://foo.bar/baz>:

Module 3.5[Foo2]:

Name: Foo2

URI: <http://foo.bar/baz?Foo2>

this@module: macro:->\edef \mh@old@repos@<http://foo.bar/baz?Foo2> {\mh@currentrepos
}\setcurrentreposinfo {Foo/Bar}

A module with URI $\langle uri \rangle$ and id $\langle id \rangle$ creates two macros $\langle uri \rangle$ and $\langle Module \langle id \rangle \rangle$, that ultimately expand to $\@invoke@module{\langle uri \rangle}$. Currently, the only functionality is $\@invoke@module{\langle uri \rangle}\@URI$, which expands to the full uri of a module (i.e. via $\langle Module \langle id \rangle \rangle \@URI$). In the future, this macro can be

extended with additional functionality, e.g. accessing symbols in a macro for overloaded (macro-)names.

```

533 \def\@URI{uri}
534 \def\@invoke@module#1#2{%
535   \ifx\@URI#2%
536     #1%
537   \else%
538     % TODO something else
539     #2%
540   \fi%
541 }

```

3.4 Inheritance

3.4.1 Selective Inclusion

The next great goal is to establish the `\requiremodules` macro, which reads an `TeX` file and processes all the module signature information in them, but does not produce any output. This is a tricky business, as we need to “parse” the modules and treat the module signature macros specially (we refer to this as “**sms mode**”, since it is equivalent to what the – now deprecated – `sms` utility did).

In the following we introduce a lot of auxiliary functionality before we can define `\requiremodules`.

`\parsemodule@allow*` The first step is setting up a functionality for registering `sTeX` macros and environments as part of a module signature.

```

542 \newif\if@smsmode\@smsmodefalse
543 \def\parsemodule@escapechar@allowed{true}
544 \def\parsemodule@allow#1{
545   \expandafter\let\csname parsemodule@allowedmacro@#1\endcsname\parsemodule@escapechar@allowed
546 }
547 \def\parsemodule@allowenv#1{
548   \expandafter\let\csname parsemodule@allowedenv@#1\endcsname\parsemodule@escapechar@allowed
549 }
550 \def\parsemodule@escapechar@beginstring{begin}
551 \def\parsemodule@escapechar@endstring{end}

```

and now we use that to actually register all the `TeX` functionality as relevant for `sms` mode.

```

552 \parsemodule@allow{symdef}
553 \parsemodule@allow{abbrdef}
554 \parsemodule@allow{importmodule}
555 \parsemodule@allowenv{module}
556 \parsemodule@allow{importmhmodule}
557 \parsemodule@allow{gimport}
558 \parsemodule@allowenv{modsig}
559 \parsemodule@allowenv{mhmodsig}
560 \parsemodule@allowenv{mhmodnl}

```

```

561 \parsemodule@allowenv{modnl}
562 \parsemodule@allow{symvariant}
563 \parsemodule@allow{symi}
564 \parsemodule@allow{symii}
565 \parsemodule@allow{symiii}
566 \parsemodule@allow{symiv}
567 \parsemodule@allow{notation}
568 \parsemodule@allow{verbalization}
569 \parsemodule@allow{symdecl}
570
571 % to deprecate:
572
573 \parsemodule@allow{defi}
574 \parsemodule@allow{defii}
575 \parsemodule@allow{defiii}
576 \parsemodule@allow{defiv}
577 \parsemodule@allow{adefi}
578 \parsemodule@allow{adefii}
579 \parsemodule@allow{adefiii}
580 \parsemodule@allow{adefiv}
581 \parsemodule@allow{defis}
582 \parsemodule@allow{defiis}
583 \parsemodule@allow{defiiis}
584 \parsemodule@allow{defivs}
585 \parsemodule@allow{Defi}
586 \parsemodule@allow{Defii}
587 \parsemodule@allow{Defiii}
588 \parsemodule@allow{Defiv}
589 \parsemodule@allow{Defis}
590 \parsemodule@allow{Defiis}
591 \parsemodule@allow{Defiiis}
592 \parsemodule@allow{Defivs}

```

To read external modules without producing output, `\requiremodules` redefines the `\`-character to be an *active* character that, instead of executing a macro, checks whether a macro name has been registered using `\parsemodule@allow` before selectively executing the corresponding macro or ignoring it. To produce the relevant code, we therefore define a macro `\@active@slash` that produces a `\`-character with category code 13 (*active*), as well as `\@open@brace` and `\@close@brace`, which produce open and closing braces with category code 12 (*other*).

```

593 \catcode'\.=0
594 .catcode'\.=13
595 .def.\@active@slash{\}
596 .catcode'<.=1
597 .catcode'>.=2
598 .catcode'{'.=12
599 .catcode'}'=12
600 .def.\@open@brace<{>

```

```

601 .def.@close@brace<>>
602 .catcode'\.=0
603 \catcode'\.=12
604 \catcode'\{=1
605 \catcode'\}=2
606 \catcode'\<=12
607 \catcode'\>=12

```

The next two macros set and reset the category codes before/after `sms` mode.

`\set@parsemodule@catcodes`

```

608 \def\set@parsemodule@catcodes{%
609     \global\catcode'\=13%
610     \global\catcode'\#=12%
611     \global\catcode'\{=12%
612     \global\catcode'\}=12%
613     \global\catcode'\$=12%$
614     \global\catcode'\^=12%
615     \global\catcode'\_ =12%
616     \global\catcode'\&=12%
617     \expandafter\let\@active@slash\parsemodule@escapechar%
618 }

```

`\reset@parsemodule@catcodes`

```

619 \def\reset@parsemodule@catcodes{%
620     \global\catcode'\=0%
621     \global\catcode'\#=6%
622     \global\catcode'\{=1%
623     \global\catcode'\}=2%
624     \global\catcode'\$=3%$
625     \global\catcode'\^=7%
626     \global\catcode'\_ =8%
627     \global\catcode'\&=4%
628 }

```

`\parsemodule@maybesetcodes`

Before a macro is executed in `sms`-mode, the category codes will be reset to normal, to ensure that all macro arguments are parsed correctly. Consequently, the macros need to set the category codes back to `sms` mode after having read all arguments iff the macro got executed in `sms` mode. `\parsemodule@maybesetcodes` takes care of that.

```

629 \def\parsemodule@maybesetcodes{%
630     \if@smsmode\set@parsemodule@catcodes\fi%
631 }

```

`\parsemodule@escapechar`

This macro gets called whenever a `\`-character occurs in `sms` mode. It is split into several macros that parse and store characters in `\parsemodule@escape@currcls` until a character with category code $\neq 11$ occurs (i.e. the macro name is complete), check whether the macro is allowed in `sms` mode, and then either ignore it or execute it after setting category codes back to normal. Special care needs to be

taken to make sure that braces have the right category codes (1 and 2 for open and closing braces, respectively) when delimiting macro arguments.

Entry point:

```
632
633 \def\parsemodule@escapechar{%
634   \def\parsemodule@escape@currcls{}%
635   \parsemodule@escape@parse@nextchar@%
636 }%
```

The next macro simply reads the next character and checks whether it has category code 11. If so, it stores it in `\parsemodule@escape@currcls`. Otherwise, the macro name is complete, it stores the last character in `\parsemodule@last@char` and calls `\parsemodule@escapechar@checkcls`.

```
637 \long\def\parsemodule@escape@parse@nextchar@#1{%
638   \ifcat a#1\relax%
639     \edef\parsemodule@escape@currcls{\parsemodule@escape@currcls#1}%
640     \let\parsemodule@do@next\parsemodule@escape@parse@nextchar@%
641   \else%
642     \def\parsemodule@last@char{#1}%
643     \def\parsemodule@do@next{\parsemodule@escapechar@checkcls}%
644   \fi%
645   \parsemodule@do@next%
646 }
```

The next macro checks whether the currently stored macroname is allowed in `sms` mode. There are four cases that need to be considered: `\begin`, `\end`, allowed macros, and others. In the first two cases, we reinsert `\parsemodule@last@char` and continue with `\parsemodule@escapechar@checkbeginenv` or `\parsemodule@escapechar@checkendenv`, respectively, to check whether the environment being opened/closed is allowed in `sms` mode. In both cases, `\parsemodule@last@char` is an open brace with category code 12. In the third case, we need to check whether `\parsemodule@last@char` is an open brace, in which case we call `\parsemodule@converttoproperbraces`, otherwise, we set category codes to normal and execute the macro. In the fourth case, we just reinsert `\parsemodule@last@char` and continue.

```
647 \def\parsemodule@escapechar@checkcls{%
648   \ifx\parsemodule@escape@currcls\parsemodule@escapechar@beginstring%
649     \edef\parsemodule@do@next{\noexpand\parsemodule@escapechar@checkbeginenv\parsemodule@last@char}%
650   \else%
651     \ifx\parsemodule@escape@currcls\parsemodule@escapechar@endstring%
652       \edef\parsemodule@do@next{\noexpand\parsemodule@escapechar@checkendenv\parsemodule@last@char}%
653     \else%
654       \expandafter\ifx\csname parsemodule@allowedmacro@\parsemodule@escape@currcls\endcsname\relax
655         \parsemodule@escapechar@allowed%
656       \ifx\parsemodule@last@char\@open@brace%
657         \expandafter\let\expandafter\parsemodule@do@next\ii\csname\parsemodule@escape@currcls\endcsname
658       \edef\parsemodule@do@next{\noexpand\parsemodule@converttoproperbraces\@open@brace}%
659     \else%
660       \reset@parsemodule@catcodes%
661     \edef\parsemodule@do@next{\expandafter\noexpand\csname\parsemodule@escape@currcls\endcsname}
```

```

662             \fi%
663             \else\def\parsemodule@do@next{\relax\parsemodule@last@char}\fi%
664         \fi%
665     \fi%
666     \parsemodule@do@next%
667 }

```

This macro simply takes an argument in braces (with category codes 12), reinserts it with “proper” braces (category codes 1 and 2), sets category codes back to normal and calls `\parsemodule@do@next@ii`, which has been `\let` as the macro to be executed.

```

668 \expandafter\expandafter\expandafter\def%
669 \expandafter\expandafter\expandafter\parsemodule@converttoproperbraces%
670 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
671     \reset@parsemodule@catcodes%
672     \parsemodule@do@next@ii{#1}%
673 }

```

The next two macros apply in the `\begin` and `\end` cases. They check whether the environment is allowed in `sms` mode, if so, open/close the environment, and otherwise do nothing.

Notably, `\parsemodule@escapechar@checkendenv` does not set category codes back to normal, since `\end{environment}` never takes additional arguments that need to be parsed anyway.

```

674 \expandafter\expandafter\expandafter\def%
675 \expandafter\expandafter\expandafter\parsemodule@escapechar@checkbeginenv%
676 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
677     \expandafter\ifx\csname parsemodule@allowedenv@#1\endcsname\parsemodule@escapechar@allowed%
678         \reset@parsemodule@catcodes%
679         \def\parsemodule@do@next{\begin{#1}}%
680     \else%
681         \def\parsemodule@do@next{#1}%
682     \fi%
683     \parsemodule@do@next%
684 }
685 \expandafter\expandafter\expandafter\def%
686 \expandafter\expandafter\expandafter\parsemodule@escapechar@checkendenv%
687 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
688     \expandafter\ifx\csname parsemodule@allowedenv@#1\endcsname\parsemodule@escapechar@allowed%
689         %\reset@parsemodule@catcodes%
690         \def\parsemodule@do@next{\end{#1}}%
691     \else%
692         \def\parsemodule@do@next{#1}%
693     \fi%
694     \parsemodule@do@next%
695 }

```

`\@requiremodules` the internal version of `\requiremodules` for use in the `*.aux` file. We disable it at the end of the document, so that when the `aux` file is read again, nothing is loaded.

```

696 \newrobustcmd\requiremodules[1]{%
697   \if@tempswa\requiremodules{#1}\fi%
698 }%

```

`\requiremodules` This macro loads the module signatures in a file using the `\requiremodules@smsmode` above. We set the flag `\mod@showfalse` in the local group, so that the macros know now to pollute the result.

```

699 \newrobustcmd\requiremodules[1]{%
700   \mod@showfalse%
701   \edef\mod@path{#1}%
702   \edef\mod@path{\expandafter\detokenize\expandafter{\mod@path}}%
703   \requiremodules@smsmode{#1}%
704 }%

```

`\requiremodules@smsmode` this reads `gTeX` modules by setting the category codes for `sms` mode, `\inputting` the required file and wrapping it in a `\vbox` that gets stored away and ignored, in order to not produce any output. It also sets `\hbadness`, `\hfuzz` and friends to values that suppress overfull and underfull hbox messages.

```

705 \newbox\modules@import@tempbox
706 \def\requiremodules@smsmode#1{%
707   \setbox\modules@import@tempbox\vbox{%
708     \smsmodetrue%
709     \set@parsemodule@catcodes%
710     \hbadness=100000\relax%
711     \hfuzz=10000pt\relax%
712     \vbadness=100000\relax%
713     \vfuzz=10000pt\relax%
714     \stexinput{#1.tex}%
715     \reset@parsemodule@catcodes%
716   }%
717   \parsemodule@maybesetcodes%
718 }

```

Test:

parsing `FOO/testmodule.tex`

macro:->`\@invoke@module {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master/FOO?testmodule}`

3.4.2 importmodule

`\importmodule@bookkeeping`

```

719 \newif\if@importmodule@switchrepos\@importmodule@switchreposfalse
720 \def\importmodule@bookkeeping#1#2#3{%
721   \@importmodule@switchreposfalse%
722   \metasetkeys{importmodule}{#1}%
723   \ifcsvoid{importmodule@mhrepos}{%
724     \ifcsvoid{currentrepos@dir}{%
725       \let\importmodule@dir\stex@maindir%
726     }%

```



```

727     \edef\importmodule@dir{\currentrepos@dir\@Slash source}%
728   }%
729 }{%
730   \@importmodule@switchrepostrue%
731   \expandafter\let\csname importmodule@oldrepos@#2\endcsname\mh@currentrepos%
732   \setcurrentreposinfo\importmodule@mhrepos%
733   \edef\importmodule@dir{\currentrepos@dir\@Slash source}%
734 }%
735 \StrCut{#2}\@QuestionMark\importmodule@subdir\importmodule@modulename%
736 \ifx\importmodule@modulename\@empty%
737   \let\importmodule@modulename\importmodule@subdir%
738   \let\importmodule@subdir\@empty%
739 \else%
740   \ifx\importmodule@subdir\@empty\else%
741     \edef\importmodule@dir{\importmodule@dir\@Slash\importmodule@subdir}%
742   \fi%
743 \fi%
744 #3%
745 \if\importmodule@switchrepos%
746   \expandafter\setcurrentreposinfo\csname importmodule@oldrepos@#2\endcsname%
747 \fi%
748 \ignorespacesandpars%
749 }

```

\importmodule

```

750 %\srefaddidkey{importmodule}
751 \addmetakey{importmodule}{mhrepos}
752 \newcommand\importmodule[2][\@importmodule[#1]{#2}{export}]
753 \newcommand\@importmodule[3][\@importmodule[#1]{#2}{%
754   \importmodule@bookkeeping{#1}{#2}{%
755     \@importmodule[\importmodule@dir]\importmodule@modulename{#3}%
756   }%
757 }

```

\@importmodule \@importmodule[\<filepath>]{\<mod>}{\<export?>} loads \<filepath>.tex and activates the module \<mod>. If \<export?> is export, then it also re-exports the \symdefs from \<mod>.

First \@load will store the base file name with full path, then check if \module@\<mod>@path is defined. If this macro is defined, a module of this name has already been loaded, so we check whether the paths coincide, if they do, all is fine and we do nothing otherwise we give a suitable error. If this macro is undefined we load the path by \requiremodules.

```

758 \newcommand\@importmodule[3][\@importmodule[#1]{#2}{%
759 {%
760   \edef\@load{#1}%
761   \edef\@importmodule@name{#2}%
762   \if@smsmode\else\ifcsvoid{Module\@importmodule@name}{%
763     \stexiffileexists\@load\requiremodules\@load}{%
764     \requiremodules{\@load\@Slash\@importmodule@name}%

```

```

765     }%
766   }{\fi%
767   \ifx\@load\@empty\else%
768     {% TODO
769     \edef\@path{\csname module@#2@path\endcsname}%
770     \IfStrEq\@load\@path{\relax}% if the known path is the same as the requested one do nothing
771     {\PackageError{stex}% else signal an error
772       {Module Name Clash\MessageBreak%
773         A module with name #2 was already loaded under the path "\@path"\MessageBreak%
774         The imported path "\@load" is probably a different module with the\MessageBreak%
775         same name; this is dangerous -- not importing}%
776       {Check whether the Module name is correct}%
777     }%
778   }%
779   \fi%
780   \global\let\@importmodule\@load\@load%
781 }%
782 \edef\@export{#3}\def\@@export{export}%prepare comparison
783 %\ifx\@export\@@export\export@defs{#2}\fi% export the module
784 \ifx\@export\@@export\addto@thismodulex{%
785   \noexpand\@importmodule[\@importmodule@load]{#2}{noexport}%
786 }%
787 \if@smsmode\else
788 \ifcsvoid{this@module}{\fi%
789   \ifcsvoid{module@imports@\module@uri}{
790     \csxdef{module@imports@\module@uri}{%
791       \csname Module#2\endcsname\@URI%
792     }%
793   }{\fi%
794     \csxdef{module@imports@\module@uri}{%
795       \csname Module#2\endcsname\@URI,%
796       \csname module@imports@\module@uri\endcsname%
797     }%
798   }%
799 }%
800 \fi\fi%
801 \if@smsmode\else\activate@defs{#2}\fi% activate the module
802 }%

```

Test:

\importmodule {testmoduleimporta}:

macro:->\@invoke@module {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?testmoduleimporta}

macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?testmoduleimporta?foo}

Test:

\importmodule {testmoduleimportb?importb}:

macro:->\@invoke@module {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?importb}

```
macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-
master?importb?bar}
```

Test:

```
macro:->\@invoke@module {http://mathhub.info/smglob/algebra?band}
macro:->\@invoke@module {http://mathhub.info/smglob/algebra?idempotent}
macro:->\@invoke@symbol {http://mathhub.info/smglob/mv?equal?notequal}
macro:->\@ifstar \@gimport@star \@gimport@nostar
```

Default document module:

```
803 \AtBeginDocument{%
804   \set@default@ns%
805   \ifx\module@narr\empty\setkeys{module}{narr=\module@ns}\fi%
806   \let\module@name\jobname%
807   \let\module@id\module@name % TODO deprecate
808   \edef\module@uri{\module@ns\@QuestionMark\module@name}%
809   \csgdef{module@names@\module@uri}{}%
810   \csgdef{module@imports@\module@uri}{}%
811   \csxdef{\module@uri}{\noexpand\@invoke@module{\module@uri}}%
812   \expandafter\global\expandafter\let\csname Module\module@name\expandafter\endcsname\csname\mo
813   \edef\this@module{%
814     \expandafter\noexpand\csname module@defs@\module@uri\endcsname%
815   }%
816   \csdef{module@defs@\module@uri}{}%
817   \ifcvoid{mh@currentrepos}{}{%
818     \@inmhrepostrue%
819     \addto@thismodule{\expandafter\edef\expandafter\noexpand\csname mh@old@repos@\module@uri\en
820       {\noexpand\mh@currentrepos}}%
821     \addto@thismodule{\noexpand\setcurrentreposinfo{\mh@currentrepos}}%
822   }%
823 }
```

`\activate@defs` To activate the `\symdefs` from a given module $\langle mod \rangle$, we call the macro `\module@defs@ $\langle mod \rangle$` . But to make sure that every module is activated only once, we only activate if the macro `\module@defs@ $\langle mod \rangle$` is undefined, and define it directly afterwards to prohibit further activations.

```
824 \def\activate@defs#1{%
825   \ifcsundef{Module#1}{
826     \PackageError{stex}{No module with name #1 loaded}{Probably missing an
827       \detokenize{\importmodule} (or variant) somewhere?
828   }
829   }{%
830     \ifcsundef{module@\csname Module#1\endcsname\@URI @activated}%
831       {\csname module@defs@\csname Module#1\endcsname\@URI\endcsname}{}%
832     \@namedef{module@\csname Module#1\endcsname\@URI @activated}{true}%
833   }%
834 }
```

`\usemodule` `\usemodule` acts like `\importmodule`, except that it does not re-export the semantic macros in the modules it loads.

```
835 \newcommand\usemodule[2] [] {\@importmodule[#1]{#2}{noexport}}
```

Test:

Module 3.26[Foo]:

Module 3.27[Bar]: macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?Foo?foo}

Module 3.28[Baz]: undefined

macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?Bar?bar}

\inputref@*skip hooks for spacing customization, they are empty by default.

```
836 \def\inputref@preskip{}
```

```
837 \def\inputref@postskip{}
```

\inputref \inputref{<path to the current file without extension>} supports both absolute path and relative path, meanwhile, records the path and the extension (not for relative path).

```
838 \newrobustcmd\inputref[2] [] {%
```

```
839   \importmodule@bookkeeping{#1}{#2}{%
```

```
840     %\inputreftrue
```

```
841     \inputref@preskip%
```

```
842     \stexinput{\importmodule@dir\@Slash\importmodule@modulename.tex}%
```

```
843     \inputref@postskip%
```

```
844   }%
```

```
845 }%
```

3.5 Symbols/Notations/Verbalizations

\if@symdeflocal A flag whether a symbol declaration is local (i.e. does not get exported) or not.

```
846 \newif\if@symdeflocal\@symdeflocalfalse
```

\define@in@module calls \edef{#1}{#2} and adds the macro definition to \this@module

```
847 \def\define@in@module#1#2{
```

```
848   \expandafter\edef\csname #1\endcsname{#2}%
```

```
849   \edef\define@in@module@temp{%
```

```
850     \def\expandafter\noexpand\csname#1\endcsname%
```

```
851     {#2}%
```

```
852   }%
```

```
853   \if@symdeflocal\else%
```

```
854     \expandafter\g@addto@macro@safe\csname module@defs\module@uri%
```

```
855     \expandafter\endcsname\expandafter{\define@in@module@temp}%
```

```
856   \fi%
```

```
857 }
```

\symdecl \symdecl[name=foo]{bar} Declares a new symbol in the current module with URI <module-uri>?foo and defines new macros \<uri> and \bar. If no optional name is given, bar is used as a name.

```
858 \addmetakey{symdecl}{name}%
```

```

859 \addmetakey{symdecl}{verbalization}%
860
861 % constructs a symbol name and a verbalization by splitting at exclamation
862 % points - e.g. \symdecl{symmetric!group} leads to name=symmetric-group
863 % and verbalization "symmetric group".
864 \def\symdecl@constructname#1{%
865   \def\symdecl@name{}%
866   \def\symdecl@verbalization{}%
867   \edef\symdecl@tempname{#1}%
868   \symdecl@constructname@loop%
869 }
870
871 \def\symdecl@constructname@loop{%
872   \ifx\symdecl@tempname\empty\else%
873     \StrCut\symdecl@tempname!\symdecl@tempfirst\symdecl@tempname%
874     \ifx\symdecl@name\empty%
875       \let\symdecl@name\symdecl@tempfirst%
876       \let\symdecl@verbalization\symdecl@tempfirst%
877       \symdecl@constructname@loop%
878     \else%
879       \edef\symdecl@name{\symdecl@name-\symdecl@tempfirst}%
880       \edef\symdecl@verbalization{\symdecl@verbalization\@Space\symdecl@tempfirst}%
881       \symdecl@constructname@loop%
882     \fi%
883   \fi%
884 }
885
886 \newcommand\symdecl[2][]{%
887   \ifcsdef{this@module}{%
888     \metasetkeys{symdecl}{#1}%
889     \ifcsvoid{symdecl@name}{%
890       \ifcsvoid{symdecl@verbalization}{%
891         \symdecl@constructname{#2}%
892       }{%
893         \edef\symdecl@name{#2}%
894       }%
895     }{%
896       \ifcsvoid{symdecl@verbalization}{\edef\symdecl@verbalization{#2}}{%
897       }%
898       \edef\symdecl@uri{\module@uri\@QuestionMark\symdecl@name}%
899       \ifcsvoid{\symdecl@uri}{
900         \ifcsvoid{module@names@\module@uri}{%
901           \csxdef{module@names@\module@uri}{\symdecl@name}%
902         }{%
903           \csxdef{module@names@\module@uri}{\symdecl@name,%
904             \csname module@names@\module@uri\endcsname}%
905         }%
906       }{%
907         % not compatible with circular dependencies, e.g. test/omdoc/07-modules/sms testa.tex
908         \PackageWarning{stex}{symbol already defined: \symdecl@uri}{%

```

```

909         You need to pick a fresh name for your symbol%
910     }%
911 }%
912 \define@in@module\symdecl@uri{\noexpand\@invoke@symbol{\symdecl@uri}}%
913 \define@in@module{#2}{\noexpand\@invoke@symbol{\symdecl@uri}}%
914 \global\expandafter\let\csname\symdecl@uri\@Fragment\endcsname\symdecl@verba
915 }{%
916 \PackageError{stex}{\detokenize{\symdecl} not in a module}{You need to be in a module%
917 in order to declare a new symbol}
918 }%
919 \if@insymdef\else\parsemodule@maybesetcodes\fi%
920 }

```

Test:

Module 3.29[foo]: \symdecl {bar}

Yields: macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?foo?bar}

3.5.1 Notations

`\modules@getURIfromName` This macro searches for the full URI given a symbol name and stores it in `\notation@uri`. Used by e.g. `\notation[...]{foo}{...}` to figure out what symbol foo refers to:

```

921 \def\modules@getURIfromName#1{%
922   \def\notation@uri{}%
923   \edef\modules@getURI@name{#1}%
924   \if@isuri\modules@getURI@name{%
925     \let\notation@uri\isuri@uri%
926   }{%
927     \ifcsvoid{this@module}{}%
928     \expandafter\modules@getURIfromModule\expandafter{this@module}%
929     \ifx\notation@uri\empty%
930       \edef\modules@getURI@modules{\csname module@imports\endcsname}%
931       \expandafter\@for\expandafter\@I\expandafter:\expandafter\modules@getURI@modules\do{%
932         \ifx\notation@uri\empty%
933           \expandafter\modules@getURIfromModule\expandafter{\@I}%
934         \fi%
935       }%
936     \fi%
937     \ifx\notation@uri\empty%
938       \def\notation@extract@uri@curr{#1}%
939       \notation@extracturifrommacro{#1}%
940     \fi%
941     \ifx\notation@uri\empty%
942       \PackageError{stex}{No symbol with name, URI or macroname \detokenize{#1} found!}{}%
943     \fi%
944   }%
945 }%
946 }
947

```

```

948 \def\if@isuri#1#2#3{%
949   \StrCount{#1}\@QuestionMark[\isuri@number]%
950   \ifnum\isuri@number=1 %
951     \StrCut{#1}\@QuestionMark\@isuri@mod\@isuri@name%
952     \ifcvoid{Module\@isuri@mod}{#3}{%
953       \edef\isuri@uri{\csname Module\@isuri@mod\endcsname\@URI\@QuestionMark\@isuri@name}%
954       #2%
955     }%
956   \else%
957     \ifnum\isuri@number=2 %
958       \edef\isuri@uri{#1}#2\else#3%
959     \fi%
960   \fi%
961 }
962
963 \def\modules@getURIfromModule#1{%
964   \edef\modules@getURI@names{\csname module@names@#1\endcsname}%
965   \expandafter\@for\expandafter\@I\expandafter:\expandafter=%
966   \modules@getURI@names\do{%
967     \ifx\notation@uri\empty%
968       \ifx\@I\modules@getURI@name%
969         \edef\notation@uri{#1\@QuestionMark\@I}%
970       \fi%
971     \fi%
972   }%
973 }
974
975 % extracts the full URI from \foo or anything being \ifx-equal to \foo,
976 % by expanding until we reach \@invoke@symbol{<uri>}
977 \def\notation@extracturifrommacro#1{%
978   \ifcvoid{#1}{}%
979   \expandafter\let\expandafter\notation@extract@uri@nextcs\csname#1\endcsname%
980   \ifx\notation@extract@uri@nextcs\notation@extract@uri@currucs\else%
981     \let\notation@extract@uri@currucs\notation@extract@uri@nextcs%
982     \expandafter\notation@extract@uriII\notation@extract@uri@nextcs\notation@end%
983   \fi%
984 }%
985 }
986 \long\def\notation@extract@uriII#1#2\notation@end{%
987   \def\notation@extract@check@temp{#2}
988   \ifx\@invoke@symbol#1%
989     \edef\notation@uri{#2}%
990   \else%
991     \ifx\notation@extract@check@temp\empty\else%
992       \expandafter\def\expandafter\notation@extract@uri@nextcs\expandafter{#1{#2}}%
993       \notation@extract@uri{notation@extract@uri@nextcs}%
994     \fi%
995   \fi%
996 }

```

```

\notation Adds a new notation to a symbol foo, as in: \notation[lang=en,arity=0,variant=op]{foo}{...}
\notation[variant=bar]{foo}[2]{...} \notation[args=aia,prec=500;50x49x51]{foo}{#1 bla #2
  TODO with brackets, e.g. \notation[withbrackets={\langle,\rangle}]{foo}{...}

997 \newif@ifinverbalization\@inverbalizationfalse
998 % parses the first two arguments:
999 \providerobustcmd\notation[2][ ]{%
1000   \edef\notation@first{#1}%
1001   \edef\notation@second{#2}%
1002   \notation@%
1003 }
1004
1005 \providerobustcmd\verbalization{%
1006   \@inverbalizationtrue%
1007   \notation%
1008 }
1009
1010 % parses the last two arguments
1011 \newcommand\notation@[2][0]{%
1012   \edef\notation@donext{\noexpand\notation@[{\notation@first}%
1013     {\notation@second}[#1]}%
1014   \notation@donext{#2}%
1015 }
1016
1017 % parses the notation arguments and wraps them in
1018 % \notation@assoc and \notation@argprec for flexary arguments and precedences
1019 \def\notation@[#1]#2[#3]#4{%
1020   \modules@getURIfromName{#2}%
1021   \notation@parse@params{#1}{#3}
1022   \let\notation@curr@todo@args\notation@curr@args%
1023   \def\notation@temp@notation{%
1024     \StrLen\notation@curr@args[\notation@temp@arity]%
1025     \expandafter\renewcommand\expandafter\notation@temp@notation%
1026       \expandafter[\notation@temp@arity]{#4}%
1027   % precedence
1028   \IfSubStr\notation@curr@prec;{%
1029     \StrCut\notation@curr@prec;\notation@curr@prec\notation@curr@prec%
1030     \ifx\notation@curr@prec\@empty\def\notation@curr@prec{0}\fi%
1031   }{%
1032     \ifx\notation@curr@prec\@empty%
1033       \ifnum\notation@temp@arity=0\relax%
1034         \edef\notation@curr@prec{\infprec}%
1035       \else%
1036         \def\notation@curr@prec{0}%
1037       \fi%
1038     \else%
1039       \edef\notation@curr@prec{\notation@curr@prec}%
1040       \def\notation@curr@prec{}%
1041     \fi%
1042   }%

```



```

1043 % arguments
1044 \def\notation@curr@extargs{}
1045 \def\notation@nextarg@index{1}%
1046 \notation@do@args%
1047 }
1048
1049 % parses additional notation components for (associative) arguments
1050 \def\notation@do@args{%
1051   \def\notation@nextarg@temp{}%
1052   \ifx\notation@curr@todo@args\@empty%
1053     \notation@after%
1054   \else%
1055     % argument precedence
1056     \IfSubStr\notation@curr@prec{s}{x}{%
1057       \StrCut\notation@curr@prec{s}{x}\notation@curr@argprec\notation@curr@prec%
1058     }{%
1059       \edef\notation@curr@argprec{\notation@curr@prec}%
1060       \def\notation@curr@prec{}%
1061     }%
1062     \ifx\notation@curr@argprec\@empty%
1063       \let\notation@curr@argprec\notation@curr@prec%
1064     \fi%
1065     \StrChar\notation@curr@todo@args1[\notation@argchar]%
1066     \StrGobbleLeft\notation@curr@todo@args1[\notation@curr@todo@args]%
1067     \expandafter\ifx\notation@argchar i%
1068       % normal argument
1069       \edef\notation@nextarg@temp{\noexpand\notation@argprec{\notation@curr@argprec}{#####\
1070       \edef\notation@nextarg@index{\the\numexpr\notation@nextarg@index+1 }
1071       \expandafter\g@addto@macro@safe\expandafter\notation@curr@extargs%
1072       \expandafter{\notation@nextarg@temp}%
1073       \expandafter\expandafter\expandafter\notation@do@args%
1074     \else%
1075       % associative argument
1076       \expandafter\expandafter\expandafter\notation@parse@assocarg%
1077     \fi%
1078   \fi%
1079 }
1080
1081 \def\notation@parse@assocarg#1{%
1082   \edef\notation@nextarg@temp{\noexpand\notation@argprec{\notation@curr@argprec}{\noexpand\not
1083   \edef\notation@nextarg@index{\the\numexpr\notation@nextarg@index+1 }%
1084   \expandafter\g@addto@macro@safe\expandafter\notation@curr@extargs%
1085   \expandafter{\notation@nextarg@temp}%
1086   \notation@do@args%
1087 }
1088
1089 \protected\def\safe@newcommand#1{%
1090   \ifdefined#1\expandafter\renewcommand\else\expandafter\newcommand\fi#1%
1091 }
1092

```

```

1093 % finally creates the actual macros
1094 \def\notation@after{
1095   \let\ex\expandafter%
1096   \ex\ex\ex\def\ex\ex\ex\notation@temp@notation\ex\ex\ex%
1097     {\ex\notation@temp@notation\notation@curr@extargs}%
1098   \edef\notation@temp@notation{\noexpand\notation@symprec{\notation@curr@prec}{\ex\unexpanded\ex%
1099     \def\notation@temp@fragment{}}%
1100   \ifx\notation@curr@arity\@empty\else%
1101     \edef\notation@temp@fragment{arity=\notation@curr@arity}%
1102   \fi%
1103   \ifx\notation@curr@lang\@empty\else%
1104     \ifx\notation@temp@fragment\@empty%
1105       \edef\notation@temp@fragment{lang=\notation@curr@lang}%
1106     \else%
1107       \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand lang=\notation@curr@lang}%
1108     \fi%
1109   \fi%
1110   \ifx\notation@curr@variant\@empty\else%
1111     \ifx\notation@temp@fragment\@empty%
1112       \edef\notation@temp@fragment{variant=\notation@curr@variant}%
1113     \else%
1114       \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand variant=\notation@curr@va
1115     \fi%
1116   \fi%
1117   \ifinverbalization\@inverbalizationfalse\verbalization@final%
1118   \else\notation@final\fi%
1119   \parsemodule@maybesetcodes%
1120 }
1121
1122 \def\notation@final{%
1123   \edef\notation@csname{\notation@uri\@Fragment\notation@temp@fragment}%
1124   \ifcsvoid{\notation@csname}{%
1125     \ex\ex\ex\ex\ex\ex\ex\newcommand\ex\ex\ex\csname\ex\ex\ex\notation@csname%
1126       \ex\ex\ex\endcsname\ex\ex\ex[\ex\notation@temp@arity\ex]%
1127     \ex{\notation@temp@notation}%
1128     \edef\symdecl@temps{%
1129       \noexpand\safe@newcommand\ex\noexpand\csname\notation@csname\endcsname[\notation@temp@ari
1130     }%
1131     \ex\g@addto@macro@safe\csname module@defs@\module@uri\ex\endcsname\ex{\symdecl@temps}%
1132     \ex\g@addto@macro@safe\csname module@defs@\module@uri\ex\endcsname\ex{\ex{\notation@temp@no
1133   }{%
1134     \PackageWarning{stex}{notation already defined: \notation@csname}{%
1135       Choose a different set of notation options (variant,lang,arity)%
1136     }%
1137   }%
1138 }
1139
1140 \def\verbalization@final{%
1141   \edef\notation@csname{\notation@uri\@Fragment verb\@Fragment\notation@temp@fragment}%
1142   \ifcsvoid{\notation@csname}{%

```

```

1143 \ex\ex\ex\ex\ex\ex\ex\newcommand\ex\ex\ex\csname\ex\ex\ex\notation@csname%
1144 \ex\ex\ex\endcsname\ex\ex\ex[\ex\notation@temp@arity\ex]%
1145 \ex{\notation@temp@notation}%
1146 \edef\symdecl@temps{%
1147 \noexpand\safe@newcommand\ex\noexpand\csname\notation@csname\endcsname[\notation@temp@ari
1148 }%
1149 \ex@g@addto@macro@safe\csname module@defs@\module@uri\ex\endcsname\ex{\symdecl@temps}%
1150 \ex@g@addto@macro@safe\csname module@defs@\module@uri\ex\endcsname\ex{\ex{\notation@temp@no
1151 }-%
1152 \PackageWarning{stex}{verbalization already defined: \notation@csname}%
1153 Choose a different set of verbalization options (variant,lang,arity)%
1154 }%
1155 }%
1156 }
1157
1158 % parses optional parameters
1159 \def\notation@parse@params#1#2{%
1160 \def\notation@curr@prec{%
1161 \def\notation@curr@args{%
1162 \def\notation@curr@variant{%
1163 \def\notation@curr@arity{%
1164 \def\notation@curr@provided@arity#{#2}
1165 \def\notation@curr@lang{%
1166 \def\notation@options@temp#{#1}
1167 \notation@parse@params%
1168 \ifx\notation@curr@args\@empty%
1169 \ifx\notation@curr@provided@arity\@empty%
1170 \notation@num@to@ia\notation@curr@arity%
1171 \else%
1172 \notation@num@to@ia\notation@curr@provided@arity%
1173 \fi%
1174 \fi%
1175 }
1176 \def\notation@parse@params@{%
1177 \IfSubStr\notation@options@temp,{%
1178 \StrCut\notation@options@temp,\notation@option@temp\notation@options@temp%
1179 \notation@parse@param%
1180 \notation@parse@params@%
1181 }{\ifx\notation@options@temp\@empty\else%
1182 \let\notation@option@temp\notation@options@temp%
1183 \notation@parse@param%
1184 \fi}%
1185 }
1186
1187 %parses an individual optional argument/key-value-pair
1188 \def\notation@parse@param{%
1189 \trimstring\notation@option@temp%
1190 \ifx\notation@option@temp\@empty\else%
1191 \IfSubStr\notation@option@temp=%{%
1192 \StrCut\notation@option@temp=\notation@key\notation@value%

```

```

1193     \trimstring\notation@key%
1194     \trimstring\notation@value%
1195     \IfStrEq\notation@key{prec}{%
1196         \edef\notation@curr@prec{\notation@value}%
1197     }{%
1198     \IfStrEq\notation@key{args}{%
1199         \edef\notation@curr@args{\notation@value}%
1200     }{%
1201     \IfStrEq\notation@key{lang}{%
1202         \edef\notation@curr@lang{\notation@value}%
1203     }{%
1204     \IfStrEq\notation@key{variant}{%
1205         \edef\notation@curr@variant{\notation@value}%
1206     }{%
1207     \IfStrEq\notation@key{arity}{%
1208         \edef\notation@curr@arity{\notation@value}%
1209     }{%
1210     }}}}%
1211 }{%
1212     \edef\notation@curr@variant{\notation@option@temp}%
1213 }%
1214 \fi%
1215 }
1216
1217 % converts an integer to a string of 'i's, e.g. 3 => iii,
1218 % and stores the result in \notation@curr@args
1219 \def\notation@num@to@ia#1{%
1220     \IfInteger{#1}{
1221         \notation@num@to@ia@#1%
1222     }{%
1223         %
1224     }%
1225 }
1226 \def\notation@num@to@ia@#1{%
1227     \ifnum#1>0%
1228         \edef\notation@curr@args{\notation@curr@args i}%
1229         \expandafter\notation@num@to@ia@\expandafter{\the\numexpr#1-1\@Space}%
1230     \fi%
1231 }

```

The following macros take care of precedences, parentheses/bracketing, associative (flexary) arguments etc. in presentation:

```

1232 \def\notation@assoc#1#2{% function, argv
1233     \let\@tmpop=\relax% do not print the function the first time round
1234     \@for\@I:=#2\do{\@tmpop% print the function
1235         % write the i-th argument with locally updated precedence
1236         \@I%
1237     \def\@tmpop{#1}%
1238     }%
1239 }%

```

```

1240
1241 \def\notation@lparen{()
1242 \def\notation@rparen{)}
1243 \def\infprec{1000000}
1244 \def\neginfprec{-\infprec}
1245
1246 \newcount\notation@downprec
1247 \notation@downprec=\neginfprec
1248
1249 % patching displaymode
1250 \newif\if@displaymode\@displaymodefalse
1251 \expandafter\everydisplay\expandafter{\the\everydisplay\@displaymodetrue}
1252 \let\old@displaystyle\displaystyle
1253 \def\displaystyle{\old@displaystyle\@displaymodetrue}
1254
1255 \def\dobrackets#1{% avoiding groups at all costs to ensure \parray still works!
1256   \def\notation@innertmp{#1}%
1257   \let\ex\expandafter%
1258   \if@displaymode%
1259     \ex\ex\ex\left\ex\ex\ex\notation@lparen%
1260     \ex\notation@resetbrackets\ex\notation@innertmp%
1261     \ex\right\notation@rparen%
1262   \else%
1263     \ex\ex\ex\notation@lparen%
1264     \ex\notation@resetbrackets\ex\notation@innertmp%
1265     \notation@rparen%
1266   \fi%
1267 }
1268
1269 \def\withbrackets#1#2#3{%
1270   \edef\notation@lparen{#1}%
1271   \edef\notation@rparen{#2}%
1272   #3%
1273   \notation@resetbrackets%
1274 }
1275
1276 \def\notation@resetbrackets{%
1277   \def\notation@lparen{()%
1278   \def\notation@rparen{)}%
1279 }
1280
1281 \def\notation@symprec#1#2{%
1282   \ifnum#1>\notation@downprec\relax%
1283     \notation@resetbrackets#2%
1284   \else%
1285     \ifnum\notation@downprec=\infprec\relax%
1286       \notation@resetbrackets#2%
1287     \else
1288       \if@inarray@
1289         \notation@resetbrackets#2

```

```

1290     \else\dobrackets{#2}\fi%
1291   \fi\fi%
1292 }
1293
1294 \newif\if@inarray@\@inarray@false
1295
1296 \def\notation@argprec#1#2{%
1297   \def\notation@innertmp{#2}
1298   \edef\notation@downprec@temp{\number#1}%
1299   \notation@downprec=\expandafter\notation@downprec@temp%
1300   \expandafter\relax\expandafter\notation@innertmp%
1301   \expandafter\notation@downprec\expandafter=\number\notation@downprec\relax%
1302 }

```

\@invoke@symbol after \symdecl{foo}, \foo expands to \@invoke@symbol{<uri>}:

```

1303 \protected\def\@invoke@symbol#1{%
1304   \def\@invoke@symbol@first{#1}%
1305   \symbol@args%
1306 }

```

takes care of the optional notation-option-argument, and either invokes \@invoke@symbol@math for symbolic presentation or \@invoke@symbol@text for verbalization (TODO)

```

1307 \newcommand\symbol@args[1][]{%
1308   \notation@parse@params{#1}{}%
1309   \def\notation@temp@fragment{}%
1310   \ifx\notation@curr@arity\@empty\else%
1311     \edef\notation@temp@fragment{arity=\notation@curr@arity}%
1312   \fi%
1313   \ifx\notation@curr@lang\@empty\else%
1314     \ifx\notation@temp@fragment\@empty%
1315       \edef\notation@temp@fragment{lang=\notation@curr@lang}%
1316     \else%
1317       \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand lang=\notation@curr@lang}%
1318     \fi%
1319   \fi%
1320   \ifx\notation@curr@variant\@empty\else%
1321     \ifx\notation@temp@fragment\@empty%
1322       \edef\notation@temp@fragment{variant=\notation@curr@variant}%
1323     \else%
1324       \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand variant=\notation@curr@va
1325     \fi%
1326   \fi%
1327   %
1328   \ifmmode\def\invoke@symbol@next{\@invoke@symbol@math\@invoke@symbol@first\notation@temp@fragm
1329   \else\def\invoke@symbol@next{\@invoke@symbol@text\@invoke@symbol@first\notation@temp@fragment
1330   \invoke@symbol@next%
1331 }

```

This finally gets called with both uri and notation-option, convenient for e.g.

a LaTeXML binding:

```
1332 \def\@invoke@symbol@math#1#2{%
1333   \csname #1\@Fragment#2\endcsname%
1334 }
```

TODO:

```
1335 \def\@invoke@symbol@text#1#2{%
1336   \@termref{#1}\csname #1\@Fragment verb\@Fragment#2\endcsname}%
1337 }
```

TODO: To set notational options (globally or locally) generically:

```
1338 \def\setstexlang#1{%
1339   \def\stex@lang{#1}%
1340 }%
1341 \setstexlang{en}
1342 \def\setstexvariant#1#2{%
1343   % TODO
1344 }
1345 \def\setstexvariants#1{%
1346   \def\stex@variants{#1}%
1347 }
```

Test:

```
Module 3.30[FooBar]: \symdecl {barbar}
\notation [arity=0]{barbar}{\psi }
\notation [prec=50;\infprec ]{barbar}[1]{\barbar [arity=0]\dobrackets {##1}}

\notation [arity=0,variant=cap]{barbar}{\Psi }
\notation [variant=cap]{barbar}[1]{\barbar [arity=0,variant=cap]\dobrackets {##1}}
```

```
$\barbar {A}$:  $\psi(A)$ 
$\barbar [variant=cap]{A}$:  $\Psi(A)$ 
```

```
\symdecl {plus}
\symdecl {times}
\symdecl {vara}
\symdecl {varb}
\symdecl {varc}
\symdecl {vard}
\symdecl {vare}
\notation {vara}{a}
\notation {varb}{b}
\notation {varc}{c}
\notation {vard}{d}
\notation {vare}{e}
\notation [prec=500;500,args=a]{plus}{\withbrackets \langle \rangle {##1}}{+}
```

`\notation [prec=600;600,args=a]{times}{##1}{\cdot }`

`$\times {\frac {\mathrm {a} }{\mathrm {b} }},{+}{\frac {\mathrm {a} }{\mathrm {b} }}{\frac {\mathrm {a} }{\mathrm {b} }},{\times {\frac {\mathrm {a} }{\mathrm {b} }},{+}{\frac {\mathrm {a} }{\mathrm {b} }}}$:`

$$\frac{a}{b} \cdot \left(\frac{a}{b} + c \cdot (d + e) \right)$$

`\[\times {\frac {\mathrm {a} }{\mathrm {b} }},{+}{\frac {\mathrm {a} }{\mathrm {b} }}{\frac {\mathrm {a} }{\mathrm {b} }},{\times {\frac {\mathrm {a} }{\mathrm {b} }},{+}{\frac {\mathrm {a} }{\mathrm {b} }}} \]`
`,\plus {\vard ,\varee }}}`

$$\frac{a}{b} \cdot \left(\frac{a}{b} + c \cdot (d + e) \right)$$

`\symdecl {foo!bar}`
`\foo !bar: foo bar`
`\symdecl [verbalization={finite group}]{finitegroup}`
`\verbalization [variant=oforder]{finitegroup}[1]{finite group of order ##1}`
`\finitegroup [oforder]{n$}: finite group of order n`

3.6 Term References

`\ifhref`

```
1348 \newif\ifhref\hreffalse%
1349 \AtBeginDocument{%
1350   \ifpackageloaded{hyperref}{%
1351     \hreftrue%
1352   }{%
1353     \hreffalse%
1354   }%
1355 }
```

`\termref@maketarget` This macro creates a hypertarget `sref@(symbol URI)@target` and defines `\sref@(symbol URI)#1` to create a hyperlink to here on the text #1.

```
1356 \def\termref@maketarget#1#2{%
1357   % #1: symbol URI
1358   % #2: text
1359   \ifhref%
1360     \hypertarget{sref@#1@target}{#2}%
1361   \fi%
1362   \expandafter\edef\csname sref@#1\endcsname##1{%
1363     \ifhref\noexpand\hyperlink{sref@#1@target}{##1}\fi%
1364   }%
1365 }
```

`\@termref`

```
1366 \def\@termref#1#2{%
1367   % #1: symbol URI
1368   % #2: text
1369   \ifcvoid{#1}{%
```



```

1370 \StrCut[2]{#1}\@QuestionMark\termref@mod\termref@name%
1371 \ifcsvoid{\termref@mod}{%
1372 \PackageError{stex}{Term reference: Module with URI \termref@mod\ not found}{}%
1373 }{%
1374 \PackageError{stex}{Term reference: Module \termref@mod\ exists, but %
1375 contains no symbol with name \termref@name.%
1376 }{%
1377 }%
1378 }{%
1379 \ifcsvoid{sref@#1}{%
1380 #2% TODO: No reference point exists!
1381 }{%
1382 \csname sref@#1\endcsname{#2}%
1383 }%
1384 }%
1385 }

\tref
1386
1387 \def\@capitalize#1{\uppercase{#1}}%
1388 \newrobustcmd\capitalize[1]{\expandafter\@capitalize #1}%
1389
1390 \newcommand\tref[2][]{%
1391 \edef\tref@name{#1}%
1392 \ifx\tref@name\empty
1393 \symdecl@constructname{#2}%
1394 \edef\tref@name{\symdecl@name}%
1395 \else%
1396 \edef\symdecl@verbalization{#2}%
1397 \fi%
1398 \expandafter\modules@getURIfromName\expandafter{\tref@name}%
1399 \expandafter\@termref\expandafter{\notation@uri}{\symdecl@verbalization}%
1400 }
1401 \def\trefs#1{%
1402 \modules@getURIfromName{#1}%
1403 \expandafter\@termref\expandafter{\notation@uri}{\csname\notation@uri\@Fragment verb\@Fragment
1404 }
1405 \def\Tref#1{%
1406 \modules@getURIfromName{#1}%
1407 \expandafter\@termref\expandafter{\notation@uri}{\expandafter\capitalize\csname\notation@uri\
1408 }
1409 \def\Trefs#1{%
1410 \modules@getURIfromName{#1}%
1411 \expandafter\@termref\expandafter{\notation@uri}{\expandafter\capitalize\csname\notation@uri\
1412 }

Test:
foo bar
foo-bar
finite group

```

```

\defi
1413 \addmetakey{defi}{name}
1414 \def\@definiendum#1#2{%
1415   \defemph{\termref@maketarget{#1}{#2}}%
1416   \parsemodule@maybesetcodes%
1417 }
1418
1419 \newcommand\defi[2][{}]{%
1420   \metasetkeys{defi}{#1}%
1421   \ifx\defi@name\@empty%
1422     \symdecl@constructname{#2}%
1423     \let\defi@name\symdecl@name%
1424     \let\defi@verbalization\symdecl@verbalization%
1425   \else%
1426     \edef\defi@verbalization{#2}%
1427   \fi%
1428   \ifcsvoid{\module@uri\@QuestionMark\defi@name}{%
1429     \symdecl\defi@name%
1430   }{\edef\symdecl@uri{\module@uri\@QuestionMark\defi@name}}%
1431   \@definiendum\symdecl@uri\defi@verbalization%
1432 }
1433 \def\Defi#1{%
1434   \symdecl{#1}%
1435   \@definiendum\symdecl@uri{\capitalize\symdecl@verbalization}%
1436 }
1437 \def\defis#1{%
1438   \symdecl{#1}%
1439   \@definiendum\symdecl@uri{\symdecl@verbalization s}%
1440 }
1441 \def\Defis#1{%
1442   \symdecl{#1}%
1443   \@definiendum\symdecl@uri{\capitalize\symdecl@verbalization s}%
1444 }

```

Test:
[a simple group](#)
[simple group](#)

3.7 sref

We find out whether the `hyperref` package is loaded, since we may want to use it for cross-references, for which we set up some internal macros that gracefully degrade if `hyperref` is not loaded.

```

\sref*{@ifh
1445 \newif\ifhref\hreffalse%
1446 \AtBeginDocument{%
1447   \ifpackageloaded{hyperref}{%
1448     \hreftrue%

```

```

1449 }{%
1450   \hreffalse%
1451 }%
1452 }%
1453 \newcommand\sref@href@ifh[2]{%
1454   \ifhref%
1455     \href{#1}{#2}%
1456   \else%
1457     #2%
1458   \fi%
1459 }%
1460 \newcommand\sref@hlink@ifh[2]{%
1461   \ifhref%
1462     \hyperlink{#1}{#2}%
1463   \else%
1464     #2%
1465   \fi%
1466 }%
1467 \newcommand\sref@target@ifh[2]{%
1468   \ifhref%
1469     \hypertarget{#1}{#2}%
1470   \else%
1471     #2%
1472   \fi%
1473 }%

```

Then we provide some macros for \TeX -specific crossreferencing

\sref@target The next macro uses this and makes an target from the current **sref@id** declared by a **id** key.

```

1474 \def\sref@target{%
1475   \ifx\sref@id@empty%
1476     \relax%
1477   \else%
1478     \edef\@target{sref@\ifcsundef{sref@part}{}\sref@part @}\sref@id @target}%
1479     \sref@target@ifh\@target{}%
1480   \fi%
1481 }%

```

\srefaddidkey **\srefaddidkey**[*<keyval>*]{*<group>*} extends the metadata keys of the group *<group>* with an **id** key. In the optional key/value pairs in *<keyval>* the **prefix** key can be used to specify a prefix. Note that the **id** key defined by **\srefaddidkey**[*<keyval>*]{*<group>*} not only defines **\sref@id**, which is used for referencing by the **sref** package, but also **\<group>@id**, which is used for showing metadata via the **showmeta** option of the **metakeys** package.

```

1482 \addmetakey{srefaddidkey}{prefix}
1483 \newcommand\srefaddidkey[2][{}]{%
1484   \metasetkeys{srefaddidkey}{#1}%
1485   \@metakeys@ext@clear@keys{#2}{sref@id}{}% id cannot have a default

```

```

1486 \metakeys@ext@clear@keys{#2}{id}{}%
1487 \metakeys@ext@showkeys{#2}{id}%
1488 \define@key{#2}{id}{%
1489   \edef\sref@id{\srefaddidkey@prefix ##1}%
1490   %\expandafter\edef\csname #2@id\endcsname{\srefaddidkey@prefix ##1}%
1491   \csedef{#2@id}{\srefaddidkey@prefix ##1}%
1492 }%
1493 }%

```

\sref@def This macro stores the value of its last argument in a custom macro for reference.

```

1494 \newcommand\sref@def[3]{\csgdef\sref@#1@#2}{#3}}

```

The next step is to set up a file to which the references are written, this is normally the .aux file, but if the `extref` option is set, we have to use an .ref file.

```

1495 \ifextrefs%
1496   \newwrite\refs@file%
1497 \else%
1498   \def\refs@file{\@auxout}%
1499 \fi%

```

\sref@def This macro writes an `\sref@def` command to the current aux file and also executes it.

```

1500 \newcommand\sref@def[3]{%
1501   \protected@write\refs@file{}\string\sref@def{#1}{#2}{#3}}%
1502 }%

```

\sref@label The `\sref@label` macro writes a label definition to the auxfile.

```

1503 \newcommand\sref@label[2]{%
1504   \sref@def{\ifcsundef\sref@part}{\sref@part @}{#2}{page}{\thepage}%
1505   \sref@def{\ifcsundef\sref@part}{\sref@part @}{#2}{label}{#1}%
1506 }%

```

\sreflabel The `\sreflabel` macro is a semantic version of `\label`, it combines the categorization given in the first argument with L^AT_EX's `\@currentlabel`.

```

1507 \newcommand\sreflabel[2]{\sref@label{#1 \@currentlabel}{#2}}

```

\sref@label@id The `\sref@label@id` writes a label definition for the current `\sref@id` if it is defined.

```

1508 \def\sref@id{} % make sure that defined
1509 \newcommand\sref@label@id[1]{%
1510   \ifx\sref@id\empty%
1511     \relax%
1512   \else%
1513     \sref@label{#1}{\sref@id}%
1514   \fi%
1515 }%

```

`\sref@label@id@arg` The `\sref@label@id@arg` writes a label definition for the second argument if it is defined.

```

1516 \newcommand\sref@label@id@arg[2]{%
1517   \def\@@id{#2}
1518   \ifx\@@id\@empty%
1519     \relax%
1520   \else%
1521     \sref@label{#1}{\@@id}%
1522   \fi%
1523 }%
```

3.8 smultiling

`modsig` The `modsig` environment is just a layer over the `module` environment. We also redefine macros that may occur in module signatures so that they do not create markup. Finally, we set the flag `\mod@<mod>\multiling` to `true`.

```

1524 \newenvironment{modsig}[2][]{\def\@test{#1}%
1525 \ifx\@test\@empty\begin{module}[name=#2]\else\begin{module}[name=#2,#1]\fi%
1526 \expandafter\gdef\csname mod@#2\multiling\endcsname{true}%
1527 \ignorespacesandpars}
1528 {\end{module}\ignorespacesandparsafterend}
```

3.9 smglom

`\gimport` Just a shortcut, we have a starred and unstarred version, the first one is conservative. For example, if we execute:

```
\gimport[smglom/numberfields]{naturalnumbers}
```

First we are redirected to `\@gimport@nostar`, we store the `smglom/numberfields` (*the repo's path*) in `\@test`, then store `\mh@currentrepos` (*current directory*) in `\mh@repos`. If no repo's path is offered, that means the module to import is under the same directory, so we let `\mhrepos=\mh@repos` and pass bunch of parameters to `\importmhmodule`, which is defined in `module.sty`. If there's a repo's path, then we let `\mhrepos=<the repo's path>`. Finally we use `\mhcurrentrepos` (defined in `module.sty`) to change the `\mh@currentrepos`.

```

1529 \def\gimport{\@ifstar\@gimport@star\@gimport@nostar}%
1530 \newrobustcmd\@gimport@star[2][]{\def\@test{#1}%
1531 \edef\mh@repos{\mh@currentrepos}%
1532 \ifx\@test\@empty%
1533   \importmhmodule[conservative,mhrepos=\mh@repos,path=#2]{#2}%
1534 \else\importmhmodule[conservative,mhrepos=#1,path=#2]{#2}\fi%
1535 \setcurrentreposinfo{\mh@repos}%
1536 \ignorespacesandpars\parsemodule@maybesetcodes}
1537 \newrobustcmd\@gimport@nostar[2][]{\def\@test{#1}%
1538 \edef\mh@repos{\mh@currentrepos}%
```

```

1539 \ifx\@test\@empty%
1540 \importmhmodule[mhrepos=\mh@repos,path=#2]{#2}%
1541 \else\importmhmodule[mhrepos=#1,path=#2]{#2}\fi%
1542 \setcurrentreposinfo{\mh@repos}%
1543 \ignorespacesandpars\parsemodule@maybesetcodes}

```

3.10 mathhub

`\libinput` the `\libinput` macro inputs from the `lib` directory of the MathHub repository and then the `meta-inf/lib` repository of the group, if they exist. Since in practice nested libinputs may occur, we make sure that we stash the old values of `\mh@inffile` and `\mh@libfile` and restore them at the end.

```

1544 \def\modules@@first#1/#2;{#1}
1545 \newcommand\libinput[1]{%
1546 \ifcsvoid{mh@currentrepos}{%
1547   \PackageError{mathhub}{current MathHub repository not found}{}%
1548   {}
1549 \edef\@mh@group{\expandafter\modules@@first\mh@currentrepos;}
1550 \let\orig@inffile\mh@inffile\let\orig@libfile\mh@libfile
1551 \def\mh@inffile{\MathHub{\@mh@group/meta-inf/lib/#1}}
1552 \def\mh@libfile{\MathHub{\mh@currentrepos/lib/#1}}%
1553 \IfFileExists\mh@inffile{\stexinput\mh@inffile}{}%
1554 \IfFileExists\mh@inffile{\IfFileExists\mh@libfile}{%
1555   {\PackageError{mathhub}
1556     {Library file missing; cannot input #1.tex\MessageBreak%
1557     Both \mh@libfile.tex\MessageBreak and \mh@inffile.tex\MessageBreak%
1558     do not exist}%
1559   {Check whether the file name is correct}}}%
1560 \IfFileExists\mh@libfile{\stexinput\mh@libfile\relax}{}
1561 \let\mh@inffile\orig@inffile\let\mh@libfile\orig@libfile}

```

3.11 omdoc/omgroup

```

1562 \newcount\section@level
1563
1564 \section@level=2
1565 \ifdefstring{\omdoc@sty@class}{book}{\section@level=0}{%
1566 \ifdefstring{\omdoc@sty@class}{report}{\section@level=0}{%
1567 \ifdefstring{\omdoc@sty@topsect}{part}{\section@level=0}{%
1568 \ifdefstring{\omdoc@sty@topsect}{chapter}{\section@level=1}{%

```

`\omgroup@nonum` convenience macro: `\omgroup@nonum{<level>}{<title>}` makes an unnumbered sectioning with title *<title>* at level *<level>*.

```

1569 \newcommand\omgroup@nonum[2]{%
1570 \ifx\hyper@anchor\@undefined\else\phantomsection\fi%
1571 \addcontentsline{toc}{#1}{#2}\@nameuse{#1}*{#2}}

```

`\omgroup@num` convenience macro: `\omgroup@num{<level>}{<title>}` makes numbered sectioning with title *<title>* at level *<level>*. We have to check the `short` key was given in the

omgroup environment and – if it is use it. But how to do that depends on whether the rdfmeta package has been loaded. In the end we call \sref@label@id to enable crossreferencing.

```

1572 \newcommand\omgroup@num[2]{%
1573 \edef\@@ID{\sref@id}
1574 \ifx\omgroup@short\empty% no short title
1575 \@nameuse{#1}{#2}%
1576 \else% we have a short title
1577 \@ifundefined{rdfmeta@sectioning}%
1578   {\@nameuse{#1}[\omgroup@short]{#2}}%
1579   {\@nameuse{rdfmeta@#1@old}[\omgroup@short]{#2}}%
1580 \fi%
1581 \sref@label@id@arg{\omdoc@sect@name~\@nameuse{the#1}}\@@ID}

```

omgroup

```

1582 \def\@true{true}
1583 \def\@false{false}
1584 \srefaddidkey{omgroup}
1585 \addmetakey{omgroup}{date}
1586 \addmetakey{omgroup}{creators}
1587 \addmetakey{omgroup}{contributors}
1588 \addmetakey{omgroup}{srccite}
1589 \addmetakey{omgroup}{type}
1590 \addmetakey*{omgroup}{short}
1591 \addmetakey*{omgroup}{display}
1592 \addmetakey[false]{omgroup}{loadmodules}[true]

```

we define a switch for numbering lines and a hook for the beginning of groups:

\at@begin@omgroup The \at@begin@omgroup macro allows customization. It is run at the beginning of the omgrou, i.e. after the section heading.

```

1593 \newif\if@mainmatter\@mainmattertrue
1594 \newcommand\at@begin@omgroup[3][]{\}

```

Then we define a helper macro that takes care of the sectioning magic. It comes with its own key/value interface for customization.

```

1595 \addmetakey{omdoc@sect}{name}
1596 \addmetakey[false]{omdoc@sect}{clear}[true]
1597 \addmetakey{omdoc@sect}{ref}
1598 \addmetakey[false]{omdoc@sect}{num}[true]
1599 \newcommand\omdoc@sectioning[3][]{\metasetkeys{omdoc@sect}{#1}%
1600 \ifx\omdoc@sect@clear\@true\cleardoublepage\fi%
1601 \if@mainmatter% numbering not overridden by frontmatter, etc.
1602 \ifx\omdoc@sect@num\@true\omgroup@num{#2}{#3}\else\omgroup@nonum{#2}{#3}\fi%
1603 \def\current@section@level{\omdoc@sect@name}%
1604 \else\omgroup@nonum{#2}{#3}%
1605 \fi}% if@mainmatter

```

and another one, if redefines the \addtocontentsline macro of L^AT_EX to import the respective macros. It takes as an argument a list of module names.

```

1606 \newcommand\omgroup@redefine@addtocontents[1]{%

```

```

1607 %\edef\@import{#1}%
1608 %\@for\@I:=\@import\do{%
1609 %\edef\@path{\csname module@\@I @path\endcsname}%
1610 %\@ifundefined{tf@toc}\relax%
1611 %    {\protected@write\tf@toc}{\string\@requiremodules{\@path}}}%
1612 %\ifx\hyper@anchor\@undefined% hyperref.sty loaded?
1613 %\def\addcontentsline##1##2##3{%
1614 %\addtocontents{##1}{\protect\contentsline{##2}{\string\withusedmodules{##1}{##3}}{\thepage}}%
1615 %\else% hyperref.sty not loaded
1616 %\def\addcontentsline##1##2##3{%
1617 %\addtocontents{##1}{\protect\contentsline{##2}{\string\withusedmodules{##1}{##3}}{\thepage}}{\@c
1618 %\fi
1619 }% hypreref.sty loaded?

    now the omgroup environment itself. This takes care of the table of contents
    via the helper macro above and then selects the appropriate sectioning com-
    mand from article.cls. It also registers the current level of omgroups in the
    \omgroup@level counter.

1620 \newcount\omgroup@level
1621 \newenvironment{omgroup}[2][ ]% keys, title
1622 {\metasetkeys{omgroup}{#1}\sref@target%
1623 \advance\omgroup@level by 1\relax%

    If the loadmodules key is set on \begin{omgroup}, we redefine the \addcontetsline
    macro that determines how the sectioning commands below construct the entries
    for the table of contents.

1624 \ifx\omgroup@loadmodules\@true%
1625 \omgroup@redefine@addtocontents{\@ifundefined{module@id}\used@modules%
1626 {\@ifundefined{module@\module@id @path}{\used@modules}\module@id}}\fi%

    now we only need to construct the right sectioning depending on the value of
    \section@level.

1627 \advance\section@level by 1\relax%
1628 \ifcase\section@level%
1629 \or\omdoc@sectioning[name=\omdoc@part@kw,clear,num]{part}{#2}%
1630 \or\omdoc@sectioning[name=\omdoc@chapter@kw,clear,num]{chapter}{#2}%
1631 \or\omdoc@sectioning[name=\omdoc@section@kw,num]{section}{#2}%
1632 \or\omdoc@sectioning[name=\omdoc@subsection@kw,num]{subsection}{#2}%
1633 \or\omdoc@sectioning[name=\omdoc@subsubsection@kw,num]{subsubsection}{#2}%
1634 \or\omdoc@sectioning[name=\omdoc@paragraph@kw,ref=this \omdoc@paragraph@kw]{paragraph}{#2}%
1635 \or\omdoc@sectioning[name=\omdoc@subparagraph@kw,ref=this \omdoc@subparagraph@kw]{paragraph}{#2}%
1636 \fi% \ifcase
1637 \at@begin{omgroup}[#1]\section@level{#2}}% for customization
1638 {\advance\section@level by -1\advance\omgroup@level by -1}

    and finally, we localize the sections

1639 \newcommand\omdoc@part@kw{Part}
1640 \newcommand\omdoc@chapter@kw{Chapter}
1641 \newcommand\omdoc@section@kw{Section}
1642 \newcommand\omdoc@subsection@kw{Subsection}

```



```

1643 \newcommand\omdoc@subsubsection@kw{Subsubsection}
1644 \newcommand\omdoc@paragraph@kw{paragraph}
1645 \newcommand\omdoc@subparagraph@kw{subparagraph}

\setSGvar set a global variable
1646 \newcommand\setSGvar[1]{\@namedef{sTeX@Gvar@#1}}

\useSGvar use a global variable
1647 \newrobustcmd\useSGvar[1]{%
1648   \ifundefined{sTeX@Gvar@#1}
1649   {\PackageError{omdoc}
1650     {The sTeX Global variable #1 is undefined}
1651     {set it with \protect\setSGvar}}
1652 \@nameuse{sTeX@Gvar@#1}}

blindomgroup
1653 \newcommand\at@begin@blindomgroup[1]{%
1654 \newenvironment{blindomgroup}
1655 {\advance\section@level by 1\at@begin@blindomgroup\setion@level}
1656 {\advance\section@level by -1}

```

3.12 omtext

3.12.1 Mathematical Text

We define the actions that are undertaken, when the keys are encountered. The first set just records metadata; this is very simple via the `\addmetakey` infrastructure [Koh20]. Note that we allow math in the `title` field, so we do not declare it to be `Semiverbatim` (indeed not at all, which allows it by default).

```

1657 \srefaddidkey{omtext}
1658 \addmetakey[]{omtext}{functions}
1659 \addmetakey*{omtext}{display}
1660 \addmetakey{omtext}{for}
1661 \addmetakey{omtext}{from}
1662 \addmetakey{omtext}{type}
1663 \addmetakey*{omtext}{title}
1664 \addmetakey*{omtext}{start}
1665 \addmetakey{omtext}{theory}
1666 \addmetakey{omtext}{continues}
1667 \addmetakey{omtext}{verbalizes}
1668 \addmetakey{omtext}{subject}

\st@flow We define this macro, so that we can test whether the display key has the value
flow
1669 \def\st@flow{flow}

```

We define a switch that allows us to see whether we are inside an `omtext` environment or a statement. It will be used to give better error messages for inline statements.

```

1670 \newif\if@in@omtext\@in@omtextfalse

omtext The omtext environment can have a title, which is used in a similar way. We
      redefine the \lec macro so the trailing \par does not get into the way.
1671 \def\omtext@pre@skip{\smallskip}
1672 \def\omtext@post@skip{}
1673 \newenvironment{omtext}[1][\@in@omtexttrue%
1674   \bgroup\metasetkeys{omtext}{#1}\sref@label{id{this paragraph}}%
1675   \def\lec##1{\@lec{##1}}}%
1676   \omtext@pre@skip\par\noindent%
1677   \ifx\omtext@title\@empty%
1678     \ifx\omtext@start\@empty\else%
1679       \ifx\omtext@display\st@flow\omtext@start\else\stDMemph{\omtext@start}\fi\enspace%
1680     \fi% end omtext@start empty
1681   \else\stDMemph{\omtext@title}:\enspace%
1682     \ifx\omtext@start\@empty\else\omtext@start\enspace\fi%
1683   \fi% end omtext@title empty
1684   \ignorespacesandpars}
1685 {\egroup\omtext@post@skip\@in@omtextfalse\ignorespacesandpars}

```

3.12.2 Phrase-level Markup

`\phrase` For the moment, we do disregard the most of the keys

```

1686 \srefaddidkey{phrase}
1687 \addmetakey{phrase}{style}
1688 \addmetakey{phrase}{class}
1689 \addmetakey{phrase}{index}
1690 \addmetakey{phrase}{verbalizes}
1691 \addmetakey{phrase}{type}
1692 \addmetakey{phrase}{only}
1693 \newcommand\phrase[2][\metasetkeys{phrase}{#1}%
1694 \ifx\phrase@only\@empty\only<\phrase@only>{#2}\else #2\fi}

```

`\coref*`

```

1695 \providecommand\textsubscript[1]{\ensuremath{_{#1}}}
1696 \newcommand\corefs[2]{#1\textsubscript{#2}}
1697 \newcommand\coreft[2]{#1\textsuperscript{#2}}

```

`\n*lex`

```

1698 \newcommand\nlex[1]{\green{\sl{#1}}}
1699 \newcommand\nlcex[1]{*\green{\sl{#1}}}

```

`sinlinequote`

```

1700 \def\@sinlinequote#1{‘‘{\sl{#1}}}’’}
1701 \def\@sinlinequote#1#2{\@sinlinequote{#2}~#1}
1702 \newcommand\sinlinequote[2][
1703 {\def\@opt{#1}\ifx\@opt\@empty\@sinlinequote{#2}\else\@sinlinequote\@opt{#2}\fi}

```

3.12.3 Declarations (under development)

The declaration macros are still under development (i.e. the macros) are still under development and may change at any time. Currently they are completely empty.

```
1704 \newcommand\vdec[2] [] {#2}
1705 \newcommand\vrest[2] [] {#2}
1706 \newcommand\vcond[2] [] {#2}
```

```
EdN:1 \strucdec 1
1707 \newcommand\strucdec[2] [] {#2}
```

```
EdN:2 \impdec 2
1708 \newcommand\impdec[2] [] {#2}
```

3.12.4 Block-Level Markup

```
sblockquote
1709 \def\begin@sblockquote{\begin{quote}\sl}
1710 \def\end@sblockquote{\end{quote}}
1711 \def\begin@@sblockquote#1{\begin@sblockquote}
1712 \def\end@@sblockquote#1{\def\@lec##1{\textrm{##1}}\@lec{#1}\end@sblockquote}
1713 \newenvironment{sblockquote}[1] []
1714 {\def\@opt{#1}\ifx\@opt\@empty\begin@sblockquote\else\begin@@sblockquote\@opt\fi}
1715 {\ifx\@opt\@empty\end@sblockquote\else\end@@sblockquote\@opt\fi}

sboxquote
1716 \newenvironment{sboxquote}[1] []
1717 {\def\@src{#1}\begin{mdframed}[leftmargin=.5cm,rightmargin=.5cm]}
1718 {\@lec{\textrm{\@src}}\end{mdframed}}
```

The line end comment macro makes sure that it will not be forced on the next line unless necessary.

`\lec` The actual appearance of the line end comment is determined by the `\@lec` macro, which can be customized in the document class. The basic one here is provided so that it is not missing.

```
1719 \providecommand{\@lec}[1]{(#1)}
1720 \def\@lec#1{\strut\hfil\strut\hfil\nobreak\hfill\@lec{#1}}
1721 \def\lec#1{\@lec{#1}\par}
```

¹EDNOTE: document above

²EDNOTE: document above

3.12.5 Index Markup

`\omdoc@index*` These are the main internal indexing commands – dividing them into four macros is awful, but I did not get list processing running. It makes sure that the modules necessary for interpreting the math in the index entries are loaded. If the `loadmodules` key is given, we import the module we are in otherwise all the currently imported modules. We do not have to require the module files, since the index is at the end of the document. If the `at` key is given, then we use that for sorting in the index.

```

1722 \addmetakey{omdoc@index}{at}
1723 \addmetakey[false]{omdoc@index}{loadmodules}[true]
1724 \newcommand\omdoc@indexi[2][\ifindex%
1725 \metasetkeys{omdoc@index}{#1}%
1726 \@bsphack\begingroup\@sanitize%
1727 \protected@write\@indexfile{}\string\indexentry%
1728 {\ifx\omdoc@index@at\@empty\else\omdoc@index@at @\fi%
1729 \ifx\omdoc@index@loadmodules\@true%
1730 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#2}%
1731 \else #2\fi% loadmodules
1732 }\the page}}%
1733 \endgroup\@esphack\fi}%ifindex
1734 \newcommand\omdoc@indexii[3][\ifindex%
1735 \metasetkeys{omdoc@index}{#1}%
1736 \@bsphack\begingroup\@sanitize%
1737 \protected@write\@indexfile{}\string\indexentry%
1738 {\ifx\omdoc@index@at\@empty\else\omdoc@index@at @\fi%
1739 \ifx\omdoc@index@loadmodules\@true%
1740 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#2}!%
1741 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#3}!%
1742 \else #2!#3\fi% loadmodules
1743 }\the page}}%
1744 \endgroup\@esphack\fi}%ifindex
1745 \newcommand\omdoc@indexiii[4][\ifindex%
1746 \metasetkeys{omdoc@index}{#1}%
1747 \@bsphack\begingroup\@sanitize%
1748 \protected@write\@indexfile{}\string\indexentry%
1749 {\ifx\omdoc@index@at\@empty\else\omdoc@index@at @\fi%
1750 \ifx\omdoc@index@loadmodules\@true%
1751 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#2}!%
1752 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#3}!%
1753 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#4}%
1754 \else #2!#3!#4\fi% loadmodules
1755 }\the page}}%
1756 \endgroup\@esphack\fi}%ifindex
1757 \newcommand\omdoc@indexiv[5][\ifindex%
1758 \metasetkeys{omdoc@index}{#1}%
1759 \@bsphack\begingroup\@sanitize%
1760 \protected@write\@indexfile{}\string\indexentry%
1761 {\ifx\omdoc@index@at\@empty\else\omdoc@index@at @\fi%

```

```

1762 \ifx\omdoc@index@loadmodules \@true%
1763 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#2}!%
1764 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#3}!%
1765 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#4}%
1766 \string\withusedmodules{\@ifundefined{module@id}\used@modules\module@id}{#5}%
1767 \else #2!#3!#4!#5\fi% loadmodules
1768 }\the page}}%
1769 \endgroup\@esphack\fi}%ifindex

```

Now, we make two interface macros that make use of this:

`*indi*`

```

1770 \newcommand\aindi[3] []{{#2}\omdoc@indexi[#1]{#3}}
1771 \newcommand\indi[2] []{{#2}\omdoc@indexi[#1]{#2}}
1772 \newcommand\indis[2] []{{#2}\omdoc@indexi[#1]{#2s}}
1773 \newcommand\Indi[2] []{{\captitalize{#2}}\omdoc@indexi[#1]{#2}}
1774 \newcommand\Indis[2] []{{\capitalize{#2}}\omdoc@indexi[#1]{#2s}}
1775
1776 \newcommand\@indii[3] []{\omdoc@indexii[#1]{#2}{#3}\omdoc@indexii[#1]{#3}{#2}}
1777 \newcommand\aindii[4] []{{#2}\@indii[#1]{#3}{#4}}
1778 \newcommand\indii[3] []{{#2 #3}\@indii[#1]{#2}{#3}}
1779 \newcommand\indiis[3] []{{#2 #3s}\@indii[#1]{#2}{#3}}
1780 \newcommand\Indii[3] []{{\captitalize{#2 #3}}\@indii[#1]{#2}{#3}}
1781 \newcommand\Indiis[3] []{{\capitalize{#2 #3}}\@indii[#1]{#2}{#3}}
1782
1783 \newcommand\@indiii[4] []{\omdoc@indexiii[#1]{#2}{#3}{#4}\omdoc@indexiii[#1]{#3}{#2 (#4)}}
1784 \newcommand\aindiii[5] []{{#2}\@indiii[#1]{#3}{#4}{#5}}
1785 \newcommand\indiii[4] []{{#2 #3 #4}\@indiii[#1]{#2}{#3}{#4}}
1786 \newcommand\indiis[4] []{{#2 #3 #4s}\@indiii[#1]{#2}{#3}{#4}}
1787 \newcommand\Indiii[4] []{{\captitalize{#2 #3 #4}}\@indiii[#1]{#2}{#3}{#4}}
1788 \newcommand\Indiis[4] []{{\capitalize{#2 #3 #4s}}\@indiii[#1]{#2}{#3}{#4}}
1789
1790 \newcommand\@indiv[5] []{\omdoc@indexiv[#1]{#2}{#3}{#4}{#5}}
1791 \newcommand\aindiv[6] []{{#2}\@indiv[#1]{#3}{#4}{#5}{#6}}
1792 \newcommand\indiv[5] []{{#2 #3 #4 #5}\@indiv[#1]{#2}{#3}{#4}{#5}}
1793 \newcommand\indivs[5] []{{#2 #3 #4 #5s}\@indiv[#1]{#2}{#3}{#4}{#5}}
1794 \newcommand\Indiv[5] []{{\capitalize{#2 #3 #4 #5s}}\@indiv[#1]{#2}{#3}{#4}{#5}}
1795 \newcommand\Indivs[5] []{{\capitalize{#2 #3 #4 #5s}}\@indiv[#1]{#2}{#3}{#4}{#5}}

```

3.12.6 Miscellaneous

Some shortcuts that use math symbols but are not mathematical at all; in particular, they should not be translated by L^AT_EX_ML.

```

1796 \newcommand\hateq{\ensuremath{\widehat{=}}\xspace}
1797 \newcommand\hatequiv{\ensuremath{\widehat{\equiv}}\xspace}
1798 \@ifundefined{ergo}%
1799 {\newcommand\ergo{\ensuremath{\leadsto}\xspace}}%
1800 {\renewcommand\ergo{\ensuremath{\leadsto}\xspace}}%
1801 \newcommand{\reflect@squig}[2]{\reflectbox{$\m@th#1\rightsquigarrow$}}%

```

```

1802 \newcommand\ogre{\ensuremath{\mathrel{\mathpalette\reflect@squig\relax}}\xspace}%
1803 \newcommand\notergo{\ensuremath{\not\leadsto}}
1804 \newcommand\notogre{\ensuremath{\not\mathrel{\mathpalette\reflect@squig\relax}}\xspace}%

```

3.12.7 Deprecated Functionality

In this section we centralize old interfaces that are only partially supported any more.

`*def*`

```

1805 \newcommand\indextoo[2] [] {\indi[#1]{#2}}%
1806 \PackageWarning{omtext}{\protect\indextoo\space is deprecated, use \protect\indi\space instead}%
1807 \newcommand\indexalt[2] [] {\aindi[#1]{#2}}%
1808 \PackageWarning{omtext}{\protect\indextoo\space is deprecated, use \protect\aindi\space instead}%
1809 \newcommand\twintoo[3] [] {\indii[#1]{#2}{#3}}%
1810 \PackageWarning{omtext}{\protect\twintoo\space is deprecated, use \protect\indii\space instead}%
1811 \newcommand\twinalt[3] [] {\aindii[#1]{#2}{#3}}%
1812 \PackageWarning{omtext}{\protect\twinalt\space is deprecated, use \protect\aindii\space instead}%
1813 \newcommand\atwintoo[4] [] {\indiii[#1]{#2}{#3}{#4}}%
1814 \PackageWarning{omtext}{\protect\atwintoo\space is deprecated, use \protect\indiii\space instead}%
1815 \newcommand\atwinalt[4] [] {\aindii[#1]{#2}{#3}{#4}}%
1816 \PackageWarning{omtext}{\protect\atwinalt\space is deprecated, use \protect\aindiii\space instead}%
1817 \</package>

```

`\my*graphics`

```

1818 \newcommand\mygraphics[2] [] {\includegraphics[#1]{#2}}%
1819 \PackageWarning{omtext}{\protect\mygraphics\space is deprecated, use \protect\includegraphics}%
1820 \newcommand\mycgraphics[2] [] {\begin{center}\mygraphics[#1]{#2}\end{center}}%
1821 \PackageWarning{omtext}{\protect\mycgraphics\space is deprecated, use \protect\includegraphics}%
1822 \newcommand\mybgraphics[2] [] {\fbox{\mygraphics[#1]{#2}}}%
1823 \PackageWarning{omtext}{\protect\mybgraphics\space is deprecated, use \protect\includegraphics}%
1824 \newcommand\mycbgraphics[2] [] {\begin{center}\fbox{\mygraphics[#1]{#2}}\end{center}}%
1825 \PackageWarning{omtext}{\protect\mycbgraphics\space is deprecated, use \protect\includegraphics}%

```

4 Things to deprecate

Module options:

```

1826 \addmetakey*{module}{id} % TODO: deprecate properly
1827 \addmetakey*{module}{load}
1828 \addmetakey*{module}{path}
1829 \addmetakey*{module}{dir}
1830 \addmetakey*{module}{align}[WithTheModuleOfTheSameName]
1831 \addmetakey*{module}{noalign}[true]
1832
1833 \newif\if@insymdef@%insymdef@false

```

`symdef:keys` The optional argument `local` specifies the scope of the function to be defined. If `local` is not present as an optional argument then `\symdef` assumes the scope of

the function is global and it will include it in the pool of macros of the current module. Otherwise, if local is present then the function will be defined only locally and it will not be added to the current module (i.e. we cannot inherit a local function). Note, the optional key local does not need a value: we write `\symdef[local]{somefunction}[0]{some expansion}`. The other keys are not used in the L^AT_EX part.

```

1834 %\srefaddidkey{symdef}% what does this do?
1835 \define@key{symdef}{local}[true]{\@symdeflocaltrue}%
1836 \define@key{symdef}{noverb}[all]{}%
1837 \define@key{symdef}{align}[WithTheSymbolOfTheSameName]{}%
1838 \define@key{symdef}{specializes}{}%
1839 \addmetakey*{symdef}{noalign}[true]
1840 \define@key{symdef}{primary}[true]{}%
1841 \define@key{symdef}{assocarg}{}%
1842 \define@key{symdef}{bvars}{}%
1843 \define@key{symdef}{bargs}{}%
1844 \addmetakey{symdef}{lang}%
1845 \addmetakey{symdef}{prec}%
1846 \addmetakey{symdef}{arity}%
1847 \addmetakey{symdef}{variant}%
1848 \addmetakey{symdef}{ns}%
1849 \addmetakey{symdef}{args}%
1850 \addmetakey{symdef}{name}%
1851 \addmetakey*{symdef}{title}%
1852 \addmetakey*{symdef}{description}%
1853 \addmetakey{symdef}{subject}%
1854 \addmetakey*{symdef}{display}%
1855 \addmetakey*{symdef}{gfc}%

```

EdN:3

3

`\symdef` The the `\symdef`, and `\@symdef` macros just handle optional arguments.

```

1856 \def\symdef{\@ifnextchar[{\@symdef}{\@symdef[]}}%
1857 \def\@symdef[#1]#2{\@ifnextchar[{\@@symdef[#1]{#2}}{\@@symdef[#1]{#2}[0]}}%

```

`\@@symdef` now comes the real meat: the `\@@symdef` macro does two things, it adds the macro definition to the macro definition pool of the current module and also provides it.

```

1858 \def\@@symdef[#1]#2[#3]{%
1859   \@insymdef@true%
1860   \metasetkeys{symdef}{#1}%
1861   \edef\symdef@tmp@optpars{\ifcsvoid{symdef@name}{[]}{[name=\symdef@name]}}%
1862   \expandafter\symdecl\symdef@tmp@optpars{#2}%
1863   \@insymdef@false%
1864   \notation[#1]{#2}[#3]%
1865 }% mod@show
1866 \def\symdef@type{Symbol}%
1867 \providecommand{\stDMemph}[1]{\textbf{#1}}

```

³EDNOTE: MK@MK: we need to document the binder keys above.

`\symvariant` `\symvariant{<sym>}[<args>]{<var>}{<cseq>}` just extends the internal macro `\modules@<sym>@pres@` defined by `\symdef{<sym>}[<args>]{...}` with a variant `\modules@<sym>@pres@<var>` which expands to `<cseq>`. Recall that this is called by the macro `\<sym>[<var>]` induced by the `\symdef`.

```

1868 \def\symvariant#1{%
1869   \ifnextchar[{\@symvariant{#1}}{\@symvariant{#1}[0]}%
1870   }%
1871 \def\@symvariant#1[#2]#3#4{%
1872   \notation[#3]{#1}[#2]{#4}%
1873 \ignorespacesandpars}%

```

`\abbrdef` The `\abbrdef` macro is a variant of `\symdef` that does the same on the L^AT_EX level.

```

1874 \let\abbrdef\symdef%

```

`\@sym*` has a starred form for primary symbols. The key/value interface has no effect on the L^AT_EX side. We read the to check whether only allowed ones are used.

```

1875 \newif\if@importing\@importingfalse
1876 \define@key{symi}{noverb}[all]{}%
1877 \define@key{symi}{align}[WithTheSymbolOfTheSameName]{}%
1878 \define@key{symi}{specializes}{}%
1879 \define@key{symi}{gfc}{}%
1880 \define@key{symi}{noalign}[true]{}%
1881 \newcommand\symi{\@ifstar\@symi@star\@symi}
1882 \newcommand\@symi[2][]{\metasetkeys{symi}{#1}%
1883   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2}\fi\ignorespaces}
1884 \newcommand\@symi@star[2][]{\metasetkeys{symi}{#1}%
1885   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2}\fi\ignorespaces}
1886 \newcommand\symii{\@ifstar\@symii@star\@symii}
1887 \newcommand\@symii[3][]{\metasetkeys{symi}{#1}%
1888   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2-#3}\fi\ignorespaces}
1889 \newcommand\@symii@star[3][]{\metasetkeys{symi}{#1}%
1890   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2-#3}\fi\ignorespaces}
1891 \newcommand\symiii{\@ifstar\@symiii@star\@symiii}
1892 \newcommand\@symiii[4][]{\metasetkeys{symi}{#1}%
1893   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2-#3-#4}\fi\ignorespaces}
1894 \newcommand\@symiii@star[4][]{\metasetkeys{symi}{#1}%
1895   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2-#3-#4}\fi\ignorespaces}
1896 \newcommand\symiv{\@ifstar\@symiv@star\@symiv}
1897 \newcommand\@symiv[5][]{\metasetkeys{symi}{#1}%
1898   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2-#3-#4-#5}\fi\ignorespaces}
1899 \newcommand\@symiv@star[5][]{\metasetkeys{symi}{#1}%
1900   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2-#3-#4-#5}\fi\ignorespaces}

```

`\importmhmodule` The `\importmhmodule[<key=value list>]{module}` saves the current value of `\mh@currentrepos` in a local macro `\mh@@repos`, resets `\mh@currentrepos` to the new value if one is given in the optional argument, and after importing resets `\mh@currentrepos` to the old value in `\mh@@repos`. We do all the `\ifx` compar-

ison with an `\expandafter`, since the values may be passed on from other key bindings. Parameters will be passed to `\importmodule`.

```

1901 %\srefaddidkey{importmhmodule}%
1902 \addmetakey{importmhmodule}{mhrepos}%
1903 \addmetakey{importmhmodule}{path}%
1904 \addmetakey{importmhmodule}{ext}% why does this exist?
1905 \addmetakey{importmhmodule}{dir}%
1906 \addmetakey[false]{importmhmodule}{conservative}[true]%
1907 \newcommand\importmhmodule[2][]{%
1908   \parsemodule@maybesetcodes
1909   \metasetkeys{importmhmodule}{#1}%
1910   \ifx\importmhmodule@dir\empty%
1911     \edef\@path{\importmhmodule@path}%
1912   \else\edef\@path{\importmhmodule@dir/#2}\fi%
1913   \ifx\@path\empty% if module name is not set
1914     \@importmodule[]{#2}{export}%
1915   \else%
1916     \edef\mh@@repos{\mh@currentrepos}% remember so that we can reset it.
1917     \ifx\importmhmodule@mhrepos\empty% if in the same repos
1918       \relax% no need to change mh@currentrepos, i.e., current directory.
1919     \else%
1920       \setcurrentreposinfo\importmhmodule@mhrepos% change it.
1921       \addto@thismodule{x}\noexpand\setcurrentreposinfo{\importmhmodule@mhrepos}}%
1922     \fi%
1923     \@importmodule[\MathHub{\mh@currentrepos/source/\@path}]{#2}{export}%
1924     \setcurrentreposinfo\mh@@repos% after importing, reset to old value
1925     \addto@thismodule{x}\noexpand\setcurrentreposinfo{\mh@@repos}}%
1926   \fi%
1927   \ignorespacesandpars%
1928 }

```

`\usemhmodule`

```

1929 \addmetakey{importmhmodule}{load}
1930 \addmetakey{importmhmodule}{id}
1931 \addmetakey{importmhmodule}{dir}
1932 \addmetakey{importmhmodule}{mhrepos}
1933
1934 \addmetakey{importmodule}{load}
1935 \addmetakey{importmodule}{id}
1936
1937 \newcommand\usemhmodule[2][]{%
1938   \metasetkeys{importmhmodule}{#1}%
1939   \ifx\importmhmodule@dir\empty%
1940     \edef\@path{\importmhmodule@path}%
1941   \else\edef\@path{\importmhmodule@dir/#2}\fi%
1942   \ifx\@path\empty%
1943     \usemodule[id=\importmhmodule@id]{#2}%
1944   \else%
1945     \edef\mh@@repos{\mh@currentrepos}%

```

```

1946 \ifx\importmhmodule@mhrepos\@empty%
1947 \else\setcurrentreposinfo{\importmhmodule@mhrepos}\fi%
1948 \usemodule{\@path\@QuestionMark#2}%
1949 %\usemodule[load=MathHub{\mh@currentrepos/source/\@path},
1950 %                                id=\importmhmodule@id]{#2}%
1951 \setcurrentreposinfo\mh@trepos%
1952 \fi%
1953 \ignorespacesandpars}

\mhinputref
1954 \newcommand\mhinputref[2][]{%
1955   \edef\mhinputref@first{#1}%
1956   \ifx\mhinputref@first\@empty%
1957     \inputref{#2}%
1958   \else%
1959     \inputref[mhrepos=\mhinputref@first]{#2}%
1960   \fi%
1961 }

\trefi*
1962 \newcommand\trefi[2][]{%
1963   \edef\trefi@mod{#1}%
1964   \ifx\trefi@mod\@empty\tref{#2}\else\tref{#1\@QuestionMark#2}\fi%
1965 }
1966 \newcommand\trefii[3][]{%
1967   \edef\trefi@mod{#1}%
1968   \ifx\trefi@mod\@empty\tref{#2-#3}\else\tref{#1\@QuestionMark#2-#3}\fi%
1969 }

\defi*
1970 \def\defii#1#2{\defi{#1!#2}}
1971 \def\Defii#1#2{\Defi{#1!#2}}
1972 \def\defiis#1#2{\defis{#1!#2}}
1973 \def\Defiis#1#2{\Defis{#1!#2}}
1974 \def\defiii#1#2#3{\defi{#1!#2!#3}}
1975 \def\Defiii#1#2#3{\Defi{#1!#2!#3}}
1976 \def\defiiis#1#2#3{\defis{#1!#2!#3}}
1977 \def\Defiiis#1#2#3{\Defis{#1!#2!#3}}
1978 \def\defiv#1#2#3#4{\defi{#1!#2!#3!#4}}
1979 \def\Defiv#1#2#3#4{\Defi{#1!#2!#3!#4}}
1980 \def\defivs#1#2#3#4{\defis{#1!#2!#3!#4}}
1981 \def\Defivs#1#2#3#4{\Defis{#1!#2!#3!#4}}

```