

Slides and Course Notes for Jacobs University*

Michael Kohlhasse
Jacobs University, Bremen
<http://kwarc.info/kohlhasse>

November 10, 2015

Abstract

We present a document class from which we can generate both course slides and course notes in a transparent way. Furthermore, we present a set of L^AT_EX XML bindings for these, so that we can also generate OMDoc-based course materials, e.g. for inclusion in the ACTIVEMATH system.

Contents

1	Introduction	2
2	The User Interface	2
2.1	Package Options	2
2.2	Notes and Slides	2
2.3	Header and Footer Lines	3
2.4	Colors and Highlighting	3
2.5	Front Matter, Titles, etc	3
2.6	Miscellaneous	3
3	Limitations	3
4	The Implementation	4
4.1	Class and Package Options	4
4.2	Notes and Slides	6
4.3	Header and Footer Lines	9
4.4	Colors and Highlighting	10
4.5	Front Matter, Titles, etc	11
4.6	Sectioning	12
4.7	Miscellaneous	13
4.8	Finale	15

*Version ? (last revised ?)

1 Introduction

This Document class is derived from `beamer.cls` [Tana], specializes it with Jacobs stuff and adds a notes version that is more suited to printing than the one supplied by `beamer.cls`.

2 The User Interface

The `mikoslides` class takes the notion of a slide frame from Till Tantau's excellent `beamer` class and adapts its notion of frames for use in the \LaTeX and OMDoc. To support semantic course notes, it extends the notion of mixing frames and explanatory text, but rather than treating the frames as images (or integrating their contents into the flowing text), the `mikoslides` package displays the slides as such in the course notes to give students a visual anchor into the slide presentation in the course (and to distinguish the different writing styles in slides and course notes).

In practice we want to generate two documents from the same source: the slides for presentation in the lecture and the course notes as a narrative document for home study. To achieve this, the `mikoslides` class has two modes: *slides mode* and *notes mode* which are determined by the package option.

2.1 Package Options

The `mikoslides` class takes a variety of class options:¹

- `slides` • The options `slidesnd` and `notesnotes` switch between slides mode and notes mode (see Section 2.2).
- `a` • If the option `sectocframes` is given, then special frames with section table of contents are produced headers²
- `sectocframes` • `showmeta`. If this is set, then the metadata keys are shown (see [Koh15] for details and customization options).
- `showmeta` • If the option `frameimages` is set, then slide mode also shows the `\frameimage`-generated frames.
- `frameimages`

2.2 Notes and Slides

`frame` Slides are represented with the `frame` just like in the `beamer` class, see [Tanb] for details. The `mikoslides` class adds the `note` environment for encapsulating the course note fragments.¹

 Note that it is essential to start and end the `notes` environment at the start of the line – in particular, there may not be leading blanks – else \LaTeX becomes confused and throws error messages that are difficult to decipher.

¹EDNOTE: leaving out `noproblems` for the moment until we decide what to do with it.

²EDNOTE: document the functionality

¹MK: it would be very nice, if we did not need this environment, and this should be possible in principle, but not without intensive \LaTeX trickery. Hints to the author are welcome.

```

\begin{note}
  We start this course with ...
\end{note}

\begin{frame}
  \frametitle{The first slide}
  ...
\end{frame}
\begin{note}
  ... and more explanatory text
\end{note}

\begin{frame}
  \frametitle{The second slide}
  ...
\end{frame}
...

```

Example 1: A typical Course Notes File

By interleaving the `frame` and `note` environments, we can build course notes as shown in Figure 1.

Sometimes, we want to integrate slides as images after all – e.g. because we already have a PowerPoint presentation, to which we want to add `STEXnotes`. In this case we can use `\frameimage[⟨opt⟩]{⟨path⟩}`, where `⟨opt⟩` are the options of `\includegraphics` from the `graphicx` package [CR99] and `⟨path⟩` is the file path (extension can be left off like in `\includegraphics`).

`\frameimage`

2.3 Header and Footer Lines

2.4 Colors and Highlighting

`\textwarning` The `\textwarning` macro generates a warning sign: 

2.5 Front Matter, Titles, etc

2.6 Miscellaneous

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `STEXGitHub` repository [sTeX].

1. when option `book` which uses `\pagestyle{headings}` is given and semantic macros are given in the `omgroup` titles, then they sometimes are not defined

by the time the heading is formatted. Need to look into how the headings are made. This is a problem of the underlying `omdoc` package.

4 The Implementation

The `mikoslides` package generates two files: the \LaTeX package (all the code between `\package` and `\endpackage`) and the \LaTeX XML bindings (between `\ltxml` and `\endltxml`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

The general preamble for \LaTeX XML:

```
1 \ltxml.cls | ltxml.sty
2 # -*- PERL -*-
3 package LaTeXML::Package::Pool;
4 use strict;
5 use LaTeXML::Package;
6 \endltxml.cls | ltxml.sty
```

4.1 Class and Package Options

We define some Package Options and switches for the `mikoslides` class and activate them by passing them on to `beamer.cls` and `omdoc.cls` and the `mikoslides` package.

```
7 \cls
8 \newif\ifnotes\notesfalse
9 \DeclareOption{notes}{\notetrue\PassOptionsToPackage{\CurrentOption}{mikoslides}}
10 \DeclareOption{slides}{\notetrue\PassOptionsToPackage{\CurrentOption}{mikoslides}}
11 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{omdoc}
12                                     \PassOptionsToClass{\CurrentOption}{beamer}
13                                     \PassOptionsToPackage{\CurrentOption}{mikoslides}}
14 \ProcessOptions
15 \endcls
16 \ltxml.cls
17 \DeclareOption{notes}{\sub{PassOptions('mikoslides','sty',ToString(Digest(T_CS('\CurrentOption'))))}}
18 \DeclareOption{slides}{\sub{PassOptions('mikoslides','sty',ToString(Digest(T_CS('\CurrentOption'))))}}
19 \DeclareOption(undef){\sub{PassOptions('omdoc','cls',ToString(Digest(T_CS('\CurrentOption'))))}};
20                                     PassOptions('mikoslides','sty',ToString(Digest(T_CS('\CurrentOption'))))}}
21                                     PassOptions('beamer','cls',ToString(Digest(T_CS('\CurrentOption'))))}}
22 \ProcessOptions();
23 \endltxml.cls
```

now we do the same for the `mikoslides` package. Note that we also have to define the same switches³, since we might use `mikoslides.sty` in a different class.

```
24 \package
25 \newif\ifnotes\notesfalse
26 \DeclareOption{notes}{\notetrue}
```

³EdNOTE: MK: we may think about making all of them internal

```

27 \DeclareOption{slides}{\notesfalse}
28 \newif\ifsectocframes\sectocframesfalse
29 \DeclareOption{sectocframes}{\sectocframestrue}
30 \newif\ifframeimages\frameimagesfalse
31 \DeclareOption{frameimages}{\frameimagestrue}
32 \newif\if@part\@partfalse
33 \DeclareOption{report}{\@parttrue\PassOptionsToPackage{\CurrentOption}{omdoc}}
34 \DeclareOption{book}{\@parttrue\PassOptionsToPackage{\CurrentOption}{omdoc}}
35 \newif\ifproblems\problemsfalse
36 \DeclareOption{noproblems}{\problemsfalse}
37 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{stex}
38                               \PassOptionsToPackage{\CurrentOption}{tikzinput}}
39 \ProcessOptions
40 \</package>
41 \<*txml.sty>
42 \DeclareOption('notes', '');
43 \DeclareOption('slides', '');
44 \DeclareOption('noproblems', '');
45 \DeclareOption('sectocframes', '');
46 \DeclareOption('frameimages', '');
47 \DeclareOption(undef, sub {PassOptions('stex','sty',ToString(Digest(T_CS('CurrentOption'))));
48                               PassOptions('tikzinput','sty',ToString(Digest(T_CS('
49 ProcessOptions();
50 \RawTeX('\newif\ifnotes\notesfalse');
51 \RawTeX('\newif\ifproblems\problemsfalse');
52 \</txml.sty>

```

Depending on the options, we either load the `article`-based `omdoc` or the `beamer` class. In the first case, we also have to make the `beamer`-specific things available to `article` via the `beamerarticle` package. We use options to avoid loading theorem-like environments, since we want to use our own from the `STEX` packages.

```

53 \<*cls>
54 \ifnotes
55   \LoadClass{omdoc}
56   \RequirePackage{a4wide}
57   \RequirePackage{marginnote}
58   \RequirePackage{mdframed}
59   \RequirePackage[notheorems,noamsthm,noxcolor]{beamerarticle}
60 \else
61   \LoadClass[notheorems,noamsthm,10pt]{beamer}
62   \newcounter{Item}
63   \newcounter{paragraph}
64   \newcounter{subparagraph}
65   \newcounter{Hfootnote}
66   \usetheme{Jacobs}
67 \fi
68 \RequirePackage{mikoslides-mh}
69 \</cls>
70 \<*txml.cls>

```

```

71 LoadClass('omdoc');
72 RequirePackage('mikoslides-mh');
73 DefConstructor('\usetheme{','}');
74 </ltxml.cls>
    now, we load the remaining packages for both versions.

75 <*package>
76 \RequirePackage{stex}
77 \RequirePackage{smglom}
78 \RequirePackage{tikzinput}
79 \RequirePackage{latexml}
80 \RequirePackage{amssymb}
81 \RequirePackage{amsmath}
82 \RequirePackage{comment}
83 \RequirePackage{textcomp}
84 \RequirePackage{url}
85 </package>
86 <*ltxml.sty>
87 RequirePackage('stex');
88 RequirePackage('smglom');
89 RequirePackage('tikzinput', options => ['image']);
90 RequirePackage('latexml');
91 RequirePackage('amssymb');
92 RequirePackage('amsmath');
93 RequirePackage('graphicx');
94 RequirePackage('url');
95 </ltxml.sty>

```

4.2 Notes and Slides

We define the sizes of slides in the notes. Somehow, we cannot get by with the same here.

```

96 <*package>
97 \newcounter{slide}
98 \newlength{\slidewidth}\setlength{\slidewidth}{12.8cm}
99 \newlength{\slideheight}\setlength{\slideheight}{9cm}
100 </package>
101 <*ltxml.sty>
102 DefRegister('\slidewidth'      => Dimension('13.6cm'));
103 DefRegister('\slideheight'    => Dimension('9cm'));
104 </ltxml.sty>

```

note The `note` environment is used to leave out text in the `slides` mode. It does not have a counterpart in OMDoc. So for course notes, we define the `note` environment to be a no-operation otherwise we declare the `note` environment as a comment via the `comment` package.

```

105 <*package>
106 \ifnotes%
107 \renewenvironment{note}{\ignorespaces}{}%

```

```

108 \else%
109   \excludecomment{note}%
110 \fi%
111 \</package>
112 \<!txml.sty>
113 DefEnvironment('note','body');
114 \</txml.sty>

```

We start by giving the L^AT_EX_ML binding for the `frame` environment from the `beamer` class. We first set up the slide boxes in `article` mode. We set up sizes and provide a box register for the frames and a counter for the slides.

```

115 \<*package>
116 \ifnotes
117   \newlength{\slideframewidth}
118   \setlength{\slideframewidth}{1.5pt}

```

frame We first define the keys.

```

119   \addmetakey{frame}{label}
120   \addmetakey[yes]{frame}{allowframebreaks}
121   \addmetakey{frame}{allowdisplaybreaks}
122   \addmetakey[yes]{frame}{fragile}
123   \addmetakey[yes]{frame}{shrink}
124   \addmetakey[yes]{frame}{squeeze}

```

We redefine the `itemize` environment so that it looks more like the one in `beamer` with `Jacobs` theme. We create the box with the `mdframed` environment from the `equinymous` package. Then we define the environment, read them, and construct the slide number and label.

```

125   \renewenvironment{frame}[1][\%
126     \metasetkeys{frame}{#1}%
127     \stepcounter{slide}%
128     \def\@currentlabel{\theslide}%
129     \ifx\frame@label\@empty%
130     \else%
131       \label{\frame@label}%
132     \fi%

```

We redefine the `itemize` environment so that it looks more like the one in `beamer` with `Jacobs` theme.

```

133   \def\itemize@level{outer}%
134   \def\itemize@outer{outer}%
135   \def\itemize@inner{inner}%
136   \renewcommand\newpage{}%
137   \renewcommand\metakeys@show@keys[2]{\marginnote{\scriptsize ##2}}%
138   \renewenvironment{itemize}{%
139     \ifx\itemize@level\itemize@outer%
140       \def\itemize@label{\$ \rhd$}%
141     \fi%
142     \ifx\itemize@level\itemize@inner%
143       \def\itemize@label{\$ \scriptstyle \rhd$}%

```

```

144     \fi%
145     \begin{list}%
146     {\itemize@label}%
147     {\setlength{\labelsep}{.3em}%
148     \setlength{\labelwidth}{.5em}%
149     \setlength{\leftmargin}{1.5em}%
150     }%
151     \edef\itemize@level{\itemize@inner}%
152     }{%
153     \end{list}%
154     }%

```

We create the box with the `mdframed` environment from the `equinymous` package.

```

155     \begin{mdframed}[linewidth=\slideframewidth,skipabove=1ex,skipbelow=1ex,userdefinedwidth=\s
156     ]{%
157     \medskip\miko@slidelabel\end{mdframed}%
158     }%
159 \end{package}
160 \end{*xml.sty}
161 DefEnvironment('frame'[],
162     "<omdoc:omgroup layout='slide'>"
163     . "#body\n"
164     . "</omdoc:omgroup>\n\n",
165     afterDigestBegin=>sub {
166         $_[1]->setProperty(theory=>LookupValue('current_module')); });
167 \end{*xml.sty}#

```

Now, we need to redefine the `frametitle` (we are still in course notes mode).

```

\frametitle
168 \end{*package}
169 \renewcommand{\frametitle}[1]{\Large\bf\sf\color{blue}{#1}}\medskip}%
170 \fi %ifnotes
171 \end{package}
172 \end{*xml.sty}
173 DefConstructor('\frametitle{',
174     "\n<omdoc:metadata><dc:title>#1</dc:title></omdoc:metadata>");
175 \end{*xml.sty}

```

`\frameimage` We have to make sure that the width is overwritten, for that we check the `\Gin@ewidth` macro from the `graphicx` package⁴

```

176 \end{*package}
177 \newrobustcmd\frameimage[2][{}]{%
178     \stepcounter{slide}%
179     \ifframeimages%
180         \def\Gin@ewidth{\setkeys{Gin}{#1}}%
181         \ifnotes%
182         \else%

```

⁴EdNOTE: MK@DG; we need to do that in the LaTeXXML binding as well!


```

183     \vfill%
184     \fi%
185     \ifx\Gin@ewidth\@empty%
186         \mycgraphics[width=\slidewidth,#1]{#2}\else\mycgraphics[#1]{#2}%
187     \fi%
188     \par\strut\hfill{\footnotesize Slide \arabic{slide}}%
189     \ifnotes%
190     \else%
191         \vfill%
192     \fi%
193 \fi%
194 }% ifframeimages
195 \</package>
196 \<!xml.sty>
197 DefMacro('frameimage[]{}','\@frameimage{\includegraphics[#1,width=\slidewidth]{#2}}');
198 DefConstructor('\@frameimage{}','<omdoc:omgroup layout='slide'>#1</omdoc:omgroup>\n");
199 \</!xml.sty>

```

4.3 Header and Footer Lines

Now, we set up the infrastructure for the footer line of the slides, we use boxes for the logos, so that they are only loaded once, that considerably speeds up processing.

```

\setslidelogo The default logo is the logo of Jacobs University. Customization can be done by
\setslidelogo{<logo name>}.
200 \<*package>
201 \newlength{\slidelogoheight}
202 \ifnotes%
203     \setlength{\slidelogoheight}{.4cm}%
204 \else%
205     \setlength{\slidelogoheight}{1cm}%
206 \fi%
207 \newsavebox{\slidelogo}%
208 \sbox{\slidelogo}{\includegraphics[height=\slidelogoheight]{jacobs-logo}}%
209 \newrobustcmd{\setslidelogo}[1]{%
210     \sbox{\slidelogo}{\includegraphics[height=\slidelogoheight]{#1}}%
211 }%

\setsource \source stores the writer's name. By default it is Michael Kohlhase since he is
the main user and designer of this package. \setsource{<name>} can change the
writer's name.
212 \def\source{Michael Kohlhase}% customize locally
213 \newrobustcmd{\setsource}[1]{\def\source{#1}}%

\setlicensing Now, we set up the copyright and licensing. By default we use the Creative
Commons Attribution-ShareAlike license to strengthen the public domain. If
package hyperref is loaded, then we can attach a hyperlink to the license logo.

```

`\setlicensing[⟨url⟩]{⟨logo name⟩}` is used for customization, where $\langle url \rangle$ is optional.

```

214 \def\copyrightnotice{\footnotesize\copyright:\hspace{.3ex}{\source}}%
215 \newsavebox{\cclogo}%
216 \sbox{\cclogo}{\includegraphics[height=\slidelogoheight]{cc_somerights}}%
217 \newif\ifcchref\cchreffalse%
218 \AtBeginDocument{%
219   \ifpackageloaded{hyperref}{\cchreftrue}{\cchreffalse}
220 }%
221 \def\licensing{%
222   \ifcchref%
223     \href{http://creativecommons.org/licenses/by-sa/2.5/}{\usebox{\cclogo}}%
224   \else%
225     {\usebox{\cclogo}}%
226   \fi%
227 }%
228 \newrobustcmd{\setlicensing}[2][]{%
229   \def\@url{#1}%
230   \sbox{\cclogo}{\includegraphics[height=\slidelogoheight]{#2}}%
231   \ifx\@url\@empty%
232     \def\licensing{{\usebox{\cclogo}}}%
233   \else%
234     \def\licensing{%
235       \ifcchref%
236         \href{#1}{\usebox{\cclogo}}%
237       \else%
238         {\usebox{\cclogo}}%
239       \fi%
240     }%
241   \fi%
242 }%

```

EdN:5

`\slidelabel` Now, we set up the slide label for the `article` mode.⁵

```

243 \newrobustcmd\miko@slidelabel{%
244   \vbox to \slidelogoheight{%
245     \vss\hbox to \slidewidth%
246       {\licensing\hfill\copyrightnotice\hfill\arabic{slide}\hfill\usebox{\slidelogo}}%
247   }%
248 }%

```

4.4 Colors and Highlighting

Now, we set up an infrastructure for highlighting phrases in slides. Note that we use content-oriented macros for highlighting rather than directly using color markup. The first thing to do is to adapt the green so that it is dark enough for most beamers

```

249 \AtBeginDocument{%

```

⁵EDNOTE: see that we can use the themes for the slides some day. This is all fake.

```

250 \definecolor{green}{rgb}{0,.5,0}%
251 \definecolor{purple}{cmyk}{.3,1,0,.17}%
252 }%

```

We customize the `\defemph`, `\notemph`, and `\stDMemph` macros with colors for the use in the `statements` package. Furthermore we customize the `\@@lec` macro for the appearance of line end comments in `\lec`.

```

253 % \def\STpresent#1{\textcolor{blue}{#1}}
254 \def\defemph#1{\textcolor{magenta}{#1}}
255 \def\notemph#1{\textcolor{magenta}{#1}}
256 \def\stDMemph#1{\textcolor{blue}{#1}}
257 \def\@@lec#1{\textcolor{green}{#1}}
258 </package>
259 <*ltxml.sty>
260 #DefMacro('defemph','\textcolor{magenta}{#1}');
261 #DefMacro('notemph','\textcolor{magenta}{#1}');
262 </ltxml.sty>

```

I like to use the dangerous bend symbol for warnings, so we provide it here.

`\textwarning` as the macro can be used quite often we put it into a box register, so that it is only loaded once.

```

263 <*package>
264 \pgfdeclareimage[width=.9em]{miko@small@dbend}{dangerous-bend}
265 \def\smalltextwarning{%
266   \pgfuseimage{miko@small@dbend}%
267   \xspace%
268 }%
269 \pgfdeclareimage[width=1.5em]{miko@dbend}{dangerous-bend}
270 \newrobustcmd\textwarning{%
271   \raisebox{-.05cm}{\pgfuseimage{miko@dbend}}%
272   \xspace%
273 }%
274 \pgfdeclareimage[width=2.5em]{miko@big@dbend}{dangerous-bend}%
275 \newrobustcmd\bigtextwarning{%
276   \raisebox{-.05cm}{\pgfuseimage{miko@big@dbend}}%
277   \xspace%
278 }%
279 </package>
280 <*ltxml.sty>
281 DefMacro('textwarning','\@textwarning\xspace');
282 DefConstructor('\@textwarning',"");
283 </ltxml.sty>

```

4.5 Front Matter, Titles, etc

We need to redefine the frontmatter macros inherited from the `beamer` class for LaTeXML, since there they take an optional argument.

```

284 <*ltxml.sty>
285 DefMacro('title[]','\@add@frontmatter{ltx:title}{#1}');

```

```

286 DefMacro('date[]{}', '\@add@frontmatter{ltx:date}[role=creation]{#1}');
287 DefMacro('author[]{}', sub { andSplit(T_CS('\@author'),$_[1]); });#$
288 </ltxml.sty>

289 %      Must be first command on slide to make positioning work.
290 <*package>
291 \newrobustcmd\putgraphicsat[3]{%
292   \begin{picture}(0,0)\put(#1){\includegraphics[#2]{#3}}\end{picture}%
293 }%
294 \newrobustcmd\putat[2]{%
295   \begin{picture}(0,0)\put(#1){#2}\end{picture}%
296 }%

```

4.6 Sectioning

If the `sectocframes` option is set, then we make section frames. We first define a set of counters

```

297 \ifsectocframes%
298   \if@part%
299     \newcounter{mpart}%
300     \newcounter{mchapter}%
301     \newcounter{msection}[mchapter]%
302   \else%
303     \newcounter{msection}%
304   \fi%
305   \newcounter{msubsection}[msection]%
306   \newcounter{msubsubsection}[msubsection]%
307   \newcounter{msubsubsubsection}[msubsubsection]%
308 \fi% ifsectocframes

and then

309 \ifnotes\else% only in slides
310   \renewenvironment{omgroup}[2][]{%
311     \metasetkeys{omgroup}{#1}\sref@target%
312     \advance\section@level by 1%
313     \ifsectocframes%
314     \begin{frame}%
315     \vfill\Large\centering%
316     \red{%
317       \ifcase\section@level\or%
318         \stepcounter{mpart}Part \Roman{mpart}\or%
319         \stepcounter{mchapter}Chapter \arabic{mchapter}\or
320         \stepcounter{msection}\if@part\arabic{mchapter}.\fi\arabic{msection}\or
321         \stepcounter{msubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msubsec
322         \stepcounter{msubsubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msub
323         \stepcounter{msubsubsubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{m
324       \fi% end ifcase
325       \quad #2%
326     }%
327     \vfill%

```

```

328     \end{frame}%
329     \fi %ifsectocframes
330 }
331 {\advance\section@level by -1}%
332 \fi% ifnotes
333 \</package>

```

4.7 Miscellaneous

The following fixes an error I do not understand, this has something to do with beamer compatibility, which has similar definitions but only up to 1.

```

334 \<*package>
335 \expandafter\def\csname Parent2\endcsname{}
336 %     \begin{macrocode}
337 %
338 % We need to disregard the columns macros introduced by the |beamer| class
339 %     \begin{macrocode}
340 \ifnotes%
341   \renewenvironment{columns}{%
342     \par\noindent%
343     \begin{minipage}%
344       \linewidth\centering\leavevmode%
345   }{%
346     \end{minipage}\par\noindent%
347   }%
348   \newsavebox\columnbox%
349   \renewenvironment{column}[1]{%
350     \begin{lrbox}{\columnbox}\begin{minipage}{#1}%
351   }{%
352     \end{minipage}\end{lrbox}\usebox\columnbox%
353   }%
354 \fi%
355 \</package>
356 \<!xml.sty>
357 DefEnvironment('{columns}','#body');
358 DefEnvironment('{column}{}','#body');

```

We also need to deal with overlay specifications introduced by the `beamer` class.⁶

```

359 DefConstructor('\uncover','#1');
360 #Define a Beamer Overlay Parameter type
361 DefParameterType('BeamerOverlay', sub {
362   my ($gullet) = @_;
363   my $tok = $gullet->readXToken;
364   if (ref $tok && ToString($tok) eq '<') {

```

⁶EDNOTE: this is just to keep latexml quiet, no real functionality here.

⁷EDNOTE: Deyan: We reuse the CMP itemizations defined in the `omdoc.cls` latexml binding, adjusting the parameters to be overlay-sensitive

```

365     $gullet->readUntil(T_OTHER('>'));
366   } else {
367     $gullet->unread($tok) if ref $tok;
368     undef; }},
369     reversion=> sub {
370 (T_OTHER('<'), $_[0]->revert, T_OTHER('>'));
371     });
372
373 #Take the "from" field of the overlay range
374 sub overlayFrom {
375   return "" unless defined $_[0];
376   my $overlay=ToString($_[0]); $overlay =~ /\d+/; $1;}
377
378 #Reuse the CMP itemizations, only adjust the \item constructors.
379 DefMacro('\beamer@group@item[] OptionalBeamerOverlay IfBeginFollows', sub {
380   my($gullet,$tag,$overlay,$needwrapper)=@_;
381   $overlay=$overlay||T_OTHER("");
382   ( T_CS('\group@item@maybe@unwrap'),
383     ($needwrapper ? (Invocation(T_CS('\beamer@group@item@wrap'),$tag,$overlay)->unlist) : ()))
384 DefConstructor('\beamer@group@item@wrap {} OptionalBeamerOverlay',
385   "<omdoc:omtext ?#2(overlay='&overlayFrom(#2)')()>"
386   . "?#1(<dc:title>#1</dc:title>())"
387   . "<omdoc:CMP>",
388   beforeDigest=>sub {
389     Let('\group@item@maybe@unwrap','\group@item@unwrap');
390     $_[0]->bgroup;
391   return; },
392   properties=>sub{ RefStepItemCounter(); });
393 #DefConstructor('\beamer@itemize@item[] OptionalBeamerOverlay',
394 #   "<omdoc:li ?#2(overlay='&overlayFrom(#2)')() >"
395 #   . "?#1(<dc:title>#1</dc:title>())",
396 #   properties=>sub{ RefStepItemCounter(); });
397 DefConstructor('\beamer@enumerate@item[] OptionalBeamerOverlay',
398   "<omdoc:li ?#2(overlay='&overlayFrom(#2)')() >"
399   . "?#1(<dc:title>#1</dc:title>())",
400   properties=>sub{ RefStepItemCounter(); });
401 DefConstructor('\beamer@description@item[] OptionalBeamerOverlay',
402   "<omdoc:di ?#2(overlay='&overlayFrom(#2)')() >"
403   . "?#1(<omdoc:dt>#1</omdoc:dt>())<omdoc:dd>", # trust di and dt to autoclose
404   properties=>sub{ RefStepItemCounter(); });
405 </ltxml.sty>#

```

Now, some things that are imported from the pgf and beamer packages:

```

406 <*ltxml.sty>
407 DefMacro('\putgraphicsat{}{}{}','\mygraphics[#2]{#3}');
408 DefMacro('\putat{}{}','\#2');
409 </ltxml.sty>

410 <*package>
411 \ifproblems%
412   \newenvironment{problems}{}{}%

```

```

413 \else%
414   \excludecomment{problems}%
415 \fi%
416 \</package>
417 \<*ltxml.sty>
418 DefEnvironment('{problems}', '#body');
419 \</ltxml.sty>

```

4.8 Finale

Finally, we set the slide body font to the sans serif, and we terminate the L^AT_EX_ML bindings file with a success mark for perl.

```

420 \<package>\ifnotes\else\sf\fi
421 \<ltxml.sty | ltxml.cls>1;

```

References

- [CR99] David Carlisle and Sebastian Rathz. *The graphicx package*. Part of the T_EX distribution. The Comprehensive T_EX Archive Network. 1999. URL: <https://www.tug.org/texlive/devsrc/Master/texmf-dist/doc/latex/graphics/graphicx.pdf>.
- [Koh15] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/metakeys/metakeys.pdf>.
- [sTeX] *KWARC/sTeX*. URL: <https://svn.kwarc.info/repos/stex> (visited on 05/15/2015).
- [Tana] Till Tantau. *beamer – A L^AT_EX class for producing presentations and slides*. URL: <http://www.ctan.org/pkg/beamer> (visited on 01/07/2014).
- [Tanb] Till Tantau. *User Guide to the Beamer Class*. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/beamer/doc/beameruserguide.pdf>.