

stex-master.sty: \TeX 2.0*

Michael Kohlhase, Dennis Müller
FAU Erlangen-Nürnberg
<http://kwarc.info/>

November 12, 2020

Abstract

TODO

*Version v2.0 (last revised 2020/11/10)

Contents

1	Introduction	3
2	Implementation	3
2.1	sTeX base	3
2.2	Paths and URIs	3
2.3	Modules	14
2.4	Inheritance	18
2.5	Symbols and Notations	26
2.6	sref	37
2.7	smultiling	37
2.8	smglom	38
3	Things to deprecate	38

1 Introduction

TODO

2 Implementation

```
1 <*package>
2 % TODO
3 \newif\if@modules@html@\@modules@html@true
4 \DeclareOption{omdocmode}{\@modules@html@false}
5 % Modules:
6 \newif\ifmod@show\mod@showfalse
7 \DeclareOption{showmods}{\mod@showtrue}
8 % sref:
9 \newif\ifextrefs\extrefsfalse
10 \DeclareOption{extrefs}{\extrefstrue}
11 %
12 \ProcessOptions
13 \RequirePackage{standalone}
14 \RequirePackage{xspace}
15 \RequirePackage{metakeys}
```

2.1 sTeX base

The sTeX logo:

```
16 \protected\def\stex{%
17   \@ifundefined{texorpdfstring}%
18   {\let\texorpdfstring\@firstoftwo}%
19   }%
20   \texorpdfstring{\raisebox{-.5ex}{S}\kern-.5ex\TeX}{sTeX}\xspace%
21 }
22 \def\sTeX{\stex}
    and a conditional for LaTeXML:
23 \newif\if@latexml\@latexmlfalse
```

2.2 Paths and URIs

```
24 \RequirePackage{xstring}
25 \RequirePackage{etoolbox}
```

`\defpath` `\defpath[optional argument]{macro name}{base path}` defines a new macro which can take another path to form one integrated path. For example, `\MathHub` in every `localpaths.tex` is defined as:

```
\defpath{MathHub}{/path/to/localmh/MathHub}
```

then we can use `\MathHub` to form other paths, for example,

```
\MathHub{source/smg1om/sets}
```

will generate /path/to/localmh/MathHub/source/smgglom/sets.

```
26 \newrobustcmd\defpath[3] []{%
27   \expandafter\newcommand\csname #2\endcsname[1]{#3/##1}%
28 }%
```

2.2.1 Path Canonicalization

We define two macros for changing the category codes of common characters in URIs, in particular #.

```
29 \def\pathsuris@setcatcodes{%
30   \edef\pathsuris@oldcatcode@hash{\the\catcode'\#}%
31   \catcode'\#=12\relax%
32   \edef\pathsuris@oldcatcode@slash{\the\catcode'\/%}
33   \catcode'\/=12\relax%
34   \edef\pathsuris@oldcatcode@colon{\the\catcode'\:}%
35   \catcode'\:=12\relax%
36   \edef\pathsuris@oldcatcode@qm{\the\catcode'\?}%
37   \catcode'\?=12\relax%
38 }
39 \def\pathsuris@resetcatcodes{%
40   \catcode'\#\pathsuris@oldcatcode@hash\relax%
41   \catcode'\/>\pathsuris@oldcatcode@slash\relax%
42   \catcode'\:\pathsuris@oldcatcode@colon\relax%
43   \catcode'\?\pathsuris@oldcatcode@qm\relax%
44 }
```

We define some macros for later comparison.

```
45 \def\@ToTop{..}
46 \def\@Slash{/}
47 \def\@Colon{:}
48 \def\@Space{ }
49 \def\@QuestionMark{?}
50 \def\@Dot{.}
51 \catcode'\&=12
52 \def\@Ampersand{&}
53 \catcode'\&=4
54 \pathsuris@setcatcodes
55 \def\@Fragment{#}
56 \pathsuris@resetcatcodes
57 \catcode'\.=0
58 .catcode'\.=12
59 .let.\@BackSlash\
60 .catcode'\.=0
61 \catcode'\.=12
62 \edef\old@percent@catcode{\the\catcode'\%}
63 \catcode'\%=12
64 \let\@Percent%
65 \catcode'\%=\old@percent@catcode
```

`\@cpath` Canonicalizes (file) paths:

```

66 \def\@cpath#1{%
67   \edef\pathsuris@cpath@temp{#1}%
68   \def\@CanPath{}%
69   \IfBeginWith\pathsuris@cpath@temp\@Slash{%
70     \@cpath@loop%
71     \edef\@CanPath{\@Slash\@CanPath}%
72   }{%
73     \IfBeginWith\pathsuris@cpath@temp{\@Dot\@Slash}{%
74       \StrGobbleLeft\pathsuris@cpath@temp2[\pathsuris@cpath@temp]%
75       \@cpath@loop%
76     }{%
77       \ifx\pathsuris@cpath@temp\@Dot\else%
78         \@cpath@loop\fi%
79     }%
80   }%
81   \IfEndWith\@CanPath\@Slash{%
82     \ifx\@CanPath\@Slash\else%
83       \StrGobbleRight\@CanPath1[\@CanPath]%
84     \fi%
85   }{}%
86 }
87
88 \def\@cpath@loop{%
89   \IfSubStr\pathsuris@cpath@temp\@Slash{%
90     \StrCut\pathsuris@cpath@temp\@Slash\pathsuris@cpath@tempa\pathsuris@cpath@temp%
91     \ifx\pathsuris@cpath@tempa\@ToTop%
92       \ifx\@CanPath\@empty%
93         \edef\@CanPath{\@ToTop}%
94       \else%
95         \edef\@CanPath{\@CanPath\@Slash\@ToTop}%
96       \fi%
97       \@cpath@loop%
98     \else%
99       \ifx\pathsuris@cpath@tempa\@Dot%
100         \@cpath@loop%
101       \else%
102         \IfBeginWith\pathsuris@cpath@temp\@ToTop{%
103           \StrBehind{\pathsuris@cpath@temp}{\@ToTop}[\pathsuris@cpath@temp]%
104           \IfBeginWith\pathsuris@cpath@temp\@Slash{%
105             \edef\pathsuris@cpath@temp{\@CanPath\pathsuris@cpath@temp}%
106           }{%
107             \ifx\@CanPath\@empty\else%
108               \edef\pathsuris@cpath@temp{\@CanPath\@Slash\pathsuris@cpath@temp}%
109             \fi%
110           }%
111           \def\@CanPath{}%
112           \@cpath@loop%
113         }{%
114           \ifx\@CanPath\@empty%
115             \edef\@CanPath{\pathsuris@cpath@tempa}%

```

```

116         \else%
117             \edef\@CanPath{\@CanPath\@Slash\pathsuris@cpath@temp@a}%
118         \fi%
119         \@cpath@loop
120     }%
121     \fi\fi%
122 }{
123     \ifx\@CanPath\@empty%
124         \edef\@CanPath{\pathsuris@cpath@temp}%
125     \else%
126         \edef\@CanPath{\@CanPath\@Slash\pathsuris@cpath@temp}%
127     \fi%
128 }%
129 }

```

Test:

path	canonicalized path	expected
aaa	aaa	aaa
../.. /aaa	../.. /aaa	../.. /aaa
aaa/bbb	aaa/bbb	aaa/bbb
aaa/..		
../.. /aaa/bbb	../.. /aaa/bbb	../.. /aaa/bbb
../aaa/.. /bbb	../bbb	../bbb
../aaa/bbb	../aaa/bbb	../aaa/bbb
aaa/bbb/.. /ddd	aaa/ddd	aaa/ddd
aaa/bbb/.. /ddd	aaa/bbb/ddd	aaa/bbb/ddd
./		
aaa/bbb/.. /..		

`\cpath` Implement `\cpath` to print the canonicalized path.

```

130 \newcommand\cpath[1]{%
131     \@cpath{#1}%
132     \@CanPath%
133 }

```

`\path@filename`

```

134 \def\path@filename#1#2{%
135     \edef\filename@oldpath{#1}%
136     \StrCount\filename@oldpath\@Slash[\filename@lastslash]%
137     \ifnum\filename@lastslash>0%
138         \StrBehind[\filename@lastslash]\filename@oldpath\@Slash[\filename@oldpath]%
139         \edef#2{\filename@oldpath}%
140     \else%
141         \edef#2{\filename@oldpath}%
142     \fi%
143 }

```

Test:

Path: /foo/bar/baz.tex

Filename: baz.tex

2.2.2 Windows

First, a conditional that tells us whether we have to use windows or unix file paths:

```
144 \newif\if@iswindows@%iswindows@false
145 \IfFileExists{nul:}%{\IfFileExists{/dev/null}}%{\@iswindows@true}}%
```

Test:

We are on windows: no.

`\windows@to@path` Converts a windows-style file path to a unix-style file path:

```
146 \newif\if@windowstopath@inpath@
147 \def\windows@to@path#1{
148   \@windowstopath@inpath@false
149   \def\windows@temp{}
150   \edef\windows@path{#1}
151   \ifx\windows@path\empty\else
152     \expandafter\windows@path@loop\windows@path\windows@path@end
153   \fi
154   \let#1\windows@temp
155 }
156 \def\windows@path@loop#1#2\windows@path@end{
157   \def\windows@temp@b{#2}
158   \ifx\windows@temp@b\empty
159     \def\windows@continue{}
160   \else
161     \def\windows@continue{\windows@path@loop#2\windows@path@end}
162   \fi
163   \if@windowstopath@inpath@
164     \ifx#1\@BackSlash
165       \edef\windows@temp{\windows@temp\@Slash}
166     \else
167       \edef\windows@temp{\windows@temp#1}
168     \fi
169   \else
170     \ifx#1:
171       \edef\windows@temp{\@Slash\windows@temp}
172       \@windowstopath@inpath@true
173     \else
174       \edef\windows@temp{\windows@temp#1}
175     \fi
176   \fi
177   \windows@continue
178 }
```

Test:

Input: C:\foo\bar.baz

Output: /C/foo/bar.baz

`\path@to@windows` Converts a unix-style file path to a windows-style file path:

```
179 \def\path@to@windows#1{
180   \@windowstopath@inpath@false
181   \def\windows@temp{ }
182   \edef\windows@path{#1}
183   \edef\windows@path{\expandafter\@gobble\windows@path}
184   \ifx\windows@path\empty\else
185     \expandafter\path@windows@loop\windows@path\windows@path@end
186   \fi
187   \let#1\windows@temp
188 }
189 \def\path@windows@loop#1#2\windows@path@end{
190   \def\windows@temp@b{#2}
191   \ifx\windows@temp@b\empty
192     \def\windows@continue{ }
193   \else
194     \def\windows@continue{\path@windows@loop#2\windows@path@end}
195   \fi
196   \if@windowstopath@inpath@
197     \ifx#1/
198       \edef\windows@temp{\windows@temp\@BackSlash}
199     \else
200       \edef\windows@temp{\windows@temp#1}
201     \fi
202   \else
203     \ifx#1/
204       \edef\windows@temp{\windows@temp:\@BackSlash}
205       \@windowstopath@inpath@true
206     \else
207       \edef\windows@temp{\windows@temp#1}
208     \fi
209   \fi
210   \windows@continue
211 }
```

Test:

Input: /C/foo/bar.baz

Output: C:\foo\bar.baz

2.2.3 Auxiliary methods

`\trimstring` Removes initial and trailing spaces from a string:

```
212 \def\trimstring#1{%
213   \edef\pathsuris@trim@temp{#1}%
214   \IfBeginWith\pathsuris@trim@temp\@Space{%
215     \StrGobbleLeft\pathsuris@trim@temp1[#1]%
216   }
```



```

216      \trimstring{#1}%
217    }{%
218      \IfEndWith\pathsuris@trim@temp\@Space{%
219        \StrGobbleRight\pathsuris@trim@temp1[#{1}]%
220        \trimstring{#1}%
221      }{%
222        \edef#1{\pathsuris@trim@temp}%
223      }%
224    }%
225 }

```

Test:

[»bla blubb«](#)

`\kpsewhich` Calls `kpsewhich` to get e.g. system variables:

```

226 \def\kpsewhich#1#2{\begingroup%
227   \edef\kpsewhich@cmd{"|kpsewhich #2"}%
228   \everyeof{\noexpand}%
229   \catcode'\=12%
230   \edef#1{\@input\kpsewhich@cmd\@Space}%
231   \trimstring#1%
232   \if@iswindows@\windows@to@path#1\fi%
233   \xdef#1{\expandafter\detokenize\expandafter{#1}}%
234 \endgroup}

```

Test:

[/usr/share/texlive/texmf-dist/tex/latex/etoolbox/etoolbox.sty](#)

2.2.4 sTeX input hooks

We determine the PWD of the current main document:

```

235 \edef\pwd@cmd{\if@iswindows@ -expand-var \percent CD\percent\else -var-value PWD\fi}
236 \kpsewhich\stex@maindir\pwd@cmd
237 \edef\stex@mainfile{\stex@maindir\@Slash\jobname}
238 \edef\stex@mainfile{\expandafter\detokenize\expandafter{\stex@mainfile}}

```

Test:

[/home/jazzpirate/work/Software/ext/sTeX/sty/stex-master](#)

We keep a stack of \inputed files:

```

239 \def\stex@currfile@stack{}
240
241 \def\stex@currfile@push#1{%
242   \edef\stex@temppath{#1}%
243   \edef\stex@temppath{\expandafter\detokenize\expandafter{\stex@temppath}}%
244   \edef\stex@currfile@stack{\stex@currfile\ifx\stex@currfile@stack\@empty\else,\stex@currfile@s
245   \IfBeginWith\stex@temppath\@Slash{\@cpath{\stex@temppath}}{%
246     \@cpath{\stex@maindir\@Slash#1}%
247   }
248   \let\stex@currfile\@CanPath%
249   \path@filename\stex@currfile\stex@currfilename%
250   \StrLen\stex@currfilename[\stex@currfile@tmp]%

```

```

251 \StrGobbleRight\stex@currfile{\the\numexpr\stex@currfile@tmp+1 }[\stex@currpath]%
252 \global\let\stex@currfile\stex@currfile%
253 \global\let\stex@currpath\stex@currpath%
254 \global\let\stex@currfilename\stex@currfilename%
255 }
256 \def\stex@currfile@pop{%
257 \ifx\stex@currfile@stack\@empty%
258 \global\let\stex@currfile\stex@mainfile%
259 \global\let\stex@currpath\stex@maindir%
260 \global\let\stex@currfilename\jobname%
261 \else%
262 \StrCut\stex@currfile@stack,\stex@currfile\stex@currfile@stack%
263 \path@filename\stex@currfile\stex@currfilename%
264 \StrLen\stex@currfilename[\stex@currfile@tmp]%
265 \StrGobbleRight\stex@currfile{\the\numexpr\stex@currfile@tmp+1 }[\stex@currpath]%
266 \global\let\stex@currfile\stex@currfile%
267 \global\let\stex@currpath\stex@currpath%
268 \global\let\stex@currfilename\stex@currfilename%
269 \fi%
270 }

```

`\stexinput` Inputs a file by (if necessary) converting its path to a windows path first, and adding the file path to the input stack above:

```

271 \def\stexinput#1{%
272 \stexiffileexists{#1}{%
273 \stex@currfile@push\stex@temp@path%
274 \input{\stex@currfile}%
275 \stex@currfile@pop%
276 }%
277 {%
278 \PackageError{stex}{File does not exist (#1): \stex@temp@path}{}%
279 }%
280 }
281 \def\stexiffileexists#1#2#3{%
282 \edef\stex@temp@path{#1}%
283 \if@iswindows@\path@to@windows\stex@temp@path\fi%
284 \IfFileExists\stex@temp@path{#2}{#3}%
285 }
286 \stex@currfile@pop

```

Test:

This file: </home/jazzpirate/work/Software/ext/sTeX/sty/stex-master/stex-master>

A test file: </home/jazzpirate/work/Software/ext/sTeX/sty/stex-master/testfile.tex>

2.2.5 MathHub repositories

We read the MATHHUB system variable and set `\MathHub` accordingly:

```

287 \kpsewhich\mathhub@path{--var-value MATHHUB}
288 \if@iswindows@\windows@to@path\mathhub@path\fi
289 \ifx\mathhub@path\@empty%

```

```

290 \PackageWarning{stex}{MATHHUB system variable not found or wrongly set}{}
291 \defpath{MathHub}{}
292 \else\defpath{MathHub}\mathhub@path\fi

```

Test:

</home/jazzpirate/work/MathHub>

`\findmanifest` `\findmanifest{<path>}` searches for a file MANIFEST.MF up and over `<path>` in the file system tree.

```

293 \def\findmanifest#1{
294   \@cpath{#1}
295   \ifx\@CanPath\@Slash
296     \def\manifest@mf{}
297   \else\ifx\@CanPath\@empty
298     \def\manifest@mf{}
299   \else
300     \edef\@findmanifest@path{\@CanPath/MANIFEST.MF}
301     \if@iswindows@path@to@windows\@findmanifest@path\fi
302     \IfFileExists{\@findmanifest@path}{
303       \%message{MANIFEST.MF found at \@findmanifest@path}
304       \edef\manifest@mf{\@findmanifest@path}
305       \xdef\temp@archive@dir{\expandafter\detokenize\expandafter{\@CanPath}}
306     }{
307       \edef\@findmanifest@path{\@CanPath/META-INF/MANIFEST.MF}
308       \if@iswindows@path@to@windows\@findmanifest@path\fi
309       \IfFileExists{\@findmanifest@path}{
310         \%message{MANIFEST.MF found at \@findmanifest@path}
311         \edef\manifest@mf{\@findmanifest@path}
312         \xdef\temp@archive@dir{\expandafter\detokenize\expandafter{\@CanPath}}
313       }{
314         \edef\@findmanifest@path{\@CanPath/meta-inf/MANIFEST.MF}
315         \if@iswindows@path@to@windows\@findmanifest@path\fi
316         \IfFileExists{\@findmanifest@path}{
317           \%message{MANIFEST.MF found at \@findmanifest@path}
318           \edef\manifest@mf{\@findmanifest@path}
319           \xdef\temp@archive@dir{\expandafter\detokenize\expandafter{\@CanPath}}
320         }{
321           \findmanifest{\@CanPath/..}
322         }}
323   \fi\fi
324 }

```

Test:

</home/jazzpirate/work/MathHub/smglob/mv/META-INF/MANIFEST.MF>

the next macro is a helper function for parsing MANIFEST.MF

```

325 \def\split@manifest@key{
326   \IfSubStr{\manifest@line}{\@Colon}{
327     \StrBefore{\manifest@line}{\@Colon}[\manifest@key]
328     \StrBehind{\manifest@line}{\@Colon}[\manifest@line]

```

```

329     \trimstring\manifest@line
330     \trimstring\manifest@key
331   }{
332     \def\manifest@key{}
333   }
334 }

```

the next helper function iterates over lines in MANIFEST.MF

```

335 \def\parse@manifest@loop{
336   \ifeof\@manifest
337   \else
338     \read\@manifest to \manifest@line\relax
339     \edef\manifest@line{\expandafter\detokenize\expandafter{\manifest@line}}
340     \split@manifest@key
341     % id
342     \IfStrEq\manifest@key{\detokenize{id}}{
343       \xdef\manifest@mf@id{\manifest@line}
344     }{
345       % narration-base
346       \IfStrEq\manifest@key{\detokenize{narration-base}}{
347         \xdef\manifest@mf@narr{\manifest@line}
348       }{
349         % namespace
350         \IfStrEq\manifest@key{\detokenize{source-base}}{
351           \xdef\manifest@mf@ns{\manifest@line}
352         }{
353           \IfStrEq\manifest@key{\detokenize{ns}}{
354             \xdef\manifest@mf@ns{\manifest@line}
355           }{
356             % dependencies
357             \IfStrEq\manifest@key{\detokenize{dependencies}}{
358               \xdef\manifest@mf@deps{\manifest@line}
359             }{
360               }}}}
361     \parse@manifest@loop
362   \fi
363 }

```

`\parsemanifest` `\parsemanifest{⟨macroname⟩}{⟨path⟩}` finds MANIFEST.MF via `\findmanifest{⟨path⟩}`, and parses the file, storing the individual fields (id, narr, ns and dependencies) in `⟨macroname⟩id`, `⟨macroname⟩narr`, etc.

```

364 \newread\@manifest
365 \def\parsemanifest#1#2{%
366   \gdef\temp@archive@dir{}%
367   \findmanifest{#2}%
368   \begingroup%
369     \gdef\manifest@mf@id{}%
370     \gdef\manifest@mf@narr{}%
371     \gdef\manifest@mf@ns{}%
372     \gdef\manifest@mf@deps{}%

```

```

373 \openin\@manifest\manifest@mf%
374 \parse@manifest@loop%
375 \closein\@manifest%
376 \endgroup%
377 \if@iswindows@\windows@to@path\manifest@mf\fi%
378 \cslet{#1id}\manifest@mf@id%
379 \cslet{#1narr}\manifest@mf@narr%
380 \cslet{#1ns}\manifest@mf@ns%
381 \cslet{#1deps}\manifest@mf@deps%
382 \ifcsvoid{manifest@mf@id}{-}%
383 \cslet{#1dir}\temp@archive@dir%
384 }%
385 }

```

Test:

id: FOO/BAR

ns: <http://mathhub.info/FOO/BAR>

dir: FOO

`\setcurrentreposinfo` `\setcurrentreposinfo{<id>}` sets the current repository to `<id>`, checks if the MANIFEST.MF of this repository has already been read, and if not, find it, parses it and stores the values in `\currentrepos@<key>@<id>` for later retrieval.

```

386 \def\setcurrentreposinfo#1{%
387 \edef\mh@currentrepos{#1}%
388 \ifx\mh@currentrepos\empty%
389 \edef\currentrepos@dir{\@Dot}%
390 \def\currentrepos@narr{}%
391 \def\currentrepos@ns{}%
392 \def\currentrepos@id{}%
393 \def\currentrepos@deps{}%
394 \else%
395 \ifcsdef{mathhub@dir@\mh@currentrepos}{%
396 \@inmhrepostrue
397 \edef\mh@currentrepos{#1}%
398 \expandafter\let\expandafter\currentrepos@dir\csname mathhub@dir@#1\endcsname%
399 \expandafter\let\expandafter\currentrepos@narr\csname mathhub@narr@#1\endcsname%
400 \expandafter\let\expandafter\currentrepos@ns\csname mathhub@ns@#1\endcsname%
401 \expandafter\let\expandafter\currentrepos@deps\csname mathhub@deps@#1\endcsname%
402 }{%
403 \parsemanifest{currentrepos@}{\MathHub{#1}}%
404 \@setcurrentreposinfo%
405 \ifcsvoid{currentrepos@dir}{\PackageError{stex}{No archive with %
406 name #1 found!}{make sure that #1 is directly in your MATHHUB folder %
407 and contains a MANIFEST.MF, either directly in #1 or in a meta-inf %
408 subfolder.}}{\@inmhrepostrue}%
409 }%
410 \fi%
411 }
412
413 \def\@setcurrentreposinfo{%

```

```

414 \edef\mh@currentrepos{\currentrepos@id}%
415 \ifcvoid{currentrepos@dir}{-}{%
416   \csxdef{mathhub@dir@\currentrepos@id}{\currentrepos@dir}%
417   \csxdef{mathhub@narr@\currentrepos@id}{\currentrepos@narr}%
418   \csxdef{mathhub@ns@\currentrepos@id}{\currentrepos@ns}%
419   \csxdef{mathhub@deps@\currentrepos@id}{\currentrepos@deps}%
420 }%
421 }

```

Finally – and that is the ultimate goal of all of the above, we set the current repos.

```

422 \newif\if@inmhrepos\@inmhreposfalse
423 \ifcvoid{stex@maindir}{-}{%
424 \parsemanifest{currentrepos@}\stex@maindir
425 \@setcurrentreposinfo
426 \ifcvoid{currentrepos@dir}{\PackageWarning{stex}{Not currently in a MathHub repository}}{-}{%
427 \message{Current repository: \mh@currentrepos}
428 }
429 }

```

2.3 Modules

```

430 \if@latexml\else\ifmod@show\RequirePackage{mdframed}\fi\fi

```

Aux:

```

431 \def\ignorespacesandpars{\begingroup\catcode13=10\ifnextchar\relax{\endgroup}{\endgroup}}

```

and more adapted from <http://tex.stackexchange.com/questions/179016/>

`ignore-spaces-and-pars-after-an-environment`

```

432 \def\ignorespacesandparsafterend#1\ignorespaces\fi{#1\fi\ignorespacesandpars}

```

```

433 \def\ignorespacesandpars{\ifhmode\unskip\fi\@ifnextchar\par{\expandafter\ignorespacesandpars\@g

```

Options for the module-environment:

```

434 \addmetakey*{module}{title}
435 \addmetakey*{module}{name}
436 \addmetakey*{module}{creators}
437 \addmetakey*{module}{contributors}
438 \addmetakey*{module}{srccite}
439 \addmetakey*{module}{ns}
440 \addmetakey*{module}{narr}

```

`module@heading` We make a convenience macro for the module heading. This can be customized.

```

441 \ifdef{\thesection}{\newcounter{module}[section]}{\newcounter{module}}%
442 \newrobustcmd\module@heading{%
443   \stepcounter{module}%
444   \ifmod@show%
445     \noindent{\textbf{Module}} \thesection.\themodule [\module@name]}%
446   \sref@label@id{Module \thesection.\themodule [\module@name]}%
447   \ifx\module@title@empty : \quad\else\quad(\module@title)\hfill\\\fi%
448   \fi%
449 }%

```

Test:
Module 2.1[Test]: Foo

module Finally, we define the `begin module` command for the module environment. Much of the work has already been done in the `keyval` bindings, so this is quite simple.

```
450 \newenvironment{module}[1] [] {%
451   \begin{@module}{#1}%
452   \module@heading% make the headings
453   \ignorespacesandpars\parsemodule@maybesetcodes}%
454   \end{@module}%
455   \ignorespacesafterend%
456 }%
457 \ifmod@show\surroundwithmdframed{module@om@common}\fi%
```

Some auxiliary methods:

```
458 \def\g@addto@macro@safe#1#2{\ifx#1\relax\def#1{}\fi\g@addto@macro#1{#2}}
459 \def\addto@thismodule#1{%
460   \@ifundefined{this@module}{}{%
461     \expandafter\g@addto@macro@safe\this@module{#1}%
462   }%
463 }
464 \def\addto@thismoduleex#1{%
465   \@ifundefined{this@module}{}{%
466     \edef\addto@thismodule@exp{#1}%
467     \expandafter\expandafter\expandafter\g@addto@macro@safe%
468     \expandafter\this@module\expandafter{\addto@thismodule@exp}%
469   }}
```

@module A variant of the `module` environment that does not create printed representations (in particular no frames).

To compute the $\langle uri \rangle$ of a module, `\set@default@ns` computes the namespace, if none is provided as an optional argument, as follows:

If the file of the module is `/some/path/file.tex` and we are not in a MathHub repository, the namespace is `file:///some/path`.

If the file of the module is `/some/path/in/mathhub/repo/sitory/source/sub/file.tex` and `repo/sitory` is an archive in the MathHub root, and the `MANIFEST.MF` of `repo/sitory` declares a namespace `http://some.namespace/foo`, then the namespace of the module is `http://some.namespace/foo/sub`.

```
470 \newif\ifarchive@ns@empty@\archive@ns@empty@false
471 \def\set@default@ns{%
472   \edef\@module@ns@temp{\stex@currpath}%
473   \if@iswindows@\windows@to@path\@module@ns@temp\fi%
474   \archive@ns@empty@false%
475   \ifcvoid{mh@currentrepos}{\archive@ns@empty@true}%
476   {\expandafter\ifx\curname mathhub@ns@\mh@currentrepos\endcurname\@empty\archive@ns@empty@true\fi}%
477   }%
478   \ifarchive@ns@empty%
479     \edef\@module@ns@tempuri{file\@Colon\@Slash\@Slash\@module@ns@temp}%
480   }
```

```

480 \else%
481   \edef\@module@filepath@temppath{\@module@ns@temp}%
482   \edef\@module@ns@tempuri{\csname mathhub@ns@mh@currentrepos\endcsname}%
483   \edef\@module@archivedirpath{\csname mathhub@dir@mh@currentrepos\endcsname\@Slash source}%
484   \edef\@module@archivedirpath{\expandafter\detokenize\expandafter{\@module@archivedirpath}}%
485   \IfBeginWith\@module@filepath@temppath\@module@archivedirpath{%
486     \StrLen\@module@archivedirpath[\ns@temp@length]%
487     \StrGobbleLeft\@module@filepath@temppath\ns@temp@length[\@module@filepath@temprest]%
488     \edef\@module@ns@tempuri{\@module@ns@tempuri\@module@filepath@temprest}%
489   }{}%
490 \fi%
491 \IfEndWith\@module@ns@tempuri\@Slash{\StrGobbleRight\@module@ns@tempuri1[\@module@ns@tempuri]}%
492 \setkeys{module}{ns=\@module@ns@tempuri}%
493 }

```

Test:

<file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master>

If the module is not given a name, `\set@next@moduleid` computes one by enumeration, e.g. `module0`, `module1`, etc.

```

494 \def\set@next@moduleid{%
495   \unless\ifcsname namespace@\module@ns @unnamedmodules\endcsname%
496     \csgdef{namespace@\module@ns @unnamedmodules}{0}%
497   \fi%
498   \edef\namespace@currnum{\csname namespace@\module@ns @unnamedmodules\endcsname}%
499   \edef\module@temp@setidname{\noexpand\setkeys{module}{name=module\namespace@currnum}}%
500   \module@temp@setidname%
501   \csxdef{namespace@\module@ns @unnamedmodules}{\the\numexpr\namespace@currnum+1}%
502 }

```

Test:

`module0`

`module1`

Finally, the `@module` environment does the actual work, i.e. setting metakeys, computing namespace/id, defining `\this@module`, etc.

For a module with name $\langle name \rangle$ (`\module@name`) and uri $\langle uri \rangle$ (`\module@uri`), this defines the following macros:

- `\module@defs@ $\langle uri \rangle$` that acts as a repository for semantic macros of the current module. It will be called by `\importmodule` to activate them.
- We will add the internal forms of the semantic macros whenever `\symdef` is invoked. To do this, we will need an unexpanded form `\this@module` that expands to `\module@defs@ $\langle uri \rangle$` ; we define it first and then initialize `\module@defs@ $\langle uri \rangle$` as empty.
- `\module@names@ $\langle uri \rangle$` will store all symbol names declared in this module.
- `\module@imports@ $\langle uri \rangle$` will store the URIs of all modules directly included in this module
- `\mathbf{\langle uri \rangle}` that expands to `\invoke@module{\mathbf{\langle uri \rangle}}` (see below).

- `\Module⟨name⟩` that expands to `\⟨uri⟩`.

If we are currently in a mathhub repository, this information will also be stored in `\module@defs@⟨uri⟩`, so we can resolve includes properly when this module is activated.

```

503 \newenvironment{@module}[1] [] {%
504   \metasetkeys{module}{#1}%
505   \ifcvoid{module@name}{\let\module@name\module@id}{}% % TODO deprecate
506   \ifx\module@ns\empty\setdefault@ns\fi%
507   \ifx\module@narr\empty%
508     \setkeys{module}{narr=\module@ns}%
509   \fi%
510   \ifcvoid{module@name}{\set@next@moduleid}{}%
511   \let\module@id\module@name% % TODO deprecate
512   \edef\module@uri{\module@ns\@QuestionMark\module@name}%
513   \csgdef{module@names@\module@uri}{}%
514   \csgdef{module@imports@\module@uri}{}%
515   \csxdef{\module@uri}{\noexpand\@invoke@module{\module@uri}}%
516   \expandafter\global\expandafter\let\csname Module\module@name\expandafter\endcsname\csname\module@uri\endcsname
517   \edef\this@module{%
518     \expandafter\noexpand\csname module@defs@\module@uri\endcsname%
519   }%
520   \csdef{module@defs@\module@uri}{}%
521   \ifcvoid{mh@currentrepos}{}{%
522     \@inmhreposttrue%
523     \addto@thismodule{\expandafter\edef\expandafter\noexpand\csname mh@old@repos@\module@uri\endcsname
524       {\noexpand\mh@currentrepos}}%
525     \addto@thismodule{\noexpand\setcurrentreposinfo{\mh@currentrepos}}%
526   }%
527 }{%
528   \if@inmhrepos%
529     \@inmhreposfalse%
530     \addto@thismodule{\noexpand\setcurrentreposinfo{\expandafter\noexpand\csname mh@old@repos@\module@uri\endcsname
531       {\noexpand\mh@currentrepos}}%
532   }%

```

Test:

Module 2.2[Foo]:

Name: Foo

URI: file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?Foo

this@module: macro:->

Test:

Faking a MathHub archive Foo/Bar with URI <http://foo.bar/baz>:

Module 2.3[Foo2]:

Name: Foo2

URI: <http://foo.bar/baz?Foo2>

this@module: macro:->\edef\mh@old@repos@<http://foo.bar/baz?Foo2>{\mh@currentrepos}\setcurrentreposinfo{Foo/Bar}

Test:

Removing the `/home/jazzpirate/work/MathHub/` system variable first:

Module 2.4[Foo]:

Name: Foo

URI: file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?Foo

this@module: macro:->Faking a MathHub archive Foo/Bar with URI `http://foo.bar/baz`:

Module 2.5[Foo2]:

Name: Foo2

URI: `http://foo.bar/baz?Foo2`

this@module: macro:->`\edef\mh@old@repos@http://foo.bar/baz?Foo2 {\mh@currentrepos}`
`\setcurrentreposinfo {Foo/Bar}`

A module with URI $\langle uri \rangle$ and id $\langle id \rangle$ creates two macros $\backslash\langle uri \rangle$ and $\backslash\text{Module}\langle id \rangle$, that ultimately expand to $\backslash\text{@invoke@module}\{\langle uri \rangle\}$. Currently, the only functionality is $\backslash\text{@invoke@module}\{\langle uri \rangle\}\backslash\text{@URI}$, which expands to the full uri of a module (i.e. via $\backslash\text{Module}\langle id \rangle\backslash\text{@URI}$). In the future, this macro can be extended with additional functionality, e.g. accessing symbols in a macro for overloaded (macro-)names.

```
533 \def\@URI{uri}
534 \def\@invoke@module#1#2{%
535   \ifx\@URI#2%
536     #1%
537   \else%
538     % TODO something else
539     #2%
540   \fi%
541 }
```

2.4 Inheritance

2.4.1 Selective Inclusion

The next great goal is to establish the `\requiremodules` macro, which reads an \LaTeX file and processes all the module signature information in them, but does not produce any output. This is a tricky business, as we need to “parse” the modules and treat the module signature macros specially (we refer to this as “**sms mode**”, since it is equivalent to what the – now deprecated – `sms` utility did).

In the following we introduce a lot of auxiliary functionality before we can define `\requiremodules`.

`\parsemodule@allow*` The first step is setting up a functionality for registering \LaTeX macros and environments as part of a module signature.

```
542 \newif\if@smsmode\@smsmodefalse
543 \def\parsemodule@escapechar@allowed{true}
544 \def\parsemodule@allow#1{
545   \expandafter\let\csname parsemodule@allowedmacro@#1\endcsname\parsemodule@escapechar@allowed
546 }
547 \def\parsemodule@allowenv#1{
548   \expandafter\let\csname parsemodule@allowedenv@#1\endcsname\parsemodule@escapechar@allowed
```

```

549 }
550 \def\parsemodule@escapechar@beginstring{begin}
551 \def\parsemodule@escapechar@endstring{end}

```

and now we use that to actually register all the \TeX functionality as relevant for `sms` mode.

```

552 \parsemodule@allow{symdef}
553 \parsemodule@allow{abbrdef}
554 \parsemodule@allow{importmodule}
555 \parsemodule@allowenv{module}
556 \parsemodule@allow{importmhmodule}
557 \parsemodule@allow{gimport}
558 \parsemodule@allowenv{modsig}
559 \parsemodule@allowenv{mhmodsig}
560 \parsemodule@allowenv{mhmodnl}
561 \parsemodule@allowenv{modnl}
562 \parsemodule@allow{symvariant}
563 \parsemodule@allow{symi}
564 \parsemodule@allow{symii}
565 \parsemodule@allow{symiii}
566 \parsemodule@allow{symiv}
567 \parsemodule@allow{notation}
568 \parsemodule@allow{symdecl}
569 %\parsemodule@allow{defi}
570 %\parsemodule@allow{defii}
571 %\parsemodule@allow{defiii}
572 %\parsemodule@allow{defiv}
573 %\parsemodule@allow{adefi}
574 %\parsemodule@allow{adefii}
575 %\parsemodule@allow{adefiii}
576 %\parsemodule@allow{adefiv}
577 %\parsemodule@allow{defis}
578 %\parsemodule@allow{defiis}
579 %\parsemodule@allow{defiiis}
580 %\parsemodule@allow{defivs}
581 %\parsemodule@allow{Defi}
582 %\parsemodule@allow{Defii}
583 %\parsemodule@allow{Defiii}
584 %\parsemodule@allow{Defiv}
585 %\parsemodule@allow{Defis}
586 %\parsemodule@allow{Defiis}
587 %\parsemodule@allow{Defiiis}
588 %\parsemodule@allow{Defivs}

```

To read external modules without producing output, `\requiremodules` redefines the `\`-character to be an *active* character that, instead of executing a macro, checks whether a macro name has been registered using `\parsemodule@allow` before selectively executing the corresponding macro or ignoring it. To produce the relevant code, we therefore define a macro `\@active@slash` that produces a `\`-character with category code 13 (*active*), as well as `\@open@brace` and

`\@close@brace`, which produce open and closing braces with category code 12 (*other*).

```

589 \catcode'\.=0
590 .catcode'\.=13
591 .def.@active@slash{\}
592 .catcode'\.<=1
593 .catcode'\.>=2
594 .catcode'\{=12
595 .catcode'\}=12
596 .def.@open@brace<{>
597 .def.@close@brace<>
598 .catcode'\.=0
599 \catcode'\.=12
600 \catcode'\{=1
601 \catcode'\}=2
602 \catcode'\<=12
603 \catcode'\>=12

```

The next two macros set and reset the category codes before/after `sms` mode.

`\set@parsemodule@catcodes`

```

604 \def\set@parsemodule@catcodes{%
605     \global\catcode'\.=13%
606     \global\catcode'\#=12%
607     \global\catcode'\{=12%
608     \global\catcode'\}=12%
609     \global\catcode'\$=12%$
610     \global\catcode'\^=12%
611     \global\catcode'\_ =12%
612     \global\catcode'\&=12%
613     \expandafter\let\@active@slash\parsemodule@escapechar%
614 }

```

`\reset@parsemodule@catcodes`

```

615 \def\reset@parsemodule@catcodes{%
616     \global\catcode'\.=0%
617     \global\catcode'\#=6%
618     \global\catcode'\{=1%
619     \global\catcode'\}=2%
620     \global\catcode'\$=3%$
621     \global\catcode'\^=7%
622     \global\catcode'\_ =8%
623     \global\catcode'\&=4%
624 }

```

`\parsemodule@maybesetcodes`

Before a macro is executed in `sms`-mode, the category codes will be reset to normal, to ensure that all macro arguments are parsed correctly. Consequently, the macros need to set the category codes back to `sms` mode after having read all arguments iff the macro got executed in `sms` mode. `\parsemodule@maybesetcodes` takes care of that.

```

625 \def\parsemodule@maybesetcodes{%
626   \if@smsmode\set@parsemodule@catcodes\fi%
627 }

```

`\parsemodule@escapechar` This macro gets called whenever a `\`-character occurs in `sms` mode. It is split into several macros that parse and store characters in `\parsemodule@escape@currcls` until a character with category code $\neq 11$ occurs (i.e. the macro name is complete), check whether the macro is allowed in `sms` mode, and then either ignore it or execute it after setting category codes back to normal. Special care needs to be taken to make sure that braces have the right category codes (1 and 2 for open and closing braces, respectively) when delimiting macro arguments.

Entry point:

```

628
629 \def\parsemodule@escapechar{%
630   \def\parsemodule@escape@currcls{}%
631   \parsemodule@escape@parse@nextchar%
632 }%

```

The next macro simply reads the next character and checks whether it has category code 11. If so, it stores it in `\parsemodule@escape@currcls`. Otherwise, the macro name is complete, it stores the last character in `\parsemodule@last@char` and calls `\parsemodule@escapechar@checkcls`.

```

633 \long\def\parsemodule@escape@parse@nextchar@#1{%
634   \ifcat a#1\relax%
635     \edef\parsemodule@escape@currcls{\parsemodule@escape@currcls#1}%
636     \let\parsemodule@do@next\parsemodule@escape@parse@nextchar%
637   \else%
638     \def\parsemodule@last@char{#1}%
639     \def\parsemodule@do@next{\parsemodule@escapechar@checkcls}%
640   \fi%
641   \parsemodule@do@next%
642 }

```

The next macro checks whether the currently stored macroname is allowed in `sms` mode. There are four cases that need to be considered: `\begin`, `\end`, allowed macros, and others. In the first two cases, we reinsert `\parsemodule@last@char` and continue with `\parsemodule@escapechar@checkbeginenv` or `\parsemodule@escapechar@checkendenv` respectively, to check whether the environment being opened/closed is allowed in `sms` mode. In both cases, `\parsemodule@last@char` is an open brace with category code 12. In the third case, we need to check whether `\parsemodule@last@char` is an open brace, in which case we call `\parsemodule@converttoproperbraces`, otherwise, we set category codes to normal and execute the macro. In the fourth case, we just reinsert `\parsemodule@last@char` and continue.

```

643 \def\parsemodule@escapechar@checkcls{%
644   \ifx\parsemodule@escape@currcls\parsemodule@escapechar@beginstring%
645     \edef\parsemodule@do@next{\noexpand\parsemodule@escapechar@checkbeginenv\parsemodule@last@char}%
646   \else%
647     \ifx\parsemodule@escape@currcls\parsemodule@escapechar@endstring%

```

```

648         \edef\parsemodule@do@next{\noexpand\parsemodule@escapechar@checkendenv\parsemodule@la
649     \else%
650         \expandafter\ifx\csname parsemodule@allowedmacro@\parsemodule@escape@curr\endcsna
651             \parsemodule@escapechar@allowed%
652         \ifx\parsemodule@last@char\@open@brace%
653             \expandafter\let\expandafter\parsemodule@do@next@ii\csname\parsemodule@escape@c
654             \edef\parsemodule@do@next{\noexpand\parsemodule@converttoproperbraces\@open@bra
655         \else%
656             \reset@parsemodule@catcodes%
657             \edef\parsemodule@do@next{\expandafter\noexpand\csname\parsemodule@escape@curr
658         \fi%
659     \else\def\parsemodule@do@next{\relax\parsemodule@last@char}\fi%
660 \fi%
661 \fi%
662 \parsemodule@do@next%
663 }

```

This macro simply takes an argument in braces (with category codes 12), reinserts it with “proper” braces (category codes 1 and 2), sets category codes back to normal and calls `\parsemodule@do@next@ii`, which has been `\let` as the macro to be executed.

```

664 \expandafter\expandafter\expandafter\def%
665 \expandafter\expandafter\expandafter\parsemodule@converttoproperbraces%
666 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
667     \reset@parsemodule@catcodes%
668     \parsemodule@do@next@ii{#1}%
669 }

```

The next two macros apply in the `\begin` and `\end` cases. They check whether the environment is allowed in sms mode, if so, open/close the environment, and otherwise do nothing.

Notably, `\parsemodule@escapechar@checkendenv` does not set category codes back to normal, since `\end{environment}` never takes additional arguments that need to be parsed anyway.

```

670 \expandafter\expandafter\expandafter\def%
671 \expandafter\expandafter\expandafter\parsemodule@escapechar@checkbeginenv%
672 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
673     \expandafter\ifx\csname parsemodule@allowedenv@#1\endcsname\parsemodule@escapechar@allowed%
674         \reset@parsemodule@catcodes%
675         \def\parsemodule@do@next{\begin{#1}}%
676     \else%
677         \def\parsemodule@do@next{#1}%
678     \fi%
679     \parsemodule@do@next%
680 }
681 \expandafter\expandafter\expandafter\def%
682 \expandafter\expandafter\expandafter\parsemodule@escapechar@checkendenv%
683 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
684     \expandafter\ifx\csname parsemodule@allowedenv@#1\endcsname\parsemodule@escapechar@allowed%

```

```

685      %\reset@parsemodule@catcodes%
686      \def\parsemodule@do@next{\end{#1}}%
687    \else%
688      \def\parsemodule@do@next{#1}%
689    \fi%
690    \parsemodule@do@next%
691 }

```

`\@requiremodules` the internal version of `\requiremodules` for use in the `*.aux` file. We disable it at the end of the document, so that when the `aux` file is read again, nothing is loaded.

```

692 \newrobustcmd\@requiremodules[1]{%
693   \if@tempswa\requiremodules{#1}\fi%
694 }%

```

`\requiremodules` This macro loads the module signatures in a file using the `\requiremodules@smsmode` above. We set the flag `\mod@showfalse` in the local group, so that the macros know now to pollute the result.

```

695 \newrobustcmd\requiremodules[1]{%
696   \mod@showfalse%
697   \edef\mod@path{#1}%
698   \edef\mod@path{\expandafter\detokenize\expandafter{\mod@path}}%
699   \requiremodules@smsmode{#1}%
700 }%

```

`\requiremodules@smsmode` this reads `SIEX` modules by setting the category codes for `sms` mode, `\inputting` the required file and wrapping it in a `\vbox` that gets stored away and ignored, in order to not produce any output. It also sets `\hbadness`, `\hfuzz` and friends to values that suppress overfull and underfull hbox messages.

```

701 \newbox\modules@import@tempbox
702 \def\requiremodules@smsmode#1{%
703   \setbox\modules@import@tempbox\vbox{%
704     \@smsmodetrue%
705     \set@parsemodule@catcodes%
706     \hbadness=100000\relax%
707     \hfuzz=10000pt\relax%
708     \vbadness=100000\relax%
709     \vfuzz=10000pt\relax%
710     \stexinput{#1.tex}%
711     \reset@parsemodule@catcodes%
712   }%
713   \parsemodule@maybesetcodes%
714 }

```

Test:

parsing `F00/testmodule.tex`

macro:->`\@invoke@module {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master/F00?testmodule}`

2.4.2 importmodule

\importmodule

```

715 \newif\if@importmodule@switchrepos\@importmodule@switchreposfalse
716 %\srefaddidkey{importmodule}
717 \addmetakey{importmodule}{mhrepos}
718 \newcommand\importmodule[2][\@importmodule[#1]{#2}{export}}
719 \newcommand\@importmodule[3][\%
720   \@importmodule@switchreposfalse%
721   \metasetkeys{importmodule}{#1}%
722   \parsemodule@maybesetcodes%
723   \ifcvoid{importmodule@mhrepos}{%
724     \ifcvoid{currentrepos@dir}{%
725       \let\importmodule@dir\stex@maindir%
726     }{%
727       \edef\importmodule@dir{\currentrepos@dir\@Slash source}%
728     }%
729   }{%
730     \@importmodule@switchrepositotrue%
731     \expandafter\let\csname importmodule@oldrepos@#2\endcsname\mh@currentrepos%
732     \setcurrentreposinfo\importmodule@mhrepos%
733     \edef\importmodule@dir{\currentrepos@dir\@Slash source}%
734   }%
735   \StrCut{#2}\@QuestionMark\importmodule@subdir\importmodule@modulename%
736   \ifx\importmodule@modulename\empty%
737     \let\importmodule@modulename\importmodule@subdir%
738     \let\importmodule@subdir\empty%
739   \else%
740     \ifx\importmodule@subdir\empty\else%
741       \edef\importmodule@dir{\importmodule@dir\@Slash\importmodule@subdir}%
742     \fi%
743   \fi%
744   \@importmodule[\importmodule@dir]\importmodule@modulename{#3}%
745   \if@importmodule@switchrepos%
746     \expandafter\setcurrentreposinfo\csname importmodule@oldrepos@#2\endcsname%
747   \fi%
748   \ignorespacesandpars%
749 }
```

\@importmodule *\@importmodule*[*<filepath>*][*{<mod>}*]{*<export?>*} loads *<filepath>.tex* and activates the module *<mod>*. If *<export?>* is **export**, then it also re-exports the **\symdefs** from *<mod>*.

First **\@load** will store the base file name with full path, then check if **\module@<mod>@path** is defined. If this macro is defined, a module of this name has already been loaded, so we check whether the paths coincide, if they do, all is fine and we do nothing otherwise we give a suitable error. If this macro is undefined we load the path by **\requiremodules**.

```

750 \newcommand\@importmodule[3][\%
751 {%
```



```

752 \edef\@load{#1}%
753 \edef\@importmodule@name{#2}
754 \if@smsmode\else\ifcsvoid{Module\@importmodule@name}{%
755   \stexiffileexists\@load{\requiremodules\@load}{%
756     \requiremodules{\@load\@Slash\@importmodule@name}%
757   }%
758 }{\fi%
759 \ifx\@load\@empty\else%
760   {% TODO
761     \edef\@path{csname module@#2@path\endcsname}%
762     \IfStrEq\@load\@path{\relax}% if the known path is the same as the requested one do nothing
763     {\PackageError{stex}% else signal an error
764       {Module Name Clash\MessageBreak%
765         A module with name #2 was already loaded under the path "\@path"\MessageBreak%
766         The imported path "\@load" is probably a different module with the\MessageBreak%
767         same name; this is dangerous -- not importing}%
768       {Check whether the Module name is correct}%
769     }%
770   }%
771 \fi%
772 \global\let\@importmodule@load\@load%
773 }%
774 \edef\@export{#3}\def\@@export{export}%prepare comparison
775 %\ifx\@export\@@export\export@defs{#2}\fi% export the module
776 \ifx\@export\@@export\addto@thismodulex{%
777   \noexpand\@importmodule[\@importmodule@load]{#2}{noexport}%
778 }%
779 \if@smsmode\else
780 \ifcsvoid{this@module}{}%
781   \ifcsvoid{module@imports@\module@uri}{%
782     \csxdef{module@imports@\module@uri}{%
783       \csname Module#2\endcsname\@URI%
784     }%
785   }{%
786     \csxdef{module@imports@\module@uri}{%
787       \csname Module#2\endcsname\@URI,%
788       \csname module@imports@\module@uri\endcsname%
789     }%
790   }%
791 }%
792 \fi\fi%
793 \if@smsmode\else\activate@defs{#2}\fi% activate the module
794 }%

```

Test:

```

\importmodule {testmoduleimporta}:
macro:->\@invoke@module {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-
master?testmoduleimporta}
macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-
master?testmoduleimporta?foo}

```

Test:

```
\importmodule {testmoduleimportb?importb}:
macro:->\@invoke@module {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-
master?importb}
macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-
master?importb?bar}
```

Test:

```
macro:->\@invoke@module {http://mathhub.info/smglob/algebra?band}
macro:->\@invoke@module {http://mathhub.info/smglob/algebra?idempotent}
macro:->\@invoke@symbol {http://mathhub.info/smglob/mv?equal?notequal}
macro:->\@ifstar \@gimport@star \@gimport@nostar
```

\activate@defs To activate the `\symdefs` from a given module $\langle mod \rangle$, we call the macro `\module@defs@ $\langle mod \rangle$` . But to make sure that every module is activated only once, we only activate if the macro `\module@defs@ $\langle mod \rangle$` is undefined, and define it directly afterwards to prohibit further activations.

```
795 \def\activate@defs#1{%
796   \ifcsundef{Module#1}{
797     \PackageError{stex}{No module with name #1 loaded}{Probably missing an
798       \detokenize{\importmodule} (or variant) somewhere?
799   }
800 }{%
801   \ifcsundef{module@\csname Module#1\endcsname\@URI @activated}%
802     {\csname module@defs@\csname Module#1\endcsname\@URI\endcsname}{}%
803   \namedef{module@\csname Module#1\endcsname\@URI @activated}{true}%
804 }%
805 }%
```

\usemodule `\usemodule` acts like `\importmodule`, except that it does not re-export the semantic macros in the modules it loads.

```
806 \newcommand\usemodule[2] [] {\@importmodule[#1]{#2}{noexport}}
```

Test:

Module 2.26[Foo]:

```
Module 2.27[Bar]: macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/st
master?Foo?foo}
```

Module 2.28[Baz]: undefined

```
macro:->\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-
master?Bar?bar}
```

2.5 Symbols and Notations

\if@symdeflocal A flag whether a symbol declaration is local (i.e. does not get exported) or not.

```
807 \newif\if@symdeflocal\@symdeflocalfalse
```

\define@in@module calls `\edef\#1{#2}` and adds the macro definition to `\this@module`

```
808 \def\define@in@module#1#2{
809   \expandafter\edef\csname #1\endcsname{#2}%
```

```

810 \edef\define@in@module@temp{%
811   \def\expandafter\noexpand\csname#1\endcsname%
812   {#2}%
813 }%
814 \if@symdeflocal\else%
815   \expandafter\g@addto@macro@safe\csname module@defs@\module@uri%
816   \expandafter\endcsname\expandafter{\define@in@module@temp}%
817 \fi%
818 }

```

`\symdecl` `\symdecl[name=foo]{bar}` Declares a new symbol in the current module with URI `<module-uri>?foo` and defines new macros `\<uri>` and `\bar`. If no optional name is given, `bar` is used as a name.

```

819 \addmetakey{symdecl}{name}%
820
821 \newcommand\symdecl[2][]{%
822   \ifcsdef{this@module}{%
823     \metasetkeys{symdecl}{#1}%
824     \ifcsvoid{symdecl@name}{\edef\symdecl@name{#2}}{}%
825     \edef\symdef@uri{\module@uri\@QuestionMark\symdecl@name}%
826     \ifcsvoid{symdef@uri}{
827       \ifcsvoid{module@names@\module@uri}{%
828         \csxdef{module@names@\module@uri}{\symdecl@name}%
829       }{%
830         \csxdef{module@names@\module@uri}{\symdecl@name,%
831           \csname module@names@\module@uri\endcsname}%
832       }%
833       \define@in@module\symdef@uri{\noexpand\@invoke@symbol{\symdef@uri}}%
834       \define@in@module{#2}{\noexpand\@invoke@symbol{\symdef@uri}}%
835     }{%
836       % not compatible with circular dependencies, e.g. test/omdoc/07-modules/smsstesta.tex
837       \PackageWarning{stex}{symbol already defined: \symdef@uri}{%
838         You need to pick a fresh name for your symbol%
839       }%
840       \define@in@module\symdef@uri{\noexpand\@invoke@symbol{\symdef@uri}}%
841       \define@in@module{#2}{\noexpand\@invoke@symbol{\symdef@uri}}%
842     }%
843   }{%
844     \PackageError{stex}{\detokenize{\symdecl} not in a module}{You need to be in a module%
845       in order to declare a new symbol}
846   }%
847   \if@insymdef\else\parsemodule@maybesetcodes\fi%
848 }

```

Test:

Module 2.29[foo]: `\symdecl {bar}`

Yields: macro:-> `\@invoke@symbol {file:///home/jazzpirate/work/Software/ext/sTeX/sty/stex-master?foo?bar}`

2.5.1 Notations

`\modules@getURIfromName` This macro searches for the full URI given a symbol name and stores it in `\notation@uri`. Used by e.g. `\notation[...]{foo}{...}` to figure out what symbol `foo` refers to:

```

849 \def\modules@getURIfromName#1{%
850   % TODO check whether #1 is a URI
851   \def\notation@uri{}%
852   \def\modules@getURI@name{#1}%
853   \ifcsvoid{this@module}{}{%
854     \expandafter\modules@getURIfromModule\expandafter{\module@uri}%
855     \ifx\notation@uri\empty%
856       \edef\modules@getURI@modules{\csname module@imports@\module@uri\endcsname}%
857       \expandafter\@for\expandafter\@I\expandafter:\expandafter=\modules@getURI@modules\do{%
858         \ifx\notation@uri\empty%
859           \expandafter\modules@getURIfromModule\expandafter{\@I}%
860         \fi%
861       }%
862     \fi%
863     \ifx\notation@uri\empty%
864       \def\notation@extract@uri@curr{cs}%
865       \notation@extracturifrommacro{#1}%
866     \fi%
867     \ifx\notation@uri\empty%
868       \PackageError{stex}{No symbol with name, URI or macroname \detokenize{#1} found!}{}%
869     \fi%
870   }%
871 }
872
873 \def\modules@getURIfromModule#1{%
874   \edef\modules@getURI@names{\csname module@names@#1\endcsname}%
875   \expandafter\@for\expandafter\@I\expandafter:\expandafter=\modules@getURI@names\do{%
876     \ifx\notation@uri\empty%
877       \ifx\@I\modules@getURI@name%
878         \edef\notation@uri{#1\@QuestionMark\@I}%
879       \fi%
880     \fi%
881   }%
882 }
883 }
884
885 % extracts the full URI from \foo or anything being \ifx-equal to \foo,
886 % by expanding until we reach \@invoke@symbol{<uri>}
887 \def\notation@extracturifrommacro#1{%
888   \ifcsvoid{#1}{}{%
889     \expandafter\let\expandafter\notation@extract@uri@nextcs\csname#1\endcsname%
890     \ifx\notation@extract@uri@nextcs\notation@extract@uri@curr\else%
891       \let\notation@extract@uri@curr\notation@extract@uri@nextcs%
892     \expandafter\notation@extract@uriIII\notation@extract@uri@nextcs\notation@end%
893   \fi%

```

```

894 }%
895 }
896 \long\def\notation@extract@uriII#1#2\notation@end{%
897   \def\notation@extract@check@temp{#2}
898   \ifx\@invoke@symbol#1%
899     \edef\notation@uri{#2}%
900   \else%
901     \ifx\notation@extract@check@temp\@empty\else%
902       \expandafter\def\expandafter\notation@extract@uri@nextcs\expandafter{#1{#2}}%
903       \notation@extract@uri{notation@extract@uri@nextcs}%
904     \fi%
905   \fi%
906 }

\notation Adds a new notation to a symbol foo, as in: \notation[lang=en,arity=0,variant=op]{foo}{...}
\notation[variant=bar]{foo}[2]{...} \notation[args=aia,prec=500;50x49x51]{foo}{#1 bla #2
  TODO with brackets, e.g. \notation[withbrackets={\langle,\rangle}]{foo}{...}

907 % parses the first two arguments:
908 \providerobustcmd\notation[2][]{%
909   \edef\notation@first{#1}%
910   \edef\notation@second{#2}%
911   \notation@%
912 }
913
914 % parses the last two arguments
915 \newcommand\notation@[2][0]{%
916   \edef\notation@donext{\noexpand\notation@@[\notation@first]%
917     {\notation@second}[#1]}%
918   \notation@donext{#2}%
919 }
920
921 % parses the notation arguments and wraps them in
922 % \notation@assoc and \notation@argprec for flexary arguments and precedences
923 \def\notation@@[#1]#2[#3]#4{%
924   \modules@getURIfromName{#2}%
925   \notation@parse@params{#1}{#3}
926   \let\notation@curr@todo@args\notation@curr@args%
927   \def\notation@temp@notation{%
928     \StrLen\notation@curr@args[\notation@temp@arity]%
929     \expandafter\renewcommand\expandafter\notation@temp@notation%
930       \expandafter[\notation@temp@arity]{#4}%
931   % precedence
932   \IfSubStr\notation@curr@args;{%
933     \StrCut\notation@curr@args;\notation@curr@prec\notation@curr@args%
934     \ifx\notation@curr@prec\@empty\def\notation@curr@prec{0}\fi%
935   }{%
936     \ifx\notation@curr@args\@empty%
937       \ifnum\notation@temp@arity=0\relax%
938         \edef\notation@curr@prec{\infprec}%

```

```

939     \else%
940     \def\notation@curr@prec{0}%
941     \fi%
942   \else%
943     \edef\notation@curr@prec{\notation@curr@prec}%
944     \def\notation@curr@prec{}%
945     \fi%
946   }%
947   % arguments
948   \def\notation@curr@extargs{}
949   \def\notation@nextarg@index{1}%
950   \notation@do@args%
951 }
952
953 % parses additional notation components for (associative) arguments
954 \def\notation@do@args{%
955   \def\notation@nextarg@temp{}%
956   \ifx\notation@curr@todo@args\empty%
957     \notation@after%
958   \else%
959     % argument precedence
960     \IfSubStr\notation@curr@prec{x}{%
961       \StrCut\notation@curr@prec{x}\notation@curr@argprec\notation@curr@prec%
962     }{%
963       \edef\notation@curr@argprec{\notation@curr@prec}%
964       \def\notation@curr@prec{}%
965     }%
966     \ifx\notation@curr@argprec\empty%
967       \let\notation@curr@argprec\notation@curr@prec%
968     \fi%
969     \StrChar\notation@curr@todo@args1[\notation@argchar]%
970     \StrGobbleLeft\notation@curr@todo@args1[\notation@curr@todo@args]%
971     \expandafter\ifx\notation@argchar i%
972       % normal argument
973       \edef\notation@nextarg@temp{{\noexpand\notation@argprec{\notation@curr@argprec}}{#####\
974       \edef\notation@nextarg@index{\the\numexpr\notation@nextarg@index+1 }
975       \expandafter\g@addto@macro@safe\expandafter\notation@curr@extargs%
976       \expandafter{\notation@nextarg@temp}%
977       \expandafter\expandafter\expandafter\notation@do@args%
978     \else%
979       % associative argument
980       \expandafter\expandafter\expandafter\notation@parse@assocarg%
981     \fi%
982   \fi%
983 }
984
985 \def\notation@parse@assocarg#1{%
986   \edef\notation@nextarg@temp{{\noexpand\notation@argprec{\notation@curr@argprec}}{\noexpand\not
987   \edef\notation@nextarg@index{\the\numexpr\notation@nextarg@index+1 }%
988   \expandafter\g@addto@macro@safe\expandafter\notation@curr@extargs%

```

```

989 \expandafter{\notation@nextarg@temp}%
990 \notation@do@args%
991 }
992
993 \protected\def\safe@newcommand#1{%
994 \ifdefined#1\expandafter\renewcommand\else\expandafter\newcommand\fi#1%
995 }
996
997 % finally creates the actual macros
998 \def\notation@after{
999 \let\ex\expandafter%
1000 \ex\ex\ex\def\ex\ex\ex\notation@temp\notation\ex\ex\ex%
1001 {\ex\notation@temp\notation\notation@curr@extargs}%
1002 \edef\notation@temp\notation{\noexpand\notation@symprec{\notation@curr@prec}{\ex\unexpanded\ex%
1003 \def\notation@temp@fragment{}%
1004 \ifx\notation@curr@arity\@empty\else%
1005 \edef\notation@temp@fragment{arity=\notation@curr@arity}%
1006 \fi%
1007 \ifx\notation@curr@lang\@empty\else%
1008 \ifx\notation@temp@fragment\@empty%
1009 \edef\notation@temp@fragment{lang=\notation@curr@lang}%
1010 \else%
1011 \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand lang=\notation@curr@lang}%
1012 \fi%
1013 \fi%
1014 \ifx\notation@curr@variant\@empty\else%
1015 \ifx\notation@temp@fragment\@empty%
1016 \edef\notation@temp@fragment{variant=\notation@curr@variant}%
1017 \else%
1018 \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand variant=\notation@curr@va
1019 \fi%
1020 \fi%
1021 \edef\notation@csname{\notation@uri\@Fragment\notation@temp@fragment}%
1022 \ifcvoid{\notation@csname}{%
1023 \ex\ex\ex\ex\ex\ex\ex\newcommand\ex\ex\ex\csname\ex\ex\ex\notation@csname%
1024 \ex\ex\ex\endcsname\ex\ex\ex[\ex\notation@temp@arity\ex]%
1025 \ex{\notation@temp\notation}%
1026 \edef\symdecl@temps{%
1027 \noexpand\safe@newcommand\ex\noexpand\csname\notation@csname\endcsname[\notation@temp@ari
1028 }%
1029 \ex\g@addto@macro@safe\csname module@defs@module@uri\ex\endcsname\ex{\symdecl@temps}%
1030 \ex\g@addto@macro@safe\csname module@defs@module@uri\ex\endcsname\ex{\ex{\notation@temp@no
1031 }-%
1032 \PackageWarning{stex}{notation already defined: \notation@csname}{%
1033 Choose a different set of notation options (variant,lang,arity)%
1034 }%
1035 }%
1036 \parsemodule@maybesetcodes%
1037 }
1038

```

```

1039 % parses optional parameters
1040 \def\notation@parse@params#1#2{%
1041   \def\notation@curr@prec{%
1042     \def\notation@curr@args{%
1043       \def\notation@curr@variant{%
1044         \def\notation@curr@arity{%
1045           \def\notation@curr@provided@arity{#2}
1046           \def\notation@curr@lang{%
1047             \def\notation@options@temp{#1}
1048             \notation@parse@params@%
1049             \ifx\notation@curr@args\@empty%
1050               \ifx\notation@curr@provided@arity\@empty%
1051                 \notation@num@to@ia\notation@curr@arity%
1052               \else%
1053                 \notation@num@to@ia\notation@curr@provided@arity%
1054               \fi%
1055             \fi%
1056           }
1057           \def\notation@parse@params@{%
1058             \IfSubStr\notation@options@temp,{%
1059               \StrCut\notation@options@temp,\notation@option@temp\notation@options@temp%
1060               \notation@parse@param%
1061               \notation@parse@params@%
1062             }{\ifx\notation@options@temp\@empty\else%
1063               \let\notation@option@temp\notation@options@temp%
1064               \notation@parse@param%
1065             \fi}%
1066           }
1067         }
1068 %parses an individual optional argument/key-value-pair
1069 \def\notation@parse@param{%
1070   \trimstring\notation@option@temp%
1071   \ifx\notation@option@temp\@empty\else%
1072     \IfSubStr\notation@option@temp={%
1073       \StrCut\notation@option@temp=\notation@key\notation@value%
1074       \trimstring\notation@key%
1075       \trimstring\notation@value%
1076       \IfStrEq\notation@key{prec}{%
1077         \edef\notation@curr@prec{\notation@value}%
1078       }{%
1079         \IfStrEq\notation@key{args}{%
1080           \edef\notation@curr@args{\notation@value}%
1081         }{%
1082           \IfStrEq\notation@key{lang}{%
1083             \edef\notation@curr@lang{\notation@value}%
1084           }{%
1085             \IfStrEq\notation@key{variant}{%
1086               \edef\notation@curr@variant{\notation@value}%
1087             }{%
1088               \IfStrEq\notation@key{arity}{%

```



```

1089         \edef\notation@curr@arity{\notation@value}%
1090     }{%
1091     }}}}}%
1092 }{%
1093     \edef\notation@curr@variant{\notation@option@temp}%
1094 }%
1095 \fi%
1096 }
1097
1098 % converts an integer to a string of 'i's, e.g. 3 => iii,
1099 % and stores the result in \notation@curr@args
1100 \def\notation@num@to@ia#1{%
1101     \IfInteger{#1}{
1102         \notation@num@to@ia@#1%
1103     }{%
1104         %
1105     }%
1106 }
1107 \def\notation@num@to@ia@#1{%
1108     \ifnum#1>0%
1109         \edef\notation@curr@args{\notation@curr@args i}%
1110         \expandafter\notation@num@to@ia@\expandafter{\the\numexpr#1-1\@Space}%
1111     \fi%
1112 }

```

The following macros take care of precedences, parentheses/bracketing, associative (flexary) arguments etc. in presentation:

```

1113 \def\notation@assoc#1#2{% function, argv
1114     \let\@tmpop=\relax% do not print the function the first time round
1115     \@for\@I:=#2\do{\@tmpop% print the function
1116         % write the i-th argument with locally updated precedence
1117         \@I%
1118     \def\@tmpop{#1}%
1119     }%
1120 }%
1121
1122 \def\notation@lparen{()
1123 \def\notation@rparen{)}
1124 \def\infprec{1000000}
1125 \def\neginfprec{-\infprec}
1126
1127 \newcount\notation@downprec
1128 \notation@downprec=\neginfprec
1129
1130 % patching displaymode
1131 \newif\if@displaymode\@displaymodefalse
1132 \expandafter\everydisplay\expandafter{\the\everydisplay\@displaymodetrue}
1133 \let\old@displaystyle\displaystyle
1134 \def\displaystyle{\old@displaystyle\@displaymodetrue}
1135

```

```

1136 \def\dobrackets#1{% avoiding groups at all costs to ensure \parray still works!
1137   \def\notation@innertmp{#1}%
1138   \let\ex\expandafter%
1139   \if@displaymode%
1140     \ex\ex\ex\left\ex\ex\ex\notation@lparen%
1141     \ex\notation@resetbrackets\ex\notation@innertmp%
1142     \ex\right\notation@rparen%
1143   \else%
1144     \ex\ex\ex\notation@lparen%
1145     \ex\notation@resetbrackets\ex\notation@innertmp%
1146     \notation@rparen%
1147   \fi%
1148 }
1149
1150 \def\withbrackets#1#2#3{%
1151   \edef\notation@lparen{#1}%
1152   \edef\notation@rparen{#2}%
1153   #3%
1154   \notation@resetbrackets%
1155 }
1156
1157 \def\notation@resetbrackets{%
1158   \def\notation@lparen{()%
1159   \def\notation@rparen{)%}
1160 }
1161
1162 \def\notation@symprec#1#2{%
1163   \ifnum#1>\notation@downprec\relax%
1164     \notation@resetbrackets#2%
1165   \else%
1166     \ifnum\notation@downprec=\infprec\relax%
1167       \notation@resetbrackets#2%
1168     \else
1169       \if@inarray@
1170         \notation@resetbrackets#2
1171       \else\dobrackets{#2}\fi%
1172   \fi\fi%
1173 }
1174
1175 \newif\if@inarray@\@inarray@false
1176
1177 \def\notation@argprec#1#2{%
1178   \def\notation@innertmp{#2}
1179   \edef\notation@downprec@temp{\number#1}%
1180   \notation@downprec=\expandafter\notation@downprec@temp%
1181   \expandafter\relax\expandafter\notation@innertmp%
1182   \expandafter\notation@downprec\expandafter=\number\notation@downprec\relax%
1183 }

```

`\@invoke@symbol` after `\symdecl{foo}`, `\foo` expands to `\@invoke@symbol{<uri>}`:

```
1184 \protected\def\@invoke@symbol#1{%
1185   \def\@invoke@symbol@first{#1}%
1186   \symbol@args%
1187 }
```

takes care of the optional notation-option-argument, and either invokes `\@invoke@symbol@math` for symbolic presentation or `\@invoke@symbol@text` for verbalization (TODO)

```
1188 \newcommand\symbol@args[1][]{%
1189   \ifmmode\def\invoke@symbol@next{\@invoke@symbol@math\@invoke@symbol@first{#1}}%
1190   \else\def\invoke@symbol@next{\@invoke@symbol@text\@invoke@symbol@first{#1}}\fi%
1191   \invoke@symbol@next%
1192 }
```

This finally gets called with both uri and notation-option, convenient for e.g. a LaTeXML binding:

```
1193 \def\@invoke@symbol@math#1#2{%
1194   % #1: URI
1195   % #2: options
1196   % TODO \setnotation variants
1197   \notation@parse@params{#2}{}%
1198   \def\notation@temp@fragment{%
1199     \ifx\notation@curr@arity\@empty\else%
1200       \edef\notation@temp@fragment{arity=\notation@curr@arity}%
1201     \fi%
1202     \ifx\notation@curr@lang\@empty\else%
1203       \ifx\notation@temp@fragment\@empty%
1204         \edef\notation@temp@fragment{lang=\notation@curr@lang}%
1205       \else%
1206         \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand lang=\notation@curr@lang}%
1207       \fi%
1208     \fi%
1209     \ifx\notation@curr@variant\@empty\else%
1210       \ifx\notation@temp@fragment\@empty%
1211         \edef\notation@temp@fragment{variant=\notation@curr@variant}%
1212       \else%
1213         \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand variant=\notation@curr@va
1214       \fi%
1215     \fi%
1216     \csname #1\@Fragment\notation@temp@fragment\endcsname%
1217 }
```

TODO:

```
1218 \def\@invoke@symbol@text#1#2{%
1219   % TODO
1220 }
```

TODO: To set notational options (globally or locally) generically:

```
1221 \def\setstexlang#1{%
```

```

1222 \def\stex@lang{#1}%
1223 }%
1224 \setstexlang{en}
1225 \def\setstexvariant#1#2{%
1226   % TODO
1227 }
1228 \def\setstexvariants#1{%
1229   \def\stex@variants{#1}%
1230 }

```

Test:

Module 2.30[FooBar]: \symdecl {barbar}
\notation [arity=0]{barbar}{\psi }
\notation [prec=50;\infprec]{barbar}[1]{\barbar [arity=0]\dobrackets {##1}}

\notation [arity=0,variant=cap]{barbar}{\Psi }
\notation [variant=cap]{barbar}[1]{\barbar [arity=0,variant=cap]\dobrackets {##1}}

$\bar{\psi}(A)$
 $\bar{\Psi}(A)$

```

\symdecl {plus}
\symdecl {times}
\symdecl {vara}
\symdecl {varb}
\symdecl {varc}
\symdecl {vard}
\symdecl {vare}
\notation {vara}{a}
\notation {varb}{b}
\notation {varc}{c}
\notation {vard}{d}
\notation {vare}{e}
\notation [prec=500;500,args=a]{plus}{\withbrackets \langle \rangle {##1}}{+}

```

```

\notation [prec=600;600,args=a]{times}{##1}{\cdot }

```

$\frac{a}{b} \cdot \left(\frac{a}{b} + c \cdot (d + e) \right)$

$\frac{a}{b} \cdot \left(\frac{a}{b} + c \cdot (d + e) \right)$

$$\frac{a}{b} \cdot \left(\frac{a}{b} + c \cdot (d + e) \right)$$

2.6 sref

`\@sref@def` This macro stores the value of its last argument in a custom macro for reference.

```
1231 \newcommand\@sref@def[3]{\csgdef{sref@#1@#2}{#3}}
```

The next step is to set up a file to which the references are written, this is normally the `.aux` file, but if the `extref` option is set, we have to use an `.ref` file.

```
1232 \ifextrefs%
1233   \newwrite\refs@file%
1234 \else%
1235   \def\refs@file{\@auxout}%
1236 \fi%
```

`\sref@def` This macro writes an `\@sref@def` command to the current aux file and also executes it.

```
1237 \newcommand\sref@def[3]{%
1238   \protected@write\refs@file{}\string\@sref@def{#1}{#2}{#3}}%
1239 }%
```

`\sref@label` The `\sref@label` macro writes a label definition to the auxfile.

```
1240 \newcommand\sref@label[2]{%
1241   \sref@def{\ifcsundef{sref@part}{}\sref@part @}{#2}{page}{\thepage}%
1242   \sref@def{\ifcsundef{sref@part}{}\sref@part @}{#2}{label}{#1}%
1243 }%
```

`\sreflabel` The `\sreflabel` macro is a semantic version of `\label`, it combines the categorization given in the first argument with L^AT_EX's `\@currentlabel`.

```
1244 \newcommand\sreflabel[2]{\sref@label{#1 \@currentlabel}{#2}}
```

`\sref@label@id` The `\sref@label@id` writes a label definition for the current `\sref@id` if it is defined.

```
1245 \def\sref@id{} % make sure that defined
1246 \newcommand\sref@label@id[1]{%
1247   \ifx\sref@id\@empty%
1248     \relax%
1249   \else%
1250     \sref@label{#1}{\sref@id}%
1251   \fi%
1252 }%
```

2.7 smultiling

`modsig` The `modsig` environment is just a layer over the `module` environment. We also redefine macros that may occur in module signatures so that they do not create markup. Finally, we set the flag `\mod@<mod>@multiling` to true.

```
1253 \newenvironment{modsig}[2] []{\def\@test{#1}%
```

```

1254 \ifx\@test\@empty\begin{module}[name=#2]\else\begin{module}[name=#2,#1]\fi%
1255 \expandafter\gdef\csname mod@#2\multiling\endcsname{true}%
1256 \ignorespacesandpars}
1257 {\end{module}\ignorespacesandparsafterend}

```

2.8 smglom

`\gimport` Just a shortcut, we have a starred and unstarred version, the first one is conservative. For example, if we execute:

```
\gimport[smglom/numberfields]{naturalnumbers}
```

First we are redirected to `\@gimport@nostar`, we store the `smglom/numberfields` (*the repo's path*) in `\@test`, then store `\mh@currentrepos` (*current directory*) in `\mh@repos`. If no repo's path is offered, that means the module to import is under the same directory, so we let `mhrepos=\mh@repos` and pass bunch of parameters to `\importmhmodule`, which is defined in `module.sty`. If there's a repo's path, then we let `mhrepos=<the repo's path>`. Finally we use `\mhcurrentrepos` (defined in `module.sty`) to change the `\mh@currentrepos`.

```

1258 \def\gimport{\@ifstar\@gimport@star\@gimport@nostar}%
1259 \newrobustcmd\@gimport@star[2][\def\@test{#1}%
1260 \edef\mh@repos{\mh@currentrepos}%
1261 \ifx\@test\@empty%
1262 \importmhmodule[conservative,mhrepos=\mh@repos,path=#2]{#2}%
1263 \else\importmhmodule[conservative,mhrepos=#1,path=#2]{#2}\fi%
1264 \setcurrentreposinfo{\mh@repos}%
1265 \ignorespacesandpars\parsemodule@maybesetcodes}
1266 \newrobustcmd\@gimport@nostar[2][\def\@test{#1}%
1267 \edef\mh@repos{\mh@currentrepos}%
1268 \ifx\@test\@empty%
1269 \importmhmodule[mhrepos=\mh@repos,path=#2]{#2}%
1270 \else\importmhmodule[mhrepos=#1,path=#2]{#2}\fi%
1271 \setcurrentreposinfo{\mh@repos}%
1272 \ignorespacesandpars\parsemodule@maybesetcodes}

```

3 Things to deprecate

Module options:

```

1273 \addmetakey*{module}{id} % TODO: deprecate properly
1274 \addmetakey*{module}{load}
1275 \addmetakey*{module}{path}
1276 \addmetakey*{module}{dir}
1277 \addmetakey*{module}{align}[WithTheModuleOfTheSameName]
1278 \addmetakey*{module}{noalign}[true]
1279
1280 \newif\if@insymdef@\@insymdef@false

```

`symdef:keys` The optional argument `local` specifies the scope of the function to be defined. If `local` is not present as an optional argument then `\symdef` assumes the scope of the function is global and it will include it in the pool of macros of the current module. Otherwise, if `local` is present then the function will be defined only locally and it will not be added to the current module (i.e. we cannot inherit a local function). Note, the optional key `local` does not need a value: we write `\symdef[local]{somefunction}[0]{some expansion}`. The other keys are not used in the L^AT_EX part.

```

1281 %\srefaddidkey{symdef}% what does this do?
1282 \define@key{symdef}{local}[true]{\@symdeflocaltrue}%
1283 \define@key{symdef}{noverb}[all]{}%
1284 \define@key{symdef}{align}[WithTheSymbolOfTheSameName]{}%
1285 \define@key{symdef}{specializes}{}%
1286 \addmetakey*{symdef}{noalign}[true]
1287 \define@key{symdef}{primary}[true]{}%
1288 \define@key{symdef}{assocarg}{}%
1289 \define@key{symdef}{bvars}{}%
1290 \define@key{symdef}{bargs}{}%
1291 \addmetakey{symdef}{lang}%
1292 \addmetakey{symdef}{prec}%
1293 \addmetakey{symdef}{arity}%
1294 \addmetakey{symdef}{variant}%
1295 \addmetakey{symdef}{ns}%
1296 \addmetakey{symdef}{args}%
1297 \addmetakey{symdef}{name}%
1298 \addmetakey*{symdef}{title}%
1299 \addmetakey*{symdef}{description}%
1300 \addmetakey{symdef}{subject}%
1301 \addmetakey*{symdef}{display}%
1302 \addmetakey*{symdef}{gfc}%

```

EdN:1

1

`\symdef` The the `\symdef`, and `\@symdef` macros just handle optional arguments.

```

1303 \def\symdef{\@ifnextchar[{\@symdef}{\@symdef[]}}%
1304 \def\@symdef[#1]#2{\@ifnextchar[{\@@symdef[#1]{#2}}{\@@symdef[#1]{#2}[0]}}%

```

`\@@symdef` now comes the real meat: the `\@@symdef` macro does two things, it adds the macro definition to the macro definition pool of the current module and also provides it.

```

1305 \def\@@symdef[#1]#2[#3]{%
1306   \@insymdef@true%
1307   \metasetkeys{symdef}{#1}%
1308   \edef\symdef@tmp@optpars{\ifcvoid{symdef@name}{[]}{[name=\symdef@name]}}%
1309   \expandafter\symdecl\symdef@tmp@optpars{#2}%
1310   \@insymdef@false%
1311   \notation[#1]{#2}[#3]%
1312 }% mod@show

```

¹EdNOTE: MK@MK: we need to document the binder keys above.

```

1313 \def\symdef@type{Symbol}%
1314 \providecommand{\stDMemph}[1]{\textbf{#1}}

\symvariant \symvariant{<sym>}[<args>]{<var>}{<cseq>} just extends the internal macro
\modules@<sym>@pres@ defined by \symdef{<sym>}[<args>]{...} with a variant
\modules@<sym>@pres@<var> which expands to <cseq>. Recall that this is called
by the macro \<sym>[<var>] induced by the \symdef.

1315 \def\symvariant#1{%
1316   \ifnextchar[{\symvariant{#1}}{\symvariant{#1}[0]}%
1317   }%
1318 \def\@symvariant#1[#2]#3#4{%
1319   \notation[#3]{#1}[#2]{#4}%
1320 \ignorespacesandpars}%

\abbrdef The \abbrdef macro is a variant of \symdef that does the same on the LATEX
level.

1321 \let\abbrdef\symdef%

\@sym* has a starred form for primary symbols. The key/value interface has no effect on
the LATEX side. We read the to check whether only allowed ones are used.

1322 \newif\if@importing\@importingfalse
1323 \define@key{symi}{noverb}[all]{}%
1324 \define@key{symi}{align}[WithTheSymbolOfTheSameName]{}%
1325 \define@key{symi}{specializes}{}%
1326 \define@key{symi}{gfc}{}%
1327 \define@key{symi}{noalign}[true]{}%
1328 \newcommand\symi{\@ifstar\@symi@star\@symi}
1329 \newcommand\@symi[2][\metasetkeys{symi}{#1}%
1330   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2}\fi\ignorespaces
1331 \newcommand\@symi@star[2][\metasetkeys{symi}{#1}%
1332   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2}\fi\ignorespaces
1333 \newcommand\symii{\@ifstar\@symii@star\@symii}
1334 \newcommand\@symii[3][\metasetkeys{symi}{#1}%
1335   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2-#3}\fi\ignorespaces
1336 \newcommand\@symii@star[3][\metasetkeys{symi}{#1}%
1337   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2-#3}\fi\ignorespaces
1338 \newcommand\symiii{\@ifstar\@symiii@star\@symiii}
1339 \newcommand\@symiii[4][\metasetkeys{symi}{#1}%
1340   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2-#3-#4}\fi\ignorespaces
1341 \newcommand\@symiii@star[4][\metasetkeys{symi}{#1}%
1342   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2-#3-#4}\fi\ignorespaces
1343 \newcommand\symiv{\@ifstar\@symiv@star\@symiv}
1344 \newcommand\@symiv[5][\metasetkeys{symi}{#1}%
1345   \parsemodule@maybesetcodes\if@importing\else\par\noindent Symbol: \textsf{#2-#3-#4-#5}\fi\ignorespaces
1346 \newcommand\@symiv@star[5][\metasetkeys{symi}{#1}%
1347   \parsemodule@maybesetcodes\if@importing\else\par\noindent Primary Symbol: \textsf{#2-#3-#4-#5}\fi\ignorespaces

\importmhmodule The \importmhmodule[<key=value list>]{module} saves the current value of
\mh@currentrepos in a local macro \mh@@repos, resets \mh@currentrepos to

```


the new value if one is given in the optional argument, and after importing resets `\mh@currentrepos` to the old value in `\mh@@repos`. We do all the `\ifx` comparison with an `\expandafter`, since the values may be passed on from other key bindings. Parameters will be passed to `\importmodule`.

```

1348 %\srefaddidkey{importmhmodule}%
1349 \addmetakey{importmhmodule}{mhrepos}%
1350 \addmetakey{importmhmodule}{path}%
1351 \addmetakey{importmhmodule}{ext}% why does this exist?
1352 \addmetakey{importmhmodule}{dir}%
1353 \addmetakey[false]{importmhmodule}{conservative}[true]%
1354 \newcommand\importmhmodule[2][]{%
1355   \parsemodule@maybesetcodes
1356   \metasetkeys{importmhmodule}{#1}%
1357   \ifx\importmhmodule@dir\@empty%
1358     \edef\@path{\importmhmodule@path}%
1359   \else\edef\@path{\importmhmodule@dir/#2}\fi%
1360   \ifx\@path\@empty% if module name is not set
1361     \@importmodule[]{#2}{export}%
1362   \else%
1363     \edef\mh@@repos{\mh@currentrepos}% remember so that we can reset it.
1364     \ifx\importmhmodule@mhrepos\@empty% if in the same repos
1365       \relax% no need to change mh@currentrepos, i.e, current directory.
1366     \else%
1367       \setcurrentreposinfo\importmhmodule@mhrepos% change it.
1368       \addto@thismodule{\noexpand\setcurrentreposinfo{\importmhmodule@mhrepos}}%
1369     \fi%
1370     \@importmodule[\MathHub{\mh@currentrepos/source/\@path}]{#2}{export}%
1371     \setcurrentreposinfo\mh@@repos% after importing, reset to old value
1372     \addto@thismodule{\noexpand\setcurrentreposinfo{\mh@@repos}}%
1373   \fi%
1374   \ignorespacesandpars%
1375 }
```