

omtext: Semantic Markup for Mathematical Text Fragments in L^AT_EX*

Michael Kohlhase
Jacobs University, Bremen
<http://kwarc.info/kohlhase>

April 27, 2014

Abstract

The **omtext** package is part of the sT_EX collection, a version of T_EX/L^AT_EX that allows to markup T_EX/L^AT_EX documents semantically without leaving the document format, essentially turning T_EX/L^AT_EX into a document format for mathematical knowledge management (MKM).

This package supplies an infrastructure for writing OMDoc text fragments in L^AT_EX.

*Version v1.0 (last revised 2012/11/06)

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package Options	3
2.2	Mathematical Text	3
2.3	Phrase-Level Markup	3
2.4	Block-Level Markup	4
2.5	Index Markup	4
2.6	Support for MathHub	5
3	Limitations	6
4	Implementation	7
4.1	Package Options	7
4.2	Metadata	8
4.3	Mathematical Text	8
4.4	Phrase-level Markup	10
4.5	Block-Level Markup	11
4.6	Index Markup	12
4.7	L ^A T _E X Commands we interpret differently	15
4.8	Providing IDs for OMDoc Elements	15
4.9	Support for MathHub	18
4.10	Finale	18

1 Introduction

The `omtext` package supplies macros and environment that allow to mark up mathematical texts in \LaTeX , a version of \TeX / \LaTeX that allows to markup \TeX / \LaTeX documents semantically without leaving the document format, essentially turning \TeX / \LaTeX into a document format for mathematical knowledge management (MKM). The package supports direct translation to the OMDoc format [Koh06]

2 The User Interface

2.1 Package Options

`showmeta` The `omtext` package takes a single option: `showmeta`. If this is set, then the metadata keys are shown (see [Koh13a] for details and customization options).

2.2 Mathematical Text

`omtext` The `omtext` environment is used for any text fragment that has a contribution to a text that needs to be marked up. It can have a title, which can be specified via the `title=` key. Often it is also helpful to annotate the `type` key. The standard relations from rhetorical structure theory `abstract`, `introduction`, `conclusion`, `thesis`, `comment`, `antithesis`, `elaboration`, `motivation`, `evidence`, `transition`, `note`, `annotate` are recommended as values. Note that some of them are unary relations like `introduction`, which calls for a target. In this case, a target using the `for=` key should be specified. The `transition` relation is special in that it is binary (a “transition between two statements”), so additionally, a source should be specified using the `from=` key.

Note that the values of the `title` and `type` keys are often displayed in the text. This can be turned off by setting the `display` key to the value `flow`. Sometimes we want to specify that a text is a continuation of another, this can be done by giving the identifier of this in the `continues=` key.

Finally, there is a set of keys that pertain to the mathematical formulae in the text. The `functions` key allows to specify a list of identifiers that are to be interpreted as functions in the generate content markup. The `theory` specifies a module (see [KGA13a]) that is to be pre-loaded in this one¹ Finally, `verbalizes=` specifies a (more) formal statement (see [Koh13b]) that this text verbalizes or paraphrases.²

2.3 Phrase-Level Markup

`\phrase` The `phrase` macro allows to mark up phrases with semantic information. It takes an optional `KeyVal` argument with the keys `verbalizes` and `type` as above and `style`, `class`, `index` that are disregarded in the \LaTeX , but copied into the gen-

¹EDNOTE: this is not implemented yet.

²EDNOTE: MK:specify the form of the reference.

erated content markup.

`\sinlinequote` The `\sinlinequote` macro allows to mark up quotes inline and attribute them. The quote itself is given as the argument, possibly preceded by the a specification of the source in a an optional argument. For instance, we would quote Hamlet with

```
\sinlinequote[Hamlet, \cite{Shak:1603:Hamlet}]{To be or not to be}
```

which would appear as “*To be or not to be*” Hamlet, (Shakespeare 1603) in the text. The style in which inline quotations appear in the text can be adapted by specializing the macros `\@sinlinequote` — for quotations without source and `\@@sinlinequote` — for quotations with source.

`\@sinlinequote`
`\@@sinlinequote`

2.4 Block-Level Markup

`sblockquote` The `sblockquote` environment is the big brother of the `\sinlinequote` macro. It also takes an optional argument to specify the source. Here the four internal macros `\begin@sblockquote` to `\end@@sblockquote` are used for styling and can be adapted by package integrators. Here a quote of Hamlet would marked up as

`\begin@sblockquote`
`\end@@sblockquote`

```
\begin{sblockquote}[Hamlet, \cite{Shak:1603:Hamlet}]\obeylines
  To be, or not to be: that is the question:
  Whether 'tis nobler in the mind to suffer
\end{sblockquote}
```

and would render as

To be, or not to be: that is the question:
Whether 'tis nobler in the mind to suffer

Hamlet, (Shakespeare 1603)

`\lec` The `\lec` macro takes one argument and sets it as a comment at the end of the line, making sure that if the content is too long it is pushed into a new line. We use it internally for placing the of source of the `sblockquote` environment above. The
`\@@lec` actual appearance of the line end comment is determined by the `\@@lec` macro, which can be customized in the document class.

2.5 Index Markup

The `omtext` package provides some extensions for the well-known indexing macros of \LaTeX . The main reason for introducing these macros is that index markup in OMDoc wraps the indexed terms rather than just marking the spot for cross-referencing. Furthermore the index commands only indexes words unless the `noindex` option is set in the `\usepackage`. The `omtext` package and class make the usual `\index` macro undefined³.

`noindex`

`\indextoo` The `\indextoo` macro renders a word and marks it for the index. Sometimes, we want to index a slightly different form of the word, e.g. for non-standard plurals: while `\indextoo{word}s` works fine, we cannot use this for the word “datum”, which has the plural “data”. For this we have the macro `\indexalt`, which takes another argument for the displayed text, allowing us to use `\indexalt{data}{datum}`, which prints “data” but puts “datum” into the index.

The second set of macros adds an infrastructure for two-word compounds. Take for instance the compound “OMDoc document”, which we usually want to add into the index under “OMDoc” and “document”. `\twintoo{OMDoc}{document}` is a variant of `\indextoo` that will do just this. Again, we have a version that prints a variant: This is useful for situations like this the one in Figure 1:

We call group `\twinalt{Abelian}{Abelian}{group}`, iff `\ldots`

will result in the following

We call group Abelian, iff ...

and put “Abelian Group” into the index.

Example 1: Index markup

The third set of macros does the same for two-word compounds with adjectives, e.g. “wonderful OMDoc document”. `\atwin{wonderful}{OMDoc}{document}` will make the necessary index entries under “wonderful” and “document”. Again, we have a variant `\atwinalt` whose first argument is the alternative text.

All index macros take an optional first argument that is used for ordering the respective entries in the index.

2.6 Support for MathHub

Much of the \LaTeX content is hosted on MathHub (<http://MathHub.info>), a portal and archive for flexiformal mathematics. MathHub offers GIT repositories (public and private escrow) for mathematical documentation projects, online and offline authoring and document development infrastructure, and a rich, interactive reading interface. The `modules` package supports repository-sensitive operations on MathHub.

Note that MathHub has two-level repository names of the form $\langle group \rangle / \langle repo \rangle$, where $\langle group \rangle$ is a MathHub-unique repository group and $\langle repo \rangle$ a repository name that is $\langle group \rangle$ -unique. The file and directory structure of a repository is arbitrary – except that it starts with the directory `source` because they are Math Archives in the sense of [Hor+11]. But this structure can be hidden from the \LaTeX author with MathHub-enabled versions of the `modules` macros.

`\mhcgraphics` The `\mhcgraphics` macro is a variant of `\mycgraphics` with repository sup-

³EDNOTE: implement this and issue the respective error message

port. Instead of writing

```
\defpath{MathHub}{/user/foo/lmh/MathHub}  
\mycgraphics{\MathHub{fooMH/bar/source/baz/foobar}}
```

we can simply write (assuming that `\MathHub` is defined as above)

```
\mhcgraphics[fooMH/bar]{baz/foobar}
```

Note that the `\mhcgraphics` form is more semantic, which allows more advanced document management features in `MathHub`.

If `baz/foobar` is the “current module”, i.e. if we are on the `MathHub` path `...MathHub/fooMH/bar...`, then stating the repository in the first optional argument is redundant, so we can just use

```
\mhcgraphics{baz/foobar}
```

Of course, neither `LATEX` nor `LATEXML` know about the repositories when they are called from a file system, so we can use the `\mhcurrentrepos` macro from the `modules` package to tell them. But this is only needed to initialize the infrastructure in the driver file. In particular, we do not need to set it in each module, since the `\importmhmodule` macro sets the current repository automatically.

Caveat if you want to use the `MathHub` support macros (let’s call them mh-variants), then every time a module is imported or a document fragment is included from another repos, the mh-variant `\importmhmodule` must be used, so that the “current repository” is set accordingly. To be exact, we only need to use mh-variants, if the imported module or included document fragment use mh-variants.

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `gTEX` TRAC [sTeX].

1. none reported yet

4 Implementation

The `omtext` package generates two files: the \LaTeX package (all the code between `<*package>` and `</package>`) and the \LaTeX XML bindings (between `<*ltxml>` and `</ltxml>`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

4.1 Package Options

The initial setup for \LaTeX XML:

```
1 <*ltxml>
2 package LaTeXML::Package::Pool;
3 use strict;
4 use LaTeXML::Package;
5 use LaTeXML::Util::Pathname;
6 </ltxml>
```

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false).⁴

```
7 <*package>
8 \DeclareOption{showmeta}{\PassOptionsToPackage{\CurrentOption}{metakeys}}
9 \newif\ifindex\indextrue
10 \DeclareOption{noindex}{\indexfalse}
11 \ProcessOptions
12 \ifindex\makeindex\fi
13 </package>
14 <*ltxml>
15 DeclareOption('noindex','');
16 </ltxml>
```

Then we need to set up the packages by requiring the `sref` package to be loaded.

```
17 <*package>
18 \RequirePackage{sref}
19 \RequirePackage{xspace}
20 \RequirePackage{modules}
21 \RequirePackage{comment}
22 </package>
23 <*ltxml>
24 RequirePackage('sref');
25 RequirePackage('xspace');
26 RequirePackage('modules');
27 RequirePackage('lxRDFa');
28 </ltxml>
```

⁴EDNOTE: need an implementation for \LaTeX XML

4.2 Metadata

All the OMDoc elements allow to specify metadata in them, which is modeled by the `omdoc:metadata` element. Since the content of this element is precisely controlled by the Schema, we can afford to auto-open and auto-close it. Thus metadata elements from various sources will just be included into one `omdoc:metadata` element, even if they are supplied by different \TeX bindings. Also we add numbering and location facilities.

```
29 <*ltxml>
30 Tag('omdoc:metadata',afterOpen=>\&numberIt,afterClose=>\&locateIt,autoClose=>1,autoOpen=>1);
31 </ltxml>
```

the `itemize`, `description`, and `enumerate` environments generate `omdoc:li`, `omdoc:di` with `autoclose` inside a CMP. This behavior will be overwritten later, so we remember that we are in a CMP by assigning `_LastSeenCMP`.

```
32 <*ltxml>
33 Tag('omdoc:CMP', afterOpen => sub {AssignValue('_LastSeenCMP', $_[1], 'global');return;});#$
34 </ltxml>
```

the `itemize`, `description`, and `enumerate` environments originally introduced in the `omtext` package do double duty in OMDoc, outside a CMP they are transformed into a `<omgroup layout='itemizedescriptionenumerate'>`, where the text after the macros `\item` come to be the children. If that is only text, then it is enclosed in an `<omtext><CMP>`, otherwise it is left as it is. The optional argument of the `\item` is transformed into the `<metadata><dc:title>` of the generated `\item` element.

```
35 <*ltxml>
36 DefParameterType('IfBeginFollows', sub {
37   my ($gullet) = @_;
38   $gullet->skipSpaces;
39   my $next = $gullet->readToken;
40   $gullet->unread($next);
41   $next = ToString($next);
42   #Hm, falling back to regexp handling, the $gullet->ifNext approach didn't work
43   return 1 unless ($next=~/\begin/);
44   return;
45 },
46 reversion=>' ', optional=>1);
47 </ltxml>
```

4.3 Mathematical Text

We define the actions that are undertaken, when the keys are encountered. The first set just records metadata; this is very simple via the `\addmetakey` infrastructure [Koh13a]. Note that we allow math in the `title` field, so we do not declare it to be `Semiverbatim` (indeed not at all, which allows it by default).

```
48 <*package>
49 \srefaddidkey{omtext}
```



```

50 \addmetakey[] {omtext} {functions}
51 \addmetakey* {omtext} {display}
52 \addmetakey {omtext} {for}
53 \addmetakey {omtext} {from}
54 \addmetakey {omtext} {type}
55 \addmetakey* {omtext} {title}
56 \addmetakey* {omtext} {start}
57 \addmetakey {omtext} {theory}
58 \addmetakey {omtext} {continues}
59 \addmetakey {omtext} {verbalizes}
60 \addmetakey {omtext} {subject}
61 \end{package}
62 \begin{xml}
63 DefKeyVal('omtext','functions','CommaList');
64 DefKeyVal('omtext','display','Semiverbatim');
65 DefKeyVal('omtext','for','Semiverbatim');
66 DefKeyVal('omtext','from','Semiverbatim');
67 DefKeyVal('omtext','type','Semiverbatim');
68 DefKeyVal('omtext','title','Plain'); #Math mode in titles.
69 DefKeyVal('omtext','start','Plain'); #Math mode in start phrases
70 DefKeyVal('omtext','theory','Semiverbatim');
71 DefKeyVal('omtext','continues','Semiverbatim');
72 DefKeyVal('omtext','verbalizes','Semiverbatim');
73 \end{xml}

```

The next keys handle module loading (see [KGA13b]).

```

74 % \ednote{need to implement these in LaTeXML, I wonder whether there is a general
75 % mechanism like numberit.}\ednote{this needs to be rethought in the light of
76 % |usemodule|. It is probably obsolete. Is this used? Is this documented?}
77 \end{package}
78 \define@key{omtext}{require}{\requiremodules{#1}{sms}}
79 \define@key{omtext}{module}{\message{module: #1}\importmodule{#1}\def\omtext@theory{#1}}
80 \end{package}
81 \begin{xml}
82 \end{xml}

```

\st@flow We define this macro, so that we can test whether the `display` key has the value `flow`

```

83 \begin{package}
84 \def\st@flow{flow}
85 \end{package}

```

omtext The `omtext` environment is different, it does not have a keyword that marks it. Instead, it can have a title, which is used in a similar way. We redefine the `\lec` macro so the trailing `\par` does not get into the way.

```

86 \begin{package}
87 \def\omtext@pre@skip{\smallskip}
88 \def\omtext@post@skip{}
89 \providecommand{\stDMemph}[1]{\textbf{#1}}
90 \newenvironment{omtext}[1] [] {\bgroup\metasetkeys{omtext}{#1}\sref@label{id{this paragraph}}%

```

```

91 \def\lec##1{\@lec{##1}}%
92 \ifx\omtext@display\st@flow\else\omtext@pre@skip\par\noindent%
93 \ifx\omtext@title\@empty%
94 \ifx\omtext@start\@empty\else\stDMemph{\omtext@start}\xspace\fi%
95 \else\stDMemph{\omtext@title}:\xspace%
96 \ifx\omtext@start\@empty\else\omtext@start\xspace\fi%
97 \fi% \omtext@title empty
98 \fi% \omtext@display=flow
99 \ignorespaces}
100 {\egroup\omtext@post@skip}
101 \</package>
102 \<*ltxml>
103 DefEnvironment('omtext' OptionalKeyVals:omtext',
104   "<omdoc:omtext "
105     . "?&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id'))() "
106     . "?&GetKeyVal(#1,'type')(type='&GetKeyVal(#1,'type'))() "
107     . "?&GetKeyVal(#1,'for')(for='&GetKeyVal(#1,'for'))() "
108     . "?&GetKeyVal(#1,'from')(from='&GetKeyVal(#1,'from'))()>"
109     . "?&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
110     . "    "?&GetKeyVal(#1,'start')(<ltx:text class='startemph'>&GetKeyVal(#1,'start')</ltx:text>)"
111     . "    "#body"
112     . "</omdoc:omtext>");
113 \</ltxml>

```

4.4 Phrase-level Markup

\phrase For the moment, we do disregard the most of the keys

```

114 \<*package>
115 \srefaddidkey{phrase}
116 \addmetakey{phrase}{style}
117 \addmetakey{phrase}{class}
118 \addmetakey{phrase}{index}
119 \addmetakey{phrase}{verbalizes}
120 \addmetakey{phrase}{type}
121 \addmetakey{phrase}{only}
122 \newcommand\phrase[2][\metasetkeys{phrase}{#1}%
123 \ifx\phrase@only\@empty\only<\phrase@only>{#2}\else #2\fi}
124 \</package>
125 \<*ltxml>
126 DefKeyVal('phrase','id','Semiverbatim');
127 DefKeyVal('phrase','style','Semiverbatim');
128 DefKeyVal('phrase','class','Semiverbatim');
129 DefKeyVal('phrase','index','Semiverbatim');
130 DefKeyVal('phrase','verbalizes','Semiverbatim');
131 DefKeyVal('phrase','type','Semiverbatim');
132 DefKeyVal('phrase','only','Semiverbatim');
133 DefConstructor('phrase OptionalKeyVals:phrase {}',
134   "<ltx:text %&GetKeyVals(#1) ?&GetKeyVal(#1,'only')(rel='beamer:only' content='&GetKeyVal
135 \</ltxml>

```

nlex For the moment, we do disregard the most of the keys

```

136 <*package>
137 \def\nlex#1{\green{\sl{#1}}}
138 \def\nlcex#1{* \green{\sl{#1}}}
139 </package>
140 <*txml>
141 DefConstructor('\nlex{}',
142   "<ltx:text class='nlex'>#1</ltx:text>");
143 DefConstructor('\nlcex{}',
144   "<ltx:text class='nlcex'>#1</ltx:text>");
145 </txml>

```

sinlinequote

```

146 <*package>
147 \def\@sinlinequote#1{'\sl{#1}}'
148 \def\@sinlinequote#1#2{\@sinlinequote{#2}~#1}
149 \newcommand\sinlinequote[2]{}
150 {\def\@opt{#1}\ifx\@opt\empty\@sinlinequote{#2}\else\@sinlinequote\@opt{#2}\fi}
151 </package>
152 <*txml>
153 DefConstructor('\sinlinequote [] {}',
154   "<ltx:quote type='inlinequote'>"
155     . "?#1(<dc:source>#1</dc:source>\n)()"
156     . "#2"
157     . "</ltx:quote>");
158 </txml>

```

4.5 Block-Level Markup

sblockquote

```

159 <*package>
160 \def\begin@sblockquote{\begin{quote}\sl}
161 \def\end@sblockquote{\end{quote}}
162 \def\begin@sblockquote#1{\begin@sblockquote}
163 \def\end@sblockquote#1{\def\@lec##1{\rm ##1}\@lec{#1}\end@sblockquote}
164 \newenvironment{sblockquote}[1]{}
165 {\def\@opt{#1}\ifx\@opt\empty\begin@sblockquote\else\begin@sblockquote\@opt\fi}
166 {\ifx\@opt\empty\end@sblockquote\else\end@sblockquote\@opt\fi}
167 </package>
168 <*txml>
169 DefEnvironment('{sblockquote} []',
170   "<ltx:quote>?#1(<ltx:note role='source'>#1</ltx:note>())#body</ltx:quote>");
171 </txml>

```

The line end comment macro makes sure that it will not be forced on the next line unless necessary.

`\lec` The actual appearance of the line end comment is determined by the `\@@lec` macro, which can be customized in the document class. The basic one here is provided so that it is not missing.

```
172 <*package>
173 \providecommand{\@@lec}[1]{( #1 )}
174 \def\@lec#1{\strut\hfil\strut\null\nobreak\hfill\hbox{\@@lec{#1}}}
175 \def\lec#1{\@lec{#1}\par}
176 </package>
177 <*xml>
178 DefConstructor(' \lec{ } ',
179   "\n<omdoc:note type='line-end-comment'>#1</omdoc:note>");
180 </xml>
```

`\mygraphics` We set up a special treatment for including graphics to respect the intended OM-
Doc document structure. The main work is done in the transformation stylesheet
though.

```
181 <xml>RawTeX('
182 <*xml | package>
183 \newcommand\mygraphics[2] [] {\includegraphics[#1]{#2}}
184 \newcommand\mycgraphics[2] [] {\begin{center}\mygraphics[#1]{#2}\end{center}}
185 \newcommand\mybgraphics[2] [] {\fbox{\mygraphics[#1]{#2}}}
186 </xml | package>
187 <xml>');
```

4.6 Index Markup

`\omdoc@index` this is the main internal indexing command. It makes sure that the modules
necessary for interpreting the math in the index entries are loaded. If we are in
a module `<mod>`, then we do that by `\importmodule{<mod>}`, else we import all
the imported modules.

```
188 <*package>
189 \newcommand\omdoc@index[2] [] {\ifindex\def\@test{#1}%
190 \ifx\@test\@empty\def\@idx{#2}\else\def\@idx{#1}\fi%
191 \@bsphack\begingroup\@sanitize%
192 \@ifundefined{mod@id}% if we are not in a module
193 {\protected@write\@indexfile{}\string\indexentry%
194 {\@idx @\string\importmodules{\imported@modules}#2}{\thepage}}}%
195 {\protected@write\@indexfile{}\string\indexentry%
196 {\@idx @\string\importmodules{mod@id}#2}{\thepage}}}%
197 \endgroup\@esphack}
```

Now, we make two interface macros that make use of this:

```
\indexalt
198 \newcommand\indexalt[3] [] {{#2}\omdoc@index[#1]{#3}} % word in text and index
199 </package>
200 <*xml>
```

```

201 DefConstructor('\indextoo[]{}',
202     "<omdoc:idx>"
203     . " <omdoc:idt>#2</omdoc:idt>"
204     . " <omdoc:ide ?#1(sort-by='#1')(>"
205     . " <omdoc:idp>#2</omdoc:idp>"
206     . " </omdoc:ide>"
207     . "</omdoc:idx>");
208 </ltxml>

\indextoo
209 <*package>
210 \newcommand\indextoo[2] []{{#2}\omdoc@index[#1]{#2}} % word in text and index
211 </package>
212 <*ltxml>
213 DefConstructor('\indexalt[]{}{}',
214     "<omdoc:idx>"
215     . " <omdoc:idt>#2</omdoc:idt>"
216     . " <omdoc:ide ?#1(sort-by='#1')(>"
217     . " <omdoc:idp>#3</omdoc:idp>"
218     . " </omdoc:ide>"
219     . "</omdoc:idx>");
220 </ltxml>

\@twin this puts two-compound words into the index in various permutations
221 <*package>
222 \newcommand\@twin[3] []{{\ifindex\def\@test{#1}%%
223 \ifx\@test\@empty\def\@@idx{#2}\else\def\@@idx{#1}\fi%
224 \@ifundefined{mod@id}%
225 {\index{\@@idx @#2!#3}%
226 \ifx\@test\@empty\def\@@idx{#3}\else\def\@@idx{#1}\fi%
227 \index{\@@idx @#2!#3}}%
228 {\index{\@@idx @{\importmodule{\mod@id} #2}!\importmodule{\mod@id} #3}}%
229 \ifx\@test\@empty\def\@@idx{#3}\else\def\@@idx{#1}\fi%
230 \index{\@@idx @{\importmodule{\mod@id} #3}!\importmodule{\mod@id} #2}}\fi}}

```

And again we have two interface macros building on this

```

\twinalt
231 \newcommand\twinalt[4] []{{#2\@twin[#1]{#3}{#4}}
232 </package>
233 <*ltxml>
234 DefConstructor('\twintoo[]{}{}',
235     "<omdoc:idx>"
236     . " <omdoc:idt>#2 #3</omdoc:idt>"
237     . " <omdoc:ide ?#1(sort-by='#1')(>"
238     . " <omdoc:idp>#2</omdoc:idp>"
239     . " <omdoc:idp>#3</omdoc:idp>"
240     . " </omdoc:ide>"
241     . "</omdoc:idx>");
242 </ltxml>

```

\twinalt

```

243 \newcommand\twintoo[3][]{\ifindex\def\twin[#1]{#2}{#3}} % and use the word compound too
244 \package
245 \package
246 \package
247 DefConstructor('\twinalt[]{}{}{}',
248     "<omdoc:idx>"
249     . "<omdoc:idx>#2</omdoc:idx>"
250     . "<omdoc:ide ?#1(sort-by='#1')()>"
251     . "<omdoc:idx>#2</omdoc:idx>"
252     . "<omdoc:idx>#3</omdoc:idx>"
253     . "</omdoc:ide>"
254     . "</omdoc:idx>");
255 \package

```

EdN:5

\@atwin this puts adjectivized two-compound words into the index in various permutations⁵

```

256 \newcommand\@atwin[4][]{\ifindex\def\@test{#1}%
257 \ifx\@test\empty\def\@idx{#2}\else\def\@idx{#1}\fi%
258 \ifundefined{mod@id}%
259 \@ifundefined{mod@id}%
260 {\index{\@idx @#2!#3!#4}%
261 \ifx\@test\empty\def\@idx{#3}\else\def\@idx{#1}\fi%
262 \index{\@idx @#3!#2 (#4)}}%
263 {\index{\@idx @{\importmodule{\mod@id} #2}%
264 !{\importmodule{\mod@id} #3}!{\importmodule{\mod@id} #4}}%
265 \ifx\@test\empty\def\@idx{#3}\else\def\@idx{#1}\fi%
266 \index{\@idx @{\importmodule{\mod@id} #3}%
267 !{\importmodule{\mod@id} #2} ({\importmodule{\mod@id} #4})}\fi}}

```

and the two interface macros for this case:

\@atwin

```

268 \newcommand\atwinalt[5][]{\ifindex\def\@atwin[#1]{#2}{#3}{#4}{#5}}
269 \package
270 \package
271 DefConstructor('\atwinalt[]{}{}{}{}',
272     "<omdoc:idx>"
273     . "<omdoc:idx>#2</omdoc:idx>"
274     . "<omdoc:ide ?#1(sort-by='#1')()>"
275     . "<omdoc:idx>#2</omdoc:idx>"
276     . "<omdoc:idx>#3</omdoc:idx>"
277     . "<omdoc:idx>#4</omdoc:idx>"
278     . "</omdoc:ide>"
279     . "</omdoc:idx>");
280 \package

```

\atwintoo

```

281 \package

```

⁵EdNOTE: what to do with the optional argument here and below?

```

282 \newcommand\atwintoo[4][{}]{#2 #3 #4}\@atwin[#1]{#2}{#3}{#4}} % and use it too
283 \end{package}
284 \end{ltxml}
285 DefConstructor('\atwintoo[]{}{}{}',
286     "<omdoc:idx>"
287     . " <omdoc:idt>#2 #3</omdoc:idt>"
288     . " <omdoc:ide ?#1(sort-by='#1')()>"
289     . " <omdoc:idp>#2</omdoc:idp>"
290     . " <omdoc:idp>#3</omdoc:idp>"
291     . " <omdoc:idp>#4</omdoc:idp>"
292     . "</omdoc:ide>"
293     . "</omdoc:idx>");
294 \end{ltxml}

```

4.7 L^AT_EX Commands we interpret differently

The first think we have to take care of are the paragraphs, we want to generate OMDoc that uses the `ltx:p` element for paragraphs inside CMPs. For that we have modified the DTD only to allowed `ltx:p` elements in `omdoc:CMP` (in particular no text). Then we instruct the `\par` macro to close a `ltx:p` element if possible. The next `ltx:p` element is then opened automatically, since we make `ltx:p` and `omdoc:CMP` autoclose and autoopen.

```

295 \end{ltxml}
296 Tag('omdoc:CMP', autoClose=>1, autoOpen=>1);
297 Tag('omdoc:omtext', autoClose=>1, autoOpen=>1);
298 Tag('ltx:p', autoClose=>1, autoOpen=>1);
299 \end{ltxml}

```

the rest of the reinterpretations is quite simple, we either disregard presentational markup or we re-interpret it in terms of OMDoc.⁶

```

300 \end{package}
301 \def\omspace#1{\hspace*{#1}}
302 \end{package}
303 \end{ltxml}
304 DefConstructor('\footnote[]{}',
305     "<omdoc:note type='foot' ?#1(mark='#1')>#2</omdoc:note>");
306 DefConstructor('\footnotemark[]{}', "");
307 DefConstructor('\footnotetext[]{}',
308     "<omdoc:note class='foot' ?#1(mark='#1')>#2</omdoc:note>");
309 \end{ltxml}

```

4.8 Providing IDs for OMDoc Elements

To provide default identifiers, we tag all OMDoc elements that allow `xml:id` attributes by executing the `numberIt` procedure below. Furthermore, we use the `locateIt` procedure to give source links.

⁶EDNOTE: MK: we should probably let LaTeXXML deal with these and allow more text in the `omdoc+ltxml.xsl`

```

310 <*ltxml>
311 Tag('omdoc:omtext',afterOpen=>\&numberIt,afterClose=>\&locateIt);
312 Tag('omdoc:omgroup',afterOpen=>\&numberIt,afterClose=>\&locateIt);
313 Tag('omdoc:CMP',afterOpen=>\&numberIt,afterClose=>\&locateIt);
314 Tag('omdoc:idx',afterOpen=>\&numberIt,afterClose=>\&locateIt);
315 Tag('omdoc:ide',afterOpen=>\&numberIt,afterClose=>\&locateIt);
316 Tag('omdoc:idt',afterOpen=>\&numberIt,afterClose=>\&locateIt);
317 Tag('omdoc:note',afterOpen=>\&numberIt,afterClose=>\&locateIt);
318 Tag('omdoc:metadata',afterOpen=>\&numberIt,afterClose=>\&locateIt);
319 Tag('omdoc:meta',afterOpen=>\&numberIt,afterClose=>\&locateIt);
320 Tag('omdoc:resource',afterOpen=>\&numberIt,afterClose=>\&locateIt);
321 Tag('omdoc:recurse',afterOpen=>\&numberIt,afterClose=>\&locateIt);
322 Tag('omdoc:imports',afterOpen=>\&numberIt,afterClose=>\&locateIt);
323 Tag('omdoc:theory',afterOpen=>\&numberIt,afterClose=>\&locateIt);
324 Tag('omdoc:ignore',afterOpen=>\&numberIt,afterClose=>\&locateIt);
325 Tag('omdoc:ref',afterOpen=>\&numberIt,afterClose=>\&locateIt);
326 </ltxml>

```

We also have to number some L^AT_EX XML tags, so that we do not get into trouble with the OMDoc tags inside them.

```

327 <*ltxml>
328 Tag('ltx:p',afterOpen=>\&numberIt,afterClose=>\&locateIt);
329 Tag('ltx:tabular',afterOpen=>\&numberIt,afterClose=>\&locateIt);
330 Tag('ltx:thead',afterOpen=>\&numberIt,afterClose=>\&locateIt);
331 Tag('ltx:td',afterOpen=>\&numberIt,afterClose=>\&locateIt);
332 Tag('ltx:tr',afterOpen=>\&numberIt,afterClose=>\&locateIt);
333 Tag('ltx:caption',afterOpen=>\&numberIt,afterClose=>\&locateIt);
334 Tag('ltx:Math',afterOpen=>\&numberIt,afterClose=>\&locateIt);
335 </ltxml>

```

The `numberIt` procedure gets the prefix from first parent with an `xml:id` attribute and then extends it with a label that reflects the number of preceding siblings, provided that there is not already an identifier. Additionally, it estimates an XPointer position in the original document of the command sequence which produced the tag. The `locateIt` subroutine is a sibling of `numberIt` as it is required as an `afterClose` handle for tags produced by L^AT_EX environments, as opposed to commands. `locateIt` estimates an XPointer end position of the LaTeX environment, allowing to meaningfully locate the entire environment at the source.

```

336 <*ltxml>
337 sub numberIt {
338   my($document,$node,$whatsit)=@_;
339   my(@parents)=$document->findnodes('ancestor::*[@xml:id]', $node);
340   my $prefix= (@parents ? $parents[$#parents]->getAttribute('xml:id')."." : '');
341   my(@siblings)=$document->findnodes('preceding-sibling::*[@xml:id]', $node);
342   my $n = scalar(@siblings)+1;
343   my $id = ($node -> getAttribute('xml:id'));
344   my $localname = $node->localname;
345   $node->setAttribute('xml:id'=>$prefix."$localname$n") unless $id;
346   my $about = $node -> getAttribute('about');
347   $node->setAttribute('about'=>'#'.$node->getAttribute('xml:id')) unless $about;

```



```

348 #Also, provide locators:
349 my $locator = $whatsit->getProperty('locator');
350 #Need to inherit locators if missing:
351 $locator = (@parents ? $parents[$#parents]->getAttribute('stex:srcref') : '') unless $locator
352 if ($locator) {
353     # There is a BUG with namespace declarations (or am I using the API wrongly??) which
354     # does not recognize the stex namespace. Hence, I need to redeclare it...
355     my $parent=$document->getNode;
356     if(! defined $parent->lookupNamespacePrefix("http://kwarc.info/ns/sTeX"))
357     { # namespace not already declared?
358         $document->getDocument->documentElement->setNamespace("http://kwarc.info/ns/sTeX","stex")
359     }
360     $node->setAttribute('stex:srcref'=>$locator);
361 }return;}
362
363 sub locateIt {
364     my($document,$node,$whatsit)=@_;
365     #Estimate trailer and locator:
366     my $locator = $node->getAttribute('stex:srcref');
367     return unless $locator; # Nothing to do here...
368     my $trailer = $whatsit->getProperty('trailer');
369     $trailer = $trailer->getLocator if $trailer;
370     $trailer = $locator unless $trailer; # bootstrap
371     # TODO: Both should be local, or both remote, any mixture or undefinedness will produce garba
372     my $file_path = LookupValue('SOURCEFILE');
373     my $baselocal = LookupValue('BASELOCAL');
374     # Hmm, we only care about relative paths, so let's just do a URL->pathname map
375     $file_path=~s/^\w+:\:\/\/ if $file_path;
376     $baselocal=~s/^\w+:\:\/\/ if $baselocal;
377     if ($file_path && $baselocal && ($locator =~ s/^(~\#)\#\/\#\/)) {
378         my $relative_path = pathname_relative($file_path,$baselocal);
379         $locator = $relative_path.$locator;
380     }
381     if ($locator =~ /\^(.+from=\d+;\d+)/) {
382         my $from = $1;
383         if ($trailer =~ /\^(,to=\d+;\d+.)$/)) {
384             my $to = $1;
385             $locator = $from.$to;
386         } else { Error("stex","locator",undef, "Trailer is garbled, expect nonsense in stex:srcref")
387     } else { Error("stex","locator",undef, "Locator \"$locator\" is garbled, expect nonsense in s
388     my $parent = $document->getNode;
389     if(! defined $parent->lookupNamespacePrefix("http://kwarc.info/ns/sTeX"))
390     { # namespace not already declared?
391         $document->getDocument->documentElement->setNamespace("http://kwarc.info/ns/sTeX","stex",
392     }
393     $node->setAttribute('stex:srcref' => $locator);
394     return;
395 }
396 </txml>#$

```

4.9 Support for MathHub

`\mh*graphics` Use the current value of `\mh@currentrepos` or the value of the `mhrepos` key if it is given in `\my*graphics`.

```

397 <*package>
398 \addmetakey{Gin}{mhrepos}
399 \newcommand\mhgraphics[2] [] {\metasetkeys{Gin}{#1}%
400 \ifx\Gin@mhrepos\empty\mygraphics[#1]{\MathHub{\mh@currentrepos/source/#2}}%
401 \else\mygraphics[#1]{\MathHub{\Gin@mhrepos/source/#2}}\fi}
402 \newcommand\mhgraphics[2] [] {\begin{center}\mhgraphics[#1]{#2}\end{center}}
403 \newcommand\mhgraphics[2] [] {\fbox{\mhgraphics[#1]{#2}}}
404 </package>
405 <*ltxml>
406 sub mhgraphics {
407   my ($gullet,$keyval,$arg2) = @_;
408   my $repo_path;
409   if ($keyval) {
410     $repo_path = ToString(GetKeyVal($keyval,'mhrepos')); }
411   if (! $repo_path) {
412     $repo_path = ToString(Digest(T_CS('\mh@currentrepos'))); }
413   else {
414     $keyval->setValue('mhrepos',undef); }
415   my $mathhub_base = ToString(Digest('\MathHub{ }'));
416   my $finalpath = $mathhub_base.$repo_path.'/source/'.ToString($arg2);
417   return Invocation(T_CS('@includegraphicx'), $keyval, T_OTHER($finalpath)); }##$
418 DefKeyVal('Gin','mhrepos','Semiverbatim');
419 DefMacro('\mhgraphics OptionalKeyVals:Gin { }', \&mhgraphics);
420 DefMacro('\mhgraphics [] { }', '\begin{center}\mhgraphics[#1]{#2}\end{center}');
421 DefMacro('\mhgraphics [] { }', '\fbox{\mhgraphics[#1]{#2}}');
422 </ltxml>

```

4.10 Finale

We need to terminate the file with a success mark for perl.

```

423 <ltxml>1;

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Abelian		Abelian	
group,	<i>5</i>	group,	<i>5</i>

References

- [Hor+11] Fulya Horozal et al. “Combining Source, Content, Presentation, Narration, and Relational Representation”. In: *Intelligent Computer Mathematics*. Ed. by James Davenport et al. LNAI 6824. Springer Verlag, 2011, pp. 212–227. ISBN: 978-3-642-22672-4. URL: http://kwarc.info/frabe/Research/HIJKR_dimensions_11.pdf.
- [KGA13a] Michael Kohlase, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Tech. rep. 2013. URL: <https://svn.kwarc.info/repos/stex/trunk/sty/modules/modules.pdf>.
- [KGA13b] Michael Kohlase, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2013. URL: <http://www.ctan.org/get/macros/latex/contrib/stex/modules/modules.pdf>.
- [KGA13c] Michael Kohlase, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Self-documenting L^AT_EX package. 2013.
- [Koh06] Michael Kohlase. OMDOC – *An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh13a] Michael Kohlase. *metakeys.sty: A generic framework for extensible Metadata in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2013. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/metakeys/metakeys.pdf>.
- [Koh13b] Michael Kohlase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. 2013. URL: <https://svn.kwarc.info/repos/stex/trunk/sty/statements/statements.pdf>.
- [sTeX] *Semantic Markup for L^AT_EX*. Project Homepage. URL: <http://trac.kwarc.info/sTeX/> (visited on 02/22/2011).