

# `smglom.cls/sty`: Semantic Multilingual Glossary for Math

Michael Kohlhase  
Jacobs University, Bremen  
<http://kwarc.info/kohlhase>

April 26, 2014

## Abstract

The `smglom` package is part of the  $\text{\LaTeX}$  collection, a version of  $\text{\TeX}/\text{\LaTeX}$  that allows to markup  $\text{\TeX}/\text{\LaTeX}$  documents semantically without leaving the document format, essentially turning  $\text{\TeX}/\text{\LaTeX}$  into a document format for mathematical knowledge management (MKM).

This package supplies an infrastructure for writing OMDoc glossary entries.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>The User Interface</b>	<b>2</b>
2.1	Package and Class Options . . . . .	2
<b>3</b>	<b>Implementation: The SMGloM Class</b>	<b>3</b>
3.1	Class Options . . . . .	3
3.2	For Module Definitions . . . . .	4
3.3	For Language Bindings . . . . .	5

## **1 Introduction**

## **2 The User Interface**

### **2.1 Package and Class Options**

`smglom.cls` accepts all options of the `omdoc.cls` and `article.cls` and just passes them on to these.

## 3 Implementation: The SMGloM Class

### 3.1 Class Options

To initialize the `smglom` class, we pass on all options to `omdoc.cls`

```
1 <*cls>
2 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{omdoc}}
3 \ProcessOptions
4 </cls>
5 <*ltxml.cls | ltxml.sty>
6 # -*- CPERL -*-
7 package LaTeXML::Package::Pool;
8 use strict;
9 use LaTeXML::Package;
10 DeclareOption(undef,sub {PassOptions('article','cls',ToString(Digest(T_CS('\CurrentOption'))));
11 ProcessOptions();
12 </ltxml.cls | ltxml.sty>
```

We load `omdoc.cls`, and the desired packages. For the  $\text{\LaTeX}$ ML bindings, we make sure the right packages are loaded.

```
13 <*cls>
14 \LoadClass{omdoc}
15 \RequirePackage{smglom}
16 </cls>
17 <*sty>
18 \RequirePackage{amstext}
19 \RequirePackage{modules}
20 \RequirePackage{dcm}
21 \RequirePackage{statements}
22 \RequirePackage{sproof}
23 \RequirePackage{cmath}
24 \RequirePackage{presentation}
25 \RequirePackage{amsfonts}
26 </sty>
27 <*ltxml.cls>
28 LoadClass('omdoc');
29 RequirePackage('smglom');
30 </ltxml.cls>
31 <*ltxml.sty>
32 RequirePackage('amstext');
33 RequirePackage('modules');
34 RequirePackage('dcm');
35 RequirePackage('statements');
36 RequirePackage('cmath');
37 RequirePackage('presentation');
38 RequirePackage('amsfonts');
39 </ltxml.sty>
```

## 3.2 For Module Definitions

**gimport** just a shortcut

```

40 <ltxml.sty>RawTeX(
41 <*sty | ltxml.sty>
42 \newcommand\gimport[2] [] {\def\@test{#1}%
43 \edef\mh@@repos{\mh@currentrepos}%
44 \ifx\@test\@empty\importmhmodule[repos=\mh@@repos,ext=tex,path=#2]{#2}%
45 \else\importmhmodule[repos=#1,ext=tex,path=#2]{#2}\fi
46 \mhcurrentrepos\mh@@repos\ignorespaces}

```

**guse** just a shortcut

```

47 \newcommand\guse[2] [] {\def\@test{#1}%
48 \edef\mh@@repos{\mh@currentrepos}%
49 \ifx\@test\@empty\usemhmodule[repos=\mh@@repos,ext=tex,path=#2]{#2}%
50 \else\usemhmodule[repos=#1,ext=tex,path=#2]{#2}\fi
51 \mhcurrentrepos\mh@@repos\ignorespaces}

```

**gadopt** just a shortcut

```

52 \newcommand\gadopt[2] [] {\def\@test{#1}%
53 \edef\mh@@repos{\mh@currentrepos}%
54 \ifx\@test\@empty\adoptmhmodule[repos=\mh@@repos,ext=tex,path=#2]{#2}%
55 \else\adoptmhmodule[repos=#1,ext=tex,path=#2]{#2}\fi
56 \mhcurrentrepos\mh@@repos\ignorespaces}

```

**gview** The **gview** environment is just a layer over the **view** environment with the keys suitably adapted.

```

57 \newenvironment{gview}[3] [] {\metasetkeys{mhview}{#1}\def\@test{#1}%
58 \edef\from@repos{\ifx\mhview@fromrepos\@empty\mh@currentrepos\else\mhview@fromrepos\fi}%
59 \edef\to@repos{\ifx\mhview@to@repos\@empty\mh@currentrepos\else\mhview@to@repos\fi}%
60 \ifx\@test\@empty%
61 \begin{mhview}[fromrepos=\from@repos,frompath=#2,torepos=\to@repos,topath=#3,ext=tex]{#2}{#3}%
62 \else%
63 \begin{mhview}[fromrepos=\from@repos,frompath=#2,torepos=\to@repos,topath=#3,ext=tex]{#2}{#3}%
64 \fi}
65 {\end{mhview}}
66 </sty | ltxml.sty>
67 <ltxml.sty>');

```

**symbol** has a starred form for primary symbols. Both do nothing.

```

68 <*sty>
69 \def\symbol{\@ifstar\@gobble\@gobble}
70 </sty>
71 <*ltxml.sty>
72 DefConstructor('\symbol OptionalMatch:* {}',
73 " <omdoc:symbol ?#1(role='primary')(role='secondary') name='#2'/>");
74 </ltxml.sty>

```

**\*nym**

```

75 <*sty>
76 \newcommand\hypernym[3] [] {#2 is a hypernym of #3}
77 \newcommand\hyponym[3] [] {#2 is a hyponym of #3}
78 \newcommand\meronym[3] [] {#2 is a meronym of #3}
79 </sty>
80 <*ltxml.sty>
81 DefConstructor('\hypernym [] {}{}', "");
82 DefConstructor('\hyponym [] {}{}', "");
83 DefConstructor('\meronym [] {}{}', "");
84 </ltxml.sty>

```

EdN:1 \MSC to define the Math Subject Classification, <sup>1</sup>

```

85 <*sty>
86 \newcommand\MSC{\@gobble}
87 </sty>
88 <*ltxml.sty>
89 DefConstructor('\MSC{}', "");
90 </ltxml.sty>

```

### 3.3 For Language Bindings

This functionality must be moved to the `smultiling` package.

**gviewsketch** The `gviewsketch` environment is just a layer over the `viewsketch` environment with the keys suitably adapted.

```

91 <ltxml.sty>RawTeX(
92 <*sty | ltxml.sty>
93 \newenvironment{gviewsketch}[3] [] {\def\@test{#1}%
94 \ifx\@test\@empty%
95 \begin{viewsketch}[from=#2,to=#3]{#2}{#3}\else%
96 \begin{viewsketch}[from=#2,to=#3,#1]{#2}{#3}\fi}
97 {\end{viewsketch}}

```

**gve** The `gve` environment is just a layer over the `gviewsketch` environment with the keys and language suitably adapted.

```

98 \newenvironment{gve}[5] [] {\def\@test{#1}%
99 \ifx\@test\@empty%
100 \begin{gviewsketch}[id=#2.#3]{#4}{#5}\else%
101 \begin{gviewsketch}[id=#2.#3,#1]{#4}{#5}\fi}
102 \smg@select@language{#3}}
103 {\end{gviewsketch}}
104 </sty | ltxml.sty>
105 <ltxml.sty>');

```

---

<sup>1</sup>EdNOTE: MK: what to do for the LaTeXML side?