

# **tikzinput: Selective Input of TIKZ Pictures\***

Michael Kohlhasse  
Jacobs University, Bremen  
<http://kwarc.info/kohlhasse>

October 22, 2015

## **Abstract**

Running `tikz` takes a lot of time in  $\text{\LaTeX}$ ML, therefore it is often more efficient externalize the TIKZ pictures into separate (standalone) files, to let  $\text{\LaTeX}$  handle the TIKZ pictures to generate an image, and just load it via the usual  $\text{\LaTeX}$  graphics packages. The `tikzinput` package supports this workflow, and allows to switch back to native TIKZ via a package option.

## **Contents**

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>The User Interface</b>	<b>2</b>
2.1	Package Options . . . . .	2
2.2	Inputting Standalone TIKZ Pictures . . . . .	2
<b>3</b>	<b>Limitations</b>	<b>3</b>
<b>4</b>	<b>Implementation</b>	<b>4</b>
4.1	Package Options and Required Packages . . . . .	4
4.2	Inputting Standalone TIKZ Pictures . . . . .	4
<b>5</b>	<b>Finale</b>	<b>5</b>

---

\*Version v1.0 (last revised 2015/10/22)

# 1 Introduction

Running `tikz` takes a lot of time in  $\text{\LaTeX}$ ML, therefore it is often more efficient externalize the TIKZ pictures into separate (standalone) files, to let  $\text{\LaTeX}$  handle the TIKZ pictures to generate an image, and just load it via the usual  $\text{\LaTeX}$  graphics packages. The `tikzinput` package supports this workflow, and allows to switch back to native TIKZ via a package option.

A side-effect of the workflow described above is that the TIKZ pictures can be developed – and formatted – independently of the document they are intended for. They can essentially be treated like an image file, which can be included into multiple documents.

## 2 The User Interface

### 2.1 Package Options

`image` The behavior of the `tikzinput` package is determined by whether the `image` option is given. If it is not, then the `tikz` package is loaded, all other options are passed on to it and `\tikzinput{<file>}` inputs the TIKZ file `<file>.tex`; if not, only the `graphicx` package is loaded and `\tikzinput{<file>}` loads an image file `<file>.<ext>` generated from `<file>.tex`.

### 2.2 Inputting Standalone TIKZ Pictures

The selective input functionality of the `tikzinput` package assumes that the TIKZ pictures are externalized into a standalone picture file, such as the one Example 1.

```
\documentclass{standalone}
\usepackage{tikz}
\usetikzpackage{...}
\begin{document}
  \begin{tikzpicture}
    ...
  \end{tikzpicture}
\end{document}
```

**Example 1:** A Standalone TIKZ Picture File

The `standalone` class is a minimal  $\text{\LaTeX}$  class that when loaded in a document that uses the `standalone` package: the preamble and the `document` environment are disregarded during loading, so they do not pose any problems. In effect, an `\input` of the file in Figure 1 only sees the `tikzpicture` environment, but the file itself is standalone in the sense that we can run  $\text{\LaTeX}$  over it separately, e.g. for generating an image file from it.

`\tikzinput` This is exactly where the `tikzinput` package comes in: it supplies the `\tikzinput` macro, which – depending on the `image` option – either directly inputs

the TIKZ picture (source) or tries to load an image file generated from it.

Concretely, if the `image` option is not set for the `tikzinput` package, then `\tikzinput[opt]{file}` disregards the optional argument *opt* and inputs *file*.tex via `\input`. If it is, `\tikzinput[opt]{file}` expands to `\includegraphics[opt]{file}`.

### 3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `TeX` GitHub repository [sTeX].

1. none reported yet

## 4 Implementation

General Setup for L<sup>A</sup>T<sub>E</sub>XML:

```
1 <*lxml>
2 package LaTeXML::Package::Pool;
3 use strict;
4 use LaTeXML::Package;
5 use Unicode::Normalize;
6 </lxml>
```

### 4.1 Package Options and Required Packages

`\iftikzinput@image` We define a new switch `\iftikzinput@image` and the image option

```
7 <*package>
8 \newif\iftikzinput@image\tikzinput@imagefalse
9 \DeclareOption{image}{\tikzinput@imagetrue}
10 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{tikz}}
11 \ProcessOptions
12 </package>
13 <*lxml>
14 DeclareOption('image', sub { AssignValue('tikzinput@image' => 1); });
15 DeclareOption(undef, sub { PassOptions('tikz', 'sty', ToString(Digest(T_CS('\CurrentOption')))); });
16 ProcessOptions();
17 </lxml>
```

Next we require the packages we need.

```
18 <*package>
19 \RequirePackage{sref}
20 \iftikzinput@image
21 \RequirePackage{graphicx}
22 \else
23 \RequirePackage{tikz}
24 \RequirePackage{standalone}
25 \fi
26 </package>
27 <*lxml>
28 RequirePackage('sref');
29 if (LookupValue('tikzinput@image')) {
30 RequirePackage('graphicx');}
31 else {
32 RequirePackage('tikz');
33 RequirePackage('standalone');}
34 </lxml>
```

### 4.2 Inputting Standalone TIKZ Pictures

`\tikzinput` Depending on the image option, we do the necessary things.

```
35 <*package>
36 \iftikzinput@image
```

```

37 \newcommand\tikzinput[2] [] {\includegraphics[#1]{#2}}
38 \else
39 \newcommand\tikzinput[2] [] {\input{#2}}
40 \fi
41 \</package>
42 \<*lxml>
43 if (LookupValue('tikzinput@image')) {
44 DefMacro('tikzinput[] {}', '\includegraphics[#1]{#2}');}
45 else {DefMacro('tikzinput[] {}', '\input{#2}');}
46 \</lxml>

\*tikzinput The variants we define in terms of \tikzinput.
47 \<lxml>RawTeX('
48 \<*package | lxml>
49 \newcommand\ctikzinput[2] [] {\begin{center}\tikzinput{#2}\end{center}}
50 \addmetakey{Gin}{mhrepos}
51 \newcommand\mhtikzinput[2] [] {\metasetkeys{Gin}{#1}%
52 \edef\mh@@repos{\mh@currentrepos}%
53 \ifx\Gin@mhrepos\@empty\tikzinput[#1]{\MathHub{\mh@currentrepos/source/#2}}%
54 \else\tikzinput[#1]{\MathHub{\Gin@mhrepos/source/#2}}\fi
55 \def\Gin@mhrepos{\mhcurrentrepos\mh@@repos}
56 \newcommand\cmhtikzinput[2] [] {\begin{center}\mhtikzinput[#1]{#2}\end{center}}
57 \</package | lxml>
58 \<lxml>');

```

## 5 Finale

We need to terminate the file with a success mark for perl.

```

59 \<lxml>1;

```

## References

[sTeX] *KWARC/sTeX*. URL: <https://github.com/KWARC/sTeX> (visited on 05/15/2015).