

Slides and Course Notes for Jacobs University*

Michael Kohlhasse
Jacobs University, Bremen
<http://kwarc.info/kohlhasse>

November 16, 2015

Abstract

We present a document class from which we can generate both course slides and course notes in a transparent way. Furthermore, we present a set of L^AT_EX XML bindings for these, so that we can also generate OMDoc-based course materials, e.g. for inclusion in the ACTIVEMATH system.

Contents

1	Introduction	2
2	The User Interface	2
2.1	Package Options	2
2.2	Notes and Slides	2
2.3	Header and Footer Lines	3
2.4	Colors and Highlighting	3
2.5	Front Matter, Titles, etc	3
2.6	Miscellaneous	3
3	Limitations	3
4	The Implementation	4
4.1	Class and Package Options	4
4.2	Notes and Slides	6
4.3	Header and Footer Lines	9
4.4	Colors and Highlighting	11
4.5	Front Matter, Titles, etc	12
4.6	Sectioning	12
4.7	Miscellaneous	13
4.8	Finale	15

*Version ? (last revised ?)

1 Introduction

This Document class is derived from `beamer.cls` [`beamerclass:on`], specializes it with Jacobs stuff and adds a notes version that is more suited to printing than the one supplied by `beamer.cls`.

2 The User Interface

The `mikoslides` class takes the notion of a slide frame from Till Tantau's excellent `beamer` class and adapts its notion of frames for use in the \TeX and OMDoc. To support semantic course notes, it extends the notion of mixing frames and explanatory text, but rather than treating the frames as images (or integrating their contents into the flowing text), the `mikoslides` package displays the slides as such in the course notes to give students a visual anchor into the slide presentation in the course (and to distinguish the different writing styles in slides and course notes).

In practice we want to generate two documents from the same source: the slides for presentation in the lecture and the course notes as a narrative document for home study. To achieve this, the `mikoslides` class has two modes: *slides mode* and *notes mode* which are determined by the package option.


2.1 Package Options

The `mikoslides` class takes a variety of class options:¹

- The options `slides` and `notes` switch between slides mode and notes mode (see Section 2.2).
- If the option `sectocframes` is given, then special frames with section table of contents are produced headers²
- `showmeta`. If this is set, then the metadata keys are shown (see [`Kohlhase:metakeys:ctan`] for details and customization options).
- If the option `frameimages` is set, then slide mode also shows the `\frameimage`-generated frames.

2.2 Notes and Slides

Slides are represented with the `frame` just like in the `beamer` class, see [`Tantau:ugbc`] for details. The `mikoslides` class adds the `note` environment for encapsulating the course note fragments.¹

 Note that it is essential to start and end the `notes` environment at the start of the line – in particular, there may not be leading blanks – else \LaTeX becomes confused and throws error messages that are difficult to decipher.

¹EDNOTE: leaving out `noproblems` for the moment until we decide what to do with it.

²EDNOTE: document the functionality

¹MK: it would be very nice, if we did not need this environment, and this should be possible in principle, but not without intensive \LaTeX trickery. Hints to the author are welcome.

```

\begin{note}
  We start this course with ...
\end{note}

\begin{frame}
  \frametitle{The first slide}
  ...
\end{frame}
\begin{note}
  ... and more explanatory text
\end{note}

\begin{frame}
  \frametitle{The second slide}
  ...
\end{frame}
...

```

Example 1: A typical Course Notes File

By interleaving the `frame` and `note` environments, we can build course notes as shown in Figure 1.

Sometimes, we want to integrate slides as images after all – e.g. because we already have a PowerPoint presentation, to which we want to add `TeX`notes. In this case we can use `\frameimage[⟨opt⟩]{⟨path⟩}`, where `⟨opt⟩` are the options of `\includegraphics` from the `graphicx` package [CarRah:tpp99] and `⟨path⟩` is the file path (extension can be left off like in `\includegraphics`).

`\frameimage`

2.3 Header and Footer Lines

2.4 Colors and Highlighting

`\textwarning` The `\textwarning` macro generates a warning sign: 

2.5 Front Matter, Titles, etc

2.6 Miscellaneous

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `sTeX`GitHub repository [sTeX:github:on].

1. when option `book` which uses `\pagestyle{headings}` is given and semantic macros are given in the `omgroup` titles, then they sometimes are not defined

by the time the heading is formatted. Need to look into how the headings are made. This is a problem of the underlying omdoc package.

4 The Implementation

The `mikoslides` package generates two files: the \LaTeX package (all the code between `\package` and `\endpackage`) and the \LaTeX XML bindings (between `\ltxml` and `\endltxml`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

The general preamble for \LaTeX XML:

```
1 \ltxml.cls | ltxml.sty
2 # -*- PERL -*-
3 package LaTeXXML::Package::Pool;
4 use strict;
5 use LaTeXXML::Package;
6 \endltxml.cls | ltxml.sty
```

4.1 Class and Package Options

We define some Package Options and switches for the `mikoslides` class and activate them by passing them on to `beamer.cls` and `omdoc.cls` and the `mikoslides` package.

```
7 \cls
8 \newif\ifnotes\notesfalse
9 \DeclareOption{notes}{\notestruetrue\PassOptionsToPackage{\CurrentOption}{mikoslides}}
10 \DeclareOption{slides}{\notestruetrue\PassOptionsToPackage{\CurrentOption}{mikoslides}}
11 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{omdoc}
12                 \PassOptionsToClass{\CurrentOption}{beamer}
13                 \PassOptionsToPackage{\CurrentOption}{mikoslides}}
14 \ProcessOptions
15 \endcls
16 \ltxml.cls
17 DefConditional('if@mikoslides');
18 DeclareOption('mh', sub {Digest(T_CS('if@mikoslides'))});
19 DeclareOption('notes', sub{PassOptions('mikoslides','sty',ToString(Digest(T_CS('if@mikoslides'))));});
20 DeclareOption('slides', sub{PassOptions('mikoslides','sty',ToString(Digest(T_CS('if@mikoslides'))));});
21 DeclareOption(undef, sub {PassOptions('omdoc','cls',ToString(Digest(T_CS('if@mikoslides'))));});
22                 PassOptions('mikoslides','sty',ToString(Digest(T_CS('if@mikoslides'))));});
23                 PassOptions('beamer','cls',ToString(Digest(T_CS('if@mikoslides'))));});
24 ProcessOptions();
25 \endltxml.cls
```

now we do the same for the `mikoslides` package. Note that we also have to define the same switches³, since we might use `mikoslides.sty` in a different class.

```
26 \package
```

³EDNOTE: MK: we may think about making all of them internal

```

27 \newif\if@mikosslides@mh@\@mikosslides@mh@false
28 \DeclareOption{mh}{\@mikosslides@mh@true}
29 \newif\ifnotes\notesfalse
30 \DeclareOption{notes}{\notesttrue}
31 \DeclareOption{slides}{\notesfalse}
32 \newif\ifsectocframes\sectocframesfalse
33 \DeclareOption{sectocframes}{\sectocframestrue}
34 \newif\ifframeimages\frameimagesfalse
35 \DeclareOption{frameimages}{\frameimagestrue}
36 \newif\if@part\@partfalse
37 \DeclareOption{report}{\@parttrue\PassOptionsToPackage{\CurrentOption}{omdoc}}
38 \DeclareOption{book}{\@parttrue\PassOptionsToPackage{\CurrentOption}{omdoc}}
39 \newif\ifproblems\problemstrue
40 \DeclareOption{nopproblems}{\problemsfalse}
41 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{stex}
42 \PassOptionsToPackage{\CurrentOption}{tikzinput}}
43 \ProcessOptions
44 </package>
45 <*ltxml.sty>
46 DeclareOption('notes', '');
47 DeclareOption('slides', '');
48 DeclareOption('nopproblems', '');
49 DeclareOption('sectocframes', '');
50 DeclareOption('frameimages', '');
51 DeclareOption(undef, sub {PassOptions('stex','sty',ToString(Digest(T_CS('\CurrentOption'))));
52 \PassOptions('tikzinput','sty',ToString(Digest(T_CS('\
53 ProcessOptions();
54 RawTeX('\newif\ifnotes\notesfalse');
55 RawTeX('\newif\ifproblems\problemstrue');
56 </ltxml.sty>

```

Depending on the options, we either load the `article`-based `omdoc` or the `beamer` class. In the first case, we also have to make the `beamer`-specific things available to `article` via the `beamerarticle` package. We use options to avoid loading theorem-like environments, since we want to use our own from the `STEX` packages.

```

57 <*cls>
58 \ifnotes
59 \LoadClass{omdoc}
60 \RequirePackage{a4wide}
61 \RequirePackage{marginnote}
62 \RequirePackage{mdframed}
63 \RequirePackage[notheorems,noamsthm,noxcolor]{beamerarticle}
64 \else
65 \LoadClass[notheorems,noamsthm,10pt]{beamer}
66 \newcounter{Item}
67 \newcounter{paragraph}
68 \newcounter{subparagraph}
69 \newcounter{Hfootnote}
70 \usetheme{Jacobs}

```

```

71 \fi
72 \RequirePackage{mikoslides}
73 \</cls>
74 \<*ltxml.cls>
75 LoadClass('omdoc');
76 RequirePackage('mikoslides');
77 if(IfCondition(T_CS('if@mikoslides'))){RequirePackage('mikoslides-mh');}
78 DefConstructor('\usetheme{','');
79 \</ltxml.cls>

```

now, we load the remaining packages for both versions.

```

80 \<*package>
81 \if@mikoslides@mh\RequirePackage{mikoslides-mh}\fi
82 \RequirePackage{stex}
83 \RequirePackage{smglom}
84 \RequirePackage{tikzinput}
85 \RequirePackage{latexml}
86 \RequirePackage{amssymb}
87 \RequirePackage{amsmath}
88 \RequirePackage{comment}
89 \RequirePackage{textcomp}
90 \RequirePackage{url}
91 \</package>
92 \<*ltxml.sty>
93 RequirePackage('stex');
94 RequirePackage('smglom');
95 RequirePackage('tikzinput', options => ['image']);
96 RequirePackage('latexml');
97 RequirePackage('amssymb');
98 RequirePackage('amsmath');
99 RequirePackage('graphicx');
100 RequirePackage('url');
101 \</ltxml.sty>

```

4.2 Notes and Slides

We define the sizes of slides in the notes. Somehow, we cannot get by with the same here.

```

102 \<*package>
103 \newcounter{slide}
104 \newlength{\slidewidth}\setlength{\slidewidth}{12.8cm}
105 \newlength{\slideheight}\setlength{\slideheight}{9cm}
106 \</package>
107 \<*ltxml.sty>
108 DefRegister('\slidewidth'      => Dimension('13.6cm'));
109 DefRegister('\slideheight'    => Dimension('9cm'));
110 \</ltxml.sty>

```

note The **note** environment is used to leave out text in the **slides** mode. It does not have a counterpart in OMDoc. So for course notes, we define the **note** environment

to be a no-operation otherwise we declare the `note` environment as a comment via the `comment` package.

```

111 <*package>
112 \ifnotes%
113   \renewenvironment{note}{\ignorespaces}{}%
114 \else%
115   \excludecomment{note}%
116 \fi%
117 </package>
118 <*ltxml.sty>
119 DefEnvironment('note','body');
120 </ltxml.sty>

```

We start by giving the L^AT_EX_ML binding for the `frame` environment from the `beamer` class. We first set up the slide boxes in `article` mode. We set up sizes and provide a box register for the frames and a counter for the slides.

```

121 <*package>
122 \ifnotes
123   \newlength{\slideframewidth}
124   \setlength{\slideframewidth}{1.5pt}

```

`frame` We first define the keys.

```

125   \addmetakey{frame}{label}
126   \addmetakey[yes]{frame}{allowframebreaks}
127   \addmetakey{frame}{allowdisplaybreaks}
128   \addmetakey[yes]{frame}{fragile}
129   \addmetakey[yes]{frame}{shrink}
130   \addmetakey[yes]{frame}{squeeze}

```

We redefine the `itemize` environment so that it looks more like the one in `beamer` with `Jacobs` theme. We create the box with the `mdframed` environment from the `equinymous` package. Then we define the environment, read them, and construct the slide number and label.

```

131   \renewenvironment{frame}[1][]{%
132     \metasetkeys{frame}{#1}%
133     \stepcounter{slide}%
134     \def\@currentlabel{\theslide}%
135     \ifx\frame@label\@empty%
136     \else%
137       \label{\frame@label}%
138     \fi%

```

We redefine the `itemize` environment so that it looks more like the one in `beamer` with `Jacobs` theme.

```

139   \def\itemize@level{outer}%
140   \def\itemize@outer{outer}%
141   \def\itemize@inner{inner}%
142   \renewcommand\newpage{}%
143   \renewcommand\metakeys@show@keys[2]{\marginnote{\scriptsize ##2}}%

```

```

144 \renewenvironment{itemize}{%
145 \ifx\itemize@level\itemize@outer%
146 \def\itemize@label{$\rhd$}%
147 \fi%
148 \ifx\itemize@level\itemize@inner%
149 \def\itemize@label{$\scriptstyle\rhd$}%
150 \fi%
151 \begin{list}%
152 {\itemize@label}%
153 {\setlength{\labelsep}{.3em}%
154 \setlength{\labelwidth}{.5em}%
155 \setlength{\leftmargin}{1.5em}%
156 }%
157 \edef\itemize@level{\itemize@inner}%
158 }{%
159 \end{list}%
160 }%

```

We create the box with the `mdframed` environment from the `equinymous` package.

```

161 \begin{mdframed}[linewidth=\slideframewidth,skipabove=1ex,skipbelow=1ex,userdefinedwidth=\s
162 ]{%
163 \medskip\miko@slidelabel\end{mdframed}%
164 }%
165 \end{package}
166 \end{*ltxml.sty}
167 DefEnvironment('frame',
168 " <omdoc:omgroup layout='slide'>"
169 . "#body\n"
170 . "</omdoc:omgroup>\n\n",
171 afterDigestBegin=>sub {
172 $_[1]->setProperty(theory=>LookupValue('current_module')); });
173 \end{*ltxml.sty}##

```

Now, we need to redefine the `frametitle` (we are still in course notes mode).

```

\frametitle
174 \begin{*package}
175 \renewcommand{\frametitle}[1]{\Large\bf\sf\color{blue}{#1}}\medskip%
176 \fi %ifnotes
177 \end{*package}
178 \end{*ltxml.sty}
179 DefConstructor('\frametitle',
180 "\n<omdoc:metadata><dc:title>#1</dc:title></omdoc:metadata>");
181 \end{*ltxml.sty}

```

`\frameimage` We have to make sure that the width is overwritten, for that we check the `\Gin@ewidth` macro from the `graphicx` package⁴

```

182 \begin{*package}

```

⁴EDNOTE: MK@DG; we need to do that in the LaTeXML binding as well!


```

183 \newrobustcmd\frameimage[2][]{%
184   \stepcounter{slide}%
185   \ifframeimages%
186     \def\Gin@ewidth{}\setkeys{Gin}{#1}%
187     \ifnotes%
188     \else%
189       \vfill%
190     \fi%
191     \ifx\Gin@ewidth\@empty%
192       \mycgraphics[width=\slidewidth,#1]{#2}\else\mycgraphics[#1]{#2}%
193     \fi%
194     \par\strut\hfill{\footnotesize Slide \arabic{slide}}%
195     \ifnotes%
196     \else%
197       \vfill%
198     \fi%
199   \fi%
200 }% \ifframeimages
201 \</package>
202 \<*txml.sty>
203 DefMacro(' \frameimage[ ]{ }', '\@frameimage{\includegraphics[#1,width=\slidewidth]{#2}}');
204 DefConstructor(' \@frameimage{ }', "<omdoc:omgroup layout='slide'>#1</omdoc:omgroup>\n");
205 \</txml.sty>

```

4.3 Header and Footer Lines

Now, we set up the infrastructure for the footer line of the slides, we use boxes for the logos, so that they are only loaded once, that considerably speeds up processing.

`\setslidelogo` The default logo is the logo of Jacobs University. Customization can be done by `\setslidelogo{<logo name>}`.

```

206 \<*package>
207 \newlength{\slidelogoheight}
208 \ifnotes%
209   \setlength{\slidelogoheight}{.4cm}%
210 \else%
211   \setlength{\slidelogoheight}{1cm}%
212 \fi%
213 \newsavebox{\slidelogo}%
214 \sbox{\slidelogo}{\includegraphics[height=\slidelogoheight]{jacobs-logo}}%
215 \newrobustcmd{\setslidelogo}[1]{%
216   \sbox{\slidelogo}{\includegraphics[height=\slidelogoheight]{#1}}%
217 }%

```

`\setsource` `\source` stores the writer's name. By default it is *Michael Kohlhase* since he is the main user and designer of this package. `\setsource{<name>}` can change the writer's name.

```

218 \def\source{Michael Kohlhase}% customize locally

```

```

219 \newrobustcmd{\setsource}[1]{\def\source{#1}}%

\setlicensing Now, we set up the copyright and licensing. By default we use the Creative
                Commons Attribution-ShareAlike license to strengthen the public domain. If
                package hyperref is loaded, then we can attach a hyperlink to the license logo.
                \setlicensing[⟨url⟩]{⟨logo name⟩} is used for customization, where ⟨url⟩ is op-
                tional.

220 \def\copyrightnotice{\footnotesize\copyright:\hspace{.3ex}{\source}}%
221 \newsavebox{\cclogo}%
222 \sbox{\cclogo}{\includegraphics[height=\slidelogoheight]{cc_somerights}}%
223 \newif\ifcchref\cchreffalse%
224 \AtBeginDocument{%
225   \ifpackageloaded{hyperref}{\cchreftrue}{\cchreffalse}
226 }%
227 \def\licensing{%
228   \ifcchref%
229     \href{http://creativecommons.org/licenses/by-sa/2.5/}{\usebox{\cclogo}}%
230   \else%
231     {\usebox{\cclogo}}%
232   \fi%
233 }%
234 \newrobustcmd{\setlicensing}[2][ ]{%
235   \def\@url{#1}%
236   \sbox{\cclogo}{\includegraphics[height=\slidelogoheight]{#2}}%
237   \ifx\@url\@empty%
238     \def\licensing{{\usebox{\cclogo}}}%
239   \else%
240     \def\licensing{%
241       \ifcchref%
242         \href{#1}{\usebox{\cclogo}}%
243       \else%
244         {\usebox{\cclogo}}%
245       \fi%
246     }%
247   \fi%
248 }%

```

EdN:5

\slidelabel Now, we set up the slide label for the article mode.⁵

```

249 \newrobustcmd\miko@slidelabel{%
250   \vbox to \slidelogoheight{%
251     \vss\hbox to \slidewidth%
252     {\licensing\hfill\copyrightnotice\hfill\arabic{slide}\hfill\usebox{\slidelogo}}%
253   }%
254 }%

```

⁵EDNOTE: see that we can use the themes for the slides some day. This is all fake.

4.4 Colors and Highlighting

Now, we set up an infrastructure for highlighting phrases in slides. Note that we use content-oriented macros for highlighting rather than directly using color markup. The first thing to do is to adapt the green so that it is dark enough for most beamers

```
255 \AtBeginDocument{%
256   \definecolor{green}{rgb}{0,.5,0}%
257   \definecolor{purple}{cmyk}{.3,1,0,.17}%
258 }%
```

We customize the `\defemph`, `\notemph`, and `\stDMemph` macros with colors for the use in the `statements` package. Furthermore we customize the `\@@lec` macro for the appearance of line end comments in `\lec`.

```
259 % \def\STpresent#1{\textcolor{blue}{#1}}
260 \def\defemph#1{{\textcolor{magenta}{#1}}}
261 \def\notemph#1{{\textcolor{magenta}{#1}}}
262 \def\stDMemph#1{{\textcolor{blue}{#1}}}
263 \def\@@lec#1{(\textcolor{green}{#1})}
264 \end{package}
265 \end{*ltxml.sty}
266 \defmacro\defemph#1{{\textcolor{magenta}{#1}}}
267 \defmacro\notemph#1{{\textcolor{magenta}{#1}}}
268 \end{*ltxml.sty}
```

I like to use the dangerous bend symbol for warnings, so we provide it here.

`\textwarning` as the macro can be used quite often we put it into a box register, so that it is only loaded once.

```
269 \end{package}
270 \pgfdeclareimage[width=.9em]{miko@small@dbend}{dangerous-bend}
271 \def\smalltextwarning{%
272   \pgfuseimage{miko@small@dbend}%
273   \xspace%
274 }%
275 \pgfdeclareimage[width=1.5em]{miko@dbend}{dangerous-bend}
276 \newrobustcmd\textwarning{%
277   \raisebox{-.05cm}{\pgfuseimage{miko@dbend}}%
278   \xspace%
279 }%
280 \pgfdeclareimage[width=2.5em]{miko@big@dbend}{dangerous-bend}%
281 \newrobustcmd\bigtextwarning{%
282   \raisebox{-.05cm}{\pgfuseimage{miko@big@dbend}}%
283   \xspace%
284 }%
285 \end{package}
286 \end{*ltxml.sty}
287 \defmacro\textwarning#1{{\@textwarning\xspace}}
288 \defmacro\textwarning#1{{\@textwarning\xspace}}
289 \end{*ltxml.sty}
```

4.5 Front Matter, Titles, etc

We need to redefine the frontmatter macros inherited from the `beamer` class for LaTeXML, since there they take an optional argument.

```
290 <*ltxml.sty>
291 DefMacro('title[]{}', '@add@frontmatter{ltx:title}{#1}');
292 DefMacro('date[]{}', '@add@frontmatter{ltx:date}[role=creation]{#1}');
293 DefMacro('author[]{}', sub { andSplit(T_CS('@author'),$_[1]); });#$
294 </ltxml.sty>

295 %      Must be first command on slide to make positioning work.
296 <*package>
297 \newrobustcmd\putgraphicsat[3]{%
298   \begin{picture}(0,0)\put(#1){\includegraphics[#2]{#3}}\end{picture}%
299 }%
300 \newrobustcmd\putat[2]{%
301   \begin{picture}(0,0)\put(#1){#2}\end{picture}%
302 }%
```

4.6 Sectioning

If the `sectocframes` option is set, then we make section frames. We first define a set of counters

```
303 \ifsectocframes%
304   \if@part%
305     \newcounter{mpart}%
306     \newcounter{mchapter}%
307     \newcounter{msection}[mchapter]%
308   \else%
309     \newcounter{msection}%
310   \fi%
311   \newcounter{msubsection}[msection]%
312   \newcounter{msubsubsection}[msubsection]%
313   \newcounter{msubsubsubsection}[msubsubsection]%
314 \fi% ifsectocframes

and then

315 \ifnotes\else% only in slides
316   \renewenvironment{omgroup}[2][]{%
317     \metasetkeys{omgroup}{#1}\sref@target%
318     \advance\section@level by 1%
319     \ifsectocframes%
320       \begin{frame}%
321       \vfill\Large\centering%
322       \red{%
323         \ifcase\section@level\or%
324           \stepcounter{mpart}Part \Roman{mpart}\or%
325           \stepcounter{mchapter}Chapter \arabic{mchapter}\or
326           \stepcounter{msection}\if@part\arabic{mchapter}.\fi\arabic{msection}\or
327           \stepcounter{msubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msubsec
```

```

328         \stepcounter{msubsubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{msub
329         \stepcounter{msubsubsubsection}\if@part\arabic{mchapter}.\fi\arabic{msection}.\arabic{m
330         \fi% end ifcase
331         \quad #2%
332     }%
333     \vfill%
334     \end{frame}%
335     \fi %ifsectocframes
336 }
337 {\advance\section@level by -1}%
338 \fi% ifnotes
339 </package>

```

4.7 Miscellaneous

The following fixes an error I do not understand, this has something to do with beamer compatibility, which has similar definitions but only up to 1.

```

340 <*package>
341 \expandafter\def\csname Parent2\endcsname{}
342 %     \begin{macrocode}
343 %
344 % We need to disregard the columns macros introduced by the |beamer| class
345 %     \begin{macrocode}
346 \ifnotes%
347 \renewenvironment{columns}{%
348     \par\noindent%
349     \begin{minipage}%
350     \linewidth\centering\leavevmode%
351 }{%
352     \end{minipage}\par\noindent%
353 }%
354 \newsavebox\columnbox%
355 \renewenvironment{column}[1]{%
356     \begin{lrbox}{\columnbox}\begin{minipage}{#1}%
357 }{%
358     \end{minipage}\end{lrbox}\usebox\columnbox%
359 }%
360 \fi%
361 </package>
362 <*ltxml.sty>
363 DefEnvironment('columns','body');
364 DefEnvironment('column','body');

```

We also need to deal with overlay specifications introduced by the beamer class.⁶

⁷

⁶EDNOTE: this is just to keep latexml quiet, no real functionality here.

⁷EDNOTE: Deyan: We reuse the CMP itemizations defined in the omdoc.cls.ltxml binding, adjusting the parameters to be overlay-sensitive

```

365 DefConstructor('\uncover', '#1');
366 #Define a Beamer Overlay Parameter type
367 DefParameterType('BeamerOverlay', sub {
368   my ($gullet) = @_;
369   my $tok = $gullet->readXToken;
370   if (ref $tok && ToString($tok) eq '<') {
371     $gullet->readUntil(T_OTHER('>'));
372   } else {
373     $gullet->unread($tok) if ref $tok;
374     undef; },
375   reversion=> sub {
376     (T_OTHER('<'), $_[0]->revert, T_OTHER('>'));
377   });
378
379 #Take the "from" field of the overlay range
380 sub overlayFrom {
381   return "" unless defined $_[0];
382   my $overlay=ToString($_[0]); $overlay =~ /\^(\\d+)/; $1;}
383
384 #Reuse the CMP itemizations, only adjust the \item constructors.
385 DefMacro('\beamer@group@item[] OptionalBeamerOverlay IfBeginFollows', sub {
386   my($gullet,$tag,$overlay,$needwrapper)=@_;
387   $overlay=$overlay||T_OTHER("");
388   ( T_CS('\group@item@maybe@unwrap'),
389     ($needwrapper ? (Invocation(T_CS('\beamer@group@item@wrap'),$tag,$overlay)->unlist) : ()))
390 DefConstructor('\beamer@group@item@wrap {} OptionalBeamerOverlay',
391   "<omdoc:omtext ?#2(overlay='&overlayFrom(#2)')()>"
392   . "?#1(<dc:title>#1</dc:title>())"
393   . "<omdoc:CMP>",
394   beforeDigest=>sub {
395     Let('\group@item@maybe@unwrap', '\group@item@unwrap');
396     #$_[0]->bgroup;
397   return; },
398   properties=>sub{ RefStepItemCounter(); });
399 #DefConstructor('\beamer@itemize@item[] OptionalBeamerOverlay',
400 #   "<omdoc:li ?#2(overlay='&overlayFrom(#2)')() >"
401 #   . "?#1(<dc:title>#1</dc:title>())",
402 #   properties=>sub{ RefStepItemCounter(); });
403 DefConstructor('\beamer@enumerate@item[] OptionalBeamerOverlay',
404   "<omdoc:li ?#2(overlay='&overlayFrom(#2)')() >"
405   . "?#1(<dc:title>#1</dc:title>())",
406   properties=>sub{ RefStepItemCounter(); });
407 DefConstructor('\beamer@description@item[] OptionalBeamerOverlay',
408   "<omdoc:di ?#2(overlay='&overlayFrom(#2)')() >"
409   . "?#1(<omdoc:dt>#1</omdoc:dt>())<omdoc:dd>", # trust di and dt to autoclose
410   properties=>sub{ RefStepItemCounter(); });
411 </ltxml.sty>#

```

Now, some things that are imported from the pgf and beamer packages:

```

412 <*ltxml.sty>

```

```

413 DefMacro('putgraphicsat{}{}{}', 'mygraphics[#2]{#3}');
414 DefMacro('putat{}{}', '#2');
415 </ltxml.sty>

416 <*package>
417 \ifproblems%
418   \newenvironment{problems}{}{}%
419 \else%
420   \excludecomment{problems}%
421 \fi%
422 </package>
423 <*ltxml.sty>
424 DefEnvironment('{problems}', '#body');
425 </ltxml.sty>

```

4.8 Finale

Finally, we set the slide body font to the sans serif, and we terminate the L^AT_EX_ML bindings file with a success mark for perl.

```

426 <package>\ifnotes\else\sf\fi
427 <ltxml.sty | ltxml.cls>1;

```