

omtext: Semantic Markup for Mathematical Text Fragments in L^AT_EX*

Michael Kohlhase
Jacobs University, Bremen
<http://kwarc.info/kohlhase>

November 21, 2015

Abstract

The **omtext** package is part of the sT_EX collection, a version of T_EX/L^AT_EX that allows to markup T_EX/L^AT_EX documents semantically without leaving the document format, essentially turning T_EX/L^AT_EX into a document format for mathematical knowledge management (MKM).

This package supplies an infrastructure for writing OMDoc text fragments in L^AT_EX.

*Version v1.1 (last revised 2015/11/04)

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package Options	3
2.2	Mathematical Text	3
2.3	Phrase-Level Markup	3
2.4	Block-Level Markup	4
2.5	Index Markup	5
3	Limitations	6
4	Implementation	7
4.1	Package Options	7
4.2	Metadata	8
4.3	Mathematical Text	9
4.4	Phrase-level Markup	10
4.5	Block-Level Markup	12
4.6	Index Markup	13
4.7	L ^A T _E X Commands we interpret differently	15
4.8	Providing IDs for OMDoc Elements	16
4.9	Miscellaneous	18
4.10	Finale	19

1 Introduction

The `omtext` package supplies macros and environment that allow to mark up mathematical texts in \LaTeX , a version of \TeX / \LaTeX that allows to markup \TeX / \LaTeX documents semantically without leaving the document format, essentially turning \TeX / \LaTeX into a document format for mathematical knowledge management (MKM). The package supports direct translation to the OMDoc format [Koh06]

2 The User Interface

2.1 Package Options

`showmeta` The `omtext` package takes a single option: `showmeta`. If this is set, then the metadata keys are shown (see [Koh15a] for details and customization options).

2.2 Mathematical Text

`omtext` The `omtext` environment is used for any text fragment that has a contribution to a text that needs to be marked up. It can have a title, which can be specified via the `title=` key. Often it is also helpful to annotate the `type` key. The standard relations from rhetorical structure theory `abstract`, `introduction`, `conclusion`, `thesis`, `comment`, `antithesis`, `elaboration`, `motivation`, `evidence`, `transition`, `note`, `annotate` are recommended as values. Note that some of them are unary relations like `introduction`, which calls for a target. In this case, a target using the `for=` key should be specified. The `transition` relation is special in that it is binary (a “transition between two statements”), so additionally, a source should be specified using the `from=` key.

Note that the values of the `title` and `type` keys are often displayed in the text. This can be turned off by setting the `display` key to the value `flow`. Sometimes we want to specify that a text is a continuation of another, this can be done by giving the identifier of this in the `continues=` key.

Finally, there is a set of keys that pertain to the mathematical formulae in the text. The `functions` key allows to specify a list of identifiers that are to be interpreted as functions in the generate content markup. The `theory` specifies a module (see [KGA15a]) that is to be pre-loaded in this one¹ Finally, `verbalizes=` specifies a (more) formal statement (see [Koh15b]) that this text verbalizes or paraphrases.²

2.3 Phrase-Level Markup

`\phrase` The `phrase` macro allows to mark up phrases with semantic information. It takes an optional `KeyVal` argument with the keys `verbalizes` and `type` as above and `style`, `class`, `index` that are disregarded in the \LaTeX , but copied into the gen-

¹EDNOTE: this is not implemented yet.

²EDNOTE: MK:specify the form of the reference.

erated content markup.

`\nlex` We use the `\nlex{<phrase>}` for marking up phrases that serve as natural language examples and `\nlcex{<phrase>}` for counter-examples (utterances that are not acceptable for some reason). In natural language examples, we sometimes use “co-reference markers” to specify the resolution of anaphora and the like. We use the `\coreft{<phrase>}{<mark>}` to mark up the “target” of a co-reference and analogously `\corefs` for coreference source – e.g. for an anaphoric reference. The usage is the following:

```
\nlex{If \coreft{a farmer}1 owns \coreft{a donkey}2,
      \corefs{he}2 beats \corefs{it}2.}
```

is formatted to

If a farmer¹ owns a donkey², he₂ beats it₂.

`\sinlinequote` The `\sinlinequote` macro allows to mark up quotes inline and attribute them. The quote itself is given as the argument, possibly preceded by the a specification of the source in a an optional argument. For instance, we would quote Hamlet with

```
\sinlinequote[Hamlet, \cite{Shak:1603:Hamlet}]{To be or not to be}
```

which would appear as “*To be or not to be*” Hamlet, (Shakespeare 1603) in the text. The style in which inline quotations appear in the text can be adapted

by specializing the macros `\@sinlinequote` — for quotations without source and `\@@sinlinequote` — for quotations with source.

2.4 Block-Level Markup

`sblockquote` The `sblockquote` environment is the big brother of the `\sinlinequote` macro. It also takes an optional argument to specify the source. Here the four internal macros `\begin@sblockquote` to `\end@@sblockquote` are used for styling and can be adapted by package integrators. Here a quote of Hamlet would marked up as

```
\begin{sblockquote}[Hamlet, \cite{Shak:1603:Hamlet}]\obeylines
  To be, or not to be: that is the question:
  Whether 'tis nobler in the mind to suffer
\end{sblockquote}
```

and would render as

*To be, or not to be: that is the question:
Whether 'tis nobler in the mind to suffer*

Hamlet, (Shakespeare 1603)

`\lec` The `\lec` macro takes one argument and sets it as a comment at the end of the line, making sure that if the content is too long it is pushed into a new line. We use it internally for placing the of source of the `sblockquote` environment above. The

`\@@lec` actual appearance of the line end comment is determined by the `\@@lec` macro, which can be customized in the document class.

2.5 Index Markup

The `omtext` package provides some extensions for the well-known indexing macros of L^AT_EX. The main reason for introducing these macros is that index markup in OMDoc wraps the indexed terms rather than just marking the spot for cross-referencing. Furthermore the index commands only indexes words unless the `noindex` option is set in the `\usepackage`. The `omtext` package and class make the usual `\index` macro undefined³.

`\indextoo` The `\indextoo` macro renders a word and marks it for the index. Sometimes, we want to index a slightly different form of the word, e.g. for non-standard plurals: while `\indextoo{word}s` works fine, we cannot use this for the word “datum”, which has the plural “data”. For this we have the macro

`\indexalt` `\indexalt`, which takes another argument for the displayed text, allowing us to use `\indexalt{data}{datum}`, which prints “data” but puts “datum” into the index.

The second set of macros adds an infrastructure for two-word compounds. Take for instance the compound “OMDoc document”, which we usually want to add into the index under “OMDoc” and “document”. `\twintoo{OMDoc}{document}` is a variant of `\indextoo` that will do just this. Again, we have a version that prints a variant: This is useful for situations like this the one in Figure 1:

We call group `\twinalt{Abelian}{Abelian}{group}`, iff `\ldots`

will result in the following

We call group Abelian, iff ...

and put “Abelian Group” into the index.

Example 1: Index markup

`\atwintoo` The third set of macros does the same for two-word compounds with adjectives, e.g. “wonderful OMDoc document”. `\atwin{wonderful}{OMDoc}{document}` will make the necessary index entries under “wonderful” and “document”. Again,

`\atwinalt` we have a variant `\atwinalt` whose first argument is the alternative text.

All index macros take an optional first argument that is used for ordering the respective entries in the index.

³EDNOTE: implement this and issue the respective error message

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `sTeX` GitHub repository [sTeX].

1. none reported yet

4 Implementation

The `omtext` package generates two files: the \LaTeX package (all the code between `*package` and `/package`) and the \LaTeX XML bindings (between `*ltxml` and `/ltxml`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

The initial setup for \LaTeX XML:

```
1 <*ltxml>
2 package LaTeXXML::Package::Pool;
3 use strict;
4 use LaTeXXML::Package;
5 use LaTeXXML::Util::Pathname;
6 </ltxml>
```

4.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false).⁴

```
7 <*package>
8 \newif\if@omtext@mh@\@omtext@mh@false
9 \DeclareOption{mh}{\@omtext@mh@true
10 \PassOptionsToPackage{\CurrentOption}{modules}}
11 \newif\ifindex@indextrue
12 \DeclareOption{noindex}{\indexfalse}
13 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{modules}}
14 \ProcessOptions
15 \ifindex\makeindex\fi
16 </package>
17 <*ltxml>
18 DeclareOption('mh', sub { AssignValue ('@omtext' => 1,'global')};
19 PassOptions('modules','sty',ToString(Digest(T_CS('\CurrentOption')))); });
20 DeclareOption('noindex','');
21 DeclareOption(undef,sub {PassOptions('modules','sty',ToString(Digest(T_CS('\CurrentOption')))); });
22 ProcessOptions();
23 </ltxml>

24 <*package>
25 \if@omtext@mh\RequirePackage{omtext-mh}\fi
26 \RequirePackage{xspace}
27 \RequirePackage{modules}
28 \RequirePackage{comment}
29 \RequirePackage{mdframed}
30 \RequirePackage{latexsym}
31 </package>
32 <*ltxml>
33 if(LookupValue('@omtext')) {RequirePackage('omtext-mh');}
```

⁴EdNOTE: need an implementation for \LaTeX XML

```

34 RequirePackage('xspace');
35 RequirePackage('modules');
36 RequirePackage('lXRdFa');
37 RequirePackage('latexsym');
38 </ltxml>

```

4.2 Metadata

All the OMDoc elements allow to specify metadata in them, which is modeled by the `omdoc:metadata` element. Since the content of this element is precisely controlled by the Schema, we can afford to auto-open and auto-close it. Thus metadata elements from various sources will just be included into one `omdoc:metadata` element, even if they are supplied by different \LaTeX bindings. Also we add numbering and location facilities.

```

39 <*ltxml>
40 Tag('omdoc:metadata', afterOpen=>\&numberIt, afterClose=>\&locateIt, autoClose=>1, autoOpen=>1);
41 </ltxml>

```

the `itemize`, `description`, and `enumerate` environments generate `omdoc:li`, `omdoc:di` with `autoclose` inside a CMP. This behavior will be overwritten later, so we remember that we are in a CMP by assigning `_LastSeenCMP`.

```

42 <*ltxml>
43 Tag('omdoc:CMP', afterOpen => sub {AssignValue('_LastSeenCMP', $_[1], 'global');return;});#$
44 </ltxml>

```

the `itemize`, `description`, and `enumerate` environments originally introduced in the `omtext` package do double duty in OMDoc, outside a CMP they are transformed into a `<omgroup layout='itemizedescriptionenumerate'>`, where the text after the macros `\item` come to be the children. If that is only text, then it is enclosed in an `<omtext><CMP>`, otherwise it is left as it is. The optional argument of the `\item` is transformed into the `<metadata><dc:title>` of the generated `\item` element.

```

45 <*ltxml>
46 DefParameterType('IfBeginFollows', sub {
47     my ($gullet) = @_;
48     $gullet->skipSpaces;
49     my $next = $gullet->readToken;
50     $gullet->unread($next);
51     $next = ToString($next);
52     #Hm, falling back to regexp handling, the $gullet->ifNext approach didn't work
53     return 1 unless ($next=~/\^\begin/);
54     return;
55 },
56 reversion=>' ', optional=>1);
57 </ltxml>

```


4.3 Mathematical Text

We define the actions that are undertaken, when the keys are encountered. The first set just records metadata; this is very simple via the `\addmetakey` infrastructure [Koh15a]. Note that we allow math in the `title` field, so we do not declare it to be `Semiverbatim` (indeed not at all, which allows it by default).

```

58 \*package
59 \srefaddidkey{omtext}
60 \addmetakey[] {omtext} {functions}
61 \addmetakey* {omtext} {display}
62 \addmetakey {omtext} {for}
63 \addmetakey {omtext} {from}
64 \addmetakey {omtext} {type}
65 \addmetakey* {omtext} {title}
66 \addmetakey* {omtext} {start}
67 \addmetakey {omtext} {theory}
68 \addmetakey {omtext} {continues}
69 \addmetakey {omtext} {verbalizes}
70 \addmetakey {omtext} {subject}
71 \*package
72 \*ltxml
73 DefKeyVal('omtext', 'functions', 'CommaList');
74 DefKeyVal('omtext', 'display', 'Semiverbatim');
75 DefKeyVal('omtext', 'for', 'Semiverbatim');
76 DefKeyVal('omtext', 'from', 'Semiverbatim');
77 DefKeyVal('omtext', 'type', 'Semiverbatim');
78 DefKeyVal('omtext', 'title', 'Plain'); #Math mode in titles.
79 DefKeyVal('omtext', 'start', 'Plain'); #Math mode in start phrases
80 DefKeyVal('omtext', 'theory', 'Semiverbatim');
81 DefKeyVal('omtext', 'continues', 'Semiverbatim');
82 DefKeyVal('omtext', 'verbalizes', 'Semiverbatim');
83 \*ltxml

```

The next keys handle module loading (see [KGA15b]).

```

84 % \ednote{MK: need to implement these in LaTeXML, I wonder whether there is a general
85 % mechanism like numberit.}\ednote{MK: this needs to be rethought in the light of
86 % |\usemodule|. It is probably obsolete. Is this used? Is this documented?}
87 \*package
88 \define@key{omtext}{require}{\requiremodules{#1}{sms}}
89 \define@key{omtext}{module}{\message{module: #1}\importmodule{#1}\def\omtext@theory{#1}}

```

```

\st@flow We define this macro, so that we can test whether the display key has the value
flow
90 \def\st@flow{flow}

```

We define a switch that allows us to see whether we are inside an `omtext` environment or a statement. It will be used to give better error messages for inline statements.

```

91 \newif\if@in@omtext\@in@omtextfalse

```

`omtext` The `omtext` environment is different, it does not have a keyword that marks it. Instead, it can have a title, which is used in a similar way. We redefine the `\lec` macro so the trailing `\par` does not get into the way.

```

92 \def\omtext@pre@skip{\smallskip}
93 \def\omtext@post@skip{}
94 \providecommand{\stDMemph}[1]{\textbf{#1}}
95 \newenvironment{omtext}[1][\in@omtexttrue%
96 \bgroup\metasetkeys{omtext}{#1}\sref@label{id}{this paragraph}%
97 \def\lec##1{\@lec{##1}}%
98 \ifx\omtext@display\st@flow\else\omtext@pre@skip\par\noindent%
99 \ifx\omtext@title\@empty%
100 \ifx\omtext@start\@empty\else\stDMemph{\omtext@start}\xspace\fi%
101 \else\stDMemph{\omtext@title}:\xspace%
102 \ifx\omtext@start\@empty\else\omtext@start\xspace\fi%
103 \fi% omtext@title empty
104 \fi% omtext@display=flow
105 \ignorespaces}
106 {\egroup\omtext@post@skip\in@omtextfalse}
107 \end{package}
108 \let\omtext\@empty
109 DefEnvironment('omtext' OptionalKeyVals:omtext',
110 "omdoc:omtext "
111 . "&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id'))()" "
112 . "&GetKeyVal(#1,'type')(type='&GetKeyVal(#1,'type'))()" "
113 . "&GetKeyVal(#1,'for')(for='&GetKeyVal(#1,'for'))()" "
114 . "&GetKeyVal(#1,'from')(from='&GetKeyVal(#1,'from'))()" ">"
115 . "&GetKeyVal(#1,'title')(<dc:title>&GetKeyVal(#1,'title')</dc:title>())"
116 . "&GetKeyVal(#1,'start')(<ltx:text class='startemph'>&GetKeyVal(#1,'start')</ltx:text>)"
117 . "#body"
118 . "</omdoc:omtext>");
119 \end{ltxml}

```

4.4 Phrase-level Markup

`\phrase` For the moment, we do disregard the most of the keys

```

120 \package
121 \srefaddidkey{phrase}
122 \addmetakey{phrase}{style}
123 \addmetakey{phrase}{class}
124 \addmetakey{phrase}{index}
125 \addmetakey{phrase}{verbalizes}
126 \addmetakey{phrase}{type}
127 \addmetakey{phrase}{only}
128 \newcommand\phrase[2][\metasetkeys{phrase}{#1}%
129 \ifx\phrase@only\@empty\only<\phrase@only>{#2}\else #2\fi]
130 \end{package}
131 \let\phrase\@empty
132 DefKeyVal('phrase','id','Semiverbatim');

```

```

133 DefKeyVal('phrase','style','Semiverbatim');
134 DefKeyVal('phrase','class','Semiverbatim');
135 DefKeyVal('phrase','index','Semiverbatim');
136 DefKeyVal('phrase','verbalizes','Semiverbatim');
137 DefKeyVal('phrase','type','Semiverbatim');
138 DefKeyVal('phrase','only','Semiverbatim');
139 DefConstructor('\phrase OptionalKeyVals:phrase {}',
140     "<ltx:text %&GetKeyVals(#1) ?&GetKeyVal(#1,'only') (rel='beamer:only' content='&GetKeyVal
141 </ltxml>

\coref*
142 <*package>
143 \providecommand\textsubscript[1]{\ensuremath{_{\{#1\}}}}
144 \newcommand\corefs[2]{#1\textsubscript{#2}}
145 \newcommand\coreft[2]{#1\textsuperscript{#2}}
146 </package>
147 <*ltxml>
148 DefConstructor('\corefs{}{}',
149     "<ltx:text class='coref-source' stex:index='#2'>#1</ltx:text>");
150 DefConstructor('\coreft{}{}',
151     "<ltx:text class='coref-target' stex:index='#2'>#1</ltx:text>");
152 </ltxml>

\n*lex
153 <*package>
154 \newcommand\nlex[1]{\green{\sl{#1}}}
155 \newcommand\nlcex[1]{*\green{\sl{#1}}}
156 </package>
157 <*ltxml>
158 DefConstructor('\nlex{}', "<ltx:text class='nlex'>#1</ltx:text>");
159 DefConstructor('\nlcex{}', "<ltx:text class='nlcex'>#1</ltx:text>");
160 </ltxml>

sinlinequote
161 <*package>
162 \def\@sinlinequote#1{'\sl{#1}}
163 \def\@sinlinequote#1#2{\@sinlinequote{#2}~#1}
164 \newcommand\sinlinequote[2] []
165 {\def\@opt{#1}\ifx\@opt\@empty\@sinlinequote{#2}\else\@sinlinequote\@opt{#2}\fi}
166 </package>
167 <*ltxml>
168 DefConstructor('\sinlinequote [] {}',
169     "<ltx:quote type='inlinequote'>"
170     . "?#1(<dc:source>#1</dc:source>\n)()"
171     . "#2"
172     . "</ltx:quote>");
173 </ltxml>

```

4.5 Block-Level Markup

`sblockquote`

```

174 <*package>
175 \def\begin@sblockquote{\begin{quote}\sl}
176 \def\end@sblockquote{\end{quote}}
177 \def\begin@@sblockquote#1{\begin@sblockquote}
178 \def\end@@sblockquote#1{\def\@lec##1{\rm ##1}\@lec{#1}\end@sblockquote}
179 \newenvironment{sblockquote}[1]{}
180 {\def\@opt{#1}\ifx\@opt\@empty\begin@sblockquote\else\begin@@sblockquote\@opt\fi}
181 {\ifx\@opt\@empty\end@sblockquote\else\end@@sblockquote\@opt\fi}
182 </package>
183 <*ltxml>
184 DefEnvironment('{sblockquote} []',
185   "<ltx:quote>?#1<ltx:note role='source'>#1</ltx:note>()#body</ltx:quote>");
186 </ltxml>

```

`sboxquote`

```

187 <*package>
188 \newenvironment{sboxquote}[1]{}
189 {\def\@src{#1}\begin{mdframed}[leftmargin=.5cm,rightmargin=.5cm]}
190 {\@lec{\rm\@src}\end{mdframed}}
191 </package>
192 <*ltxml>
193 DefEnvironment('{sboxquote} []',
194   "<ltx:quote class='boxed'>?#1<ltx:note role='source'>#1</ltx:note>()#body</ltx:quote>");
195 </ltxml>

```

The line end comment macro makes sure that it will not be forced on the next line unless necessary.

`\lec` The actual appearance of the line end comment is determined by the `\@lec` macro, which can be customized in the document class. The basic one here is provided so that it is not missing.

```

196 <*package>
197 \providecommand{\@lec}[1]{(##1)}
198 \def\@lec#1{\strut\hfil\strut\hfil\@lec{#1}}
199 \def\lec#1{\@lec{#1}\par}
200 </package>
201 <*ltxml>
202 DefConstructor('{\lec}',
203   "\n<omdoc:note type='line-end-comment'>#1</omdoc:note>");
204 </ltxml>

```

`\my*graphics` We set up a special treatment for including graphics to respect the intended OM-Doc document structure. The main work is done in the transformation stylesheet though.

```

205 <ltxml>RawTeX(
206 <*ltxml | package>

```

```

207 \newcommand\mygraphics[2] [] {\includegraphics[#1]{#2}}
208 \newcommand\mycgraphics[2] [] {\begin{center}\mygraphics[#1]{#2}\end{center}}
209 \newcommand\mybgraphics[2] [] {\fbox{\mygraphics[#1]{#2}}}
210 \newcommand\mycbgraphics[2] [] {\begin{center}\fbox{\mygraphics[#1]{#2}}\end{center}}
211 \ltxml | package>
212 \ltxml>';

```

4.6 Index Markup

`\omdoc@index` this is the main internal indexing command. It makes sure that the modules necessary for interpreting the math in the index entries are loaded. If the `loadmodules` key is given, we import the module we are in otherwise all the currently imported modules. We do not have to require the module files, since the index is at the end of the document. If the `at` key is given, then we use that for sorting in the index.

```

213 <*package>
214 \addmetakey{omdoc@index}{at}
215 \addmetakey[false]{omdoc@index}{loadmodules}[true]
216 \newcommand\omdoc@index[2] [] {\ifindex%
217 \metasetkeys{omdoc@index}{#1}%
218 \@bsphack\beginngroup\@sanitize%
219 \ifx\omdoc@index@loadmodules\@true%
220 \protected@write\@indexfile{}\string\indexentry%
221 {\ifx\omdoc@index@at\@empty\else\omdoc@index@at @\fi%
222 {\string\importmodules{\@ifundefined{mod@id}\imported@modules\mod@id}%
223 #2}}{\thepage}}%
224 \else%
225 \protected@write\@indexfile{}\string\indexentry%
226 {\ifx\omdoc@index@at\@empty\else\omdoc@index@at @\fi#2}{\thepage}}%
227 \fi% loadmodules
228 \endgroup\@esphack\fi}%ifindex

```

Now, we make two interface macros that make use of this:

`\indexalt`

```

229 \newcommand\indexalt[3] [] {\ifindex\omdoc@index[#1]{#3}} % word in text and index
230 </package>
231 <*ltxml>
232 DefConstructor('\indexalt[]{}{}',
233     "<omdoc:idx>"
234     . " <omdoc:idt>#2</omdoc:idt>"
235     . " <omdoc:ide ?#1(sort-by='#1')()>"
236     . " <omdoc:idp>#3</omdoc:idp>"
237     . " </omdoc:ide>"
238     . "</omdoc:idx>");
239 </ltxml>

```

`\indextoo`

```

240 <*package>

```

```

241 \newcommand\indextoo[2] [] [{#2}\omdoc@index[#{1}{#2}] % word in text and index
242 \</package>
243 \<*ltxml>
244 DefConstructor('\indextoo[]{}',
245     "<omdoc:idx>"
246     . "<omdoc:idt>#2</omdoc:idt>"
247     . "<omdoc:ide ?#1(sort-by='#1')()>"
248     . "<omdoc:idp>#2</omdoc:idp>"
249     . "</omdoc:ide>"
250     . "</omdoc:idx>");
251 \</ltxml>

```

\@twin this puts two-compound words into the index in various permutations

```

252 \<*package>
253 \newcommand\@twin[3] [] [{\omdoc@index[#{1}{#2!#3}\omdoc@index[#{1}{#3!#2}]}

```

And again we have two interface macros building on this

\twinalt

```

254 \newcommand\twinalt[4] [] [{#2\@twin[#{1}{#3}{#4}]}
255 \</package>
256 \<*ltxml>
257 DefConstructor('\twinalt[]{}{}',
258     "<omdoc:idx>"
259     . "<omdoc:idt>#2</omdoc:idt>"
260     . "<omdoc:ide ?#1(sort-by='#1')()>"
261     . "<omdoc:idp>#2</omdoc:idp>"
262     . "<omdoc:idp>#3</omdoc:idp>"
263     . "</omdoc:ide>"
264     . "</omdoc:idx>");
265 \</ltxml>

```

\twintoo

```

266 \<*package>
267 \newcommand\twintoo[3] [] [{#2 #3}\@twin[#{1}{#2}{#3}] % and use the word compound too
268 \</package>
269 \<*ltxml>
270 DefConstructor('\twintoo[]{}{}',
271     "<omdoc:idx>"
272     . "<omdoc:idt>#2 #3</omdoc:idt>"
273     . "<omdoc:ide ?#1(sort-by='#1')()>"
274     . "<omdoc:idp>#2</omdoc:idp>"
275     . "<omdoc:idp>#3</omdoc:idp>"
276     . "</omdoc:ide>"
277     . "</omdoc:idx>");
278 \</ltxml>

```

EdN:5

\@atwin this puts adjectivized two-compound words into the index in various permutations⁵

⁵EDNOTE: what to do with the optional argument here and below?

```

279 <*package>
280 \newcommand\@atwin[4] [] {\omdoc@index[#1]{#2!#3!#4}\omdoc@index[#1]{#3!#2 (#4)}}

```

and the two interface macros for this case:

```
\@atwinalt
```

```

281 \newcommand\atwinalt[5] [] {#2\@atwin[#1]{#3}{#4}{#4}}
282 </package>
283 <*ltxml>
284 DefConstructor('\atwinalt[]{}{}{}{}',
285     "<omdoc:idx>"
286     . "<omdoc:idt>#2</omdoc:idt>"
287     . "<omdoc:ide ?#1(sort-by='#1')()>"
288     . "<omdoc:idp>#2</omdoc:idp>"
289     . "<omdoc:idp>#3</omdoc:idp>"
290     . "<omdoc:idp>#4</omdoc:idp>"
291     . "</omdoc:ide>"
292     . "</omdoc:idx>");
293 </ltxml>

```

```
\@atwintoo
```

```

294 <*package>
295 \newcommand\atwintoo[4] [] {{#2 #3 #4}\@atwin[#1]{#2}{#3}{#4}} % and use it too
296 </package>
297 <*ltxml>
298 DefConstructor('\atwintoo[]{}{}{}{}',
299     "<omdoc:idx>"
300     . "<omdoc:idt>#2 #3</omdoc:idt>"
301     . "<omdoc:ide ?#1(sort-by='#1')()>"
302     . "<omdoc:idp>#2</omdoc:idp>"
303     . "<omdoc:idp>#3</omdoc:idp>"
304     . "<omdoc:idp>#4</omdoc:idp>"
305     . "</omdoc:ide>"
306     . "</omdoc:idx>");
307 </ltxml>

```

4.7 L^AT_EX Commands we interpret differently

The first think we have to take care of are the paragraphs, we want to generate OMDoc that uses the `ltx:p` element for paragraphs inside CMPs. For that we have modified the DTD only to allowed `ltx:p` elements in `omdoc:CMP` (in particular no text). Then we instruct the `\par` macro to close a `ltx:p` element if possible. The next `ltx:p` element is then opened automatically, since we make `ltx:p` and `omdoc:CMP` autoclose and autoopen.

```

308 <*ltxml>
309 Tag('omdoc:CMP', autoClose=>1, autoOpen=>1);
310 Tag('omdoc:omtext', autoClose=>1, autoOpen=>1);
311 Tag('ltx:p', autoClose=>1, autoOpen=>1);
312 </ltxml>

```

the rest of the reinterpretations is quite simple, we either disregard presentational markup or we re-interpret it in terms of OMDoc.⁶

```

313 <*package>
314 \def\omspace#1{\hspace*{#1}}
315 </package>
316 <*ltxml>
317 DefConstructor('\footnote[]{}',
318     "<omdoc:note type='foot' ?#1(mark='#1')>#2</omdoc:note>");
319 DefConstructor('\footnotemark[]', "");
320 DefConstructor('\footnotetext[]{}',
321     "<omdoc:note class='foot' ?#1(mark='#1')>#2</omdoc:note>");
322 </ltxml>

```

4.8 Providing IDs for OMDoc Elements

To provide default identifiers, we tag all OMDoc elements that allow `xml:id` attributes by executing the `numberIt` procedure below. Furthermore, we use the `locateIt` procedure to give source links.

```

323 <*ltxml>
324 Tag('omdoc:omtext', afterOpen=>\&numberIt, afterClose=>\&locateIt);
325 Tag('omdoc:omgroup', afterOpen=>\&numberIt, afterClose=>\&locateIt);
326 Tag('omdoc:CMP', afterOpen=>\&numberIt, afterClose=>\&locateIt);
327 Tag('omdoc:idx', afterOpen=>\&numberIt, afterClose=>\&locateIt);
328 Tag('omdoc:ide', afterOpen=>\&numberIt, afterClose=>\&locateIt);
329 Tag('omdoc:idt', afterOpen=>\&numberIt, afterClose=>\&locateIt);
330 Tag('omdoc:note', afterOpen=>\&numberIt, afterClose=>\&locateIt);
331 Tag('omdoc:metadata', afterOpen=>\&numberIt, afterClose=>\&locateIt);
332 Tag('omdoc:meta', afterOpen=>\&numberIt, afterClose=>\&locateIt);
333 Tag('omdoc:resource', afterOpen=>\&numberIt, afterClose=>\&locateIt);
334 Tag('omdoc:recurse', afterOpen=>\&numberIt, afterClose=>\&locateIt);
335 Tag('omdoc:imports', afterOpen=>\&numberIt, afterClose=>\&locateIt);
336 Tag('omdoc:theory', afterOpen=>\&numberIt, afterClose=>\&locateIt);
337 Tag('omdoc:ignore', afterOpen=>\&numberIt, afterClose=>\&locateIt);
338 Tag('omdoc:ref', afterOpen=>\&numberIt, afterClose=>\&locateIt);
339 </ltxml>

```

We also have to number some L^AT_EXML tags, so that we do not get into trouble with the OMDoc tags inside them.

```

340 <*ltxml>
341 Tag('ltx:p', afterOpen=>\&numberIt, afterClose=>\&locateIt);
342 Tag('ltx:tabular', afterOpen=>\&numberIt, afterClose=>\&locateIt);
343 Tag('ltx:thead', afterOpen=>\&numberIt, afterClose=>\&locateIt);
344 Tag('ltx:td', afterOpen=>\&numberIt, afterClose=>\&locateIt);
345 Tag('ltx:tr', afterOpen=>\&numberIt, afterClose=>\&locateIt);
346 Tag('ltx:caption', afterOpen=>\&numberIt, afterClose=>\&locateIt);
347 Tag('ltx:Math', afterOpen=>\&numberIt, afterClose=>\&locateIt);

```

⁶EdNOTE: MK: we should probably let L^AT_EXML deal with these and allow more text in the `omdoc+ltxml.xml`

348 `</ltxml>`

The `numberIt` procedure gets the prefix from first parent with an `xml:id` attribute and then extends it with a label that reflects the number of preceding siblings, provided that there is not already an identifier. Additionally, it estimates an XPointer position in the original document of the command sequence which produced the tag. The `locateIt` subroutine is a sibling of `numberIt` as it is required as an `afterClose` handle for tags produced by L^AT_EX environments, as opposed to commands. `locateIt` estimates an XPointer end position of the L^AT_EX environment, allowing to meaningfully locate the entire environment at the source.

349 `<*ltxml>`

```

350 sub numberIt {
351   my($document,$node,$whatsit)=@_;
352   my(@parents)=$document->findnodes('ancestor::*[xml:id]', $node);
353   my $prefix= (@parents ? $parents[$#parents]->getAttribute('xml:id')." " : '');
354   my(@siblings)=$document->findnodes('preceding-sibling::*[xml:id]', $node);
355   my $n = scalar(@siblings)+1;
356   my $id = ($node -> getAttribute('xml:id'));
357   my $localname = $node->localname;
358   $node->setAttribute('xml:id'=>$prefix."$localname$n") unless $id;
359   my $about = $node -> getAttribute('about');
360   $node->setAttribute('about'=>'#'.$node->getAttribute('xml:id')) unless $about;
361   #Also, provide locators:
362   my $locator = $whatsit && $whatsit->getProperty('locator');
363   #Need to inherit locators if missing:
364   $locator = (@parents ? $parents[$#parents]->getAttribute('stex:srcref') : '') unless $locator;
365   if ($locator) {
366     # There is a BUG with namespace declarations (or am I using the API wrongly??) which
367     # does not recognize the stex namespace. Hence, I need to redeclare it...
368     my $parent=$document->getNode;
369     if(! defined $parent->lookupNamespacePrefix("http://kwarc.info/ns/sTeX"))
370       { # namespace not already declared?
371         $document->getDocument->documentElement->setNamespace("http://kwarc.info/ns/sTeX", "stex");
372       }
373     $node->setAttribute('stex:srcref'=>$locator);
374   }return;}
375
376 sub locateIt {
377   my($document,$node,$whatsit)=@_;
378   #Estimate trailer and locator:
379   my $locator = $node->getAttribute('stex:srcref');
380   return unless $locator; # Nothing to do here...
381   my $trailer = $whatsit && $whatsit->getProperty('trailer');
382   $trailer = $trailer->getLocator if $trailer;
383   $trailer = $locator unless $trailer; # bootstrap
384   # TODO: Both should be local, or both remote, any mixture or undefinedness will produce garba
385   my $file_path = LookupValue('SOURCEFILE');
386   my $baselocal = LookupValue('BASELOCAL');
387   # Hmm, we only care about relative paths, so let's just do a URL->pathname map
388   $file_path=~s/~/\w+\/\:\/\/ if $file_path;

```

```

389 $baselocal=~s/^\w+\\:\/\\ if $baselocal;
390 if ($file_path && $baselocal && ($locator =~ s/^(\[^\#\]+\)\#\/\#\/)) {
391     my $relative_path = pathname_relative($file_path,$baselocal);
392     $locator = $relative_path.$locator;
393 }
394 if ($locator =~ /^(.+from=\d+;\d+)/) {
395     my $from = $1;
396     if ($trailer =~ /(,to=\d+;\d+.)$/ ) {
397         my $to = $1;
398         $locator = $from.$to;
399     } else { Error("stex","locator",undef, "Trailer is garbled, expect nonsense in stex:srcref
400 } else { Error("stex","locator",undef, "Locator \"$locator\" is garbled, expect nonsense in s
401 my $parent = $document->getNode;
402 if(! defined $parent->lookupNamespacePrefix("http://kwarc.info/ns/sTeX"))
403     { # namespace not already declared?
404         $document->getDocument->documentElement->setNamespace("http://kwarc.info/ns/sTeX","stex",
405     }
406 $node->setAttribute('stex:srcref' => $locator);
407 return;
408 }
409 </ltxml>#$

```

4.9 Miscellaneous

Some shortcuts that use math symbols but are not mathematical at all; in particular, they should not be translated by L^AT_EXML.

```

410 <*package>
411 \newcommand\hateq{\ensuremath{\hat{=}}\xspace}
412 \newcommand\hatequiv{\ensuremath{\hat{\equiv}}\xspace}
413 \@ifundefined{ergo}%
414 {\newcommand\ergo{\ensuremath{\leadsto}\xspace}}%
415 {\renewcommand\ergo{\ensuremath{\leadsto}\xspace}}%
416 \newcommand{\reflect@sqwig}[2]{\reflectbox{$\m@th#1\rightsquigarrow$}}%
417 \newcommand\ogre{\ensuremath{\mathrel{\mathpalette\reflect@sqwig\relax}}\xspace}%
418 </package>
419 <*ltxml>
420 DefMacro('hateq','@hateq\xspace');
421 DefConstructor('@hateq',"x{2259}");
422 DefMacro('hatequiv','@hatequiv\xspace');
423 DefConstructor('@hatequiv',"x{2A6F}");
424 DefMacro('ergo','@ergo\xspace');
425 DefConstructor('@ergo',"x{219D}");
426 DefMacro('ogre','@ogre\xspace');
427 DefConstructor('@ogre',"x{2B3F}");
428 </ltxml>

```

4.10 Finale

We need to terminate the file with a success mark for perl.

```
429 <ltxml>1;
```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Abelian		group	
group,	<u>5</u>	Abelian,	5

References

- [KGA15a] Michael Kohlhase, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Tech. rep. 2015. URL: <https://github.com/KWARC/sTeX/raw/master/sty/modules/modules.pdf>.
- [KGA15b] Michael Kohlhase, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/get/macros/latex/contrib/stex/modules/modules.pdf>.
- [KGA15c] Michael Kohlhase, Deyan Ginev, and Rares Ambrus. *modules.sty: Semantic Macros and Module Scoping in sTeX*. Self-documenting L^AT_EX package. 2015.
- [Koh06] Michael Kohlhase. OMDoc – *An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh15a] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/metakeys/metakeys.pdf>.
- [Koh15b] Michael Kohlhase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. 2015. URL: <https://github.com/KWARC/sTeX/raw/master/sty/statements/statements.pdf>.
- [sTeX] *KWARC/sTeX*. URL: <https://svn.kwarc.info/repos/stex> (visited on 05/15/2015).