

`omdoc.sty/cls`: Semantic Markup for Open Mathematical Documents in \LaTeX

Michael Kohlhase
Jacobs University, Bremen
<http://kwarc.info/kohlhase>

November 19, 2015

Abstract

The `omdoc` package is part of the \LaTeX collection, a version of $\text{\TeX}/\text{\LaTeX}$ that allows to markup $\text{\TeX}/\text{\LaTeX}$ documents semantically without leaving the document format, essentially turning $\text{\TeX}/\text{\LaTeX}$ into a document format for mathematical knowledge management (MKM).

This package supplies an infrastructure for writing OMDoc documents in \LaTeX . This includes a simple structure sharing mechanism for \LaTeX that allows to move from a copy-and-paste document development model to a copy-and-reference model, which conserves space and simplifies document management. The augmented structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package and Class Options	3
2.2	Document Structure	4
2.3	Ignoring Inputs	5
2.4	Structure Sharing	5
2.5	Colors	6
3	Limitations	6
4	Implementation: The OMDoc Class	7
4.1	Class Options	7
4.2	Setting up Namespaces and Schemata for LaTeXML	8
4.3	Beefing up the <code>document</code> environment	9
5	Implementation: OMDoc Package	10
5.1	Package Options	10
5.2	Document Structure	11
5.3	Front and Backmatter	14
5.4	Ignoring Inputs	15
5.5	Structure Sharing	16
5.6	Colors	17
5.7	L ^A T _E X Commands we interpret differently	17
5.8	Leftovers	17

1 Introduction

$\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ is a version of $\mathcal{T}\mathcal{E}\mathcal{X}/\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}$ that allows to markup $\mathcal{T}\mathcal{E}\mathcal{X}/\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}$ documents semantically without leaving the document format, essentially turning $\mathcal{T}\mathcal{E}\mathcal{X}/\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}$ into a document format for mathematical knowledge management (MKM). The package supports direct translation to the OMDoc format [Koh06]

The `omdoc` package supplies macros and environment that allow to label document fragments and to reference them later in the same document or in other documents. In essence, this enhances the document-as-trees model to documents-as-directed-acyclic-graphs (DAG) model. This structure can be used by MKM systems for added-value services, either directly from the $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ sources, or after translation. Currently, trans-document referencing provided by this package can only be used in the $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ collection.

DAG models of documents allow to replace the “Copy and Paste” in the source document with a label-and-reference model where document are shared in the document source and the formatter does the copying during document formatting/presentation.¹

2 The User Interface

The `omdoc` package generates four files: `omdoc.cls`, `omdoc.sty` and their $\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}\mathcal{M}\mathcal{L}$ bindings `omdoc.cls.ltxml` and `omdoc.sty.ltxml`. We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync. The OMDoc class is a minimally changed variant of the standard `article` class that includes the functionality provided by `omdoc.sty`. Most importantly, `omdoc.cls` sets up the $\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}\mathcal{M}\mathcal{L}$ infrastructure and thus should be used if OMDoc is to be generated from the $\mathcal{S}\mathcal{T}\mathcal{E}\mathcal{X}$ sources. The rest of the documentation pertains to the functionality introduced by `omdoc.sty`.

2.1 Package and Class Options

The `omdoc` package and class accept the following options:

<code>report</code>	load <code>report.cls</code> instead of <code>article.cls</code>
<code>book</code>	load <code>book.cls</code> instead of <code>article.cls</code>
<code>showignores</code>	show the the contents of the <code>ignore</code> environment after all
<code>showmeta</code>	show the metadata; see <code>metakeys.sty</code>
<code>showmods</code>	show modules; see <code>modules.sty</code>
<code>extrefs</code>	allow external references; see <code>sref.sty</code>
<code>defindex</code>	index definienda; see <code>statements.sty</code>

¹EDNOTE: integrate with `latexml`’s `XMRef` in the Math mode.

2.2 Document Structure

document	The top-level document environment is augmented with an optional key/value argument that can be used to give metadata about the document. For the moment
id	only the id key is used to give an identifier to the omdoc element resulting from the L ^A T _E X _{ML} transformation.
omgroup	The structure of the document is given by the omgroup environment just like in OMDoc. In the L ^A T _E X route, the omgroup environment is flexibly mapped to sectioning commands, inducing the proper sectioning level from the nesting of omgroup environments. Correspondingly, the omgroup environment takes an optional key/value argument for metadata followed by a regular argument for the (section) title of the omgroup . The optional metadata argument has the
id	keys id for an identifier, creators and contributors for the Dublin Core meta-
creators	data [DCM03]; see [Koh15a] for details of the format. The short allows to give
contributors	a short title for the generated section. If the title contains semantic macros, they
short	need to be protected by <code>\protect</code> , and we need to give the loadmodules key it
loadmodules	needs no value. For instance we would have

```

\begin{module}{foo}
\symdef{bar}{Ba_r}
...
\begin{omgroup}[id=barderviv,loadmodules]
{Introducing $\protect\bar$ Derivations}

```

blindomgroup	<p> \TeX automatically computes the sectioning level, from the nesting of omgroup environments. But sometimes, we want to skip levels (e.g. to use a subsection* as an introduction for a chapter). Therefore the omdoc package provides a variant blindomgroup that does not produce markup, but increments the sectioning level and logically groups document parts that belong together, but where traditional document markup relies on convention rather than explicit markup. The blindomgroup environment is useful e.g. for creating frontmatter at the correct level. Example 1 shows a typical setup for the outer document structure of a book with parts and chapters. We use two levels of blindomgroup: </p> <ul style="list-style-type: none"> • The outer one groups the introductory parts of the book (which we assume to have a sectioning hierarchy topping at the part level). This blindomgroup makes sure that the introductory remarks become a “chapter” instead of a “part”. • The inner one groups the frontmatter¹ and makes the preface of the book a section-level construct. Note that here the display=flow on the omgroup environment prevents numbering as is traditional for prefaces.
---------------------	---

\currentsectionlevel	The \currentsectionlevel macro supplies the name of the current sectioning level, e.g. “chapter”, or “subsection”. \CurrentSectionLevel is the capitalized variant. They are useful to write something like “In this \currentsectionlevel , we will...” in an omgroup environment, where we do not know which sectioning level we will end up.
\CurrentSectionLevel	

¹We shied away from redefining the **frontmatter** to induce a **blindomgroup**, but this may be the “right” way to go in the future.

```

\begin{document}
\begin{blindomgroup}
\begin{blindomgroup}
\begin{frontmatter}
\maketitle\newpage
\begin{omgroup}[display=flow]{Preface}
... <<preface>> ...
\end{omgroup}
\clearpage\setcounter{tocdepth}{4}\tableofcontents\clearpage
\end{frontmatter}
\end{blindomgroup}
... <<introductory remarks>> ...
\end{blindomgroup}
\begin{omgroup}{Introduction}
... <<intro>> ...
\end{omgroup}
... <<more chapters>> ...
\bibliographystyle{alpha}\bibliography{kwarc}
\end{document}

```

Example 1: A typical Document Structure of a Book

2.3 Ignoring Inputs

ignore The `ignore` environment can be used for hiding text parts from the document structure. The body of the environment is not PDF or DVI output unless the `showignores` option is given to the `omdoc` class or `package`. But in the generated OMDoc result, the body is marked up with a `ignore` element. This is useful in two situations. For

editing One may want to hide unfinished or obsolete parts of a document

narrative/content markup In \LaTeX we mark up narrative-structured documents. In the generated OMDoc documents we want to be able to cache content objects that are not directly visible. For instance in the `statements` package [Koh15c] we use the `\inlinedef` macro to mark up phrase-level definitions, which verbalize more formal definitions. The latter can be hidden by an `ignore` and referenced by the `verbalizes` key in `\inlinedef`.

2.4 Structure Sharing

`\STRlabel` The `\STRlabel` macro takes two arguments: a label and the content and stores the the content for later use by `\STRcopy[$\langle URL \rangle$]{ $\langle label \rangle$ }`, which expands to the previously stored content. If the `\STRlabel` macro was in a different file, then we can give a URL $\langle URL \rangle$ that lets \LaTeXML generate the correct reference.

`\STRcopy`

`\STRsemantics` The `\STRlabel` macro has a variant `\STRsemantics`, where the label argument is optional, and which takes a third argument, which is ignored in \LaTeX . This allows to specify the meaning of the content (whatever that may mean) in cases,

where the source document is not formatted for presentation, but is transformed into some content markup format.

2.5 Colors

For convenience, the `omdoc` package defines a couple of color macros for the `color` package: For instance `\blue` abbreviates `\textcolor{blue}`, so that `\blue{\langle something \rangle}` writes *\langle something \rangle* in blue. The macros `\red`, `\green`, `\cyan`, `\magenta`, `\brown`, `\yellow`, `\orange`, `\gray`, and finally `\black` are analogous.

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the `sTeX` GitHub repository [sTeX].

1. when option `book` which uses `\pagestyle{headings}` is given and semantic macros are given in the `omgroup` titles, then they sometimes are not defined by the time the heading is formatted. Need to look into how the headings are made.

4 Implementation: The OMDoc Class

The functionality is spread over the `omdoc` class and package. The class provides the `document` environment and the `omdoc` element corresponds to it, whereas the package provides the concrete functionality.

`omdoc.dtx` generates four files: `omdoc.cls` (all the code between `<*cls>` and `</cls>`), `omdoc.sty` (between `<*package>` and `</package>`) and their \LaTeX ML bindings (between `<*ltxml.cls>` and `</ltxml.cls>` and `<*ltxml.sty>` and `</ltxml.sty>` respectively). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

The initial setup for \LaTeX ML (both package and class actually):

```
1 <*ltxml.sty | ltxml.cls>
2 # -*- CPERL -*-
3 package LaTeXML::Package::Pool;
4 use strict;
5 use LaTeXML::Package;
6 use LaTeXML::Util::Pathname;
7 use Cwd qw(abs_path);
8 </ltxml.sty | ltxml.cls>
```

4.1 Class Options

To initialize the `omdoc` class, we declare and process the necessary options. For `omdoc.cls` this is quite simple. We have options `report` and `book`, which set the `\omdoc@class` macro and pass on the macro to `omdoc.sty` for further processing. The `book` option also sets the conditional to true for the frontmatter handling later.

`\omdoc@class`
`\ifclass@book`

```
9 <*cls>
10 \def\omdoc@class{article}
11 \DeclareOption{report}{\def\omdoc@class{report}%
12 \PassOptionsToPackage{\CurrentOption}{omdoc}}
13 \newif\ifclass@book\class@bookfalse
14 \DeclareOption{book}{\def\omdoc@class{book}\class@booktrue%
15 \PassOptionsToPackage{\CurrentOption}{omdoc}}
```

the rest of the options are only passed on to `omdoc.sty` and the class selected by the first options.

```
16 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{\omdoc@class}
17 \PassOptionsToPackage{\CurrentOption}{omdoc}}
18 \ProcessOptions
19 </cls>
20 <*ltxml.cls>
21 AssignValue('omdoc@class'=>'article');
22 DeclareOption('report', sub {AssignValue('omdoc@class' => 'report'); });
23 DeclareOption('book', sub {AssignValue('omdoc@class' => 'book'); });
24 DeclareOption(undef, sub {PassOptions('article','cls',ToString(Digest(T_CS('\CurrentOption'))))
25 PassOptions('omdoc','sty',ToString(Digest(T_CS('\Curr
```

```

26 ProcessOptions();
27 </ltxml.cls>

```

We load `article.cls`, and the desired packages. For the L^AT_EX_ML bindings, we make sure the right packages are loaded.

```

28 <*cls>
29 \LoadClass{\omdoc@class}
30 \RequirePackage{etoolbox}
31 \RequirePackage{omdoc}
32 </cls>
33 <*ltxml.cls>
34 my $class = LookupValue('omdoc@class');
35 LoadClass($class);
36 </ltxml.cls>

```

4.2 Setting up Namespaces and Schemata for L^AT_EX_ML

Now, we also need to register the namespace prefixes for L^AT_EX_ML to use.

```

37 <*ltxml.cls>
38 RegisterNamespace('omdoc'=>"http://omdoc.org/ns");
39 RegisterNamespace('om'=>"http://www.openmath.org/OpenMath");
40 RegisterNamespace('m'=>"http://www.w3.org/1998/Math/MathML");
41 RegisterNamespace('dc'=>"http://purl.org/dc/elements/1.1/");
42 RegisterNamespace('cc'=>"http://creativecommons.org/ns");
43 RegisterNamespace('stex'=>"http://kwarc.info/ns/sTeX");
44 RegisterNamespace('ltx'=>"http://dlmf.nist.gov/LaTeXML");
45 </ltxml.cls>

```

Since we are dealing with a class, we need to set up the document type in the L^AT_EX_ML bindings.

```

46 <*ltxml.cls>
47 RelaxNGSchema('omdoc+ltxml',
48     '#default'=>"http://omdoc.org/ns",
49     'om'=>"http://www.openmath.org/OpenMath",
50     'm'=>"http://www.w3.org/1998/Math/MathML",
51     'dc'=>"http://purl.org/dc/elements/1.1/",
52     'cc'=>"http://creativecommons.org/ns",
53     'stex'=>"http://kwarc.info/ns/sTeX",
54     'ltx'=>"http://dlmf.nist.gov/LaTeXML");
55 </ltxml.cls>

```

Then we load the `omdoc` package `omdoc.sty`, which contains the main body of functionality (e.g.sectioning/grouping). It can be loaded by classes other than `omdoc.cls` as well.

```

56 <*ltxml.cls>
57 RequirePackage('omdoc');
58 </ltxml.cls>

```


4.3 Beefing up the document environment

Now, we will define the environments we need. The top-level one is the `document` environment, which we redefined so that we can provide keyval arguments.

`document` For the moment we do not use them on the \LaTeX level, but the document identifier is picked up by \LaTeX ML.

```

59 <*cls>
60 \let\orig@document=\document
61 \srefaddidkey{document}
62 \renewcommand{\document}[1][\metasetkeys{document}{#1}\orig@document}
63 </cls>
64 <*ltxml.cls>
65 sub xmlBase {
66   my $baseuri = LookupValue('URLBASE');
67   $baseuri =~ s\/$//g; # No trailing slashes
68   Tokenize($baseuri); }
69 DefEnvironment('{document} OptionalKeyVals:omdoc',
70   "<omdoc:omdoc "
71   . "&GetKeyVal{#1,'id'}(xml:id='&GetKeyVal{#1,'id'}))"
72   . "(?&Tokenize(&LookupValue('SOURCEBASE'))"
73   . "(xml:id='&Tokenize(&LookupValue('SOURCEBASE')).omdoc'))() "
74   . "&Tokenize(&LookupValue('URLBASE'))"
75   . "(xml:base='&xmlBase()')()>"
76   . "#body"
77   . "</omdoc:omdoc>",
78   beforeDigest=> sub { AssignValue(inPreamble=>0); },
79   afterDigest=> sub { $_[0]->getGullet->flush; return; },
80   afterDigestBegin => sub {
81     $_[1]->setProperty(id => Expand(T_CS('\thedocument@ID')));
82     if (my $ops = LookupValue('@at@begin@document')) {
83       Digest(Tokens(@$ops)); }
84     else {
85       return; } },
86   beforeDigestEnd => sub {
87     $_[0]->getGullet->flush;
88     if (my $ops = LookupValue('@at@end@document')) {
89       Digest(Tokens(@$ops)); }
90     else {
91       return; } },
92   mode => 'text');
93 Tag('omdoc:omdoc', 'afterOpen:late'=>\&insertFrontMatter,
94   afterOpen=>\&numberIt,afterClose=>\&locateIt);
95 </ltxml.cls>%$

```

5 Implementation: OMDoc Package

5.1 Package Options

The package options come in two parts: the first we only pass on to the various other \TeX packages.

```
96 <*package>
97 \DeclareOption{showmeta}{\PassOptionsToPackage{\CurrentOption}{metakeys}}
98 \DeclareOption{showmods}{\PassOptionsToPackage{\CurrentOption}{modules}}
99 \DeclareOption{extrefs}{\PassOptionsToPackage{\CurrentOption}{sref}}
100 \DeclareOption{noauxreq}{\PassOptionsToPackage{\CurrentOption}{modules}}
101 \DeclareOption{defindex}{\PassOptionsToPackage{\CurrentOption}{statements}}
102 </package>
103 <*ltxml.sty>
104 DeclareOption('showmeta',sub {PassOptions('metakeys','sty',ToString(Digest(T_CS('\CurrentOption
105 DeclareOption('showmods',sub {PassOptions('modules','sty',ToString(Digest(T_CS('\CurrentOption'
106 DeclareOption('extrefs',sub {PassOptions('sref','sty',ToString(Digest(T_CS('\CurrentOption'))))
107 DeclareOption('noauxreq',sub {PassOptions('modules','sty',ToString(Digest(T_CS('\CurrentOption'
108 DeclareOption('defindex',sub {PassOptions('statements','sty',ToString(Digest(T_CS('\CurrentOpti
109 </ltxml.sty>
```

For the rest we declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false). The `report` and `book` options affect the sectioning behavior of the `omgroup` environment via the `\section@level` macro later.

`\section@level`

```
110 <*package>
111 \newif\ifshow@ignores\show@ignorefalse
112 \DeclareOption{showignores}{\show@ignoretrue}
113 \newcount\section@level\section@level=2
114 \DeclareOption{report}{\section@level=0}
115 \DeclareOption{book}{\section@level=0}
116 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{sref}}
117 \ProcessOptions
118 </package>
119 <*ltxml.sty>
120 DeclareOption(undef, sub {PassOptions('omtext','sty',ToString(Digest(T_CS('\CurrentOption'))));
121 ProcessOptions();
122 </ltxml.sty>
```

Then we need to set up the packages by requiring the `sref` package to be loaded.

```
123 <*package>
124 \RequirePackage{sref}
125 \RequirePackage{xspace}
126 \RequirePackage{comment}
127 \RequirePackage{etoolbox}
128 </package>
129 <*ltxml.sty>
```

```

130 RequirePackage('sref');
131 RequirePackage('xspace');
132 RequirePackage('omtext');
133 \ltxml.sty

```

5.2 Document Structure

The structure of the document is given by the `omgroup` environment just like in OMDoc. The hierarchy is adjusted automatically according to the L^AT_EX class in effect.

EdN:2 `\currentsectionlevel` For the `\currentsectionlevel` and `\Currentsectionlevel` macros we use an internal macro `\current@section@level` that only contains the keyword (no markup). We initialize it with “document” as a default. In the generated OMDoc, we only generate a text element of class `omdoc_currentsectionlevel`, which will be instantiated by CSS later.²

```

134 \*package
135 \def\current@section@level{document}%
136 \newcommand\currentsectionlevel{\lowercase\expandafter{\current@section@level}\xspace}%
137 \newcommand\Currentsectionlevel{\expandafter\MakeUppercase\current@section@level\xspace}%
138 \*package
139 \ltxml.sty
140 DefMacro('currentsectionlevel', '@currentsectionlevel\xspace');
141 DefMacro('Currentsectionlevel', '@Currentsectionlevel\xspace');
142 DefConstructor('\currentsectionlevel',
143               "<ltx:text class='omdoc-currentsectionlevel'>section</ltx:text>");
144 DefConstructor('\Currentsectionlevel',
145               "<ltx:text class='omdoc-Currentsectionlevel'>Section</ltx:text>");
146 \ltxml.sty

```

`blindomgroup`

```

147 \*package
148 \newcommand\at@begin@blindomgroup[1]{
149 \newenvironment{blindomgroup}
150 {\advance\section@level by 1\at@begin@blindomgroup\section@level}
151 {\advance\section@level by -1}
152 \*package
153 \ltxml.sty
154 DefEnvironment('{blindomgroup} OptionalKeyVals:omgroup',
155               "<omdoc:omgroup layout='invisible'"
156               . "&GetKeyVal{#1,'id'}(xml:id='&GetKeyVal{#1,'id'}')()\""
157               . "&GetKeyVal{#1,'type'}(type='&GetKeyVal{#1,'type'}')()>\n"
158               . "#body\n"
159               . "</omdoc:omgroup>");
160 \ltxml.sty

```

²EDNOTE: MK: we may have to experiment with the more powerful uppercasing macro from `mfirstuc.sty` once we internationalize.

`\omgroup@nonum` convenience macro: `\omgroup@nonum{<level>}{<title>}` makes an unnumbered sectioning with title *<title>* at level *<level>*.

```
161 <*package>
162 \newcommand\omgroup@nonum[2]{%
163 \ifx\hyper@anchor\@undefined\else\phantomsection\fi%
164 \addcontentsline{toc}{#1}{#2}\@nameuse{#1}*{#2}}
```

`\omgroup@num` convenience macro: `\omgroup@num{<level>}{<title>}` makes numbered sectioning with title *<title>* at level *<level>*. We have to check the `short` key was given in the `omgroup` environment and – if it is use it. But how to do that depends on whether the `rdfmata` package has been loaded.

```
165 \newcommand\omgroup@num[2]{%
166 \sref{label{id}\omdoc@sect@name~\@nameuse{the#1}}}%
167 \ifx\omgroup@short\@empty\@nameuse{#1}{#2}%
168 \else\@ifundefined{rdfmata@sectioning}{\@nameuse{#1}[\omgroup@short]{#2}}%
169 {\@nameuse{rdfmata@#1@old}[\omgroup@short]{#2}}%
170 \fi}
171 </package>
```

`omgroup`

```
172 <*package>
173 \def\@true{true}
174 \def\@false{false}
175 \srefaddidkey{omgroup}
176 \addmetakey{omgroup}{date}
177 \addmetakey{omgroup}{creators}
178 \addmetakey{omgroup}{contributors}
179 \addmetakey{omgroup}{srccite}
180 \addmetakey{omgroup}{type}
181 \addmetakey*{omgroup}{short}
182 \addmetakey*{omgroup}{display}
183 \addmetakey[false]{omgroup}{loadmodules}[true]
```

we define a switch for numbering lines and a hook for the beginning of groups:

`\at@begin@omgroup` The `\at@begin@omgroup` macro allows customization. It is run at the beginning of the `omgroup`, i.e. after the section heading.

```
184 \newif\if@num\@numtrue
185 \newif\if@frontmatter\@frontmatterfalse
186 \newif\if@backmatter\@backmatterfalse
187 \newcommand\at@begin@omgroup[3][]{}
```

Then we define a helper macro that takes care of the sectioning magic. It comes with its own key/value interface for customization.

```
188 \addmetakey{omdoc@sect}{name}
189 \addmetakey[false]{omdoc@sect}{clear}[true]
190 \addmetakey{omdoc@sect}{ref}
191 \addmetakey[false]{omdoc@sect}{num}[true]
192 \newcommand\omdoc@sectioning[3][]{\metasetkeys{omdoc@sect}{#1}%
193 \ifx\omdoc@sect@clear\@true\cleardoublepage\fi%
```

```

194 \if@num% numbering not overridden by frontmatter, etc.
195 \ifx\omdoc@sect@num\@true\omgroup@num{#2}{#3}\else\omgroup@nonum{#2}{#3}\fi%
196 \def\current@section@level{\omdoc@sect@name}%
197 \else\omgroup@nonum{#2}{#3}\fi}

```

and another one, if redefines the `\addtocontentsline` macro of L^AT_EX to import the respective macros. It takes as an argument a list of module names.³

```

198 \newcommand\omgroup@redefine@addtocontents[1]{\edef\@import{#1}%
199 \@for\@I:=\@import\do{\edef\@path{\csname module@\@I @path\endcsname}%
200 \@ifundefined{tf@toc}\relax{\protected@write\tf@toc}{\string\@requiremodules{\@path}{sms}}}}
201 \ifx\hyper@anchor\@undefined% hyperref.sty loaded?
202 \def\addcontentsline##1##2##3{%
203 \addtocontents{##1}{\protect\contentsline{##2}{\string\importmodules{##1}{##3}{\thepage}}}%
204 \else\def\addcontentsline##1##2##3{%
205 \addtocontents{##1}{\protect\contentsline{##2}{\string\importmodules{##1}{##3}{\thepage}}{\@current
206 \fi}% hyperref.sty loaded?

```

now the `omgroup` environment itself. This takes care of the table of contents via the helper macro above and then selects the appropriate sectioning command from `article.cls`.

```

207 \newenvironment{omgroup}[2][]% keys, title
208 {\metasetkeys{omgroup}{#1}\sref@target%
209 \ifx\omgroup@display\st@flow\@numfalse\fi
210 \if@frontmatter\@numfalse\fi

```

If the `loadmodules` key is set on `\begin{omgroup}`, we redefine the `\addcontetsline` macro that determines how the sectioning commands below construct the entries for the table of contents.

```

211 \ifx\omgroup@loadmodules\@true%
212 \omgroup@redefine@addtocontents{\@ifundefined{mod@id}\imported@modules%
213 {\@ifundefined{module@\mod@id @path}{\imported@modules}\mod@id}}\fi%
214 \advance\section@level by 1
215 \ifcase\section@level%
216 \or\omdoc@sectioning[name=Part,clear,num]{part}{#2}%
217 \or\omdoc@sectioning[name=Chapter,clear,num]{chapter}{#2}%
218 \or\omdoc@sectioning[name=Section,num]{section}{#2}%
219 \or\omdoc@sectioning[name=Subsection,num]{subsection}{#2}%
220 \or\omdoc@sectioning[name=Subsubsection,num]{subsubsection}{#2}%
221 \or\omdoc@sectioning[name=Paragraph,ref=this paragraph]{paragraph}{#2}%
222 \or\omdoc@sectioning[name=Subparagraph,ref=this subparagraph]{subparagraph}{#2}%
223 \fi% \ifcase
224 \at@begin@omgroup[#1]\section@level{#2}}% for customization
225 {\advance\section@level by -1}
226 \end{package}
227 \end{*txml.sty}

```

³EDNOTE: MK: the extension `sms` is hard-coded here, but should not be. This will not work in multilingual settings.

```

228 DefEnvironment('{omgroup} OptionalKeyVals:omgroup {}',
229               "<omdoc:omgroup layout='sectioning'"
230               .   "?&GetKeyVal(#1,'id')(xml:id='&GetKeyVal(#1,'id'))()"
231               .   "?&GetKeyVal(#1,'type')(type='&GetKeyVal(#1,'type'))()">\n"
232               .   "<dc:title>#2</dc:title>\n"
233               .   "#body\n"
234               .   "</omdoc:omgroup>");
235 </ltxml.sty>

```

5.3 Front and Backmatter

Index markup is provided by the `omtext` package [Koh15b], so in the `omdoc` package we only need to supply the corresponding `\printindex` command, if it is not already defined

```

\printindex
236 <*package>
237 \providecommand\printindex{\IfFileExists{\jobname.ind}{\input{\jobname.ind}}{}}
238 </package>
239 <*ltxml.sty>
240 DefConstructor('\printindex','<omdoc:index/>');
241 Tag('omdoc:index',afterOpen=>\&numberIt,afterClose=>\&locateIt);
242 </ltxml.sty>

```

`\tableofcontents` The table of contents already exists in L^AT_EX, so we only need to provide a L^AT_EXML binding for it.

```

243 <*ltxml.sty>
244 DefConstructor('\tableofcontents',
245               "<omdoc:tableofcontents level='&ToString(&CounterValue('tocdepth'))' />");
246 Tag('omdoc:tableofcontents',afterOpen=>\&numberIt,afterClose=>\&locateIt);
247 </ltxml.sty>

```

The case of the `\bibliography` command is similar

```

\bibliography
248 <*ltxml.sty>
249 DefConstructor('\bibliography{}',"<omdoc:bibliography files='#1' />");
250 Tag('omdoc:bibliography',afterOpen=>\&numberIt,afterClose=>\&locateIt);
251 </ltxml.sty>

```

`frontmatter` `book.cls` already has a `\frontmatter` macro, so we have to redefine the front matter environment in this case.

```

252 <*cls>
253 \ifclass@book
254 \renewenvironment{frontmatter}
255 {\@frontmattertrue\cleardoublepage\@mainmatterfalse\pagenumbering{roman}}
256 {\@frontmatterfalse\setcounter{page}{1}\pagenumbering{arabic}}
257 \else

```

```

258 \newenvironment{frontmatter}
259 {\@frontmattertrue\pagenumbering{roman}}
260 {\@frontmatterfalse\setcounter{page}{1}\pagenumbering{arabic}}
261 \fi
262 \</cls>
263 \<!--*ltxml.cls-->
264 DefEnvironment('{frontmatter}', '#body');
265 \</ltxml.cls>
266 % \End{macrocode}
267 % \end{environment}
268 %
269 % \begin{environment}{backmatter}
270 % |book.cls| already has a |\backmatter| macro, so we have to redefine the back
271 % matter environment in this case.
272 % \begin{macrocode}
273 \<!--*cls-->
274 \ifclass@book
275 \renewenvironment{backmatter}
276 {\cleardoublepage\@mainmatterfalse\@backmattertrue}
277 {\@backmatterfalse}
278 \else
279 \newenvironment{backmatter}{\@backmattertrue}{\@backmatterfalse}
280 \fi
281 \</cls>
282 \<!--*ltxml.cls-->
283 DefEnvironment('{backmatter}', '#body');
284 \</ltxml.cls>

```

5.4 Ignoring Inputs

ignore

```

285 \<!--*package-->
286 \ifshow@ignores
287 \addmetakey{ignore}{type}
288 \addmetakey{ignore}{comment}
289 \newenvironment{ignore}[1] []
290 {\metasetkeys{ignore}{#1}\textless\ignore@type\textgreater\bgrou\itshape}
291 {\egrou\textless/\ignore@type\textgreater}
292 \renewenvironment{ignore}{}{} \else\excludecomment{ignore}\fi
293 \</package>
294 \<!--*ltxml.sty-->
295 DefKeyVal('ignore', 'type', 'Semiverbatim');
296 DefKeyVal('ignore', 'comment', 'Semiverbatim');
297 DefEnvironment('{ignore} OptionalKeyVals:ignore',
298               "<omdoc:ignore %&GetKeyVals(#1)>#body</omdoc:ignore>");
299 Tag('omdoc:ignore', afterOpen=>\&numberIt, afterClose=>\&locateIt);
300 \</ltxml.sty>

```

5.5 Structure Sharing

`\STRlabel` The main macro, it is used to attach a label to some text expansion. Later on, using the `\STRcopy` macro, the author can use this label to get the expansion originally assigned.

```
301 <*package>
302 \long\def\STRlabel#1#2{\STRlabeldef{#1}{#2}{#2}}
303 </package>
304 <*ltxml.sty>
305 DefConstructor('\STRlabel{}{}', sub {
306   my($document,$label,$object)=@_;
307   $document->absorb($object);
308   $document->addAttribute('xml:id'=>ToString($label)) if $label; });
309 </ltxml.sty>
```

`\STRcopy` The `\STRcopy` macro is used to call the expansion of a given label. In case the label is not defined it will issue a warning.⁴

```
310 <*package>
311 \newcommand\STRcopy[2] [] {\expandafter\ifx\csname STR@#2\endcsname\relax
312 \message{STR warning: reference #2 undefined!}
313 \else\csname STR@#2\endcsname\fi}
314 </package>
315 <*ltxml.sty>
316 DefConstructor('\STRcopy[]{}', "<omdoc:ref xref='#1##2'/>");
317 Tag('omdoc:ref', afterOpen=>\&numberIt, afterClose=>\&locateIt);
318 </ltxml.sty>
```

`\STRsemantics` if we have a presentation form and a semantic form, then we can use

```
319 <*package>
320 \newcommand\STRsemantics[3] [] {#2\def\@test{#1}\ifx\@test\empty\STRlabeldef{#1}{#2}\fi}
321 </package>
322 <*ltxml.sty>
323 DefConstructor('\STRsemantics[]{}{}', sub {
324   my($document,$label,$ignore,$object)=@_;
325   $document->absorb($object);
326   $document->addAttribute('xml:id'=>ToString($label)) if $label; });
327 </ltxml.sty>##$
```

`\STRlabeldef` This is the macro that does the actual labeling. Is it called inside `\STRlabel`

```
328 <*package>
329 \def\STRlabeldef#1{\expandafter\gdef\csname STR@#1\endcsname}
330 </package>
331 <*ltxml.sty>
332 DefMacro('\STRlabeldef{}{}', "");
333 </ltxml.sty>
```

⁴EDNOTE: MK: we need to do something about the ref!

5.6 Colors

blue, red, green, magenta We will use the following abbreviations for colors from `color.sty`

```
334 <*package>
335 \def\black#1{\textcolor{black}{#1}}
336 \def\gray#1{\textcolor{gray}{#1}}
337 \def\blue#1{\textcolor{blue}{#1}}
338 \def\red#1{\textcolor{red}{#1}}
339 \def\green#1{\textcolor{green}{#1}}
340 \def\cyan#1{\textcolor{cyan}{#1}}
341 \def\magenta#1{\textcolor{magenta}{#1}}
342 \def\brown#1{\textcolor{brown}{#1}}
343 \def\yellow#1{\textcolor{yellow}{#1}}
344 \def\orange#1{\textcolor{orange}{#1}}
345 </package>
```

For the L^AT_EX XML bindings, we go a generic route, we replace `\blue{#1}` by `{\@omdoc@color{blue}\@omdoc@color@content{#1}}`.

```
346 <*ltxml.sty>
347 sub omdocColorMacro {
348   my ($color, @args) = @_;
349   my $tok_color = TokenizeInternal($color);
350   (T_BEGIN, T_CS('\@omdoc@color'), T_BEGIN, $tok_color->unlist,
351    T_END, T_CS('\@omdoc@color@content'), T_OTHER(''), $tok_color->unlist, T_OTHER('')),
352   T_BEGIN, $args[1]->unlist, T_END, T_END); }
353 DefMacro('\@omdoc@color{', sub { MergeFont(color=>$_[1]->toString); return; });#$
354 </ltxml.sty>
```

Ideally, here we will remove the optional argument and have a conversion module add the attribute at the end (or maybe add it just for math?) or, we can take the attributes for style from the current font ?

```
355 <*ltxml.sty>
356 DefConstructor('\@omdoc@color@content[]{}',
357   "?#isMath(#2)(<ltx:text ?#1(style='color:#1')()>#2</ltx:text>)");
358 foreach my $color(qw(black gray blue red green cyan magenta brown yellow orange)) {
359   DefMacro("\\".$color.'{}', sub { omdocColorMacro($color, @_); }); }#$
360 </ltxml.sty>
```

5.7 L^AT_EX Commands we interpret differently

The reinterpretations are quite simple, we either disregard presentational markup or we re-interpret it in terms of OMDoc.

```
361 <*ltxml.sty>
362 DefConstructor('\newpage', '');
363 </ltxml.sty>
```

5.8 Leftovers

```
364 <*package>
```

```

365 \newcommand\baseUrl[2] [] {}
366 \end{package}
367 \end{ltxml.sty}
368 DefMacro('\baseUrl []Semiverbatim', sub {
369   my $baselocal = ToString(Digest($_[1]));
370   $baselocal = abs_path($baselocal) unless $baselocal =~ /^(w+):\/\//;
371   AssignValue('BASELOCAL'=>$baselocal,'global');
372   AssignValue('URLBASE'=>ToString(Digest($_[2])), 'global');
373 });
374 \end{ltxml.sty}%$

```

EdN:5 ⁵ and finally, we need to terminate the file with a success mark for perl.

```

375 \end{ltxml.sty} | ltxml.cls 1;

```

⁵EDNOTE: this should be handled differently, omdoc.sty should include url and give a new macro for it, which we then use in omdoc

References

- [DCM03] The DCMI Usage Board. *DCMI Metadata Terms*. DCMI Recommendation. Dublin Core Metadata Initiative, 2003. URL: <http://dublincore.org/documents/dcmi-terms/>.
- [Koh06] Michael Kohlhase. OMDOC – *An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh15a] Michael Kohlhase. *dcm.sty: An Infrastructure for marking up Dublin Core Metadata in L^AT_EX documents*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/dcm/dcm.pdf>.
- [Koh15b] Michael Kohlhase. *omtext: Semantic Markup for Mathematical Text Fragments in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/omtext/omtext.pdf>.
- [Koh15c] Michael Kohlhase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/statements/statements.pdf>.
- [sTeX] *KWARC/sTeX*. URL: <https://svn.kwarc.info/repos/stex> (visited on 05/15/2015).