

`modules.sty`: Semantic Macros and Module Scoping in \LaTeX^*

Michael Kohlhase & Deyan Ginev & Rares Ambrus
Jacobs University, Bremen
<http://kwarc.info/kohlhase>

March 31, 2015

Abstract

The `modules` package is a central part of the \LaTeX collection, a version of $\text{\TeX}/\text{\LaTeX}$ that allows to markup $\text{\TeX}/\text{\LaTeX}$ documents semantically without leaving the document format, essentially turning $\text{\TeX}/\text{\LaTeX}$ into a document format for mathematical knowledge management (MKM).

This package supplies a definition mechanism for semantic macros and a non-standard scoping construct for them, which is oriented at the semantic dependency relation rather than the document structure. This structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

*Version v1.3 (last revised 2013/12/12)

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package Options	3
2.2	Semantic Macros	4
2.3	Testing Semantic Macros	6
2.4	Semantic Macros for Variables	6
2.5	Symbol and Concept Names	7
2.6	Modules and Inheritance	8
2.7	Dealing with multiple Files	9
2.8	Using Semantic Macros in Narrative Structures	11
2.9	Including Externally Defined Semantic Macros	12
2.10	Views	12
2.11	Support for MathHub	13
3	Limitations & Extensions	14
3.1	Perl Utility sms	14
3.2	Module Signatures loaded even if Modules are	14
3.3	Only one level of path simplification	14
3.4	Qualified Imports	14
3.5	Error Messages	15
3.6	Crossreferencing	15
3.7	No Forward Imports	15
4	The Implementation	16
4.1	Package Options	16
4.2	Modules and Inheritance	16
4.3	Semantic Macros	19
4.4	Defining Math Operators	22
4.5	Semantic Macros for Variables	22
4.6	Testing Semantic Macros	23
4.7	Symbol and Concept Names	23
4.8	Dealing with Multiple Files	24
4.9	Loading Module Signatures	25
4.10	Including Externally Defined Semantic Macros	28
4.11	Views	28
4.12	Support for MathHub	29
4.13	Deprecated Functionality	31
4.14	Experiments	32

1 Introduction

Following general practice in the $\text{\TeX}/\text{\LaTeX}$ community, we use the term “semantic macro” for a macro whose expansion stands for a mathematical object, and whose name (the command sequence) is inspired by the name of the mathematical object. This can range from simple definitions like `\def\Reals{\mathbb{R}}` for individual mathematical objects to more complex (functional) ones object constructors like `\def\SmoothFunctionsOn#1{\mathcal{C}^\infty(\#1,\#1)}`. Semantic macros are traditionally used to make $\text{\TeX}/\text{\LaTeX}$ code more portable. However, the $\text{\TeX}/\text{\LaTeX}$ scoping model (macro definitions are scoped either in the local group or until the rest of the document), does not mirror mathematical practice, where notations are scoped by mathematical environments like statements, theories, or such. For an in-depth discussion of semantic macros and scoping we refer the reader [Koh08].

The `modules` package provides a \LaTeX -based markup infrastructure for defining module-scoped semantic macros and \LaTeX ML bindings [LTX] to create OMDOC [Koh06] from \gTeX documents. In the \gTeX world semantic macros have a special status, since they allow the transformation of $\text{\TeX}/\text{\LaTeX}$ formulae into a content-oriented markup format like OPENMATH [Bus+04] and (strict) content MATHML [Aus+10]; see Figure 1 for an example, where the semantic macros above have been defined by the `\symdef` macros (see Section 2.2) in the scope of a `\begin{module}[id=calculus]` (see Section 2.6).

\LaTeX	<code>\SmoothFunctionsOn\Reals</code>
PDF/DVI	$\mathcal{C}^\infty(\mathbb{R}, \mathbb{R})$
OPENMATH	<pre>% <OMA> % <OMS cd="calculus" name="SmoothFunctionsOn"/> % <OMS cd="calculus" name="Reals"/> % </OMA></pre>
MATHML	<pre>% <apply> % <csymbol cd="calculus">SmoothFunctionsOn</csymbol> % <csymbol cd="calculus">Reals</csymbol> % </apply></pre>

Example 1: OPENMATH and MATHML generated from Semantic Macros

2 The User Interface

The main contributions of the `modules` package are the `module` environment, which allows for lexical scoping of semantic macros with inheritance and the `\symdef` macro for declaration of semantic macros that underly the `module` scoping.

2.1 Package Options

`showmods` The `modules` package takes two options: If we set `showmods`¹, then the views (see

¹EDNOTE: This mechanism does not work yet, since we cannot disable it when importing modules and that leads to unwanted boxes. What we need to do instead is to tweak the `sms` utility to use an

<code>qualifiedimports</code>	Section 2.10) are shown. If we set the <code>qualifiedimports</code> option, then qualified imports are enabled. Qualified imports give more flexibility in module inheritance, but consume more internal memory. As qualified imports are not fully implemented at the moment, they are turned off by default see Limitation 3.4.
<code>noauxreq</code>	The option <code>noauxreq</code> prohibits the registration of <code>\@requiremodules</code> commands in the <code>aux</code> file. They are necessary for preloading the module signatures so that entries in the table of contents can have semantic macros; but as they sometimes cause trouble the option allows to turn off preloading.
<code>showmeta</code>	If the <code>showmeta</code> is set, then the metadata keys are shown (see [Koh15a] for details and customization options).

2.2 Semantic Macros

`\symdef` The is the main constructor for semantic macros in \LaTeX . A call to the `\symdef` macro has the general form

$$\text{\symdef}[\langle keys \rangle][\langle cseq \rangle][\langle args \rangle][\langle definiens \rangle]$$

where $\langle cseq \rangle$ is a control sequence (the name of the semantic macro) $\langle args \rangle$ is a number between 0 and 9 for the number of arguments $\langle definiens \rangle$ is the token sequence used in macro expansion for $\langle cseq \rangle$. Finally $\langle keys \rangle$ is a keyword list that further specifies the semantic status of the defined macro.

The two semantic macros in Figure 1 would have been declared by invocations of the `\symdef` macro of the form:

$$\begin{aligned} &\text{\symdef}\{\text{Reals}\}\{\text{\mathbb{R}}\} \\ &\text{\symdef}\{\text{SmoothFunctionsOn}\}[1]\{\text{\mathcal{C}}^{\infty}(\#1,\#1)\} \end{aligned}$$

Note that both semantic macros correspond to OPENMATH or MATHML “symbols”, i.e. named representations of mathematical concepts (the real numbers and the constructor for the space of smooth functions over a set); we call these names the **symbol name** of a semantic macro. Normally, the symbol name of a semantic macro declared by a `\symdef` directive is just $\langle cseq \rangle$. The key-value pair `name= $\langle symname \rangle$` can be used to override this behavior and specify a differing name. There are two main use cases for this.

The first one is shown in Example 3, where we define semantic macros for the “exclusive or” operator. Note that we define two semantic macros: `\xorOp` and `\xor` for the applied form and the operator. As both relate to the same mathematical concept, their symbol names should be the same, so we specify `name=xor` on the definition of `\xorOp`.

`local` A key `local` can be added to $\langle keys \rangle$ to specify that the symbol is local to the module and is invisible outside. Note that even though `\symdef` has no advantage over `\def` for defining local semantic macros, it is still considered good style to use `\symdef` and `\abbrdef`, if only to make switching between local and exported semantic macros easier.

`primary` Finally, the key `primary` (no value) can be given for primary symbols.

internal version that never shows anything during sms reading.

`\abbrdef` The `\abbrdef` macro is a variant of `\symdef` that is only different in semantics, not in presentation. An abbreviative macro is like a semantic macro, and underlies the same scoping and inheritance rules, but it is just an abbreviation that is meant to be expanded, it does not stand for an atomic mathematical object.

We will use a simple module for natural number arithmetics as a running example. It defines exponentiation and summation as new concepts while drawing on the basic operations like $+$ and $-$ from L^AT_EX. In our example, we will define a semantic macro for summation `\Sumfromto`, which will allow us to express an expression like $\sum_{i=1}^n x^i$ as `\Sumfromto{i}1n{2i-1}` (see Example 2 for an example). In this example we have also made use of a local semantic symbol for n , which is treated as an arbitrary (but fixed) symbol.

```
\begin{module}[id=arith]
  \symdef{Sumfromto}[4]{\sum_{\#1=\#2}^{\#3}{\#4}}
  \symdef[local]{arbitraryn}{n}
  What is the sum of the first $\arbitraryn$ odd numbers, i.e.
  $\Sumfromto{i}1\arbitraryn{2i-1}$?
\end{module}
```

What is the sum of the first n odd numbers, i.e. $\sum_{i=1}^n 2i - 1$?

Example 2: Semantic Markup in a module Context

`\symvariant` The `\symvariant` macro can be used to define presentation variants for semantic macros previously defined via the `\symdef` directive. In an invocation

```
\symdef[⟨keys⟩]{⟨cseq⟩}[⟨args⟩]{⟨pres⟩}
\symvariant{⟨cseq⟩}[⟨args⟩]{⟨var⟩}{⟨varpres⟩}
```

the first line defines the semantic macro `\⟨cseq⟩` that when applied to `⟨args⟩` arguments is presented as `⟨pres⟩`. The second line allows the semantic macro to be called with an optional argument `⟨var⟩`: `\⟨cseq⟩[⟨var⟩]` (applied to `⟨args⟩` arguments) is then presented as `⟨varpres⟩`. We can define a variant presentation for `\xor`; see Figure 3 for an example.

```
\begin{module}[id=xbool]
  \symdef[name=xor]{xorOp}{\oplus}
  \symvariant{xorOp}{uvee}{\underline{\vee}}
  \symdef{xor}[2]{\#1\xorOp \#2}
  \symvariant{xor}[2]{uvee}{\#1\xorOp[uvee] \#2}
  Exclusive disjunction is commutative: $\xor{p}q=\xor{q}p$\\
  Some authors also write exclusive or with the $\xorOp[uvee]$ operator,
  then the formula above is $\xor[uvee]{p}q=\xor[uvee]{q}p$
\end{module}
```

Exclusive disjunction is commutative: $p \oplus q = q \oplus p$
 Some authors also write exclusive or with the $\underline{\vee}$ operator, then the formula above is $p \underline{\vee} q = q \underline{\vee} p$

Example 3: Presentation Variants of a Semantic Macro

`\resymdef` Version 1.0 of the `modules` package had the `\resymdef` macro that allowed to locally redefine the presentation of a macro. But this did not interact well with the `beamer` package and was less useful than the `\symvariant` functionality. Therefore it is deprecated now and leads to an according error message.

2.3 Testing Semantic Macros

One of the problems in managing large module graphs with many semantic macros, so the `module` package gives an infrastructure for unit testing. The first macro is `\symtest`, which allows the author of a semantic macro to generate test output (if the `symtest` option is set) see figure 4 for a “tested semantic macro definition”. Note that the language in this purely generated, so that it can be adapted (tbd).

```
\symdef[name=setst]{SetSt}[2]{\{#1\,\vert\,#2\}}
\symtest[name=setst]{SetSt}{\SetSt{a}{a>0}}
```

generates the output

Symbol `setst` with semantic macro `\SetSt`: used e.g. in $\{a \mid a > 0\}$

Example 4: A Semantic Macro Definition with Test

`\abbrtest` The `\abbrtest` macro gives the analogous functionality for `\abbrdef`.

2.4 Semantic Macros for Variables

Up to now, the semantic macros generated OPENMATH and MATHML markup where the heads of the semantic macros become constants (the `OMS` and `csymbol` elements in Figure 1). But sometimes we want to have semantic macros for variables, e.g. to associate special notation conventions. For instance, if we want to define mathematical structures from components as in Figure 5, where the semigroup operation \circ is a variable epistemologically, but is a n -ary associative operator – we are in a semigroup after all. Let us call such variables **semantic variables** to contrast them from **semantic constants** generated by `\symdef` and `\symvariant`.

Definition 3.17 Let $\langle G, \circ \rangle$ be a semigroup, then we call $e \in G$ a **unit**, iff $e \circ x = x \circ e = x$. A semigroup with unit $\langle G, \circ, e \rangle$ is called a **monoid**.

Example 5: A Definition of a Structure with “semantic variables”.

Semantic variables differ from semantic constants in two ways: *i*) they do not participate in the imports mechanism and *ii*) they generate markup with variables. In the case of Figure 5 we (want to) have the XML markup in Figure 6. To associate the notation to the variables, we define semantic macros for them, here the macro `\op` for the (semigroup) operation via the `\vardef` macro. `\vardef` works exactly like, except *i*) semantic variables are local to the current \TeX group and *ii*) they generate variable markup in the XML

`\vardef`

\TeX	$\backslash\text{vardef}\{\text{op}\}[1]\{\backslash\text{assoc}\backslash\text{circ}\{\#1\}\}$
OMDoc	<pre>% <notation> % <prototype> % <OMA> % <OMV name="op"/> % <expr name="a1"/> % <expr name="a2"/> % </OMA> % </prototype> % <rendering> % <mrow> % <render name="a1"/> % <mo>&#x2384;</mo> % <render name="a2"/> % </mrow> % </rendering> % </notation></pre>
\LaTeX	$\backslash\text{op}\{x,e\}$
PDF/DVI	$x \circ e$
OPENMATH	$\% \text{\textless OMA\textless OMV name="op"/>\textless OMV name="x"/>\textless OMV name="e"/>\textless OMA\textgreater}$
MATHML	$\% \text{\textless apply\textless ci>op</ci>\textless ci>x</ci>\textless ci>e</ci>\textless apply\textgreater}$

Example 6: Semantic Variables in OPENMATH and MATHML

2.5 Symbol and Concept Names

Just as the $\backslash\text{symdef}$ declarations define semantic macros for mathematical symbols, the `modules` package provides an infrastructure for *mathematical concepts* that are expressed in mathematical vernacular. The key observation here is that concept names like “finite symplectic group” follow the same scoping rules as mathematical symbols, i.e. they are module-scoped. The $\backslash\text{termdef}$ macro is an analogue to $\backslash\text{symdef}$ that supports this: use $\backslash\text{termdef}[\langle\text{keys}\rangle]\{\langle\text{cseq}\rangle\}\{\langle\text{concept}\rangle\}$ to declare the macro $\backslash\langle\text{cseq}\rangle$ that expands to $\langle\text{concept}\rangle$. See Figure 7 for an example, where we use the $\backslash\text{capitalize}$ macro to adapt $\langle\text{concept}\rangle$ to the sentence beginning.² The main use of the $\backslash\text{termdef}$ -defined concepts lies in automatic cross-referencing facilities via the $\backslash\text{termref}$ and $\backslash\text{symref}$ macros provided by the `statements` package [Koh15c]. Together with the `hyperref` package [RO], this provide cross-referencing to the definitions of the symbols and concepts. As discussed in section 3.6, the $\backslash\text{symdef}$ and $\backslash\text{termdef}$ declarations must be on top-level in a module, so the infrastructure provided in the `modules` package alone cannot be used to locate the definitions, so we use the infrastructure for mathematical statements for that.

```
\termdef[name=xor]{xdisjunction}{exclusive disjunction}
\capitalize\xdisjunction is commutative: $\xor{p}q=\xor{q}p$
```

Example 7: Extending Example 3 with Term References

²EdNOTE: continue, describe $\langle\text{keys}\rangle$, they will have to to with plurals,... once implemented

2.6 Modules and Inheritance

`module` The `module` environment takes an optional `KeyVal` argument. Currently, only the `id` key is supported for specifying the identifier of a module (also called the module name). A module introduced by `\begin{module}[id=foo]` restricts the scope the semantic macros defined by the `\symdef` form to the end of this module given by the corresponding `\end{module}`, and to any other `module` environments that import them by a `\importmodule{foo}` directive. If the module `foo` contains `\importmodule` directives of its own, these are also exported to the importing module.

`\importmodule` Thus the `\importmodule` declarations induce the semantic inheritance relation. Figure 9 shows a module that imports the semantic macros from three others. In the simplest form, `\importmodule{<mod>}` will activate the semantic macros and concepts declared by `\symdef` and `\termdef` in module `<mod>` in the current module¹. To understand the mechanics of this, we need to understand a bit of the internals. The `module` environment sets up an internal macro pool, to which all the macros defined by the `\symdef` and `\termdef` declarations are added; `\importmodule` only activates this macro pool. Therefore `\importmodule{<mod>}` can only work, if the `TeX` parser — which linearly goes through the `gTeX` sources — already came across the module `<mod>`. In many situations, this is not obtainable; e.g. for “semantic forward references”, where symbols or concepts are previewed or motivated to knowledgeable readers before they are formally introduced or for modularizations of documents into multiple files. To enable situations like these, the `module` package uses auxiliary files called **gTeX module signatures**. For any file, `<file>.tex`, we generate a corresponding `gTeX` module signature `<file>.sms` with the `sms` utility (see also Limitation 3.1), which contains (copies of) all `\begin/\end{module}`, `\importmodule`, `\symdef`, and `\termdef` invocations in `<file>.tex`. The value of an `gTeX` module signature is that it can be loaded instead its corresponding `gTeX` document, if we are only interested in the semantic macros. So `\importmodule[load=<filepath>]{<mod>}` will load the `gTeX` module signature `<filepath>.sms` (if it exists and has not been loaded before) and activate the semantic macros from module `<mod>` (which was supposedly defined in `<filepath>.tex`). Note that since `<filepath>.sms` contains all `\importmodule` statements that `<filepath>.tex` does, an `\importmodule` recursively loads all necessary files to supply the semantic macros inherited by the current module.³

EdN:3

`importmodulevia` The `\importmodule` macro has a variant `\importmodulevia` that allows the specification of a theory morphism to be applied. `\importmodulevia{<thyid>}{<assignments>}` specifies the “source theory” via its identifier `<thyid>` and the morphism by `<assignments>`. There are three kinds:

`\vassign` **symbol assignments** via `\vassign{<sym>}{<exp>}`, which defines the symbol `<sym>` introduced in the current theory by an expression `<exp>` in the source theory.

`\tassign` **term assignments** via `\tassign[<source-cd>]{<tname>}{<source-tname>}`, which

¹Actually, in the current `TeX` group, therefore `\importmodule` should be placed directly after the `\begin{module}`.

³EdNOTE: MK: document the other keys of module

assigns to the term with name $\langle tname \rangle$ in the current theory a term with name $\langle source-tname \rangle$ in the theory $\langle source-cd \rangle$ whose default value is the source theory.

`\ttassign` **term text assignments** via `\tassign{ $\langle tname \rangle$ }{ $\langle text \rangle$ }`, which defines a term with name $\langle tname \rangle$ in the current theory via a definitional text.

```
\begin{module}[id=ring]
\begin{importmodulevia}{monoid}
  \vassign{rbase}\magbase
  \vassign{rtimesOp}\magmaop
  \vassign{rone}\monunit
\end{importmodulevia}
\symdef{rbase}{G}
\symdef[name=rtimes]{rtimesOp}{\cdot}
\symdef{rtimes}[2]{\infix\rtimesOp{#1}{#2}}
\symdef{rone}{1}
\begin{importmodulevia}{cgroup}
  \vassign{rplus}\magmaop
  \vassign{rzero}\monunit
  \vassign{rinvOp}\cginvOp
\end{importmodulevia}
\symdef[name=rplus]{rplusOp}{+}
\symdef{rplus}[2]{\infix\rplusOp{#1}{#2}}
\symdef[name=rminus]{rminusOp}{-}
\symdef{rminus}[1]{\infix\rminusOp{#1}{#2}}
...
\end{module}
```

Example 8: A Module for Rings with inheritance from monoids and commutative groups

`\metalanguage` The `\metalanguage` macro is a variant of `importmodule` that imports the meta language, i.e. the language in which the meaning of the new symbols is expressed. For mathematics this is often first-order logic with some set theory; see [RabKoh:WSMSML10] for discussion.

2.7 Dealing with multiple Files

The infrastructure presented above works well if we are dealing with small files or small collections of modules. In reality, collections of modules tend to grow, get re-used, etc, making it much more difficult to keep everything in one file. This general trend towards increasing entropy is aggravated by the fact that modules are very self-contained objects that are ideal for re-used. Therefore in the absence of a content management system for L^AT_EX document (fragments), module collections tend to develop towards the “one module one file” rule, which leads to situations with lots and lots of little files.

Moreover, most mathematical documents are not self-contained, i.e. they do not build up the theory from scratch, but pre-suppose the knowledge (and notation) from other documents. In this case we want to make use of the semantic macros from these prerequisite documents without including their text into the current document. One way to do this would be to have \LaTeX read the prerequisite documents without producing output. For efficiency reasons, \S\TeX chooses a different route. It comes with a utility `sms` (see Section 3.1) that exports the modules and macros defined inside them from a particular document and stores them inside `.sms` files. This way we can avoid overloading \LaTeX with useless information, while retaining the important information which can then be imported in a more efficient way.

`\importmodule`

For such situations, the `\importmodule` macro can be given an optional first argument that is a path to a file that contains a path to the module file, whose module definition (the `.sms` file) is read. Note that the `\importmodule` macro can be used to make module files truly self-contained. To arrive at a file-based content management system, it is good practice to reuse the module identifiers as module names and to prefix module files with corresponding `\importmodule` statements that pre-load the corresponding module files.

```
\begin{module}[id=foo]
\importmodule[load=../other/bar]{bar}
\importmodule[load=../mycolleaguesmodules]{baz}
\importmodule[load=../other/bar]{foobar}
...
\end{module}
```

Example 9: Self-contained Modules via `importmodule`

In Example 9, we have shown the typical setup of a module file. The `\importmodule` macro takes great care that files are only read once, as \S\TeX allows multiple inheritance and this setup would lead to an exponential (in the module inheritance depth) number of file loads.

Sometimes we want to import an existing OMDoc theory² $\hat{\mathcal{T}}$ into (the OMDoc document $\hat{\mathcal{D}}$ generated from) a \S\TeX document \mathcal{D} . Naturally, we have to provide an \S\TeX stub module \mathcal{T} that provides `\symdef` declarations for all symbols we use in \mathcal{D} . In this situation, we use `\importOMDocmodule[$\langle spath \rangle$]{ $\langle OURI \rangle$ }{ $\langle name \rangle$ }`, where $\langle spath \rangle$ is the file system path to \mathcal{T} (as in `\importmodule`, this argument must not contain the file extension), $\langle OURI \rangle$ is the URI to the OMDoc module (this time with extension), and $\langle name \rangle$ is the name of the theory $\hat{\mathcal{T}}$ and the module in \mathcal{T} (they have to be identical for this to work). Note that since the $\langle spath \rangle$ argument is optional, we can make “local imports”, where the stub \mathcal{T} is in \mathcal{D} and only contains the `\symdefs` needed there.

`\importOMDocmodule`

Note that the recursive (depth-first) nature of the file loads induced by this setup is very natural, but can lead to problems with the depth of the file stack in

²OMDoc theories are the counterpart of \S\TeX modules.

```
\requiremodules
```

\sinput

\sinputref

\inputref

\includeref

\defpath

```
\defpath{OPaths}{../other}
```

instead of the second line in Example 9. The variant `\OPaths` has the big advantage that we can get around the fact that `TEX/LATEX` does not set the current directory in `\input`, so that we can use systematically deployed `\defpath`-defined path macros to make modules relocatable by defining the path macros locally. The optional parameter $\langle baseURI \rangle$ is for the `LATEXML` transformation, which (if $\langle baseURI \rangle$ is specified) resolves $\langle path \rangle$ to an absolute URI according to [BFM05, section 5.2].

2.8 Using Semantic Macros in Narrative Structures

The `\importmodule` macro establishes the inheritance relation, a transitive relation among modules that governs visibility of semantic macros. In particular, it can only be used in modules (and has to be used at the top-level, otherwise it

³If you have sufficient rights to change your TeX installation, you can also increase the variable `max_in_open` in the relevant `texmf.cnf` file. Setting it to 50 usually suffices

⁴files without modules should be treated by the regular L^AT_EX input mechanism, since they do not need to be registered.

is hindered by \LaTeX groups). In many cases, we only want to *use* the semantic macros in an environment (and not re-export them). Indeed, this is the normal situation for most parts of mathematical documents. For that \S\TeX provides the `\usemodule` macro, which takes the same arguments as `\importmodule`, but is treated differently in the \S\TeX module signatures. A typical situation is shown in Figure 10, where we open the module `ring` (see Figure 8) and use its semantic macros (in the `omtext` environment). In earlier versions of \S\TeX , we would have to wrap the `omtext` environment in an anonymous `module` environment to prevent re-export.

`\usemodule`

```
\begin{omtext}
  \usemodule[../algebra/rings.tex]{ring}
  We  $\mathbb{R}$  be a ring  $(\mathbb{R}, +, 0, -, \cdot, 1)$ , ...
\end{omtext}
```

Example 10: Using Semantic Macros in Narrative Structures

Still another import-like relation is the adoption of a module (see [Koh13] for details). We use the `\adoptmodule` macro for that.⁴

`\adoptmodule`

2.9 Including Externally Defined Semantic Macros

In some cases, we use an existing \LaTeX macro package for typesetting objects that have a conventionalized mathematical meaning. In this case, the macros are “semantic” even though they have not been defined by a `\symdef`. This is no problem, if we are only interested in the \LaTeX workflow. But if we want to e.g. transform them to OMDOC via \LaTeX XML, the \LaTeX XML bindings will need to contain references to an OMDOC theory that semantically corresponds to the \LaTeX package. In particular, this theory will have to be imported in the generated OMDOC file to make it OMDOC-valid.

`\requirepackage`

To deal with this situation, the `modules` package provides the `\requirepackage` macro. It takes two arguments: a package name, and a URI of the corresponding OMDOC theory. In the \LaTeX workflow this macro behaves like a `\usepackage` on the first argument, except that it can — and should — be used outside the \LaTeX preamble. In the \LaTeX XML workflow, this loads the \LaTeX XML bindings of the package specified in the first argument and generates an appropriate `imports` element using the URI in the second argument.

2.10 Views

A view is a mapping between modules, such that all model assumptions (axioms) of the source module are satisfied in the target module.⁵

⁴EdNOTE: elaborate this, so that the documentation becomes (more) self-contained.

⁵EdNOTE: Document and make Examples

2.11 Support for MathHub

Much of the \LaTeX content is hosted on **MathHub** (<http://MathHub.info>), a portal and archive for flexiformal mathematics. **MathHub** offers GIT repositories (public and private escrow) for mathematical documentation projects, online and offline authoring and document development infrastructure, and a rich, interactive reading interface. The `modules` package supports repository-sensitive operations on **MathHub**.

Note that **MathHub** has two-level repository names of the form $\langle group \rangle / \langle repo \rangle$, where $\langle group \rangle$ is a **MathHub**-unique repository group and $\langle repo \rangle$ a repository name that is $\langle group \rangle$ -unique. The file and directory structure of a repository is arbitrary – except that it starts with the directory `source` because they are Math Archives in the sense of [Hor+11]. But this structure can be hidden from the \LaTeX author with **MathHub**-enabled versions of the `modules` macros.

`\importmhmodule` The `\importmhmodule` macro is a variant of `\importmodule` with repository support. Instead of writing

```
\defpath{MathHub}{/user/foo/lmh/MathHub}
\importmodule[load=\MathHub{fooMH/bar/source/baz/foobar}]{foobar}
```

we can simply write (assuming that `\MathHub` is defined as above)

```
\importmhmodule[repos=fooMH/bar,path=baz/foobar]{foobar}
```

Note that the `\importmhmodule` form is more semantic, which allows more advanced document management features in **MathHub**.

If `baz/foobar` is the “current module”, i.e. if we are on the **MathHub** path `...MathHub/fooMH/bar...`, then stating the repository in the first optional argument is redundant, so we can just use

```
\importmhmodule[path=baz/foobar]{foobar}
```

if no file needs to be loaded, `\importmhmodule` is the same as `\importmodule`.

`\mhcurrentrepos` Of course, neither \LaTeX nor \LaTeXML know about the repositories when they are called from a file system, so we can use the `\mhcurrentrepos` macro to tell them. But this is only needed to initialize the infrastructure in the driver file. In particular, we do not need to set it in each module, since the `\importmhmodule` macro sets the current repository automatically.

`\usemhmodule` The `\usemhmodule` and `\adoptmhmodule` macros are the analogs to `\usemodule`
`\adoptmhmodule` and `\adoptmodule`.

Caveat if you want to use the **MathHub** support macros (let’s call them *mh*-variants), then every time a module is imported or a document fragment is included from another repos, the *mh*-variant `\importmhmodule` must be used, so that the “current repository” is set accordingly. To be exact, we only need to use *mh*-variants, if the imported module or included document fragment use *mh*-variants.

`\mhinputref` For this, the `modules` package supplies the mh-variants `\mhinputref` and
`\mhinput` `\mhinput` of the `\inputref` macro introduced above and normal L^AT_EX `\input`
macro.

3 Limitations & Extensions

In this section we will discuss limitations and possible extensions of the `modules` package. Any contributions and extension ideas are welcome; please discuss ideas, requests, fixes, etc on the `gTEX` TRAC [sTeX].

3.1 Perl Utility `sms`

Currently we have to use an external perl utility `sms` to extract `gTEX` module signatures from `gTEX` files. This considerably adds to the complexity of the `gTEX` installation and workflow. If we can solve security setting problems that allows us to write to `gTEX` module signatures outside the current directory, writing them from `gTEX` may be an avenue of future development see [sTeX, issue #1522] for a discussion.

3.2 Module Signatures loaded even if Modules are

Currently, the module signature `<filepath>.sms` is loaded even if `<filepath>.tex` has already been loaded. The Problem is that the `\input` `\inputref` macros do not register the files. I guess, for `\input` we may not want that, but for `\inputref` we should; and maybe we should also have a registering variant `\rinput` that does, then we can leave the choice to the user.

3.3 Only one level of path simplification

It seems that module simplification only covers one level, in particular `foo/bar/./..` is only simplified to `foo/..`, which is not enough in practice. As a consequence, module signatures are loaded unnecessary in the presence of relative paths.

3.4 Qualified Imports

In an earlier version of the `modules` package we used the `usesqualified` for importing macros with a disambiguating prefix (this is used whenever we have conflicting names for macros inherited from different modules). This is not accessible from the current interface. We need something like a `\importqualified` macro for this; see [sTeX, issue #1505]. Until this is implemented the infrastructure is turned off by default, but we have already introduced the `qualifiedimports` option for the future.

3.5 Error Messages

The error messages generated by the `modules` package are still quite bad. For instance if `thyA` does not exist we get the cryptic error message

```
! Undefined control sequence.
\module@defs@thyA ...hy
                        \expandafter \mod@newcomma...
1.490 ...ortmodule{thyA}
```

This should definitely be improved.

3.6 Crossreferencing

Note that the macros defined by `\symdef` are still subject to the normal \TeX scoping rules. Thus they have to be at the top level of a module to be visible throughout the module as intended. As a consequence, the location of the `\symdef` elements cannot be used as targets for crossreferencing, which is currently supplied by the `statement` package [Koh15c]. A way around this limitation would be to import the current module from the \LaTeX module signature (see Section 2.6) via the `\importmodule` declaration.

3.7 No Forward Imports

\LaTeX allows imports in the same file via `\importmodule{<mod>}`, but due to the single-pass linear processing model of \TeX , `<mod>` must be the name of a module declared *before* the current point. So we cannot have forward imports as in

```
\begin{module}[id=foo]
  \importmodule{mod}
  ...
\end{module}
...
\begin{module}[id=mod]
  ...
\end{module}
```

a workaround, we can extract the module `<mod>` into a file `mod.tex` and replace it with `\sinput{mod}`, as in

```
\begin{module}[id=foo]
  \importmodule[load=mod]{mod}
  ...
\end{module}
...
\sinput{mod}
```

then the `\importmodule` command can read `mod.sms` (created via the `sms` utility) without having to wait for the module `<mod>` to be defined.

4 The Implementation

The `modules` package generates two files: the \LaTeX package (all the code between `\package` and `\endpackage`) and the \LaTeX ML bindings (between `\ltxml` and `\endltxml`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

4.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false).

```
1 \package
2 \DeclareOption{showmeta}{\PassOptionsToPackage{\CurrentOption}{metakeys}}
3 \newif\ifmod@show\mod@showfalse
4 \DeclareOption{showmods}{\mod@showtrue}
5 \newif\ifaux@req\aux@reqtrue
6 \DeclareOption{noauxreq}{\aux@reqfalse}
7 \newif\ifmod@qualified\mod@qualifiedfalse
8 \DeclareOption{qualifiedimports}{\mod@qualifiedtrue}
```

Finally, we need to declare the end of the option declaration section to \LaTeX .

```
9 \ProcessOptions
```

\LaTeX ML does not support module options yet, so we do not have to do anything here for the \LaTeX ML bindings. We only set up the PERL packages (and tell `emacs` about the appropriate mode for convenience).

The next measure is to ensure that the `sref` and `xcomment` packages are loaded (in the right version). For \LaTeX ML, we also initialize the package inclusions.

```
10 \RequirePackage{sref}
11 \RequirePackage{xspace}
12 \RequirePackage{mdframed}
```

4.2 Modules and Inheritance

We define the keys for the `module` environment and the actions that are undertaken, when the keys are encountered.

`module:cd` This `KeyVal` key is only needed for \LaTeX ML at the moment; use this to specify a content dictionary name that is different from the module name.

```
13 \addmetakey{module}{cd}% no longer used
14 \addmetakey{module}{load}% ignored
15 \addmetakey*{module}{title}
16 \addmetakey*{module}{creators}
17 \addmetakey*{module}{contributors}
```

`module:id` For a module with `[id=<name>]`, we have a macro `\module@defs@<name>` that acts as a repository for semantic macros of the current module. It will be called by `\importmodule` to activate them. We will add the internal forms of the semantic

macros whenever `\symdef` is invoked. To do this, we will need an unexpanded form `\this@module` that expands to `\module@defs@<name>`; we define it first and then initialize `\module@defs@<name>` as empty. Then we do the same for qualified imports as well (if the `qualifiedimports` option was specified). Furthermore, we save the module name in `\mod@id` and the module path in `\<name>@cd@file@base` which we add to `\module@defs@<name>`, so that we can use it in the importing module.

```

18 \define@key{module}{id}{%
19 % \ifundefined{module@defs@#1}{\PackageError{modules}%
20 % {The module name #1 has already been used in this scope; please rename it!}}%
21 \edef\this@module{\expandafter\noexpand\csname module@defs@#1\endcsname}%
22 \global\@namedef{module@defs@#1}{}%
23 \ifmod@qualified
24 \edef\this@qualified@module{\expandafter\noexpand\csname module@defs@qualified@#1\endcsname}%
25 \global\@namedef{module@defs@qualified@#1}{}%
26 \fi
27 \def\mod@id{#1}%
28 \expandafter\edef\csname #1@cd@file@base\endcsname{\mod@path}%
29 \expandafter\g@addto@macro\csname module@defs@#1\endcsname\expandafter%
30 {\expandafter\def\csname #1@cd@file@base\endcsname\expandafter{\mod@path}}

```

module@heading Then we make a convenience macro for the module heading. This can be customized.

```

31 \newcounter{module}[section]
32 \newcommand\module@heading{\stepcounter{module}%
33 \ifmod@show%
34 \noindent{\textbf{Module}} \thesection.\themodule [\mod@id]}%
35 \sref{label@id{Module} \thesection.\themodule [\mod@id]}%
36 \ifx\module@title\empty : \quad\else\quad(\module@title)\hfill\\fi%
37 \fi}%mod@show

```

module Finally, we define the begin module command for the module environment. All the work has already been done in the keyval bindings, so this is very simple.

```

38 \newenvironment{module}[1] [] {\begin{@module}{#1}\module@heading}{\end{@module}}
39 \ifmod@show\surroundwithmdframed{module}\fi

```

@module A variant of the module environment that does not create printed representations (in particular no frames)

```

40 \newenvironment{@module}[1] [] {\metasetkeys{module}{#1}}{}

```

\activate@defs To activate the `\symdefs` from a given module `<mod>`, we call the macro `\module@defs@<mod>`. But to make sure that every module is activated only once, we only activate if the macro `\module@defs@<mod>` is undefined, and define it directly afterwards to prohibit further activations.

```

41 \def\activate@defs#1{%
42 \ifundefined{module@#1@activated}{\csname module@defs@#1\endcsname}{}%
43 \@namedef{module@#1@activated}{true}}

```

`\export@defs` `\export@defs{<mod>}` exports all the `\symdefs` from module `<mod>` to the current module (if it has the name `<currmod>`), by adding a call to `\module@defs@<mod>` to the registry `\module@defs@<currmod>`.⁶

```

44 \def\export@defs#1{\ifundefined{mod@id}{}%
45 {\expandafter\expandafter\expandafter\g@addto@macro\expandafter%
46 \this@module\expandafter{\activate@defs{#1}}}}

```

Now we come to the implementation of `\importmodule`, but before we do, we define two conditionals:

`\if@export` `\if@export` distinguishes the `\importmodule` and `\usemodule` macros defined below, they differ in whether they re-export macros they import.

```

47 \newif\if@export

```

`\if@importing` `\if@importing` can be used to shut up macros in an import situation.

```

48 \newif\if@importing\@importingfalse

```

`\importmodule` The `\importmodule[<file>]{<mod>}` macro is an interface macro that loads `<file>` and activates and re-exports the `\symdefs` from module `<mod>`. It also remembers the file name in `\mod@path`. As we will need to keep a record of the currently imported modules (top-level only), we divide the functionality into a user-visible macro that records modules in the `\imported@modules` register and an internal one (`\@importmodule`) that does the actual work.

```

49 \gdef\imported@modules{}
50 \srefaddidkey{importmodule}
51 \addmetakey{importmodule}{load}
52 \addmetakey[sms]{importmodule}{ext}
53 \newcommand\importmodule[2][\metasetkeys{importmodule}{#1}%
54 \ifx\imported@modules\empty\edef\imported@modules{#2}%
55 \else\edef\imported@modules{#2,\imported@modules}\fi%
56 \@exporttrue\@importmodule[\importmodule@load]{#2}{\importmodule@ext}\ignorespaces}

```

`\@importmodule` `\@importmodule[<file>]{<mod>}{<ext>}` loads `<file>.<ext>` (if it is given) and activates the module `<mod>`. There is a slight inefficiency in that modules can be recorded multiply, but since `\activate@defs` is efficient about not activating twice, this is OK.

```

57 \newcommand\@importmodule[3][\%
58 {\@importingtrue% to shut up macros
59 \edef\@load{#1}\ifx\@load\empty\else{\mod@showfalse\requiremodules\@load{#3}}\fi}%
60 \activate@defs{#2}\if@export\export@defs{#2}\fi}

```

`\usemodule` `\usemodule` acts like `\importmodule` for the L^AT_EX side, except that the `sms` utility does not transfer it to the module signatures and it does not export the `symdefs`.

```

61 \newcommand\usemodule[2][\@exportfalse\importmodule{#1}{#2}]

```

⁶EDNOTE: MK: I have the feeling that we may be exporting modules multiple times here, is that a problem?

EdN:7

`\importmodules` This variant just imports all the modules in a comma-separated list (usually `\imported@modules`)

```
62 \newcommand\importmodules[1]{\@for\@I:=#1\do{\importmodule\@I}}%
```

`\importmodulevia` The `importmodulevia` environment just calls `\importmodule`, but to get around the group, we first define a local macro `\@@doit`, which does that and can be called with an `\aftergroup` to escape the environment grouping introduced by `importmodulevia`.

```
63 \newenvironment{importmodulevia}[2][]{\gdef\@@doit{\importmodule[#1]{#2}}%
64 \ifmod@show\par\noindent importing module #2 via \@@doit\fi}
65 {\aftergroup\@@doit\ifmod@show end import\fi}
```

`vassign`

```
66 \newcommand\vassign[3][]{\ifmod@show\ensuremath{#2\mapsto #3}, \fi}
```

`tassign`

```
67 \newcommand\tassign[3][]{\ifmod@show #2\ensuremath{\mapsto} #3, \fi}
```

`ttassign`

```
68 \newcommand\ttassign[3][]{\ifmod@show #2\ensuremath{\mapsto} ‘‘#3’’, \fi}
```

`\importOMDocmodule` for the L^AT_EX side we can just re-use `\importmodule`, for the L^AT_EXML side we have a full URI anyways. So things are easy.⁷

```
69 \newcommand\importOMDocmodule[3][]{\importmodule[#1]{#3}}
```

`\metalinguage` `\metalinguage` behaves exactly like `\importmodule` for formatting. For L^AT_EXML, we only add the `type` attribute.

```
70 \let\metalinguage=\importmodule
```

`\adoptmodule` `\adoptmodule` macro behaves exactly like `\importmodule` for formatting. For L^AT_EXML.

```
71 \let\adoptmodule=\importmodule
```

4.3 Semantic Macros

`\mod@newcommand` We first hack the L^AT_EX kernel macros to obtain a version of the `\newcommand` macro that does not check for definedness.

```
72 \let\mod@newcommand=\providerobustcmd
```

Now we define the optional KeyVal arguments for the `\symdef` form and the actions that are taken when they are encountered.

`conceptdef`

```
73 \srefaddidkey{conceptdef}
74 \addmetakey*{conceptdef}{title}
75 \addmetakey{conceptdef}{subject}
```

⁷EdNOTE: MK@DG: this macro is seldom used, maybe I should just switch arguments.

```

76 \addmetakey*{conceptdef}{display}
77 \def\conceptdef@type{Symbol}
78 \newcommand\conceptdef[2] [] {\metasetkeys{conceptdef}{#1}%
79 \ifx\conceptdef@display\st@flow\else{\stdMemph{\conceptdef@type} #2:}\fi%
80 \ifx\conceptdef@title\empty~\else~(\stdMemph{\conceptdef@title})\par\fi}
8

```

EdN:8

symdef:keys The optional argument `local` specifies the scope of the function to be defined. If `local` is not present as an optional argument then `\symdef` assumes the scope of the function is global and it will include it in the pool of macros of the current module. Otherwise, if `local` is present then the function will be defined only locally and it will not be added to the current module (i.e. we cannot inherit a local function). Note, the optional key `local` does not need a value: we write `\symdef[local]{somefunction}[0]{some expansion}`. The other keys are not used in the L^AT_EX part.

```

81 \newif\if@symdeflocal
82 \srefaddidkey{symdef}
83 \define@key{symdef}{local}[true]{\@symdeflocaltrue}
84 \define@key{symdef}{primary}[true]{}
85 \define@key{symdef}{assocarg}{}
86 \define@key{symdef}{bvars}{}
87 \define@key{symdef}{bargs}{}
88 \addmetakey{symdef}{name}
89 \addmetakey*{symdef}{title}
90 \addmetakey*{symdef}{description}
91 \addmetakey{symdef}{subject}
92 \addmetakey*{symdef}{display}

```

EdN:9

9

\symdef The the `\symdef`, and `\@symdef` macros just handle optional arguments.

```

93 \def\symdef{\@ifnextchar [{\@symdef}{\@symdef []}}
94 \def\@symdef[#1]#2{\@ifnextchar [{\@@symdef[#1]{#2}}{\@@symdef[#1]{#2}[0]}}

```

next we locally abbreviate `\mod@newcommand` to simplify argument passing.

```

95 \def\@mod@nc#1{\mod@newcommand{#1}[1]}

```

\@@symdef now comes the real meat: the `\@@symdef` macro does two things, it adds the macro definition to the macro definition pool of the current module and also provides it.

```

96 \def\@@symdef[#1]#2[#3]#4{%

```

We use a switch to keep track of the local optional argument. We initialize the switch to false and set all the keys that have been provided as arguments: `name`, `local`.

```

97 \@symdeflocalfalse\metasetkeys{symdef}{#1}%

```

⁸EdNOTE: MK@DG: maybe we need to add `DefKeyVals` here?

⁹EdNOTE: MK@MK: we need to document the binder keys above.

First, using `\mod@newcommand` we initialize the intermediate macro `\module@<sym>@pres@`, the one that can be extended with `\symvariant`

```
98 \expandafter\mod@newcommand\csname modules@#2@pres@\endcsname[#3]{#4}%
```

and then we define the actual semantic macro, which when invoked with an optional argument `<opt>` calls `\modules@<sym>@pres@<opt>` provided by the `\symvariant` macro.

```
99 \expandafter\mod@newcommand\csname #2\endcsname[1][]%
100 {\csname modules@#2@pres@##1\endcsname}%
```

Finally, we prepare the internal macro to be used in the `\symref` call.

```
101 \expandafter\@mod@nc\csname mod@symref@#2\expandafter\endcsname\expandafter%
102 {\expandafter\mod@termref\expandafter{\mod@id}{#2}{##1}}%
```

We check if the switch for the local scope is set: if it is we are done, since this function has a local scope. Similarly, if we are not inside a module, which we could export from.

```
103 \if@symdeflocal\else%
104 \ifundefined{mod@id}{-}{%
```

Otherwise, we add three functions to the module's pool of defined macros using `\g@addto@macro`. We first add the definition of the intermediate function `\modules@<sym>@pres@`.

```
105 \expandafter\g@addto@macro\this@module%
106 {\expandafter\mod@newcommand\csname modules@#2@pres@\endcsname[#3]{#4}}%
```

Then we add the definition of `\<sym>` which calls the intermediate function and handles the optional argument.

```
107 \expandafter\g@addto@macro\this@module%
108 {\expandafter\mod@newcommand\csname #2\endcsname[1][]%
109 {\csname modules@#2@pres@##1\endcsname}}%
```

We also add `\mod@symref@<sym>` macro to the macro pool so that the `\symref` macro can pick it up.

```
110 \expandafter\g@addto@macro\csname module@defs@\mod@id\expandafter\endcsname\expandafter%
111 {\expandafter\@mod@nc\csname mod@symref@#2\expandafter\endcsname\expandafter%
112 {\expandafter\mod@termref\expandafter{\mod@id}{#2}{##1}}}%
```

Finally, using `\g@addto@macro` we add the two functions to the qualified version of the module if the `qualifiedimports` option was set.

```
113 \ifmod@qualified%
114 \expandafter\g@addto@macro\this@qualified@module%
115 {\expandafter\mod@newcommand\csname modules@#2@pres@qualified\endcsname[#3]{#4}}%
116 \expandafter\g@addto@macro\this@qualified@module%
117 {\expandafter\def\csname#2atqualified\endcsname{\csname modules@#2@pres@qualified\endcsname}}%
118 \fi}% mod@qualified
119 \fi% symdeflocal
```

So now we only need to show the data in the `symdef`, if the options allow.

```
120 \ifmod@show
121 \ifx\symdef@display\st@flow\else{\noindent\stDMemph{\symdef@type} #2:}\fi%
122 \ifx\symdef@title@empty~\else~(\stDMemph{\symdef@title})\par\fi
```

EdN:10

```

123 \fi}% mod@show
124 \def\symdef@type{Symbol}

\symvariant \symvariant{<sym>}[<args>]{<var>}{<cseq>} just extends the internal macro
\modules@<sym>@pres@ defined by \symdef{<sym>}[<args>]{...} with a variant
\modules@<sym>@pres@<var> which expands to <cseq>. Recall that this is called
by the macro \<sym>[<var>] induced by the \symdef.10

125 \def\symvariant#1{\@ifnextchar[{\@symvariant{#1}}{\@symvariant{#1}[0]}}
126 \def\@symvariant#1[#2]#3#4{%
127 \expandafter\mod@newcommand\csname modules@#1@pres@#3\endcsname[#2]{#4}%
and if we are in a named module, then we need to export the function
\modules@<sym>@pres@<opt> just as we have done that in \symdef.
128 \@ifundefined{mod@id}{\{}{%
129 \expandafter\g@addto@macro\this@module%
130 {\expandafter\mod@newcommand\csname modules@#1@pres@#3\endcsname[#2]{#4}}}%

\resymdef This is now deprecated.

131 \def\resymdef{\@ifnextchar[{\@resymdef}{\@resymdef[]}}
132 \def\@resymdef[#1]#2{\@ifnextchar[{\@@resymdef[#1]{#2}}{\@@resymdef[#1]{#2}[0]}}
133 \def\@@resymdef[#1]#2[#3]#4{\PackageError{modules}
134 {The \protect\resymdef macro is deprecated,\MessageBreak
135 use the \protect\symvariant instead!}}

\abbrdef The \abbrdef macro is a variant of \symdef that does the same on the LATEX
level.

136 \let\abbrdef\symdef

```

4.4 Defining Math Operators

EdN:11

```

\DefMathOp 11

137 \define@key{DefMathOp}{name}{\def\defmathop@name{#1}}
138 \newcommand\DefMathOp[2][]{\%
139 \setkeys{DefMathOp}{#1}%
140 \symdef[#1]{\defmathop@name}{#2}}

```

4.5 Semantic Macros for Variables

\vardef We do the argument parsing like in `\symdef` above, but add the `local` key. All the other changes are in the L^AT_EX binding exclusively.

```

141 \def\vardef{\@ifnextchar[{\@vardef}{\@vardef[]}}
142 \def\@vardef[#1]#2{\@ifnextchar[{\@@vardef[#1]{#2}}{\@@vardef[#1]{#2}[0]}}
143 \def\@@vardef[#1]#2[#3]#4{\def\@test{#1}%
144 \ifx\@test\@empty\@symdef[local]{#2}{#3}{#4}\fi}

```

¹⁰EdNOTE: MK@DG: this needs to be implemented in L^AT_EXML

¹¹EdNOTE: MK@MK,DG: DefMathOp needs to be documented above, what can we do with it?

4.6 Testing Semantic Macros

`\symtest` Allows to test a `\symdef` in place, this shuts up when being imported.

```

145 \addmetakey{symtest}{name}
146 \addmetakey{symtest}{variant}
147 \newcommand\symtest[3][]{\if@importing\else%
148 \metasetkeys{symtest}{#1}%
149 \par\noindent \textbf{Symbol}~%
150 \ifx\symtest@name\@empty\texttt{#2}\else\texttt{\symtest@name}\fi%
151 \ifx\symtest@variant\@empty\else\ (variant \texttt{\symtest@variant})\fi%
152 \ with semantic macro %
153 \texttt{\textbackslash #2\ifx\symtest@variant\@empty\else[\symtest@variant]\fi}%
154 : used e.g. in \ensuremath{#3}%
155 \fi}

```

`\abbrtest`

```

156 \addmetakey{abbrtest}{name}
157 \newcommand\abbrtest[3][]{\if@importing\else%
158 \metasetkeys{abbrtest}{#1}%
159 \par\noindent \textbf{Abbreviation}~%
160 \ifx\abbrtest@name\@empty\texttt{#2}\else\texttt{\abbrtest@name}\fi%
161 : used e.g. in \ensuremath{#3}%
162 \fi}

```

4.7 Symbol and Concept Names

`\mod@path` the `\mod@path` macro is used to remember the local path, so that the module environment can set it for later cross-referencing of the modules. If `\mod@path` is empty, then it signifies the local file.

```

163 \def\mod@path{}

```

`\termdef`

```

164 \def\mod@true{true}
165 \addmetakey[false]{termdef}{local}
166 \addmetakey{termdef}{name}
167 \newcommand\termdef[3][]{\metasetkeys{termdef}{#1}%
168 \expandafter\mod@newcommand\csname#2\endcsname[0]{#3\space}%
169 \ifx\termdef@local\mod@true\else%
170 \@ifundefined{mod@id}{\expandafter\g@addto@macro\this@module%
171 {\expandafter\mod@newcommand\csname#2\endcsname[0]{#3\space}}}%
172 \fi}

```

`\capitalize`

```

173 \def\@capitalize#1{\uppercase{#1}}
174 \newcommand\capitalize[1]{\expandafter\@capitalize #1}

```

`\mod@termref` `\mod@termref{\<module>}{\<name>}{\<nl>}` determines whether the macro `\<module>` is defined. If it is, we make it the prefix of a URI reference in the local macro `\@uri`, which we compose to the hyper-reference, otherwise we give a warning.

```

175 \def\mod@termref#1#2#3{\def\@test{#3}%
176 \@ifundefined{#1@cd@file@base}%
177 {\protect\G@refundefinedtrue%
178 \@latex@warning{\protect\termref with unidentified cd "#1": the cd key must reference an active
179 \def\@label{sref@#2 @target}}}%
180 {\def\@label{sref@#2@#1@target}}}%
181 \ifx\csname #1@cd@file@base\endcsname\@empty% local reference
182 \sref@hlink@ifh{\@label}{\ifx\@test\@empty #2\else #3\fi}\else%
183 \def\@uri{\csname #1@cd@file@base\endcsname.pdf\#\@label}%
184 \sref@href@ifh{\@uri}{\ifx\@test\@empty #2\else #3\fi}\fi}

```

4.8 Dealing with Multiple Files

Before we can come to the functionality we want to offer, we need some auxiliary functions that deal with path names.

4.8.1 Simplifying Path Names

The `\mod@simplify` macro is used for simplifying path names by removing `<xxx>/..` from a string. eg: `<aaa>/<bbb>/../<ddd>` goes to `<aaa>/<ddd>` unless `<bbb>` is ... This is used to normalize relative path names below.

`\mod@simplify` The macro `\mod@simplify` recursively runs over the path collecting the result in the internal `\mod@savedprefix` macro.

```

185 \def\mod@simplify#1{\expandafter\mod@simpl#1/\relax}

```

It is based on the `\mod@simpl` macro¹²

```

186 \def\mod@simpl#1/#2\relax{\def\@second{#2}%
187 \ifx\mod@blaaaa\@empty\edef\mod@savedprefix{}\def\mod@blaaaa{aaa}\fi%
188 \ifx\@second\@empty\edef\mod@savedprefix{\mod@savedprefix#1}%
189 \else\mod@simplhelp#1/#2\relax\fi}

```

which in turn is based on a helper macro

```

190 \def\mod@updir{..}
191 \def\mod@simplhelp#1/#2/#3\relax{\def\@first{#1}\def\@second{#2}\def\@third{#3}%
192 %\message{mod@simplhelp: first=\@first, second=\@second, third=\@third, result=\mod@savedprefix
193 \ifx\@third\@empty% base case
194 \ifx\@second\mod@updir\else%
195 \ifx\@second\@empty\edef\mod@savedprefix{\mod@savedprefix#1}%
196 \else\edef\mod@savedprefix{\mod@savedprefix#1/#2}%
197 \fi% @second empty
198 \fi% @second = ..
199 \else% non-base case: @third non-empty
200 \ifx\@first\mod@updir%
201 \edef\mod@savedprefix{\mod@savedprefix#1/}\mod@simplhelp#2/#3\relax%
202 \else% @first != ..
203 \ifx\@second\mod@updir\mod@simpl#3\relax%

```

¹²EdNOTE: what does the `mod@blaaa` do?; it seems to be a switch that checks if `mod@savedprefix` has been saved.


```

204 \else\edef\mod@savdprefix{\mod@savdprefix#1/}\mod@simplhelp#2/#3\relax%
205 \fi% @first
206 \fi% @first = ..
207 \fi}% non-base case

```

We directly test the simplification:

source	result	should be
aaa	aaa	aaa
../../aaa	../../aaa	../../aaa
aaa/bbb	aaa/bbb	aaa/bbb
aaa/..		
../../aaa/bbb	../../aaa/bbb	../../aaa/bbb
../aaa../bbb	../bbb	../bbb
../aaa/bbb	../aaa/bbb	../aaa/bbb
aaa/bbb../ddd	aaa/ddd	aaa/ddd
aaa/bbb../..	aaa/..	

\defpath

```

208 \newcommand\defpath[3] [] {\expandafter\newcommand\csname #2\endcsname[1]{#3/#1}}

```

4.9 Loading Module Signatures

We will need a switch¹³

```

209 \newif\ifmodules

```

and a “registry” macro whose expansion represents the list of added macros (or files)

\mod@reg We initialize the \mod@reg macro with the empty string.

```

210 \gdef\mod@reg{}

```

\mod@update This macro provides special append functionality. \mod@update{<string>} takes appends <string> to the expansion of the \mod@reg macro in the following way: <string>@\mod@reg.

```

211 \def\mod@update#1{\ifx\mod@reg\empty\edef\mod@reg{#1}%
212 \else\xdef\mod@reg{#1\mod@reg}\fi}

```

\mod@check The \mod@check takes as input a file path (arg 3), and searches the registry. If the file path is not in the registry it means it means it has not been already added, so we make \ifmodules true, otherwise make \ifmodules false. The macro \mod@search will look at \ifmodules and update the registry for \modulestrue or do nothing for \modulesfalse.

```

213 \def\mod@check#1#2///#3\relax{%
214 \def\mod@one{#1}\def\mod@two{#2}\def\mod@three{#3}%

```

¹³EDNOTE: explain why?

Define a few intermediate macros so that we can split the registry into separate file paths and compare to the new one

```
215 \expandafter%
216 \ifx\mod@three\mod@one\modulestrue%
217 \else%
218 \ifx\mod@two\@empty\modulesfalse\else\mod@check#2///#3\relax\fi%
219 \fi}
```

\mod@search Macro for updating the registry after the execution of **\mod@check**

```
220 \def\mod@search#1{%
```

We put the registry as the first argument for **\mod@check** and the other argument is the new file path.

```
221 \modulesfalse\expandafter\mod@check\mod@reg @///#1\relax%
```

We run **\mod@check** with these arguments and the check **\ifmodules** for the result

```
222 \ifmodules\else\mod@update{#1}\fi}
```

\mod@reguse The macro operates almost as the **mod@search** function, but it does not update the registry. Its purpose is to check whether some file is or not inside the registry but without updating it. Will be used before deciding on a new sms file

```
223 \def\mod@reguse#1{\modulesfalse\expandafter\mod@check\mod@reg @///#1\relax}
```

\mod@prefix This is a local macro for storing the path prefix, we initialize it as the empty string.

```
224 \def\mod@prefix{}
```

\mod@updatedpre This macro updates the path prefix **\mod@prefix** with the last word in the path given in its argument.

```
225 \def\mod@updatedpre#1{%
```

```
226 \edef\mod@prefix{\mod@prefix\mod@pathprefix@check#1/\relax}}
```

\mod@pathprefix@check **\mod@pathprefix@check** returns the last word in a string composed of words separated by slashes

```
227 \def\mod@pathprefix@check#1/#2\relax{%
```

```
228 \ifx\\#2\\% no slash in string
```

```
229 \else\mod@ReturnAfterFi{#1/\mod@pathprefix@help#2\relax}%
```

```
230 \fi}
```

It needs two helper macros:

```
231 \def\mod@pathprefix@help#1/#2\relax{%
```

```
232 \ifx\\#2\\% end of recursion
```

```
233 \else\mod@ReturnAfterFi{#1/\mod@pathprefix@help#2\relax}%
```

```
234 \fi}
```

```
235 \long\def\mod@ReturnAfterFi#1\fi{\fi#1}
```

\mod@pathpostfix@check **\mod@pathpostfix@check** takes a string composed of words separated by slashes and returns the part of the string until the last slash

```
236 \def\mod@pathpostfix@check#1/#2\relax{% slash
```

```

237 \ifx\\#2\\%no slash in string
238 #1\else\mod@ReturnAfterFi{\mod@pathpostfix@help#2\relax}%
239 \fi}

```

Helper function for the `\pathpostfix@check` macro defined above

```

240 \def\mod@pathpostfix@help#1/#2\relax{%
241 \ifx\\#2\\%
242 #1\else\mod@ReturnAfterFi{\mod@pathpostfix@help#2\relax}%
243 \fi}

```

`\mod@updatedpost` This macro updates `\mod@savedprefix` with leading path (all but the last word) in the path given in its argument.

```

244 \def\mod@updatedpost#1{%
245 \edef\mod@savedprefix{\mod@savedprefix\mod@pathpostfix@check#1/\relax}}

```

4.9.1 Selective Inclusion

`\requiremodules` this macro loads the modules in a file. It does quite a lot of work to make sure that they are only loaded once (actually this does not quite work so they are loaded only twice). `\requiremodules{<file>}{<ext>}` also deposits a call to `\@requiremodules{<file>}{<ext>}` to the aux file to make sure that the semantic macros are already loaded for the table of contents. Another thing `\requiremodules{<file>}` does is that it writes a `\@requiremodules{<file>}` into the aux file, so that the table of contents can use semantic macros (the table of contents uses `\importmodules{\imported@modules}` in the titles, see [Koh15b] for details).

```

246 \newcommand\requiremodules[2]{%
247 {\mod@showfalse% save state and ensure silence while reading sms
248 \mod@updatedpre{#1}% add the new file to the already existing path
249 \let\mod@savedprefix\mod@prefix% add the path of the new file to the prefix
250 \mod@updatedpost{#1}%
251 \def\mod@blaaaa{}% macro used in the simplify function (remove .. from the prefix)
252 \mod@simplify{\mod@savedprefix}% remove |xxx/..| from the path (in case it exists)
253 \mod@reguse{\mod@savedprefix}%
254 \ifmodules\else%
255 \let\newreg\mod@reg% use to compare, in case the .sms file was loaded before
256 \mod@search{\mod@savedprefix}% update registry
257 \ifx\newreg\mod@reg\else % load if not in registry
258 \ifaux@req% if we write to the aux file
259 \ifx\@mhcurrentrepos\@undefined\else%
260 \protected@write\@auxout{}{\string\@mhcurrentrepos{\mh@currentrepos}}%
261 \fi%
262 \protected@write\@auxout{}{\string\@requiremodules{\mod@savedprefix}{#2}}
263 \fi% aux file write
264 \input{\mod@savedprefix.#2}%
265 \fi% load
266 \fi}}% ifmodules

```

```

\@requiremodules the internal macro that actually does the loading. We disable it at the end of the
                  document, so that when the aux file is read again, nothing is loaded.
267 \newcommand\@requiremodules[2]{\if@tempswa\mod@showfalse\@importingtrue\input{#1.#2}\fi}

\sinput
268 \def\sinput#1{
269 {\mod@updatedpre{#1}% add the new file to the already existing path
270 \let\mod@savexprefix\mod@prefix% add the path to the new file to the prefix
271 \mod@updatedpost{#1}%
272 \def\mod@blaaaa{}% macro used in the simplify function (remove .. from the prefix)
273 \mod@simplify{\mod@savexprefix}% remove |xxx/..| from the path (in case it exists)
274 \mod@reguse{\mod@savexprefix}%
275 \let\newreg\mod@reg% use to compare, in case the .sms file was loaded before
276 \mod@search{\mod@savexprefix}% update registry
277 \ifx\newreg\mod@reg%\message{This file has been previously introduced}
278 \else\input{\mod@savexprefix}%
279 \fi}}

14

280 \let\sinputref=\sinput
281 \let\inputref=\input
282 \let\includeref=\include

```

EdN:14

4.10 Including Externally Defined Semantic Macros

```

\requirepackage
283 \def\requirepackage#1#2{\makeatletter\input{#1.sty}\makeatother}

```

4.11 Views

We first prepare the ground by defining the keys for the `view` environment.

```

284 \srefaddidkey{view}
285 \addmetakey*{view}{title}
286 \addmetakey{view}{display}
287 \addmetakey{view}{from}
288 \addmetakey{view}{to}
289 \addmetakey{view}{creators}
290 \addmetakey{view}{contributors}
291 \addmetakey[sms]{view}{ext}

\view@heading Then we make a convenience macro for the view heading. This can be customized.
292 \newcounter{view}[section]
293 \newcommand\view@heading[4]{\if@importing\else%
294 \stepcounter{view}%
295 \edef\@display{#3}\edef\@title{#4}%

```

¹⁴EdNOTE: the `sinput` macro is just faked, it should be more like `requiremodules`, except that the `tex` file is inputted; I wonder if this can be simplified.

```

296 \noindent\ifx\@display\st@flow\else
297 {\textbf{View} {\thesection.\theview} from \textsf{#1} to \textsf{#2}}%
298 \sref@label@id{View \thesection.\theview}%
299 \ifx\@title\@empty\quad\else\quad(\@title)\fi%
300 \par\noindent%
301 \fi\ignorespaces\fi}%ifmod@show

```

view The `view` environment relies on the `@view` environment (used also in the \TeX module signatures) for module bookkeeping and adds presentation (a heading and a box) if the `showmods` option is set.

```

302 \newenvironment{view}[3] []%
303 {\metasetkeys{view}{#1}\sref@target%
304 \begin{@view}{#2}{#3}\view@heading{#2}{#3}{\view@display}{\view@title}}
305 {\end{@view}\ignorespaces}
306 \ifmod@show\surroundwithmdframed{view}\fi

```

@view The `@view` does the actual bookkeeping at the module level.

```

307 \newenvironment{@view}[2] {%from, to
308 \@importmodule[\view@from]{#1}{\view@ext}%
309 \@importmodule[\view@to]{#2}{\view@ext}}
310 {}

```

viewsketch The `viewsketch` environment behaves like `view`, but only has text contents.

```

311 \newenvironment{viewsketch}[3] []%
312 {\metasetkeys{view}{#1}\sref@target%
313 \begin{@view}{#2}{#3}\view@heading{#2}{#3}{\view@display}{\view@title}}
314 {\end{@view}}
315 \ifmod@show\surroundwithmdframed{viewsketch}\fi

```

4.12 Support for MathHub

\importmhmodule The `\importmhmodule` saves the current value of `\mh@currentrepos` in a local macro `\mh@@repos`, resets `\mh@currentrepos` to the new value if one is given in the optional argument, and after importing resets `\mh@currentrepos` to the old value in `\mh@@repos`. We do all the `\ifx` comparison with an `\expandafter`, since the values may be passed on from other key bindings.

```

316 \srefaddidkey{importmhmodule}
317 \addmetakey{importmhmodule}{repos}
318 \addmetakey{importmhmodule}{path}
319 \addmetakey[sms]{importmhmodule}{ext}
320 \newcommand\importmhmodule[2] [] {\metasetkeys{importmhmodule}{#1}%
321 \ifx\importmhmodule@path\@empty
322 \importmodule[ext=\importmhmodule@ext,id=\importmhmodule@id]{#2}\else
323 \edef\mh@@repos{\mh@currentrepos}%
324 \ifx\importmhmodule@repos\@empty\else\mhcurrentrepos{\importmhmodule@repos}\fi%
325 \importmodule[load=\MathHub{\mh@currentrepos/source/\importmhmodule@path},
326 ext=\importmhmodule@ext,id=\importmhmodule@id]{#2}%
327 \mhcurrentrepos\mh@@repos\fi\ignorespaces}

```

and now the analogs

```

\usemhmodule
328 \newcommand\usemhmodule[2] [] {\metasetkeys{importmhmodule}{#1}%
329 \ifx\importmhmodule@path\@empty
330 \usemodule[ext=\importmhmodule@ext,id=\importmhmodule@id]{#2}\else
331 \edef\mh@@repos{\mh@currentrepos}%
332 \ifx\importmhmodule@repos\@empty\else\mhcurrentrepos{\importmhmodule@repos}\fi%
333 \usemodule[load=\MathHub{\mh@currentrepos/source/\importmhmodule@path},
334             ext=\importmhmodule@ext,id=\importmhmodule@id]{#2}%
335 \mhcurrentrepos\mh@@repos\fi\ignorespaces}

\adoptmhmodule
336 \newcommand\adoptmhmodule[2] [] {\metasetkeys{importmhmodule}{#1}%
337 \ifx\importmhmodule@path\@empty
338 \adoptmodule[ext=\importmhmodule@ext,id=\importmhmodule@id]{#2}\else
339 \edef\mh@@repos{\mh@currentrepos}%
340 \ifx\importmhmodule@repos\@empty\else\mhcurrentrepos{\importmhmodule@repos}\fi%
341 \adoptmodule[load=\MathHub{\mh@currentrepos/source/\importmhmodule@path},
342             ext=\importmhmodule@ext,id=\importmhmodule@id]{#2}%
343 \mhcurrentrepos\mh@@repos\fi\ignorespaces}

\mhinputref
344 \newcommand\mhinputref[2] [] {\def\@repos{#1}%
345 \edef\mh@@repos{\mh@currentrepos}%
346 \ifx\@repos\@empty\else\mhcurrentrepos{#1}\fi%
347 \inputref{\MathHub{\mh@currentrepos/source/#2}}%
348 \mhcurrentrepos\mh@@repos\ignorespaces}

\mhinput
349 \let\mhinput\mhinputref

\mhcurrentrepos \mhcurrentrepos is used to initialize the current repository. If the repos has
\@mhcurrentrepos changed, it writes a call to the internal macro \@mhcurrentrepos for the aux file
and calls it. So that the \importmodule calls there work with the correct repos.
350 \newcommand\mhcurrentrepos[1] {\edef\@test{#1}%
351 \ifx\@test\mh@currentrepos\else%
352 \protected@write\@auxout{}{\string\@mhcurrentrepos{#1}}\fi%
353 \@mhcurrentrepos{#1}}
354 \newcommand\@mhcurrentrepos[1] {\edef\mh@currentrepos{#1}}

importmhmodulevia
355 \newenvironment{importmhmodulevia}[3] [] {\gdef\@@doit{\importmhmodule[#1]{#2}{#3}}%
356 \ifmod@show\par\noindent importing module #2 via \@@doit\fi}
357 {\aftergroup\@@doit\ifmod@show end import\fi}

358 \srefaddidkey{mhview}
359 \addmetakey{mhview}{display}
360 \addmetakey{mhview}{creators}

```

```

361 \addmetakey{mhview}{contributors}
362 \addmetakey*{mhview}{title}
363 \addmetakey{mhview}{fromrepos}
364 \addmetakey{mhview}{torepos}
365 \addmetakey{mhview}{frompath}
366 \addmetakey{mhview}{topath}
367 \addmetakey[sms]{mhview}{ext}

```

mhview the MathHub version

```

368 \newenvironment{mhview}[3][{}% keys, from, to
369 {\metasetkeys{mhview}{#1}\sref@target%
370 \begin{@mhview}{#2}{#3}\view@heading{#2}{#3}{\mhview@display}{\mhview@title}}
371 {\end{@mhview}\ignorespaces}
372 \ifmod@show\surroundwithmdframed{mhview}\fi

```

@mhview The @mhview does the actual bookkeeping at the module level.

```

373 \newenvironment{@mhview}[2]{%from, to
374 \importmhmodule[repos=\mhview@fromrepos,path=\mhview@frompath,ext=\mhview@ext]{#1}%
375 \importmhmodule[repos=\mhview@torepos,path=\mhview@topath,ext=\mhview@ext]{#2}}
376 {}

```

mhviewsketch The mhviewsketch environment behaves like mhview, but only has text contents.

```

377 \newenvironment{mhviewsketch}[3][{}%
378 {\metasetkeys{mhview}{#1}\sref@target%
379 \begin{@mhview}{#2}{#3}\view@heading{#2}{#3}{\mhview@display}{\mhview@title}}
380 {\end{@mhview}\ignorespaces}
381 \ifmod@show\surroundwithmdframed{mhviewsketch}\fi

```

EdN:15

\obligation The \obligation element does not do anything yet on the latexml side.¹⁵

```

382 \newcommand\obligation[3][{}{\if@importing\else Axiom #2 is proven by \sref{#3}\fi}

```

4.13 Deprecated Functionality

In this section we centralize old interfaces that are only partially supported any more.

EdN:16

module:uses For each the module name xxx specified in the uses key, we activate their symdefs and we export the local symdefs.¹⁶

```

383 \define@key{module}{uses}{%
384 \@for\module@tmp:=#1\do{\activate@defs\module@tmp\export@defs\module@tmp}}

```

module:usesqualified This option operates similarly to the module:uses option defined above. The only difference is that here we import modules with a prefix. This is useful when two modules provide a macro with the same name.

```

385 \define@key{module}{usesqualified}{%
386 \@for\module@tmp:=#1\do{\activate@defs{qualified@\module@tmp}\export@defs\module@tmp}}

```

¹⁵EdNOTE: document above

¹⁶EdNOTE: this issue is deprecated, it will be removed before 1.0.

`\coolurion/off`

```
387 \def\coolurion{\PackageWarning{modules}{coolurion is obsolete, please remove}}
388 \def\coolurioff{\PackageWarning{modules}{coolurioff is obsolete, please remove}}
```

4.14 Experiments

In this section we develop experimental functionality. Currently support for complex expressions, see https://svn.kwarc.info/repos/stex/doc/blue/complex_semmacros/note.pdf for details.

`\csymdef` For the L^AT_EX we use `\symdef` and forget the last argument. The code here is just needed for parsing the (non-standard) argument structure.

```
389 \def\csymdef{\@ifnextchar[{\@csymdef}{\@csymdef[]}}
390 \def\@csymdef[#1]#2{\@ifnextchar[{\@csymdef[#1]{#2}}{\@csymdef[#1]{#2}[0]}}
391 \def\@csymdef[#1]#2[#3]#4#5{\@csymdef[#1]{#2}[#3]{#4}}
```

`\notationdef` For the L^AT_EX side, we just make `\notationdef` invisible.

```
392 \def\notationdef[#1]#2#3{}
```

The code for avoiding duplicate loading is very very complex and brittle (and does not quite work). Therefore I would like to replace it with something better. It has two parts:

- keeping a registry of file paths, and only loading when the file path has not been mentioned in that, and
- dealing with relative paths (for that we have to string together prefixes and pass them one)

For the first problem, there is a very nice and efficient solution using `etoolbox` which I document below. If I decide to do away with relative paths, this would be it.

`\reqmodules` We keep a file path registry `\@register` and only load a module signature, if it is not in there.

```
393 \newcommand\reqmodules[2]{\ifinlist{#1}{\@register}{\listadd\@register{#1}\input{#1.#2}}}
```

for the relative paths, I have to find out the directory prefix and the file name. Here are two helper functions, which work well, but do not survive being called in an `\edef`, which is what we would need. First some preparation: we set up a path parser

```
394 \newcounter{@pl}
395 \DeclareListParser*\forpathlist{/}
```

`\file@name` `\file@name` selects the filename of the file path: `\file@name{/foo/bar/baz.tex}` is `baz.tex`.

```
396 \def\file@name#1{\setcounter{@pl}{0}%
397 \forpathlist{\stepcounter{@pl}\listadd\@pathlist}{#1}
398 \def\do##1{\ifnumequal{value{@pl}}{1}{##1}{\addtocounter{@pl}{-1}}}
399 \dolistloop{\@pathlist}}
```


`\file@path` `\file@path` selects the path of the file path `\file@path{/foo/bar/baz.tex}` is `/foo/bar`

```

400 \def\file@path#1{\setcounter{@pl}{0}%
401 \forpathlist{\stepcounter{@pl}\listadd{@pathlist}{#1}
402 \def\do##1{\ifnumequal{\value{@pl}}{1}{\}\addtocounter{@pl}{-1}%
403 \ifnumequal{\value{@pl}}{1}{##1}{##1/}}
404 \dolistloop{\@pathlist}}
405 \endpackage

```

what I would really like to do in this situation is

`\NEWrequiremodules` but this does not work, since the `\file@name` and `\file@path` do not survive the `\edef`.

```

406 \def\@NEWcurrentprefix{}
407 \def\NEWrequiremodules#1{\def\@pref{\file@path{#1}}%
408 \ifx\@pref\@empty\else\xdef\@NEWcurrentprefix{\@NEWcurrentprefix/\@pref}\fi%
409 \edef\@input@me{\@NEWcurrentprefix/\file@name{#1}}
410 \message{requiring \@input@me}\reqmodule{\@input@me}

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

L ^A T _E X ^M L, 3, 11– 13, 16, 19, 22	module, 8	inheritance (se- mantic), 8
	OMD ^O C, 3, 7, 10, 12	
M ^A T _H M ^L , 3, 4, 6, 7	OPEN ^M ATH, 3, 4, 6, 7	semantic
module		inheritance
name, 8	PERL, 16	relation, 8
name	relation	XML, 6

References

- [Aus+10] Ron Ausbrooks et al. *Mathematical Markup Language (MathML) Version 3.0*. Tech. rep. World Wide Web Consortium (W3C), 2010. URL: <http://www.w3.org/TR/MathML3>.
- [BFM05] Tim Berners-Lee, Roy T. Fielding, and Larry Masinter. *Uniform Resource Identifier (URI): Generic Syntax*. RFC 3986. Internet Engineering Task Force (IETF), 2005. URL: <http://www.ietf.org/rfc/rfc3986.txt>.
- [Bus+04] Stephen Buswell et al. *The Open Math Standard, Version 2.0*. Tech. rep. The OpenMath Society, 2004. URL: <http://www.openmath.org/standard/om20>.
- [Hor+11] Fulya Horozal et al. “Combining Source, Content, Presentation, Narration, and Relational Representation”. In: *Intelligent Computer Mathematics*. Ed. by James Davenport et al. LNAI 6824. Springer Verlag, 2011, pp. 212–227. ISBN: 978-3-642-22672-4. URL: http://kwarc.info/frabe/Research/HIJKR_dimensions_11.pdf.
- [Koh06] Michael Kohlhase. OMDoc – *An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh08] Michael Kohlhase. “Using L^AT_EX as a Semantic Markup Format”. In: *Mathematics in Computer Science 2.2* (2008), pp. 279–304. URL: <https://svn.kwarc.info/repos/stex/doc/mcs08/stex.pdf>.
- [Koh13] Michael Kohlhase. “Organizing Symbols between Slides, Lecture Notes, Encyclopedias, and Original Papers in Semantic Digital Libraries”. KWARC Blue Note. 2013. URL: <https://svn.omdoc.org/repos/omdoc/doc/blue/slides-notes/note.pdf>.
- [Koh15a] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/metakeys/metakeys.pdf>.
- [Koh15b] Michael Kohlhase. *omdoc.sty/cls: Semantic Markup for Open Mathematical Documents in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/omdoc/omdoc.pdf>.
- [Koh15c] Michael Kohlhase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2015. URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/stex/statements/statements.pdf>.
- [LTX] Bruce Miller. *LaTeXML: A L^AT_EX to XML Converter*. URL: <http://dlmf.nist.gov/LaTeXML/> (visited on 03/12/2013).

- [RO] Sebastian Rahtz and Heiko Oberdiek. *Hypertext marks in LATEX: a manual for hyperref*. URL: <http://tug.org/applications/hyperref/ftp/doc/manual.pdf> (visited on 01/28/2010).
- [sTeX] *Semantic Markup for L^AT_EX*. Project Homepage. URL: <http://trac.kwarc.info/sTeX/> (visited on 02/22/2011).