

modules.sty: Semantic Macros and Module Scoping in \LaTeX^*

Michael Kohlhase
FAU Erlangen-Nürnberg
<http://kwarc.info/kohlhase>

Deyan Ginev
Authorea

Rares Ambrus
Jacobs University Bremen

October 6, 2020

Abstract

The `modules` package is a central part of the \LaTeX collection, a version of $\text{\TeX}/\text{\LaTeX}$ that allows to markup $\text{\TeX}/\text{\LaTeX}$ documents semantically without leaving the document format, essentially turning $\text{\TeX}/\text{\LaTeX}$ into a document format for mathematical knowledge management (MKM).

This package supplies a definition mechanism for semantic macros and a non-standard scoping construct for them, which is oriented at the semantic dependency relation rather than the document structure. This structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

*Version v1.4 (last revised 2019/03/20)

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package Options	3
2.2	Semantic Macros	4
2.3	Testing Semantic Macros	5
2.4	Axiomatic Assumptions	6
2.5	Semantic Macros for Variables	6
2.6	Symbol and Concept Names	7
2.7	Modules and Inheritance	8
2.8	Dealing with multiple Files	9
2.9	Using Semantic Macros in Narrative Structures	11
2.10	Including Externally Defined Semantic Macros	11
2.11	Namespaces and Alignments	11
3	Limitations & Extensions	12
3.1	Perl Utility <code>sms</code>	12
3.2	Qualified Imports	13
3.3	Error Messages	13
3.4	Crossreferencing	13
3.5	No Forward Imports	13
4	The Implementation	15
4.1	Package Options	15
4.2	Modules and Inheritance	15
4.3	Semantic Macros	20
4.4	Defining Math Operators	24
4.5	Axiomatic Assumptions	24
4.6	Semantic Macros for Variables	24
4.7	Testing Semantic Macros	24
4.8	Symbol and Concept Names	25
4.9	Loading Module Signatures	26
4.10	Including Externally Defined Semantic Macros	27
4.11	Namespaces and Alignments	27
4.12	Deprecated Functionality	27
4.13	Experiments	28

1 Introduction

Following general practice in the $\text{\TeX}/\text{\LaTeX}$ community, we use the term “semantic macro” for a macro whose expansion stands for a mathematical object, and whose name (the command sequence) is inspired by the name of the mathematical object. This can range from simple definitions like `\def\Reals{\mathbb{R}}` for individual mathematical objects to more complex (functional) ones object constructors like `\def\SmoothFunctionsOn#1{\mathcal{C}^\infty(\#1,\#1)}`. Semantic macros are traditionally used to make $\text{\TeX}/\text{\LaTeX}$ code more portable. However, the $\text{\TeX}/\text{\LaTeX}$ scoping model (macro definitions are scoped either in the local group or until the rest of the document), does not mirror mathematical practice, where notations are scoped by mathematical environments like statements, theories, or such. For an in-depth discussion of semantic macros and scoping we refer the reader [Koh08].

The `modules` package provides a \LaTeX -based markup infrastructure for defining module-scoped semantic macros and \LaTeX ML bindings [LTX] to create OMDOC [Koh06] from \gTeX documents. In the \gTeX world semantic macros have a special status, since they allow the transformation of $\text{\TeX}/\text{\LaTeX}$ formulae into a content-oriented markup format like OPENMATH [Bus+04] and (strict) content MATHML [Aus+10]; see Figure 1 for an example, where the semantic macros above have been defined by the `\symdef` macros (see Section 2.2) in the scope of a `\begin{module}[id=calculus]` (see Section 2.7).

\LaTeX	<code>\SmoothFunctionsOn\Reals</code>
PDF/DVI	$\mathcal{C}^\infty(\mathbb{R}, \mathbb{R})$
OPENMATH	<pre>% <OMA> % <OMS cd="calculus" name="SmoothFunctionsOn"/> % <OMS cd="calculus" name="Reals"/> % </OMA></pre>
MATHML	<pre>% <apply> % <csymbol cd="calculus">SmoothFunctionsOn</csymbol> % <csymbol cd="calculus">Reals</csymbol> % </apply></pre>

Example 1: OPENMATH and MATHML generated from Semantic Macros

2 The User Interface

The main contributions of the `modules` package are the `module` environment, which allows for lexical scoping of semantic macros with inheritance and the `\symdef` macro for declaration of semantic macros that underly the `module` scoping.

2.1 Package Options

`showmods` The `modules` package takes six options: If we set `showmods`¹, then the views (see

¹EDNOTE: This mechanism does not work yet, since we cannot disable it when importing modules and that leads to unwanted boxes. What we need to do instead is to tweak the `sms` utility to use an

<code>qualifiedimports</code>	Section ??) are shown. If we set the <code>qualifiedimports</code> option, then qualified imports are enabled. Qualified imports give more flexibility in module inheritance, but consume more internal memory. As qualified imports are not fully implemented at the moment, they are turned off by default see Limitation 3.2.
<code>noauxreq</code>	The option <code>noauxreq</code> prohibits the registration of <code>\@requiremodules</code> commands in the <code>aux</code> file. They are necessary for preloading the module signatures so that entries in the table of contents can have semantic macros; but as they sometimes cause trouble the option allows to turn off preloading.
<code>showmeta</code>	If the <code>showmeta</code> option is set, then the metadata keys are shown (see [Koh18b] for details and customization options). The <code>mh</code> option enables MathHub support; see [Koh18a].
<code>trwarn</code>	Finally, if the <code>trwarn</code> is given, then the <code>modules</code> package only gives warnings instead of hard errors when term references are unknown.

2.2 Semantic Macros

`\symdef` The is the main constructor for semantic macros in \TeX . A call to the `\symdef` macro has the general form

$$\text{\symdef}[\langle keys \rangle][\langle cseq \rangle][\langle args \rangle][\langle definiens \rangle]$$

where $\langle cseq \rangle$ is a control sequence (the name of the semantic macro) $\langle args \rangle$ is a number between 0 and 9 for the number of arguments $\langle definiens \rangle$ is the token sequence used in macro expansion for $\langle cseq \rangle$. Finally $\langle keys \rangle$ is a keyword list that further specifies the semantic status of the defined macro.

The two semantic macros in Figure 1 would have been declared by invocations of the `\symdef` macro of the form:

$$\begin{aligned} &\text{\symdef}\{\text{Reals}\}\{\text{\mathbb{R}}\} \\ &\text{\symdef}\{\text{SmoothFunctionsOn}\}[1]\{\text{\mathcal{C}}^{\infty}(\#1, \#1)\} \end{aligned}$$

Note that both semantic macros correspond to OPENMATH or MATHML “symbols”, i.e. named representations of mathematical concepts (the real numbers and the constructor for the space of smooth functions over a set); we call these names the **symbol name** of a semantic macro. Normally, the symbol name of a semantic macro declared by a `\symdef` directive is just $\langle cseq \rangle$. The key-value pair `name= $\langle symname \rangle$` can be used to override this behavior and specify a differing name. There are two main use cases for this.

The first one is shown in Example 3, where we define semantic macros for the “exclusive or” operator. Note that we define two semantic macros: `\xorOp` and `\xor` for the applied form and the operator. As both relate to the same mathematical concept, their symbol names should be the same, so we specify `name=xor` on the definition of `\xorOp`.

`local` A key `local` can be added to $\langle keys \rangle$ to specify that the symbol is local to the module and is invisible outside. Note that even though `\symdef` has no advantage

internal version that never shows anything during sms reading.

over `\def` for defining local semantic macros, it is still considered good style to use `\symdef` and `\abbrdef`, if only to make switching between local and exported semantic macros easier.

primary
\abbrdef

Finally, the key **primary** (no value) can be given for primary symbols. The `\abbrdef` macro is a variant of `\symdef` that is only different in semantics, not in presentation. An abbreviative macro is like a semantic macro, and underlies the same scoping and inheritance rules, but it is just an abbreviation that is meant to be expanded, it does not stand for an atomic mathematical object.

We will use a simple module for natural number arithmetics as a running example. It defines exponentiation and summation as new concepts while drawing on the basic operations like $+$ and $-$ from L^AT_EX. In our example, we will define a semantic macro for summation `\Sumfromto`, which will allow us to express an expression like $\sum_{i=1}^n x^i$ as `\Sumfromto{i}{1}{n}{2i-1}` (see Example 2 for an example). In this example we have also made use of a local semantic symbol for n , which is treated as an arbitrary (but fixed) symbol.

```
\begin{module}[id=arith]
  \symdef{Sumfromto}[4]{\sum_{\#1=\#2}^{\#3}{\#4}}
  \symdef[local]{arbitraryn}{n}
  What is the sum of the first $\arbitraryn$ odd numbers, i.e.
  $\Sumfromto{i}{1}{\arbitraryn}{2i-1}$?
\end{module}
```

What is the sum of the first n odd numbers, i.e. $\sum_{i=1}^n 2i - 1$?

Example 2: Semantic Markup in a module Context

\symvariant

The `\symvariant` macro can be used to define presentation variants for semantic macros previously defined via the `\symdef` directive. In an invocation

```
\symdef[\langle keys \rangle]{\langle cseq \rangle}[\langle args \rangle]{\langle pres \rangle}
\symvariant{\langle cseq \rangle}[\langle args \rangle]{\langle var \rangle}{\langle varpres \rangle}
```

the first line defines the semantic macro `\langle cseq \rangle` that when applied to `\langle args \rangle` arguments is presented as `\langle pres \rangle`. The second line allows the semantic macro to be called with an optional argument `\langle var \rangle`: `\langle cseq \rangle[\langle var \rangle]` (applied to `\langle args \rangle` arguments) is then presented as `\langle varpres \rangle`. We can define a variant presentation for `\xor`; see Figure 3 for an example.

\resymdef

Version 1.0 of the `modules` package had the `\resymdef` macro that allowed to locally redefine the presentation of a macro. But this did not interact well with the `beamer` package and was less useful than the `\symvariant` functionality. Therefore it is deprecated now and leads to an according error message.

2.3 Testing Semantic Macros

One of the problems in managing large module graphs with many semantic macros, so the `module` package gives an infrastructure for unit testing. The first macro is

\symtest

`\symtest`, which allows the author of a semantic macro to generate test output

```

\begin{module}[id=xbool]
  \symdef[name=xor]{xorOp}{\oplus}
  \symvariant{xorOp}{uvee}{\underline{\vee}}
  \symdef{xor}[2]{#1\xorOp #2}
  \symvariant{xor}[2]{uvee}{#1\xorOp[uvee] #2}
  Exclusive disjunction is commutative:  $\text{\xor{p}q}=\text{\xor{q}p}$ 
  Some authors also write exclusive or with the  $\text{\xorOp[uvee]}$  operator,
  then the formula above is  $\text{\xor[uvee]{p}q}=\text{\xor[uvee]{q}p}$ 
\end{module}

```

Exclusive disjunction is commutative: $p \oplus q = q \oplus p$
Some authors also write exclusive or with the $\underline{\vee}$ operator, then the formula above is $p \underline{\vee} q = q \underline{\vee} p$

Example 3: Presentation Variants of a Semantic Macro

(if the `symtest` option is set) see figure 4 for a “tested semantic macro definition”. Note that the language in this purely generated, so that it can be adapted (tbd).

```

\symdef[name=setst]{SetSt}[2]{\{#1\,\vert\,#2\}}
\symtest[name=setst]{SetSt}{\SetSt{a}{a>0}}

```

generates the output
Symbol `setst` with semantic macro `\SetSt`: used e.g. in $\{a \mid a > 0\}$

Example 4: A Semantic Macro Definition with Test

`\abbrtest` The `\abbrtest` macro gives the analogous functionality for `\abbrdef`.

2.4 Axiomatic Assumptions

`\assdef` In many ways, axioms and assumptions in definitions behave a lot like symbols (see [RK13] for discussion). Therefore we provide the macro `\assdef` that can be used to mark up assumptions. Given a phrase $\langle phrase \rangle$ in a definition², we can use `\assdef{\langle name \rangle}{\langle phrase \rangle}` to give this the symbol name $\langle name \rangle$.³

2.5 Semantic Macros for Variables

Up to now, the semantic macros generated OPENMATH and MATHML markup where the heads of the semantic macros become constants (the `OMS` and `csymbol` elements in Figure 1). But sometimes we want to have semantic macros for variables, e.g. to associate special notation conventions. For instance, if we want to define mathematical structures from components as in Figure 5, where the semigroup operation \circ is a variable epistemologically, but is a n -ary associative operator – we are in a semigroup after all. Let us call such variables **semantic variables** to contrast them from **semantic constants** generated by `\symdef` and `\symvariant`.

²EdNOTE: only definitions?

³EdNOTE: continue

Definition 3.17 Let $\langle G, \circ \rangle$ be a semigroup, then we call $e \in G$ a **unit**, iff $e \circ x = x \circ e = x$. A semigroup with unit $\langle G, \circ, e \rangle$ is called a **monoid**.

Example 5: A Definition of a Structure with “semantic variables”.

Semantic variables differ from semantic constants in two ways:

1. they do not participate in the imports mechanism and
2. they generate markup with variables.

In the case of Figure 5 we (want to) have the XML markup in Figure 6. To associate the notation to the variables, we define semantic macros for them, here the macro `\op` for the (semigroup) operation via the `\vardef` macro. `\vardef` works exactly like, except

1. semantic variables are local to the current $\text{T}_{\text{E}}\text{X}$ group and
2. they generate variable markup in the XML

$\text{T}_{\text{E}}\text{X}$	<code>\vardef{op}[1]{\assoc\circ{#1}}</code>
OMDoc	<pre>% <notation> % <prototype> % <OMA> % <OMV name="op"/> % <expr name="a1"/> % <expr name="a2"/> % </OMA> % </prototype> % <rendering> % <mrow> % <render name="a1"/> % <mo>&#x2384;</mo> % <render name="a2"/> % </mrow> % </rendering> % </notation></pre>
$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$	<code>\op{x,e}</code>
PDF/DVI	$x \circ e$
OPENMATH	<code>% <OMA><OMV name="op"/><OMV name="x"/><OMV name="e"/></OMA></code>
MATHML	<code>% <apply><ci>op</ci><ci>x</ci><ci>e</ci></apply></code>

Example 6: Semantic Variables in OPENMATH and MATHML

2.6 Symbol and Concept Names

Just as the `\symdef` declarations define semantic macros for mathematical symbols, the `modules` package provides an infrastructure for *mathematical concepts* that are expressed in mathematical vernacular. The key observation here is that concept names like “finite symplectic group” follow the same scoping rules as mathematical symbols, i.e. they are module-scoped. The `\termdef` macro is an ana-

EdN:4

`\capitalize`
`\termref`
`\symref`

logue to `\symdef` that supports this: use `\termdef[\langle keys \rangle]{\langle cseq \rangle}{\langle concept \rangle}` to declare the macro `\langle cseq \rangle` that expands to `\langle concept \rangle`. See Figure 7 for an example, where we use the `\capitalize` macro to adapt `\langle concept \rangle` to the sentence beginning.⁴ The main use of the `\termdef`-defined concepts lies in automatic cross-referencing facilities via the `\termref` and `\symref` macros provided by the `statements` package [Koh18c]. Together with the `hyperref` package [RO], this provide cross-referencing to the definitions of the symbols and concepts. As discussed in section 3.4, the `\symdef` and `\termdef` declarations must be on top-level in a module, so the infrastructure provided in the `modules` package alone cannot be used to locate the definitions, so we use the infrastructure for mathematical statements for that.

```
\termdef[name=xor]{xdisjunction}{exclusive disjunction}
\capitalize\xdisjunction is commutative: $\xor{p}q=\xor{q}p$
```

Example 7: Extending Example 3 with Term References

2.7 Modules and Inheritance

`module` The `module` environment takes an optional `KeyVal` argument. Currently, only the `id` key is supported for specifying the identifier of a module (also called the module name). A module introduced by `\begin{module}[id=foo]` restricts the scope the semantic macros defined by the `\symdef` form to the end of this module given by the corresponding `\end{module}`, and to any other `module` environments that import them by a `\importmodule{foo}` directive. If the module `foo` contains `\importmodule` directives of its own, these are also exported to the importing module.

`\importmodule`

Thus the `\importmodule` declarations induce the semantic inheritance relation. Figure 8 shows a module that imports the semantic macros from three others. In the simplest form, `\importmodule{\langle mod \rangle}` will activate the semantic macros and concepts declared by `\symdef` and `\termdef` in module `\langle mod \rangle` in the current module¹. To understand the mechanics of this, we need to understand a bit of the internals. The `module` environment sets up an internal macro pool, to which all the macros defined by the `\symdef` and `\termdef` declarations are added; `\importmodule` only activates this macro pool. Therefore `\importmodule{\langle mod \rangle}` can only work, if the `TeX` parser — which linearly goes through the `gTeX` sources — already came across the module `\langle mod \rangle`. In many situations, this is not obtainable; e.g. for “semantic forward references”, where symbols or concepts are previewed or motivated to knowledgeable readers before they are formally introduced or for modularizations of documents into multiple files. We come to this next: ⁵

EdN:5

`\metalinguage`

The `\metalinguage` macro is a variant of `importmodule` that imports the meta language, i.e. the language in which the meaning of the new symbols is expressed.

⁴EDNOTE: continue, describe `\langle keys \rangle`, they will have to to with plurals,... once implemented

¹Actually, in the current `TeX` group, therefore `\importmodule` should be placed directly after the `\begin{module}`.

⁵EDNOTE: MK: document the other keys of module

For mathematics this is often first-order logic with some set theory; see [RK13] for discussion.

2.8 Dealing with multiple Files

The infrastructure presented above works well if we are dealing with small files or small collections of modules. In reality, collections of modules tend to grow, get re-used, etc, making it much more difficult to keep everything in one file. This general trend towards increasing entropy is aggravated by the fact that modules are very self-contained objects that are ideal for re-used. Therefore in the absence of a content management system for L^AT_EX document (fragments), module collections tend to develop towards the “one module one file” rule, which leads to situations with lots and lots of little files.

Moreover, most mathematical documents are not self-contained, i.e. they do not build up the theory from scratch, but pre-suppose the knowledge (and notation) from other documents. In this case we want to make use of the semantic macros from these prerequisite documents without including their text into the current document. One way to do this would be to have L^AT_EX read the prerequisite documents without producing output. For efficiency reasons, S_TE_X chooses a different route, the `module` package uses auxiliary files called **S_TE_X module signatures**. For any file, $\langle file \rangle.tex$, we generate a corresponding S_TE_X module signature $\langle file \rangle.sms$ with the `sms` utility (see also Limitation 3.1), which contains (copies of) all `\begin/\end{module}`, `\importmodule`, `\symdef`, and `\termdef` invocations in $\langle file \rangle.tex$. The value of an S_TE_X module signature is that it can be loaded instead its corresponding S_TE_X document, if we are only interested in the semantic macros.

`\importmodule` The `\importmodule` macro can be given an optional first keyword argument that can be used to specify which S_TE_X module signatures to load.

`load` `\importmodule[load= $\langle filepath \rangle$]{ $\langle mod \rangle$ }` will load the S_TE_X module signature $\langle filepath \rangle.sms$ (if it exists and has not been loaded before) and activate the semantic macros from module $\langle mod \rangle$ (which was supposedly defined in $\langle filepath \rangle.tex$). Note that since $\langle filepath \rangle.sms$ contains all `\importmodule` statements that $\langle filepath \rangle.tex$ does, an `\importmodule` recursively loads all necessary files to supply the semantic macros inherited by the current module.

Thus `\importmodule` can be used to make module files truly self-contained. To arrive at a file-based content management system, it is good practice to reuse the module identifiers as module names and to prefix module files with corresponding `\importmodule` statements that pre-load the corresponding module files. But this leads to tedious duplication: We see imports of the form

```
\importmhmodule[path=foo/en/very-long-name]{very-long-name}
```

`dir` To avoid this, `\importmhmodule` allows a second key: `dir`, which specifies the directory of the S_TE_X module signature. So we can write

```
\importmhmodule[dir=foo/en]{very-long-name}
```

instead when the module name and file name coincide. This also avoids the maintenance problems (typos) induced by duplication. If both `path` and `dir` are given, the latter takes precedence.

```
\begin{module}[id=foo]
\importmodule[dir=../other]{bar}
\importmodule[load=../mycolleaguesmodules]{baz}
\importmodule[load=../other/bar]{foobar}
...
\end{module}
```

Example 8: Self-contained Modules via `importmodule`

In Example 8, we have shown the typical setup of a module file. The `\importmodule` macro takes great care that files are only read once, as \TeX allows multiple inheritance and this setup would lead to an exponential (in the module inheritance depth) number of file loads.

Sometimes we want to import an existing OMDoc theory² $\widehat{\mathcal{T}}$ into (the OMDoc document $\widehat{\mathcal{D}}$ generated from) a \TeX document \mathcal{D} . Naturally, we have to provide an \TeX stub module \mathcal{T} that provides `\symdef` declarations for all symbols we use in \mathcal{D} . In this situation, we use `\importOMDocmodule[$\langle spath \rangle$]{ $\langle OURI \rangle$ }{ $\langle name \rangle$ }`, where $\langle spath \rangle$ is the file system path to \mathcal{T} (as in `\importmodule`, this argument must not contain the file extension), $\langle OURI \rangle$ is the URI to the OMDoc module (this time with extension), and $\langle name \rangle$ is the name of the theory $\widehat{\mathcal{T}}$ and the module in \mathcal{T} (they have to be identical for this to work). Note that since the $\langle spath \rangle$ argument is optional, we can make “local imports”, where the stub \mathcal{T} is in \mathcal{D} and only contains the `\symdefs` needed there.

Note that the recursive (depth-first) nature of the file loads induced by this setup is very natural, but can lead to problems with the depth of the file stack in the \TeX formatter (it is usually set to something like 15^3). Therefore, it may be necessary to circumvent the recursive load pattern providing (logically spurious) `\importmodule` commands. Consider for instance module `bar` in Example 8, say that `bar` already has load depth 15, then we cannot naively import it in this way. If module `bar` depended say on a module `base` on the critical load path, then we could add a statement `\requiremodules{../base}` in the second line. This would load the modules from `../base.sms` in advance (uncritical, since it has load depth 10) without activating them, so that it would not have to be re-loaded in the critical path of the module `foo`. Solving the load depth problem.

The `\inputref` macro behaves just like `\input` in the \LaTeX workflow, but in the \LaTeXML conversion process creates a reference to the transformed version of the input file instead. Moreover, spacing can be customized by the `\inputref@preskip` and `\inputref@postskip` macros, which default to nothing, but could be customized e.g. to `\medskip`.

²OMDoc theories are the counterpart of \TeX modules.

³If you have sufficient rights to change your \TeX installation, you can also increase the variable `max_in_open` in the relevant `texmf.cnf` file. Setting it to 50 usually suffices

2.9 Using Semantic Macros in Narrative Structures

The `\importmodule` macro establishes the inheritance relation, a transitive relation among modules that governs visibility of semantic macros. In particular, it can only be used in modules (and has to be used at the top-level, otherwise it is hindered by \LaTeX groups). In many cases, we only want to *use* the semantic macros in an environment (and not re-export them). Indeed, this is the normal situation for most parts of mathematical documents. For that \S\TeX provides the `\usemodule` macro, which takes the same arguments as `\importmodule`, but is treated differently in the \S\TeX module signatures. A typical situation is shown in Figure 9, where we open the module `ring` (see Figure ??) and use its semantic macros (in the `omtext` environment). In earlier versions of \S\TeX , we would have to wrap the `omtext` environment in an anonymous `module` environment to prevent re-export.

`\usemodule`

```
\begin{omtext}
  \usemodule[load=../algebra/rings.tex]{ring}
  We  $R$  be a ring  $(\text{\textbackslash}rbase, \text{\textbackslash}rplus, \text{\textbackslash}rzero, \text{\textbackslash}rminusOp, \text{\textbackslash}rtimes, \text{\textbackslash}rone)$ , ...
\end{omtext}
```

Example 9: Using Semantic Macros in Narrative Structures

2.10 Including Externally Defined Semantic Macros

In some cases, we use an existing \LaTeX macro package for typesetting objects that have a conventionalized mathematical meaning. In this case, the macros are “semantic” even though they have not been defined by a `\symdef`. This is no problem, if we are only interested in the \LaTeX workflow. But if we want to e.g. transform them to OMDOC via \LaTeX XML, the \LaTeX XML bindings will need to contain references to an OMDOC theory that semantically corresponds to the \LaTeX package. In particular, this theory will have to be imported in the generated OMDOC file to make it OMDOC-valid.

`\requirepackage`

To deal with this situation, the `modules` package provides the `\requirepackage` macro. It takes two arguments: a package name, and a URI of the corresponding OMDOC theory. In the \LaTeX workflow this macro behaves like a `\usepackage` on the first argument, except that it can — and should — be used outside the \LaTeX preamble. In the \LaTeX XML workflow, this loads the \LaTeX XML bindings of the package specified in the first argument and generates an appropriate `imports` element using the URI in the second argument.

2.11 Namespaces and Alignments

We often want to align the content of \S\TeX modules to formalizations, e.g. to take advantage of type declarations there. For this, we extend the keys of the `module` environment and the `\symdef` macro with a key `align` whose value is an external

`align`

MMT theory or symbol name respectively. Note that symbols can only be aligned in aligned modules.

As full MMT URIs are of the form $\langle URI \rangle ? \langle theory \rangle ? \langle name \rangle$, we need a way to specify the $\langle URI \rangle$. We adopt the system of **namespaces** of MMT [MNS]: `\namespace` the macro declares a namespace URI. If the optional argument is given, then this is a namespace abbreviation declaration, which can be used later to reference theories/modules from other namespaces.

The example below shows off all possibilities. We first declare the namespace of the document (which places all theories and their symbols into this namespace). Then we add two more a namespace abbreviation: `sets:` and `moresets:` that we will use to for the alignments in the module. We use the `ns` and `align` keys in the `module` environment to specify that the external theory `sets:?ESet` is the default alignment target, i.e. any symbol that in the `emptyset` module is aligned by default to the symbol with the same name in the external `sets:?ESet` theory.

```
\namespace{http://mathhub.info/smgom/sets}
\namespace[sets]{http://mathhub.info/MitM/smgom/sets}
\namespace[moresets]{http://mathhub.info/more/sets}
\begin{module}[creators=miko,ns=sets,align=ESet]{emptyset}
  \importmodule{set}
  \symdef[assocarg=1]{set}[1]{\{#1\}}
  \symdef[align=empty]{eset}{\emptyset}
  \symdef[align=AEset?eset]{aeset}{\emptyset^+}
  \symdef[ns=moresets,align=fuzzy?eset]{feset}{\emptyset^f}
  \symdef[noalign]{neset}{\emptyset^*}
\end{module}
```

The first `\symdef` aligns the symbol `emptyset?set` with `sets:?ESet?set` via default alignment. This breaks down for the symbol `eset`, so we specify an alignment to the symbol `sets:?empty` via the `align` key on the `\symdef`. If we want to align with a different theory we can just use the `?` notation as for `aeset`. A different namespace can be specified by the `ns` key, and finally, we can indicate that a symbol should not be aligned via the `noalign` key.

3 Limitations & Extensions

In this section we will discuss limitations and possible extensions of the `modules` package. Any contributions and extension ideas are welcome; please discuss ideas, requests, fixes, etc on the `gTeX` TRAC [sTeX].

3.1 Perl Utility `sms`

Currently we have to use an external perl utility `sms` to extract `gTeX` module signatures from `gTeX` files. This considerably adds to the complexity of the `gTeX` installation and workflow. If we can solve security setting problems that allows us to write to `gTeX` module signatures outside the current directory, writing them

from `\sTeX` may be an avenue of future development see [sTeX, issue #1522] for a discussion.

3.2 Qualified Imports

In an earlier version of the `modules` package we used the `usesqualified` for importing macros with a disambiguating prefix (this is used whenever we have conflicting names for macros inherited from different modules). This is not accessible from the current interface. We need something like a `\importqualified` macro for this; see [sTeX, issue #1505]. Until this is implemented the infrastructure is turned off by default, but we have already introduced the `qualifiedimports` option for the future.

`qualifiedimports`

3.3 Error Messages

The error messages generated by the `modules` package are still quite bad. For instance if `thyA` does not exist we get the cryptic error message

```
! Undefined control sequence.
\module@defs@thyA ...hy
\expandafter \mod@newcomma...
1.490 ...ortmodule{thyA}
```

This should definitely be improved.

3.4 Crossreferencing

Note that the macros defined by `\symdef` are still subject to the normal `TeX` scoping rules. Thus they have to be at the top level of a module to be visible throughout the module as intended. As a consequence, the location of the `\symdef` elements cannot be used as targets for crossreferencing, which is currently supplied by the `statement` package [Koh18c]. A way around this limitation would be to import the current module from the `\sTeX` module signature (see Section 2.7) via the `\importmodule` declaration.

3.5 No Forward Imports

`\sTeX` allows imports in the same file via `\importmodule{<mod>}`, but due to the single-pass linear processing model of `TeX`, `<mod>` must be the name of a module declared *before* the current point. So we cannot have forward imports as in ⁶

```
\begin{module}[id=foo]
  \importmodule{mod}
  ...
\end{module}
...
```

⁶EdNOTE: `usemodule` should work here; revise

```

\begin{module}[id=mod]
...
\end{module}

```

a workaround, we can extract the module $\langle mod \rangle$ into a file `mod.tex` and replace it with `\sinput{mod}`, as in

```

\begin{module}[id=foo]
  \importmodule[load=mod]{mod}
  ...
\end{module}
...
\sinput{mod}

```

then the `\importmodule` command can read `mod.sms` (created via the `sms` utility) without having to wait for the module $\langle mod \rangle$ to be defined.

4 The Implementation

The `modules` package generates two files: the L^AT_EX package (all the code between `<*package>` and `</package>`) and the L^AT_EXML bindings (between `<*ltxml>` and `</ltxml>`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

4.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false). The options we are not using, we pass on to the `sref` package we require next.

```

1 <*package>
2 \newif\if@modules@html@\@modules@html@true
3 \DeclareOption{omdocmode}{\@modules@html@false}
4 \newif\if@modules@mh@\@modules@mh@false
5 \DeclareOption{mh}{\@modules@mh@true}
6 \newif\ifmod@show\mod@showfalse
7 \DeclareOption{showmods}{\mod@showtrue}
8 \newif\ifaux@req\aux@reqtrue
9 \DeclareOption{noauxreq}{\aux@reqfalse}
10 \newif\ifmod@qualified\mod@qualifiedfalse
11 \DeclareOption{qualifiedimports}{\mod@qualifiedtrue}
12 \newif\if@trwarn\@trwarnfalse
13 \DeclareOption{trwarn}{\@trwarntrue}
14 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{sref}}
15 \ProcessOptions

16 \RequirePackage{stex-base}
17 \RequirePackage{sref}
18 \RequirePackage{pathsuris}
19 \RequirePackage[abspath]{currfile}
20 \if@modules@mh\RequirePackage{modules-mh}\fi
21 \RequirePackage{xspace}
22 \if@ltxml\else\ifmod@show\RequirePackage{mdframed}\fi\fi

```

4.2 Modules and Inheritance

We define the keys for the `module` environment and the actions that are undertaken, when the keys are encountered.

`module:cd` This `KeyVal` key is only needed for L^AT_EXML at the moment; use this to specify a content dictionary name that is different from the module name.

```

23 \addmetakey*{module}{title}
24 \addmetakey*{module}{creators}
25 \addmetakey*{module}{contributors}
26 \addmetakey*{module}{srccite}
27 \addmetakey*{module}{align}[WithTheModuleOfTheSameName]

```

```

28 \addmetakey*{module}{ns}
29 \addmetakey*{module}{narr}
30 \addmetakey*{module}{noalign}[true]

```

module:id For a module with [id=*<name>*], we have a macro `\module@defs@<name>` that acts as a repository for semantic macros of the current module. I will be called by `\importmodule` to activate them. We will add the internal forms of the semantic macros whenever `\symdef` is invoked. To do this, we will need an unexpanded form `\this@module` that expands to `\module@defs@<name>`; we define it first and then initialize `\module@defs@<name>` as empty. Then we do the same for qualified imports as well (if the `qualifiedimports` option was specified). Furthermore, we save the module name in the token register `\mod@id`.

```

31 \define@key{module}{id}{%
32   \edef\this@module{%
33     \expandafter\noexpand\csname module@defs@#1\endcsname%
34   }%
35   \csgdef{module@defs@#1}{}%
36   \ifmod@qualified%
37     \edef\this@qualified@module{%
38       \expandafter\noexpand\csname module@defs@#1\endcsname%
39     }%
40     \csgdef{module@defs@qualified@#1}{}%
41   \fi%
42   \def\mod@id{#1}%
43 }%

```

module@heading Then we make a convenience macro for the module heading. This can be customized.

```

44 \ifdef{\thesection}{\newcounter{module}[section]}{\newcounter{module}}%
45 \newrobustcmd\module@heading{%
46   \stepcounter{module}%
47   \ifmod@show%
48     \noindent\textbf{Module} \thesection.\themodule [\mod@id]}%
49     \sref@label@id{Module \thesection.\themodule [\mod@id]}%
50     \ifx\module@title\@empty : \quad\else\quad(\module@title)\hfill\\fi%
51   \fi%
52 }% mod@show

```

module Finally, we define the begin module command for the module environment. Much of the work has already been done in the keyval bindings, so this is quite simple. We store the file name (without extension) and extension of the module file in the global macros `\module@<name>@path` and `\module@<name>@ext`, so that we can use them later. The source of these two macros, `\mod@path` and `\mod@ext`, are defined in `\requiremodules`.

```

53 \newenvironment{module}[1][]{%
54   \begin@module{#1}%
55   \ifcsundef{mod@path}{\csxdef{module@\mod@id @path}{\mod@path}}%
56   \ifcsundef{mod@ext}{\csxdef{module@\mod@id @ext}{\mod@ext}}%

```



```

57 \module@heading% make the headings
58 \ignorespacesandpars}{%
59 \end{@module}%
60 \ignorespacesafterend%
61 }%
62 \ifmod@show\surroundwithmdframed{module@om@common}\fi%

@module A variant of the module environment that does not create printed representations
(in particular no frames)

63 \newif\ifarchive@ns@empty@archive@ns@empty@false
64 \def\set@default@ns{
65 \edef\@module@ns@temp{\currfileabspath}
66 \edef\@module@ns@temp{\ifiswindows@windows@to@path\@module@ns@temp\else\@module@ns@temp\fi}
67 \path@droptextension\@module@ns@temp\@module@ns@temp}
68 \archive@ns@empty@false
69 \unless\ifcsname mathhub@archive@ns\endcsname
70 \archive@ns@empty@true
71 \else
72 \ifx\mathhub@archive@ns\empty\archive@ns@empty@true\fi
73 \fi
74 \ifarchive@ns@empty@
75 \asuri{\@module@ns@temp}{file\@Colon\@Slash\@Slash\@module@ns@temp}
76 \@module@ns@temp{drop extension}
77 \setkeys{module}{ns=\@module@ns@tempuri}
78 \else
79 \asuri{\@module@filepath@temp}{file\@Colon\@Slash\@Slash\@module@ns@temp}
80 \asuri{\@module@ns@temp}{\mathhub@archive@ns}
81 \asuri{\@module@archivedir}{file\@Colon\@Slash\@Slash\mathhub@archive@dir\@Slash source}
82 \IfBeginWith\@module@filepath@temppath\@module@archivedirpath{
83 \StrLen\@module@archivediruri[\ns@temp@length]
84 \StrGobbleLeft\@module@filepath@tempuri\ns@temp@length[\@module@filepath@tempuri]
85 \edef\@module@ns@tempuri{\@module@ns@tempuri\@module@filepath@tempuri}
86 }{}
87 \setkeys{module}{ns=\@module@ns@tempuri}
88 \fi
89 }
90
91 \def\set@next@moduleid{
92 \unless\ifcsname namespace@\module@ns @unnamedmodules\endcsname
93 \csgdef{namespace@\module@ns @unnamedmodules}{0}
94 \fi
95 \edef\namespace@currnum{csname namespace@\module@ns @unnamedmodules\endcsname}
96 \edef\module@temp@setidname{\noexpand\setkeys{module}{id=module\namespace@currnum}}
97 \module@temp@setidname
98 \csxdef{namespace@\module@ns @unnamedmodules}{\the\numexpr\namespace@currnum+1}
99 }
100
101
102 \newenvironment{@module}[1][[]]{
103 \metasetkeys{module}{#1}

```

```

104 \ifx\module@ns\@empty\set@default@ns\fi
105 \ifx\module@narr\@empty
106 \setkeys{module}{narr=\module@ns}
107 \fi
108 \ifcsname mod@id\endcsname
109 \ifx\mod@id\@empty\set@next@moduleid\fi
110 \else\set@next@moduleid\fi
111 \seturi{module@uri@}{\module@ns?\mod@id}
112 }{}%

```

`\activate@defs` To activate the `\symdefs` from a given module $\langle mod \rangle$, we call the macro `\module@defs@ $\langle mod \rangle$` . But to make sure that every module is activated only once, we only activate if the macro `\module@defs@ $\langle mod \rangle$` is undefined, and define it directly afterwards to prohibit further activations.

```

113 \def\activate@defs#1{%
114 \ifcsundef{module@#1@activated}{\csname module@defs@#1\endcsname}{}%
115 \@namedef{module@#1@activated}{true}%
116 }%

```

`\export@defs` `\export@defs{ $\langle mod \rangle$ }` exports all the `\symdefs` from module $\langle mod \rangle$ to the current module (if it has the name $\langle currmod \rangle$), by adding a call to `\module@defs@ $\langle mod \rangle$` to the registry `\module@defs@ $\langle currmod \rangle$` .⁷⁸

Naive understanding of this code: `#1` be will be expanded first, then `\this@module`, then `\active@defs`, then `\g@addto@macro`.

```

117 \def\export@defs#1{\@ifundefined{mod@id}{}%
118 \expandafter\expandafter\expandafter\g@addto@macro%
119 \expandafter\this@module\expandafter{\activate@defs{#1}}}%

```

Now we come to the implementation of `\importmodule`, but before we do, we define conditional and an auxiliary macro:

`\if@importing` `\if@importing` can be used to shut up macros in an import situation.

```

120 \newif\if@importing\@importingfalse

```

`\update@used@modules` This updates the register `\used@modules`

```

121 \newcommand\update@used@modules[1]{%
122 \ifx\used@modules\@empty%
123 \edef\used@modules{#1}%
124 \else%
125 \edef\used@modules{\used@modules,#1}%
126 \fi}

```

`\importmodule` The `\importmodule[$\langle file \rangle$]{ $\langle mod \rangle$ }` macro is an interface macro that loads $\langle file \rangle$ and activates and re-exports the `\symdefs` from module $\langle mod \rangle$. As we will (probably) need to keep a record of the currently imported modules (top-level only),

⁷EDNOTE: MK: I have the feeling that we may be exporting modules multiple times here, is that a problem?

⁸EDNOTE: Jinbo: This part of code is extremely easy to generate bugs, cautiously edit this part of code.

we divide the functionality into a user-visible macro that records modules in the `\used@modules` register and an internal one (`\@importmodule`) that does the actual work.

```

127 \gdef\used@modules{}
128 \srefaddidkey{importmodule}
129 \addmetakey{importmodule}{load}
130 \addmetakey{importmodule}{dir}
131 \addmetakey[sms]{importmodule}{ext}
132 \addmetakey[false]{importmodule}{conservative}[true]
133 \newcommand\importmodule[2][{}]{%
134 \metasetkeys{importmodule}{#1}%
135 \update@used@modules{#2}%
136 \ifx\importmodule@dir\empty
137 \@importmodule[\importmodule@load]{#2}{\importmodule@ext}{export}%
138 \else\@importmodule[\importmodule@dir/#2]{#2}{\importmodule@ext}{export}\fi%
139 \ignorespacesandpars}

```

`\@importmodule` `\@importmodule[\langle filepath \rangle]{\langle mod \rangle}{\langle ext \rangle}{\langle export? \rangle}` loads `\langle filepath \rangle.\langle ext \rangle` (if it is given) and activates the module `\langle mod \rangle`. If `\langle export? \rangle` is `export`, then it also re-exports the `\symdefs` from `\langle mod \rangle`.

First `\@load` will store the base file name with full path, then check if `\module@<mod>@path` is defined. If this macro is defined, a module of this name has already been loaded, so we check whether the paths coincide, if they do, all is fine and we do nothing otherwise we give a suitable error. If this macro is undefined we load the path by `\requiremodules`.

```

140 \newcommand\@importmodule[4][{}]{%
141 {\@importingtrue% to shut up macros while in the group opened here
142 \edef\@load{#1}%
143 \ifx\@load\empty\relax\else%
144 \ifcsundef{module@#2@path}{\requiremodules{#1}{#3}}%
145 {\edef\@path{csname module@#2@path\endcsname}%
146 \IfStrEq\@load\@path{\relax}% if the known path is the same as the requested one do nothing
147 {\PackageError{modules}% else signal an error
148 {Module Name Clash\MessageBreak
149 A module with name #2 was already loaded under the path "\@path"\MessageBreak
150 The imported path "\@load" is probably a different module with the\MessageBreak
151 same name; this is dangerous -- not importing}%
152 {Check whether the Module name is correct}}}%
153 \fi}%
154 \activate@defs{#2}% activate the module
155 \edef\@export{#4}\def\@@export{export}%prepare comparison
156 \ifx\@export\@@export\export@defs{#2}\fi% export the module
157 }%

```

`\usemodule` `\usemodule` acts like `\importmodule`, except that the `sms` utility does not transfer it to the module signatures and it does not re-export the `\symdefs`.

```

158 \newcommand\usemodule[2][{}]{%
159 \metasetkeys{importmodule}{#1}%

```

```

160 \update@used@modules{#2}%
161 \ifx\importmodule@dir\empty
162 \@importmodule[\importmodule@load]{#2}{\importmodule@ext}{noexport}%
163 \else\@importmodule[\importmodule@dir/#2]{#2}{\importmodule@ext}{noexport}\fi%
164 \ignorespacesandpars}

```

`\withusedmodules` This variant just imports all the modules in a comma-separated list (usually `\used@modules`)

```

165 \newcommand\withusedmodules[2]{\@for\@I:=#1\do{\activate@defs\@I}{#2}}%

```

EdN:9

`\importOMDocmodule` for the L^AT_EX side we can just re-use `\importmodule`, for the L^AT_EX_ML side we have a full URI anyways. So things are easy.⁹

```

166 \newrobustcmd\importOMDocmodule[3][]{\importmodule[#1]{#3}}%

```

`\metalinguage` `\metalinguage` behaves exactly like `\importmodule` for formatting. For L^AT_EX_ML, we only add the `type` attribute.

```

167 \let\metalinguage=\importmodule%

```

4.3 Semantic Macros

`\mod@newcommand` We first hack the L^AT_EX kernel macros to obtain a version of the `\newcommand` macro that does not check for definedness.

```

168 \let\mod@newcommand=\providerobustcmd%

```

Now we define the optional `KeyVal` arguments for the `\symdef` form and the actions that are taken when they are encountered.

`conceptdef`

```

169 \srefaddidkey{conceptdef}%
170 \addmetakey*{conceptdef}{title}%
171 \addmetakey{conceptdef}{subject}%
172 \addmetakey*{conceptdef}{display}%
173 \def\conceptdef@type{Symbol}%
174 \newrobustcmd\conceptdef[2][]{%
175   \metasetkeys{conceptdef}{#1}%
176   \ifx\conceptdef@display\st@flow\else{\stDMemph{\conceptdef@type} #2:}\fi%
177   \ifx\conceptdef@title\empty~\else~(\stDMemph{\conceptdef@title})\par\fi%
178 }%

```

EdN:10

10

`symdef:keys` The optional argument `local` specifies the scope of the function to be defined. If `local` is not present as an optional argument then `\symdef` assumes the scope of the function is global and it will include it in the pool of macros of the current module. Otherwise, if `local` is present then the function will be defined only locally and it will not be added to the current module (i.e. we cannot inherit

⁹EdNOTE: MK@DG: this macro is seldom used, maybe I should just switch arguments.

¹⁰EdNOTE: MK@DG: maybe we need to add `DefKeyVals` here?

a local function). Note, the optional key `local` does not need a value: we write `\symdef[local]{somefunction}[0]{some expansion}`. The other keys are not used in the L^AT_EX part.

```

179 \newif\if@symdeflocal%
180 \srefaddidkey{symdef}%
181 \define@key{symdef}{local}[true]{\@symdeflocaltrue}%
182 \define@key{symdef}{noverb}[all]{}%
183 \define@key{symdef}{align}[WithTheSymbolOfTheSameName]{}%
184 \define@key{symdef}{specializes}{}%
185 \addmetakey*{symdef}{noalign}[true]
186 \define@key{symdef}{primary}[true]{}%
187 \define@key{symdef}{assocarg}{}%
188 \define@key{symdef}{bvars}{}%
189 \define@key{symdef}{bargs}{}%
190 \addmetakey{symdef}{ns}%
191 \addmetakey{symdef}{name}%
192 \addmetakey*{symdef}{title}%
193 \addmetakey*{symdef}{description}%
194 \addmetakey{symdef}{subject}%
195 \addmetakey*{symdef}{display}%

```

EdN:11

11

`\symdef` The the `\symdef`, and `\@symdef` macros just handle optional arguments.

```

196 \def\symdef{\ifnextchar[{\@symdef}{\@symdef[]}}%
197 \def\@symdef[#1]#2{\ifnextchar[{\@@symdef[#1]{#2}}{\@@symdef[#1]{#2}[0]}}%

```

next we locally abbreviate `\mod@newcommand` to simplify argument passing.

```

198 \def\@mod@nc#1{\mod@newcommand{#1}[1]}%

```

and we copy a very useful piece of code from <http://tex.stackexchange.com/questions/23100/looking-for-an-ignorespacesandpars>, it ignores spaces and following implicit paragraphs (double newlines), explicit `\pars` are respected however

```

199 \def\ignorespacesandpars{\begingroup\catcode13=10\ifnextchar\relax{\endgroup}{\endgroup}}
and more adapted from http://tex.stackexchange.com/questions/179016/
ignore-spaces-and-pars-after-an-environment
200 \def\ignorespacesandparsafterend#1\ignorespaces\fi{#1\fi\ignorespacesandpars}
201 \def\ignorespacesandpars{\ifhmode\unskip\fi\ifnextchar\par{\expandafter\ignorespacesandpars\@g

```

`\@@symdef` now comes the real meat: the `\@@symdef` macro does two things, it adds the macro definition to the macro definition pool of the current module and also provides it.

```

202 \def\@@symdef[#1]#2[#3]#4{%

```

We use a switch to keep track of the local optional argument. We initialize the switch to false and set all the keys that have been provided as arguments: `name`, `local`.

¹¹EdNOTE: MK@MK: we need to document the binder keys above.

```

203 \symdeflocalfalse%
204 \metasetkeys{symdef}{#1}%

```

If the `mmt` option is set and we are not importing, then we write out the constant declaration for this `symdef`¹²

```

205 %\ifx\symdef@name\empty\mmtconstdec{#2}\else\mmtconstdec{\symdef@name}\fi%

```

First, using `\mod@newcommand` we initialize the intermediate macro `\module@sym@pres@`, the one that can be extended with `\symvariant`

```

206 \expandafter\mod@newcommand\csname modules@#2@pres@\endcsname[#3]{#4}%

```

and then we define the actual semantic macro, which when invoked with an optional argument *opt* calls `\modules@sym@pres@opt` provided by the `\symvariant` macro.

```

207 \expandafter\mod@newcommand\csname #2\endcsname[1] []%
208 {\csname modules@#2@pres@##1\endcsname}%

```

Finally, we prepare the internal macro to be used in the `\symref` call.

```

209 \expandafter\@mod@nc\csname mod@symref@#2\expandafter\endcsname\expandafter%
210 {\expandafter\mod@termref\expandafter{\mod@id}{#2}{##1}}%

```

We check if the switch for the local scope is set: if it is we are done, since this function has a local scope. Similarly, if we are not inside a module, which we could export from.

```

211 \ifsymdeflocal%
212 \else%
213 \ifcsundef{mod@id}{}%

```

Otherwise, we add three functions to the module's pool of defined macros using `\g@addto@macro`. We first add the definition of the intermediate function `\modules@sym@pres@`.

```

214 \expandafter\g@addto@macro\this@module%
215 {\expandafter\mod@newcommand\csname modules@#2@pres@\endcsname[#3]{#4}}%

```

Then we add the definition of `\<sym>` which calls the intermediate function and handles the optional argument.

```

216 \expandafter\g@addto@macro\this@module%
217 {\expandafter\mod@newcommand\csname #2\endcsname[1] []%
218 {\csname modules@#2@pres@##1\endcsname}}%

```

We also add `\mod@symref@sym` macro to the macro pool so that the `\symref` macro can pick it up.

```

219 \expandafter\g@addto@macro\csname module@defs@\mod@id\expandafter\endcsname\expandafter%
220 {\expandafter\@mod@nc\csname mod@symref@#2\expandafter\endcsname\expandafter%
221 {\expandafter\mod@termref\expandafter{\mod@id}{#2}{##1}}}%

```

Finally, using `\g@addto@macro` we add the two functions to the qualified version of the module if the `qualifiedimports` option was set.

```

222 \ifmod@qualified%

```

¹²EDNOTE: eventually we may want to do something about the notations. This would pass `#4` to MMT via a macro that makes the `#` (argumentmarkers) active and empty. I am not clear how well this works, so we leave out notations.

```

223     \expandafter\g@addto@macro\this@qualified@module%
224     {\expandafter\mod@newcommand\csname modules@#2@pres@qualified\endcsname[#3]{#4}}%
225     \expandafter\g@addto@macro\this@qualified@module%
226     {\expandafter\def\csname#2@qualified\endcsname{\csname modules@#2@pres@qualified\endcsname
227     \fi%
228     }% mod@qualified
229 \fi% symdeflocal

```

So now we only need to show the data in the symdef, if the options allow.

```

230 \ifmod@show%
231   \ifx\symdef@display\st@flow\else\noindent\stDMemph{\symdef@type} #2:\fi%
232   \ifx\symdef@title\empty~\else~(\stDMemph{\symdef@title})\par\fi%
233 \fi%
234 \ignorespacesandpars%
235 }% mod@show
236 \def\symdef@type{Symbol}%

```

`\symvariant` `\symvariant{<sym>}[<args>]{<var>}{<cseq>}` just extends the internal macro `\modules@<sym>@pres@` defined by `\symdef{<sym>}[<args>]{...}` with a variant `\modules@<sym>@pres@<var>` which expands to `<cseq>`. Recall that this is called by the macro `\<sym>[<var>]` induced by the `\symdef`.¹³

```

237 \def\symvariant#1{%
238   \@ifnextchar[{\@symvariant{#1}}{\@symvariant{#1}[0]}%
239 }%
240 \def\@symvariant#1[#2]#3#4{%
241   \expandafter\mod@newcommand\csname modules@#1@pres@#3\endcsname[#2]{#4}%
   and if we are in a named module, then we need to export the function
   \modules@<sym>@pres@<opt> just as we have done that in \symdef.
242   \ifcsundef{mod@id}{}%
243     \expandafter\g@addto@macro\this@module%
244     {\expandafter\mod@newcommand\csname modules@#1@pres@#3\endcsname[#2]{#4}}%
245   }%
246 \ignorespacesandpars}%

```

`\resymdef` This is now deprecated.

```

247 \def\resymdef{%
248   \@ifnextchar[{\@resymdef}{\@resymdef[]}%
249 }%
250 \def\@resymdef[#1]#2{%
251   \@ifnextchar[{\@@resymdef[#1]{#2}}{\@@resymdef[#1]{#2}[0]}%
252 }%
253 \def\@@resymdef[#1]#2[#3]#4{%
254   \PackageError{modules}%
255   {The \protect\resymdef macro is deprecated}{use the \protect\symvariant instead!}%
256 }%

```

`\abbrdef` The `\abbrdef` macro is a variant of `\symdef` that does the same on the L^AT_EX level.

¹³EDNOTE: MK@DG: this needs to be implemented in LaTeXML

```
257 \let\abbrdef\symdef%
```

4.4 Defining Math Operators

`\DefMathOp` `\DefMathOp[⟨key pair⟩]{definition}` will take 2 arguments. *⟨key pair⟩* should be something like `[name=...]`, for example, `[name=equal]`. Though `\setkeys`, `\defmathop@name` will be set. Further definition will be done by `\symdef`.

```
258 \define@key{DefMathOp}{name}{%
259   \def\defmathop@name{#1}%
260 }%
261 \newrobustcmd\DefMathOp[2] [] {%
262   \setkeys{DefMathOp}{#1}%
263   \symdef[#1]{\defmathop@name}{#2}%
264 }%
```

4.5 Axiomatic Assumptions

`\assdef` We fake it for now, not clear what we should do on the L^AT_EX side.

```
265 \newcommand\assdef[2] [] {#2}
```

4.6 Semantic Macros for Variables

`\vardef` From the L^AT_EX point of view `\vardef` is just an abbreviation

```
266 \let\vardef\abbrdef
```

4.7 Testing Semantic Macros

`\symtest` Allows to test a `\symdef` in place, this shuts up when being imported.

```
267 \addmetakey{symtest}{name}%
268 \addmetakey{symtest}{variant}%
269 \newrobustcmd\symtest[3] [] {%
270   \if@importing%
271   \else%
272     \metasetkeys{symtest}{#1}%
273     \par\noindent \textbf{Symbol}~%
274     \ifx\symtest@name\@empty\texttt{#2}\else\texttt{\symtest@name}\fi%
275     \ifx\symtest@variant\@empty\else\ (variant \texttt{\symtest@variant})\fi%
276     \ with semantic macro %
277     \texttt{\textbackslash #2\ifx\symtest@variant\@empty\else[\symtest@variant]\fi}%
278     : used e.g. in \ensuremath{#3}%
279   \fi%
280   \ignorespacesandpars%
281 }%
```

`\abbrtest`

```
282 \addmetakey{abbrtest}{name}%
283 \newrobustcmd\abbrtest[3] [] {%
284   \if@importing%
```



```

285 \else%
286 \metasetkeys{abbrtest}{#1}%
287 \par\noindent \textbf{Abbreviation}~%
288 \ifx\abbrtest@name\@empty\texttt{#2}\else\texttt{\abbrtest@name}\fi%
289 : used e.g. in \ensuremath{#3}%
290 \fi%
291 \ignorespacesandpars}%

```

4.8 Symbol and Concept Names

`\termdef`

```

292 \def\mod@true{true}%
293 \addmetakey[false]{termdef}{local}%
294 \addmetakey{termdef}{name}%
295 \newrobustcmd\termdef[3][]{%
296 \metasetkeys{termdef}{#1}%
297 \expandafter\mod@newcommand\csname#2\endcsname[0]{#3\space}%
298 \ifx\termdef@local\mod@true%
299 \else%
300 \ifcsundef{mod@id}{}%
301 \expandafter\g@addto@macro\this@module%
302 {\expandafter\mod@newcommand\csname#2\endcsname[0]{#3\space}}%
303 }%
304 \fi%
305 }%

```

`\capitalize`

```

306 \def\@capitalize#1{\uppercase{#1}}%
307 \newrobustcmd\capitalize[1]{\expandafter\@capitalize #1}%

```

`\module@component` This macro computes the module component identifier for external links on term references. It is initially empty, but can be redefined later (e.g. in the `smultiling` package).

```

308 \newcommand\mod@component[1]{}

```

`\mod@termref` `\mod@termref{<module>}{<name>}{<nl>}` determines whether the macro `\module@<module>@path` is defined. If it is, we make it the prefix of a URI reference in the local macro `\@uri`, which we compose to the hyper-reference, otherwise we give a warning.¹⁴

```

309 \newcommand\mod@termref[3]{\def\@test{#3}%
310 \@ifundefined{module@defs@#1}{%
311 \protect\G@refundefinedtrue%
312 \if@trwarn
313 \PackageWarning{modules}{‘\protect\termref’ with unidentified cd “#1”:\MessageBreak
314 the cd key must reference an active module}%
315 \else
316 \PackageError{modules}{‘\protect\termref’ with unidentified cd “#1”}
317 {the cd key must reference an active module}%

```

¹⁴EDNOTE: MK: this should be rethought, in particular the local reference does not work!

```

318   \fi}%
319   {\def\@label{sref@#2@#1\mod@component{#1}@target}%
320    \ifundefined{module@#1@path}% local reference
321    {\sref@hlink@ifh{\@label}{\ifx\@test\@empty #2\else #3\fi}%
322 %      \footnote{sTeX mod@termref: local reference to\@label}
323   }%
324   {\def\@uri{\csname module@#1@path\endcsname\mod@component{#1}.pdf\#\@label}%
325    \sref@href@ifh{\@uri}{\ifx\@test\@empty #2\else #3\fi}%
326 %      \footnote{sTeX mod@termref: external reference to \@uri}
327   }%
328   }}%

```

4.9 Loading Module Signatures

4.9.1 Selective Inclusion

`\requiremodules` this macro loads the modules in a file and makes sure that no text is deposited (we set the flags `\mod@showfalse` and `\@importingtrue` in the local group). It also remembers the file name and extension in `\mod@path` and `\mod@ext` so that `\begin{module}` can pick them up later.

```

329 \newrobustcmd\requiremodules[2]{%
330   \mod@showfalse%
331   \@importingtrue% save state and ensure silence while reading sms
332   \edef\mod@path{#1}%
333   \edef\mod@ext{#2}% set up path/ext
334   \input{#1.#2}%
335 }%

```

`\@requiremodules` the internal version of `\requiremodules` for use in the `*.aux` file. We disable it at the end of the document, so that when the aux file is read again, nothing is loaded.

```

336 \newrobustcmd\@requiremodules[2]{%
337   \if@tempswa\requiremodules{#1}{#2}\fi%
338 }%

```

`\inputref@*skip` hooks for spacing customization, they are empty by default.

```

339 \def\inputref@preskip{}
340 \def\inputref@postskip{}

```

`\inputref` `\inputref{<path to the current file without extension>}` supports both absolute path and relative path, meanwhile, records the path and the extension (not for relative path).

```

341 \newrobustcmd\inputref[1]{%
342   \def\@Slash{/}%
343   \edef\@load{#1}%
344   \StrChar{\@load}{1}[\@testchar]
345   \inputref@preskip%
346   \ifx\@testchar\@Slash%
347     \edef\mod@path{#1}%

```

```

348 \edef\mod@ext{tex}%
349 \input{#1}%
350 \else%
351 \cpath{#1}\input{\@CanPath.tex}%
352 \fi%
353 \inputref@postskip%
354 }%

```

4.10 Including Externally Defined Semantic Macros

`\requirepackage`

```

355 \def\requirepackage#1#2{\makeatletter\input{#1.sty}\makeatother}%

```

4.11 Namespaces and Alignments

`\namespace`

```

356 \newcommand\namespace[2][\ignorespacesandpars]

```

4.12 Deprecated Functionality

`\sinput*`

```

357 \newrobustcmd\sinput[1]{%
358 \PackageError{modules}%
359 {The ‘\protect\sinput’ macro is deprecated}{use the \protect\input instead!}%
360 }%
361 \newrobustcmd\sinputref[1]{%
362 \PackageError{modules}%
363 {The \protect\sinputref macro is deprecated}{use the \protect\inputref instead!}%
364 }%

```

In this section we centralize old interfaces that are only partially supported any more.

`module:uses` For each the module name `xxx` specified in the `uses` key, we activate their symdefs and we export the local symdefs.¹⁵

```

365 \define@key{module}{uses}{%
366 \@for\module@tmp:=#1\do{\activate@defs\module@tmp\export@defs\module@tmp}%
367 }%

```

`module:usesqualified` This option operates similarly to the `module:uses` option defined above. The only difference is that here we import modules with a prefix. This is useful when two modules provide a macro with the same name.

```

368 \define@key{module}{usesqualified}{%
369 \@for\module@tmp:=#1\do{\activate@defs{qualified@\module@tmp}\export@defs\module@tmp}%
370 }%

```

¹⁵EDNOTE: this issue is deprecated, it will be removed before 1.0.

`\coolurion/off`

```
371 \def\coolurion{\PackageWarning{modules}{coolurion is obsolete, please remove}}%
372 \def\coolurioff{\PackageWarning{modules}{coolurioff is obsolete, please remove}}%
```

4.13 Experiments

In this section we develop experimental functionality. Currently support for complex expressions, see https://svn.kwarc.info/repos/stex/doc/blue/comlex_semmacros/note.pdf for details.

`\csymdef` For the L^AT_EX we use `\symdef` and forget the last argument. The code here is just needed for parsing the (non-standard) argument structure.

```
373 \def\csymdef{\@ifnextchar[{\@csymdef}{\@csymdef[]}}%
374 \def\@csymdef[#1]#2{%
375   \@ifnextchar[{\@csymdef[#1]{#2}}{\@csymdef[#1]{#2}[0]}%
376 }%
377 \def\@csymdef[#1]#2[#3]#4#5{%
378   \@csymdef[#1]{#2}[#3]{#4}%
379 }%
```

`\notationdef` For the L^AT_EX side, we just make `\notationdef` invisible.

```
380 \def\notationdef[#1]#2#3{}
```

The code for avoiding duplicate loading is very very complex and brittle (and does not quite work). Therefore I would like to replace it with something better. It has two parts:

- keeping a registry of file paths, and only loading when the file path has not been mentioned in that, and
- dealing with relative paths (for that we have to string together prefixes and pass them one)

For the first problem, there is a very nice and efficient solution using `etoolbox` which I document below. If I decide to do away with relative paths, this would be it.

`\reqmodules` We keep a file path registry `\@register` and only load a module signature, if it is not in there.

```
381 \newrobustcmd\reqmodules[2]{%
382   \ifinlist{#1}{\@register}{\listadd\@register{#1}\input{#1.#2}}%
383 }%
```

for the relative paths, I have to find out the directory prefix and the file name. Here are two helper functions, which work well, but do not survive being called in an `\edef`, which is what we would need. First some preparation: we set up a path parser

```
384 \newcounter{@pl}
385 \DeclareListParser*\forpathlist{/}
```

`\file@name` `\file@name` selects the filename of the file path: `\file@name{/foo/bar/baz.tex}` is `baz.tex`.

```

386 \def\file@name#1{%
387   \setcounter{@pl}{0}%
388   \forpathlist{\stepcounter{@pl}\listadd{@pathlist}{#1}
389   \def\do##1{%
390     \ifnumequal{\value{@pl}}{1}{##1}{\addtocounter{@pl}{-1}}
391   }%
392   \dolistloop{@pathlist}%
393 }%
```

`\file@path` `\file@path` selects the path of the file path `\file@path{/foo/bar/baz.tex}` is `/foo/bar`

```

394 \def\file@path#1{%
395   \setcounter{@pl}{0}%
396   \forpathlist{\stepcounter{@pl}\listadd{@pathlist}{#1}%
397   \def\do##1{%
398     \ifnumequal{\value{@pl}}{1}{\%
399       \addtocounter{@pl}{-1}%
400       \ifnumequal{\value{@pl}}{1}{##1}{##1/}%
401     }%
402   }%
403   \dolistloop{@pathlist}%
404 }%
405 \endpackage
```

what I would really like to do in this situation is

`\NEWrequiremodules` but this does not work, since the `\file@name` and `\file@path` do not survive the `\edef`.

```

406 \def\@NEWcurrentprefix{}
407 \def\NEWrequiremodules#1{%
408   \def\@pref{\file@path{#1}}%
409   \ifx\@pref\@empty%
410   \else%
411     \xdef\@NEWcurrentprefix{\@NEWcurrentprefix/\@pref}%
412   \fi%
413   \edef\@input@me{\@NEWcurrentprefix/\file@name{#1}}%
414   \message{requiring \@input@me}\reqmodule{\@input@me}%
415 }%
```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

L ^A T _E X ^M L,	3,	10,	module,				8	semantic			
	11,	15,	20								
			OMDoc,	3,	7,	10,	11	inheritance			
MATHML,	3,	4,	6,	7	OPENMATH,	3,	4,	6,	7	relation,	8
module											
name,				8	relation						
				inheritance			(se-				
name				mantic),			8	XML,			7

Change History

v0.9	adding optional arguments to semantic macros for display variants. The resymdef functionality introduced in 0.9g is now deprecated. It was hardly used.	1
General: First Version with Documentation		1
v0.9a	exporting requiremodules to the aux file, so that they are preloaded (pre-required) so semantic macros in section titles can work.	1
General: Completed Documentation		1
v0.9b	Moving LaTeXML bindings into modules.sty.ltxml and disabling generation	1
General: Complete functionality and Updated Documentation . .		1
v0.9c		
General: more packaging		1
v0.9d		
General: fixing double loading of .tex and .sms		1
v0.9e	v1.2	
General: fixing LaTeXML	General: No longer loading the aux file at the end of the document	1
v0.9f	v1.3	
General: remove unused options uses and usesqualified	General: adding MathHub support	1
v0.9g	v1.4	
General: adding importOMDocmodule	General: Completely revamped importing modules this is much faster now, but can no longer do relative paths.	1
adding resymdef functionality . .	deprecated \sinput and \sinputref	1
v0.9h	v1.5	
General: adding \metallanguage . .	General: “unidentified cd” in termref is now an error.	1
using \mod@newcommand instead of \providecommand for more intuitive inheritance.	adding dir attribute to import/usemodule	1
v1.0	Moved MH Versions to a separate mathhub package	1
General: minor fixes		1
v1.1		
General: adding additional keys for the \symdef macro and exporting them to OMDoc . . .		1

References

- [Aus+10] Ron Ausbrooks et al. *Mathematical Markup Language (MathML) Version 3.0*. Tech. rep. World Wide Web Consortium (W3C), 2010. URL: <http://www.w3.org/TR/MathML3>.
- [Bus+04] Stephen Buswell et al. *The Open Math Standard, Version 2.0*. Tech. rep. The OpenMath Society, 2004. URL: <http://www.openmath.org/standard/om20>.
- [Koh06] Michael Kohlhase. *OMDoc – An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh08] Michael Kohlhase. “Using L^AT_EX as a Semantic Markup Format”. In: *Mathematics in Computer Science 2.2* (2008), pp. 279–304. URL: <https://kwarc.info/kohlhase/papers/mcs08-stex.pdf>.
- [Koh18a] Michael Kohlhase. *MathHub Support for sT_EX*. Tech. rep. 2018. URL: <https://github.com/sLaTeX/sTeX/raw/master/sty/mathhub/mathhub.pdf>.
- [Koh18b] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in L^AT_EX*. Tech. rep. 2018. URL: <https://github.com/sLaTeX/sTeX/raw/master/sty/metakeys/metakeys.pdf>.
- [Koh18c] Michael Kohlhase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. 2018. URL: <https://github.com/sLaTeX/sTeX/raw/master/sty/statements/statements.pdf>.
- [LTX] Bruce Miller. *LaTeXML: A L^AT_EX to XML Converter*. URL: <http://dlmf.nist.gov/LaTeXML/> (visited on 03/12/2013).
- [MNS] *Documents and Namespaces*. URL: <https://uniformal.github.io/doc/language/namespaces> (visited on 11/23/2019).
- [RK13] Florian Rabe and Michael Kohlhase. “A Scalable Module System”. In: *Information & Computation* 0.230 (2013), pp. 1–54. URL: <http://kwarc.info/frabe/Research/mmt.pdf>.
- [RO] Sebastian Rahtz and Heiko Oberdiek. *Hypertext marks in L^AT_EX: a manual for hyperref*. URL: <http://tug.org/applications/hyperref/ftp/doc/manual.pdf> (visited on 01/28/2010).
- [sTeX] *sTeX: A semantic Extension of TeX/LaTeX*. URL: <https://github.com/sLaTeX/sTeX> (visited on 05/15/2015).