

`omdoc.sty/cls`: Semantic Markup for Open Mathematical Documents in \LaTeX

Michael Kohlhase
FAU Erlangen-Nürnberg
<http://kwarc.info/kohlhase>

December 4, 2018

Abstract

The `omdoc` package is part of the \LaTeX collection, a version of $\text{\TeX}/\text{\LaTeX}$ that allows to markup $\text{\TeX}/\text{\LaTeX}$ documents semantically without leaving the document format, essentially turning $\text{\TeX}/\text{\LaTeX}$ into a document format for mathematical knowledge management (MKM).

This package supplies an infrastructure for writing OMDoc documents in \LaTeX . This includes a simple structure sharing mechanism for \LaTeX that allows to move from a copy-and-paste document development model to a copy-and-reference model, which conserves space and simplifies document management. The augmented structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package and Class Options	3
2.2	Document Structure	3
2.3	Ignoring Inputs	5
2.4	Structure Sharing	5
2.5	Global Variables	6
2.6	Colors	6
3	Limitations	6
4	Implementation: The OMDoc Class	7
4.1	Class Options	7
4.2	Beefing up the <code>document</code> environment	7
5	Implementation: OMDoc Package	8
5.1	Package Options	8
5.2	Document Structure	8
5.3	Front and Backmatter	11
5.4	Ignoring Inputs	12
5.5	Structure Sharing	12
5.6	Global Variables	13
5.7	Colors	13

1 Introduction

$\mathcal{S}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ is a version of $\mathrm{T}_{\mathrm{E}}\mathrm{X}/\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ that allows to markup $\mathrm{T}_{\mathrm{E}}\mathrm{X}/\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ documents semantically without leaving the document format, essentially turning $\mathrm{T}_{\mathrm{E}}\mathrm{X}/\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ into a document format for mathematical knowledge management (MKM). The package supports direct translation to the OMDoc format [Koh06]

The `omdoc` package supplies macros and environment that allow to label document fragments and to reference them later in the same document or in other documents. In essence, this enhances the document-as-trees model to documents-as-directed-acyclic-graphs (DAG) model. This structure can be used by MKM systems for added-value services, either directly from the $\mathcal{S}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ sources, or after translation. Currently, trans-document referencing provided by this package can only be used in the $\mathcal{S}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ collection.

DAG models of documents allow to replace the “Copy and Paste” in the source document with a label-and-reference model where document are shared in the document source and the formatter does the copying during document formatting/presentation.¹

2 The User Interface

The `omdoc` package generates two files: `omdoc.cls`, and `omdoc.sty`. The OMDoc class is a minimally changed variant of the standard `article` class that includes the functionality provided by `omdoc.sty`. The rest of the documentation pertains to the functionality introduced by `omdoc.sty`.

2.1 Package and Class Options

The `omdoc` class accept the following options:

<code>class=<name></code>	load <code><name>.cls</code> instead of <code>article.cls</code>
<code>topsect=<number></code>	The top-level sectioning level; the default is <code>section</code>
<code>showignores</code>	show the the contents of the <code>ignore</code> environment after all
<code>showmeta</code>	show the metadata; see <code>metakeys.sty</code>
<code>showmods</code>	show modules; see <code>modules.sty</code>
<code>extrefs</code>	allow external references; see <code>sref.sty</code>
<code>defindex</code>	index definienda; see <code>statements.sty</code>
<code>mh</code>	MathHub support; see <code>[Kohlhase:mss:ctan]</code>

The `omdoc` package accepts the same except the first two.

2.2 Document Structure

`document` The top-level `document` environment can be given key/value information by the `\documentkeys` macro in the preamble¹. This can be used to give metadata about

¹EdNOTE: integrate with latexml’s XMRref in the Math mode.

id the document. For the moment only the **id** key is used to give an identifier to the **omdoc** element resulting from the \LaTeX XML transformation.

omgroup The structure of the document is given by the **omgroup** environment just like in OMDoc. In the \LaTeX route, the **omgroup** environment is flexibly mapped to sectioning commands, inducing the proper sectioning level from the nesting of **omgroup** environments. Correspondingly, the **omgroup** environment takes an optional key/value argument for metadata followed by a regular argument for the (section) title of the **omgroup**. The optional metadata argument has the keys **id** for an identifier, **creators** and **contributors** for the Dublin Core metadata [DCM03]; see [Koh16a] for details of the format. The **short** allows to give a short title for the generated section. If the title contains semantic macros, they need to be protected by \protect , and we need to give the **loadmodules** key it needs no value. For instance we would have

```
\begin{module}{foo}
\symdef{bar}{B^a_r}
...
\begin{omgroup}[id=barderv,loadmodules]
{Introducing  $\text{\protect}\bar{\$}$  Derivations}
```

\TeX automatically computes the sectioning level, from the nesting of **omgroup** environments. But sometimes, we want to skip levels (e.g. to use a subsection* as an introduction for a chapter). Therefore the **omdoc** package provides a variant **blindomgroup** that does not produce markup, but increments the sectioning level and logically groups document parts that belong together, but where traditional document markup relies on convention rather than explicit markup. The **blindomgroup** environment is useful e.g. for creating frontmatter at the correct level. Example 1 shows a typical setup for the outer document structure of a book with parts and chapters. We use two levels of **blindomgroup**:

- The outer one groups the introductory parts of the book (which we assume to have a sectioning hierarchy topping at the part level). This **blindomgroup** makes sure that the introductory remarks become a “chapter” instead of a “part”.
- The inner one groups the frontmatter² and makes the preface of the book a section-level construct. Note that here the **display=flow** on the **omgroup** environment prevents numbering as is traditional for prefaces.

\currentsectionlevel The **\currentsectionlevel** macro supplies the name of the current sectioning level, e.g. “chapter”, or “subsection”. **\CurrentSectionLevel** is the capitalized variant. They are useful to write something like “In this **\currentsectionlevel**, we will...” in an **omgroup** environment, where we do not know which sectioning level we will end up.

¹We cannot patch the document environment to accept an optional argument, since other packages we load already do; pity.

²We shied away from redefining the **frontmatter** to induce a **blindomgroup**, but this may be the “right” way to go in the future.

```

\begin{document}
\begin{blindomgroup}
\begin{blindomgroup}
\begin{frontmatter}
\maketitle\newpage
\begin{omgroup}[display=flow]{Preface}
... <<preface>> ...
\end{omgroup}
\clearpage\setcounter{tocdepth}{4}\tableofcontents\clearpage
\end{frontmatter}
\end{blindomgroup}
... <<introductory remarks>> ...
\end{blindomgroup}
\begin{omgroup}{Introduction}
... <<intro>> ...
\end{omgroup}
... <<more chapters>> ...
\bibliographystyle{alpha}\bibliography{kwarc}
\end{document}

```

Example 1: A typical Document Structure of a Book

2.3 Ignoring Inputs

ignore The `ignore` environment can be used for hiding text parts from the document structure. The body of the environment is not PDF or DVI output unless the `showignores` option is given to the `omdoc` class or `package`. But in the generated OMDoc result, the body is marked up with a `ignore` element. This is useful in two situations. For

editing One may want to hide unfinished or obsolete parts of a document

narrative/content markup In \LaTeX we mark up narrative-structured documents. In the generated OMDoc documents we want to be able to cache content objects that are not directly visible. For instance in the `statements` package [Koh16c] we use the `\inlinedef` macro to mark up phrase-level definitions, which verbalize more formal definitions. The latter can be hidden by an `ignore` and referenced by the `verbalizes` key in `\inlinedef`.

2.4 Structure Sharing

\STRlabel The `\STRlabel` macro takes two arguments: a label and the content and stores the content for later use by `\STRcopy[⟨URL⟩]{⟨label⟩}`, which expands to the previously stored content. If the `\STRlabel` macro was in a different file, then we can give a URL `⟨URL⟩` that lets \LaTeX ML generate the correct reference.

\STRcopy

\STRsemantics The `\STRlabel` macro has a variant `\STRsemantics`, where the label argument is optional, and which takes a third argument, which is ignored in \LaTeX . This allows to specify the meaning of the content (whatever that may mean) in cases,

where the source document is not formatted for presentation, but is transformed into some content markup format.²

2.5 Global Variables

Text fragments and modules can be made more re-usable by the use of global variables. For instance, the admin section of a course can be made course-independent (and therefore re-usable) by using variables (actually token registers) `courseAcronym` and `courseTitle` instead of the text itself. The variables can then be set in the \LaTeX preamble of the course notes file. `\setSGvar{<vname>}{<text>}` to set the global variable `<vname>` to `<text>` and `\useSGvar{<vname>}` to reference it.

`\ifSGvar` With `\ifSGvar` we can test for the contents of a global variable: the macro call `\ifSGvar{<vname>}{<val>}{<ctext>}` tests the content of the global variable `<vname>`, only if (after expansion) it is equal to `<val>`, the conditional text `<ctext>` is formatted.

2.6 Colors

For convenience, the `omdoc` package defines a couple of color macros for the `color` package: For instance `\blue` abbreviates `\textcolor{blue}`, so that `\blue{<something>}` writes `<something>` in blue. The macros `\red`, `\green`, `\cyan`, `\magenta`, `\brown`, `\yellow`, `\orange`, `\gray`, and finally `\black` are analogous.

3 Limitations

In this section we document known limitations. If you want to help alleviate them, please feel free to contact the package author. Some of them are currently discussed in the \LaTeX GitHub repository [sTeX].

1. when option `book` which uses `\pagestyle{headings}` is given and semantic macros are given in the `omgroup` titles, then they sometimes are not defined by the time the heading is formatted. Need to look into how the headings are made.

²EdNOTE: document LMID und LMXREF here if we decide to keep them.

4 Implementation: The OMDoc Class

The functionality is spread over the `omdoc` class and package. The class provides the `document` environment and the `omdoc` element corresponds to it, whereas the package provides the concrete functionality.

4.1 Class Options

To initialize the `omdoc` class, we declare and process the necessary options using the `kvoptions` package for key/value options handling. For `omdoc.cls` this is quite simple. We have options `report` and `book`, which set the `\omdoc@cls@class` macro and pass on the macro to `omdoc.sty` for further processing.

`\omdoc@cls@class`

```
1 \*cls
2 \RequirePackage{kvoptions}
3 \SetupKeyvalOptions{family=omdoc@cls,prefix=omdoc@cls@}
4 \DeclareStringOption[article]{class}
5 \RequirePackage{etoolbox}
```

the following options are deprecated.

```
6 \DeclareVoidOption{report}{\def\omdoc@cls@class{report}}%
7 \ClassWarning{omdoc}{the option 'report' is deprecated, use 'class=report', instead}}
8 \DeclareVoidOption{book}{\def\omdoc@cls@class{book}}%
9 \ClassWarning{omdoc}{the option 'bookpart' is deprecated, use 'class=book', instead}}
10 \DeclareVoidOption{bookpart}{\def\omdoc@cls@class{book}}%
11 \PassOptionToPackage{topsect=chapter}{omdoc}%
12 \ClassWarning{omdoc}{the option 'bookpart' is deprecated, use 'class=book,topsect=chapter', ins
```

the rest of the options are only passed on to `omdoc.sty` and the class selected by the first options.

```
13 \def\@omdoc@cls@docopt{}
14 \DeclareDefaultOption{%
15 \ifx\@omdoc@cls@docopt\@empty%
16 \xdef\@omdoc@cls@docopt{\CurrentOption}%
17 \else\xappto\@omdoc@cls@docopt{,\CurrentOption}%
18 \fi}%
19 \PassOptionsToPackage{\CurrentOption}{omdoc}
20 \PassOptionsToPackage{\CurrentOption}{stex}
21 \ProcessKeyvalOptions{omdoc@cls}
```

We load `article.cls`, and the desired packages. For the L^AT_EXML bindings, we make sure the right packages are loaded.

```
22 \LoadClass[\@omdoc@cls@docopt]{\omdoc@cls@class}
23 \RequirePackage{omdoc}
24 \RequirePackage{stex}
```

4.2 Beefing up the document environment

Now, we will define the environments we need. The top-level one is the `document` environment, which we redefined so that we can provide keyval arguments.

`document` For the moment we do not use them on the \LaTeX level, but the document identifier is picked up by \LaTeX XML.³

```

25 \srefaddidkey{document}
26 \newcommand\documentkeys[1]{\metasetkeys{document}{#1}}
27 \let\orig@document=\document
28 \srefaddidkey{document}
29 \renewcommand{\document}[1][\metasetkeys{document}{#1}\orig@document}
30 \</cls>

```

5 Implementation: OMDoc Package

5.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false).

```

31 <*package>
32 \RequirePackage{kvoptions}
33 \SetupKeyvalOptions{family=omdoc@sty,prefix=omdoc@sty@}
34 \DeclareBoolOption{mh}
35 \DeclareBoolOption{showignores}
36 \DeclareStringOption[section]{topsect}
37 \newcount\section@level
38 \DeclareDefaultOption{\PassOptionsToPackage{\CurrentOption}{sref}}
39 \ProcessKeyvalOptions{omdoc@sty}

```

Then we need to set up the packages by requiring the `sref` package to be loaded.

```

40 \ifomdoc@sty@mh\RequirePackage{omdoc-mh}\fi
41 \RequirePackage{etoolbox}
42 \RequirePackage{sref}
43 \RequirePackage{xspace}
44 \RequirePackage{comment}
45 \RequirePackage{pathsuris}

```

`\section@level` Finally, we set the `\section@level` macro that governs sectioning.

```

46 \section@level=2
47 \ifdefstring{\omdoc@sty@topsect}{part}{\section@level=0}{ }
48 \ifdefstring{\omdoc@sty@topsect}{chapter}{\section@level=1}{ }
49 \ifdefstring{\omdoc@cls@class}{book}{\section@level=0}{ }
50 \ifdefstring{\omdoc@cls@class}{report}{\section@level=0}{ }

```

5.2 Document Structure

The structure of the document is given by the `omgroup` environment just like in OMDoc. The hierarchy is adjusted automatically according to the \LaTeX class in effect.

³EdNOTE: faking `documentkeys` for now. @HANG, please implement

`\currentsectionlevel` For the `\currentsectionlevel` and `\Currentsectionlevel` macros we use an internal macro `\current@section@level` that only contains the keyword (no markup). We initialize it with “document” as a default. In the generated OMDoc, we only generate a text element of class `omdoc_currentsectionlevel`, which will be instantiated by CSS later.⁴

```

51 \def\current@section@level{document}%
52 \newcommand\currentsectionlevel{\lowercase\expandafter{\current@section@level}\xspace}%
53 \newcommand\Currentsectionlevel{\expandafter\MakeUppercase\current@section@level\xspace}%

blindomgroup
54 \newcommand\at@begin@blindomgroup[1]{%
55 \newenvironment{blindomgroup}
56 {\advance\section@level by 1\at@begin@blindomgroup\section@level}
57 {\advance\section@level by -1}

\omgroup@nonum convenience macro: \omgroup@nonum{<level>}{<title>} makes an unnumbered sectioning with title <title> at level <level>.
58 \newcommand\omgroup@nonum[2]{%
59 \ifx\hyper@anchor\@undefined\else\phantomsection\fi%
60 \addcontentsline{toc}{#1}{#2}\@nameuse{#1}*{#2}}

\omgroup@num convenience macro: \omgroup@num{<level>}{<title>} makes numbered sectioning with title <title> at level <level>. We have to check the short key was given in the omgroup environment and – if it is use it. But how to do that depends on whether the rdfmata package has been loaded. In the end we call \sref@label@id to enable crossreferencing.
61 \newcommand\omgroup@num[2]{%
62 \edef\@ID{\sref@id}
63 \ifx\omgroup@short\@empty% no short title
64 \@nameuse{#1}{#2}%
65 \else% we have a short title
66 \@ifundefined{rdfmata@sectioning}%
67 {\@nameuse{#1}[\omgroup@short]{#2}}%
68 {\@nameuse{rdfmata@#1@old}[\omgroup@short]{#2}}%
69 \fi%
70 \sref@label@id@arg{\omdoc@sect@name~\@nameuse{the#1}}\@ID}

omgroup
71 \def\@true{true}
72 \def\@false{false}
73 \srefaddidkey{omgroup}
74 \addmetakey{omgroup}{date}
75 \addmetakey{omgroup}{creators}
76 \addmetakey{omgroup}{contributors}
77 \addmetakey{omgroup}{srccite}
78 \addmetakey{omgroup}{type}

```

⁴EdNOTE: MK: we may have to experiment with the more powerful uppercasing macro from `mfirstuc.sty` once we internationalize.

```

79 \addmetakey*{omgroup}{short}
80 \addmetakey*{omgroup}{display}
81 \addmetakey[false]{omgroup}{loadmodules}[true]

\at@begin@omgroup we define a switch for numbering lines and a hook for the beginning of groups:
The \at@begin@omgroup macro allows customization. It is run at the beginning
of the omgroup, i.e. after the section heading.

82 \newif\if@num\@numtrue
83 \newif\if@frontmatter\@frontmatterfalse
84 \newif\if@backmatter\@backmatterfalse
85 \newcommand\at@begin@omgroup[3] [] {}

```

Then we define a helper macro that takes care of the sectioning magic. It comes with its own key/value interface for customization.

```

86 \addmetakey{omdoc@sect}{name}
87 \addmetakey[false]{omdoc@sect}{clear}[true]
88 \addmetakey{omdoc@sect}{ref}
89 \addmetakey[false]{omdoc@sect}{num}[true]
90 \newcommand\omdoc@sectioning[3] [] {\metasetkeys{omdoc@sect}{#1}%
91 \ifx\omdoc@sect@clear\@true\cleardoublepage\fi%
92 \if@num% numbering not overridden by frontmatter, etc.
93 \ifx\omdoc@sect@num\@true\omgroup@num{#2}{#3}\else\omgroup@nonum{#2}{#3}\fi%
94 \def\current@section@level{\omdoc@sect@name}%
95 \else\omgroup@nonum{#2}{#3}%
96 \fi}% if@num

```

and another one, if redefines the `\addtocontentsline` macro of L^AT_EX to import the respective macros. It takes as an argument a list of module names.⁵

```

97 \newcommand\omgroup@redefine@addtocontents[1]{%
98 \edef\@import{#1}%
99 \@for\@I:=\@import\do{%
100 \edef\@path{\csname module@\@I @path\endcsname}%
101 \@ifundefined{tf@toc}\relax%
102 {\protected@write\tf@toc}{\string\@requiremodules{\@path}{sms}}}%
103 \ifx\hyper@anchor\@undefined% hyperref.sty loaded?
104 \def\addcontentsline##1##2##3{%
105 \addtocontents{##1}{\protect\contentsline{##2}{\string\withusedmodules{##1}{##3}}{\thepage}}%
106 \else% hyperref.sty not loaded
107 \def\addcontentsline##1##2##3{%
108 \addtocontents{##1}{\protect\contentsline{##2}{\string\withusedmodules{##1}{##3}}{\thepage}}{\@cu
109 \fi}% hyperref.sty loaded?

```

now the `omgroup` environment itself. This takes care of the table of contents via the helper macro above and then selects the appropriate sectioning command from `article.cls`.

```

110 \newenvironment{omgroup}[2] []% keys, title
111 {\metasetkeys{omgroup}{#1}\sref@target%
112 \ifx\omgroup@display\st@flow\@numfalse\fi

```

⁵EdNOTE: MK: the extension `sms` is hard-coded here, but should not be. This will not work in multilingual settings.

```

113 \if@frontmatter\@numfalse\fi

If the loadmodules key is set on \begin{omgroup}, we redefine the \addcontetsline
macro that determines how the sectioning commands below construct the entries
for the table of contents.

114 \ifx\omgroup@loadmodules\@true%
115 \omgroup@redefine@addtocontents{\@ifundefined{mod@id}\used@modules%
116 {\@ifundefined{module@mod@id @path}\used@modules\mod@id}}\fi%

now we only need to construct the right sectioning depending on the value of
\section@level.

117 \advance\section@level by 1\relax%
118 \ifcase\section@level%
119 \or\omdoc@sectioning[name=Part,clear,num]{part}{#2}%
120 \or\omdoc@sectioning[name=Chapter,clear,num]{chapter}{#2}%
121 \or\omdoc@sectioning[name=Section,num]{section}{#2}%
122 \or\omdoc@sectioning[name=Subsection,num]{subsection}{#2}%
123 \or\omdoc@sectioning[name=Subsubsection,num]{subsubsection}{#2}%
124 \or\omdoc@sectioning[name=Paragraph,ref=this paragraph]{paragraph}{#2}%
125 \or\omdoc@sectioning[name=Subparagraph,ref=this subparagraph]{subparagraph}{#2}%
126 \fi% \ifcase
127 \at@begin@omgroup[#1]\section@level{#2}}% for customization
128 {\advance\section@level by -1}

```

5.3 Front and Backmatter

Index markup is provided by the `omtext` package [Koh16b], so in the `omdoc` package we only need to supply the corresponding `\printindex` command, if it is not already defined

```

\printindex

129 \providecommand\printindex{\IfFileExists{\jobname.ind}{\input{\jobname.ind}}{}}
130 \</package>

```

frontmatter some classes (e.g. `book.cls`) already have `\frontmatter` and `\mainmatter` macros. We use those (possibly defining them).

```

131 <{*cls}
132 \ifcsdef{frontmatter}% to redefine if necessary
133 {\cslet{orig@frontmatter}\frontmatter}\cslet{frontmatter}{\relax}}
134 {\cslet{orig@frontmatter}\clearpage\@mainmatterfalse\pagenumbering{roman}}}
135 \newenvironment{frontmatter}
136 {\@frontmattertrue\orig@mainmatter}
137 {\@frontmatterfalse%
138 \ifcsdef{mainmatter}{\mainmatter}%
139 {\clearpage\@mainmattertrue\pagenumbering{arabic}}}}

```

backmatter some classes (e.g. `book.cls`) already have a `\backmatter` macro. We use that (possibly defining it).

```

140 \ifcsdef{backmatter}% to redefine if necessary

```

```

141 {\cslet{orig@backmatter}{\backmatter}\cslet{backmatter}{\relax}}
142 {\cslet{orig@backmatter}{\clearpage\@mainmatterfalse\pagenumbering{roman}}}}
143 \newenvironment{backmatter}{\orig@backmatter\backmattertrue}{\@backmatterfalse}
144 </cls>

```

5.4 Ignoring Inputs

ignore

```

145 <*package>
146 \ifomdoc@sty@showignores
147 \addmetakey{ignore}{type}
148 \addmetakey{ignore}{comment}
149 \newenvironment{ignore}[1]{}
150 {\metasetkeys{ignore}{#1}\textless\ignore@type\textgreater\bgroup\itshape}
151 {\egroup\textless/\ignore@type\textgreater}
152 \renewenvironment{ignore}{}{\else\excludacomment{ignore}\fi}

```

5.5 Structure Sharing

6

```

153 \providecommand{\lxDocumentID}[1]{}%
154 \def\LXMID#1#2{\expandafter\gdef\csname xmarg#1\endcsname{#2}\csname xmarg#1\endcsname}
155 \def\LXMRef#1{\csname xmarg#1\endcsname}

```

\STRlabel The main macro, it is used to attach a label to some text expansion. Later on, using the **\STRcopy** macro, the author can use this label to get the expansion originally assigned.

```

156 \long\def\STRlabel#1#2{\STRlabeldef{#1}{#2}{#2}}

```

\STRcopy The **\STRcopy** macro is used to call the expansion of a given label. In case the label is not defined it will issue a warning.⁷

```

157 \newcommand\STRcopy[2]{}{\expandafter\ifx\csname STR@#2\endcsname\relax
158 \message{STR warning: reference #2 undefined!}
159 \else\csname STR@#2\endcsname\fi}

```

\STRsemantics if we have a presentation form and a semantic form, then we can use

```

160 \newcommand\STRsemantics[3]{}{\#2\def\@test{#1}\ifx\@test\@empty\STRlabeldef{#1}{#2}\fi}

```

\STRlabeldef This is the macro that does the actual labeling. Is it called inside **\STRlabel**

```

161 \def\STRlabeldef#1{\expandafter\gdef\csname STR@#1\endcsname}

```

⁶EDNOTE: The following is simply copied over from the latexml package, which we eliminated, we should integrate better.

⁷EDNOTE: MK: we need to do something about the ref!

5.6 Global Variables

`\setSGvar` set a global variable
162 `\newcommand\setSGvar[1]{\@namedef{sTeX@Gvar@#1}}`

`\useSGvar` use a global variable
163 `\newcommand\useSGvar[1]{\@nameuse{sTeX@Gvar@#1}}`

`\ifSGvar` set a global variable
164 `\newcommand\ifSGvar[3]{\def\@test{#2}\expandafter\ifx\csname sTeX@Gvar@#1\endcsname\@test #3\fi}`

5.7 Colors

blue, red, green, magenta We will use the following abbreviations for colors from `color.sty`

```
165 \def\black#1{\textcolor{black}{#1}}
166 \def\gray#1{\textcolor{gray}{#1}}
167 \def\blue#1{\textcolor{blue}{#1}}
168 \def\red#1{\textcolor{red}{#1}}
169 \def\green#1{\textcolor{green}{#1}}
170 \def\cyan#1{\textcolor{cyan}{#1}}
171 \def\magenta#1{\textcolor{magenta}{#1}}
172 \def\brown#1{\textcolor{brown}{#1}}
173 \def\yellow#1{\textcolor{yellow}{#1}}
174 \def\orange#1{\textcolor{orange}{#1}}
175 \</package>
```

Change History

v0.1		v1.0	
General: First Version	1	General: separated out <code>omtext.dtx</code>	1
v0.2		v1.1	
General: added OMDoc class	1	General: integrated <code>etoolbox</code>	
v0.3		package	1
General: moved <code>omtext</code> and friends		v1.2	
here from the statements		General: front/backmatter	1
package	1	v1.3	
v0.4		General: changed to <code>keyval</code>	
General: added quotes	1	class/package options, allowed	
v0.5		arbitrary classes	1
General: more package/class		global variables and switches . .	1
options	1	removing <code>keyval</code> arg from	
v0.7		document in favor of	
General: giving <code>keyval</code> arguments		<code>\documentkeys</code> macro	1
to the document environment .	1		

References

- [DCM03] The DCMI Usage Board. *DCMI Metadata Terms*. DCMI Recommendation. Dublin Core Metadata Initiative, 2003. URL: <http://dublincore.org/documents/dcmi-terms/>.
- [Koh06] Michael Kohlhase. OMDOC – *An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh16a] Michael Kohlhase. *dcm.sty: An Infrastructure for marking up Dublin Core Metadata in L^AT_EX documents*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2016. URL: <http://mirror.ctan.org/macros/latex/contrib/stex/sty/dcm/dcm.pdf>.
- [Koh16b] Michael Kohlhase. *omtext: Semantic Markup for Mathematical Text Fragments in L^AT_EX*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2016. URL: <http://mirror.ctan.org/macros/latex/contrib/stex/sty/omtext/omtext.pdf>.
- [Koh16c] Michael Kohlhase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. Comprehensive T_EX Archive Network (CTAN), 2016. URL: <http://mirror.ctan.org/macros/latex/contrib/stex/sty/statements/statements.pdf>.
- [sTeX] *KWARC/sTeX*. URL: <https://github.com/KWARC/sTeX> (visited on 05/15/2015).