

`modules.sty`: Semantic Macros and Module Scoping in \LaTeX^*

Michael Kohlhase, Dennis Müller
FAU Erlangen-Nürnberg
<http://kwarc.info/>

October 25, 2020

Abstract

The `modules` package is a central part of the \LaTeX collection, a version of $\text{\TeX}/\text{\LaTeX}$ that allows to markup $\text{\TeX}/\text{\LaTeX}$ documents semantically without leaving the document format, essentially turning $\text{\TeX}/\text{\LaTeX}$ into a document format for mathematical knowledge management (MKM).

This package supplies a definition mechanism for semantic macros and a non-standard scoping construct for them, which is oriented at the semantic dependency relation rather than the document structure. This structure can be used by MKM systems for added-value services, either directly from the \LaTeX sources, or after translation.

*Version v1.6 (last revised 2020/10/14)

Contents

1	Introduction	3
2	The User Interface	3
2.1	Package Options	3
2.2	Semantic Macros	4
2.3	Testing Semantic Macros	5
2.4	Axiomatic Assumptions	6
2.5	Semantic Macros for Variables	6
2.6	Symbol and Concept Names	7
2.7	Modules, Inheritance, and \LaTeX Module Signatures	8
2.8	Dealing with multiple Files	9
2.9	Using Semantic Macros in Narrative Structures	10
2.10	Including Externally Defined Semantic Macros	11
2.11	Namespaces and Alignments	11
3	Limitations & Extensions	12
3.1	Qualified Imports	12
3.2	Error Messages	13
3.3	Crossreferencing	13
3.4	No Forward Imports	13
4	The Implementation	14
4.1	Package Options	14
4.2	Modules and Inheritance	14
4.3	Semantic Macros	20
4.4	Defining Math Operators	32
4.5	Axiomatic Assumptions	32
4.6	Semantic Macros for Variables	32
4.7	Testing Semantic Macros	32
4.8	Symbol and Concept Names	33
4.9	Loading Modules	34
4.10	Including Externally Defined Semantic Macros	40
4.11	Namespaces and Alignments	40
4.12	Deprecated Functionality	40
4.13	Experiments	40

1 Introduction

Following general practice in the $\text{\TeX}/\text{\LaTeX}$ community, we use the term “semantic macro” for a macro whose expansion stands for a mathematical object, and whose name (the command sequence) is inspired by the name of the mathematical object. This can range from simple definitions like `\def\Reals{\mathbb{R}}` for individual mathematical objects to more complex (functional) ones object constructors like `\def\SmoothFunctionsOn#1{\mathcal{C}^\infty(\#1,\#1)}`. Semantic macros are traditionally used to make $\text{\TeX}/\text{\LaTeX}$ code more portable. However, the $\text{\TeX}/\text{\LaTeX}$ scoping model (macro definitions are scoped either in the local group or until the rest of the document), does not mirror mathematical practice, where notations are scoped by mathematical environments like statements, theories, or such. For an in-depth discussion of semantic macros and scoping we refer the reader [Koh08].

The `modules` package provides a \LaTeX -based markup infrastructure for defining module-scoped semantic macros and \LaTeX ML bindings [LTX] to create OMDOC [Koh06] from \LaTeX documents. In the \LaTeX world semantic macros have a special status, since they allow the transformation of $\text{\TeX}/\text{\LaTeX}$ formulae into a content-oriented markup format like OPENMATH [Bus+04] and (strict) content MATHML [Aus+10]; see Figure 1 for an example, where the semantic macros above have been defined by the `\symdef` macros (see Section 2.2) in the scope of a `\begin{module}[name=calculus]` (see Section 2.7).

\LaTeX	<code>\SmoothFunctionsOn\Reals</code>
PDF/DVI	$\mathcal{C}^\infty(\mathbb{R}, \mathbb{R})$
OPENMATH	<pre>% <OMA> % <OMS cd="calculus" name="SmoothFunctionsOn"/> % <OMS cd="calculus" name="Reals"/> % </OMA></pre>
MATHML	<pre>% <apply> % <csymbol cd="calculus">SmoothFunctionsOn</csymbol> % <csymbol cd="calculus">Reals</csymbol> % </apply></pre>

Example 1: OPENMATH and MATHML generated from Semantic Macros

2 The User Interface

The main contributions of the `modules` package are the `module` environment, which allows for lexical scoping of semantic macros with inheritance and the `\symdef` macro for declaration of semantic macros that underly the `module` scoping.

2.1 Package Options

`showmods` The `modules` package takes six options: If we set `showmods`, then the views (see Section ??) are shown. If we set the `qualifiedimports` option, then qualified imports are enabled. Qualified imports give more flexibility in module inheritance,

but consume more internal memory. As qualified imports are not fully implemented at the moment, they are turned off by default see Limitation 3.1. The option `noauxreq` prohibits the registration of `\@requiremodules` commands in the `aux` file. They are necessary for preloading the modules so that entries in the table of contents can have semantic macros; but as they sometimes cause trouble the option allows to turn off preloading.¹

`showmeta` If the `showmeta` option is set, then the metadata keys are shown (see [Koh20b] for details and customization options).

The `mh` option enables MathHub support; see [Koh20a].

`trwarn` Finally, if the `trwarn` is given, then the `modules` package only gives warnings instead of hard errors when term references are unknown.

2.2 Semantic Macros

`\symdef` The is the main constructor for semantic macros in \LaTeX . A call to the `\symdef` macro has the general form

$$\text{\symdef}[\langle keys \rangle]\{\langle cseq \rangle\}[\langle args \rangle]\{\langle definiens \rangle\}$$

where $\langle cseq \rangle$ is a control sequence (the name of the semantic macro) $\langle args \rangle$ is a number between 0 and 9 for the number of arguments $\langle definiens \rangle$ is the token sequence used in macro expansion for $\langle cseq \rangle$. Finally $\langle keys \rangle$ is a keyword list that further specifies the semantic status of the defined macro.

The two semantic macros in Figure 1 would have been declared by invocations of the `\symdef` macro of the form:

$$\begin{aligned} &\text{\symdef}\{\text{Reals}\}\{\text{\mathbb{R}}\} \\ &\text{\symdef}\{\text{SmoothFunctionsOn}\}[1]\{\text{\mathcal{C}}^{\sim\infty}(\#1,\#1)\} \end{aligned}$$

Note that both semantic macros correspond to OPENMATH or MATHML “symbols”, i.e. named representations of mathematical concepts (the real numbers and the constructor for the space of smooth functions over a set); we call these names the **symbol name** of a semantic macro. Normally, the symbol name of a semantic macro declared by a `\symdef` directive is just $\langle cseq \rangle$. The key-value pair `name= $\langle symname \rangle$` can be used to override this behavior and specify a differing name. There are two main use cases for this.

The first one is shown in Example 3, where we define semantic macros for the “exclusive or” operator. Note that we define two semantic macros: `\xorOp` and `\xor` for the applied form and the operator. As both relate to the same mathematical concept, their symbol names should be the same, so we specify `name=xor` on the definition of `\xorOp`.

`local` A key `local` can be added to $\langle keys \rangle$ to specify that the symbol is local to the module and is invisible outside. Note that even though `\symdef` has no advantage over `\def` for defining local semantic macros, it is still considered good style to

¹EDNOTE: MK: is this still needed without sms files?

use `\symdef` and `\abbrdef`, if only to make switching between local and exported semantic macros easier.

primary Finally, the key **primary** (no value) can be given for primary symbols.
\abbrdef The `\abbrdef` macro is a variant of `\symdef` that is only different in semantics, not in presentation. An abbreviative macro is like a semantic macro, and underlies the same scoping and inheritance rules, but it is just an abbreviation that is meant to be expanded, it does not stand for an atomic mathematical object.

We will use a simple module for natural number arithmetics as a running example. It defines exponentiation and summation as new concepts while drawing on the basic operations like $+$ and $-$ from L^AT_EX. In our example, we will define a semantic macro for summation `\Sumfromto`, which will allow us to express an expression like $\sum_{i=1}^n x^i$ as `\Sumfromto{i}{n}{2i-1}` (see Example 2 for an example). In this example we have also made use of a local semantic symbol for n , which is treated as an arbitrary (but fixed) symbol.

```
\begin{module}[name=arith]
  \symdef{Sumfromto}[4]{\sum_{\#1=\#2}^{\#3}{\#4}}
  \symdef[local]{arbitraryn}{n}
  What is the sum of the first $\arbitraryn$ odd numbers, i.e.
  $\Sumfromto{i}{1}{\arbitraryn{2i-1}}?
\end{module}
```

What is the sum of the first odd numbers, i.e. $\sum_{i=1} 2i - 1$?

Example 2: Semantic Markup in a module Context

\symvariant The `\symvariant` macro can be used to define presentation variants for semantic macros previously defined via the `\symdef` directive. In an invocation

```
\symdef[\langle keys \rangle]{\langle cseq \rangle}[\langle args \rangle]{\langle pres \rangle}
\symvariant{\langle cseq \rangle}[\langle args \rangle]{\langle var \rangle}{\langle varpres \rangle}
```

the first line defines the semantic macro `\langle cseq \rangle` that when applied to `\langle args \rangle` arguments is presented as `\langle pres \rangle`. The second line allows the semantic macro to be called with an optional argument `\langle var \rangle`: `\langle cseq \rangle[\var]` (applied to `\langle args \rangle` arguments) is then presented as `\langle varpres \rangle`. We can define a variant presentation for `\xor`; see Figure 3 for an example.

\resymdef Version 1.0 of the `modules` package had the `\resymdef` macro that allowed to locally redefine the presentation of a macro. But this did not interact well with the `beamer` package and was less useful than the `\symvariant` functionality. Therefore it is deprecated now and leads to an according error message.

2.3 Testing Semantic Macros

One of the problems in managing large module graphs with many semantic macros, so the `module` package gives an infrastructure for unit testing. The first macro is **\symtest** `\symtest`, which allows the author of a semantic macro to generate test output (if the `symtest` option is set) see figure 4 for a “tested semantic macro definition”. Note that the language in this purely generated, so that it can be adapted (tbd).

```

\begin{module}[name=xbool]
\symdef[name=xor]{xorOp}{\oplus}
\symvariant{xorOp}{uvee}{\underline{\vee}}
\symdef{xor}[2]{\#1\xorOp\#2}
\symvariant{xor}[2]{uvee}{\#1\xorOp[uvee]\#2}
Exclusive disjunction is commutative:  $\text{\xor{p}q}=\text{\xor{q}p}$ 
Some authors also write exclusive or with the  $\text{\xorOp[uvee]}$  operator,
then the formula above is  $\text{\xor[uvee]{p}q}=\text{\xor[uvee]{q}p}$ 
\end{module}

```

Exclusive disjunction is commutative: $p \oplus q = q \oplus p$
Some authors also write exclusive or with the $\underline{\vee}$ operator, then the formula above is $p \underline{\vee} q = q \underline{\vee} p$

Example 3: Presentation Variants of a Semantic Macro

```

\symdef[name=setst]{SetSt}[2]{\{\#1\,\,\text{\vert}\,\,\#2\}}
\symtest[name=setst]{SetSt}{\SetSt{a}{a>0}}

```

generates the output

Symbol `setst` with semantic macro `\SetSt`: used e.g. in $\{a \mid a > 0\}$

Example 4: A Semantic Macro Definition with Test

`\abbrtest` The `\abbrtest` macro gives the analogous functionality for `\abbrdef`.

2.4 Axiomatic Assumptions

`\assdef` In many ways, axioms and assumptions in definitions behave a lot like symbols (see [RK13] for discussion). Therefore we provide the macro `\assdef` that can be used to mark up assumptions. Given a phrase $\langle phrase \rangle$ in a definition², we can use `\assdef{\langle name \rangle}{\langle phrase \rangle}` to give this the symbol name $\langle name \rangle$.³

2.5 Semantic Macros for Variables

Up to now, the semantic macros generated OPENMATH and MATHML markup where the heads of the semantic macros become constants (the `OMS` and `csymbol` elements in Figure 1). But sometimes we want to have semantic macros for variables, e.g. to associate special notation conventions. For instance, if we want to define mathematical structures from components as in Figure 5, where the semigroup operation \circ is a variable epistemologically, but is a n -ary associative operator – we are in a semigroup after all. Let us call such variables **semantic variables** to contrast them from **semantic constants** generated by `\symdef` and `\symvariant`.

Semantic variables differ from semantic constants in two ways:

1. they do not participate in the imports mechanism and

²EDNOTE: only definitions?

³EDNOTE: continue

Definition 3.17 Let $\langle G, \circ \rangle$ be a semigroup, then we call $e \in G$ a **unit**, iff $e \circ x = x \circ e = x$. A semigroup with unit $\langle G, \circ, e \rangle$ is called a **monoid**.

Example 5: A Definition of a Structure with “semantic variables”.

2. they generate markup with variables.

In the case of Figure 5 we (want to) have the XML markup in Figure 6. To associate the notation to the variables, we define semantic macros for them, here the macro `\op` for the (semigroup) operation via the `\vardef` macro. `\vardef` works exactly like, except

1. semantic variables are local to the current \TeX group and
2. they generate variable markup in the XML

\TeX	<code>\vardef{op}[1]{\assoc\circ{#1}}</code>
OMDoc	<pre>% <notation> % <prototype> % <OMA> % <OMV name="op"/> % <expr name="a1"/> % <expr name="a2"/> % </OMA> % </prototype> % <rendering> % <mrow> % <render name="a1"/> % <mo>&#x2384;</mo> % <render name="a2"/> % </mrow> % </rendering> % </notation></pre>
\LaTeX	<code>\op{x,e}</code>
PDF/DVI	$x \circ e$
OPENMATH	<code>% <OMA><OMV name="op"/><OMV name="x"/><OMV name="e"/></OMA></code>
MATHML	<code>% <apply><ci>op</ci><ci>x</ci><ci>e</ci></apply></code>

Example 6: Semantic Variables in OPENMATH and MATHML

2.6 Symbol and Concept Names

Just as the `\symdef` declarations define semantic macros for mathematical symbols, the `modules` package provides an infrastructure for *mathematical concepts* that are expressed in mathematical vernacular. The key observation here is that concept names like “finite symplectic group” follow the same scoping rules as mathematical symbols, i.e. they are module-scoped. The `\termdef` macro is an analogue to `\symdef` that supports this: use `\termdef[⟨keys⟩]{⟨cseq⟩}{⟨concept⟩}` to declare the macro `\⟨cseq⟩` that expands to `⟨concept⟩`. See Figure 7 for an example, where we use the `\capitalize` macro to adapt `⟨concept⟩` to the sentence

EdN:4

`\termref`
`\symref`

beginning.⁴ The main use of the `\termdef`-defined concepts lies in automatic cross-referencing facilities via the `\termref` and `\symref` macros provided by the `statements` package [Koh20c]. Together with the `hyperref` package [RO], this provide cross-referencing to the definitions of the symbols and concepts. As discussed in section 3.3, the `\symdef` and `\termdef` declarations must be on top-level in a module, so the infrastructure provided in the `modules` package alone cannot be used to locate the definitions, so we use the infrastructure for mathematical statements for that.

```
\termdef[name=xor]{xdisjunction}{exclusive disjunction}
\capitalize\xdisjunction is commutative: $\xor{p}q=\xor{q}p$
```

Example 7: Extending Example 3 with Term References

2.7 Modules, Inheritance, and $\text{\texttt{S}}\text{\texttt{T}}\text{\texttt{E}}\text{\texttt{X}}$ Module Signatures

`module`

The `module` environment takes an optional `KeyVal` argument. Currently, only the `id` key is supported for specifying the identifier of a module (also called the module name). A module introduced by `\begin{module}[name=foo]` restricts the scope the semantic macros defined by the `\symdef` form to the end of this module given by the corresponding `\end{module}`, and to any other `module` environments that import them by a `\importmodule{foo}` directive. If the module `foo` contains `\importmodule` directives of its own, these are also exported to the importing module.

`\importmodule`

Thus the `\importmodule` declarations induce the semantic inheritance relation. Figure 8 shows a module that imports the semantic macros from three others. In the simplest form, `\importmodule{<mod>}` will activate the semantic macros and concepts declared by `\symdef` and `\termdef` in module `<mod>` in the current module¹. To understand the mechanics of this, we need to understand a bit of the internals. The `module` environment sets up an internal macro pool, to which all the macros defined by the `\symdef` and `\termdef` declarations are added; `\importmodule` only activates this macro pool. Therefore `\importmodule{<mod>}` can only work, if the $\text{\texttt{T}}\text{\texttt{E}}\text{\texttt{X}}$ parser — which linearly goes through the $\text{\texttt{S}}\text{\texttt{T}}\text{\texttt{E}}\text{\texttt{X}}$ sources — already came across the module `<mod>`. In many situations, this is not obtainable; e.g. for “semantic forward references”, where symbols or concepts are previewed or motivated to knowledgeable readers before they are formally introduced or for modularizations of documents into multiple files. We come to this next: ⁵

EdN:5

`\metalinguage`

The `\metalinguage` macro is a variant of `importmodule` that imports the meta language, i.e. the language in which the meaning of the new symbols is expressed. For mathematics this is often first-order logic with some set theory; see [RK13] for discussion.

⁴EdNOTE: continue, describe `<keys>`, they will have to to with plurals,... once implemented

¹Actually, in the current $\text{\texttt{T}}\text{\texttt{E}}\text{\texttt{X}}$ group, therefore `\importmodule` should be placed directly after the `\begin{module}`.

⁵EdNOTE: MK: document the other keys of `module`

2.8 Dealing with multiple Files

The infrastructure presented above works well if we are dealing with small files or small collections of modules. In reality, collections of modules tend to grow, get re-used, etc, making it much more difficult to keep everything in one file. This general trend towards increasing entropy is aggravated by the fact that modules are very self-contained objects that are ideal for re-used. Therefore in the absence of a content management system for L^AT_EX document (fragments), module collections tend to develop towards the “one module one file” rule, which leads to situations with lots and lots of little files.

Moreover, most mathematical documents are not self-contained, i.e. they do not build up the theory from scratch, but pre-suppose the knowledge (and notation) from other documents. In this case we want to make use of the semantic macros from these prerequisite documents without including their text into the current document.

`\importmodule` The `\importmodule` macro can be given an optional first keyword argument that can be used to specify which S^TE^X modules to load.

`load` `\importmodule[load=filepath]{mod}` will read the S^TE^X file at *filepath*.tex without producing output (if it exists and has not been loaded before) and activate the semantic macros from module *mod* (which was supposedly defined in *filepath*.tex). Note that an `\importmodule` recursively loads all necessary files to supply the semantic macros inherited by the current module. `\importmhmodule` does not produce output, it only uses the side effects of the symbol declarations `\sympi*` and definitions (`\symdef` and `\symvariant`) the module environment (`\begin/\end{module}`), as well as the `\import/\usemodule` directives – we jointly call this information the **S^TE^X module signatures**.

Thus `\importmodule` can be used to make module files truly self-contained. To arrive at a file-based content management system, it is good practice to reuse the module identifiers as module names and to prefix module files with corresponding `\importmodule` statements that pre-load the corresponding module files. But this leads to tedious duplication: We see imports of the form

```
\importmhmodule[path=foo/en/very-long-name]{very-long-name}
```

`dir` To avoid this, `\importmhmodule` allows a second key: `dir`, which specifies the directory of the S^TE^X module. So we can write

```
\importmhmodule[dir=foo/en]{very-long-name}
```

instead when the module name and file name coincide. This also avoids the maintenance problems (typos) induced by duplication. If both `path` and `dir` are given, the latter takes precedence.

In Example 8, we have shown the typical setup of a module file. The `\importmodule` macro takes great care that files are only read once, as S^TE^X allows multiple inheritance and this setup would lead to an exponential (in the module inheritance depth) number of file loads.

```

\documentclass{article}
\usepackage{stex}
\begin{document}
...
\begin{module}[name=foo]
\importmodule[dir=../other]{bar}
\importmodule[load=../mycolleaguesmodules]{baz}
\importmodule[load=../other/bar]{foobar}
...
\end{module}
...
\end{document}

```

Example 8: Self-contained Modules via `importmodule`

Note that – as \LaTeX uses the `standalone` package [`standalone:ctan:on`], we can make the \LaTeX modules “standalone”, i.e. with a `\documentclass`, preamble and `\begin/\end{document}` that can directly be formatted with `pdflatex`, but also included with `\include/\usemodule`. This is very convenient for distributing functionality into \LaTeX modules.

Note that the recursive (depth-first) nature of the file loads induced by this setup is very natural, but can lead to problems with the depth of the file stack in the \TeX formatter (it is usually set to something like 15^2). Therefore, it may be necessary to circumvent the recursive load pattern providing (logically spurious) `\importmodule` commands. Consider for instance module `bar` in Example 8, say that `bar` already has load depth 15, then we cannot naively import it in this way. If module `bar` depended say on a module `base` on the critical load path, then we could add a statement `\requiremodules{../base}` in the second line. This would load the modules from `../base.tex` in advance (uncritical, since it has load depth 10) without activating them, so that it would not have to be re-loaded in the critical path of the module `foo`. Solving the load depth problem.

`\requiremodules`

`\inputref`

The `\inputref` macro behaves just like `\input` in the \LaTeX workflow, but in the \LaTeX conversion process creates a reference to the transformed version of the input file instead. Moreover, spacing can be customized by the `\inputref@preskip` and `\inputref@postskip` macros, which default to nothing, but could be customized e.g. to `\medskip`.

`\inputref@preskip`

`\inputref@postskip`

2.9 Using Semantic Macros in Narrative Structures

The `\importmodule` macro establishes the inheritance relation, a transitive relation among modules that governs visibility of semantic macros. In particular, it can only be used in modules (and has to be used at the top-level, otherwise it is hindered by \LaTeX groups). In many cases, we only want to *use* the semantic macros in an environment (and not re-export them). Indeed, this is the normal

²If you have sufficient rights to change your \TeX installation, you can also increase the variable `max_in_open` in the relevant `texmf.cnf` file. Setting it to 50 usually suffices

situation for most parts of mathematical documents. For that $\text{\S}\text{\TeX}$ provides the `\usemodule` macro, which takes the same arguments as `\importmodule`, but the semantic macros the module imports are not re-exported from the current module. A typical situation is shown in Figure 9, where we open the module `ring` (see Figure ??) and use its semantic macros (in the `omtext` environment). In earlier versions of $\text{\S}\text{\TeX}$, we would have to wrap the `omtext` environment in an anonymous module environment to prevent re-export.

```
\begin{omtext}
  \usemodule[load=../algebra/rings.tex]{ring}
  We  $R$  be a ring  $(\text{\textbackslash}rbase, \text{\textbackslash}rplus, \text{\textbackslash}rzero, \text{\textbackslash}rminusOp, \text{\textbackslash}rtimes, \text{\textbackslash}rone)$ , ...
\end{omtext}
```

Example 9: Using Semantic Macros in Narrative Structures

2.10 Including Externally Defined Semantic Macros

In some cases, we use an existing \LaTeX macro package for typesetting objects that have a conventionalized mathematical meaning. In this case, the macros are “semantic” even though they have not been defined by a `\symdef`. This is no problem, if we are only interested in the \LaTeX workflow. But if we want to e.g. transform them to OMDOC via $\text{\LaTeX}\text{\ML}$, the $\text{\LaTeX}\text{\ML}$ bindings will need to contain references to an OMDOC theory that semantically corresponds to the \LaTeX package. In particular, this theory will have to be imported in the generated OMDOC file to make it OMDOC-valid.

To deal with this situation, the `modules` package provides the `\requirepackage` macro. It takes two arguments: a package name, and a URI of the corresponding OMDOC theory. In the \LaTeX workflow this macro behaves like a `\usepackage` on the first argument, except that it can — and should — be used outside the \LaTeX preamble. In the $\text{\LaTeX}\text{\ML}$ workflow, this loads the $\text{\LaTeX}\text{\ML}$ bindings of the package specified in the first argument and generates an appropriate `imports` element using the URI in the second argument.

2.11 Namespaces and Alignments

We often want to align the content of $\text{\S}\text{\TeX}$ modules to formalizations, e.g. to take advantage of type declarations there. For this, we extend the keys of the `module` environment and the `\symdef` macro with a key `align` whose value is an external MMT theory or symbol name respectively. Note that symbols can only be aligned in aligned modules.

As full MMT URIs are of the form $\langle \text{\textit{URI}} \rangle ? \langle \text{\textit{theory}} \rangle ? \langle \text{\textit{name}} \rangle$, we need a way to specify the $\langle \text{\textit{URI}} \rangle$. We adopt the system of **namespaces** of MMT [MNS]: the macro declares a namespace URI. If the optional argument is given, then this is a namespace abbreviation declaration, which can be used later to reference theories/modules from other namespaces.

The example below shows off all possibilities. We first declare the namespace of the document (which places all theories and their symbols into this namespace). Then we add two more a namespace abbreviation: `sets:` and `moresets:` that we will use to for the alignments in the module. We use the `ns` and `align` keys in the `module` environment to specify that the external theory `sets:?ESet` is the default alignment target, i.e. any symbol that in the `emptyset` module is aligned by default to the symbol with the same name in the external `sets:?ESet` theory.

```
\namespace{http://mathhub.info/smgloM/sets}
\namespace[sets]{http://mathhub.info/MitM/smgloM/sets}
\namespace[moresets]{http://mathhub.info/more/sets}
\begin{module}[creators=miko,ns=sets,align=ESet]{emptyset}
  \importmodule{set}
  \symdef[assocarg=1]{set}[1]{\{#1\}}
  \symdef[align=empty]{eset}{\emptyset}
  \symdef[align=AEset?eset]{aeset}{\emptyset^+}
  \symdef[ns=moresets,align=fuzzy?eset]{feset}{\emptyset^f}
  \symdef[noalign]{neset}{\emptyset^*}
\end{module}
```

The first `\symdef` aligns the symbol `emptyset?set` with `sets:?ESet?set` via default alignment. This breaks down for the symbol `eset`, so we specify an alignment to the symbol `sets:?empty` via the `align` key on the `\symdef`. If we want to align with a different theory we can just use the `?` notation as for `aeset`. A different namespace can be specified by the `ns` key, and finally, we can indicate that a symbol should not be aligned via the `noalign` key.

3 Limitations & Extensions

In this section we will discuss limitations and possible extensions of the `modules` package. Any contributions and extension ideas are welcome; please discuss ideas, requests, fixes, etc. on the `STEX` issue tracker at [sTeX].

3.1 Qualified Imports

In an earlier version of the `modules` package we used the `usesqualified` for importing macros with a disambiguating prefix (this is used whenever we have conflicting names for macros inherited from different modules). This is not accessible from the current interface. We need something like a `\importqualified` macro for this; see [sTeX, issue #1505]. Until this is implemented the infrastructure is turned off by default, but we have already introduced the `qualifiedimports` option for the future.

`qualifiedimports`

3.2 Error Messages

The error messages generated by the `modules` package are still quite bad. For instance if `thyA` does not exist we get the cryptic error message

```
! Undefined control sequence.
\module@defs@thyA ...hy
                        \expandafter \mod@newcomma...
1.490 ...ortmodule{thyA}
```

This should definitely be improved.

3.3 Crossreferencing

Note that the macros defined by `\symdef` are still subject to the normal \TeX scoping rules. Thus they have to be at the top level of a module to be visible throughout the module as intended. As a consequence, the location of the `\symdef` elements cannot be used as targets for crossreferencing, which is currently supplied by the `statement` package [Koh20c]. A way around this limitation would be to import the current module from the \TeX module (see Section 2.7) via the `\importmodule` declaration.

3.4 No Forward Imports

\TeX allows imports in the same file via `\importmodule{<mod>}`, but due to the single-pass linear processing model of \TeX , `<mod>` must be the name of a module declared *before* the current point. So we cannot have forward imports as in

```
\begin{module}[name=foo]
  \importmodule{mod}
  ...
\end{module}
...
\begin{module}[name=mod]
  ...
\end{module}
```

a workaround, we can extract the module `<mod>` into a file `mod.tex` and replace it with `\inputref{mod}`, as in

```
\begin{module}[name=foo]
  \importmodule[load=mod]{mod}
  ...
\end{module}
...
\inputref{mod}
```

then the `\importmodule` command can read `mod.tex` without having to wait for the module `<mod>` to be defined.

4 The Implementation

The `modules` package generates two files: the L^AT_EX package (all the code between `<*package>` and `</package>`) and the L^AT_EXML bindings (between `<*txml>` and `</txml>`). We keep the corresponding code fragments together, since the documentation applies to both of them and to prevent them from getting out of sync.

4.1 Package Options

We declare some switches which will modify the behavior according to the package options. Generally, an option `xxx` will just set the appropriate switches to true (otherwise they stay false). The options we are not using, we pass on to the `sref` package we require next.

```
1 <*package>
2 \newif\if@modules@html@\@modules@html@true
3 \DeclareOption{omdocmode}{\@modules@html@false}
4 \newif\if@modules@mh@\@modules@mh@false
5 \DeclareOption{mh}{\@modules@mh@true}
6 \newif\ifmod@show\mod@showfalse
7 \DeclareOption{showmods}{\mod@showtrue}
8 \newif\ifaux@req\aux@reqtrue
9 \DeclareOption{noauxreq}{\aux@reqfalse}
10 \newif\ifmod@qualified\mod@qualifiedfalse
11 \DeclareOption{qualifiedimports}{\mod@qualifiedtrue}
12 \newif\if@trwarn\@trwarnfalse
13 \DeclareOption{trwarn}{\@trwarntrue}
14 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{sref}}
15 \ProcessOptions

16 \RequirePackage{stex-base}
17 \RequirePackage{sref}
18 \RequirePackage{standalone}
19 \if@modules@mh\RequirePackage{modules-mh}\fi
20 \RequirePackage{xspace}
21 \if@latexml\else\ifmod@show\RequirePackage{mdframed}\fi\fi
22 \RequirePackage{stex-currfile}
```

4.2 Modules and Inheritance

We define the keys for the module environment and the actions that are undertaken, when the keys are encountered.

```
23 \addmetakey*{module}{title}
24 \addmetakey*{module}{name}
25 \addmetakey*{module}{id} % TODO: deprecate properly
26 \addmetakey*{module}{creators}
27 \addmetakey*{module}{contributors}
28 \addmetakey*{module}{srccite}
29 \addmetakey*{module}{align}[WithTheModuleOfTheSameName]
30 \addmetakey*{module}{ns}
```

```

31 \addmetakey*{module}{narr}
32 \addmetakey*{module}{noalign}[true]

module@heading We make a convenience macro for the module heading. This can be customized.
33 \ifdef{\thesection}{\newcounter{module}[section]}{\newcounter{module}}%
34 \newrobustcmd\module@heading{%
35   \stepcounter{module}%
36   \ifmod@show%
37   \noindent{\textbf{Module} \thesection.\thetitle [\module@id]]}%
38   \sref@label@id{Module \thesection.\thetitle [\module@id]]}%
39   \ifx\module@title\empty : \quad\else\quad(\module@title)\hfill\\fi%
40   \fi%
41 }% mod@show

```

module Finally, we define the begin module command for the module environment. Much of the work has already been done in the keyval bindings, so this is quite simple. We store the file name (without extension) and extension of the module file in the global macros `\module@<name>@path` and `\module@<name>@ext`, so that we can use them later. The source of these two macros, `\mod@path` and `\mod@ext`, are defined in `\requiremodules`.

```

42 \newenvironment{module}[1][]{%
43   \begin{@module}[#1]%
44   \ifcsundef{mod@path}{\csxdef{module@\module@id @path}{\mod@path}}%
45   \ifcsundef{mod@ext}{\csxdef{module@\module@id @ext}{\mod@ext}}%
46   \module@heading% make the headings
47   \ignorespacesandpars\usemodule@maybesetcodes}%
48   \end{@module}%
49   \ignorespacesafterend%
50 }%
51 \ifmod@show\surroundwithmdframed{module@om@common}\fi%

```

@module A variant of the `module` environment that does not create printed representations (in particular no frames).

For a module with uri `<uri>`, we have a macro `\module@defs@<uri>` that acts as a repository for semantic macros of the current module. It will be called by `\importmodule` to activate them. We will add the internal forms of the semantic macros whenever `\symdef` is invoked. To do this, we will need an unexpanded form `\this@module` that expands to `\module@defs@<uri>`; we define it first and then initialize `\module@defs@<uri>` as empty. Then we do the same for qualified imports as well (if the `qualifiedimports` option was specified). Furthermore, we save the module name in the token register `\module@id`.

To compute the `<uri>` of a module, `\set@default@ns` computes the namespace, if none is provided as an optional argument, as follows:

If the file of the module is `/some/path/file.tex` and we are not in a MathHub repository, the namespace is `file:///some/path`.

If the file of the module is `/some/path/in/mathhub/repo/sitory/source/sub/file.tex` and `repo/sitory` is an archive in the MathHub root, and the MANIFEST.MF

of `repo/sitory` declares a namespace `http://some.namespace/foo`, then the namespace of the module is `http://some.namespace/foo/sub`.

```

52 \newif\ifarchive@ns@empty@archive@ns@empty@false
53 \def\set@default@ns{
54   \edef\@module@ns@temp{\stex@currpath}
55   \if@iswindows@\edef\@module@ns@temp{\windows@to@path\@module@ns@temp}\fi
56   \archive@ns@empty@false
57   \unless\ifcsname mh@currentrepos\endcsname
58     \archive@ns@empty@true
59   \else
60     \expandafter\ifx\csname currentrepos@ns@mh@currentrepos\endcsname\@empty\archive@ns@empty@
61   \fi
62   \ifarchive@ns@empty@
63     \edef\@module@ns@tempuri{file\@Colon\@Slash\@Slash\@module@ns@temp}
64   \else
65     \edef\@module@filepath@temppath{\@module@ns@temp}
66     \edef\@module@ns@tempuri{\csname currentrepos@ns@mh@currentrepos\endcsname}
67     \edef\@module@archivedirpath{\csname currentrepos@dir@mh@currentrepos\endcsname\@Slash sou
68     \edef\@module@archivedirpath{\expandafter\detokenize\expandafter{\@module@archivedirpath}}
69     \IfBeginWith\@module@filepath@temppath\@module@archivedirpath{
70       \StrLen\@module@archivedirpath[\ns@temp@length]
71       \StrGobbleLeft\@module@filepath@temppath\ns@temp@length[\@module@filepath@temprest]
72       \edef\@module@ns@tempuri{\@module@ns@tempuri\@module@filepath@temprest}
73     }{}
74   \fi
75   \IfEndWith\@module@ns@tempuri\@Slash{\StrGobbleRight\@module@ns@tempuri1[\@module@ns@tempuri]}
76   \setkeys{module}{ns=\@module@ns@tempuri}
77 }

```

If the module is not given an id, `\set@next@moduleid` computes one by enumeration, e.g. `module0`, `module1`, etc.

```

78 \def\set@next@moduleid{
79   \unless\ifcsname namespace@\module@ns @unnamedmodules\endcsname
80     \csgdef{namespace@\module@ns @unnamedmodules}{0}
81   \fi
82   \edef\namespace@currnum{\csname namespace@\module@ns @unnamedmodules\endcsname}
83   \edef\module@temp@setidname{\noexpand\setkeys{module}{name=module\namespace@currnum}}
84   \module@temp@setidname
85   \csxdef{namespace@\module@ns @unnamedmodules}{\the\numexpr\namespace@currnum+1}
86 }

```

Finally, the `@module` environment does the actual work, i.e. setting metakeys, computing namespace/id, defining `\this@module`, etc.

```

87 \newenvironment{@module}[1][]{
88   \metasetkeys{module}{#1}
89   \ifcvoid{module@name}{\let\module@name\module@id}{ } % TODO deprecate
90   \ifx\module@ns@empty\set@default@ns\fi
91   \ifx\module@narr\@empty
92     \setkeys{module}{narr=\module@ns}
93   \fi

```



```

94 \ifcvoid{module@name}{\set@next@moduleid}{%
95 \let\module@id\module@name
96 \edef\module@uri@uri{\module@ns\@QuestionMark\module@id} % faster, and at this point equivalent
97 \csgdef{module@names@\module@uri@uri}{%
98 \csgdef{module@imports@\module@uri@uri}{%
99 \csxdef{\module@uri@uri}{\noexpand\@invoke@module{\module@uri@uri}}
100 \csxdef{module@id@\module@id}{\noexpand\@invoke@module{\module@uri@uri}}
101 \csxdef{Module\module@id}{\noexpand\@invoke@module{\module@uri@uri}}
102 \edef\this@module{%
103 \module@uri@uri%
104 %\expandafter\noexpand\csname module@defs@\module@uri@uri\endcsname%
105 }%
106 \csxdef{module@defs@\module@uri@uri}{%
107 \expandafter\def\expandafter\noexpand\csname Module\module@id\endcsname%
108 {\noexpand\@invoke@module{\module@uri@uri}}%
109 }%
110 \ifmod@qualified%
111 \edef\this@qualified@module{%
112 \expandafter\noexpand\csname module@defs@\module@uri@uri\endcsname%
113 }%
114 \csxdef{module@defs@qualified@\module@uri@uri}{%
115 \expandafter\def\expandafter\noexpand\csname Module\module@id\endcsname%
116 {\noexpand\@invoke@module{\module@uri@uri}}%
117 }%
118 \fi%
119 }{}%

```

A module with URI $\langle uri \rangle$ and id $\langle id \rangle$ creates two macros $\backslash\langle uri \rangle$ and $\backslash\text{Module}\langle id \rangle$, that ultimately expand to $\backslash\text{@invoke@module}\{\langle uri \rangle\}$. Currently, the only functionality is $\backslash\text{@invoke@module}\{\langle uri \rangle\}\text{@URI}$, which expands to the full uri of a module (i.e. via $\backslash\text{Module}\langle id \rangle\text{@URI}$). In the future, this macro can be extended with additional functionality, e.g. accessing symbols in a macro for overloaded (macro-)names.

```

120
121 \def\@URI{uri}
122
123 \def\@invoke@module#1#2{%
124 \ifx\@URI#2%
125 #1%
126 \else%
127 % TODO something else
128 #2%
129 \fi%
130 }
131

```

$\backslash\text{activate@defs}$ To activate the $\backslash\text{symdefs}$ from a given module $\langle mod \rangle$, we call the macro $\backslash\text{module@defs@}\langle mod \rangle$. But to make sure that every module is activated only once, we only activate if the macro $\backslash\text{module@defs@}\langle mod \rangle$ is undefined, and define

it directly afterwards to prohibit further activations.

```

132 \def\activate@defs#1{%
133   \ifcsundef{moduleid@#1}{
134     \PackageError{modules}{No module with name #1 loaded}{Probably missing an
135       \detokenize{\importmodule} (or variant) somewhere?
136   }
137 }{%
138   \ifcsundef{module@\csname moduleid@#1\endcsname\@URI @activated}%
139     {\csname module@defs@\csname moduleid@#1\endcsname\@URI\endcsname}{}%
140     \namedef{module@\csname moduleid@#1\endcsname\@URI @activated}{true}%
141   }%
142 }%

```

`\export@defs` `\export@defs{<mod>}` exports all the `\symdefs` from module `<mod>` to the current module (if it has the name `<currmod>`), by adding a call to `\module@defs@<mod>` to the registry `\module@defs@<currmod>`.

Naive understanding of this code: `#1` be will be expanded first, then `\this@module`, then `\active@defs`, then `\g@addto@macro`.

```

143 \def\g@addto@macro@safe#1#2{\ifx#1\relax\def#1{}\fi\g@addto@macro#1{#2}}
144 \def\export@defs#1{\ifundefined{moduleid}{}\fi}%
145 \ifcsvoid{this@module}{}\fi
146 \expandafter\g@addto@macro@safe%
147   \csname module@defs@\this@module\expandafter\endcsname%
148   \expandafter{\activate@defs{#1}}%
149 }}%
150 }%

```

Now we come to the implementation of `\importmodule`, but before we do, we define conditional and an auxiliary macro:

`\if@importing` `\if@importing` can be used to shut up macros in an import situation.

```

151 \newif\if@importing\@importingfalse

```

`\update@used@modules` This updates the register `\used@modules`

```

152 \newcommand\update@used@modules[1]{%
153   \ifx\used@modules\@empty%
154     \edef\used@modules{#1}%
155   \else%
156     \edef\used@modules{\used@modules,#1}%
157   \fi}

```

`\importmodule` The `\importmodule[<file>]{<mod>}` macro is an interface macro that loads `<file>` and activates and re-exports the `\symdefs` from module `<mod>`. As we will (probably) need to keep a record of the currently imported modules (top-level only), we divide the functionality into a user-visible macro that records modules in the `\used@modules` register and an internal one (`\@importmodule`) that does the actual work.

```

158 \gdef\used@modules{}

```

```

159 \srefaddidkey{importmodule}
160 \addmetakey{importmodule}{load}
161 \addmetakey{importmodule}{dir}
162 \addmetakey[false]{importmodule}{conservative}[true]
163 \newcommand\importmodule[2][{}]{%
164 \metasetkeys{importmodule}{#1}%
165 \usemodule@maybesetcodes
166 \update@used@modules{#2}%
167 \ifx\importmodule@dir\@empty
168 \@importmodule[\importmodule@load]{#2}{export}%
169 \else\@importmodule[\importmodule@dir/#2]{#2}{export}\fi%
170 \ignorespacesandpars}

\@importmodule \@importmodule[\filepath][\{<mod>\}{<export?>}] loads <filepath>.tex and acti-
vates the module <mod>. If <export?> is export, then it also re-exports the
\symdefs from <mod>.

First \@load will store the base file name with full path, then check if
\module@<mod>@path is defined. If this macro is defined, a module of this name
has already been loaded, so we check whether the paths coincide, if they do, all
is fine and we do nothing otherwise we give a suitable error. If this macro is
undefined we load the path by \requiremodules.

171 \newcommand\@importmodule[3][{}]{%
172 {\@importingtrue% to shut up macros while in the group opened here
173 \edef\@load{#1}%
174 \edef\@load{\expandafter\detokenize\expandafter{\@load}}%
175 \ifx\@load\@empty%
176 \ifcsundef{Module#2}{\requiremodules{\stex@maindir\@Slash#2}}{}
177 \else%
178 \ifcsundef{module@#2@path}{\requiremodules{\@load}}%
179 {\edef\@path{\csname module@#2@path\endcsname}%
180 \IfStrEq\@load\@path{\relax}% if the known path is the same as the requested one do nothing
181 {\PackageError{modules}% else signal an error
182 {Module Name Clash\MessageBreak
183 A module with name #2 was already loaded under the path "\@path"\MessageBreak
184 The imported path "\@load" is probably a different module with the\MessageBreak
185 same name; this is dangerous -- not importing}%
186 {Check whether the Module name is correct}}}%
187 \fi}%
188 \ifcsvoid{this@module}{-}{%
189 \ifcsvoid{module@imports@\this@module}{
190 \csxdef{module@imports@\this@module}{%
191 \csname Module#2\endcsname\@URI%
192 }%
193 }{
194 \csxdef{module@imports@\this@module}{%
195 \csname Module#2\endcsname\@URI,%
196 \csname module@imports@\this@module\endcsname%
197 }%
198 }%

```

```

199 }%
200 \activate@defs{#2}% activate the module
201 \edef\@export{#3}\def\@export{export}%prepare comparison
202 \ifx\@export\@export\export@defs{#2}\fi% export the module
203 }%

\usemodule \usemodule acts like \importmodule, except that it does not re-export the se-
semantic macros in the modules it loads.
204 \newcommand\usemodule[2][]{%
205 \metasetkeys{importmodule}{#1}%
206 \update@used@modules{#2}%
207 \ifx\importmodule@dir\@empty
208 \@importmodule[\importmodule@load]{#2}{noexport}%
209 \else\@importmodule[\importmodule@dir/#2]{#2}{noexport}\fi%
210 \ignorespacesandpars}

\withusedmodules This variant just imports all the modules in a comma-separated list (usually
\used@modules)
211 \newcommand\withusedmodules[2]{\@for\@I:=#1\do{\activate@defs\@I}{#2}}}%

\importOMDocmodule this is now deprecated.
212 \newrobustcmd\importOMDocmodule[3][]{\PackageError{modules}%
213 {The \protect\importOMDocmodule macro is deprecated}
214 {use \protect\importmodule instead!}}}%

\metalanguage \metalanguage behaves exactly like \importmodule for formatting. For LA-
TEXML, we only add the type attribute.
215 \let\metalanguage=\importmodule%

```

4.3 Semantic Macros

```

\mod@newcommand We first hack the LATEX kernel macros to obtain a version of the \newcommand
macro that does not check for definedness.
216 \let\mod@newcommand=\providerobustcmd%

```

Now we define the optional KeyVal arguments for the \symdef form and the actions that are taken when they are encountered.

```

conceptdef
217 \srefaddidkey{conceptdef}%
218 \addmetakey*{conceptdef}{title}%
219 \addmetakey{conceptdef}{subject}%
220 \addmetakey*{conceptdef}{display}%
221 \def\conceptdef@type{Symbol}%
222 \newrobustcmd\conceptdef[2][]{%
223 \metasetkeys{conceptdef}{#1}%
224 \ifx\conceptdef@display\st@flow\else{\stDMemph{\conceptdef@type} #2:}\fi%
225 \ifx\conceptdef@title\@empty~\else~(\stDMemph{\conceptdef@title})\par\fi%
226 }%

```

New stuff:

```

227 % -----
228
229 % calls \edef\#1{#2} and adds the macro definition to \this@module
230 \def\define@in@module#1#2{
231   \expandafter\edef\csname #1\endcsname{#2}
232   \edef\define@in@module@temp{%
233     \def\expandafter\noexpand\csname#1\endcsname%
234     {#2}%
235   }%
236   \if@symdeflocal\else%
237     \expandafter\g@addto@macro@safe\csname module@defs@\this@module%
238     \expandafter\endcsname\expandafter{\define@in@module@temp}%
239   \fi%
240 }
241
242 \catcode'\&=12
243 \def\@Ampersand{&}
244 \catcode'\&=4
245
246 % -----
247
248 % Declares a new symbol
249 % In module http://authority/path?module, defines new macros
250 % \http://authority/path?module?<name> and \#2
251
252 \addmetakey{symdecl}{name}%
253
254 \newcommand\symdecl[2][]{%
255   \ifcsdef{this@module}{%
256     \metasetkeys{symdecl}{#1}%
257     \ifcsvoid{symdecl@name}{\edef\symdecl@name{#2}}{}%
258     \edef\symdef@uri{\this@module\@QuestionMark\symdecl@name}%
259     \ifcsvoid{\symdef@uri}{
260       \ifcsvoid{module@names@\this@module}{%
261         \csxdef{module@names@\this@module}{\symdecl@name}%
262       }{%
263         \csxdef{module@names@\this@module}{\symdecl@name,%
264           \csname module@names@\this@module\endcsname}%
265       }%
266       \define@in@module\symdef@uri{\noexpand\@invoke@symbol{\symdef@uri}}%
267       \define@in@module{#2}{\noexpand\@invoke@symbol{\symdef@uri}}%
268     }{%
269       % not compatible with circular dependencies, e.g. test/omdoc/07-modules/sms testa.tex
270       \PackageWarning{modules}{symbol already defined: \symdef@uri}%
271       You need to pick a fresh name for your symbol%
272     }%
273     \define@in@module\symdef@uri{\noexpand\@invoke@symbol{\symdef@uri}}%
274     \define@in@module{#2}{\noexpand\@invoke@symbol{\symdef@uri}}%

```

```

275     }%
276 }{%
277   \PackageError{modules}{\detokenize{\symdecl} not in a module}{You need to be in a module%
278   in order to declare a new symbol}
279 }%
280 \if@insymdef@ \else \usemodule@maybesetcodes \fi
281 }
282
283 % -----
284
285 % after \symdecl{foo}, \foo expands to \@invoke@symbol{<uri of foo>}
286 \protected\def \@invoke@symbol#1{%
287   \def \@invoke@symbol@first{#1}
288   \symbol@args%
289 }
290
291 % takes care of the optional notation-option-argument, and either invokes \@invoke@symbol@math :
292 % symbolic presentation or \@invoke@symbol@text for verbalization
293 \newcommand \symbol@args[1] []{%
294   \ifmmode \def \invoke@symbol@next{\@invoke@symbol@math \@invoke@symbol@first{#1}}%
295   \else \def \invoke@symbol@next{\@invoke@symbol@text \@invoke@symbol@first{#1}} \fi%
296   \invoke@symbol@next%
297 }
298
299 % finally gets called with both uri and notation-option,
300 % convenient for e.g. a LaTeXML binding
301 \def \@invoke@symbol@math#1#2{%
302   % #1: URI
303   % #2: options
304   % TODO \setnotation variants
305   \notation@parse@params{#2}{}%
306   \def \notation@temp@fragment{%
307     \ifx \notation@curr@arity \@empty \else%
308       \edef \notation@temp@fragment{arity=\notation@curr@arity}%
309     \fi%
310     \ifx \notation@curr@lang \@empty \else%
311       \ifx \notation@temp@fragment \@empty%
312         \edef \notation@temp@fragment{lang=\notation@curr@lang}%
313       \else%
314         \edef \notation@temp@fragment{\notation@temp@fragment\@Ampersand lang=\notation@curr@lang}%
315       \fi%
316     \fi%
317     \ifx \notation@curr@variant \@empty \else%
318       \ifx \notation@temp@fragment \@empty%
319         \edef \notation@temp@fragment{variant=\notation@curr@variant}%
320       \else%
321         \edef \notation@temp@fragment{\notation@temp@fragment\@Ampersand variant=\notation@curr@va
322       \fi%
323     \fi%
324     \csname #1\@Fragment\notation@temp@fragment\endcsname%

```

```

325 }
326
327 \def\@invoke@symbol@text#1#2{%
328     % TODO
329 }
330
331 % -----
332
333 % \modules@getURIfromName - searches for the full URI given a symbol name
334 % and stores it in \notation@uri
335 \def\modules@getURIfromName#1{%
336     % TODO check whether #1 is a URI
337     \def\notation@uri{}%
338     \def\modules@getURI@name{#1}%
339     \ifcsvoid{this@module}{}{%
340         \expandafter\modules@getURIfromModule\expandafter{\this@module}%
341         \ifx\notation@uri@empty%
342             \edef\modules@getURI@modules{\csname module@imports@\this@module\endcsname}%
343             \expandafter\@for\expandafter\@I\expandafter:\expandafter=\modules@getURI@modules\do{%
344                 \ifx\notation@uri@empty%
345                     \expandafter\modules@getURIfromModule\expandafter{\@I}%
346                 \fi%
347             }%
348         \fi%
349         \ifx\notation@uri@empty%
350             \def\notation@extract@uri@currcs{}%
351             \notation@extract@uri{#1}%
352         \fi%
353         \ifx\notation@uri@empty%
354             \PackageError{modules}{No symbol with name, URI or macroname \detokenize{#1} found!}{}%
355         \fi%
356     }%
357 }
358
359 \def\modules@getURIfromModule#1{%
360     \edef\modules@getURI@names{\csname module@names@#1\endcsname}%
361     \expandafter\@for\expandafter\@I\expandafter:\expandafter=%
362     \modules@getURI@names\do{%
363         \ifx\notation@uri@empty%
364             \ifx\@I\modules@getURI@name%
365                 \edef\notation@uri{#1\@QuestionMark\@I}%
366             \fi%
367         \fi%
368     }%
369 }
370
371 % extracts the full URI from \foo or anything being \ifx-equal to \foo,
372 % by expanding until we reach \@invoke@symbol{<uri>}
373 \def\notation@extract@uri#1{%
374     \ifcsvoid{#1}{}{%

```

```

375 \expandafter\let\expandafter\notation@extract@uri@nextcs\csname#1\endcsname%
376 \ifx\notation@extract@uri@nextcs\notation@extract@uri@currucs\else%
377 \let\notation@extract@uri@currucs\notation@extract@uri@nextcs%
378 \expandafter\notation@extract@uriII\notation@extract@uri@nextcs\notation@end%
379 \fi%
380 }%
381 }
382 \long\def\notation@extract@uriII#1#2\notation@end{%
383 \def\notation@extract@check@temp{#2}
384 \ifx\@invoke@symbol#1%
385 \edef\notation@uri{#2}%
386 \else%
387 \ifx\notation@extract@check@temp\@empty\else%
388 \expandafter\def\expandafter\notation@extract@uri@nextcs\expandafter{#1{#2}}%
389 \notation@extract@uri{notation@extract@uri@nextcs}%
390 \fi%
391 \fi%
392 %
393 }
394
395 % \notation
396 % adds a new notation to \foo, as in:
397 % \notation[lang=en,arity=0,variant=op]{foo}{...}
398 % \notation[variant=bar]{foo}[2]{...}
399 % \notation[args=aia,prec=500;50x49x51]{foo}{#1 bla #2 bla #3}{arg1}{arg3}
400
401 % TODO with brackets, e.g.
402 %\notation[withbrackets={\langle,\rangle}]{foo}{...}
403
404 % parses the first two arguments
405 \mod@newcommand\notation[2][0]{%
406 \edef\notation@first{#1}%
407 \edef\notation@second{#2}%
408 \notation@%
409 }
410
411 % parses the last two arguments
412 \newcommand\notation@[2][0]{%
413 \notation@@[\notation@first]\notation@second[#1]{#2}%
414 }
415
416 % parses the notation arguments and wraps them in
417 % \notation@assoc and \notation@argprec for flexary arguments and precedences
418 \def\notation@@[#1]#2[#3]#4{%
419 \modules@getURIfromName{#2}%
420 \notation@parse@params{#1}{#3}
421 \let\notation@curr@todo@args\notation@curr@args%
422 \def\notation@temp@notation{}%
423 \StrLen\notation@curr@args[\notation@temp@arity]%
424 \expandafter\renewcommand\expandafter\notation@temp@notation%

```



```

425 \expandafter[\notation@temp@arity]{#4}%
426 % precedence
427 \IfSubStr\notation@curr@prec;{%
428 \StrCut\notation@curr@prec;\notation@curr@prec\notation@curr@prec%
429 \ifx\notation@curr@prec\empty\def\notation@curr@prec{0}\fi%
430 }{%
431 \ifx\notation@curr@prec\empty%
432 \ifnum\notation@temp@arity=0\relax%
433 \edef\notation@curr@prec{\infprec}%
434 \else%
435 \def\notation@curr@prec{0}%
436 \fi%
437 \else%
438 \edef\notation@curr@prec{\notation@curr@prec}%
439 \def\notation@curr@prec{}%
440 \fi%
441 }%
442 % arguments
443 \def\notation@curr@extargs{}
444 \def\notation@nextarg@index{1}%
445 \notation@do@args%
446 }
447
448 % parses additional notation components for (associative) arguments
449 \def\notation@do@args{%
450 \def\notation@nextarg@temp{}%
451 \ifx\notation@curr@todo@args\empty%
452 \notation@after%
453 \else%
454 % argument precedence
455 \IfSubStr\notation@curr@prec{x}{%
456 \StrCut\notation@curr@prec{x}\notation@curr@argprec\notation@curr@prec%
457 }{%
458 \edef\notation@curr@argprec{\notation@curr@prec}%
459 \def\notation@curr@prec{}%
460 }%
461 \ifx\notation@curr@argprec\empty%
462 \let\notation@curr@argprec\notation@curr@prec%
463 \fi%
464 \StrChar\notation@curr@todo@args1[\notation@argchar]%
465 \StrGobbleLeft\notation@curr@todo@args1[\notation@curr@todo@args]%
466 \expandafter\ifx\notation@argchar i%
467 % normal argument
468 \edef\notation@nextarg@temp{\noexpand\notation@argprec{\notation@curr@argprec}{#####\
469 \edef\notation@nextarg@index{\the\numexpr\notation@nextarg@index+1 }
470 \expandafter\g@addto@macro@safe\expandafter\notation@curr@extargs%
471 \expandafter{\notation@nextarg@temp}%
472 \expandafter\expandafter\expandafter\notation@do@args%
473 \else%
474 % associative argument

```

```

475     \expandafter\expandafter\expandafter\notation@parse@assocarg%
476     \fi%
477 \fi%
478 }
479
480 \def\notation@parse@assocarg#1{%
481   \edef\notation@nextarg@temp{\noexpand\notation@argprec{\notation@curr@argprec}{\noexpand\notation@nextarg@temp}%
482   \edef\notation@nextarg@index{\the\numexpr\notation@nextarg@index+1 }%
483   \expandafter\g@addto@macro@safe\expandafter\notation@curr@extargs%
484   \expandafter{\notation@nextarg@temp}%
485   \notation@do@args%
486 }
487
488 % finally creates the actual macros
489 \def\notation@after{
490   \let\ex\expandafter%
491   \ex\ex\ex\def\ex\ex\ex\notation@temp\notation\ex\ex\ex%
492     {\ex\notation@temp\notation\notation@curr@extargs}%
493   \edef\notation@temp\notation{\noexpand\notation@symprec{\notation@curr@prec}{\ex\notation@temp\notation}%
494   \def\notation@temp@fragment{}%
495   \ifx\notation@curr@arity\@empty\else%
496     \edef\notation@temp@fragment{arity=\notation@curr@arity}%
497   \fi%
498   \ifx\notation@curr@lang\@empty\else%
499     \ifx\notation@temp@fragment\@empty%
500       \edef\notation@temp@fragment{lang=\notation@curr@lang}%
501     \else%
502       \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand lang=\notation@curr@lang}%
503     \fi%
504   \fi%
505   \ifx\notation@curr@variant\@empty\else%
506     \ifx\notation@temp@fragment\@empty%
507       \edef\notation@temp@fragment{variant=\notation@curr@variant}%
508     \else%
509       \edef\notation@temp@fragment{\notation@temp@fragment\@Ampersand variant=\notation@curr@variant}%
510     \fi%
511   \fi%
512   \edef\notation@csname{\notation@uri\@Fragment\notation@temp@fragment}%
513   \ifcsvoid{\notation@csname}{%
514     \ex\ex\ex\ex\ex\ex\ex\newcommand\ex\ex\ex\csname\ex\ex\ex\notation@csname%
515       \ex\ex\ex\endcsname\ex\ex\ex[\ex\notation@temp@arity\ex]%
516     \ex{\notation@temp\notation}%
517   \edef\symdecl@temps{%
518     \noexpand\newcommand\ex\notation@csname\endcsname[\notation@temp@arity]%
519   }%
520   \ex\g@addto@macro@safe\csname module@defs@this@module\ex\endcsname\ex{\symdecl@temps}%
521   \ex\g@addto@macro@safe\csname module@defs@this@module\ex\endcsname\ex{\ex{\notation@temp\notation}%
522 }{%
523   \PackageWarning{modules}{notation already defined: \notation@csname}{%
524     Choose a different set of notation options (variant,lang,arity)%

```

```

525     }%
526 }%
527 \usemodule@maybesetcodes%
528 }
529
530 % parses optional parameters
531 \def\notation@parse@params#1#2{%
532   \def\notation@curr@prec{%
533     \def\notation@curr@args{%
534       \def\notation@curr@variant{%
535         \def\notation@curr@arity{%
536           \def\notation@curr@provided@arity{#2}
537           \def\notation@curr@lang{%
538             \def\notation@options@temp{#1}
539             \notation@parse@params@%
540             \ifx\notation@curr@args\@empty%
541               \ifx\notation@curr@provided@arity\@empty%
542                 \notation@num@to@ia\notation@curr@arity%
543               \else%
544                 \notation@num@to@ia\notation@curr@provided@arity%
545             \fi%
546           \fi%
547         }
548       \def\notation@parse@params@{%
549         \IfSubStr\notation@options@temp,{%
550           \StrCut\notation@options@temp,\notation@option@temp\notation@options@temp%
551           \notation@parse@param%
552           \notation@parse@params@%
553         }{\ifx\notation@options@temp\@empty\else%
554           \let\notation@option@temp\notation@options@temp%
555           \notation@parse@param%
556         \fi}%
557       }
558
559 %parses an individual optional argument/key-value-pair
560 \def\notation@parse@param{%
561   \trimstring\notation@option@temp%
562   \ifx\notation@option@temp\@empty\else%
563     \IfSubStr\notation@option@temp={%
564       \StrCut\notation@option@temp=\notation@key\notation@value%
565       \trimstring\notation@key%
566       \trimstring\notation@value%
567       \IfStrEq\notation@key{prec}{%
568         \edef\notation@curr@prec{\notation@value}%
569       }{%
570         \IfStrEq\notation@key{args}{%
571           \edef\notation@curr@args{\notation@value}%
572         }{%
573           \IfStrEq\notation@key{lang}{%
574             \edef\notation@curr@lang{\notation@value}%

```

```

575     }{%
576     \IfStrEq\notation@key{variant}{%
577         \edef\notation@curr@variant{\notation@value}%
578     }{%
579     \IfStrEq\notation@key{arity}{%
580         \edef\notation@curr@arity{\notation@value}%
581     }{%
582     }}}}%
583     }{%
584         \edef\notation@curr@variant{\notation@option@temp}%
585     }%
586 \fi%
587 }
588
589 % converts an integer to a string of 'i's, e.g. 3 => iii,
590 % and stores the result in \notation@curr@args
591 \def\notation@num@to@ia#1{%
592     \IfInteger{#1}{
593         \notation@num@to@ia@#1%
594     }{%
595         %
596     }%
597 }
598 \def\notation@num@to@ia@#1{%
599     \ifnum#1>0%
600         \edef\notation@curr@args{\notation@curr@args i}%
601         \expandafter\notation@num@to@ia@\expandafter{\the\numexpr#1-1\@Space}%
602     \fi%
603 }
604
605
606 % -----
607
608 \def\notation@assoc#1#2{% function, argv
609     \let\@tmpop=\relax% do not print the function the first time round
610     \@for\@I:=#2\do{\@tmpop% print the function
611         % write the i-th argument with locally updated precedence
612         \@I%
613         \def\@tmpop{#1}%
614     }%
615 }%
616
617 \def\notation@lparen{(}
618 \def\notation@rparen{)}
619 \def\infprec{1000000}
620 \def\neginfprec{-\infprec}
621
622 \newcount\notation@downprec
623 \notation@downprec=\neginfprec
624

```

```

625
626 \def\dobrackets#1{% avoiding groups at all costs to ensure \parray still works!
627   \def\notation@innertmp{#1}%
628   \expandafter\expandafter%\expandafter\left
629   \expandafter%
630   \notation@lparen%
631   \expandafter\notation@resetbrackets\expandafter\notation@innertmp%
632   %\expandafter\right
633   \notation@rparen%
634   %\mathchoice{\left\notation@lparen{\notation@resetbrackets#1}\right\notation@rparen}%
635   % {\notation@lparen{\notation@resetbrackets#1}\notation@rparen}%
636   % {\notation@lparen{\notation@resetbrackets#1}\notation@rparen}%
637   % {\notation@lparen{\notation@resetbrackets#1}\notation@rparen}%
638 }
639
640 \def\withbrackets#1#2#3{%
641   \edef\notation@lparen{#1}%
642   \edef\notation@rparen{#2}%
643   #3%
644   \notation@resetbrackets%
645 }
646
647 \def\notation@resetbrackets{%
648   \def\notation@lparen{(%}
649   \def\notation@rparen{)%}%
650 }
651
652 \def\notation@symprec#1#2{%
653   \ifnum#1>\notation@downprec\relax%
654     \notation@resetbrackets#2%
655   \else%
656     \ifnum\notation@downprec=\infprec\relax%
657       \notation@resetbrackets#2%
658     \else
659       \if@inarray@
660         \notation@resetbrackets#2
661       \else\dobrackets{#2}\fi%
662     \fi\fi%
663 }
664
665 \newif\if@inarray@\@inarray@false
666
667 \def\notation@argprec#1#2{%
668   \def\notation@innertmp{#2}
669   \edef\notation@downprec@temp{\number#1}%
670   \notation@downprec=\expandafter\notation@downprec@temp%
671   \expandafter\relax\expandafter\notation@innertmp%
672   \expandafter\notation@downprec\expandafter=\number\notation@downprec\relax%
673 }
674

```

```

675
676 % -----

```

symdef:keys The optional argument `local` specifies the scope of the function to be defined. If `local` is not present as an optional argument then `\symdef` assumes the scope of the function is global and it will include it in the pool of macros of the current module. Otherwise, if `local` is present then the function will be defined only locally and it will not be added to the current module (i.e. we cannot inherit a local function). Note, the optional key `local` does not need a value: we write `\symdef[local]{somefunction}[0]{some expansion}`. The other keys are not used in the L^AT_EX part.

```

677 \newif\if@symdeflocal%
678 \srefaddidkey{symdef}%
679 \define@key{symdef}{local}[true]{\@symdeflocaltrue}%
680 \define@key{symdef}{noverb}[all]{}%
681 \define@key{symdef}{align}[WithTheSymbolOfTheSameName]{}%
682 \define@key{symdef}{specializes}{}%
683 \addmetakey*{symdef}{noalign}[true]
684 \define@key{symdef}{primary}[true]{}%
685 \define@key{symdef}{assocarg}{}%
686 \define@key{symdef}{bvars}{}%
687 \define@key{symdef}{bargs}{}%
688 \addmetakey{symdef}{lang}%
689 \addmetakey{symdef}{prec}%
690 \addmetakey{symdef}{arity}%
691 \addmetakey{symdef}{variant}%
692 \addmetakey{symdef}{ns}%
693 \addmetakey{symdef}{name}%
694 \addmetakey*{symdef}{title}%
695 \addmetakey*{symdef}{description}%
696 \addmetakey{symdef}{subject}%
697 \addmetakey*{symdef}{display}%

```

EdN:6

6

\symdef The the `\symdef`, and `\@symdef` macros just handle optional arguments.

```

698 \def\symdef{\@ifnextchar[{\@symdef}{\@symdef[]}}%
699 \def\@symdef[#1]#2{\@ifnextchar[{\@@symdef[#1]{#2}}{\@@symdef[#1]{#2}[0]}}%

```

next we locally abbreviate `\mod@newcommand` to simplify argument passing.

```

700 \def\@mod@nc#1{\mod@newcommand{#1}[1]}%

```

and we copy a very useful piece of code from <http://tex.stackexchange.com/questions/23100/looking-for-an-ignorespacesandpars>, it ignores spaces and following implicit paragraphs (double newlines), explicit `\pars` are respected however

```

701 \def\ignorespacesandpars{\begingroup\catcode13=10\@ifnextchar\relax{\endgroup}{\endgroup}}

```

⁶EdNOTE: MK@MK: we need to document the binder keys above.

and more adapted from <http://tex.stackexchange.com/questions/179016/ignore-spaces-and-pars-after-an-environment>

```

702 \def\ignorespacesandparsafterend#1\ignorespaces\fi{#1\fi\ignorespacesandpars}
703 \def\ignorespacesandpars{\ifhmode\unskip\fi\@ifnextchar\par{\expandafter\ignorespacesandpars\g
\@@symdef now comes the real meat: the \@@symdef macro does two things, it adds the macro
definition to the macro definition pool of the current module and also provides it.
704 \newif\if@insymdef@\@insymdef@false
705 \def\@@symdef[#1]#2[#3]{%
706   \@insymdef@true
707   \metasetkeys{symdef}{#1}%
708   \edef\symdef@tmp@optpars{\ifcvoid{symdef@name}{[]}{[name=\symdef@name]}}%
709   \expandafter\symdecl\symdef@tmp@optpars{#2}%
710   \@insymdef@false
711   \notation[#1]{#2}[#3]%
712 }% mod@show
713 \def\symdef@type{Symbol}%
714 \providecommand{\stDMemph}[1]{\textbf{#1}}

\symvariant \symvariant{<sym>}[<args>]{<var>}{<cseq>} just extends the internal macro
\modules@<sym>@pres@ defined by \symdef{<sym>}[<args>]{...} with a variant
\modules@<sym>@pres@<var> which expands to <cseq>. Recall that this is called
by the macro \<sym>[<var>] induced by the \symdef.
715 \def\symvariant#1{%
716   \@ifnextchar[{\@symvariant{#1}}{\@symvariant{#1}[0]}%
717   }%
718 \def\@symvariant#1[#2]#3#4{%
719   \notation[#3]{#1}[#2]{#4}%
720 \ignorespacesandpars}%

\resymdef This is now deprecated.
721 \def\resymdef{%
722   \@ifnextchar[{\@resymdef}{\@resymdef[]}%
723 }%
724 \def\@resymdef[#1]#2{%
725   \@ifnextchar[{\@@resymdef[#1]{#2}}{\@@resymdef[#1]{#2}[0]}%
726 }%
727 \def\@@resymdef[#1]#2[#3]#4{%
728   \PackageError{modules}%
729   {The \protect\resymdef macro is deprecated}{use the \protect\symvariant instead!}%
730 }%

\abbrdef The \abbrdef macro is a variant of \symdef that does the same on the LATEX
level.
731 \let\abbrdef\symdef%

```

4.4 Defining Math Operators

`\DefMathOp` `\DefMathOp[⟨key pair⟩]{definition}` will take 2 arguments. *⟨key pair⟩* should be something like `[name=...]`, for example, `[name=equal]`. Though `\setkeys`, `\defmathop@name` will be set. Further definition will be done by `\symdef`.

```
732 \define@key{DefMathOp}{name}{%
733   \def\defmathop@name{#1}%
734 }%
735 \newrobustcmd\DefMathOp[2] [] {%
736   \setkeys{DefMathOp}{#1}%
737   \symdef[#1]{\defmathop@name}{#2}%
738 }%
```

4.5 Axiomatic Assumptions

`\assdef` We fake it for now, not clear what we should do on the L^AT_EX side.

```
739 \newcommand\assdef[2] [] {#2}
```

4.6 Semantic Macros for Variables

`\vardef` From the L^AT_EX point of view `\vardef` is just an abbreviation

```
740 \let\vardef\abbrdef
```

4.7 Testing Semantic Macros

`\symtest` Allows to test a `\symdef` in place, this shuts up when being imported.

```
741 \addmetakey{symtest}{name}%
742 \addmetakey{symtest}{variant}%
743 \newrobustcmd\symtest[3] [] {%
744   \if@importing%
745   \else%
746     \metasetkeys{symtest}{#1}%
747     \par\noindent \textbf{Symbol}~%
748     \ifx\symtest@name\@empty\texttt{#2}\else\texttt{\symtest@name}\fi%
749     \ifx\symtest@variant\@empty\else (variant \texttt{\symtest@variant})\fi%
750     \ with semantic macro %
751     \texttt{\textbackslash #2\ifx\symtest@variant\@empty\else[\symtest@variant]\fi}%
752     : used e.g. in \ensuremath{#3}%
753   \fi%
754   \ignorespacesandpars%
755 }%
```

`\abbrtest`

```
756 \addmetakey{abbrtest}{name}%
757 \newrobustcmd\abbrtest[3] [] {%
758   \if@importing%
759   \else%
760     \metasetkeys{abbrtest}{#1}%
761   \fi%
762 }
```



```

761 \par\noindent \textbf{Abbreviation}~%
762 \ifx\abbrtest@name\@empty\texttt{#2}\else\texttt{\abbrtest@name}\fi%
763 : used e.g. in \ensuremath{#3}%
764 \fi%
765 \ignorespacesandpars}%

```

4.8 Symbol and Concept Names

```

\termdef
766 \def\mod@true{true}%
767 \addmetakey[false]{termdef}{local}%
768 \addmetakey{termdef}{name}%
769 \newrobustcmd\termdef[3][]{%
770 \metasetkeys{termdef}{#1}%
771 \expandafter\mod@newcommand\csname#2\endcsname[0]{#3\space}%
772 \ifx\termdef@local\mod@true%
773 \else%
774 \ifcsundef{module@id}{}{%
775 \expandafter\g@addto@macro@safe\csname module@defs@\this@module\expandafter\endcsname%
776 \expandafter{\expandafter\mod@newcommand\csname#2\endcsname[0]{#3\space}}%
777 }%
778 \fi%
779 }%

\capitalize
780 \def\@capitalize#1{\uppercase{#1}}%
781 \newrobustcmd\capitalize[1]{\expandafter\@capitalize #1}%

\module@component This macro computes the module component identifier for external links on term
references. It is initially empty, but can be redefined later (e.g.in the smultiling
package).
782 \newcommand\mod@component[1]{}

\mod@termref \mod@termref{<module>}{<name>}{<nl>} determines whether the macro \module@<module>@path
is defined. If it is, we make it the prefix of a URI reference in the local macro
\@uri, which we compose to the hyper-reference, otherwise we give a warning.7
783 \newcommand\mod@termref[3]{\def\@test{#3}%
784 \@ifundefined{module@defs@#1}{%
785 \protect\G@refundefinedtrue%
786 \if@trwarn
787 \PackageWarning{modules}{‘\protect\termref’ with unidentified cd “#1”:\MessageBreak
788 the cd key must reference an active module}%
789 \else
790 \PackageError{modules}{‘\protect\termref’ with unidentified cd “#1”}
791 {the cd key must reference an active module}%
792 \fi}%
793 {\def\@label{sref@#1\@QuestionMark#2\mod@component{#1}@target}%

```

⁷EDNOTE: MK: this should be rethought, in particular the local reference does not work!

```

794 \ifundefined{module@#1@path}% local reference
795 {\sref@hlink@ifh{\@label}{\ifx\@test\@empty #2\else #3\fi}%
796 % \footnote{sTeX mod@termref: local reference to\@label}
797 }%
798 {\def\@uri{\csname module@#1@path\endcsname\mod@component{#1}.pdf\@label}%
799 \sref@href@ifh{\@uri}{\ifx\@test\@empty #2\else #3\fi}%
800 % \footnote{sTeX mod@termref: external reference to \@uri}
801 }%
802 }%

```

4.9 Loading Modules

4.9.1 Selective Inclusion

The next great goal is to establish the `\requiremodules` macro, which reads an `STeX` file and processes all the module signature information in them, but does not produce any output. This is a tricky business, as we need to “parse” the modules and treat the module signature macros specially (we refer to this as “**sms mode**”, since it is equivalent to what the – now deprecated – `sms` utility did).

In the following we introduce a lot of auxiliary functionality before we can define `\requiremodules`.

```

\usemodule@allow* The first step is setting up a functionality for registering \sTeX macros and envi-
                  ronments as part of a module signature.
803 \newif\if@smsmode\@smsmodefalse
804 \def\usemodule@escapechar@allowed{true}
805 \def\usemodule@allow#1{
806   \expandafter\let\csname usemodule@allowedmacro@#1\endcsname\usemodule@escapechar@allowed
807 }
808 \def\usemodule@allowenv#1{
809   \expandafter\let\csname usemodule@allowedenv@#1\endcsname\usemodule@escapechar@allowed
810 }
811 \def\usemodule@escapechar@beginstring{begin}
812 \def\usemodule@escapechar@endstring{end}

```

and now we use that to actually register all the `STeX` functionality as relevant for `sms` mode.

```

813 \usemodule@allow{symdef}
814 \usemodule@allow{abbrdef}
815 \usemodule@allow{importmodule}
816 \usemodule@allowenv{module}
817 \usemodule@allow{importmhmodule}
818 \usemodule@allow{gimport}
819 \usemodule@allowenv{modsig}
820 \usemodule@allowenv{mhmodsig}
821 \usemodule@allowenv{mhmodnl}
822 \usemodule@allowenv{modnl}
823 \usemodule@allow{symvariant}
824 \usemodule@allow{symi}

```

```

825 \usemodule@allow{symii}
826 \usemodule@allow{symiii}
827 \usemodule@allow{symiv}
828 \usemodule@allow{notation}
829 \usemodule@allow{symdecl}
830 %\usemodule@allow{defi}
831 %\usemodule@allow{defii}
832 %\usemodule@allow{defiii}
833 %\usemodule@allow{defiv}
834 %\usemodule@allow{adefi}
835 %\usemodule@allow{adefii}
836 %\usemodule@allow{adefiii}
837 %\usemodule@allow{adefiv}
838 %\usemodule@allow{defis}
839 %\usemodule@allow{defiis}
840 %\usemodule@allow{defiiis}
841 %\usemodule@allow{defivs}
842 %\usemodule@allow{Defi}
843 %\usemodule@allow{Defii}
844 %\usemodule@allow{Defiii}
845 %\usemodule@allow{Defiv}
846 %\usemodule@allow{Defis}
847 %\usemodule@allow{Defiis}
848 %\usemodule@allow{Defiiis}
849 %\usemodule@allow{Defivs}

```

To read external modules without producing output, `\requiremodules` redefines the `\`-character to be an *active* character that, instead of executing a macro, checks whether a macro name has been registered using `\usemodule@allow` before selectively executing the corresponding macro or ignoring it. To produce the relevant code, we therefore define a macro `\@active@slash` that produces a `\`-character with category code 13 (*active*), as well as `\@open@brace` and `\@close@brace`, which produce open and closing braces with category code 12 (*other*).

```

850 \catcode'\.=0
851 .catcode'\.=13
852 .def.\@active@slash{\}
853 .catcode'\.<=1
854 .catcode'\.>=2
855 .catcode'\{=12
856 .catcode'\}=12
857 .def.\@open@brace<{>
858 .def.\@close@brace<}>
859 .catcode'\.=0
860 \catcode'\.=12
861 \catcode'\{=1
862 \catcode'\}=2
863 \catcode'\<=12
864 \catcode'\>=12

```

The next two macros set and reset the category codes before/after `sms` mode.

`\set@usemodule@catcodes`

```

865 \def\set@usemodule@catcodes{%
866     \global\catcode'\=13%
867     \global\catcode'\#=12%
868     \global\catcode'\{=12%
869     \global\catcode'\}=12%
870     \global\catcode'\$=12%$
871     \global\catcode'\^=12%
872     \global\catcode'\_ =12%
873     \global\catcode'\&=12%
874     \expandafter\let\@active@slash\usemodule@escapechar%
875 }
```

`\reset@usemodule@catcodes`

```

876 \def\reset@usemodule@catcodes{%
877     \global\catcode'\=0%
878     \global\catcode'\#=6%
879     \global\catcode'\{=1%
880     \global\catcode'\}=2%
881     \global\catcode'\$=3%$
882     \global\catcode'\^=7%
883     \global\catcode'\_ =8%
884     \global\catcode'\&=4%
885 }
```

`\usemodule@maybesetcodes` Before a macro is executed in `sms`-mode, the category codes will be reset to normal, to ensure that all macro arguments are parsed correctly. Consequently, the macros need to set the category codes back to `sms` mode after having read all arguments iff the macro got executed in `sms` mode. `\usemodule@maybesetcodes` takes care of that.

```

886 \def\usemodule@maybesetcodes{%
887     \if@smsmode\set@usemodule@catcodes\fi%
888 }
```

`\requiremodules` This macro loads the module signatures in a file using the `\requiremodules@smsmode` above. We set the flag `\mod@showfalse` in the local group, so that the macros know now to pollute the result.

```

889 \newrobustcmd\requiremodules[1]{%
890     \mod@showfalse%
891     \edef\mod@path{#1}%
892     \edef\mod@path{\expandafter\detokenize\expandafter{\mod@path}}%
893     \requiremodules@smsmode{#1}%
894 }
```

`\requiremodules@smsmode` this reads `gTEX` modules by setting the category codes for `sms` mode, `\inputting` the required file and wrapping it in a `\vbox` that gets stored away and ignored, in

order to not produce any output. It also sets `\hbadness`, `\hfuzz` and friends to values that suppress overfull and underfull hbox messages.

```

895 \newbox\modules@import@tempbox
896 \def\requiremodules@smsmode#1{
897   \setbox\modules@import@tempbox\vbox{%
898     \@smsmodetrue%
899     \set@usemodule@catcodes%
900     \hbadness=100000\relax%
901     \hfuzz=10000pt\relax%
902     \vbadness=100000\relax%
903     \vfuzz=10000pt\relax%
904     \stexinput{#1.tex}%
905     \reset@usemodule@catcodes%
906   }%
907   \usemodule@maybesetcodes
908 }

```

`\usemodule@escapechar` This macro gets called whenever a `\`-character occurs in `sms` mode. It is split into several macros that parse and store characters in `\usemodule@escape@currcls` until a character with category code $\neq 11$ occurs (i.e. the macro name is complete), check whether the macro is allowed in `sms` mode, and then either ignore it or execute it after setting category codes back to normal. Special care needs to be taken to make sure that braces have the right category codes (1 and 2 for open and closing braces, respectively) when delimiting macro arguments.

Entry point:

```

909
910 \def\usemodule@escapechar{%
911   \def\usemodule@escape@currcls{}%
912   \usemodule@escape@parse@nextchar%
913 }%

```

The next macro simply reads the next character and checks whether it has category code 11. If so, it stores it in `\usemodule@escape@currcls`. Otherwise, the macro name is complete, it stores the last character in `\usemodule@last@char` and calls `\usemodule@escapechar@checkcls`.

```

914 \long\def\usemodule@escape@parse@nextchar@#1{%
915   \ifcat a#1 %
916     \edef\usemodule@escape@currcls{\usemodule@escape@currcls#1}%
917     \let\usemodule@do@next\usemodule@escape@parse@nextchar%
918   \else%
919     \def\usemodule@last@char{#1}%
920     \def\usemodule@do@next{\usemodule@escapechar@checkcls}%
921   \fi%
922   \usemodule@do@next%
923 }

```

The next macro checks whether the currently stored macroname is allowed in `sms` mode. There are four cases that need to be considered: `\begin`, `\end`, allowed macros, and others. In the first two cases, we reinsert `\usemodule@last@char` and

continue with `\usemodule@escapechar@checkbeginenv` or `\usemodule@escapechar@checkendenv` respectively, to check whether the environment being opened/closed is allowed in `sms` mode. In both cases, `\usemodule@last@char` is an open brace with category code 12. In the third case, we need to check whether `\usemodule@last@char` is an open brace, in which case we call `\usemodule@converttoproperbraces`, otherwise, we set category codes to normal and execute the macro. In the fourth case, we just reinsert `\usemodule@last@char` and continue.

```

924 \def\usemodule@escapechar@checkcs{
925   \ifx\usemodule@escape@currcls\usemodule@escapechar@beginstring%
926     \edef\usemodule@do@next{\noexpand\usemodule@escapechar@checkbeginenv\usemodule@last@char}
927   \else%
928     \ifx\usemodule@escape@currcls\usemodule@escapechar@endstring%
929       \edef\usemodule@do@next{\noexpand\usemodule@escapechar@checkendenv\usemodule@last@char}
930     \else%
931       \expandafter\ifx\csname usemodule@allowedmacro@\usemodule@escape@currcls\endcsname%
932         \usemodule@escapechar@allowed%
933       \ifx\usemodule@last@char\@open@brace%
934         \expandafter\let\expandafter\usemodule@do@next\ii\csname\usemodule@escape@currcls\endcsname
935         \edef\usemodule@do@next{\noexpand\usemodule@converttoproperbraces\@open@brace}
936       \else%
937         \reset@usemodule@catcodes%
938         \edef\usemodule@do@next{\expandafter\noexpand\csname\usemodule@escape@currcls\endcsname}
939       \fi%
940     \else\def\usemodule@do@next{\relax\usemodule@last@char}\fi%
941   \fi%
942 \fi%
943 \usemodule@do@next%
944 }

```

This macro simply takes an argument in braces (with category codes 12), reinserts it with “proper” braces (category codes 1 and 2), sets category codes back to normal and calls `\usemodule@do@next@ii`, which has been `\let` as the macro to be executed.

```

945 \expandafter\expandafter\expandafter\def%
946 \expandafter\expandafter\expandafter\usemodule@converttoproperbraces%
947 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
948   \reset@usemodule@catcodes%
949   \usemodule@do@next@ii{#1}%
950 }

```

The next two macros apply in the `\begin` and `\end` cases. They check whether the environment is allowed in `sms` mode, if so, open/close the environment, and otherwise do nothing.

Notably, `\usemodule@escapechar@checkendenv` does not set category codes back to normal, since `\end{environment}` never takes additional arguments that need to be parsed anyway.

```

951 \expandafter\expandafter\expandafter\def%
952 \expandafter\expandafter\expandafter\usemodule@escapechar@checkbeginenv%
953 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%

```

```

954 \expandafter\ifx\cscname usemodule@allowedenv@#1\endcscname\usemodule@escapechar@allowed%
955 \reset@usemodule@catcodes%
956 \def\usemodule@do@next{\begin{#1}}%
957 \else%
958 \def\usemodule@do@next{#1}%
959 \fi%
960 \usemodule@do@next%
961 }
962 \expandafter\expandafter\expandafter\def%
963 \expandafter\expandafter\expandafter\usemodule@escapechar@checkendenv%
964 \expandafter\@open@brace\expandafter#\expandafter1\@close@brace{%
965 \expandafter\ifx\cscname usemodule@allowedenv@#1\endcscname\usemodule@escapechar@allowed%
966 %\reset@usemodule@catcodes%
967 \def\usemodule@do@next{\end{#1}}%
968 \else%
969 \def\usemodule@do@next{#1}%
970 \fi%
971 \usemodule@do@next%
972 }

```

`\@requiremodules` the internal version of `\requiremodules` for use in the *.aux file. We disable it at the end of the document, so that when the aux file is read again, nothing is loaded.

```

973 \newrobustcmd\@requiremodules[1]{%
974 \if@tempswa\requiremodules{#1}\fi%
975 }%

```

`\inputref@*skip` hooks for spacing customization, they are empty by default.

```

976 \def\inputref@preskip{}
977 \def\inputref@postskip{}

```

`\inputref` `\inputref{<path to the current file without extension>}` supports both absolute path and relative path, meanwhile, records the path and the extension (not for relative path).

```

978 \newrobustcmd\inputref[1]{%
979 \def\@Slash{/}%
980 \edef\@load{#1}%
981 \StrChar{\@load}{1}[\@testchar]
982 \inputref@preskip%
983 \ifx\@testchar\@Slash%
984 \edef\mod@path{#1}%
985 \edef\mod@path{\expandafter\detokenize\expandafter{\mod@path}}%
986 \stexinput{#1}%
987 \else%
988 \@cpath{#1}\stexinput{\@CanPath.tex}%
989 \fi%
990 \inputref@postskip%
991 }%

```

4.10 Including Externally Defined Semantic Macros

```
\requirepackage
992 \def\requirepackage#1#2{\makeatletter\stexinput{#1.sty}\makeatother}%
```

4.11 Namespaces and Alignments

```
\namespace
993 \newcommand\namespace[2][]{\ignorespacesandpars}
```

4.12 Deprecated Functionality

```
\sinput*
994 \newrobustcmd\sinput[1]{%
995   \PackageError{modules}%
996   {The ‘\protect\sinput’ macro is deprecated}{use the \protect\input instead!}%
997 }%
998 \newrobustcmd\sinputref[1]{%
999   \PackageError{modules}%
1000   {The \protect\sinputref macro is deprecated}{use the \protect\inputref instead!}%
1001 }%
```

In this section we centralize old interfaces that are only partially supported any more.

EdN:8

module:uses For each the module name `xxx` specified in the `uses` key, we activate their symdefs and we export the local symdefs.⁸

```
1002 \define@key{module}{uses}{\PackageError{modules}%
1003   {The ‘uses’ key on {module} macro is deprecated}{}}
```

module:usesqualified This option operates similarly to the `module:uses` option defined above. The only difference is that here we import modules with a prefix. This is useful when two modules provide a macro with the same name.

```
1004 \define@key{module}{usesqualified}{\PackageError{modules}%
1005   {The ‘usesqualified’ key on {module} macro is deprecated}{}}
```

\coolurion/off

```
1006 \def\coolurion{\PackageWarning{modules}{coolurion is obsolete, please remove}}%
1007 \def\coolurioff{\PackageWarning{modules}{coolurioff is obsolete, please remove}}%
```

4.13 Experiments

In this section we develop experimental functionality. Currently support for complex expressions, see https://svn.kwarc.info/repos/stex/doc/blue/comlex_semmacros/note.pdf for details.

⁸EDNOTE: this issue is deprecated, it will be removed before 1.0.

`\csymdef` For the L^AT_EX we use `\symdef` and forget the last argument. The code here is just needed for parsing the (non-standard) argument structure.

```

1008 \def\csymdef{\@ifnextchar[\@csymdef]{\@csymdef[]}}%
1009 \def\@csymdef[#1]#2{%
1010   \@ifnextchar[\@@csymdef[#1]{#2}]{\@csymdef[#1]{#2}[0]}%
1011 }%
1012 \def\@@csymdef[#1]#2[#3]#4#5{%
1013   \@symdef[#1]{#2}[#3]{#4}%
1014 }%

```

`\notationdef` For the L^AT_EX side, we just make `\notationdef` invisible.

```

1015 \def\notationdef[#1]#2#3{}

```

The code for avoiding duplicate loading is very very complex and brittle (and does not quite work). Therefore I would like to replace it with something better. It has two parts:

- keeping a registry of file paths, and only loading when the file path has not been mentioned in that, and
- dealing with relative paths (for that we have to string together prefixes and pass them one)

For the first problem, there is a very nice and efficient solution using `etoolbox` which I document below. If I decide to do away with relative paths, this would be it.

`\reqmodules` We keep a file path registry `\@register` and only load a module, if it is not in there.

```

1016 \newrobustcmd\reqmodules[2]{%
1017   \ifinlist{#1}{\@register}{\listadd\@register{#1}\stexinput{#1.#2}}%
1018 }%

```

for the relative paths, I have to find out the directory prefix and the file name. Here are two helper functions, which work well, but do not survive being called in an `\edef`, which is what we would need. First some preparation: we set up a path parser

```

1019 \newcounter{@pl}
1020 \DeclareListParser*\forpathlist{/}

```

`\file@name` `\file@name` selects the filename of the file path: `\file@name{/foo/bar/baz.tex}` is `baz.tex`.

```

1021 \def\file@name#1{%
1022   \setcounter{@pl}{0}%
1023   \forpathlist{\stepcounter{@pl}\listadd\@pathlist}{#1}
1024   \def\do##1{%
1025     \ifnumequal{\value{@pl}}{1}{##1}{\addtocounter{@pl}{-1}}
1026   }%
1027   \dolistloop{\@pathlist}%
1028 }%

```

`\file@path` `\file@path` selects the path of the file path `\file@path{/foo/bar/baz.tex}` is `/foo/bar`

```

1029 \def\file@path#1{%
1030   \setcounter{@pl}{0}%
1031   \forpathlist{\stepcounter{@pl}\listadd{@pathlist}{#1}%
1032   \def\do##1{%
1033     \ifnumequal{\value{@pl}}{1}{-}{%
1034       \addtocounter{@pl}{-1}%
1035       \ifnumequal{\value{@pl}}{1}{##1}{##1/}%
1036     }%
1037   }%
1038   \dolistloop{@pathlist}%
1039 }%
1040 \endpackage

```

what I would really like to do in this situation is

`\NEWrequiremodules` but this does not work, since the `\file@name` and `\file@path` do not survive the `\edef`.

```

1041 \def\@NEWcurrentprefix{}
1042 \def\NEWrequiremodules#1{%
1043   \def\@pref{\file@path{#1}}%
1044   \ifx\@pref\@empty%
1045     \else%
1046       \xdef\@NEWcurrentprefix{\@NEWcurrentprefix/\@pref}%
1047     \fi%
1048     \edef\@input@me{\@NEWcurrentprefix/\file@name{#1}}%
1049     \message{requiring \@input@me}\reqmodule{\@input@me}%
1050 }%

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

L ^A T _E X ^M L,	3,	10,	module,	8	semantic	
	11,	14,	20			
			OMDOC,	3,	7,	11
MATHML,	3,	4,	6,	7	inheritance	
module			OPENMATH,	3,	4,	6,
				7	relation,	8
name,			8	relation		
				inheritance	(se-	
name				mantic),	8	XML,
						7

Change History

v0.9	General: First Version with Documentation	1			variants. The resymdef functionality introduced in 0.9g is now deprecated. It was hardly used.	1
v0.9a	General: Completed Documentation	1			exporting requiremodules to the aux file, so that they are preloaded (pre-required) so semantic macros in section titles can work.	1
v0.9b	General: Complete functionality and Updated Documentation . .	1			Moving LaTeXML bindings into modules.sty.ltxml and disabling generation	1
v0.9c	General: more packaging	1				
v0.9d	General: fixing double loading of .tex and .sms	1	v1.2		General: No longer loading the aux file at the end of the document	1
v0.9e	General: fixing LaTeXML	1	v1.3		General: adding MathHub support	1
v0.9f	General: remove unused options uses and usesqualified	1	v1.4		General: Completely revamped importing modules this is much faster now, but can no longer do relative paths.	1
v0.9g	General: adding importOMDocmodule	1			deprecated \sinput and \sinputref	1
	adding resymdef functionality . .	1	v1.5		General: “unidentified cd” in termref is now an error.	1
v0.9h	General: adding \metallanguage . .	1			adding dir attribute to import/usemodule	1
	using \mod@newcommand instead of \providecommand for more intuitive inheritance.	1			Moved MH Versions to a separate mathhub package	1
v1.0	General: minor fixes	1	v1.6		General: deprecating importOMDocmodule	1
v1.1	General: adding additional keys for the \symdef macro and exporting them to OMDoc . . .	1			getting rid of sms files	1
	adding optional arguments to semantic macros for display					

References

- [Aus+10] Ron Ausbrooks et al. *Mathematical Markup Language (MathML) Version 3.0*. Tech. rep. World Wide Web Consortium (W3C), 2010. URL: <http://www.w3.org/TR/MathML3>.
- [Bus+04] Stephen Buswell et al. *The Open Math Standard, Version 2.0*. Tech. rep. The OpenMath Society, 2004. URL: <http://www.openmath.org/standard/om20>.
- [Koh06] Michael Kohlhase. *OMDoc – An open markup format for mathematical documents [Version 1.2]*. LNAI 4180. Springer Verlag, Aug. 2006. URL: <http://omdoc.org/pubs/omdoc1.2.pdf>.
- [Koh08] Michael Kohlhase. “Using L^AT_EX as a Semantic Markup Format”. In: *Mathematics in Computer Science 2.2* (2008), pp. 279–304. URL: <https://kwarc.info/kohlhase/papers/mcs08-stex.pdf>.
- [Koh20a] Michael Kohlhase. *MathHub Support for sT_EX*. Tech. rep. 2020. URL: <https://github.com/sLaTeX/sTeX/raw/master/sty/mathhub/mathhub.pdf>.
- [Koh20b] Michael Kohlhase. *metakeys.sty: A generic framework for extensible Metadata in L^AT_EX*. Tech. rep. 2020. URL: <https://github.com/sLaTeX/sTeX/raw/master/sty/metakeys/metakeys.pdf>.
- [Koh20c] Michael Kohlhase. *statements.sty: Structural Markup for Mathematical Statements*. Tech. rep. 2020. URL: <https://github.com/sLaTeX/sTeX/raw/master/sty/statements/statements.pdf>.
- [LTX] Bruce Miller. *LaTeXML: A L^AT_EX to XML Converter*. URL: <http://dlmf.nist.gov/LaTeXML/> (visited on 03/12/2013).
- [MNS] *Documents and Namespaces*. URL: <https://uniformal.github.io/doc/language/namespaces> (visited on 11/23/2019).
- [RK13] Florian Rabe and Michael Kohlhase. “A Scalable Module System”. In: *Information & Computation* 0.230 (2013), pp. 1–54. URL: <https://kwarc.info/frabe/Research/mmt.pdf>.
- [RO] Sebastian Rahtz and Heiko Oberdiek. *Hypertext marks in L^AT_EX: a manual for hyperref*. URL: <http://tug.org/applications/hyperref/ftp/doc/manual.pdf> (visited on 01/28/2010).
- [sTeX] *sTeX: A semantic Extension of TeX/LaTeX*. URL: <https://github.com/sLaTeX/sTeX> (visited on 05/11/2020).