CIS27 - Spring 2013 Sample Final; Name:	Page 1 of 5
Email:	
Date:	

#### Note!

- To receive credit, you must show your work and steps for each problem.
- Provide explanation as required or as if you wish to.
- When asked, draw the correct map(s) or structure(s) and record the EXACT output for full credit.
- Put your name on the sheets.

### Reminder!

- ❖ When writing code (even by hand), pay attention to syntax and statement completeness, and
- **\*** Be consistent when selecting names for functions and variables (as well as styles and conventions).

CIS27 – Spring 2013	Sample Final; Name:	Dogo	2 of	: =
C1327 - Spring 2013	Sample rmai, Name	 Page 1	2 of	J

A) Given the following displaying forms of a binary tree,

In-Order: G H A L M B D U T
Post-Order: G H L M A U T D B

Draw the corresponding binary tree.

B) Then, display the above binary tree in **Pre-Order** form.

CIS27 – Spring 2013	Sample Final:	Name:	Page :	3 c	)f	4
010= ,	~	1 (01110)			-	•

A complete binary search tree CBT of 315 nodes of integers is stored in an array (assuming that the storage will start at index 1).

- 1. How many levels does this tree have? Show work.
- 2. How many nodes are leaf nodes? Show work.
- 3. Where is the second largest value in the array? Show work.

CIS27 - Spring 2013 Sample Fina	l; Name:	Page 4 of 5
---------------------------------	----------	-------------

Write a function named  ${\tt getLeafCount}$  ( ) that returns the number of leaf nodes in a binary tree of integers.

CIS27 - Spring 2013	Sample Final; Name:		Page	5 c	of	5
---------------------	---------------------	--	------	-----	----	---

Given that a BST is storing an integer series from 0 to n (n is some non-negative integer) with one missing value (for example, n is 7 and the missing value is 4).

Write a function named getMissingValue() that will return this missing integer from the above BST of integers.