

Pages 90 – 99 *Java Programming A Comprehensive Introduction*

Section 1: Define / Answer

Explain the difference between a **for** loop and a **while** loop-

For has initializer while while loop doesn't have it

What is the basic difference between a **do-while** loop and **[or/while]** loops?

Do while would run the problem before the comparison while the while loop would run the comparison before looping

How do **break** statements work in relation to **for**, **while**, and **do-while** loops?

Break would stop the loop

Describe how an infinite **for** loop operates.

Once it operate, it would keep looping without stop

Programming Assignments

1st Task: Pg. 115 #15 Java Programming *A Comprehensive Guide*

There are 6 different programs + output required for this assignment.

Please Have 6 Different snippets photos with programs and outputs.

Hint** The programs should not be very long for each answer.

The Class **ContDemo** in Chapter 3 shows one way to use a **for** loop to print the even numbers 0 to 100. Write programs that print the same output as that program, but do it in the following ways:

A. Using a **for** loop that increments the loop control variable by 2 each iteration

```
1 package javaapplication4;
3
5
6 public class JavaApplication4 {
7
8
9     public static void main(String[] args) {
10
11         int count;
12
13         for(count = 0; count <= 100; count++) {
14
15             if(count % 2 == 0) {
16                 System.out.println(count);
17             }
18         }
19     }
20 }
21
22
```

run:

```
0
2
4
6
8
10
12
14
16
18
20
22
24
26
28
30
32
34
36
38
40
42
44
46
48
50
```

50
52
54
56
58
60
62
64
66
68
70
72
74
76
78
80
82
84
86
88
90
92
94
96
98
100

BUILD SUCCESSFUL (total time: 1 second)

B. Using a **for** loop whose loop control variable goes from 0 to 50.

```
1 package javaapplication4;
3
5 import java.util.Scanner;
7
9 public class JavaApplication4 {
11     public static void main(String[] args) {
13         int count;
15         for(count = 0; count <= 50; count++) {
17             if(count % 2 == 0) {
19                 System.out.println(count);
21             }
22         }
23     }
24 }
```

Output - JavaApplication2 (run) %

```
run:
0
2
4
6
8
10
12
14
16
18
20
22
24
26
28
30
32
34
36
38
40
42
44
46
48
50
```

C. Using a **for** loop whose loop control variable goes from 100 down to 0.

```
1 package javaapplication4;
3
5 import java.util.Scanner;
6
7 public class JavaApplication4 {
8
9     public static void main(String[] args) {
10
11         int count;
12
13         for(count = 100; count >= 0; count--){
14             if(count % 2 == 0){
15                 System.out.println(count);
16             }
17         }
18     }
19 }
20
21
```

run:

100
98
96
94
92
90
88
86
84
82
80
78
76
74
72
70
68
66
64
62
60
58
56
54
52
50


48	
46	
44	
42	
40	
38	
36	
34	
32	
30	
28	
26	
24	
22	
20	
18	
16	
14	
12	
10	
8	
6	
4	
2	
0	

D. Using an infinite **for** loop with no conditional expression and exiting the loop with a **break** statement.

```
1 package javaapplication4;
2
3 import java.util.Scanner;
4
5 public class JavaApplication4 {
6
7     public static void main(String[] args) {
8
9         int count;
10
11         count = 0;
12         for(;;){
13
14             if(count % 2 == 0){
15                 System.out.println(count);
16             }
17
18             if(count == 100){
19                 break;
20             }
21             count++;
22         }
23     }
24 }
25
26
27
28
```


CIS 36A – 7th In Class / Take Home Assignment – 10 Points

Student Name	Ka Chi Lau	Student ID	10819338	Point Total
--------------	------------	------------	----------	-------------



0
2
4
6
8
10
12
14
16
18
20
22
24
26
28
30
32
34
36
38
40
42
44
46
48
50
52
54
56
58
60
62
64
66
68
70
72
74
76
78
80
82
84
86
88
90
92
94
96
98
100
BUILD SUCCESSFUL (total time: 0 seconds)

E. Using a **while** loop.

```
1 package javaapplication4;
3
5 import java.util.Scanner;
6
7 public class JavaApplication4 {
8
9     public static void main(String[] args) {
10
11         int count;
12
13         count = 0;
14         while(count <= 100){
15             if(count % 2 == 0){
16                 System.out.println(count);
17             }
18             count++;
19         }
20
21     }
22 }
23
```

Student Name	Ka Chi Lau	Student ID	10819338	Point Total
---------------------	-------------------	-------------------	-----------------	--------------------

```

0
2
4
6
8
10
12
14
16
18
20
22
24
26
28
30
32
34
36
38
40
42
44
46
48
50
52
54
56
58
60
62
64
66
68
70
72
74
76
78
80
82
84
86
88
90
92
94
96
98
100
BUILD SUCCESSFUL (total time: 0 seconds)

```

F. Using a **do-while** loop.

```
1 package javaapplication4;
3
5 import java.util.Scanner;
7
9 public class JavaApplication4 {
11
13     public static void main(String[] args) {
15         int count;
17         count = 0;
19         do {
21             if(count % 2 == 0) {
23                 System.out.println(count);
25             }
27             count++;
29         } while(count <= 100);
31     }
33 }
```

CIS 36A – 7th In Class / Take Home Assignment – 10 Points

Student Name	Ka Chi Lau	Student ID	10819338	Point Total
--------------	------------	------------	----------	-------------



0
2
4
6
8
10
12
14
16
18
20
22
24
26
28
30
32
34
36
38
40
42
44
46
48
50
52
54
56
58
60
62
64
66
68
70
72
74
76
78
80
82
84
86
88
90
92
94
96
98
100

BUILD SUCCESSFUL (total time: 0 seconds)

There should be 6 different Snipping photos. One photo for each program A – F.

2nd Task- Change Calculator

Write a program that directs a cashier how to give change. The program has two inputs: The amount due and the amount received from the customer. Display the dollars, quarters, dimes, nickels, and pennies that the customer should receive.

```
1 package javaapplication4;
2
3
4 import java.util.Scanner;
5
6 public class JavaApplication4 {
7
8
9     public static void main(String[] args) {
10
11         //int count;
12
13         Scanner input = new Scanner(System.in);
14
15         Double amountdue, recevie, returnx, cent;
16
17         int dollars, quarters, dimes,
18             nickels, pennies;
19
20         System.out.print("Enter the cost of the item: ");
21         amountdue = input.nextDouble();
22         if(amountdue < 0) {
23             System.out.print("Invalid input");
24         }
25
26         System.out.print("Enter the money you recevie: ");
27         recevie = input.nextDouble();
28         if(recevie < 0) {
29             System.out.print("Invalid input");
30         }
31
32         returnx = recevie - amountdue;
33         if(returnx < 0) {
34             System.out.print("Ask more money from customer");
35         }
36
37         cent = returnx % 1;
38         dollars = (int) (returnx - cent);
39
40         quarters = 0;
41         quarters = (int) (cent / 0.25);
42         cent -= quarters * 0.25;
43
44         .. ..
45     }
```

```
43      dimes = 0;
44      dimes = (int) (cent / 0.1);
45      cent -= dimes * 0.1;
46
47      nickels = 0;
48      nickels = (int) (cent / 0.05);
49      cent -= nickels * 0.05;
50
51      pennies = 0;
52      pennies = (int) (cent / 0.01);
53      cent -= pennies * 0.01;
54
55      System.out.print("Dollars: " + dollars + " Quarters: " + quarters
56                      + " Dimes: " + dimes + " Nickels: " + nickels + " Pennies: "
57                      + pennies);
58
59
60
61  }
62 }
63
```

Output - JavaApplication2 (run) %

```
run:
Enter the cost of the item: 10.50
Enter the money you receive: 20
Dollars: 9 Quarters: 2 Dimes: 0 Nickels: 0 Pennies: 0 BUILD SUCCESSFUL (total time: 11 seconds)
```