

DESIGN CONCEPTS

Lecture # 21




MODULARITY

- A software is separately divided into name and addressable components. Sometime they are called as modules which integrate to satisfy the requirements.
- Modularity is the single attribute of a software that permits a program to be managed easily.
 - **Modular decomposability:** A design method provides a systematic mechanism for decomposing the problem into sub-problems -->reduce the complexity and achieve the modularity
 - **Modular composability:** A design method enables existing design components to be assembled into a new system.
 - **Modular understandability:** A module can be understood as a standalone unit it will be easier to build and easier to change.
 - **Modular continuity:** A small changes to the system requirements result in changes to individual modules, rather than system- wide changes.
 - **Modular protection:** An aberrant condition occurs within a module and its effects are constrained within the module.



MODULARITY TRADE-OFFS




INFORMATION HIDING

- Information (data and procedure) contained within a module should be inaccessible to other modules that have no need for such information.
- Hiding defines and enforces access constraints to both procedural detail within a module and any local data structure used by the module
- **Why Information Hiding?**
 - Decreases the probability of adverse effects
 - Restricts the effects of changes in one component on others
 - Emphasizes communication through controlled interfaces
 - Discourages the use of global data
 - Leads to encapsulation—an attribute of high-quality design



INFORMATION HIDING



FUNCTIONAL INDEPENDENCE

- Functional independence is achieved by developing modules with "single-minded" function and an "aversion" to excessive interaction with other modules.
- Independence is assessed using two qualitative criteria:
- **Cohesion** is an indication of the relative functional strength of a module.
 - A cohesive module performs a single task, requiring little interaction with other components in other parts of a program. Stated simply, a cohesive module should(ideally) do just one thing.
- **Coupling** is an indication of the relative interdependence among modules.
 - Coupling depends on the interface complexity between modules, the point at which entry or reference is made to a module, and what data pass across the interface.



COHESION

- A cohesive module performs a single task in a procedure with little interactions with others.
- **Goal**
 - Achieve high cohesion for modules in a system.
- **Different types of cohesion:**
 - **Communication cohesion:** data sharing among processing elements
 - **Procedural cohesion:** order among processing elements
 - **Coincidentally cohesive:** a set of tasks related to each other loosely
 - **Logically cohesive:** logical connection among processing elements



COUPLING

- **Goal:**
 - Strive for lowest possible coupling among modules.
- **Good coupling:**
 - Reduce or avoid change impact and ripple effects.
 - Reduce the cost in program changes, testing, maintenance
- **Types of coupling:**
 - **Data coupling:** parameter passing or data interaction
 - **Control coupling:** share related control logical (for a control data)
 - **Common coupling:** common data sharing
 - **Content coupling:** module A use of data or control information maintained in another module.




REFINEMENT

- Refinement is a top-down design approach.
- It is a process of elaboration.
- A program is established for refining levels of procedural details.
- A hierarchy is established by decomposing a statement of function in a stepwise manner till the programming language statement are reached.
- Abstraction and refinement are complementary concepts



STEPWISE REFINEMENT



ASPECT

- A crosscutting concern is some characteristic of the system that applies across many different requirements.
- It is important to identify aspects so that the design can properly accommodate them as refinement and modularization occur.
- In an ideal context, an aspect is implemented as a separate module (component) rather than as software fragments that are “scattered” or “tangled” throughout many components.
- To accomplish this, the design architecture should support a mechanism for defining an aspect—a module that enables the concern to be implemented across all other concerns that it crosscuts.



REFACTORING

- It is a reorganization technique which simplifies the design of components without changing its function or behavior.
- Fowler [FOW99] defines refactoring in the following manner:
 - "Refactoring is the process of changing a software system in such a way that it does not alter the external behavior of the code [design] yet improves its internal structure."
- When software is refactored, the existing design is examined for:
 - Redundancy
 - Unused design elements
 - Inefficient or unnecessary algorithms
 - Poorly constructed or inappropriate data structures
 - or Any other design failure that can be corrected to yield better design.

