


Parameter Estimation

Ahmet Sacan

Parameter Estimation


- **Simulation:**

- Can generate predicted values
- Predictions are dependent on parameters



- **Experimental Data:**

- "Real-world" measurements
- Noisy
- May be condition-dependent




- **Parameter Estimation:**

- Reconcile simulation & experimental data
- Optimize model parameters so the simulation can replicate experimental data (as best as possible)


Error/Evaluation/Objective Function

- Define an error function that (for given parameters, θ) quantifies how well simulation values match experimental data
 - $eval(\theta) \rightarrow \text{error}$




Error Function Example

- Let θ be 2-dimensional, i.e., we can vary two parameters in the model.
- The error function can be visualized in 3D (surface) or in 2D (contour plot, level sets).



https://en.wikipedia.org/wiki/Himmelblau%27s_function



Function Optimization

- Find best θ that results in smallest error.
- If the minimum points of the error function could be calculated analytically, we would have the correct/exact answer.
- But for most problems, closed form solution not available.
- We cannot try all possible parameters (infinitely many!)

Function Optimization Ideas


- Try many different random values of θ , pick the best one.
- Try many equally spaced values of θ , pick the best one. (e.g., meshgrid)
- Start with a random initial θ , and repeatedly improve θ to give a smaller error.
 - How to improve?

Line Search Methods


- Start with an initial guess x_0
- Repeat:
 - Find a descent direction along which error function is reduced
 - Methods: Gradient Descent, Newton's method, Quasi-Newton method
 - Choose a step size and move by the step size along that direction.

Gradient Descent

- aka Steepest Descent
- $x_{n+1} = x_n - \eta \nabla f(x_n)$
- Sometimes ∇f is available. When it's not, approximate from data



https://en.wikipedia.org/wiki/Gradient_descent



$$f(x_1, x_2) = 100(x_1^2 - x_2)^2 + (x_1 - 1)^2$$

Demo: fminunc()

- fminunc: Unconstrained Nonlinear Optimization
- Objective function:
 - $f(x_1, x_2) = 100(x_1^2 - x_2)^2 + (x_1 - 1)^2$

Demo: fmincon()

- fminunc: Constrained Nonlinear Optimization
- Objective function:
 - $f(x_1, x_2) = 100(x_1^2 - x_2)^2 + (x_1 - 1)^2$
- Constraint:
 - $x_1 + 2x_2 \leq 1$
 - Rewrite constraint as: $Ax \leq b$, $A=[1,2]$, $b=1$.


Fmincon exercise

Nelder-Mead Simplex Method

- Keep track of $n+1$ points in n dimensions
 - e.g., a triangle in 2D.
- At each iteration, do one of:
 - reflect, expand, contract, shrink

Nelder-Mead


- Basic operation: **Reflect**
 - Calculate f at each point
 - identify the x_{worst} , and its f_{worst}
 - x_m : average of remaining points.
 - Reflect: $x_{reflect} = x_{mean} + R(x_{mean} - x_{worst})$



Is $f_{reflect}$ better
than f_{best} ?

Expand & done.

$$x_{new} = x_{mean} + E(x_{reflect} - x_{mean})$$




Is $f_{reflect}$ worse
than f_{worst} ?

Contract Inside:

$$x_{try} = x_{mean} - C(x_{mean} - x_{worst})$$

Shrink if still worse than f_{worst} .




Is $f_{reflect}$ better
than f_{worst} but
worse than second
worst?


Contract Inside:

$$x_{try} = x_{mean} + C(x_{reflect} - x_{mean})$$


Shrink if worse than $f_{reflect}$.



Shrink: $x_i = x_i + S(x_i - x_{best})$




Nelder-Mead



Demo: Mass-Spring-Damper


- Integrator1: $\dot{x} \rightarrow x$
- Integrator2: $\dot{v} \rightarrow v = \dot{x}$
- Implement the equation:
- $\dot{v} = -\frac{k}{m}x - \frac{c}{m}\dot{x}$



Mass-Spring-Damper - Steps

- Get experimental data (Extract from figure if numerical data not available)
- Decide which parameters of the model to vary
- Write an evaluation function that returns the error for a given parameter vector
 - Simulate the system for that parameter vector
 - Compare the simulated data with experimental data to calculate error.
- Use one of the optimization functions to find the best parameters & its error.

Comparing with real data



Have a Simulink or Simbiology Model to Optimize?

- No problem.
- Just write an objective function that takes in parameters, runs Simulink/Simbiology model with those parameters and returns the error.
- Demo: massspringdamper_demo

Genetic Algorithms

