



# **CS 228 : Logic in Computer Science**

Krishna. S

# So Far

---


- ▶  $\omega$ -automata with Büchi acceptance, also called Büchi automata
- ▶ Non-determinism versus determinism

## Büchi Acceptance


For Büchi Acceptance,  $Acc$  is specified as a set of states,  $G \subseteq Q$ . The  $\omega$ -word  $\alpha$  is accepted if there is a run  $\rho$  of  $\alpha$  such that  $Inf(\rho) \cap G \neq \emptyset$ .

# Union and Intersection of NBA

---




# Union and Intersection of NBA




- States as  $Q_1 \times Q_2 \times \{1, 2\}$ , start state  $(q_0, q'_0, 1)$

# Union and Intersection of NBA




- ▶ States as  $Q_1 \times Q_2 \times \{1, 2\}$ , start state  $(q_0, q'_0, 1)$
- ▶  $(q_1, q_2, 1) \xrightarrow{a} (q'_1, q'_2, 1)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_1 \notin G_1$
- ▶  $(q_1, q_2, 1) \xrightarrow{a} (q'_1, q'_2, 2)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_1 \in G_1$

# Union and Intersection of NBA



- ▶ States as  $Q_1 \times Q_2 \times \{1, 2\}$ , start state  $(q_0, q'_0, 1)$
- ▶  $(q_1, q_2, 1) \xrightarrow{a} (q'_1, q'_2, 1)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_1 \notin G_1$
- ▶  $(q_1, q_2, 1) \xrightarrow{a} (q'_1, q'_2, 2)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_1 \in G_1$
- ▶  $(q_1, q_2, 2) \xrightarrow{a} (q'_1, q'_2, 2)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_2 \notin G_2$
- ▶  $(q_1, q_2, 2) \xrightarrow{a} (q'_1, q'_2, 1)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_2 \in G_2$

# Union and Intersection of NBA



- ▶ States as  $Q_1 \times Q_2 \times \{1, 2\}$ , start state  $(q_0, q'_0, 1)$
- ▶  $(q_1, q_2, 1) \xrightarrow{a} (q'_1, q'_2, 1)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_1 \notin G_1$
- ▶  $(q_1, q_2, 1) \xrightarrow{a} (q'_1, q'_2, 2)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_1 \in G_1$
- ▶  $(q_1, q_2, 2) \xrightarrow{a} (q'_1, q'_2, 2)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_2 \notin G_2$
- ▶  $(q_1, q_2, 2) \xrightarrow{a} (q'_1, q'_2, 1)$  if  $q_1 \xrightarrow{a} q'_1$  and  $q_2 \xrightarrow{a} q'_2$  and  $q_2 \in G_2$
- ▶ Good states =  $Q_1 \times G_2 \times \{2\}$  or  $G_1 \times Q_2 \times \{1\}$

# Emptiness

---


Given an NBA/DBA  $\mathcal{A}$ , how do you check if  $L(\mathcal{A}) = \emptyset$ ?

- ▶ Enumerate SCCs
- ▶ Check if there is an SCC containing a good state





# Complementation of DBA

---





# Complementation of DBA

---



# Complementation of DBA

---



# Complementation of DBA

---

- ▶ Given  $\mathcal{A}$  is a DBA, and  $w \notin L(\mathcal{A})$ , then after some finite prefix, the unique run of  $w$  settles in bad states.
- ▶ Idea for complement: “copy” states of  $Q - G$ , once you enter this block, you stay there.
- ▶ View this as the set of good states, any word  $w$  that was rejected by  $\mathcal{A}$  has two possible runs in this automaton: the original run, and one another, that will settle in the  $Q - G$  copy, and will be accepted.
- ▶ What we get now is an NBA for  $\overline{L(\mathcal{A})}$ , not a DBA.

Complementing NBA non-trivial, can be done.

# GNBA

---

- ▶ Generalized NBA, a variant of NBA
- ▶ Only difference is in acceptance condition
- ▶ Acceptance condition in GNBA is a set  $\mathcal{F} = \{F_1, \dots, F_k\}$ , each  $F_i \subseteq Q$
- ▶ An infinite run  $\rho$  is accepting in a GNBA iff

$$\forall F_i \in \mathcal{F}, \text{Inf}(\rho) \cap F_i \neq \emptyset$$

- ▶ Note that when  $\mathcal{F} = \emptyset$ , all infinite runs are accepting
- ▶ GNBA and NBA are equivalent in expressive power.